CONSTRUCTION EQUIPMENT

U.S. PRICE LIST EXCAVATORS

PL-200 CX SAP REVISION 35

EFFECTIVE JULY 9, 2021

THIS IS AN ELECTRONIC COPY ONLY - HARD COPIES WILL NOT BE DISTRIBUTED.

This price list is intended for dealers with the Excavators (CX) contract only.

The prices included in this revision supersede any prices established prior to the effective date shown unless specifically identified in a price bulletin as superseding this price list.

Below is a list of Family(s) and Model(s) that are included in this price list.

Crawler Excavator (Midi)

CX75C Tier 4 Final

CX80C Tier 4 Final

Crawler Excavator (Conventional)

CX130D Tier 4 Final

CX145D Tier 4 Final

CX160D Tier 4 Final

CX210D Tier 4 Final

CX245D Tier 4 Final

CX250D Tier 4 Final CX290D Tier 4 Final

CX300D Tier 4 Final

CX350D Tier 4 Final

CX490D Tier 4 Final

CX500D Tier 4 Final

CX750D RTC Tier 4 Final

CX750D RTC ME Tier 4 Final

PLEASE NOTE: Retain the price book pages of the discontinued series for your records.

Copyright 2021 By

CNH Industrial America LLC

(This page intentionally left blank)

General Information

Prices shown herein are suggested prices only and in no way are they to be construed as limiting or restricting the dealer in his determination of the ultimate retail selling price. It is understood that the dealers are free to determine their selling price. Subject to any Federal, State or local laws.

Where shown herein liquid capacities are U.S. measure unless otherwise noted.

ADVANCE FREIGHT

Advance freight will be added to the machinery invoice as a separate net charge for machinery shipped from field locations or from other than specified Ex Works locations.

PRICES

Prices are Ex Works factory, where the goods are manufactured, except where noted. For detailed information concerning prices, please refer to your OPERATING GUIDE.

Prices and specifications are subject to change without notice.

CONTENTS OF ORGANIZATION

Case Construction Equipment Inc issues price lists and revisions covering each Case contract. U.S. Price List is published in U.S. funds. Canadian Price List is published in Canadian funds. Assure that you are using the correct price list. The Canadian price lists are denoted by a Maple Leaf on the price list cover page and the symbol "(CDN)" is printed at the head of the Factory Supplied Attachments List columns.

Freight, duty and sales taxes are NOT included in any wholegoods or attachment prices shown in the price list. Any appropriate freight, duty, Federal, State, and Provincial taxes will be added to the machinery invoice as separate net charges.

PROCEDURE

The price pages for each machine (or group of machines) lists both "Factory" and "Factory Supplied Attachments".

Each price list is comprised of the various machines sold under that contract. Each price book section has "Factory", "Factory Supplied Attachments", or "Third Party Supplied Attachments" pages. When ordering and pricing a machine follow the ordering instructions listed for that machine. Attachments listed following the "Factory Supplied Attachments" or "Third Party Supplied Attachments" heading are available for installation in the field.

ATTACHMENTS

Expect Attachments to be shipped within 2 -3 weeks from order entry.



General Information

DISTRIBUTION OF PRICE LISTS / REQUESTS FOR ADDITIONAL COPIES

Price lists will be provided electronically via that Dealer Portal.

Contact information for additional copies of Case Construction Equipment Price Lists

Additional price lists, divider tabs and binders may be ordered at the Document Management Center. From Dealer Portal click on Tools then Document Management Center link. Any questions you can call the Document Management Center at 262-636-7540

You will only receive price lists for contracts covered by your current Dealer Agreement with the Company.

The revisions are dated and are effective as of that date. However, PRICES ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Bid Term: 2/22/19 - 2/21/21; Extended to 2/21/22: EXtended to 2/21/23



EXCAVATORS TABLE OF CONTENTS

CX SERIES EXCAVATORS

CX75C MINIMUM SWING RADIUS CRAWLER EXCAVATOR	
Standard Features	7
Price List	9
Factory Supplied Accessories	13
CX80C CRAWLER EXCAVATOR	
Standard Features	15
Price List	17
Factory Supplied Accessories	20
CX130D STANDARD EXCAVATOR	
Standard Features	21
Price List	24
Factory Supplied Accessories	30
CX145D LC and STD/DZ CRAWLER EXCAVATOR	
Standard Features	33
Price List	35
Factory Supplied Accessories	41
CX160D CRAWLER EXCAVATOR	
Standard Features	43
Price List	46
Factory Supplied Accessories	52
CX210D CRAWLER EXCAVATOR	02
Standard Features	55
Price List	58
Factory Supplied Accessories	66
CX210D LR CRAWLER EXCAVATOR	00
Standard Features	67
Price List	70
Factory Supplied Accessories	74
CX245D LC and LC/DZ CRAWLER EXCAVATOR	74
	7.5
Standard Features	75 77
Price List	
Factory Supplied Accessories	83
	0.5
Standard Features	85
Price List	88
Factory Supplied Accessories	95
CX250D LR CRAWLER EXCAVATOR	-
Standard Features	97
Price List	100
Factory Supplied Accessories	104
CX290D LC MATERIAL HANDLER CRAWLER EXCAVATOR	
Standard Features	105
Price List	107
CX290D LC SCRAP CRAWLER EXCAVATOR	
Standard Features	111
Price Liet	112



EXCAVATORS TABLE OF CONTENTS

CX300D CRAWLER EXCAVATOR	
Standard Features	117
Price List	120
Factory Supplied Accessories	126
CX350D CRAWLER EXCAVATOR	
Standard Features	135
Price List	138
Factory Supplied Accessories	144
CX350D LR CRAWLER EXCAVATOR	
Standard Features	141
Price List	144
Factory Supplied Accessories	148
CX490D CRAWLER EXCAVATOR	
Standard Features	149
Price List	152
Factory Supplied Accessories	158
CX500D MASS CRAWLER EXCAVATOR	
Standard Features	159
Price List	162
Factory Supplied Accessories	168
CX750D RTC CRAWLER EXCAVATOR	
Standard Features	169
Price List	171
Factory Supplied Accessories	176
CX750D RTC ME CRAWLER EXCAVATOR	
Standard Features	177
Price List	179
Factory Supplied Accessories	184



(Ex Works Port of Entry) Standard Equipment

ENGINE:

Isuzu AP-4LE2X turbocharged
Tier 4 Final Certified
4 Cylinder liquid cooled diesel
High Pressure Common Rail
Cooled EGR with variable controlled
valve
DOC - diesel oxidation catalyst
133 cu. in. (2.2 liter) displacement

Net (SAE) 53.6 (40.0kw) at 2000 RPM

Fuel Tank Capacity: 31.7 gal. (US) Long Life Anti-freeze (protect to -34°F)

OPERATOR'S CAB:

Horsepower:

4-point viscous-mounted ROPS cab Pressurized cab

- Climate control: AC/Heat/Defrost
- Fully adjustable deluxe seat with 3" seat-belt
- AM/FM radio with dual speakers
- Floor mats
- 12-volt outlet
- In-cab light

Cab roof skylight

Safety glass:

- Two-piece front window
- Front windshield wiper with washer

Waterproof/illuminated membrane

switches

Low-effort pilot controls

Full-color LCD display - rearview

camera ready

Dial type throttle control for engine

speed

Work mode selector: SP, H, Auto

One-touch idle

External rearview mirrors

Programmable anti-theft protection

ELECTRICAL:

24 Volt system
Alternator: 50 AMP
Batteries: 2

BLADE:

CX75C W/DOZER BLADE ONLY
Hydraulically controlled dozer blade

- Blade width: 7'7"
- Blade height: 1'6"

UPPER STRUCTURE:

Swing brake
Casted counterweight
Upper undercovers
500 hour greasing interval - turntable
bearing

UNDERCARRIAGE:

X-pattern car-body LC/long undercarriage: 9'4" (2.85M) Track gauge: 6'6" (1.99M) Shoes: 3-bar/18" (39 per side) Hydraulic adjustable track tension Tapered upper track frame Front track guides Lower under covers

TRACK DRIVE:

2-speed independent hydrostatic travel
 (max. 3.2 mph)
SAHR disc brakes
Drive motor guards



(Ex Works Port of Entry) Standard Equipment

HYDRAULICS:

Control pattern change selector

Open-center system

Two - variable displacement axial
 piston pumps with regulating system

One - pilot control gear pump

Auxiliary hydraulic valve

Boom anti-drift valve

5000 hour hydraulic oil change interval

1000 hour hydraulic filter change
 interval

ATTACHMENTS:

Arm: 5'6" (less bucket)
Boom: 12'4" one piece
Hammer operation adaptable Reinforcing required for
crusher/cutter operation
Swing brake

MISCELLANEOUS:

Parts catalogue
Single key lock-up
Travel alarm and horn
Centralized lube bank
Rubber bumpers for upper sides
(order through Service Parts)
Working lights: lx boom, 1 x cab

Order from Factory Supplied Attachments:

Please consult excavator
attachments weight limits prior to
selecting a coupler and large bucket.
Excessive bucket and coupler weight
will negatively impact machine
performance.



(Ex Works Port of Entry) Models

COMMERCIAL MODEL	Weight	Factory Data	List Price
CX75C W/DOZER BLADE	17,400 LBS		\$124,962.00

LANGUAGE

SD_47083 OPERATOR'S MANUAL

English Literature

Spanish Literature

French Canadian Literature

781981

461540

781980

CX75C MIN SWING RADIUS CRAWLER EXCAVATOR US PRICE LIST

(Ex Works Port of Entry) Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
BOOMS				
BOOMS				
SD_E5311 BC	DOM			
481858	Std Boom			No Charge
	12'4" (3.75 M) Standard Boom			3.
461025	Offset Boom			\$7,730.00
	12'9" (3.89 M) Offset Boom			, ,
- ! !	1 () () () () () () () () () (•	
ARMS				
, ii tiii C				
SD E5320 AF	RM/DIPPERSTICK			
	Standard Boom			
781172	5'7" (1.69 M) Arm			No Charge
481265	7'2" (2.19 M) Arm			\$635.00
	Offset Boom		<u> </u>	φοσο.σσ
481062	5'9" (1.75 M) Standard Arm			\$942.00
481063	6' 11" (2.11 M) Standard Arm			\$1,484.00
		•		+ · , · · · · · · ·
TRACK SHOES				
SD_E5199 TF	RACK SHOES			
9560017	18" (450mm) Steel Shoes, 3-bar			No Charge
9560002	23.6"(600mm) Steel Shoes			\$763.00
	Blade will not fully cover track width when using 24" shoes			
9560018	18"(450mm)Bolt-on Rubber Track			\$5,882.00
	Rubber pads bolted on regular 18" track			
9560020	17.7"(450mm)Full Rubber Tracks			\$3,588.00
	, , , , , , , , , , , , , , , , , , , 	•	· '	

No Charge

No Charge

No Charge



(Ex Works Port of Entry)

ADI	DITIONAL EQU	JIPMENT CXM			
AD	DITIONAL OPTI	ONS			
	SD_E5443 CA	AB GUARD (FOPS)			
	XE5443X	No FOPS Top Cab Guard			No Charge
	481070	FOPS Top Cab Guard			\$1,146.00
		AB GUARD (FRONT)	1	1	
		No Front Guard			No Charge
	461142	Front Guard - Wire Mesh Screen			\$1,326.00
	461024	Front Stone Guard (OPG L2)			\$2,324.00
		vertical bars (one piece/full length)			
	SD E6410 AL	IXILIARY HYDRAULICS			
		No Optional Hydraulics			No Charge
•	-	Standard Boom	•	•	
	461868	Multi Function - Proportional			\$6,885.00
		Multi-Function Auxiliary Hydraulics			
		For use with multiple applications:			
		hammers/thumbs/grapples/crushers			
		Does not include the in-cab Electronic Pressure Control feature			
		Joystick activated with Electronic Proportional Controls			
		Provides single or dual pump, two-way flow			
		Secondary Low-flow Auxiliary Hydraulics can be added			
		Includes manually adjustable relief valve to set required pressures			
		Is switchable to single acting flow for hammer applications			
		Notes:			
		1) Not for use with other Auxiliary Hydraulics options with the			
		exception of Low Flow.			
		2) Heavy duty bucket linkage is standard equipment			
		on C Series excavators.			
		3) For dealer installed auxiliary hydraulic kits contact:	1		
		HydrauliCircuit Technology (HCT)			
		(1-888-603-0080 or sales@hctkits.com or www.hctkits.com)			

For use with Offset Boom

CX75C MIN SWING RADIUS CRAWLER EXCAVATOR US PRICE LIST

(Ex Works Port of Entry)

	461873	Offset Boom Double Aux Hyd	\$3,783.00
		Offset Boom Double Acting Auxiliary Hydraulics	
		For use with Offset Boom option 461025 ONLY	
		For use with Offset Short Arm 481062 ONLY	
		For use with thumb applications	
		Joystick Activated with Electronic Proportional Controls	
		Provides single pump, two-way flow	
		Hydraulic plumbing provided to the end of the boom only,	
		no piping to the arm	
		This system is not switchable to single acting flow	
		Notes:	
		1) Not for use other Auxiliary Hydraulics options with the	
		exception of Low Flow.	
		2) Heavy duty bucket linkage is standard equipment on	
		C series excavators.	
		3) For dealer installed auxiliary hydraulic kits contact:	
		HydrauliCircuit Technology (HCT) (1-888-603-0080 or sales@hctkits.com or www.hctkits.com)	
s	XE6417X	CONDARY AUXILIARY HYDRAULICS No Low Flow Circuit	No Charge
S	_	CONDARY AUXILIARY HYDRAULICS No Low Flow Circuit Secondary Auxiliary Hydraulics Secondary Low Flow Auxiliary Hydraulics	
S	XE6417X	CONDARY AUXILIARY HYDRAULICS No Low Flow Circuit Secondary Auxiliary Hydraulics	
S	XE6417X	CONDARY AUXILIARY HYDRAULICS No Low Flow Circuit Secondary Auxiliary Hydraulics Secondary Low Flow Auxiliary Hydraulics	
S	XE6417X	CONDARY AUXILIARY HYDRAULICS No Low Flow Circuit Secondary Auxiliary Hydraulics Secondary Low Flow Auxiliary Hydraulics Provides low-flow for rotation or tilt hydraulic attachments.	
S	XE6417X	CONDARY AUXILIARY HYDRAULICS No Low Flow Circuit Secondary Auxiliary Hydraulics Secondary Low Flow Auxiliary Hydraulics Provides low-flow for rotation or tilt hydraulic attachments. For use with Standard Boom option 481858	
	XE6417X 461863	CONDARY AUXILIARY HYDRAULICS No Low Flow Circuit Secondary Auxiliary Hydraulics Secondary Low Flow Auxiliary Hydraulics Provides low-flow for rotation or tilt hydraulic attachments. For use with Standard Boom option 481858 Not for use with Offset Boom option 461025 Joystick Activated with Electronic Proportional Controls	
	XE6417X 461863 :D_E9702 RE	CONDARY AUXILIARY HYDRAULICS No Low Flow Circuit Secondary Auxiliary Hydraulics Secondary Low Flow Auxiliary Hydraulics Provides low-flow for rotation or tilt hydraulic attachments. For use with Standard Boom option 481858 Not for use with Offset Boom option 461025 Joystick Activated with Electronic Proportional Controls AR VIEW CAMERA	\$4,039.00
	XE6417X 461863 5D_E9702 RE XE9702X	CONDARY AUXILIARY HYDRAULICS No Low Flow Circuit Secondary Auxiliary Hydraulics Secondary Low Flow Auxiliary Hydraulics Provides low-flow for rotation or tilt hydraulic attachments. For use with Standard Boom option 481858 Not for use with Offset Boom option 461025 Joystick Activated with Electronic Proportional Controls AR VIEW CAMERA No Rear View Camera	\$4,039.00 No Charge
	XE6417X 461863 :D_E9702 RE	CONDARY AUXILIARY HYDRAULICS No Low Flow Circuit Secondary Auxiliary Hydraulics Secondary Low Flow Auxiliary Hydraulics Provides low-flow for rotation or tilt hydraulic attachments. For use with Standard Boom option 481858 Not for use with Offset Boom option 461025 Joystick Activated with Electronic Proportional Controls AR VIEW CAMERA	\$4,039.00 No Charge
S	XE6417X 461863 SD_E9702 RE XE9702X 461504 SD_E9730 SA	CONDARY AUXILIARY HYDRAULICS No Low Flow Circuit Secondary Auxiliary Hydraulics Secondary Low Flow Auxiliary Hydraulics Provides low-flow for rotation or tilt hydraulic attachments. For use with Standard Boom option 481858 Not for use with Offset Boom option 461025 Joystick Activated with Electronic Proportional Controls AR VIEW CAMERA No Rear View Camera Rear View Camera FETY VALVE	\$4,039.00 No Charge \$646.00
S	XE6417X 461863 3D_E9702 RE XE9702X 461504 3D_E9730 SA XE9730X	CONDARY AUXILIARY HYDRAULICS No Low Flow Circuit Secondary Auxiliary Hydraulics Secondary Low Flow Auxiliary Hydraulics Provides low-flow for rotation or tilt hydraulic attachments. For use with Standard Boom option 481858 Not for use with Offset Boom option 461025 Joystick Activated with Electronic Proportional Controls AR VIEW CAMERA No Rear View Camera Rear View Camera FETY VALVE No Hose Burst Check Valve	\$4,039.00 No Charge \$646.00 No Charge
S	XE6417X 461863 SD_E9702 RE XE9702X 461504 SD_E9730 SA	CONDARY AUXILIARY HYDRAULICS No Low Flow Circuit Secondary Auxiliary Hydraulics Secondary Low Flow Auxiliary Hydraulics Provides low-flow for rotation or tilt hydraulic attachments. For use with Standard Boom option 481858 Not for use with Offset Boom option 461025 Joystick Activated with Electronic Proportional Controls AR VIEW CAMERA No Rear View Camera Rear View Camera FETY VALVE No Hose Burst Check Valve Hose Burst Check Valve	\$4,039.00 No Charge \$646.00 No Charge
S	XE6417X 461863 3D_E9702 RE XE9702X 461504 3D_E9730 SA XE9730X	CONDARY AUXILIARY HYDRAULICS No Low Flow Circuit Secondary Auxiliary Hydraulics Secondary Low Flow Auxiliary Hydraulics Provides low-flow for rotation or tilt hydraulic attachments. For use with Standard Boom option 481858 Not for use with Offset Boom option 461025 Joystick Activated with Electronic Proportional Controls AR VIEW CAMERA No Rear View Camera Rear View Camera FETY VALVE No Hose Burst Check Valve	\$4,039.00 No Charge \$646.00 No Charge
s	XE6417X 461863 D_E9702 RE XE9702X 461504 D_E9730 SA XE9730X 461559	No Low Flow Circuit Secondary Auxiliary Hydraulics Secondary Low Flow Auxiliary Hydraulics Provides low-flow for rotation or tilt hydraulic attachments. For use with Standard Boom option 481858 Not for use with Offset Boom option 461025 Joystick Activated with Electronic Proportional Controls AR VIEW CAMERA No Rear View Camera Rear View Camera FETY VALVE No Hose Burst Check Valve Hose Burst Check Valve Located on Boom and Arm Cylinder	\$4,039.00 No Charge \$646.00 No Charge
s	XE6417X 461863 3D_E9702 RE XE9702X 461504 3D_E9730 SA XE9730X	No Low Flow Circuit Secondary Auxiliary Hydraulics Secondary Low Flow Auxiliary Hydraulics Provides low-flow for rotation or tilt hydraulic attachments. For use with Standard Boom option 481858 Not for use with Offset Boom option 461025 Joystick Activated with Electronic Proportional Controls AR VIEW CAMERA No Rear View Camera Rear View Camera FETY VALVE No Hose Burst Check Valve Hose Burst Check Valve Located on Boom and Arm Cylinder	No Charge \$4,039.00 No Charge \$646.00 No Charge \$4,051.00



(Ex Works Port of Entry) Factory Supplied Attachments

Order Code	Description	Weight	Factory Data	List Price
Case Coupler				
47603261	Multi-Fit S Hyd.Pin Grabber Coupler Kit Full Kit and Pins Optimized for use with Case coupler buckets. Also can be used with a wide range of buckets from other manufacturers including pin-on types. Includes hydraulic installation kit and instructions.	205 LB		\$6,193.00
Case Coupler Buck	ets			
84422902	18" Heavy-Duty Coupler Bucket with 3 teeth (.24 cu. yd.)	440 LB		\$1,749.00
84422903	24" Heavy-Duty Coupler Bucket with 4 teeth (.32 cu. yd.)	520 LB		\$2,067.00
84422906	30" Heavy-Duty Coupler Bucket with 5 teeth (.41 cu. yd.)	585 LB		\$2,292.00
84422909	36" Heavy-Duty Coupler Bucket with 5 teeth (.50 cu. yd.)	670 LB		\$2,550.00
84422911	42" Heavy-Duty Coupler Bucket with 6 teeth (.59 cu. yd.)	760 LB		\$2,798.00
Case Pin-On Bucke				
84404122	42" Ditching Pin-On Bucket (.60 cu. yd.) (.60 cu. yd.)			\$1,871.00
84404123	48" Ditching Pin-On Bucket (.70 cu. yd.)			\$1,947.00
84422873	18" Heavy-Duty Pin-On Bucket with 3 teeth (.21 cu. yd.)	450 LB		\$1,375.00
84422885	24" Heavy-Duty Pin-On Bucket with 4 teeth (.31 cu. yd.)	530 LB		\$1,617.00
84422889	30" Heavy-Duty Pin-On Bucket with 5 teeth (.39 cu. yd.)	600 LB		\$1,802.00
84422894	36" Heavy-Duty Pin-On Bucket with 5 teeth (.48 cu. yd.)	685 LB		\$2,003.00
84422897	42" Heavy-Duty Pin-On Bucket with 6 teeth (.57 cu. yd.)	790 LB		\$2,196.00
Direct Link Thumb				
47609053	KIT, THUMB, HYD, 2-TINE, use with bucket only (2 tine - for use with buckets with odd number of teeth)	425 LB		\$4,043.00
47609054	KIT, THUMB, HYD, 2-TINE, use with bucket and coupler (2 tine - for use with buckets with odd number of teeth)	475 LB		\$4,285.00
47625914	KIT, THUMB, HYD, 2-TINE, use with bucket only (2 tine - for use with buckets with even number of teeth)	425 LB		\$4,043.00
47625915	KIT, THUMB, HYD, 2-TINE, use with bucket and coupler (2 tine - for use with buckets with even number of teeth)	475 LB		\$4,285.00

(This page intentionally left blank)



CX80C CRAWLER EXCAVATOR - W/ DOZER BLADE US PRICE LIST

(Ex Works Port of Entry) Standard Equipment

ENGINE:

Isuzu AU-4LE2X turbocharged
Tier 4 Final Certified
4 Cylinder liquid cooled diesel
High pressure common rail
Cooled EGR with variable
 controlled valve
DOC - diesel oxidation catalyst
133 cu. in. (2.2 liter) displacement
Horsepower:
 - Net (SAE) 53.6 (40.0 kw) at
 2000 RPM
Fuel Tank Capacity: 31.7 gal. (US)

OPERATOR'S CAB:

4-point viscous-mounted ROPS cab Pressurized cab

- Climate control: AC/Heat/Defrost
- Fully adjustable deluxe seat with 3" seat-belt
- AM/FM radio with dual speakers
- Floor mats
- 12-volt outlet

Long Life Anti-freeze

(protect to - 34°F)

- In-cab light

Cab roof skylight

Safety glass:

- Two-piece front window
- Front windshield wiper with washer

Waterproof/illuminated membrane

switches

Low-effort pilot controls

Full-color LCD display - rearview

camera ready

Dial type throttle control for engine

speed

Work mode selector: SP, H, Auto

One-touch idle

External rearview mirrors

Programmable anti-theft protection

ELECTRICAL:

24 Volt system
Alternator: 50 AMP
Batteries: 2

BLADE:

Hydraulically controlled dozer blade

- Blade width: 7'7"
- Blade height: 1'6"

UPPER STRUCTURE:

Swing brake
Casted counterweight
Upper undercovers
500 hour greasing interval - turntable
bearing

UNDERCARRIAGE:

X-pattern car-body
LC/long undercarriage: 94" (2.85M)
Track gauge: 62" (1.99M)
Shoes: 3-bar/18" (39 per side)
Hydraulic adjustable track tension
Tapered upper track frame
Front track guides
Lower under covers

TRACK DRIVE:

2 speed independent hydrostatic travel
 (max. 3.2 mph)
SAHR disc brakes
Drive motor guards



CX80C CRAWLER EXCAVATOR - W/ DOZER BLADE US PRICE LIST

(Ex Works Port of Entry) Standard Equipment

HYDRAULICS:

Control pattern change selector
Open-center system
Two - variable displacement axial
 piston pumps with regulating
 system
One - pilot control gear pump
One position mode selector
 Auxiliary hydraulic valve
Boom anti-drift valve
5000 hour hydraulic oil change interval
1000 hour hydraulic filter change
 interval

ATTACHMENTS:

Arm: 5'6" (less bucket)
Swing Boom: 11'6" one piece
Hammer operation adaptable Reinforcing required for
crusher/cutter operation

MISCELLANEOUS:

Parts catalogue
Single key lock-up
Travel alarm and horn
Centralized lube bank
Rubber bumpers for upper sides
 (order through Service Parts)
Working lights: 1 x boom, 1 x cab,
 1 x house

Order from Factory Supplied Attachments:

Please consult excavator
attachments weight limits prior to
selecting a coupler and large bucket.
Excessive bucket and coupler weight
will negatively impact machine
performance.



CX80C CRAWLER EXCAVATOR - W/ DOZER BLADE US PRICE LIST

(Ex Works Port of Entry) Models

COMMERCIAL MODEL	Weight	Factory Data	List Price
CX80C	18,900 LBS		\$137,557.00

XE6410X No Optional Hydraulics



CX80C CRAWLER EXCAVATOR - W/ DOZER BLADE US PRICE LIST

(Ex Works Port of Entry) Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
ADMO				
ARMS				
SD F5320 AR	M/DIPPERSTICK			
781172	5'7" (1.69 M) Arm			No Charge
481265	7'2" (2.19 M) Arm			\$635.00
		•		•
TRACK SHOES				
SD_E5199 TR	ACK SHOES			
9560017	18" (450mm) Steel Shoes, 3-bar			No Charge
9560002	23.6"(600mm) Steel Shoes			\$763.00
9560018	18"(450mm)Bolt-on Rubber Track			\$5,882.00
	Rubber pads bolted on regular 18" track			A
9560020	17.7"(450mm)Full Rubber Tracks			\$3,588.00
LANGUAGE				
00 47000 00	EDATORIO MANUAL			
781981	ERATOR'S MANUAL			No Charge
461540	English Literature French Canadian Literature			No Charge
781980	Spanish Literature			No Charge
701000	Opariion Enoratare			140 Chargo
ADDITIONAL EQU	IIPMENT CYM			
ADDITIONAL EQU	III III DAIII			
ADDITIONAL OPTI	ONS			
SD_E5443 CA	B GUARD (FOPS)			
XE5443X	No FOPS Top Cab Guard			No Charge
481070	FOPS Top Cab Guard			\$1,146.00
	B GUARD (FRONT)		1	
XE5444X				No Charge
461142	Front Guard - Wire Mesh Screen			\$1,326.00
461024	Front Stone Guard (OPG L2)			\$2,324.00
	vertical bars (one piece/full length)			
OD 50440 AL	IVII IA DV LIVDD ALII IOC			
SD_E6410 AL	XILIARY HYDRAULICS			

No Charge

Refuel Pump

481257

CX80C CRAWLER EXCAVATOR - W/ DOZER BLADE US PRICE LIST

(Ex Works Port of Entry)

	,		
461868	Multi Function - Proportional		\$6,885.00
	Multi-Function Auxiliary Hydraulics		
	For use with multiple applications:		
	hammers/thumbs/grapples/crushers		
	Does not include the in-cab Electronic Pressure Control feature		
	Joystick activated with Electronic Proportional Controls		
	Provides single or dual pump, two-way flow		
	Secondary Low-flow Auxiliary Hydraulics can be added		
	Includes manually adjustable relief valve to set required pressures		
	Is switchable to single acting flow for hammer applications		
	Notes:		
	1) Not for use with other Auxiliary Hydraulics options with the		
	exception of Low Flow.		
	2) Heavy duty bucket linkage is standard equipment		
	on C Series excavators.		
	3) For dealer installed auxiliary hydraulic kits contact:		
	HydrauliCircuit Technology (HCT)		
	(1-888-603-0080 or sales@hctkits.com or www.hctkits.com)		
OD 50447 O	FOONDARY ALIVILIA BY LIVER ALILIAN		
	ECONDARY AUXILIARY HYDRAULICS	<u> </u>	No Chargo
461863	No Low Flow Circuit Secondary Auxiliary Hydraulics		No Charge \$4,039.00
401003			\$4,039.00
	Secondary Low Flow Auxiliary Hydraulics Provides low-flow for rotation or tilt hydraulic attachments.		
	For use with Standard Boom option 481858		
	Not for use with Offset Boom option 461025		
	Joystick Activated with Electronic Proportional Controls		
	Joystick Activated with Electronic Proportional Controls	<u>l</u>	
SD E9702 R	EAR VIEW CAMERA		
	No Rear View Camera		No Charge
461504	Rear View Camera		\$646.00
1 101004	······································	<u> </u>	ψο 10.00
SD_E9730 S.	AFETY VALVE		
	No Hose Burst Check Valve		No Charge
461559	Hose Burst Check Valve		\$4,051.00
	Located on Boom and Arm Cylinder		
SD_E9874 R	EFUEL PUMP		
XE9874X	No Refuel Pump		No Charge

\$1,296.00



CX80C CRAWLER EXCAVATOR - W/ DOZER BLADE US PRICE LIST

(Ex Works Port of Entry)

Factory Supplied Attachments

Order Code	Description	Weight	Factory Data	List Price
Case Coupler Bucl	kets			
84422902	18" Heavy-Duty Coupler Bucket with 3 teeth (.24 cu. yd.)	440 LB		\$1,749.00
84422903	24" Heavy-Duty Coupler Bucket with 4 teeth (.32 cu. yd.)	520 LB		\$2,067.00
84422906	30" Heavy-Duty Coupler Bucket with 5 teeth (.41 cu. yd.)	585 LB		\$2,292.00
84422909	36" Heavy-Duty Coupler Bucket with 5 teeth (.50 cu. yd.)	670 LB		\$2,550.00
84422911	42" Heavy-Duty Coupler Bucket with 6 teeth (.59 cu. yd.)	760 LB		\$2,798.00
Case Multi Fit Cou	pler			
47603261	Multi-Fit S Hyd.Pin Grabber Coupler Kit Full Kit and Pins Optimized for use with Case coupler buckets. Also can be used with a wide range of buckets from other manufacturers including pin-on types. Includes hydraulic installation kit and instructions.	205 LB		\$6,193.00
Case Pin On Bucke	ets			
84404122	42" Ditching Pin-On Bucket (.60 cu. yd.) (.60 cu. yd.)			\$1,871.00
84404123	48" Ditching Pin-On Bucket (.70 cu. yd.)			\$1,947.00
84422873	18" Heavy-Duty Pin-On Bucket with 3 teeth (.21 cu. yd.)	450 LB		\$1,375.00
84422885	24" Heavy-Duty Pin-On Bucket with 4 teeth (.31 cu. yd.)	530 LB		\$1,617.00
84422889	30" Heavy-Duty Pin-On Bucket with 5 teeth (.39 cu. yd.)	600 LB		\$1,802.00
84422894	36" Heavy-Duty Pin-On Bucket with 5 teeth (.48 cu. yd.)	685 LB		\$2,003.00
84422897	42" Heavy-Duty Pin-On Bucket with 6 teeth (.57 cu. yd.)	790 LB		\$2,196.00
Direct Link Thumb				
47609053	KIT, THUMB, HYD, 2-TINE, use with bucket only (2 tine - for use with buckets with odd number of teeth)	425 LB		\$4,043.00
47609054	KIT, THUMB, HYD, 2-TINE, use with bucket and coupler (2 tine - for use with buckets with odd number of teeth)	475 LB		\$4,285.00
47625914	KIT, THUMB, HYD, 2-TINE, use with bucket only (2 tine - for use with buckets with even number of teeth)	425 LB		\$4,043.00
47625915	KIT, THUMB, HYD, 2-TINE, use with bucket and coupler (2 tine - for use with buckets with even number of teeth)	475 LB		\$4,285.00

SWC- Swing Relief Control

SSC- Spool Stroke Control



CX130D CRAWLER EXCAVATOR US PRICE LIST

(Ex Works Port of Entry) Standard Equipment

ENGINE: HYDRAULICS: Isuzu AR-4JJ1X Auto power boost Tier 4 Final Certified Auto swing priority Selective Catalytic Reduction (SCR) Arm speed assistance (2 pump flow) Diesel Oxidation Catalyst (DOC) Auxiliary flow control Cooled Exhaust Gas Recirculation Auxiliary valve (CEGR) Boom speed assistance (2 pump flow) Four-cylinder turbo-charged diesel Bucket curl assist VGT turbocharger Control levers pre-wired for auxiliary Electronic fuel injection hydraulics High pressure common rail system Electronically controlled hydraulic Neutral safety start Auto-engine warm up Holding valve (Boom and Arm) Glow-plug pre-heat Fire wall Hydraulic filter restriction indicator Fuel Economy Assist System (FEA) Engine Protection Feature (EPF) Neutral pump de-stroke Dual-stage fuel filtration Oil cooler Dual element air filter Power save Remote oil filter Pump stand-by pressure Drain for fuel tank Auto travel speed change Remote engine oil drain Selectable work modes 500-hour engine oil change interval Free swing - switch activated Hydraulic oil sample port 24-volt system Engine oil sample port Control pattern selector Battery disconnect switch Pre-set auxiliary pump settings Emergency engine stop Auxiliary valve External Fuel and DEF gauges 5,000-hour hydraulic oil change Fan housing interval Fuel cooler 1,000-hour hydraulic filter change Fuel filter restriction indicator interval Fuel shut-off valve SAHR brake Idle start Radiator, oil cooler, intercooler -UPPER STRUCTURE: protective screen ISO mirrors (3) Cab viscous-mounts (fluid) FUEL ECONOMY SYSTEMS: Upper mounted work light (70 watt) Engine Idle / Fuel Economy System: Swivel quard belly pan Auto-idle Center cover (over main CV) One-touch idle Fuel tank belly pan Auto-idle shut-down Handrail (RH access) Lifting eyes for counterweight BEC- Boom Economy Control AEC- Auto Economy Control Lockable fuel cap, service doors and

toolbox



(Ex Works Port of Entry) Standard Equipment

ATTACHMENTS:

Boom- 15 ft. 2 in. (4.63 m) Arm- 8 ft. 2 in. (2.50 m) Heavy-duty bucket linkage Boom mounted work light (70 watt) Auxiliary pipe brackets Centralized grease fittings

Arm and boom regeneration
Bucket anti-clatter device

Chrome pins

Easy Maintenance System (EMS)

bushings

Teardrop pin retention keepers

OPERATOR STATION:

ROPS protection FOPS cab (Level 1) Pressurized cab Face vent Cab lights (2)

One-touch lock front window

One piece window (right)

Safety glass windows

Interior dome light

Gate lock hydraulic activation

Emergency exit and hammer

Clear (polycarbonate) roof window w/
 sunshade

AC/heat/defrost w/ auto climate control

LED Color monitor— 7 in (180 mm)

26 selectable languages for monitor

On-board diagnostic system

10 programmable attachments settings
 on monitor - 5 single flow, 5 dual
 flow

Seatbelt-3 in. (76 mm)

Heated high-back cloth seat with air suspension and 650 tilt adjustment

Sliding seat - 3.54 in. (90 mm)

Adjustable armrests

Tilting consoles- 4-position

Sliding cockpit - 3.15 in. (80 mm)

Low-effort joystick controls

OPERATOR STATION (continued):

Controls pre-wired for auxiliary

Straight travel

AM/FM radio w/ antenna, 2 speakers

and Bluetooth capabilities

Aux-in port for personal electronics

Radio mute switch (joystick)

Rear-view & Side-view camera

Anti-theft system (start code system)

Rubber floormat

12-volt electric outlet

24-volt cigarette lighter

Windshield wiper/washer

Cup holder

Storage compartments

Warm/cool storage compartment

Travel alarm with cancel switch

Ignition keys

One key start & lock-up

Cab filter (external)

Cab handrails

Operator's manual

UNDERCARRIAGE:

Long undercarriage

23.6 in. (600 mm) steel shoes, triple

semi-grouser

Full overlap turntable bearing tub

No track chain guides

Hydraulic track adjustment

Sealed link chain

Steps

Carbody belly pan (swivel guard)

X-pattern carbody

Lashing points (tie downs)

FRONT DOZER BLADE:

8 ft. 6 in. (2.59m) width - comes with
23.6 in. (600 mm) steel shoes



(Ex Works Port of Entry) Standard Equipment

EXTRA FILTER KIT:

Engine oil filter

Filter wrench

Fuel filters

Grease gun

Green plug oil drain hose for engine oil drain

Hydraulic return filter

Pilot circuit hydraulic filter

CASE ProCare - Full Machine Protection Factory Warranty (3-yr/3000-hr), Planned Maintenance (3-yr/2000-hr) and SiteWatch™ Telematics CASE SiteWatch™ Telematics
Includes hardware and a 3-yr
advanced data subscription

PARTS OFFERING:
Hammers; Thumbs
Rubber bumper guard



(Ex Works Port of Entry) Models

COMMERCIAL MODEL	Weight	Factory Data	List Price
CX130D STD LC	28,400 LB		\$217,867.00
CX130D STD DZB	30,400 LB		\$243,658.00

9560003

27.6" (700mm) TG Steel Shoes

Triple-Grouser Steel Shoes



CX130D CRAWLER EXCAVATOR US PRICE LIST

(Ex Works Port of Entry)

Factory Supplied Options

Oudou Cada	Description	Weight	Footow: Data	Liet Price
Order Code	Description	Weight	Factory Data	List Price
IGHTS				
SD F5408 W	ORKING LIGHTS			
488134	Halogen Working Lights			No Charg
488135	LED Working Lights			\$2,754.0
	8 LED lights			
	2 LED light are mounted on the front (1 on boom, 1 on house)			
	2 LED lights are mounted on the rear			
	(above the rear view camera)			
	1 LED light mounted on each side (2)			
	2 LED lights mounted on the top of the cab			
•		•		
BOOMS				
SD_E5311 BC	OOM			
481858	Std Boom			No Charge
	15'2" (4.63 M) Boom			· ·
781917	No Boom			(\$3,293.00
	Less boom, hoist and arm cylinders and plumbing.			
	Boom-foot and cylinder pins are provided.			
		•		
ARMS				
SD E5320 AF	RM/DIPPERSTICK			
461574	6'10" (2.11 m) HD Arm			(\$433.00
781174	8'2" (2.50 m) Std Arm			No Charge
781178	9'10" (3.01 m) Std Arm			\$737.00
XE5320X				(\$2,080.00
	Less arm, bucket cylinder and linkage			,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
	· · · · · · · · · · · · · · · · · · ·	•	<u>'</u>	
TRACK SHOES				
SIIOLO				
SD_E5199 TF	RACK SHOES			
9560013	23.6" (600 mm) Steel Shoes			No Charge
3300013	Triple-Grouser Steel Shoes	1		ino charge
0500000	OZ CII (700-ses) TO Cheel Chees	+		Ф4 04E 00

\$1,245.00



(Ex Works Port of Entry)

	9560052	20" (500mm) Rubber Pads		\$10,106.00
		Steel Chain with individual rubber pads (steel pads		
		coated with rubber)		

LANGUAGE

SD_47083 OPERATOR'S MANUAL

	461540	French Canadian Literature		No Charge
	781980	Spanish Literature		No Charge
	781981	English Literature		No Charge

ADDITIONAL EQUIPMENT CXC

HYDRAULIC OPTIONS

SD E6410 AUXILIARY HYDRAULICS

	AUXILIARY HYDRAULICS	
	X No Optional Hydraulics	(\$9,331.00)
Not for use	e with No Boom	
461869	MF w/ pressure setting - Prop	No Charge
	Multi-Function Auxiliary Hydraulics with Electronic Pressure	
	Control (EPC)	
	For use with multiple applications:	
	hammers/thumbs/grapples/crushers.	
	Includes in-cab Electronic Pressure Control feature	
	Pressure Control feature allows hydraulic pressure setting	
	from the cab monitor and maintaining pressure settings in	
	memory when multiple tools are used.	
	Joystick Activated with Electronic Proportional Controls	
	Provides single or dual pump, two-way flow,	
	Secondary Low-flow Auxiliary Hydraulics can be added	
	Includes in-cab electronically controlled pressure setting feature	
	Is switchable to single acting flow for hammer application.	
	Notes:	
	1) Not for use with other Auxiliary Hydraulics options, with the	
	exception of Low Flow.	
	2) Heavy duty bucket linkage is standard equipment on	
	C/D series excavators.	
	3) For dealer installed auxiliary hydraulic kits contact:	
	HydrauliCircuit Technology (HCT)	
	(1-888-603-0080 or sales@hctkits.com or www.hctkits.com)	



(Ex Works Port of Entry)

SD_E6417 SECONDARY AUXILIARY HYDRAULICS

Front rock guard (OPG 1) option 781986, or Front rock guard (OPG 2) option 461024.

SD_E5451 SUN VISOR

XE5451X No Sun Visor

461554 | Sun Visor

3D_L0417 3L	CONDACT AUXILIANT TITURAULICS	
XE6417X	No Low Flow Circuit	No Charge
461863	Secondary Auxiliary Hydraulics	\$6,643.00
	Low Flow Electrical Proportional Control	
	Joystick Activated	
	Provides low-flow for rotation or tilt of hydraulic tools.	
	Notes:	
	1) May be used stand alone or with any Case Excavator Auxiliary	
	Hydraulics option.	
	2) For dealer installed auxiliary hydraulic kits contact:	
	HydrauliCircuit Technology (HCT)	
ı	(1-888-603-0080 or sales@hctkits.com or www.hctkits.com)	
CAB OPTIONS		
SD_E5443 CA	AB GUARD (FOPS)	
XE5443X	No FOPS Top Cab Guard	No Charge
481070	FOPS Top Cab Guard	\$1,146.00
SD_E5444 CA	AB GUARD (FRONT)	
XE5444X	No Front Guard	No Charge
461142	Front Guard - Wire Mesh Screen	\$1,326.00
781986	Front Stone Guard (OPG L1)	\$1,973.00
	vertical bars (two piece/upper and lower)	
461024	Front Stone Guard (OPG L2)	\$2,324.00
	vertical bars (one piece/full length)	
461552	Vandal Guard	\$574.00
	Removable steel panels for front windshield	
SD_E5449 RA	AIN DEFLECTOR	
XE5449X	No Rain Deflector	No Charge
461555	Rain Deflector	\$380.00
	Not for use with Front grill guard - 2 x 2 mesh option 461142,	
. 1	1	1

No Charge \$108.00



(Ex Works Port of Entry)

BUCKETS	
SD_E6300 EXCAVATOR BUCKET(S)	
XE6300X No Bucket	No Charge
Buckets may be ordered using Order Codes listed in the	
Factory Supplied Attachments Section	
ADDITIONAL OPTIONS	
SD_E5206 TRACK CHAIN GUIDE	
XE5206X No Track Chain Guide	No Charge
461542 Double Track Chain Guide	\$728.00
SD_E6400 MEC/HYD QUICK COUPLER	
XE6400X No Quick Coupler	No Charge
781128 Hydraulic Quick Coupler Ready	\$1,974.00
Does not come with coupler. Must order coupler from Factory	
Supplied Attachments section	
CD FOZOO CAFETYAYAYA	
SD_E9730 SAFETY VALVE XE9730X No Hose Burst Check Valve	No Charge
481064 Hose Burst Check Valve (HBCV)	No Charge \$7,913.00
Located on Boom and Arm Cylinder	\$7,913.00
Located on Boom and Arm Cymruer	
SD_E9739 FULL VIEW CAMERA	
XE9739X No max view monitor	No Charge
488055 Case Max View Monitor	\$1,700.00
	1
SD E9874 REFUEL PUMP	
XE9874X No Refuel Pump	No Charge
481257 Refuel Pump	\$1,296.00



(Ex Works Port of Entry) Factory Supplied Attachments

	Order Code	Description	Weight	Factory Data	List Price
CAS	E Machine Guid	dance			
	90456016	OEM-Fit 2D Machine Guidance Sys Leica	26 LB		\$18,800.00
		- Option available to Precision-Certified Dealers only.			
		- Expect extended lead times when ordering this option. Contact your CASE representative for more information Attachment calibration required upon delivery Display will arrive in case located in cab, and will need to be			
+	90456015	mounted upon dealer arrival. OEM-Fit 3D Machine Guidance Sys Leica	43 LB		\$64,090.00
	30430013	- Option available to Precision-Certified Dealers only.	40 LD		ψ0+,030.00
		 Expect extended lead times when ordering this option. Contact your CASE representative for more information. Attachment calibration required upon delivery. Display and GNSS antennas will arrive in case located in cab, and will need to be mounted upon dealer arrival. Radio Antenna required- Purchased separately through CNH Parts. 			
		- For 900MHz Radio/Antenna order: LG916750 - CCD21, Satel M3-TR9 Radio iCG80 and L827067 - CA26, Antenna, for CCD15 and 4G modem For 4xx MHz Antenna order: LG916751 - CCD22, Satel TR4+Radio iCG80 and Order 1 of the following: LG805281 CA12, Radio Antenna 406-440MHz or LG805282 CA13, Radio Antenna, 430-480MHz.			
0					
Case	47867959	Multi-Fit S Hyd.Pin Grabber Coupler Kit	551 LB		\$5,197.00
Coo	-		001125		φο,τοτ.σο
Case	84404117	24" Heavy Duty (HD) Coupler Bucket with 4 teeth (.43 cu. yd.)			\$4,075.00
	84404118	30" Heavy Duty (HD) Coupler Bucket with 4 teeth (.56 cu. yd.)	870 LB		\$4,523.00
	84404119	36" Heavy Duty (HD) Coupler Bucket with 5 teeth (.70 cu. yd.)			\$4,905.00
	84404121	42" Heavy Duty (HD) Coupler Bucket with 5 teeth (.83 cu. yd.)			\$5,133.00
Case	e Pin-On Bucke	ts			
	84404093	24" Heavy-Duty Pin-On Bucket with 4 teeth (.50 cu. yd.)			\$2,948.00
	84404095	30" Heavy-Duty Pin-On Bucket with 4 teeth (.65 cu. yd.)			\$3,073.00

(Ex Works Port of Entry)

		(EX WORKS)	,	
	84404103	36" Heavy-Duty Pin-On Bucket with 5 teeth (.79 cu. yd.)	1,301 LB	\$3,329.00
	84406310	42" Heavy-Duty Pin-On Bucket with 5 teeth (.93 cu. yd.)		\$3,740.00
	84404105	24" HD Hi-Capacity Pin-On Bucket with 4 teeth (.58 cu. yd.)		\$3,158.00
	84404108	30" HD Hi-Capacity Pin-On Bucket with 4 teeth (.74 cu. yd.)		\$3,505.00
	84404109	36" HD Hi-Capacity Pin-On Bucket with 5 teeth (.91 cu. yd.)	1,433 LB	\$3,838.00
	84404110	42" HD Hi-Capacity Pin-On Bucket with 5 teeth (1.08 cu. yd.)		\$4,097.00
	84404113	48" Ditching Pin-On Bucket (.79 cu. yd.)		\$2,992.00
	84404115	60" Ditching Pin-On Bucket (1.02 cu yd.)		\$3,394.00
	47609058	Hydraulic Main Pin Direct Link Thumb use with bucket only (2 tine)	830 LB	\$6,569.00
rec	t Link Thumb			
	47609059	KIT, THUMB, HYD, 4-TINE, use with bucket only (3 tine)	860 LB	\$6,953.00
	47609060	KIT, THUMB, HYD, 3-TINE, use with bucket and coupler (2 tine)	870 LB	\$6,813.00
	47609061	KIT, THUMB, HYD, 4-TINE, use with bucket and coupler (3 tine)	910 LB	\$7,293.00
rogr	ressive Link T	humb		
	47609095	KIT, THUMB, PROG LINK, 3- use with bucket only (2 tine)	1,170 LB	\$8,256.00
	47609096	KIT, THUMB, PROG LINK, 4- use with bucket only (3 tine)	1,200 LB	\$8,640.00
	47609097	KIT, THUMB, PROG LINK, 3- use with bucket and coupler (2 tine)	1,200 LB	\$8,504.00
T	47609098	KIT, THUMB, PROG LINK, 4-	1,210 LB	\$8,980.00

use with bucket and coupler (3 tine)

Cab top mounted (2)



CX145D LC AND CX145D STD/DZ US PRICE LIST

(Ex Works Port of Entry) Standard Equipment

ENGINE: OPERATOR'S CAB: Isuzu AM-4JJ1X ROPS protection Tier-4 Final Certified Pressurized cab area Selective Catalytic Reduction (SCR) AC/heat/defrost with auto control Diesel Oxidation Catalyst (DOC) Electronics: Cooled Exhaust Gas Recirculation Color monitor (7 in/180 mm) (CEGR) with Rearview camera view 183 cubic in. displacement/3.0 Liter Rear-view camera Turbocharged/air cooled intercooler Side-view camera Horsepower: AM/FM radio with antenna and Net: 102 (76.4 kW) @ 2000 RPM 2-speakers High pressure common rail system Aux-in port for personal electronics Auto engine warm-up 12-volt electric socket FEA (Fuel Economy Assist System) 24-volt cigarette lighter Engine Idle/Fuel Economy System: KAB ® Air-suspension seat (cloth) Auto Idle Seat belt One-touch Idle Adjustable arm rests Idle Shut-down 4-position tilting consoles Fuel Capacity: Sliding cockpit (7 in/180 mm) 53 gallons (200 L) Low-effort joystick controls AEC (auto economy control) Clear (poly carbonate) roof window External rearview mirrors BEC (boom economy control) Rubber floormat Standard Handrails HYDRAULTCS: Open-center system design Cab interior features: Optional auxiliary hydraulics Cup holder Selectable work modes (3) Storage compartments Auto power boost Warm/cool storage compartments Auto swing priority Easy access fuse box SWC (swing relief control) Interior dome light SSC (spool stroke control) One touch lock front window One key start & lock-up 5000 hour hydraulic oil change interval 1000 hour hyd. filter change interval Interior Light (1 x 10 watt) Two-speed independent travel Free Swing - switch activated Control Pattern Selector Valve Straight travel Travel alarm and horn ELECTRICAL: Windshield wiper and washer 24-volt system Programmable anti-theft system Two batteries (12 volt/92 Ah) 50 Amp Alternator Worklights (4 x 70 watt) Boom mounted (1) Upper mounted (1)



(Ex Works Port of Entry) Standard Equipment

UNDERCARRIAGE:

X-pattern carbody
Undercarriage:

STD LC: 12'4"(3.76 M) length STD DZB: 11'6"(3.50 M) length

Track Gauge:

STD: 6'6" (1.99 M) gauge

Shoe:

STD: 23.6" triple grouser

6.75" pitch

43 shoes per side

LC: Carrier rollers (2 per side)
DZB: Carrier rollers (1 per side)
LC: Track rollers (7 per side)
DZB: Track rollers (7 per side)

 ${\tt Grease \ lubricated \ and \ strutted \ track}$

chains

Hydraulic track adjustment No track chain guides SAHR disc parking break Tapered upper track frame

CX145D MSR W/DOZER model only

DOZER BLADE:

Dozer blade width: 8'6" (2590 mm)
Dozer blade height: 22" (570 mm)

ATTACHMENTS:

Standard LC and DZB Versions:

Boom: 15'2" (4.63M)
Arm: 8'2" (2.50 M)
Heavy-duty bucket linkage
Auxiliary pipe brackets
Attachment cushion valve
Arm and boom regeneration
Arm and boom holding valves
Centralized grease bank

CASE ProCare - Full Machine Protection Factory Warranty (3-yr/3000-hr),
Planned Maintenance (3-yr/2000-hr)
and SiteWatch™ Telematics
CASE SiteWatch™ Telematics
Includes hardware and a 3-yr

Undercarriage:

Rubber shoes: 20.0" (500 mm)

Steel/triple-grouser: 27.6" (700 mm)

Track chain guides - double

Order from Wholegood Attachments

-Third Party section:

advanced data subscription

Buckets

Coupler/Case multi-pin grabber



(Ex Works Port of Entry) Models

COMMERCIAL MODEL	Weight	Factory Data	List Price
CX145D MSR LC	32,100 LB		\$214,192.00
CX145D MSR W/DOZER	33,600 LB		\$225,582.00

(Ex Works Port of Entry)

Factory Supplied Options

Gradi Goad Troight Tuotory Butta Elect 1 1160	Order Code	Description	Weight	Factory Data	List Price
---	------------	-------------	--------	--------------	------------

LIGHTS

SD_E5408 WORKING LIGHTS

	488134	Halogen Working Lights		No Charge
	488135	LED Working Lights		\$2,754.00
		8 LED lights:		
		2 LED light are mounted on the front (1 on boom, 1 on house)		
		2 LED lights are mounted on the rear		
		(above the rear view camera)		
		1 LED light mounted on each side (2)		
		2 LED lights mounted on the top of the cab		

BOOMS

SD_E5311 BOOM

	481858	Std Boom		No Charge
		15' 6" (4.72 M) Standard Boom		
	461025	Offset Boom		\$21,600.00
		15' 6" (4.72 M) Offset Boom		
		For use with CX145C/D MSR W/DOZER		
	781917	No Boom		(\$3,378.00)
		Less boom, hoist and arm cylinders and plumbing.		
		Boom foot and cylinder pins are provided.		

ARMS

SD_E5320 ARM/DIPPERSTICK

 	,	
781174	8'2" (2.50 m) Std Arm	No Charge
	FOR USE WITH STANDARD BOOM (options 481858)	
461574	6'10" (2.11 m) HD Arm	\$576.00
	FOR USE WITH STANDARD BOOM (options 481858)	
	(Recommended for heavy-duty applications - example: hammer)	
781178	9'10" (3.01 m) Std Arm	\$1,089.00
	FOR USE WITH STANDARD BOOM (options 481858)	
XE5320X	No Arm/Dipperstick	(\$2,051.00)
	Less arm, bucket cylinder and linkage	

(Ex Works Port of Entry)

TRACK SHOES

SD_E5199 TRACK SHOES

	9560013	23.6" (600 mm) Steel Shoes		(\$1,547.00)
	9560039	27.5" (700 mm) Steel Shoes		No Charge
	9560052	20" (500mm) Rubber Pads		\$8,277.00
		Steel Chain with individual rubber pads (steel pads		
		coated with rubber)		

LANGUAGE

SD_47083 OPERATOR'S MANUAL

	781981	English Literature		No Charge
	461540	French Canadian Literature		No Charge
	781980	Spanish Literature		No Charge

ADDITIONAL EQUIPMENT CXC

HYDRAULIC OPTIONS		
I RIDRAULIC OPTIONS		

SD_E6410 AUXILIARY HYDRAULICS

 OD_EOTIO NOMENTITIONOCIOO					
	XE6410X	No Optional Hydraulics			(\$9,905.00)



(Ex Works Port of Entry)

	For use with	Standard Boom		
	461869	MF w/ pressure setting - Prop		No Charge
		Multi-Function Auxiliary Hydraulics with Electronic Pressure		
		Control (EPC)		
		For use with multiple applications:		
		hammers/thumbs/grapples/crushers.		
		Includes in-cab Electronic Pressure Control feature		
		Pressure Control feature allows hydraulic pressure setting		
		from the cab monitor and maintaining pressure settings in		
		memory when multiple tools are used.		
		Joystick Activated with Electronic Proportional Controls		
		Bassida single sedest some for the first		
		Provides single or dual pump, two-way flow,		
		Secondary Low-flow Auxiliary Hydraulics can be added		
		Includes in-cab electronically controlled pressure setting feature		
		Is switchable to single acting flow for hammer application.		
		Notes:		
		1) Not for use with other Auxiliary Hydraulics options, with the		
		exception of Low Flow.		
		2) Heavy duty bucket linkage is standard equipment on		
		C/D series excavators.		
		3) For dealer installed auxiliary hydraulic kits contact:		
		HydrauliCircuit Technology (HCT)		
		(1-888-603-0080 or sales@hctkits.com or www.hctkits.com)		
	For use with	Offset Boom		
	461866	Offset Boom Single Aux Hyd		(\$4,216.00)
		Only Available on CX145C DZ		
		Offset Boom Single Acting Auxiliary Hydraulics		
		For use with Offset Boom option 461025 only		
		For use with hammer applications		
		Joystick Activated with Electronic Proportional Controls		
		Provides single direction flow		
		Includes manually adjustable relief valve to set required pressures		
		Notes:		
		1) Not for use other Auxiliary Hydraulics options, with the		
		exception of Low Flow.		
		2) Heavy duty bucket linkage is standard equipment on C series		
		excavators.		
		3) For dealer installed auxiliary hydraulic kits contact:		
		HKX (1-800-493-5487 or www.HKX.com).		

CX145D LC AND CX145D STD/DZ US PRICE LIST

(Ex Works Port of Entry)

461873	Offset Boom Double Aux Hyd	(\$4,531.00)
	Use only with CX145C DZ	
	Offset Boom Double Acting Auxiliary Hydraulics	
	For use with Offset Boom option 461025 only	
	For use with thumb applications	
	Joystick Activated with Electronic Proportional Controls	
	Provides single pump, two-way flow	
	Hydraulic plumbing provided to the end of the boom only,	
	no piping to the arm	
	This system is not switchable to single acting flow	
	Notes:	
	1) Not for use other Auxiliary Hydraulics options with the	
	exception of Low Flow.	
	2) Heavy duty bucket linkage is standard equipment on	
	C series excavators.	
	For dealer installed auxiliary hydraulic kits contact:	
	HKX (1-800-493-5487 or www.HKX.com).	

SD_E6417 SECONDARY AUXILIARY HYDRAULICS

XE6417X	No Low Flow Circuit	No Charge
461863	Secondary Auxiliary Hydraulics	\$6,683.00
	Secondary Low Flow Auxiliary Hydraulics	
	Provides low-flow for rotation or tilt hydraulic attachments.	
	For use with Standard Boom option 481858	
	Not for use with Offset Boom option 461025	
	Joystick Activated with Electronic Proportional Controls	
	Notes:	
	1) May be used stand alone or with any Case Excavator Auxiliary	
	Hydraulics option.	
	2) For dealer installed auxiliary hydraulic kits contact:	
	HydrauliCircuit Technology (HCT) (1-888-603-0080 or sales@hctkits.com or www.hctkits.com)	

CAB OPTIONS

SD_E5443 CAB GUARD (FOPS)

	XE5443X	No FOPS Top Cab Guard		No Charge
	481070	FOPS Top Cab Guard		\$1,146.00

SD_E5444 CAB GUARD (FRONT)

	XE5444X	No Front Guard		No Charge
	461142	Front Guard - Wire Mesh Screen		\$1,326.00

488055

Case Max View Monitor

CX145D LC AND CX145D STD/DZ US PRICE LIST

	(Ex Works Port of Entry)	
781986	Front Stone Guard (OPG L1)	\$1,973.00
	vertical bars (two piece/upper and lower)	
461024	Front Stone Guard (OPG L2)	\$2,324.00
	vertical bars (one piece/full length)	
461552	Vandal Guard	\$574.00
	Removable steel panels for front windshield	
SD E5440 PA	NIN DEFLECTOR	
	No Rain Deflector	No Charge
461555	Rain Deflector	\$380.00
401000	Not for use with Front grill guard - 2 x 2 mesh option 461142,	ψοσο.σο
	Front rock guard (OPG 1) option 781986, or	
	Front rock guard (OPG 2) option 461024.	
	Front rock guard (OFG 2) option 46 1024.	
SD_E5451 SL		
	No Sun Visor	No Charge
461554	Sun Visor	\$108.00
UCKETS		
	CAVATOR BUCKET(S)	
XE6300X		No Charge
	Buckets may be ordered using Order Codes listed in the	
	Factory Supplied Attachments Section	
DDITIONAL OPT	ONS	
CD EEOOG TE	VOK CHVIN CHIDE	
	ACK CHAIN GUIDE No Track Chain Guide	No Charge
461542	Double Track Chain Guide	\$728.00
401342	Double Hack Chain Guide	ψ120.00
SD F6400 MF	EC/HYD QUICK COUPLER	
	No Quick Coupler	No Charge
781128	Hydraulic Quick Coupler Ready	\$2,304.00
701120	Only available on the D series	ψ2,304.00
	Only available on the D series	
SD_E9730 SA	FETY VALVE	
	No Hose Burst Check Valve	No Charge
481064	Hose Burst Check Valve (HBCV)	\$8,667.00
	Located on Boom and Arm Cylinder	\$3,007.00
		1
SD_E9739 FU	ILL VIEW CAMERA	
	No max view monitor	No Charge
400055	One Man View Maritan	£4.700.00

\$1,700.00



CX145D LC AND CX145D STD/DZ US PRICE LIST

(Ex Works Port of Entry)

Factory Supplied Attachments

Order Code	Description	Weight	Factory Data	List Price
CASE Machine (Guidance			
90456016	OEM-Fit 2D Machine Guidance Sys Leica - Option available to Precision-Certified Dealers only. - Expect extended lead times when ordering this option. Contact your CASE representative for more information. - Attachment calibration required upon delivery. - Display will arrive in case located in cab, and will need to be	26 LB		\$18,800.00
90456015	mounted upon dealer arrival. OEM-Fit 3D Machine Guidance Sys Leica - Option available to Precision-Certified Dealers only. - Expect extended lead times when ordering this option. Contact your CASE representative for more information. - Attachment calibration required upon delivery. - Display and GNSS antennas will arrive in case located in cab, and will need to be mounted upon dealer arrival. - Radio Antenna required- Purchased separately through CNH Parts. - For 900MHz Radio/Antenna order: LG916750 - CCD21, Satel M3-TR9 Radio iCG80 and L827067 - CA26, Antenna, for CCD15 and 4G modem. - For 4xx MHz Antenna order: LG916751 - CCD22, Satel TR4+Radio iCG80 and Order 1 of the following: LG805281 CA12, Radio Antenna 406-440MHz or LG805282 CA13, Radio Antenna, 430-480MHz.	43 LB		\$64,090.00
Case Coupler Bu 84404117	24" Heavy Duty (HD) Coupler Bucket			\$4,075.00
84404118	with 4 teeth (.43 cu. yd.) 30" Heavy Duty (HD) Coupler Bucket with 4 teeth (.56 cu. yd.)	870 LB		\$4,523.00
84404119	36" Heavy Duty (HD) Coupler Bucket with 5 teeth (.70 cu. yd.)			\$4,905.00
84404121	42" Heavy Duty (HD) Coupler Bucket with 5 teeth (.83 cu. yd.)			\$5,133.00
Case Pin-On Bu	ckets			
84404093	24" Heavy-Duty Pin-On Bucket with 4 teeth (.50 cu. yd.)			\$2,948.00
84404095	30" Heavy-Duty Pin-On Bucket with 4 teeth (.65 cu. yd.)			\$3,073.00
84404103	36" Heavy-Duty Pin-On Bucket with 5 teeth (.79 cu. yd.)	1,301 LB		\$3,329.00
84406310	42" Heavy-Duty Pin-On Bucket with 5 teeth (.93 cu. yd.)			\$3,740.00

CX145D LC AND CX145D STD/DZ US PRICE LIST

(Ex Works Port of Entry)

	(Ex Wo	rks Port of Entry)	
84404	105 24" HD Hi-Capacity Pin-On Bucket with 4 teeth (.58 cu. yd.)		\$3,158.00
84404	108 30" HD Hi-Capacity Pin-On Bucket with 4 teeth (.74 cu. yd.)		\$3,505.00
84404	36" HD Hi-Capacity Pin-On Bucket with 5 teeth (.91 cu. yd.)	1,433 LB	\$3,838.00
84404	110 42" HD Hi-Capacity Pin-On Bucket with 5 teeth (1.08 cu. yd.)		\$4,097.00
84404	113 48" Ditching Pin-On Bucket (.79 cu. yd.)		\$2,992.00
84404	115 60" Ditching Pin-On Bucket (1.02 cu yd.)		\$3,394.00
476090	058 Hydraulic Main Pin Direct Link Thumb	830 LB	\$6,569.00
476090	use with bucket only (2 tine) KIT, THUMB, HYD, 4-TINE, use with bucket only (3 tine)	860 LB	\$6,953.00
476090	060 KIT, THUMB, HYD, 3-TINE, use with bucket and coupler (2 tine)	870 LB	\$6,813.00
476090	061 KIT, THUMB, HYD, 4-TINE, use with bucket and coupler (3 tine)	910 LB	\$7,293.00
476090	095 KIT, THUMB, PROG LINK, 3- use with bucket only (2 tine)	1,170 LB	\$8,256.00
476090	096 KIT, THUMB, PROG LINK, 4- use with bucket only (3 tine)	1,200 LB	\$8,640.00
476090	097 KIT, THUMB, PROG LINK, 3- use with bucket and coupler (2 tine)	1,200 LB	\$8,504.00
			\$8,980.00



(Ex Works Port of Entry) Standard Equipment

ENGINE:

Isuzu AR-4JJ1X Tier 4 Final Certified

183 cubic in. displacement/3.0 Liter Selective Catalytic Reduction (SCR) Diesel Oxidation Catalyst (DOC) Cooled Exhaust Gas Recirculation

(CEGR) Four-cylinder turbo-charged diesel Turbocharged/air cooled intercooler

Horsepower:

Net: 112 (83.2 kW) @ 2200 rpm

Electronic fuel injection

High pressure common rail system Neutral safety start, Idle start

Auto-engine warm up Glow-plug pre-heat

Fuel Economy Assist System (FEA)

Engine Protection Feature (EPF)

Dual-stage fuel filtration

Dual element air filter

Remote oil filter

Drain for fuel tank

Remote engine oil drain

500-hour engine oil change interval

24-volt system

Engine oil sample port

Battery disconnect switch

Emergency engine stop

External Fuel and DEF gauges

Fan housing

Fuel cooler, Fuel shut-off valve Fuel filter restriction indicator

Radiator, oil cooler, intercooler -

protective screen

FUEL ECONOMY SYSTEMS:

Engine Idle / Fuel Economy System:

Auto-idle

One-touch idle

Auto-idle shut-down

BEC- Boom Economy Control

AEC- Auto Economy Control

SWC- Swing Relief Control

SSC- Spool Stroke Control

HYDRAULICS:

Auto power boost

Auto swing priority

Arm speed assistance (2 pump flow)

Auxiliary flow control

Auxiliary valve

Boom speed assistance (2 pump flow)

Bucket curl assist

Control levers pre-wired for auxiliary

hydraulics

Electronically controlled hydraulic

Holding valve (Boom and Arm)

Fire wall

Hydraulic filter restriction indicator

Neutral pump de-stroke

Oil cooler

Power save

Pump stand-by pressure

Auto travel speed change

Selectable work modes

Free swing - switch activated

Hydraulic oil sample port

Control pattern selector

Pre-set auxiliary pump settings

Auxiliary valve

5,000-hour hydraulic oil change

interval

1,000-hour hydraulic filter change

interval

SAHR brake

UPPER STRUCTURE:

ISO mirrors (3)

Cab viscous-mounts (fluid)

Upper mounted work light (70 watt)

Swivel guard belly pan

Center cover (over main CV)

Fuel tank belly pan

Handrail (RH access)

ISO guard rails (2 right side)

Lifting eyes for counterweight

Lockable fuel cap, service doors and

tool box



OPERATOR STATION (continued):

CX160D CRAWLER EXCAVATOR (STD LC) US PRICE LIST

(Ex Works Port of Entry) Standard Equipment

ATTACHMENTS: Boom- 16 ft. 11 in. (5.15 m) Arm-8 ft. 7 in. (2.62 m) Heavy-duty bucket linkage Boom mounted work light (70 watt) Auxiliary pipe brackets Centralized grease fittings Attachment cushion valve Arm and boom regeneration Bucket anti-clatter device Chrome pins Easy Maintenance System (EMS) bushings Teardrop pin retention keepers OPERATOR STATION: ROPS protection FOPS cab (Level 1) Pressurized cab Face vent

Cab lights (2) Interior dome light One-touch lock front window One piece window (right) Safety glass windows Gate lock hydraulic activation Emergency exit and hammer Clear (polycarbonate) roof window w/ sunshade AC/heat/defrost w/ auto climate control LED Color monitor- 7 in (180 mm) 26 selectable languages for monitor On-board diagnostic system 10 programmable attachments settings on monitor - 5 single flow, 5 dual Seatbelt-3 in. (76 mm) Heated high-back cloth seat with air suspension and 650 tilt adjustment Sliding seat - 3.54 in. (90 mm) Adjustable armrests Tilting consoles- 4-position Sliding cockpit - 3.15 in. (80 mm) Low-effort joystick controls

Controls pre-wired for auxiliary Straight travel AM/FM radio w/ antenna, 2 speakers and Bluetooth capabilities Aux-in port for personal electronics Radio mute switch (joystick) Rear-view & Side-view camera Anti-theft system (start code system) Rubber floormat 12-volt electric outlet 24-volt cigarette lighter Windshield wiper/washer Cup holder Storage compartments Warm/cool storage compartment Travel alarm with cancel switch Ignition keys One key start & lock-up Cab filter (external) Cab handrails Operator's manual

UNDERCARRIAGE:

23.6 in. (600 mm) steel shoes, triple semi-grouser
Full overlap turntable bearing tub
Single track chain guides
Hydraulic track adjustment
Sealed link chain
Steps
Carbody belly pan (swivel guard)
X-pattern carbody
Lashing points (tie downs)

EXTRA FILTER KIT:

Engine oil filter

Filter wrench
Fuel filters
Grease gun
Green plug oil drain hose for
engine oil drain
Hydraulic return filter
Pilot circuit hydraulic filter



(Ex Works Port of Entry) Standard Equipment

CASE ProCare - Full Machine Protection Factory Warranty (3-yr/3000-hr), Planned Maintenance (3-yr/2000-hr) and SiteWatch™ Telematics
CASE SiteWatch™ Telematics
Includes hardware and a 3-yr advanced data subscription



(Ex Works Port of Entry) Models

COMMERCIAL MODEL	Weight	Factory Data	List Price
CX160D STD LC	38,400 LB		\$259,655.00

(Ex Works Port of Entry)

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
LIGHTS				

SD_E5408 WORKING LIGHTS

	488134	Halogen Working Lights		No Charge
	488135	LED Working Lights		\$2,754.00
		8 LED lights		
		2 LED light are mounted on the front (1 on boom, 1 on house)		
		2 LED lights are mounted on the rear		
		(above the rear view camera)		
		1 LED light mounted on each side (2)		
		2 LED lights mounted on the top of the cab		

BOOMS

SD_E5311 BOOM

-	68_20011					
	481858	Std Boom			No Charge	
		16' 11" (5.15 m) Standard Boom				
	781917	No Boom			(\$4,767.00)	
		Less boom, hoist and arm cylinders and plumbing.				
١		Boom-foot and cylinder pins are provided.				

ARMS

SD_E5320 ARM/DIPPERSTICK

	05_10010 / WWW 1 1 1 KO 11 0 K				
	781176	8'7" (2.63 m) Std Arm			No Charge
	781178	9'10" (3.01 m) Std Arm			\$1,300.00
	XE5320X	No Arm/Dipperstick			(\$2,600.00)
		Less arm, bucket cylinder and linkage			

TRACK SHOES

SD_E5199 TRACK SHOES

	9560013	23.6" (600 mm) Steel Shoes		No Charge
		Triple-Grouser Steel Shoes		
	9560003	27.6" (700mm) TG Steel Shoes		\$1,612.00
		Triple-Grouser Steel Shoes		



(Ex Works Port of Entry)

LANGUAGE

SD_47083 OPERATOR'S MANUAL

_	 05_11000 01 E1011011011E						
	781981	English Literature			No Charge		
I	461540	French Canadian Literature			No Charge		
Γ	781980	Spanish Literature			No Charge		

ADDITIONAL EQUIPMENT CXC

HYDRAULIC OPTIONS

SD_E6410 AUXILIARY HYDRAULICS

XE64	10X No Optional Hydraulics	(\$9,905.00)
Not for	use with No Boom	
4618	69 MF w/ pressure setting - Prop	No Charge
	Multi-Function Auxiliary Hydraulics with Electronic Pressure	
	Control (EPC)	
	For use with multiple applications:	
	hammers/thumbs/grapples/crushers.	
	Hammer striumbs/grappies/crushers.	
	Includes in-cab Electronic Pressure Control feature	
	Pressure Control feature allows hydraulic pressure setting	
	from the cab monitor and maintaining pressure settings in	
	memory when multiple tools are used.	
	Joystick Activated with Electronic Proportional Controls	
	Provides single or dual pump, two-way flow,	
	Secondary Low-flow Auxiliary Hydraulics can be added	
	Includes in-cab electronically controlled pressure setting feature	
	Is switchable to single acting flow for hammer application.	
	Notes:	
	Not for use with other Auxiliary Hydraulics options, with the	
	exception of Low Flow.	
	2) Heavy duty bucket linkage is standard equipment on	
	C/D series excavators.	
	For dealer installed auxiliary hydraulic kits contact:	
	HydrauliCircuit Technology (HCT)	
	(1-888-603-0080 or sales@hctkits.com or www.hctkits.com)	

SD_E6417 SECONDARY AUXILIARY HYDRAULICS

ſ		XE6417X	No Low Flow Circuit	No Charge

XE5451X No Sun Visor

Sun Visor

461554

CX160D CRAWLER EXCAVATOR (STD LC) US PRICE LIST

(Ex Works Port of Entry)

econdary Auxiliary Hydraulics econdary Low Flow Auxiliary Hydraulics rovides low-flow for rotation or tilt hydraulic attachments. or use with Standard Boom option 481858 ot for use with Offset Boom option 461025 oystick Activated with Electronic Proportional Controls	\$6,721.00
or use with Standard Boom option 481858 of for use with Offset Boom option 461025 oystick Activated with Electronic Proportional Controls	
or use with Standard Boom option 481858 ot for use with Offset Boom option 461025 oystick Activated with Electronic Proportional Controls	
ot for use with Offset Boom option 461025 bystick Activated with Electronic Proportional Controls	
ot for use with Offset Boom option 461025 bystick Activated with Electronic Proportional Controls	
bystick Activated with Electronic Proportional Controls	
otes:	
May be used stand alone or with any Case Excavator Auxiliary	
1	
	No Charge
·	\$1,146.00
· ·	
o Front Guard	No Charge
ont Guard - Wire Mesh Screen	\$1,326.00
ont Stone Guard (OPG L1)	\$1,973.00
ertical bars (two piece/upper and lower)	
ont Stone Guard (OPG L2)	\$2,324.00
ertical bars (one piece/full length)	
andal Guard	\$574.00
emovable steel panels for front windshield	
	No Charge
	\$380.00
ont rock guard (OPG 2) option 461024.	
	Hydraulics option. 2) For dealer installed auxiliary hydraulic kits contact: HydrauliCircuit Technology (HCT) (1-888-603-0080 or sales@hctkits.com or www.hctkits.com) GUARD (FOPS) To FOPS Top Cab Guard DPS Top Cab Guard DPS Top Cab Guard Tont Guard Tont Guard Tont Stone Guard (OPG L1) Tortical bars (two piece/upper and lower) Tont Stone Guard (OPG L2) Tortical bars (one piece/full length) Tondal Guard Tont Stone Guard Tont Stone Guard (OPG L2) Tortical bars (one piece/full length) Tont Stone Guard (OPG L2) Tortical bars (one piece/full length) Tont Stone Guard (OPG L2) Tortical bars (one piece/full length) Tont Stone Guard (OPG L2) Tortical bars (one piece/full length) Tont Stone Guard (OPG L2) Tortical bars (one piece/full length) Tont Stone Guard (OPG L2) Tortical bars (one piece/full length) Tortical bars (one piece/full length)

No Charge

\$108.00

481257

Refuel Pump



CX160D CRAWLER EXCAVATOR (STD LC) US PRICE LIST

(Ex Works Port of Entry)

BUCKETS	
SD_E6300 EXCAVATOR BUCKET(S)	
XE6300X No Bucket	No Charge
Buckets may be ordered using Order Codes listed in the	
Factory Supplied Attachments Section	
ADDITIONAL OPTIONS	
SD_E5206 TRACK CHAIN GUIDE	
461541 Single Track Chain Guide	No Charge
461143 Triple Track Chain Guide	\$1,123.00
SD_E6400 MEC/HYD QUICK COUPLER	
XE6400X No Quick Coupler	No Charge
781128 Hydraulic Quick Coupler Ready	\$2,079.00
Does not come with coupler. Must order coupler from Factory	
Supplied Attachments section	
SD_E9730 SAFETY VALVE	
XE9730X No Hose Burst Check Valve	No Charge
481064 Hose Burst Check Valve (HBCV)	\$7,913.00
Located on Boom and Arm Cylinder	
SD_E9739 FULL VIEW CAMERA	
XE9739X No max view monitor	No Charge
488055 Case Max View Monitor	\$1,700.00
SD_E9874 REFUEL PUMP	
XE9874X No Refuel Pump	No Charge

\$1,296.00



(Ex Works Port of Entry) Factory Supplied Attachments

Order Code	Description	Weight	Factory Data	List Price
CASE Machine Gui	dance			
90456016	OEM-Fit 2D Machine Guidance Sys Leica	26 LB		\$18,800.00
	- Option available to Precision-Certified Dealers only.			
	 Expect extended lead times when ordering this option. Contact your CASE representative for more information. Attachment calibration required upon delivery. Display will arrive in case located in cab, and will need to be mounted upon dealer arrival. 			
90456015	OEM-Fit 3D Machine Guidance Sys Leica	43 LB		\$64,090.00
	- Option available to Precision-Certified Dealers only.			
	 Expect extended lead times when ordering this option. Contact your CASE representative for more information. Attachment calibration required upon delivery. Display and GNSS antennas will arrive in case located in cab, and will need to be mounted upon dealer arrival. Radio Antenna required- Purchased separately through CNH Parts. 			
	- For 900MHz Radio/Antenna order: LG916750 - CCD21, Satel M3-TR9 Radio iCG80 and L827067 - CA26, Antenna, for CCD15 and 4G modem For 4xx MHz Antenna order: LG916751 - CCD22, Satel TR4+Radio iCG80 and Order 1 of the following: LG805281 CA12, Radio Antenna 406-440MHz or LG805282 CA13, Radio Antenna, 430-480MHz.			
Case Coupler				
47867960	Multi-Fit S Hyd.Pin Grabber Coupler Kit	793 LB		\$5,620.00
Case Coupler Buck		. 00 == 1		ψο,ο20.00
84404140	24" Heavy-Duty Coupler Bucket with 4 teeth (.51 cu. yd.)			\$4,495.00
84404141	30" Heavy-Duty Coupler Bucket wtih 4 teeth (.66 cu. yd.)			\$4,924.00
84404142	36" Heavy-Duty Coupler Bucket with 5 teeth (.81 cu. yd.)			\$5,193.00
84404143	42" Heavy-Duty Coupler Bucket with 5 teeth (.97 cu. yd.)			\$5,490.00
Case Pin-On Bucke	ets			
84404124	24" Heavy-Duty Pin-On Bucket with 4 teeth (.58 cu. yd.)			\$3,574.00
84404125	30" Heavy-Duty Pin-On Bucket with 4 teeth (.74 cu. yd.)			\$3,718.00

(Ex Works Port of Entry)

	(LX WOIKS I O	it of Endry	
84404126	36" Heavy-Duty Pin-On Bucket with 5 teeth (.91 cu. yd.)	1,425 LB	\$3,931.00
84404129	42" Heavy-Duty Pin-On Bucket with 5 teeth (1.08 cu. yd.)		\$4,163.00
84404131	24" HD Hi-Capacity Pin-On Bucket with 4 teeth (.65 cu. yd.)		\$3,522.00
84404132	30" HD Hi-Capacity Pin-On Bucket with 4 teeth (.84 cu. yd.)		\$3,772.00
84404133	36" HD Hi-Capacity Pin-On Bucket with 5 teeth (10.3 cu. yd.)		\$3,993.00
84404134	42" Heavy-Duty Pin-On Bucket wtih 5 teeth (1.22 cu. yd.)		\$4,392.00
84404136	48" Ditching Pin-On Bucket (.79 cu. yd.)		\$2,799.00
84404139	60" Ditching Pin-On Bucket (1.02 cu yd.)		\$3,176.00
Pirect Link Thumb 47609064	KIT, THUMB, HYD, 3-TINE,	840 LB	\$7,220.00
47609065	use with bucket only (3 tine) KIT, THUMB, HYD, 4-TINE,	860 LB	\$7,639.00
47609066	use with bucket only (4 tine) KIT, THUMB, HYD, 3-TINE, use with bucket and coupler (3 tine)	985 LB	\$7,504.00
47609067	KIT, THUMB, HYD, 4-TINE, use with bucket and coupler (4 tine)	1,005 LB	\$7,951.00
Progressive Link	Гһить		
47609102	KIT, THUMB, PROG LINK, 3- use with bucket only (3 tine)	1,180 LB	\$9,307.00
47609103	KIT, THUMB, PROG LINK, 4- use with bucket only (4 tine)	1,200 LB	\$9,725.00
47609104	KIT, THUMB, PROG LINK, 3-	1,325 LB	\$9,591.00
47609106	Progressive Link Thumb Kit with Coupler use with bucket and coupler (4 tine)	1,345 LB	\$10,037.00



(Ex Works Port of Entry) Standard Equipment

ENGINE: Isuzu AR-4HK1X Tier 4 Final Certified Selective Catalytic Reduction (SCR) Diesel Oxidation Catalyst (DOC) Cooled Exhaust Gas Recirculation (CEGR) 317 cubic in. displacement/3.0 Liter Turbocharged/air cooled intercooler Horsepower: Net: 160 (119.3 kW) @ 1800 RPM Electronic fuel injection High pressure common rail system Neutral safety start, Idle start Auto-engine warm up Glow-plug pre-heat Fuel Economy Assist System (FEA) Engine Protection Feature (EPF) Dual-stage fuel filtration Dual element air filter Remote oil filter Drain for fuel tank Remote engine oil drain 500-hour engine oil change interval 24-volt system Engine oil sample port Battery disconnect switch Emergency engine stop External Fuel and DEF gauges Fan housing Fuel cooler Fuel filter restriction indicator Fuel shut-off valve Radiator, oil cooler, intercooler protective screen FUEL ECONOMY SYSTEMS: Engine Idle / Fuel Economy System: Auto-idle

One-touch idle

Auto-idle shut-down

BEC- Boom Economy Control

AEC- Auto Economy Control

SWC-Swing Relief Control

SSC- Spool Stroke Control

HYDRAULICS: Auto power boost Auto swing priority Arm speed assistance (2 pump flow) Auxiliary flow control Auxiliary valve Boom speed assistance (2 pump flow) Bucket curl assist Control levers pre-wired for auxiliary hydraulics Electronically controlled hydraulic Holding valve (Boom and Arm) Fire wall Hydraulic filter restriction indicator Neutral pump de-stroke Oil cooler Power save Pump stand-by pressure Auto travel speed change Selectable work modes Free swing - switch activated Hydraulic oil sample port Control pattern selector Pre-set auxiliary pump settings Auxiliary valve 5,000-hour hydraulic oil change interval 1,000-hour hydraulic filter change interval SAHR brake UPPER STRUCTURE: ISO mirrors (3) Cab viscous-mounts (fluid) Upper mounted work light (70 watt) Swivel quard belly pan Center cover (over main CV) Fuel tank belly pan Handrail (RH access) ISO guard rails Lifting eyes for counterweight Lockable fuel cap, service doors and

tool box



(Ex Works Port of Entry) Standard Equipment

ATTACHMENTS: Boom- 18 ft. 8 in. (5.70 m) Arm-9 ft. 8 in. (2.94 m) Heavy-duty bucket linkage Boom mounted work light (70 watt) Auxiliary pipe brackets Centralized grease fittings Attachment cushion valve Arm and boom regeneration Bucket anti-clatter device Chrome pins Easy Maintenance System (EMS) bushings Teardrop pin retention keepers OPERATOR STATION: ROPS protection FOPS cab (Level 1) Pressurized cab Face vent Cab lights (2) Interior dome light One-touch lock front window One piece window (right) Safety glass windows Gate lock hydraulic activation Emergency exit and hammer Clear (polycarbonate) roof window w/ sunshade AC/heat/defrost w/ auto climate control LED Color monitor- 7 in (180 mm) 26 selectable languages for monitor On-board diagnostic system 10 programmable attachments settings on monitor - 5 single flow, 5 dual flow Seatbelt-3 in. (76 mm) Heated high-back cloth seat with air suspension and 650 tilt adjustment Sliding seat - 3.54 in. (90 mm) Adjustable armrests Tilting consoles- 4-position

Sliding cockpit - 3.15 in. (80 mm)

Low-effort joystick controls

```
OPERATOR STATION (continued):
  Controls pre-wired for auxiliary
 Straight travel
 AM/FM radio w/ antenna, 2 speakers
    and Bluetooth capabilities
 Aux-in port for personal electronics
 Radio mute switch (joystick)
 Rear-view & Side-view camera
 Anti-theft system (start code system)
 Rubber floormat
  12-volt electric outlet
  24-volt cigarette lighter
 Windshield wiper/washer
 Cup holder
  Storage compartments
  Warm/cool storage compartment
  Travel alarm with cancel switch
  Ignition keys
 One key start & lock-up
  Cab filter (external)
  Cab handrails
  Operator's manual
UNDERCARRIAGE:
 Long undercarriage
    31.5 in. (800 mm) steel shoes, triple
      semi-grouser
 Narrow
    23.6 in. (600 mm) steel shoes, triple
      semi-grouser
 Full overlap turntable bearing tub
  Single track chain guides
 Hydraulic track adjustment
 Sealed link chain
 Steps
  Carbody belly pan (swivel guard)
 X-pattern carbody
 Lashing points (tie downs)
```



(Ex Works Port of Entry) Standard Equipment

EXTRA FILTER KIT:

Engine oil filter

Filter wrench

Fuel filters

Grease gun

Green plug oil drain hose for engine oil drain

Hydraulic return filter

Pilot circuit hydraulic filter

CASE ProCare - Full Machine Protection
Factory Warranty (3-yr/3000-hr),
Planned Maintenance (3-yr/2000-hr)
and SiteWatch™ Telematics
CASE SiteWatch™ Telematics
Includes hardware and a 3-yr
advanced data subscription



(Ex Works Port of Entry) Models

COMMERCIAL MODEL	Weight	Factory Data	List Price
CX210D STD LC	48,900 LB		\$300,230.00
CX210D NRRW	48,100 LB		\$298,008.00
Includes the following Equipment 23.6" (600 mm) Steel Shoes (956001)	3) (\$867.00)		

(Ex Works Port of Entry)

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price

LIGHTS

SD_E5408 WORKING LIGHTS

	488134	Halogen Working Lights		No Charge
	488135	LED Working Lights		\$2,754.00
		8 LED lights:		
		2 LED light are mounted on the front (1 on boom, 1 on house)		
		2 LED lights are mounted on the rear		
		(above the rear view camera)		
		1 LED light mounted on each side (2)		
		2 LED lights mounted on the top of the cab		

BOOMS

SD_E5311 BOOM

	481858	Std Boom		No Charge
		18'8" (5.70 M) Standard Boom		
	781917	No Boom		(\$5,374.00)
		Less boom, hoist and arm cylinders and plumbing.		
		Boom-foot and cylinder pins are provided.		
		Not for use with CX210D NRRW		

ARMS

SD_E5320 ARM/DIPPERSTICK

	461501	7'10" (2.40 m) HD Arm		(\$548.00)
		For use with 18'8" Standard Boom (option 481858)		
		(Recommended for heavy-duty applications - example: hammer)		
	481268	9'8" (2.94 M) Arm		No Charge
		For use with 18'8" Standard Boom (option 481858)		
	XE5320X	No Arm/Dipperstick		(\$3,033.00)
		Less arm, bucket cylinder and linkage		



(Ex Works Port of Entry)

TRACK SHOES

SD_E5199 TRACK SHOES

OD_E3133 11	ACK GIOLO	
9560013	23.6" (600 mm) Steel Shoes	(\$867.00)
	Triple-Grouser Steel Shoes	
	For use with CX210D STD LC and CX210D NRRW	
9560003	27.6" (700mm) TG Steel Shoes	(\$351.00)
	Triple-Grouser Steel Shoes	
	For use with CX210D STD LC	
9560005	31.5" (800 mm) TG Steel Shoes	No Charge
	Triple-Grouser Steel Shoes	
	For use with CX210D STD LC	
9560007	35.4" (900 mm) Steel Shoes	\$1,456.00
	Triple-Grouser Steel Shoes	
	For use with CX210D STD LC commercial model only	
9560055	23.6" (600 mm) Rubber Pads	\$12,134.00
	Rubber pads molded to steel base on standard chain	
	For use with CX210D STD LC and CX210D NRRW	

LANGUAGE

SD_47083 OPERATOR'S MANUAL

	781981	English Literature		No Charge
	461540	French Canadian Literature		No Charge
Г	781980	Spanish Literature		No Charge

ADDITIONAL EQUIPMENT CXC

HYDRAULIC OPTIONS

S	D_E6410	AU	XILIARY HYDRAULICS
	VE044	01/	No. On Consell Declared to

XE6410X No Optional Hydraulics (\$11,374.00)



(Ex Works Port of Entry)

Not for use	with No Boom	
461869	MF w/ pressure setting - Prop	No Charge
	Multi-Function Auxiliary Hydraulics with Electronic Pressure	
	Control (EPC)	
	For use with multiple applications:	
	hammers/thumbs/grapples/crushers.	
	Includes in-cab Electronic Pressure Control feature	
	Pressure Control feature allows hydraulic pressure setting	
	from the cab monitor and maintaining pressure settings in	
	memory when multiple tools are used.	
	Joystick Activated with Electronic Proportional Controls	
	Provides single or dual pump, two-way flow,	
	Secondary Low-flow Auxiliary Hydraulics can be added	
	Includes in-cab electronically controlled pressure setting feature	
	Is switchable to single acting flow for hammer application.	
	Notes:	
	Not for use with other Auxiliary Hydraulics options, with the exception of Low Flow.	
	2) Heavy duty bucket linkage is standard equipment on	
	C/D series excavators.	
	3) For dealer installed auxiliary hydraulic kits contact:	
	HydrauliCircuit Technology (HCT)	
	(1-888-603-0080 or sales@hctkits.com or www.hctkits.com)	

SD_E6417 SECONDARY AUXILIARY HYDRAULICS

XE6417X	No Low Flow Circuit	No Charge
461863	Secondary Auxiliary Hydraulics	\$7,039.00
	Secondary Low Flow Auxiliary Hydraulics	
	Provides low-flow for rotation or tilt hydraulic attachments.	
	For use with Standard Boom option 481858	
	Joystick Activated with Electronic Proportional Controls	
	Notes:	
	May be used stand alone or with any Case Excavator Auxiliary Hydraulics option.	
	2) For dealer installed auxiliary hydraulic kits contact:	
	HydrauliCircuit Technology (HCT)	
	(1-888-603-0080 or sales@hctkits.com or www.hctkits.com)	



(Ex Works Port of Entry)

CAB OPTIONS	
SD_E5443 CAB GUARD (FOPS)	
XE5443X No FOPS Top Cab Guard	No Charge
481070 FOPS Top Cab Guard	\$1,146.00
401070 TOTO TOP Cab Guard	ψ1,140.00
SD_E5444 CAB GUARD (FRONT)	
XE5444X No Front Guard	No Charge
461142 Front Guard - Wire Mesh Screen	\$1,326.00
781986 Front Stone Guard (OPG L1)	\$1,973.00
vertical bars (two piece/upper and lower)	
461024 Front Stone Guard (OPG L2)	\$2,324.00
vertical bars (one piece/full length)	
461552 Vandal Guard	\$574.00
Removable steel panels for front windshield	
SD_E5449 RAIN DEFLECTOR	
XE5449X No Rain Deflector	No Charge
461555 Rain Deflector	\$380.00
Not for use with Front grill guard - 2 x 2 mesh option 461142,	
Front rock guard (OPG 1) option 781986, or	
Front rock guard (OPG 2) option 461024.	
CD FEATA CHANNEOD	
SD_E5451 SUN VISOR	No Charge
461554 Sun Visor	\$108.00
	•
BUCKETS	
SD_E6300 EXCAVATOR BUCKET(S)	
XE6300X No Bucket	No Charge
Buckets may be ordered using Order Codes listed in the	
Factory Supplied Attachments Section	
ADDITIONAL OPTIONS	
ADDITIONAL OF HONS	
SD_02005 ENGINE PRE-CLEANER	
X02005X No Pre-Cleaner	No Charge
488031 Pre-Cleaner Cyclone	\$470.00
	<u> </u>
SD_E5206 TRACK CHAIN GUIDE	
461541 Single Track Chain Guide	No Charge
461143 Triple Track Chain Guide	\$1,123.00
SD_E5407 COOLING PACKAGE	
XE5407X Standard Cooling Package	No Charge

SD_E9874 REFUEL PUMP

XE9874X No Refuel Pump

481257 Refuel Pump

CX210D CRAWLER EXCAVATOR (STD LC & NRRW) US PRICE LIST

	(Ex Works Port of Entry)	
481027	Tropical Cooling Package	\$504.00
	High ambient temperature cooling package	
	Includes hardware to support the cooling of the	
	main machine systems.	
	Must also order: Pre-Cleaner Cyclone option 488031	
	Note: Recommended for machines operating in high heat	
	conditions not to exceed 122°F (50°C)	
	Not for use with CX210D NRRW	
	EC/HYD QUICK COUPLER	
	No Quick Coupler	No Charge
781128	Hydraulic Quick Coupler Ready	\$2,188.00
	Does not come with coupler. Must order coupler from Factory	
	Supplied Attachments section	
SD_E9730 SA	FETY VALVE	
XE9730X	No Hose Burst Check Valve	No Charge
481064	Hose Burst Check Valve (HBCV)	\$7,913.00
	Located on Boom and Arm Cylinder	
SD_E9739 FL	JLL VIEW CAMERA	
XE9739X	No max view monitor	No Charge
488055	Case Max View Monitor	\$1,700.00
SD_E9742 RE	VERSIBLE FAN	
XE9742X	No Reversible Fan	No Charge
488121	Reversible Fan	\$8,709.00
	Variable pitch reversing fan features rotating blades, that provides	
	maximum airflow in either direction when engaged by operator.	

No Charge

\$1,296.00



(Ex Works Port of Entry)

Factory Supplied Attachments

Order Code	Description	Weight	Factory Data	List Price
CASE Machine G	Buidance			
90456016	OEM-Fit 2D Machine Guidance Sys Leica - Option available to Precision-Certified Dealers only. - Expect extended lead times when ordering this option. Contact your CASE representative for more information. - Attachment calibration required upon delivery.	26 LB		\$18,800.00
	 Display will arrive in case located in cab, and will need to be mounted upon dealer arrival. 			
90456015	OEM-Fit 3D Machine Guidance Sys Leica Option available to Precision-Certified Dealers only. Expect extended lead times when ordering this option. Contact your CASE representative for more information. Attachment calibration required upon delivery. Display and GNSS antennas will arrive in case located in cab, and will need to be mounted upon dealer arrival. Radio Antenna required- Purchased separately through CNH Parts. For 900MHz Radio/Antenna order: LG916750 - CCD21, Satel M3-TR9 Radio iCG80 and L827067 - CA26, Antenna, for CCD15 and 4G modem. For 4xx MHz Antenna order: LG916751 - CCD22, Satel TR4+Radio iCG80 and Order 1 of the following: LG805281 CA12, Radio Antenna 406-440MHz or LG805282 CA13, Radio Antenna, 430-480MHz.	43 LB		\$64,090.00
Case Coupler Bu 84404187	24" Heavy-Duty Coupler Bucket			\$5,418.00
84404188	with 4 teeth (.63 cu. yd.) 30" Heavy-Duty Coupler Bucket with 4 teeth (.82 cu. yd.)			\$5,958.00
84404189	36" Heavy-Duty Coupler Bucket with 5 teeth (1.02 cu. yd.)			\$6,556.00
84404190	42" Heavy-Duty Coupler Bucket with 5 teeth (1.20 cu. yd.)			\$7,213.00
84404191	48" Heavy-Duty Coupler Bucket with 6 teeth (1.48 cu. yd.)			\$7,622.00
Case Pin On Buo	kets			
84404166	24" Heavy-Duty Pin-On Bucket with 4 teeth (.50 cu. yd.)			\$3,997.00
84404167	30" Heavy-Duty Pin-On Bucket with 4 teeth (.84 cu. yd.)			\$4,475.00
84404168	36" Heavy-Duty Pin-On Bucket with 5 teeth (1.03 cu. yd.)			\$4,884.00

(Ex Works Port of Entry)

	(EX WOLKS F	ort or Entry)	
84404169	42" Heavy-Duty Pin-On Bucket with 5 teeth (1.22 cu. yd.)	2,050 LB	\$5,265.00
84404170	24" HD Hi-Capacity Pin-On Bucket with 4 teeth (.79 cu. yd.)		\$4,322.00
84404175	30" HD Hi-Capacity Pin-On Bucket with 4 teeth (1.02 cu. yd.)		\$4,775.00
84404178	36" HD Hi-Capacity Pin-On Bucket with 5 teeth (1.25 cu. yd.)		\$5,278.00
84404179	42" HD Hi-Capacity Pin-On Bucket with 5 teeth (1.48 cu. yd.)		\$5,542.00
84404180	48" HD Hi-Capacity Pin-On Bucket with 6 teeth (1.72 cu. yd.)	2,650 LB	\$6,056.00
84404181	24" Severe-Duty Pin-On Bucket with 4 teeth (.65 cu. yd.)		\$5,404.00
84404182	30" Severe-Duty Pin-On Bucket with 4 teeth (.84 cu. yd.)		\$6,054.00
84404183	36" Severe-Duty Pin-On Bucket with 5 teeth (1.03 cu. yd.)		\$6,780.00
84404184	42" Severe-Duty Pin-On Bucket with 5 teeth (1.22 cu. yd.)		\$7,015.00
84404185	60" Ditching Pin-On Bucket (1.02 cu yd.)		\$3,620.00
84404186	72" Ditching Pin-On Bucket(1.22 cu. yd.)		\$3,921.00
84405214	48" Heavy-Duty Pin-On Bucket		\$5,360.00
oupler 47855901	KIT, COUPLER, MULTI-FIT S	683 LB	\$5,882.00
irect Link Thur		000 22	ψο,σο2.σο
47609071	KIT, THUMB, HYD, 3-TINE, use with bucket only (3 tine)	1,155 LB	\$8,604.00
47609072	KIT, THUMB, HYD, 4-TINE, use with bucket only (4 tine)	1,190 LB	\$9,089.00
47609073	KIT, THUMB, HYD, 3-TINE, use with bucket and coupler (3 tine)	1,300 LB	\$8,972.00
47609074		4.00=1.5	
	KIT, THUMB, HYD, 4-TINE, use with bucket and coupler (4 tine)	1,325 LB	\$9,573.00
	use with bucket and coupler (4 tine)	1,325 LB	\$9,573.00
rogressive Lini 47609109	use with bucket and coupler (4 tine) k Thumb KIT, THUMB, PROG LINK, 3-	1,325 LB	\$9,573.00
rogressive Lini	k Thumb KIT, THUMB, PROG LINK, 3- use with bucket only (3 tine) KIT, THUMB, PROG LINK, 4-		
rogressive Lini 47609109	k Thumb KIT, THUMB, PROG LINK, 3- use with bucket only (3 tine)	1,680 LB	\$11,176.00

(This page intentionally left blank)



(Ex Works Port of Entry) Standard Equipment

ENGINE: Isuzu AR-4HK1X Tier 4 Final Certified Selective Catalytic Reduction (SCR) Diesel Oxidation Catalyst (DOC) Cooled Exhaust Gas Recirculation (CEGR) Turbocharged/air cooled intercooler 317 cubic in displacement/5.2 Liter Horsepower: Net 160 (119.3 kW) @ 1800 RPM Electronic fuel injection High pressure common rail system Neutral safety start, Idle start Auto-engine warm up Glow-plug pre-heat Fuel Economy Assist System (FEA) Engine Protection Feature (EPF) Dual-stage fuel filtration Dual element air filter Remote oil filter Drain for fuel tank Remote engine oil drain 500-hour engine oil change interval 24-volt system Engine oil sample port Battery disconnect switch Emergency engine stop External Fuel and DEF gauges Fan housing Fuel cooler Fuel filter restriction indicator

FUEL ECONOMY SYSTEMS:

Fuel shut-off valve

protective screen

SSC- Spool Stroke Control

Engine Idle / Fuel Economy System:
Auto-idle
One-touch idle
Auto-idle shut-down
BEC- Boom Economy Control
AEC- Auto Economy Control
SWC- Swing Relief Control

Radiator, oil cooler, intercooler -

HYDRAULICS:

Auto power boost Auto swing priority Arm speed assistance (2 pump flow) Auxiliary flow control Auxiliary valve Boom speed assistance (2 pump flow) Bucket curl assist Control levers pre-wired for auxiliary hydraulics Electronically controlled hydraulic Holding valve (Boom and Arm) Fire wall Hydraulic filter restriction indicator Neutral pump de-stroke Oil cooler Power save Pump stand-by pressure Auto travel speed change Selectable work modes Free swing - switch activated Hydraulic oil sample port Control pattern selector Pre-set auxiliary pump settings Auxiliary valve 5,000-hour hydraulic oil change interval 1,000-hour hydraulic filter change interval SAHR brake

UPPER STRUCTURE:

ISO mirrors (3)
Cab viscous-mounts (fluid)
Upper mounted work light (70 watt)
Swivel guard belly pan
Center cover (over main CV)
Fuel tank belly pan
Handrail (RH access)
ISO guard rails
Lifting eyes for counterweight
Lockable fuel cap, service doors and tool box



(Ex Works Port of Entry) Standard Equipment

ATTACHMENTS: Boom- 28 ft. 7 in. (8.70 m) Arm-21 ft. (6.40 m) Heavy-duty bucket linkage Boom mounted work light (70 watt) Auxiliary pipe brackets Centralized grease fittings Attachment cushion valve Arm and boom regeneration Bucket anti-clatter device Chrome pins Easy Maintenance System (EMS) bushings Teardrop pin retention keepers OPERATOR STATION: ROPS protection FOPS cab (Level 1) Pressurized cab Face vent Cab lights (2) Interior dome light One-touch lock front window One piece window (right) Safety glass windows Gate lock hydraulic activation Emergency exit and hammer Clear (polycarbonate) roof window w/ sunshade AC/heat/defrost w/ auto climate control LED Color monitor- 7 in (180 mm) 26 selectable languages for monitor On-board diagnostic system 10 programmable attachments settings on monitor - 5 single flow, 5 dual Seatbelt-3 in. (76 mm) Heated high-back cloth seat with air suspension and 650 tilt adjustment Sliding seat - 3.54 in. (90 mm) Adjustable armrests

Tilting consoles- 4-position

Low-effort joystick controls

Sliding cockpit - 3.15 in. (80 mm)

```
OPERATOR STATION (continued):
  Controls pre-wired for auxiliary
  Straight travel
  AM/FM radio w/ antenna, 2 speakers
    and Bluetooth capabilities
  Aux-in port for personal electronics
 Radio mute switch (joystick)
 Rear-view & Side-view camera
  Anti-theft system (start code system)
 Rubber floormat
  12-volt electric outlet
  24-volt cigarette lighter
  Windshield wiper/washer
  Cup holder
  Storage compartments
  Warm/cool storage compartment
  Travel alarm with cancel switch
  Ignition keys
  One key start & lock-up
  Cab filter (external)
  Cab handrails
  Operator's manual
UNDERCARRIAGE:
 Long undercarriage
  31.5 in. (800 mm) steel shoes, triple
    semi-grouser
 Full overlap turntable bearing tub
  Single track chain guides
 Hydraulic track adjustment
  Sealed link chain
  Steps
  Carbody belly pan (swivel guard)
 X-pattern carbody
 Lashing points (tie downs)
EXTRA FILTER KIT:
  Engine oil filter
 Filter wrench
 Fuel filters
  Grease gun
 Green plug oil drain hose for
    engine oil drain
 Hydraulic return filter
  Pilot circuit hydraulic filter
```



(Ex Works Port of Entry) Standard Equipment

CASE ProCare - Full Machine Protection Factory Warranty (3-yr/3000-hr), Planned Maintenance (3-yr/2000-hr) and SiteWatch™ Telematics
CASE SiteWatch™ Telematics
Includes hardware and a 3-yr advanced data subscription



(Ex Works Port of Entry) Models

COMMERCIAL MODEL	Weight	Factory Data	List Price
CX210D LR	49,090 LB		\$330,645.00

(Ex Works Port of Entry) Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
LIGHTS				
LIGITIO				
	ORKING LIGHTS	_		
488134	Halogen Working Lights	+		No Charge
488135	LED Working Lights			\$2,754.00
	8 LED lights:			
	2 LED light are mounted on the front (1 on boom, 1 on house)			
	2 LED lights are mounted on the rear			
	(above the rear view camera)			
	1 LED light mounted on each side (2)			
	2 LED lights mounted on the top of the cab			
DOOMS				
BOOMS				
SD_E5311 BC	OOM			
461029	Standard Long Reach Boom			No Charge
1 1 401023	28'7" (8.70 M) Long Reach Boom			140 Onlarge
	201 (Cito III) Long Rough Boom	1		
ARMS				
ARINO				
SD F5320 AF	'M/DIPPERSTICK			
	RM/DIPPERSTICK	1	1	No Charge
SD_E5320 AF	RM/DIPPERSTICK 21'0" (6.40 M) Arm			No Charge
481248				No Charge
				No Charge
481248				No Charge
TRACK SHOES	21'0" (6.40 M) Arm			No Charge
481248	21'0" (6.40 M) Arm ACK SHOES			
TRACK SHOES SD_E5199 TR	21'0" (6.40 M) Arm			No Charge No Charge
TRACK SHOES SD_E5199 TR	21'0" (6.40 M) Arm ACK SHOES 31.5" (800 mm) TG Steel Shoes			
### 481248 TRACK SHOES SD_E5199 TR 95600005	21'0" (6.40 M) Arm ACK SHOES 31.5" (800 mm) TG Steel Shoes Triple-Grouser Steel Shoes			No Charge
### 481248 TRACK SHOES SD_E5199 TR 9560005	21'0" (6.40 M) Arm ACK SHOES 31.5" (800 mm) TG Steel Shoes Triple-Grouser Steel Shoes 35.4" (900 mm) Steel Shoes			No Charge
### 481248 TRACK SHOES SD_E5199 TR 95600005	21'0" (6.40 M) Arm ACK SHOES 31.5" (800 mm) TG Steel Shoes Triple-Grouser Steel Shoes 35.4" (900 mm) Steel Shoes			No Charge
### ### ##############################	21'0" (6.40 M) Arm ACK SHOES 31.5" (800 mm) TG Steel Shoes Triple-Grouser Steel Shoes 35.4" (900 mm) Steel Shoes			No Charge
### ### ##############################	21'0" (6.40 M) Arm ACK SHOES 31.5" (800 mm) TG Steel Shoes Triple-Grouser Steel Shoes 35.4" (900 mm) Steel Shoes			No Charge
### ### ##############################	21'0" (6.40 M) Arm ACK SHOES 31.5" (800 mm) TG Steel Shoes Triple-Grouser Steel Shoes 35.4" (900 mm) Steel Shoes			No Charge
### ### ##############################	21'0" (6.40 M) Arm RACK SHOES 31.5" (800 mm) TG Steel Shoes Triple-Grouser Steel Shoes 35.4" (900 mm) Steel Shoes Triple-Grouser Steel Shoes			No Charge

XE5451X No Sun Visor

Sun Visor

461554

CX210D LONG REACH CRAWLER EXCAVATOR (LR) US PRICE LIST

	(Ex Works Port of Entry)					
781980	Spanish Literature	No Charge				
ADDITIONAL EQ	UIPMENT CXC					
HYDRAULIC OPT	IONS					
	ECONDARY AUXILIARY HYDRAULICS					
XE6417X		No Charge				
461863	Secondary Auxiliary Hydraulics	\$7,874.00				
	Secondary Low Flow Auxiliary Hydraulics					
	Provides low-flow for rotation or tilt hydraulic attachments.					
	Joystick Activated with Electronic Proportional Controls					
	Notes:					
	1) May be used stand alone or with any Case Excavator Auxiliary					
	Hydraulics option.					
	2) For dealer installed auxiliary hydraulic kits contact:					
	HydrauliCircuit Technology (HCT)					
	(1-888-603-0080 or sales@hctkits.com or www.hctkits.com)					
 	AB GUARD (FOPS)					
	No FOPS Top Cab Guard	No Charge				
481070	FOPS Top Cab Guard	\$1,146.00				
CD 55444 C	AR CHARR (FRONT)					
	AB GUARD (FRONT) No Front Guard	No Charge				
461142	Front Guard - Wire Mesh Screen	No Charge \$1,326.00				
781986	Front Stone Guard (OPG L1)	\$1,973.00				
701300	vertical bars (two piece/upper and lower)	Ψ1,373.00				
461024						
	L Front Stone Guard (OPG L2)	\$2.324.00				
401024	Front Stone Guard (OPG L2) vertical bars (one piece/full length)	\$2,324.00				
	vertical bars (one piece/full length) Vandal Guard					
461552	vertical bars (one piece/full length) Vandal Guard					
	vertical bars (one piece/full length)					
461552	Vertical bars (one piece/full length) Vandal Guard Removable steel panels for front windshield					
461552	vertical bars (one piece/full length) Vandal Guard Removable steel panels for front windshield AIN DEFLECTOR	\$574.00				
461552 SD_E5449 R	vertical bars (one piece/full length) Vandal Guard Removable steel panels for front windshield AIN DEFLECTOR	\$574.00 No Charge				
461552 SD_E5449 R XE5449X	vertical bars (one piece/full length) Vandal Guard Removable steel panels for front windshield AIN DEFLECTOR No Rain Deflector	\$574.00 No Charge				
461552 SD_E5449 R XE5449X	vertical bars (one piece/full length) Vandal Guard Removable steel panels for front windshield AIN DEFLECTOR No Rain Deflector Rain Deflector	\$2,324.00 \$574.00 No Charge \$380.00				
461552 SD_E5449 R XE5449X	vertical bars (one piece/full length) Vandal Guard Removable steel panels for front windshield AIN DEFLECTOR No Rain Deflector Rain Deflector Not for use with Front grill guard - 2 x 2 mesh option 461142,	\$574.00 No Charge				

No Charge \$108.00



(Ex Works Port of Entry)

BUCKETS	
BOOKETO	
SD_E6300 EXCAVATOR BUCKET(S)	
XE6300X No Bucket	No Charge
Buckets may be ordered using Order Codes listed in the	
Factory Supplied Attachments section	
ADDITIONAL OPTIONS	
SD_02005 ENGINE PRE-CLEANER	
X02005X No Pre-Cleaner	No Charge
488031 Pre-Cleaner Cyclone	\$470.00
SD_E5206 TRACK CHAIN GUIDE	
461541 Single Track Chain Guide	No Charge
461143 Triple Track Chain Guide	\$1,123.00
SD_E5407 COOLING PACKAGE	No Observe
XE5407X Standard Cooling Package	No Charge
481027 Tropical Cooling Package	\$504.00
High ambient temperature cooling package	
Includes Pre-Cleaner Cyclone option 488031	
Note: Recommended for machines operating in high heat	
conditions not to exceed 122°F (50°C)	
SD E6400 MEC/HYD QUICK COUPLER	
XE6400X No Quick Coupler	No Charge
781128 Hydraulic Quick Coupler Ready	\$2,187.00
Does not come with coupler. Must order coupler from Fac	
Supplied Attachments section	,
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	<u> </u>
SD_E9730 SAFETY VALVE	
XE9730X No Hose Burst Check Valve	No Charge
481064 Hose Burst Check Valve (HBCV)	\$7,913.00
Located on Boom and Arm Cylinder	
SD_E9739 FULL VIEW CAMERA	
XE9739X No max view monitor	No Charge
488055 Case Max View Monitor	\$1,700.00
SD_E9874 REFUEL PUMP	
XE9874X No Refuel Pump	No Charge
481257 Refuel Pump	\$1,296.00



(Ex Works Port of Entry)

Factory Supplied Attachments

	Order Code	Description	Weight	Factory Data	List Price
Са	se Pin On Buckets	6			
	84404113	48" Ditching Pin-On Bucket (.79 cu. yd.)			\$2,992.00
	84404115	60" Ditching Pin-On Bucket (1.02 cu yd.)			\$3,394.00
Diı	47609058	Hydraulic Main Pin Direct Link Thumb use with bucket only (2 tine)	830 LB		\$6,569.00
	47609059	KIT, THUMB, HYD, 4-TINE, use with bucket only (3 tine)	860 LB		\$6,953.00
	47609060	KIT, THUMB, HYD, 3-TINE, use with bucket and coupler (2 tine)	870 LB		\$6,813.00
	47609061	KIT, THUMB, HYD, 4-TINE,	910 LB		\$7,293.00

ENGINE:



OPERATOR ENVIRONMENT:

CX245D LC AND CX245D LC DZ US PRICE LIST

(Ex Works Port of Entry) Standard Equipment

```
Isuzu AM-4HK1X
                                                      ROPS protection
                                                      FOPS cab top guard - Level 1
 Tier4 Final Certified
 Selective Catalytic Reduction - SCR
                                                      Pressurized cab
 Diesel Oxidation Catalyst - DOC
                                                      Face vent
 Cooled Exhaust Gas Recirculation -
                                                      Cab lights - 2
                                                      Interior dome light
  317 cubic in. displacement/5.2 Liter
                                                      One-touch lock front window
 Turbocharged/air cooled intercooler
                                                      One piece window - right
 Horsepower:
                                                      Safety glass windows
   Net: 160 (119.3 kW) @ 1800 RPM
                                                      Gate lock hydraulic activation
 Electronic fuel injection
                                                      Emergency exit and hammer
 High pressure common rail system
                                                      Clear polycarbonate roof window with
 Auto engine warm-up
                                                        sunshade
                                                      AC/heat/defrost with auto climate
 FEA (Fuel Economy Assist System)
 Engine Idle/Fuel Economy System:
                                                        control
   Auto Idle
                                                      LED Color monitor - 7 in (180 mm)
   One-touch Idle
                                                      26 selectable languages for monitor
   Idle Shut-down
                                                      On-board diagnostic system
 Fuel Capacity:
                                                      10 programmable attachments settings
    85 gallons (320 L)
                                                        on monitor - 5 single flow, 5 dual
 AEC (auto economy control)
                                                        flow
                                                      Seat belt - 3 in (76 mm)
 BEC (boom economy control)
                                                      Heated high-back cloth seat with air
ELECTRICAL:
                                                        suspension and 65° tilt adjustment
                                                      Sliding seat - 3.54 in (90 mm)
  24-volt system
  Two batteries (12 volt/92 Ah)
                                                      Adjustable armrests
                                                      Tilting consoles - 4-position
  50 Amp Alternator
                                                      Sliding cockpit - 3.15 in (80 mm)
 Worklights (2 x 70 watt)
   Boom mounted (1)
                                                      Low-effort joystick controls
    Upper mounted (1)
                                                      Controls pre-wired for auxiliary
                                                      Single pedal travel
HYDRAULICS:
                                                      AM/FM radio with antenna, 2 speakers
  Open-center system design
                                                        and Bluetooth capabilities
  Optional auxiliary hydraulics
                                                      Aux-in port for personal electronics
                                                      Radio mute switch - joystick
  Selectable work modes (3)
 Auto power boost
                                                      Rear-view camera
 Auto swing priority
                                                      Side-view camara
 SWC (swing relief control)
                                                      Anti-theft system - start code system
 SSC (spool stroke control)
                                                      Rubber floormat
  5000 hour hydraulic oil change interval
                                                      12 Volt electric outlet
  1000 hour hyd. filter change interval
                                                      24 Volt cigarette lighter
  Control pattern change selector
                                                      Windshield wiper/washer
 Free Swing - switch activated
                                                      Cup holder
```

Storage compartments



CX245D LC AND CX245D LC DZ US PRICE LIST

(Ex Works Port of Entry) Standard Equipment

Warm/cool storage compartment
Travel alarm with cancel switch
Ignition keys
One key start & lock-up
Cab filter - external
Cab handrails
Additional handrails (right)
Operator's manual

UNDERCARRIAGE:

X-pattern carbody
Undercarriage:

STD LC: 14'8" (4.47 M) length

Track Gauge:

STD: 7'10" (2.39 M) gauge

Shoe:

STD: 31.5" (800 mm) Rubber Shoe

7.5" pitch

49 shoes per side Carrier rollers (2 per side) Track rollers (8 per side)

Grease lubricated and strutted track

chains

Hydraulic track adjustment Single track chain guides SAHR disc parking break Tapered upper track frame DOZER BLADE:

Dozer blade width: 9'1" (2800 mm)
Dozer blade height: 24" (610 mm)

ATTACHMENTS:

Standard LC Version:
Boom: 18'8" (5.70 M)
Arm: 9'8" (2.94 M)
Heavy-duty bucket linkage
Auxiliary pipe brackets
Attachment cushion valve
Arm and boom regeneration
Arm and boom holding valves

Centralized grease bank

CASE ProCare - Full Machine Protection Factory Warranty (3-yr/3000-hr),
Planned Maintenance (3-yr/2000-hr)

and SiteWatch™ Telematics
CASE SiteWatch™ Telematics
Includes hardware and a 3-yr
advanced data subscription



CX245D LC AND CX245D LC DZ US PRICE LIST

(Ex Works Port of Entry) Models

COMMERCIAL MODEL	Weight	Factory Data	List Price
CX245D MSR LC	56,900 LB		\$320,894.00
CX245D MSR LC W/DOZER	60,400 LB		\$367,377.00

CX245D LC AND CX245D LC DZ US PRICE LIST

(Ex Works Port of Entry)

Factory Supplied Options

C	rder Code	Description	Weight	Factory Data	List Price
LIG	HTS				
	OD 55400 M/	ODIVINO LIQUITO			
		ORKING LIGHTS		1	No Chara
\vdash	488134	Halogen Working Lights			No Charge
	488135	LED Working Lights			\$2,754.00
		8 LED lights:			
		2 LED light are mounted on the front (1 on boom, 1 on house)			
		2 LED lights are mounted on the rear			
		(above the rear view camera)			
		1 LED light mounted on each side (2)			
		2 LED lights mounted on the top of the cab			
BO	OMS				
	SD_E5311 BC	DOM			
	481858	Std Boom			No Charge
		18'8" (5.70 M) Standard Boom			
		For use with CX235C MSR LC and CX235C MSR w/dozer			
		commercial models.			
	781917	No Boom			(\$6,057.00)
		Less boom, hoist and arm cylinders and plumbing.			,, ,
		Boom-foot and cylinder pins are provided.			

ARMS

SD_E5320 ARM/DIPPERSTICK

	481268	9'8" (2.94 M) Arm		No Charge
L		For use wtih 18'8" Standard Boom (option 481858)		
	461501	7'10" (2.40 m) HD Arm		(\$273.00)
		For use with 18'8" Standard Boom (option 481858)		
		(Recommended for heavy-duty applications - example: hammer)		
	XE5320X	No Arm/Dipperstick		(\$3,142.00)
		Less arm, bucket cylinder and linkage		

if MODEL is CX245D

CX245D LC AND CX245D LC DZ US PRICE LIST

(Ex Works Port of Entry)

TRA	CK SHOES				
	CD F5400 TD	MCK CHOEC			
	SD_E5199 TR 9560007	35.4" (900 mm) Steel Shoes			\$1,456.00
	9300007	Triple-Grouser Steel Shoes			\$1,430.00
		Not for use with the CX245D MSR with Dozer Blade			
	0560013				(\$4.547.00\
	9560013 9560039				(\$1,547.00) (\$178.00)
		· · · · ·			No Charge
	9560046	,			
	9560055	23.6" (600 mm) Rubber Pads			\$12,118.00
		Steel Chain with individual rubber tracks (steel base			
\Box		coated with rubber)			
LAN	IGUAGE				
	SD_47083 OF	ERATOR'S MANUAL			
	781981	English Literature			No Charge
	461540	French Canadian Literature			No Charge
	781980	Spanish Literature			No Charge
BUC	KETS				
	-				
	SD F6300 FX	CAVATOR BUCKET(S)			
		No Bucket			No Charge
	7.200007.		.		1.0090
ΔDΓ	ITIONAL FOL	JIPMENT CXC			
ADL	MIONAL EQ	THE INTO ONC			
PI	I IMBING AND A	CTUATION FOR AUXILIARY HYDRAULICS			
_ ' _	OMBINO AND A	OTOATION FOR ADVILIANT ITTERACTION			
	SD E6423 CC	ONTROL PATTERN SELECTION			
	461558	Control Pattern Selection			No Charge
	401000	Control i attern Selector valve		1	I No Charge
⊔∨	DRAULIC OPTI	ONS			
<u> </u>	DRAULIC OPTI	OINO			
	SD E6440 AL				
		IXILIARY HYDRAULICS			
$oldsymbol{oldsymbol{\sqcup}}$	XE6410X	No Optional Hydraulics			

(\$11,471.00)



CX245D LC AND CX245D LC DZ US PRICE LIST

(Ex Works Port of Entry)

461869	MF w/ pressure setting - Prop		No Charge
	Multi-Function Auxiliary Hydraulics with Electronic Pressure		
	Control (EPC)		
	For use with multiple applications:		
	hammers/thumbs/grapples/crushers.		
	Includes in-cab Electronic Pressure Control feature		
	Brassius Control footuus allama hudusulia massaus oottina		
	Pressure Control feature allows hydraulic pressure setting		
	from the cab monitor and maintaining pressure settings in		
	memory when multiple tools are used.		
	Joystick Activated with Electronic Proportional Controls		
	Provides single or dual pump, two-way flow,		
	Secondary Low-flow Auxiliary Hydraulics can be added		
	Includes in-cab electronically controlled pressure setting feature		
	Is switchable to single acting flow for hammer application.		
	Notes:		
	1) Not for use with other Auxiliary Hydraulics options, with the		
	exception of Low Flow.		
	Heavy duty bucket linkage is standard equipment on		
	C/D series excavators.		
	3) For dealer installed auxiliary hydraulic kits contact:		
	HydrauliCircuit Technology (HCT)		
	(1-888-603-0080 or sales@hctkits.com or www.hctkits.com)		
 1	(1-000-000-000 of sales@fictalis.com of www.fictalis.com)		

SD_E6417 SECONDARY AUXILIARY HYDRAULICS

XE6417X	No Low Flow Circuit		No Charge
461863	Secondary Auxiliary Hydraulics		\$7,105.00
	Secondary Low Flow Auxiliary Hydraulics		
	Provides low-flow for rotation or tilt hydraulic attachments.		
	For use with Standard Boom option 481858		
	Not for use with Offset Boom option 461025		
	Joystick Activated with Electronic Proportional Controls		
	Notes:		
	1) May be used stand alone or with any Case Excavator Auxiliary		
	Hydraulics option.		
	2) For dealer installed auxiliary hydraulic kits contact:		
	HydrauliCircuit Technology (HCT)		
	(1-888-603-0080 or sales@hctkits.com or www.hctkits.com)		

Case Max View Monitor



CX245D LC AND CX245D LC DZ US PRICE LIST

(Ex Works Port of Entry)

CAB OPTIONS		
OAD OF HONO		
SD E5443	CAB GUARD (FOPS)	
	3X No FOPS Top Cab Guard	No Charge
481070	·	\$1,146.00
		, , , , , , , , , , , , , , , , , , , ,
SD_E5444	CAB GUARD (FRONT)	
	4X No Front Guard	No Charge
461142	2 Front Guard - Wire Mesh Screen	\$1,326.00
781986	Front Stone Guard (OPG L1)	\$1,973.00
	vertical bars (two piece/upper and lower)	
461024	Front Stone Guard (OPG L2)	\$2,324.00
	vertical bars (one piece/full length)	
461552	2 Vandal Guard	\$574.00
	Removable steel panels for front windshield	
		•
SD_E5449	RAIN DEFLECTOR	
XE544	9X No Rain Deflector	No Charge
46155	Rain Deflector	\$380.00
	Not for use with Front grill guard - 2 x 2 mesh option 461142,	
	Front rock guard (OPG 1) option 781986, or	
	Front rock guard (OPG 2) option 461024.	
-		•
SD_E5451	SUN VISOR	
XE545	1X No Sun Visor	No Charge
461554	4 Sun Visor	\$108.00
ADDITIONAL O	PTIONS	
SD_E5206	TRACK CHAIN GUIDE	
46154°	1 Single Track Chain Guide	No Charge
461143	3 Triple Track Chain Guide	\$2,115.00
SD_E6400	MEC/HYD QUICK COUPLER	
XE640	0X No Quick Coupler	No Charge
781128	B Hydraulic Quick Coupler Ready	\$2,304.00
SD_E9730	SAFETY VALVE	,
XE973	0X No Hose Burst Check Valve	No Charge
	Located on Boom and Arm Cylinder	
481064	Hose Burst Check Valve (HBCV)	\$8,667.00
	(BOOM/ARM) WARNING DEVICE	
SD_E9739	FULL VIEW CAMERA	
XE973	9X No max view monitor	No Charge
		7

\$1,700.00



CX245D LC AND CX245D LC DZ US PRICE LIST

(Ex Works Port of Entry)

Factory Supplied Attachments

Order Code	Description	Weight	Factory Data	List Price
CASE Machine G	uidance			
90456016	OEM-Fit 2D Machine Guidance Sys Leica	26 LB		\$18,800.00
	- Option available to Precision-Certified Dealers only.			
	 Expect extended lead times when ordering this option. Contact your CASE representative for more information. Attachment calibration required upon delivery. 			
	 Display will arrive in case located in cab, and will need to be mounted upon dealer arrival. 			
90456015	OEM-Fit 3D Machine Guidance Sys Leica	43 LB		\$64,090.00
	- Option available to Precision-Certified Dealers only.			
	 Expect extended lead times when ordering this option. Contact your CASE representative for more information. Attachment calibration required upon delivery. Display and GNSS antennas will arrive in case located in cab, and will need to be mounted upon dealer arrival. Radio Antenna required- Purchased separately through CNH Parts. 			
	- For 900MHz Radio/Antenna order: LG916750 - CCD21, Satel M3-TR9 Radio iCG80 and L827067 - CA26, Antenna, for CCD15 and 4G modem For 4xx MHz Antenna order: LG916751 - CCD22, Satel TR4+Radio iCG80 and Order 1 of the following: LG805281 CA12, Radio Antenna 406-440MHz or LG805282 CA13, Radio Antenna, 430-480MHz.			
Case Coupler Bud	skate			
84404187	24" Heavy-Duty Coupler Bucket with 4 teeth (.63 cu. yd.)			\$5,418.00
84404188	30" Heavy-Duty Coupler Bucket with 4 teeth (.82 cu. yd.)			\$5,958.00
84404189	36" Heavy-Duty Coupler Bucket with 5 teeth (1.02 cu. yd.)			\$6,556.00
84404190	42" Heavy-Duty Coupler Bucket with 5 teeth (1.20 cu. yd.)			\$7,213.00
84404191	48" Heavy-Duty Coupler Bucket with 6 teeth (1.48 cu. yd.)			\$7,622.00
Casa Bin On Bers				
84404166	24" Heavy-Duty Pin-On Bucket	I		\$3,997.00
84404167	with 4 teeth (.50 cu. yd.) 30" Heavy-Duty Pin-On Bucket			\$4,475.00
84404168	with 4 teeth (.84 cu. yd.) 36" Heavy-Duty Pin-On Bucket with 5 teeth (1.03 cu. yd.)			\$4,884.00

CX245D LC AND CX245D LC DZ US PRICE LIST

(Ex Works Port of Entry)

42" Heavy-Duty Pin-On Bucket	2,050 LB	\$5,265.00
24" HD Hi-Capacity Pin-On Bucket		\$4,322.00
30" HD Hi-Capacity Pin-On Bucket with 4 teeth (1.02 cu. yd.)		\$4,775.00
42" HD Hi-Capacity Pin-On Bucket with 5 teeth (1.48 cu. yd.)		\$5,542.00
48" HD Hi-Capacity Pin-On Bucket with 6 teeth (1.72 cu. yd.)	2,650 LB	\$6,056.00
24" Severe-Duty Pin-On Bucket with 4 teeth (.65 cu. yd.)		\$5,404.00
30" Severe-Duty Pin-On Bucket with 4 teeth (.84 cu. yd.)		\$6,054.00
36" Severe-Duty Pin-On Bucket with 5 teeth (1.03 cu. yd.)		\$6,780.00
42" Severe-Duty Pin-On Bucket with 5 teeth (1.22 cu. yd.)		\$7,015.00
60" Ditching Pin-On Bucket (1.02 cu yd.)		\$3,620.00
72" Ditching Pin-On Bucket(1.22 cu. yd.)		\$3,921.00
KIT, THUMB, HYD, 3-TINE, use with bucket only (3 tine)	1,155 LB	\$8,604.00
KIT, THUMB, HYD, 4-TINE, use with bucket only (4 tine)	1,190 LB	\$9,089.00
KIT, THUMB, HYD, 3-TINE, use with bucket and coupler (3 tine)	1,300 LB	\$8,972.00
KIT, THUMB, HYD, 4-TINE, use with bucket and coupler (4 tine)	1,325 LB	\$9,573.00
KIT, COUPLER, MULTI-FIT S	683 LB	\$5,882.00
	with 5 teeth (1.22 cu. yd.) 24" HD Hi-Capacity Pin-On Bucket with 4 teeth (.79 cu. yd.) 30" HD Hi-Capacity Pin-On Bucket with 4 teeth (1.02 cu. yd.) 42" HD Hi-Capacity Pin-On Bucket with 5 teeth (1.48 cu. yd.) 48" HD Hi-Capacity Pin-On Bucket with 6 teeth (1.72 cu. yd.) 24" Severe-Duty Pin-On Bucket with 4 teeth (.65 cu. yd.) 30" Severe-Duty Pin-On Bucket with 4 teeth (.84 cu. yd.) 36" Severe-Duty Pin-On Bucket with 5 teeth (1.03 cu. yd.) 42" Severe-Duty Pin-On Bucket with 5 teeth (1.22 cu. yd.) 60" Ditching Pin-On Bucket (1.02 cu yd.) 72" Ditching Pin-On Bucket (1.22 cu. yd.) KIT, THUMB, HYD, 3-TINE, use with bucket only (3 tine) KIT, THUMB, HYD, 3-TINE, use with bucket and coupler (3 tine) KIT, THUMB, HYD, 4-TINE, use with bucket and coupler (4 tine)	with 5 teeth (1.22 cu. yd.) 24" HD Hi-Capacity Pin-On Bucket with 4 teeth (7.9 cu. yd.) 30" HD Hi-Capacity Pin-On Bucket with 4 teeth (1.02 cu. yd.) 42" HD Hi-Capacity Pin-On Bucket with 5 teeth (1.48 cu. yd.) 48" HD Hi-Capacity Pin-On Bucket with 6 teeth (1.72 cu. yd.) 24" Severe-Duty Pin-On Bucket with 4 teeth (.65 cu. yd.) 30" Severe-Duty Pin-On Bucket with 4 teeth (.84 cu. yd.) 36" Severe-Duty Pin-On Bucket with 5 teeth (1.03 cu. yd.) 42" Severe-Duty Pin-On Bucket with 5 teeth (1.03 cu. yd.) 42" Severe-Duty Pin-On Bucket with 5 teeth (1.22 cu. yd.) 60" Ditching Pin-On Bucket (1.02 cu yd.) 72" Ditching Pin-On Bucket (1.22 cu. yd.) KIT, THUMB, HYD, 3-TINE, use with bucket only (3 tine) KIT, THUMB, HYD, 3-TINE, use with bucket and coupler (3 tine) KIT, THUMB, HYD, 3-TINE, use with bucket and coupler (4 tine)

(This page intentionally left blank)



(Ex Works Port of Entry) Standard Equipment

ENGINE:

Isuzu AQ-4HK1X

Tier 4 Final Certified

Selective Catalytic Reduction (SCR)

Diesel Oxidation Catalyst (DOC)

Cooled Exhaust Gas Recirculation

(CEGR)

Turbocharged/air cooled intercooler

Horsepower:

Net: 177 (132.1 kW) @ 2000 rpm $\,$

Electronic fuel injection

High pressure common rail system

Neutral safety start

Auto-engine warm up

Glow-plug pre-heat

Fuel Economy Assist System (FEA)

Engine Protection Feature (EPF)

Dual-stage fuel filtration

Dual element air filter

Remote oil filter

Drain for fuel tank

Remote engine oil drain

500-hour engine oil change interval

24-volt system

Engine oil sample port

Battery disconnect switch

Emergency engine stop

External Fuel and DEF gauges

Fan housing

Fuel cooler

Fuel filter restriction indicator

Fuel shut-off valve

Idle start

Radiator, oil cooler, intercooler -

protective screen

FUEL ECONOMY SYSTEMS:

Engine Idle / Fuel Economy System:

Auto-idle

One-touch idle

Auto Idle shut-down

BEC- Boom Economy Control

AEC- Auto Economy Control

SWC- Swing Relief Control

SSC- Spool Stroke Control

ore areas something the

HYDRAULICS:

Auto power boost

Auto swing priority

Arm speed assistance (2 pump flow)

Auxiliary flow control

Auxiliary valve

Boom speed assistance (2 pump flow)

Bucket curl assist

Control levers pre-wired for auxiliary

hydraulics

Electronically controlled hydraulic

pumps

Holding valve (Boom and Arm)

Fire wall

Hydraulic filter restriction indicator

Neutral pump de-stroke

Oil cooler

Power save

Pump stand-by pressure

Auto travel speed change

Selectable work modes

Free swing - switch activated

Hydraulic oil sample port

Control pattern selector

Pre-set auxiliary pump settings

Auxiliary valve

5,000-hour hydraulic oil change

interval

1,000-hour hydraulic filter change

interval

SAHR brake



(Ex Works Port of Entry) Standard Equipment

UPPER STRUCTURE:

ISO mirrors (3)
Cab viscous-mounts (fluid)
Upper mounted work light (70 watt)
Swivel guard belly pan

Center cover (over main CV)
Fuel tank belly pan
Handrail (RH access)

ISO guard rails

Lifting eyes for counterweight Lockable fuel cap, service doors and

tool box

ATTACHMENTS:

Boom- 19 ft. 2 in. (5.85 m)
Arm- 9 ft. 10 in. (3.00 m)
Heavy-duty bucket linkage
Boom mounted work light (70 watt)
Auxiliary pipe brackets
Centralized grease fittings
Attachment cushion valve

Arm and boom regeneration

Bucket anti-clatter device

Chrome pins

Easy Maintenance System (EMS)

bushings

Teardrop pin retention keepers

OPERATOR STATION:

ROPS protection FOPS cab (Level 1) Pressurized cab Face vent

Cab lights (2)

Interior dome light

One-touch lock front window

One piece window (right)

Safety glass windows

Gate lock hydraulic activation

Emergency exit and hammer

Clear (polycarbonate) roof window w/

sunshade

AC/heat/defrost w/ auto climate control

OPERATOR STATION (continued):

LED Color monitor— 7 in (180 mm)

26 selectable languages for monitor

On-board diagnostic system

10 programmable attachments settings
 on monitor - 5 single flow, 5 dual

flow

Seatbelt-3 in. (76 mm)

Heated high-back cloth seat with air suspension and 650 tilt adjustment

Sliding seat - 3.54 in. (90 mm)

Adjustable armrests

Tilting consoles- 4-position

Sliding cockpit - 3.15 in. (80 mm)

Low-effort joystick controls

Controls pre-wired for auxiliary

Single pedal travel

Straight travel

AM/FM radio w/ antenna, 2 speakers

and Bluetooth capabilities

Aux-in port for personal electronics

Radio mute switch (joystick)

Rear-view & Side-view camera

Anti-theft system (start code system)

Rubber floormat

12-volt electric outlet

24-volt cigarette lighter

Windshield wiper/washer

Cup holder

Storage compartments

Warm/cool storage compartment

Travel alarm with cancel switch

Ignition keys

One key start & lock-up

Cab filter (external)

Cab handrails

Operator's manual



(Ex Works Port of Entry) Standard Equipment

UNDERCARRIAGE:

Long undercarriage
31.5 in. (800 mm) steel shoes, triple
semi-grouser
Full overlap turntable bearing tub
Single track chain guides
Hydraulic track adjustment
Sealed link chain
Steps
Carbody belly pan (swivel guard)
X-pattern carbody
Lashing points (tie downs)

EXTRA FILTER KIT:
Engine oil filter
Filter wrench

Fuel filters
Grease gun
Green plug oil drain hose for
engine oil drain
Hydraulic return filter
Pilot circuit hydraulic filter

CASE ProCare - Full Machine Protection
Factory Warranty (3-yr/3000-hr),
Planned Maintenance (3-yr/2000-hr)
and SiteWatch™ Telematics
CASE SiteWatch™ Telematics
Includes hardware and a 3-yr
advanced data subscription



(Ex Works Port of Entry) Models

COMMERCIAL MODEL	Weight	Factory Data	List Price
CX250D STD	56,909 LBS		\$386,373.00



(Ex Works Port of Entry) Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

LIGHTS

SD_E5408 WORKING LIGHTS

	488134	Halogen Working Lights		No Charge
	488135	LED Working Lights		\$2,754.00
		8 LED lights:		
		2 LED light are mounted on the front (1 on boom, 1 on house)		
		2 LED lights are mounted on the rear		
		(above the rear view camera)		
		1 LED light mounted on each side (2)		
L		2 LED lights mounted on the top of the cab		

BOOMS

SD_E5311 BOOM

	481858	Std Boom		No Charge
		19'2" (5.85 M) Standard Boom		
	781917	No Boom		(\$6,769.00)
		Less boom, hoist and arm cylinders and plumbing.		
		Boom-foot and cylinder pins are provided.		

ARMS

SD_E5320 ARM/DIPPERSTICK

	461548	8'2" (2.50 m) HD Arm		\$217.00
		For use with 19"2" Standard Boom (option 481858)		
		(Recommended for heavy-duty applications - example: hammer)		
	781178	9'10" (3.01 m) Std Arm		No Charge
		For use with 19'2" Standard Boom (option 481858)		
	781149	11'6" (3.52 M) Standard Arm		\$1,300.00
		For use with 19'2" Standard Boom (option 481858)		
	XE5320X	No Arm/Dipperstick		(\$3,467.00)
		Less arm, bucket cylinder and linkage.		



(Ex Works Port of Entry)

TRACK SHOES

SD_E5199 TRACK SHOES

	9560013	23.6" (600 mm) Steel Shoes		(\$1,153.00)
		Triple-Grouser Steel Shoes		
	9560003	27.6" (700mm) TG Steel Shoes		(\$568.00)
		Triple-Grouser Steel Shoes		
	9560005	31.5" (800 mm) TG Steel Shoes		No Charge
		Triple-Grouser Steel Shoes		
	9560007	35.4" (900 mm) Steel Shoes		\$1,377.00

LANGUAGE

SD_47083 OPERATOR'S MANUAL

	781981	English Literature		No Charge
	461540	French Canadian Literature		No Charge
	781980	Spanish Literature		No Charge

ADDITIONAL EQUIPMENT CXC

HYDRAULIC OPTIONS	

SD_E6410 AUXILIARY HYDRAULICS

XE6410X	No Optional Hydraulics		(\$11,536.00)



(Ex Works Port of Entry)

461869	MF w/ pressure setting - Prop		No Charge
	Multi-Function Auxiliary Hydraulics with Electronic Pressure		
	Control (EPC)		
	For use with multiple applications:		
	hammers/thumbs/grapples/crushers.		
	Includes in-cab Electronic Pressure Control feature		
	Pressure Control feature allows hydraulic pressure setting		
	from the cab monitor and maintaining pressure settings in		
	memory when multiple tools are used.		
	Joystick Activated with Electronic Proportional Controls		
	Provides single or dual pump, two-way flow,		
	Secondary Low-flow Auxiliary Hydraulics can be added		
	Includes in-cab electronically controlled pressure setting feature		
	Is switchable to single acting flow for hammer application.		
	Notes:		
	1) Not for use with other Auxiliary Hydraulics options, with the		
	exception of Low Flow.		
	2) Heavy duty bucket linkage is standard equipment on		
	C/D series excavators.		
	For dealer installed auxiliary hydraulic kits contact:		
	HydrauliCircuit Technology (HCT)		
	(1-888-603-0080 or sales@hctkits.com or www.hctkits.com)		

SD E6417 SECONDARY AUXILIARY HYDRAULICS

 J_L0417 3L	CONDAKT AUXILIAKT TITDKAULICS	
XE6417X	No Low Flow Circuit	No Charg
461863	Secondary Auxiliary Hydraulics	\$7,171.0
	Secondary Low Flow Auxiliary Hydraulics	
	Provides low-flow for rotation or tilt hydraulic attachments.	
	For use with Standard Boom option 481858	
	Not for use with Offset Boom option 461025	
	Joystick Activated with Electronic Proportional Controls	
	Notes:	
	1) May be used stand alone or with any Case Excavator Auxiliary	
	Hydraulics option.	
	2) For dealer installed auxiliary hydraulic kits contact:	
	HydrauliCircuit Technology (HCT)	
	(1-888-603-0080 or sales@hctkits.com or www.hctkits.com)	



(Ex Works Port of Entry)

CAB OPTIONS		
CD E5440	CAR CHARD (FORC)	
	CAB GUARD (FOPS)	No Charge
	3X No FOPS Top Cab Guard	No Charge
48107	0 FOPS Top Cab Guard	\$1,146.00
SD_E5444	CAB GUARD (FRONT)	
	4X No Front Guard	No Charge
46114		\$1,326.00
78198	6 Front Stone Guard (OPG L1)	\$1,973.00
	vertical bars (two piece/upper and lower)	
46102	4 Front Stone Guard (OPG L2)	\$2,324.00
	vertical bars (one piece/full length)	
46155	2 Vandal Guard	\$574.00
	Removable steel panels for front windshield	
	RAIN DEFLECTOR	
	9X No Rain Deflector	No Charge
46155		\$380.00
	Not for use with Front grill guard - 2 x 2 mesh option 461142,	
	Front rock guard (OPG 1) option 781986, or	
	Front rock guard (OPG 2) option 461024.	
SD F5451	SUN VISOR	
	itX No Sun Visor	No Charge
46155	4 Sun Visor	\$108.00
BUCKETS		
SD E6300	EXCAVATOR BUCKET(S)	
T XE630		No Charge
/=====	Buckets may be ordered using Order Codes listed in the	110 01141.90
	Factory Supplied Attachments Section	
- I	Table y Capping The Control	1
ADDITIONAL O	PTIONS	
SD_02005	ENGINE PRE-CLEANER	
X0200	5X No Pre-Cleaner	No Charge
48803	1 Pre-Cleaner Cyclone	\$470.00
05 5-000		
	TRACK CHAIN GUIDE	No Charry
46154		No Charge
46114	S Hiple Hack Chaill Guide	\$1,123.00
SD E5407	COOLING PACKAGE	
	17X Standard Cooling Package	No Charge
	_ · · · _	

XE9874X No Refuel Pump

Refuel Pump

481257



CX250D STD CRAWLER EXCAVATOR US PRICE LIST

	(Ex Works Port of Entry)	
481027	Tropical Cooling Package	\$504.00
	High ambient temperature cooling package	
	Includes hardware to support the cooling of the	
	main machine systems.	
	Must also order: Pre-Cleaner Cyclone option 488031	
	Note: Recommended for machines operating in high heat	
	conditions not to exceed 122°F (50°C)	
SD_E6400 M	EC/HYD QUICK COUPLER	
	No Quick Coupler	No Charge
781128	Hydraulic Quick Coupler Ready	\$2,304.00
	Does not come with coupler. Must order coupler from Factory	
	Supplied Attachments section	
SD_E9730 S/	AFETY VALVE	
XE9730X	No Hose Burst Check Valve	No Charge
481064	Hose Burst Check Valve (HBCV)	\$7,913.00
	Located on Boom and Arm Cylinder	
SD_E9739 FU	JLL VIEW CAMERA	
XE9739X	No max view monitor	No Charge
488055	Case Max View Monitor	\$1,700.00
SD_E9742 RI	EVERSIBLE FAN	
XE9742X	No Reversible Fan	No Charge
488121	Reversible Fan	\$8,709.00
	Variable pitch reversing fan features rotating blades, that provides	
	maximum airflow in either direction when engaged by operator.	
SD E9874 RI	EFUEL PUMP	

No Charge

\$1,296.00



(Ex Works Port of Entry)

Factory Supplied Attachments

Order Code	Description	Weight	Factory Data	List Price
E Machine Guid	dance			
90456016	OEM-Fit 2D Machine Guidance Sys Leica	26 LB		\$18,800.00
	- Option available to Precision-Certified Dealers only.			
	Expect extended lead times when ordering this option. Contact your CASE representative for more information. Attachment calibration required upon delivery. Display will arrive in case located in cab, and will need to be mounted upon dealer arrival.			
90456015	OEM-Fit 3D Machine Guidance Sys Leica	43 LB		\$64,090.00
	- Option available to Precision-Certified Dealers only.			
	 Expect extended lead times when ordering this option. Contact your CASE representative for more information. Attachment calibration required upon delivery. Display and GNSS antennas will arrive in case located in cab, and will need to be mounted upon dealer arrival. Radio Antenna required- Purchased separately through CNH Parts. 			
	- For 900MHz Radio/Antenna order: LG916750 - CCD21, Satel M3-TR9 Radio iCG80 and L827067 - CA26, Antenna, for CCD15 and 4G modem For 4xx MHz Antenna order: LG916751 - CCD22, Satel TR4+Radio iCG80 and Order 1 of the following: LG805281 CA12, Radio Antenna 406-440MHz or LG805282 CA13, Radio Antenna, 430-480MHz.			
Pin On Bucke	te			
84404217	36" Heavy-Duty Pin-On Bucket			\$5,659.00
84404219	42" Heavy-Duty Pin-On Bucket			\$6,226.00
84404220	48" Heavy-Duty Pin-On Bucket			\$6,510.00
84404224	36" HD Hi-Capacity Pin-On Bucket			\$6,103.00
84404228	42" HD Hi-Capacity Pin-On Bucket			\$6,713.00
84404230	48" Extra Heavy Duty Bucket			\$7,103.00
84404232	54" HD Hi-Capacity Pin-On Bucket with 6 teeth (2.14 cu. yd.)			\$7,438.00
84404234	36" Severe-Duty Pin-On Bucket			\$7,291.00
84404237	42" Severe-Duty Pin-On Bucket with 5 teeth (1.48 cu. yd.)			\$8,022.00
	Pin On Bucke 84404217 84404224 84404224 84404230 84404232 84404234	E Machine Guidance 90456016 OEM-Fit 2D Machine Guidance Sys Leica - Option available to Precision-Certified Dealers only Expect extended lead times when ordering this option. Contact your CASE representative for more information Attachment calibration required upon delivery Display will arrive in case located in cab, and will need to be mounted upon dealer arrival. 90456015 OEM-Fit 3D Machine Guidance Sys Leica - Option available to Precision-Certified Dealers only Expect extended lead times when ordering this option. Contact your CASE representative for more information Attachment calibration required upon dealer arrival Attachment calibration required upon dealer arrival Radio Antenna required- Purchased separately through CNH Parts For 900MHz Radio/Antenna order: LG916750 - CCD21, Satel M3-TR8 Radio iCG80 and L827067 - CA26, Antenna, for CCD15 and 4G modem For 4xx MHz Antenna order: LG916751 - CCD22, Satel TR4+Radio iCG80 and Order 1 of the following: LG805281 CA12, Radio Antenna 406-440MHz or LG805281 CA13, Radio Antenna, 430-480MHz. Prin On Buckets 84404217 36" Heavy-Duty Pin-On Bucket with 5 teeth (1.25 cu. yd.) 84404220 48" Heavy-Duty Pin-On Bucket with 5 teeth (1.48 cu. yd.) 84404224 36" HD Hi-Capacity Pin-On Bucket with 5 teeth (1.36 cu. yd.) 84404230 48" Extra Heavy Duty Bucket with 5 teeth (1.36 cu. yd.) 84404230 48" Extra Heavy Duty Bucket with 5 teeth (1.36 cu. yd.) 84404231 36" Ho Hi-Capacity Pin-On Bucket with 5 teeth (1.62 cu. yd.) 84404231 36" Severe-Duty Pin-On Bucket with 6 teeth (1.75 cu. yd.) 84404231 36" Severe-Duty Pin-On Bucket with 6 teeth (1.75 cu. yd.)	E Machine Guidance 90456016 OEM-Fit 2D Machine Guidance Sys Leica - Option available to Precision-Certified Dealers only Expect extended lead times when ordering this option. Contact your CASE representative for more information Attachment calibration required upon delivery Display will arrive in case located in cab, and will need to be mounted upon dealer arrival. 90456015 OEM-Fit 3D Machine Guidance Sys Leica - Option available to Precision-Certified Dealers only Expect extended lead times when ordering this option. Contact your CASE representative for more information Attachment calibration required upon delivery Display and GNSS antennas will arrive in case located in cab, and will need to be mounted upon dealer arrival Radio Antenna required- Purchased separately through CNH Parts For 900MHz Radio/Antenna order:	E Machine Guidance 90456016 OEM-Fit 2D Machine Guidance Sys Leica 26 LB

(Ex	Works	Port o	of Entry	1)
-----	-------	--------	----------	----

	84404240	48" Severe-Duty Pin-On Bucket with 6 teeth (1.72 cu. yd.)		\$8,824.00
	84404242	60" Ditching Pin-On Bucket (1.38 cu yd.)		\$5,059.00
	84404244	72" Ditching Pin-On Bucket(1.77 cu. yd.)		\$5,398.00
Cas	se Coupler Buck	•		
	84404245	36" Heavy-Duty Coupler Bucket with 5 teeth (1.16 cu. yd.)		\$7,114.00
	84404246	42" Heavy-Duty Coupler Bucket with 5 teeth (1.38 cu. yd.)		\$7,589.00
	84404249	48" Heavy-Duty Coupler Bucket with 6 teeth (1.60 cu. yd.)		\$8,315.00
	84404251	54" Heavy-Duty Coupler Bucket with 6 teeth (1.84 cu. yd.)		\$8,999.00
Cou	upler			
	47848464	Multi-Fit S Coupler Kit	1,265 LB	\$8,414.00
Dire	ect Link Thumb			
	47609075	KIT, THUMB, HYD, 3-TINE, use with bucket only (3 tine)	1,235 LB	\$9,136.00
	47609076	KIT, THUMB, HYD, 4-TINE, use with bucket only (4 tine)	1,275 LB	\$9,621.00
	47609077	KIT, THUMB, HYD, 3-TINE, use with bucket and coupler (3 tine)	1,380 LB	\$9,539.00
	47609078	KIT, THUMB, HYD, 4-TINE, use with bucket and coupler (4 tine)	1,415 LB	\$10,155.00
Pro	gressive Link T	humb		
	47609115	KIT, THUMB, PROG LINK, 3- use with bucket only (3 tine)	1,760 LB	\$11,776.00
	47609116	KIT, THUMB, PROG LINK, 4- use with bucket only (4 tine)	1,800 LB	\$12,261.00
	47609117	KIT, THUMB, PROG LINK, 3- use with bucket and coupler (3 tine)	1,905 LB	\$12,179.00
	47609118	KIT, THUMB, PROG LINK, 4- use with bucket and coupler (4 tine)	1,940 LB	\$12,795.00

(This page intentionally left blank)



(Ex Works Port of Entry) Standard Equipment

ENGINE:

Isuzu AO-4HK1X

Tier 4 Final Certified

Selective Catalytic Reduction (SCR)

Diesel Oxidation Catalyst (DOC)

Cooled Exhaust Gas Recirculation

(CEGR)

EGR Coolers

Four-cylinder turbo-charged diesel

Turbocharged/air cooled intercooler

Horsepower:

Net: 177 (132.1 kW) @ 2000 RPM

Electronic fuel injection

High pressure common rail system

Neutral safety start

Auto-engine warm up

Glow-plug pre-heat

Fuel Economy Assist System (FEA)

Engine Protection Feature (EPF)

Dual-stage fuel filtration

Dual element air filter

Remote oil filter

Drain for fuel tank

Remote engine oil drain

500-hour engine oil change interval

24-volt system

Engine oil sample port

Battery disconnect switch

Emergency engine stop

External Fuel and DEF gauges

Fan housing

Fuel cooler

Fuel filter restriction indicator

Fuel shut-off valve

Idle start

Radiator, oil cooler, intercooler -

protective screen

FUEL ECONOMY SYSTEMS:

Engine Idle/Fuel Economy System:

Auto-idle

One-touch idle

Auto-Idle shut-down

BEC- Boom Economy Control

AEC- Auto Economy Control

SWC- Swing Relief Control

SSC- Spool Stroke Control

HYDRAULICS:

Auto power boost

Auto swing priority

Arm speed assistance (2 pump flow)

Auxiliary flow control

Auxiliary valve

Boom speed assistance (2 pump flow)

Bucket curl assist

Control levers pre-wired for auxiliary

hydraulics

Electronically controlled hydraulic

pumps

Holding valve (Boom and Arm)

Fire wall

Hydraulic filter restriction indicator

Neutral pump de-stroke

Oil cooler

Power save

Pump stand-by pressure

Auto travel speed change

Selectable work modes

Free swing

Hydraulic oil sample port

Control pattern selector

Pre-set auxiliary pump settings

Auxiliary valve

5,000-hour hydraulic oil change

interval

1,000-hour hydraulic filter change

interval

SAHR brake



(Ex Works Port of Entry) Standard Equipment

UPPER STRUCTURE:

ISO mirrors (3)

Cab viscous-Mounts (fluid)

Upper mounted work light (70 watt)

Swivel guard belly pan

Center cover (over main CV)

Fuel tank belly pan

Handrail (RH access)

ISO quard rails

Lifting eyes for counterweight

Lockable fuel cap, service doors and

tool box

ATTACHMENTS:

Boom- 33 ft. 10 in. (10.30 m)

Arm- 26 ft. 3 in. (8.00 m)

Heavy-duty bucket linkage

Boom mounted work light (70 watt)

Auxiliary pipe brackets

Centralized grease fittings

Attachment cushion valve

Arm and boom regeneration

Bucket anti-clatter device

Chrome pins

Easy Maintenance System (EMS)

bushings

Teardrop pin retention keepers

OPERATOR STATION:

ROPS protection

FOPS cab (Level 1)

Pressurized cab

Face vent

Cab lights (2)

Interior dome light

One-touch lock front window

One piece window (right)

Safety glass windows

Gate lock hydraulic activation

Emergency exit and hammer

Clear (polycarbonate) roof window

w/sunshade

OPERATOR STATION (continued):

AC/heat/defrost w/ auto climate

control

LED Color monitor— 7 in (180 mm)

26 selectable languages for monitor

On-board diagnostic system

 $10 \ \mathrm{programmable}$ attachments settings

on monitor - 5 single flow, 5 dual

flow

Seatbelt-3 in. (76 mm)

Heated high-back cloth seat with air

suspension and 650 tilt adjustment

Sliding seat - 3.54 in. (90 mm)

Adjustable armrests

Tilting consoles- 4-position

Sliding cockpit - 3.15 in. (80 mm)

Low-effort joystick controls

Controls pre-wired for auxiliary

Single pedal travel

Straight travel

AM/FM radio w/ antenna, 2 speakers

and Bluetooth capabilities

Aux-in port for personal electronics

Radio mute switch (joystick)

Rear-view & Side-view camera

Anti-theft system (start code system)

Rubber floormat

12-volt electric outlet

24-volt cigarette lighter

Windshield wiper/washer

Cup holder

Storage compartments

Warm/cool storage compartment

Travel alarm with cancel switch

Ignition keys

One key start & lock-up

Cab filter (external)

Cab handrails

Operators manual



(Ex Works Port of Entry) Standard Equipment

UNDERCARRIAGE:

Long undercarriage
31.5 in. (800 mm) steel shoes, triple
semi-grouser
Full overlap turntable bearing tub
Single track chain guides
Hydraulic track adjustment
Sealed link chain
Steps
Carbody belly pan (swivel guard)
X-pattern carbody
Lashing points (tie downs)

EXTRA FILTER KIT:
Engine oil filter
Filter wrench
Fuel filters

Grease gun
Green plug oil drain hose for
engine oil drain
Hydraulic return filter
Pilot circuit hydraulic filter

CASE ProCare - Full Machine Protection Factory Warranty (3-yr/3000-hr),
Planned Maintenance (3-yr/2000-hr) and SiteWatch™ Telematics
CASE SiteWatch™ Telematics
Includes hardware and a 3-yr advanced data subscription



(Ex Works Port of Entry) Models

COMMERCIAL MODEL	Weight	Factory Data	List Price
CX250D LR	62,100 LBS		\$437,816.00

781980

Spanish Literature



CX250D LONG REACH CRAWLER EXCAVATOR US PRICE LIST

(Ex Works Port of Entry) Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
LIGHTS				
SD_E5408 W	ORKING LIGHTS			
488134	Halogen Working Lights			No Charge
488135	LED Working Lights			\$2,754.00
	8 LED lights:			Ψ=,:
	2 LED light are mounted on the front (1 on boom, 1 on house)			
	2 LED lights are mounted on the rear			
	(above the rear view camera)			
	1 LED light mounted on each side (2)			
	2 LED lights mounted on the top of the cab			
! ! !			!	
BOOMS				
2000				
SD_E5311 BC	OOM			
461029	Standard Long Reach Boom			No Charge
	33'10" (10.30 M) Long Reach Boom			
	to to (tolor in/ zong noutri zoom			
ARMS				
Aitino				
SD F5320 AF	RM/DIPPERSTICK			
481238	26'3" (8.00 M) Arm			No Charge
	For use with 33'10" Standard Long Reach Boom (option 461029)			110 01101.90
TRACK SHOES				
TRACK SHOLD				
SD_E5199 TF	ACK SHOES			
9560005	31.5" (800 mm) TG Steel Shoes			No Charge
	Triple-Grouser Steel Shoes			740 Orlange
	The course state and the	!	1	
LANGUAGE				
LANOUAGE				
SD_47083 OF	PERATOR'S MANUAL			
781981	English Literature		1	No Charge
461540	French Canadian Literature			No Charge
401340	i ionon Ganadian Ellerature			ino charge

No Charge

XE5451X No Sun Visor

Sun Visor

461554



CX250D LONG REACH CRAWLER EXCAVATOR US PRICE LIST

(Ex Works Port of Entry)

ADDITIONAL E	QUIPMENT CXC	
HYDRAULIC OF	PTIONS	
SD_E6417	SECONDARY AUXILIARY HYDRAULICS	
XE641	7X No Low Flow Circuit	No Charge
461863	B Secondary Auxiliary Hydraulics	\$8,083.00
	Secondary Low Flow Auxiliary Hydraulics	
	Provides low-flow for rotation or tilt hydraulic attachments.	
	Joystick Activated with Electronic Proportional Controls	
	Notes:	
	1) May be used stand alone or with any Case Excavator Auxiliary	
	Hydraulics option.	
	2) For dealer installed auxiliary hydraulic kits contact:	
	HydrauliCircuit Technology (HCT)	
	(1-888-603-0080 or sales@hctkits.com or www.hctkits.com)	
CAB OPTIONS		
SD_E5443	CAB GUARD (FOPS)	
XE544	3X No FOPS Top Cab Guard	No Charge
481070	FOPS Top Cab Guard	\$1,146.00
	CAB GUARD (FRONT)	
XE544	4X No Front Guard	No Charge
461142		\$1,326.00
781986	Front Stone Guard (OPG L1)	\$1,973.00
	vertical bars (two piece/upper and lower)	
461024	Front Stone Guard (OPG L2)	\$2,324.00
	vertical bars (one piece/full length)	
461552	2 Vandal Guard	\$574.00
	Removable steel panels for front windshield	
SD_E5449	RAIN DEFLECTOR	
XE544	9X No Rain Deflector	No Charge
46155	Rain Deflector	\$380.00
	Not for use with Front grill guard - 2 x 2 mesh option 461142,	
	Front rock guard (OPG 1) option 781986, or	
	Front rock guard (OPG 2) option 461024.	
SD_E5451		
1 1 2		1 1 1 1

No Charge

\$108.00

481257

Refuel Pump



CX250D LONG REACH CRAWLER EXCAVATOR US PRICE LIST

(Ex Works Port of Entry)

-	BUC	KETS		
	S		CAVATOR BUCKET(S)	
		XE6300X	No Bucket	No Charge
			Buckets may be ordered using Order Codes listed in the	
			Factory Supplied Attachments Section	
/	ADD	ITIONAL OPTI	ONS	
	_			
	S		GINE PRE-CLEANER	
			No Pre-Cleaner	No Charge
		488031	Pre-Cleaner Cyclone	\$470.00
	_	D F5000 TD	ACK CHAIN CHIPE	
		461541	ACK CHAIN GUIDE Single Track Chain Guide	No Charge
		461143	Triple Track Chain Guide	No Charge \$1,123.00
		401143	Triple Track Chain Guide	\$1,123.00
	9	D E5407 CO	OLING PACKAGE	
			Standard Cooling Package	No Charge
		481027	Tropical Cooling Package	\$504.00
		.0.02.	High ambient temperature cooling package	
			Includes Pre-Cleaner Cyclone option 488031	
			Note: Recommended for machines operating in high heat	
			conditions not to exceed 122°F (50°C)	
	S	D_E6400 ME	C/HYD QUICK COUPLER	
		XE6400X	No Quick Coupler	No Charge
			Does not come with coupler. Must order coupler from Factory	
			Supplied Attachments section	
		781128	Hydraulic Quick Coupler Ready	\$3,013.00
			Does not come with coupler. Must order coupler from Factory	
			Supplied Attachments section	
	S	D_E9730 SA	FETY VALVE	, , , , , , , , , , , , , , , , , , ,
		XE9730X	No Hose Burst Check Valve	No Charge
			Located on Boom and Arm Cylinder	
		481064	Hose Burst Check Valve (HBCV)	\$7,913.00
			boom and arm	
	S		LL VIEW CAMERA	
			No max view monitor	No Charge
		488055	Case Max View Monitor	\$1,700.00
	_	D F00=: 5=	EUEL DUMP	
	S	D_E9874 RE		N. Ohama
		⊼⊑98/4X	No Refuel Pump	No Charge

\$1,296.00



(Ex Works Port of Entry) Factory Supplied Attachments

	Order Code	Description	Weight	Factory Data	List Price
ase	Pin On Bucke	ts			
	84404095	30" Heavy-Duty Pin-On Bucket with 4 teeth (.65 cu. yd.)			\$3,073.00
	84404103	36" Heavy-Duty Pin-On Bucket with 5 teeth (.79 cu. yd.)	1,301 LB		\$3,329.00
	84404113	48" Ditching Pin-On Bucket (.79 cu. yd.)			\$2,992.00
	84404115	60" Ditching Pin-On Bucket (1.02 cu yd.)			\$3,394.00
	47609058	Hydraulic Main Pin Direct Link Thumb use with bucket only (2 tine)	830 LB		\$6,569.00
Direc	ct Link Thumb				
	47609059	KIT, THUMB, HYD, 4-TINE, use with bucket only (3 tine)	860 LB		\$6,953.00
	47609060	KIT, THUMB, HYD, 3-TINE, use with bucket and coupler (2 tine)	870 LB		\$6,813.00
	47609061	KIT, THUMB, HYD, 4-TINE, use with bucket and coupler (3 tine)	910 LB		\$7,293.00
-abc	o Buckets				
	84404117	24" Heavy Duty (HD) Coupler Bucket with 4 teeth (.43 cu. yd.)			\$4,075.00
	84404118	30" Heavy Duty (HD) Coupler Bucket with 4 teeth (.56 cu. vd.)	870 LB		\$4,523.00

ENGINE:



CX290D LC MATERIAL HANDLING US PRICE LIST

HYDRAULICS:

Standard Equipment

Isuzu AO-4HK1X Auto power boost Tier 4 Final Certified Auto swing priority Selective Catalytic Reduction (SCR) Arm speed assistance (2 pump flow) Diesel Oxidation Catalyst (DOC) Auxiliary flow control Cooled Exhaust Gas Recirculation Auxiliary valve (CEGR) Boom speed assistance (2 pump flow) Four-cylinder turbo-charged diesel Bucket curl assist VGT turbocharger Control levers pre-wired for auxiliary Electronic fuel injection hydraulics High pressure common rail system Electronically controlled hydraulic Neutral safety start Auto-engine warm up Holding valve (Boom and Arm) Glow-plug pre-heat Fire wall Fuel Economy Assist System (FEA) Double-acting (2 pumps) plus 2nd Engine Protection Feature (EPF) auxiliary Dual-stage fuel filtration Hydraulic filter restriction indicator Dual element air filter Neutral pump de-stroke Remote oil filter Oil cooler Drain for fuel tank Power save Remote engine oil drain Pump stand-by pressure 500-hour engine oil change interval Auto travel speed change Selectable work modes 24-volt system Engine oil sample port Free swing Battery disconnect switch Hydraulic oil sample port Emergency engine stop Control pattern selector External Fuel and DEF gauges Pre-set auxiliary pump settings Fan housing Auxiliary valve Fuel cooler 5,000-hour hydraulic oil change Fuel filter restriction indicator interval Fuel shut-off valve 1,000-hour hydraulic filter change Idle start interval Radiator, oil cooler, intercooler -SAHR brake protective screen UPPER STRUCTURE: FUEL ECONOMY SYSTEMS: ISO mirrors (3) Engine Idle / Fuel Economy System: Elevated Hydraulic Cab Auto-idle 7'6" (3.2M) riser One-touch idle Emergancy cab lowering device# Auto Idle shut-down Upper mounted work light (70 watt) BEC- Boom Economy Control Swivel guard belly pan AEC- Auto Economy Control Center cover (over main CV) SWC- Swing Relief Control Fuel tank belly pan SSC- Spool Stroke Control Handrail (RH access)



CX290D LC MATERIAL HANDLING US PRICE LIST

Standard Equipment

UPPER STRUCTURE CONT. ISO quard rails Lifting eyes for counterweight Lockable fuel cap, service doors and tool box Anti-interference device ATTACHMENTS: Boom-16 ft. 5 in. (7.1 m) Arm-9 ft. 10 in. (5.0 m) Boom mounted work light (70 watt) Auxiliary pipe brackets Centralized grease fittings Attachment cushion valve Arm and boom regeneration Chrome pins Easy Maintenance System (EMS) bushings Teardrop pin retention keepers OPERATOR STATION: ROPS protection FOPS cab (Level 1) Pressurized cab Face vent Cab lights (2) Interior dome light One-touch lock front window One piece window (right) Safety glass windows Gate lock hydraulic activation Emergency exit and hammer Clear (polycarbonate) roof window w/ sunshade AC/heat/defrost w/ auto climate control LED Color monitor- 7 in (180 mm) 26 selectable languages for monitor On-board diagnostic system 10 programmable attachments settings on monitor - 5 single flow, 5 dual Seatbelt-3 in. (76 mm) Heated high-back cloth seat with air suspension and 650 tilt adjustment Sliding seat - 3.54 in. (90 mm)

Adjustable armrests Tilting consoles- 4-position Sliding cockpit - 3.15 in. (80 mm) Low-effort joystick controls Controls pre-wired for auxiliary Single pedal travel Straight travel AM/FM radio w/ antenna, 2 speakers and Bluetooth capabilities Aux-in port for personal electronics Radio mute switch (joystick) Rear-view camera Side-view camera Anti-theft system (start code system) Rubber floormat 12-volt electric outlet 24-volt cigarette lighter Windshield wiper/washer Cup holder Storage compartments Warm/cool storage compartment Travel alarm with cancel switch Ignition keys One key start & lock-up Cab filter (external) Cab handrails Operator's manual UNDERCARRIAGE: Long undercarriage 23.6 in. (600 mm) steel shoes, flatgrouser Full overlap turntable bearing tub Single track chain guides Hydraulic track adjustment Sealed link chain, Steps Carbody belly pan (swivel guard) X-pattern carbody Lashing points (tie downs) CASE ProCare - Full Machine Protection Factory Warranty (3-yr/3000-hr), Planned Maintenance (3-yr/2000-hr) and SiteWatch™ Telematics CASE SiteWatch™ Telematics Includes hardware and a 3-yr advanced data subscription



CX290D LC MATERIAL HANDLING US PRICE LIST

Models

COMMERCIAL MODEL	Weight	Factory Data	List Price
CX290D LC MH	72,100 LB		\$552,405.00

781981

English Literature



CX290D LC MATERIAL HANDLING US PRICE LIST

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
LIGHTS				
LIGHTO				
SD_E5408 W	ORKING LIGHTS			
488134	Halogen Working Lights			No Charge
488135	LED Working Lights			\$2,754.00
	8 LED light and 1 side camera:			
	2 LED light are mounted on the front (1 on boom, 1 on house)			
	2 LED lights are mounted on the rear			
	(above the rear view camera)			
	1 LED light mounted on each side (2)			
	2 LED lights mounted on the top of the cab			
BOOMS				
SD_E5311 B0	DOM			
461031	MATERIAL HANDLING B			No Charge
ARMS				
SD_E5320 AF	RM/DIPPERSTICK			
781930	16'5" (5.0 M) Arm			No Charge
TRACK SHOES				
SD_E5199 TF	RACK SHOES			
9560025	23.6" (600mm) Flat Steel Shoes			No Charge
9560003	, ,			(\$11,022.00)
9560013				(\$11,749.00)
9560005				(\$10,308.00)
LANGUAGE				
SD 47083 OF	PERATOR'S MANUAL			
461540	French Canadian Literature			No Charge
781980	Spanish Literature	1		No Charge
	1='	1		

No Charge

SD_E9909 TELEMATICS SERVICE 461742 3 YEARS ADV SUB



CX290D LC MATERIAL HANDLING US PRICE LIST

ADDITIONAL E	QUIPMENT CXC	
CAB OPTIONS		
SD_E5443	CAB GUARD (FOPS)	
XE544	3X No FOPS Top Cab Guard	No Charge
481070	· '	\$1,089.00
	Not for use with Vandal Guard option 461552	
SD F5444	CAB GUARD (FRONT)	
781986		No Charge
461024	· · ·	\$351.00
		•
ADDITIONAL O	PTIONS	
	ENGINE PRE-CLEANER	
X0200	5X No Pre-Cleaner	No Charge
48803	Pre-Cleaner Cyclone	\$470.00
SD E5206	TRACK CHAIN GUIDE	
46154		No Charge
461143	3 Triple Track Chain Guide	\$1,123.00
OD 50700	ELILL MEW CAMERA	
	FULL VIEW CAMERA 9X No max view monitor	No Chargo
48805		No Charge \$1,700.00
1 40003	Case wax view wormon	j \$1,700.00
SD_E9742	REVERSIBLE FAN	
XE974	2X No Reversible Fan	No Charge
48812 ⁻	Reversible Fan	\$8,709.00
	Variable pitch reversing fan features rotating blades, that provides	
	maximum airflow in either direction when engaged by operator.	
TELEMATICS		
SD_E9908	TELEMATICS ON BOARD	
461860	CASE SiteWatch Telematics	No Charge

No Charge

(This page intentionally left blank)



CX290D LC SCRAP US PRICE LIST

Standard Equipment

ENGINE: Isuzu AO-4HK1X Tier 4 Final Certified Selective Catalytic Reduction (SCR) Diesel Oxidation Catalyst (DOC) Cooled Exhaust Gas Recirculation (CEGR) Four-cylinder turbo-charged diesel VGT turbocharger Horsepower: Net 177 (132.1 kW) @ 2000 RPM Electronic fuel injection High pressure common rail system Neutral safety start Auto-engine warm up Glow-plug pre-heat Fuel Economy Assist System (FEA) Engine Protection Feature (EPF) Dual-stage fuel filtration Dual element air filter Remote oil filter Drain for fuel tank Remote engine oil drain 500-hour engine oil change interval 24-volt system Engine oil sample port Battery disconnect switch Emergency engine stop External Fuel and DEF gauges Fan housing Fuel cooler Fuel filter restriction indicator Fuel shut-off valve Idle start Radiator, oil cooler, intercooler protective screen FUEL ECONOMY SYSTEMS: Engine Idle / Fuel Economy System: Auto-idle One-touch idle Auto Idle shut-down BEC- Boom Economy Control AEC- Auto Economy Control

SWC- Swing Relief Control

SSC- Spool Stroke Control

```
HYDRAULICS:
 Auto power boost
  Auto swing priority
  Arm speed assistance (2 pump flow)
  Auxiliary flow control
  Auxiliary valve
  Boom speed assistance (2 pump flow)
  Bucket curl assist
  Control levers pre-wired for auxiliary
    hydraulics
  Electronically controlled hydraulic
    pumps
 Holding valve (Boom and Arm)
  2nd Auxiliary valve (proportional
  Fire wall
  Hydraulic filter restriction indicator
 Neutral pump de-stroke
 Oil cooler
  Power save
  Pump stand-by pressure
  Auto travel speed change
  Selectable work modes
  Free swing
  Hydraulic oil sample port
  Control pattern selector
  Pre-set auxiliary pump settings
  Auxiliary valve
  5,000-hour hydraulic oil change
    interval
  1,000-hour hydraulic filter change
    interval
  SAHR brake
UPPER STRUCTURE:
  ISO mirrors (3)
  Elevated Hydraulic Cab
    7'6" (3.2M) riser
    Emergancy cab lowering device#
  Upper mounted work light (70 watt)
  Swivel guard belly pan
  Center cover (over main CV)
 Fuel tank belly pan
 Handrail (RH access)
  ISO quard rails
 Lifting eyes for counterweight
```



CX290D LC SCRAP US PRICE LIST

Standard Equipment

UPPER STRUCTURE CONT. Lockable fuel cap, service doors and tool box Anti-interference device ATTACHMENTS: Boom-24 ft. 4 in. (7.4 m) Arm-19 ft. 2 in. (5.8 m) Boom mounted work light (70 watt) Auxiliary pipe brackets Centralized grease fittings Attachment cushion valve Arm and boom regeneration Chrome pins Easy Maintenance System (EMS) bushings Teardrop pin retention keepers OPERATOR STATION: ROPS protection FOPS cab (Level 1) Pressurized cab Face vent Cab lights (2) Interior dome light One-touch lock front window One piece window (right) Safety glass windows Gate lock hydraulic activation Emergency exit and hammer Clear (polycarbonate) roof window w/ sunshade AC/heat/defrost w/ auto climate control LED Color monitor- 7 in (180 mm) 26 selectable languages for monitor On-board diagnostic system 10 programmable attachments settings on monitor - 5 single flow, 5 dual flow Seatbelt- 3 in. (76 mm) Heated high-back cloth seat with air suspension and 650 tilt adjustment Sliding seat - 3.54 in. (90 mm) Adjustable armrests

Tilting consoles- 4-position Sliding cockpit - 3.15 in. (80 mm) Low-effort joystick controls Controls pre-wired for auxiliary Single pedal travel Straight travel AM/FM radio w/ antenna, 2 speakers and Bluetooth capabilities Aux-in port for personal electronics Radio mute switch (joystick) Rear-view camera Side-view camera Anti-theft system (start code system) Rubber floormat 12-volt electric outlet 24-volt cigarette lighter Windshield wiper/washer Cup holder Storage compartments Warm/cool storage compartment Travel alarm with cancel switch Ignition keys One key start & lock-up Cab filter (external) Cab handrails Operator's manual UNDERCARRIAGE: Long undercarriage 23.6 in. (600 mm) steel shoes, flatgrouser Full overlap turntable bearing tub Single track chain guides Hydraulic track adjustment Sealed link chain Steps Carbody belly pan (swivel guard) X-pattern carbody Lashing points (tie downs) CASE ProCare - Full Machine Protection Factory Warranty (3-yr/3000-hr), Planned Maintenance (3-yr/2000-hr) and SiteWatch™ Telematics CASE SiteWatch™ Telematics Includes hardware and a 3-yr advanced data subscription



CX290D LC SCRAP US PRICE LIST

Models

COMMERCIAL MODEL	Weight	Factory Data	List Price	
CX290D LC SC	71,700 LB		\$549,776.00	

781981

English Literature



CX290D LC SCRAP US PRICE LIST

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
LIGHTS				
SD E5408 W	ORKING LIGHTS			
488134	Halogen Working Lights			No Charge
488135	LED Working Lights			\$2,754.00
	8 LED light and 1 side camera:			ţ_,: cc .
	2 LED light are mounted on the front (1 on boom, 1 on house)			
	2 LED lights are mounted on the rear			
	(above the rear view camera)			
	1 LED light mounted on each side (2)			
	2 LED lights mounted on the top of the cab			
<u> </u>	2 220 lights mounted on the top of the out			
BOOMS				
BOOMS				
CD FE244 DC	NOM .			
SD_E5311 BC 461032	DOM MATERIAL HANDLING S			No Charge
401032	I MATERIAL HANDLING 3			ino charge
4040				
ARMS				
OD 55000 A5	M/DIDDEDOTION			
	RM/DIPPERSTICK	1	<u> </u>	
461033	GOOSE NECK ARM			No Charge
TRACK SHOES				
SD_E5199 TF				
9560025	23.6" (600mm) Flat Steel Shoes	-		No Charge
9560003	·	-		(\$11,022.00)
9560013	·			(\$11,749.00)
9560005	31.5" (800 mm) TG Steel Shoes			(\$10,308.00)
LANGUAGE				
SD_47083 OF	PERATOR'S MANUAL			
461540	French Canadian Literature			No Charge
781980	Spanish Literature			No Charge

No Charge

SD_E9909 TELEMATICS SERVICE 461742 3 YEARS ADV SUB



CX290D LC SCRAP US PRICE LIST

ADDITIONAL EQ	UIPMENT CXC	
CAB OPTIONS		
SD_E5443 C	AB GUARD (FOPS)	
XE5443>	No FOPS Top Cab Guard	No Charge
481070	FOPS Top Cab Guard	\$1,089.00
	Not for use with Vandal Guard option 461552	
SD F5444 C	AB GUARD (FRONT)	
781986	Front Stone Guard (OPG L1)	No Charge
461024	Front Stone Guard (OPG L2)	\$351.00
		<u> </u>
ADDITIONAL OPT	TIONS	
	NGINE PRE-CLEANER	
X02005X	No Pre-Cleaner	No Charge
488031	Pre-Cleaner Cyclone	\$470.00
SD E5206 T	RACK CHAIN GUIDE	
461541	Single Track Chain Guide	No Charge
461143	Triple Track Chain Guide	\$1,123.00
CD 50720 5	III. VIEW CAMEDA	
	JLL VIEW CAMERA No max view monitor	No Charge
488055	Case Max View Monitor	\$1,700.00
1 1 400000	Case wax view wormon	ψ1,700.00
SD_E9742 R	EVERSIBLE FAN	
XE9742>	No Reversible Fan	No Charge
488121	Reversible Fan	\$8,709.00
	Variable pitch reversing fan features rotating blades, that provides	
	maximum airflow in either direction when engaged by operator.	
TELEMATICS		
SD_E9908 T	ELEMATICS ON BOARD	
461860	CASE SiteWatch Telematics	No Charge

No Charge

(This page intentionally left blank)



FUEL ECONOMY SYSTEMS:

CX300D CRAWLER EXCAVATOR US PRICE LIST

(Ex Works Port of Entry) Standard Equipment

ENGINE: Isuzu AO-6HK1X Tier 4 Final Certified Selective Catalytic Reduction (SCR) Diesel Oxidation Catalyst (DOC) Cooled Exhaust Gas Recirculation (CEGR) Turbocharged/air cooled intercooler Horsepower: Net: 207 (154 kW) @ 1800 RPM Electronic fuel injection High pressure common rail system Neutral safety start Auto-engine warm up Glow-plug pre-heat Fuel Economy Assist System (FEA) Engine Protection Feature (EPF) Dual-stage fuel filtration Dual element air filter Remote oil filter Drain for fuel tank Remote engine oil drain 500-hour engine oil change interval 24-volt system Engine oil sample port Battery disconnect switch High ambient temperature cooling package Emergency engine stop External Fuel and DEF gauges Fan housing Fuel cooler

Fuel filter restriction indicator

Radiator, oil cooler, intercooler -

Fuel shut-off valve

protective screen

Idle start

```
Engine Idle / Fuel Economy System:
    Auto-idle
    One-touch idle
    Auto-Idle shut-down
  BEC- Boom Economy Control
 AEC- Auto Economy Control
  SWC- Swing Relief Control
  SSC- Spool Stroke Control
HYDRAULICS:
  Auto power boost
  Auto swing priority
 Arm speed assistance (2 pump flow)
  Auxiliary flow control
  Auxiliary valve
  Boom speed assistance (2 pump flow)
 Bucket curl assist
  Control levers pre-wired for auxiliary
    hydraulics
 Electronically controlled hydraulic
    pumps
 Holding valve (Boom and Arm)
  Fire wall
 Hydraulic filter restriction indicator
 Neutral pump de-stroke
  Oil cooler
  Power save
  Pump stand-by pressure
  Auto travel speed change
  Selectable work modes
  Free swing
  Hydraulic oil sample port
  Control pattern selector
 Pre-set auxiliary pump settings
  Auxiliary valve
  5,000-hour hydraulic oil change
    interval
  1,000-hour hydraulic filter change
    interval
  SAHR brake
```



(Ex Works Port of Entry) Standard Equipment

UPPER STRUCTURE: ISO mirrors (3)

Cab viscous-mounts (fluid)

Upper mounted work light (70 watt)

Swivel guard belly pan

Center cover (over main CV)

Fuel tank belly pan

Handrail (RH access)

ISO quard rails

Lifting eyes for counterweight

Lockable fuel cap, service doors and $% \left(1\right) =\left(1\right) \left(1\right)$

tool box

ATTACHMENTS:

Boom- 20 ft. 2 in. (6.15 m)

Arm-10 ft. 5 in. (3.18 m)

Heavy-duty bucket linkage

Boom mounted work light (70 watt)

Auxiliary pipe brackets

Centralized grease fittings

Attachment cushion valve

Arm and boom regeneration

Bucket anti-clatter device

Chrome pins

Easy Maintenance System (EMS)

bushings

Teardrop pin retention keepers

OPERATOR STATION:

ROPS protection

FOPS cab (Level 1)

Pressurized cab

Face vent

Cab lights (2)

Interior dome light

One-touch lock front window

One piece window (right)

Safety glass windows

Gate lock hydraulic activation

Emergency exit and hammer

Clear (polycarbonate) roof window w/

sunshade

OPERATOR STATION (Continued):

AC/heat/defrost w/ auto climate

control

LED Color monitor— 7 in (180 mm)

26 selectable languages for monitor

On-board diagnostic system

10 programmable attachments settings

on monitor - 5 single flow, 5 dual

flow

Seatbelt- 3 in. (76 mm)

Heated high-back cloth seat with air

suspension and 650 tilt adjustment

Sliding seat - 3.54 in. (90 mm)

Adjustable armrests

Tilting consoles- 4-position

Sliding cockpit - 3.15 in. (80 mm)

Low-effort joystick controls

Controls pre-wired for auxiliary

Single pedal travel

Straight travel

AM/FM radio w/ antenna, 2 speakers

and Bluetooth capabilities

Aux-in port for personal electronics

Radio mute switch (joystick)

Rear-view & Side-view camera

Anti-theft system (start code system)

Rubber floormat

12-volt electric outlet

24-volt cigarette lighter

Windshield wiper/washer

Cup holder

Storage compartments

Warm/cool storage compartment

Travel alarm with cancel switch

Ignition keys

One key start & lock-up

Cab filter (external)

Cab handrails

Operator's manual



(Ex Works Port of Entry) Standard Equipment

UNDERCARRIAGE:

Long undercarriage
31.5 in. (800 mm) steel shoes, triple
semi-grouser
Full overlap turntable bearing tub
Single track chain guides
Hydraulic track adjustment
Sealed link chain
Steps
Carbody belly pan (swivel guard)
X-pattern carbody
Lashing points (tie downs)

EXTRA FILTER KIT:
Engine oil filter
Filter wrench

Fuel filters
Grease gun
Green plug oil drain hose for
engine oil drain
Hydraulic return filter
Pilot circuit hydraulic filter

CASE ProCare - Full Machine Protection
Factory Warranty (3-yr/3000-hr),
Planned Maintenance (3-yr/2000-hr)
and SiteWatch™ Telematics
CASE SiteWatch™ Telematics
Includes hardware and a 3-yr
advanced data subscription



(Ex Works Port of Entry) Models

COMMERCIAL MODEL	Weight	Factory Data	List Price
CX300D STD	67,271 LBS		\$451,434.00



(Ex Works Port of Entry)

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
		-		

LIGHTS

SD_E5408 WORKING LIGHTS

	488134	Halogen Working Lights		No Charge
	488135	LED Working Lights		\$2,754.00
		8 LED lights:		
		2 LED light are mounted on the front (1 on boom, 1 on house)		
		2 LED lights are mounted on the rear		
		(above the rear view camera)		
		1 LED light mounted on each side (2)		
		2 LED lights mounted on the top of the cab		

BOOMS

SD_E5311 BOOM

	481858	Std Boom		No Charge
		20'2" (6.15 M) Standard Boom		
	781917	No Boom		(\$7,367.00)
		Less boom, hoist and arm cylinders and plumbing.		
		Boom-foot and cylinder pins are provided.		

ARMS

SD_E5320 ARM/DIPPERSTICK

	481243	8'8" (2.65 M) Standard Arm		(\$433.00)
		For use with 20'2" Standard Boom (option 481858)		
	781180	10'5" (3.18 M) Standard Arm		No Charge
		For use with 20'2" Standard Boom (option 481858)		
	481850	12' (3.66 M) Standard Arm		\$1,127.00
		For use with 20'2" Standard Boom (option 481858)		
	XE5320X	No Arm/Dipperstick		(\$3,909.00)
		Less arm, bucket cylinder and linkage		

(Ex Works Port of Entry)

TRACK SHOES

SD_E5199 TRACK SHOES

	9560013	23.6" (600 mm) Steel Shoes		(\$871.00)
		Triple-Grouser Steel Shoes		
	9560003	27.6" (700mm) TG Steel Shoes		(\$672.00)
		Triple-Grouser Steel Shoes		
Γ	9560005	31.5" (800 mm) TG Steel Shoes		No Charge
		Triple-Grouser Steel Shoes		

LANGUAGE

SD_47083 OPERATOR'S MANUAL

	781981	English Literature		No Charge
	461540	French Canadian Literature		No Charge
	781980	Spanish Literature		No Charge

ADDITIONAL EQUIPMENT CXC

LIVDDALII	10	OPTIONS
TIDRAUL	JI.	OPTIONS

	SD_E6410 AU	XILIARY HYDRAULICS		
	XE6410X	No Optional Hydraulics		(\$11,934.00)



(Ex Works Port of Entry)

461869	MF w/ pressure setting - Prop		No Charge
	Multi-Function Auxiliary Hydraulics with Electronic Pressure		
	Control (EPC)		
	For use with multiple applications:		
	hammers/thumbs/grapples/crushers.		
	Includes in-cab Electronic Pressure Control feature		
	Burney Control for two allows budged in a control of		
	Pressure Control feature allows hydraulic pressure setting		
	from the cab monitor and maintaining pressure settings in		
	memory when multiple tools are used.		
	Joystick Activated with Electronic Proportional Controls		
	Provides single or dual pump, two-way flow,		
	Secondary Low-flow Auxiliary Hydraulics can be added		
	Includes in-cab electronically controlled pressure setting feature		
	Is switchable to single acting flow for hammer application.		
	Notes:		
	1) Not for use with other Auxiliary Hydraulics options, with the		
	exception of Low Flow.		
	2) Heavy duty bucket linkage is standard equipment on		
	C/D series excavators.		
	3) For dealer installed auxiliary hydraulic kits contact:		
	HydrauliCircuit Technology (HCT)		
	(1-888-603-0080 or sales@hctkits.com or www.hctkits.com)		

SD_E6417 SECONDARY AUXILIARY HYDRAULICS

XE	E6417X	No Low Flow Circuit		No Charge
46	1863	Secondary Auxiliary Hydraulics		\$7,647.00
		Secondary Low Flow Auxiliary Hydraulics		
		Provides low-flow for rotation or tilt hydraulic attachments.		
		For use with Standard Boom option 481858		
		Not for use with Offset Boom option 461025		
		Joystick Activated with Electronic Proportional Controls		
		Notes:		
		May be used stand alone or with any Case Excavator Auxiliary Hydraulics option.		
		2) For dealer installed auxiliary hydraulic kits contact:		
		HydrauliCircuit Technology (HCT)		
		(1-888-603-0080 or sales@hctkits.com or www.hctkits.com)		



(Ex Works Port of Entry)

CAB OPTIONS	
OND OF FIGHT	
SD_E5443 CAB GUARD (FOPS)	
XE5443X No FOPS Top Cab Guard	No Charge
481070 FOPS Top Cab Guard	\$1,146.00
SD_E5444 CAB GUARD (FRONT)	
XE5444X No Front Guard	No Charge
461142 Front Guard - Wire Mesh Screen	\$1,326.00
781986 Front Stone Guard (OPG L1)	\$1,973.00
vertical bars (two piece/upper and lower)	
461024 Front Stone Guard (OPG L2)	\$2,324.00
vertical bars (one piece/full length)	
461552 Vandal Guard	\$574.00
Removable steel panels for front windshield	
SD_E5449 RAIN DEFLECTOR	
XE5449X No Rain Deflector	No Charge
461555 Rain Deflector	\$380.00
Not for use with Front grill guard - 2 x 2 mesh option 461142,	
Front rock guard (OPG 1) option 781986, or	
Front rock guard (OPG 2) option 461024.	
	,
SD_E5451 SUN VISOR XE5451X No Sun Visor	No Chargo
461554 Sun Visor	No Charge
401334 Sull VISUI	\$108.00
BUCKETS	
SD_E6300 EXCAVATOR BUCKET(S)	
XE6300X No Bucket	No Charge
Buckets may be ordered using Order Codes listed in the	
Factory Supplied Attachments Section	
, <i>y</i>	-
ADDITIONAL OPTIONS	
SD_02005 ENGINE PRE-CLEANER	
X02005X No Pre-Cleaner	No Charge
488031 Pre-Cleaner Cyclone	\$972.00
	<u> </u>
SD_E5206 TRACK CHAIN GUIDE	
461541 Single Track Chain Guide	No Charge
461143 Triple Track Chain Guide	\$1,996.00
	, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
SD_E6400 MEC/HYD QUICK COUPLER	
XE6400X No Quick Coupler	No Charge

SD_E9874 REFUEL PUMP

481257

XE9874X No Refuel Pump

Refuel Pump

CX300D CRAWLER EXCAVATOR US PRICE LIST (Ex Works Port of Entry) 781128 \$2,764.00 Hydraulic Quick Coupler Ready Does not come with coupler. Must order coupler from Factory **Supplied Attachments section** SD_E9730 SAFETY VALVE XE9730X No Hose Burst Check Valve No Charge \$9,165.00 481064 Hose Burst Check Valve (HBCV) Located on Boom and Arm Cylinder SD_E9739 FULL VIEW CAMERA XE9739X | No max view monitor No Charge 488055 Case Max View Monitor \$1,700.00 SD_E9742 REVERSIBLE FAN XE9742X No Reversible Fan No Charge \$8,709.00 488121 Reversible Fan Variable pitch reversing fan features rotating blades, that provides maximum airflow in either direction when engaged by operator.

No Charge

\$1,296.00



(Ex Works Port of Entry)

Factory Supplied Attachments

Order Cod	de Description	Weight	Factory Data	List Price
CASE Machine	Guidance			
9045601		26 LB		\$18,800.00
	- Option available to Precision-Certified Dealers only.			
	 Expect extended lead times when ordering this option Contact your CASE representative for more informati 			
	 Attachment calibration required upon delivery. Display will arrive in case located in cab, and will need mounted upon dealer arrival. 	d to be		
9045601	·	43 LB		\$64,090.00
	- Option available to Precision-Certified Dealers only.			
	 Expect extended lead times when ordering this option Contact your CASE representative for more informati Attachment calibration required upon delivery. Display and GNSS antennas will arrive in case locate and will need to be mounted upon dealer arrival. Radio Antenna required- Purchased separately throug CNH Parts. 	on. d in cab,		
	- For 900MHz Radio/Antenna order: LG916750 - CCD21, Satel M3-TR9 Radio iCG80 and L827067 - CA26, Antenna, for CCD15 and 4G moder - For 4xx MHz Antenna order: LG916751 - CCD22, Satel TR4+Radio iCG80 and Order 1 of the following: LG805281 CA12, Radio Antenna 406-440MHz or LG805282 CA13, Radio Antenna, 430-480MHz.			
Case Pin On B	uckets			
8440425	4 36" Heavy-Duty Pin-On Bucket with 5 teeth (1.36 cu. yd.)			\$6,357.00
8440425	42" Heavy-Duty Pin-On Bucket with 5 teeth (1.62 cu. yd.)			\$6,824.00
8440425				\$7,506.00
8440425				\$7,208.00
8440425				\$7,642.00
8440425				\$8,405.00
8440426	· · · · · · · · · · · · · · · · · · ·	3,649 LB		\$9,246.00
8440426				\$7,445.00
8440426				\$7,998.00

	84404265	48" Severe-Duty Pin-On Bucket with 6 teeth (1.88 cu. yd.)		\$8,798.00
	84404266	60" Ditching Pin-On Bucket (1.71 cu yd.)		\$5,693.00
	84404267	72" Ditching Pin-On Bucket (2.09 cu yd.)		\$6,068.00
Cas	se Coupler Buck	· · · · · · · · · · · · · · · · · · ·		
	84404268	36" Heavy-Duty Coupler Bucket with 5 teeth (1.26 cu. yd.)		\$7,615.00
	84404269	42" Heavy-Duty Coupler Bucket with 5 teeth (1.52 cu. yd.)		\$8,375.00
	84404270	48" Heavy-Duty Coupler Bucket with 6 teeth (1.78 cu. yd.)		\$9,213.00
	84404272	54" Heavy-Duty Coupler Bucket with 6 teeth (2.03 cu. yd.)		\$10,133.00
Cou	ıpler			
	47848465	Multi-Fit S Hyd.Pin Grabber Coupler Kit	1,009 LB	\$8,414.00
Dire	ect Link Thumb			
	47609082	KIT, THUMB, HYD, 3-TINE, use with bucket only (3 tine)	1,235 LB	\$10,896.00
	47609084	KIT, THUMB, HYD, 4-TINE, use with bucket only (4 tine)	1,275 LB	\$11,540.00
	47609085	KIT, THUMB, HYD, 3-TINE, use with bucket and coupler (3 tine)	1,380 LB	\$11,199.00
	47609086	KIT, THUMB, HYD, 4-TINE, use with bucket and coupler (4 tine)	1,415 LB	\$11,740.00
Pro	gressive Link T	humb		
	47609119	KIT, THUMB, PROG LINK, 3- use with bucket only (3 tine)	1,760 LB	\$13,136.00
	47609120	KIT, THUMB, PROG LINK, 4- use with bucket only (4 tine)	1,800 LB	\$13,380.00
	47609121	KIT, THUMB, PROG LINK, 3- use with bucket and coupler (3 tine)	1,905 LB	\$13,439.00
	47609122	Progressive Link Thumb Kit with Coupler use with bucket and coupler (4 tine)	1,940 LB	\$13,899.00

(This page intentionally left blank)



Engine Idle / Fuel Economy System:

FUEL ECONOMY SYSTEMS:

CX350D CRAWLER EXCAVATOR US PRICE LIST

(Ex Works Port of Entry) Standard Equipment

ENGINE: Isuzu AO-6HK1X Tier 4 Final Certified Selective Catalytic Reduction (SCR) Diesel Oxidation Catalyst (DOC) Cooled Exhaust Gas Recirculation (CEGR) Turbocharged/air cooled intercooler Horsepower: Net 268 (200 kW) @ 1900 RPM Electronic fuel injection High pressure common rail system Neutral safety start Auto-engine warm up Glow-plug pre-heat Fuel Economy Assist System (FEA) Engine Protection Feature (EPF) Dual-stage fuel filtration Dual element air filter Remote oil filter Drain for fuel tank Remote engine oil drain 500-hour engine oil change interval 24-volt system Engine oil sample port Battery disconnect switch Air pre-cleaner (Cyclone) High ambient temperature cooling package Emergency engine stop External Fuel and DEF gauges Fan housing Fuel cooler Fuel filter restriction indicator

Fuel shut-off valve

protective screen

Radiator, oil cooler, intercooler -

Idle start

Auto-idle One-touch idle Auto-Idle shut-down BEC- Boom Economy Control AEC- Auto Economy Control SWC- Swing Relief Control SSC- Spool Stroke Control HYDRAULICS: Auto power boost Auto swing priority Arm speed assistance (2 pump flow) Auxiliary flow control Auxiliary valve Boom speed assistance (2 pump flow) Bucket curl assist Control levers pre-wired for auxiliary hydraulics Electronically controlled hydraulic pumps Holding valve (Boom and Arm) Fire wall Hydraulic filter restriction indicator Neutral pump de-stroke Oil cooler Power save Pump stand-by pressure Auto travel speed change Selectable work modes Free swing - switch activated Hydraulic oil sample port Control pattern selector Pre-set auxiliary pump settings Auxiliary valve 5,000-hour hydraulic oil change interval 1,000-hour hydraulic filter change interval SAHR brake



(Ex Works Port of Entry) Standard Equipment

UPPER STRUCTURE:

ISO mirrors (3)

Cab viscous-mounts (fluid)

Upper mounted work light (70 watt)

Swivel guard belly pan

Center cover (over main CV)

Fuel tank belly pan

Handrail (RH access)

ISO guard rails

Lifting eyes for counterweight

Lockable fuel cap, service doors and

tool box

ATTACHMENTS:

Boom- 21 ft. 2 in. (6.45 m)

Arm-10 ft. 8 in. (3.25 m)

Heavy-duty bucket linkage

Boom mounted work light (70 watt)

Auxiliary pipe brackets

Centralized grease fittings

Attachment cushion valve

Arm and boom regeneration

Bucket anti-clatter device

Chrome pins

Easy Maintenance System (EMS)

bushings

Teardrop pin retention keepers

OPERATOR STATION:

ROPS protection

FOPS cab (Level 1)

Pressurized cab

Face vent

Cab lights (2)

Interior dome light

One-touch lock front window

One piece window (right)

Safety glass windows

Gate lock hydraulic activation

Emergency exit and hammer

Clear (polycarbonate) roof window w/

sunshade

OPERATOR STATION (continued):

AC/heat/defrost w/ auto climate

control

LED Color monitor— 7 in (180 mm)

26 selectable languages for monitor

On-board diagnostic system

10 programmable attachments settings

on monitor - 5 single flow, 5 dual

flow

Seatbelt-3 in. (76 mm)

Heated high-back cloth seat with air

suspension and 650 tilt adjustment

Sliding seat - 3.54 in. (90 mm)

Adjustable armrests

Tilting consoles- 4-position

Sliding cockpit - 3.15 in. (80 mm)

Low-effort joystick controls

Controls pre-wired for auxiliary

Single pedal travel

Straight travel

AM/FM radio w/ antenna, 2 speakers

and Bluetooth capabilities

Aux-in port for personal electronics

Radio mute switch (joystick)

Rear-view & Side-view camera

Anti-theft system (start code system)

Rubber floormat

12-volt electric outlet

24-volt cigarette lighter

Windshield wiper/washer

Cup holder

Storage compartments

Warm/cool storage compartment

Travel alarm with cancel switch

Ignition keys

One key start & lock-up

Cab filter (external)

Cab handrails

Operator's manual



(Ex Works Port of Entry) Standard Equipment

UNDERCARRIAGE:

Long undercarriage
31.5 in. (800 mm) steel shoes, triple
semi-grouser
Full overlap turntable bearing tub
Double track chain guides
Hydraulic track adjustment
Sealed link chain
Steps
Carbody belly pan (swivel guard)
X-pattern carbody
Lashing points (tie downs)

EXTRA FILTER KIT:
Engine oil filter
Filter wrench

Fuel filters
Grease gun
Green plug oil drain hose for
engine oil drain
Hydraulic return filter
Pilot circuit hydraulic filter

CASE ProCare - Full Machine Protection
Factory Warranty (3-yr/3000-hr),
Planned Maintenance (3-yr/2000-hr)
and SiteWatch™ Telematics
CASE SiteWatch™ Telematics
Includes hardware and a 3-yr
advanced data subscription



(Ex Works Port of Entry) Models

COMMERCIAL MODEL	Weight	Factory Data	List Price
CX350D STD	82,483 LBS		\$501,020.00



(Ex Works Port of Entry)

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price

LIGHTS

SD_E5408 WORKING LIGHTS

	488134	Halogen Working Lights		No Charge
	488135	LED Working Lights		\$2,754.00
		8 LED lights:		
		2 LED light are mounted on the front (1 on boom, 1 on house)		
		2 LED lights are mounted on the rear		
		(above the rear view camera)		
		1 LED light mounted on each side (2)		
		2 LED lights mounted on the top of the cab		

BOOMS

SD_E5311 BOOM

	481858	Std Boom		No Charge
		21'2" (6.45 M) Standard Boom		
	461543	Heavy-Duty Boom		\$2,639.00
		21'2" (6.45 M)		
	781917	No Boom		(\$7,800.00)
		Less boom, hoist and arm cylinders and plumbing.		
		Boom-foot and cylinder pins are provided.		

ARMS

SD_E5320 ARM/DIPPERSTICK

481245	10' 8" (3.25 m) Std Arm		No Charge
	For use with 21'2" Standard Boom (option 481858)		
781184	13'3" (4.03 m) Std Arm		\$2,769.00
	For use with 21'2" Standard Boom (option 481858)		
461546	8'8" (2.63 m) HD Arm		\$139.00
	For use with Heavy-Duty Boom option 461543		
461545	10'8" (3.25 m) HD Arm		\$2,279.00
	For use with Heavy-Duty Boom option 461543		
XE5320X	No Arm/Dipperstick		(\$5,200.00)
	Less arm, bucket cylinder and linkage.		

(Ex Works Port of Entry)

TRACK SHOES

SD_E5199 TRACK SHOES

	9560003	27.6" (700mm) TG Steel Shoes		(\$780.00)
L		Triple-Grouser Steel Shoes		
	9560005	31.5" (800 mm) TG Steel Shoes		No Charge
L		Triple-Grouser Steel Shoes		
	9560006	33.5" (850 mm) TG Steel Shoes		\$680.00
L		Triple-Grouser Steel Shoes		
	9560049	27.6" (700 mm) SG Steel Shoes		\$4,993.00
		Single-Grouser Steel Shoes		

LANGUAGE

SD_47083 OPERATOR'S MANUAL

	781981	English Literature		No Charge
	461540	French Canadian Literature		No Charge
	781980	Spanish Literature		No Charge

ADDITIONAL EQUIPMENT CXC

HYDRAULIC OPTIONS

S	D_E64	10	ΑU	XILI	AR	Υŀ	JYI	DR.	ΑUI	LICS	;	
									-			

	XE6410X	No Optional Hydraulics		(\$12,571.00)

(Ex Works Port of Entry)

461869	MF w/ pressure setting - Prop		No Charge
	Multi-Function Auxiliary Hydraulics with Electronic Pressure		
	Control (EPC)		
	For use with multiple applications:		
	hammers/thumbs/grapples/crushers.		
	Includes in-cab Electronic Pressure Control feature		
	Pressure Control feature allows hydraulic pressure setting		
	from the cab monitor and maintaining pressure settings in		
	memory when multiple tools are used.		
	Joystick Activated with Electronic Proportional Controls		
	Provides single or dual pump, two-way flow,		
	Secondary Low-flow Auxiliary Hydraulics can be added		
	Includes in-cab electronically controlled pressure setting feature		
	Is switchable to single acting flow for hammer application.		
	Notes:		
	1) Not for use with other Auxiliary Hydraulics options, with the		
	exception of Low Flow.		
	2) Heavy duty bucket linkage is standard equipment on		
	C/D series excavators.		
	3) For dealer installed auxiliary hydraulic kits contact:		
	HydrauliCircuit Technology (HCT)		
	(1-888-603-0080 or sales@hctkits.com or www.hctkits.com)		

SD_E6417 SECONDARY AUXILIARY HYDRAULICS

XE6417X	No Low Flow Circuit		No Charge
461863	Secondary Auxiliary Hydraulics		\$9,285.00
	Secondary Low Flow Auxiliary Hydraulics		
	Provides low-flow for rotation or tilt hydraulic attachments.		
	Not for use with Offset Boom option 461025		
	Joystick Activated with Electronic Proportional Controls		
	Notes:		
	May be used stand alone or with any Case Excavator Auxiliary Hydraulics option.		
	For dealer installed auxiliary hydraulic kits contact:		
	HydrauliCircuit Technology (HCT)		
	(1-888-603-0080 or sales@hctkits.com or www.hctkits.com)		

CAB OPTIONS

	SD_E5443 CAB GUARD (FOPS)		
Г	XE5443X No FOPS Top Cab Guard		No Charge



		(Ex Works Port of Entry)	
	481070	FOPS Top Cab Guard	\$1,146.00
_			
T		AB GUARD (FRONT) No Front Guard	No Charre
	461142	Front Guard - Wire Mesh Screen	No Charge \$1,326.00
	781986	Front Stone Guard (OPG L1)	\$1,973.00
	701900	vertical bars (two piece/upper and lower)	\$1,973.00
	461024	Front Stone Guard (OPG L2)	\$2,324.00
	101021	vertical bars (one piece/full length)	Ψ2,02 1.00
	461552	Vandal Guard	\$574.00
		Removable steel panels for front windshield	
-			
S	D_E5449 RA	NIN DEFLECTOR	
	XE5449X	No Rain Deflector	No Charge
	461555	Rain Deflector	\$380.00
		Not for use with Front grill guard - 2 x 2 mesh option 461142,	
		Front rock guard (OPG 1) option 781986, or	
		Front rock guard (OPG 2) option 461024.	
0	D E5454 OL	INLVIOOD	
T 5	D_E5451 SU	No Sun Visor	No Charre
	461554	Sun Visor	No Charge \$108.00
	101001	Out vice	ψ100.00
BUC	KETS		
	-		
S	SD_E6300 EX	CAVATOR BUCKET(S)	
	XE6300X	No Bucket	No Charge
		Buckets may be ordered using Order Codes listed in the	
		Factory Supplied Attachments Section	
ADD	ITIONAL OPTI	IONS	
_			
S	SD_E5448 CA		No Observe
		No Catwalk	No Charge
	461553	Catwalk - Left and Right Sides	\$2,110.00
		(Note: catwalk is not compliant with ISO standards)	
9	CD E6400 ME	EC/HYD QUICK COUPLER	
Т	XE6400X		No Charge
	781128	Hydraulic Quick Coupler Ready	\$2,909.00
	701120	Does not come with coupler. Must order coupler from Factory	Ψ2,300.00
		Supplied Attachments section	
	ı		<u>'</u>
S	SD_E9730 SA	FETY VALVE	
	XE9730X		No Charge
	481064	Hose Burst Check Valve (HBCV)	\$9,501.00
1	Ī	1 1	

Located on Boom and Arm Cylinder



(Ex Works Port of Entry)

SD_E9739 FULL VIEW CAMERA

L	XE9739X	No max view monitor		No Charge
	488055	Case Max View Monitor		\$1,700.00
	-		•	

	SD	E9874	REFUEL	PUMP
--	----	-------	--------	------

	XE9874X	No Refuel Pump		No Charge
	481257	Refuel Pump		\$1,296.00



(Ex Works Port of Entry)

Factory Supplied Attachments

	Order Code	Description	Weight	Factory Data	List Price
CAS	E Machine Guid	lance			
	90456016	OEM-Fit 2D Machine Guidance Sys Leica Option available to Precision-Certified Dealers only. Expect extended lead times when ordering this option. Contact your CASE representative for more information. Attachment calibration required upon delivery. Display will arrive in case located in cab, and will need to be	26 LB		\$18,800.00
	90456015	mounted upon dealer arrival. OEM-Fit 3D Machine Guidance Sys Leica Option available to Precision-Certified Dealers only. Expect extended lead times when ordering this option. Contact your CASE representative for more information. Attachment calibration required upon delivery. Display and GNSS antennas will arrive in case located in cab, and will need to be mounted upon dealer arrival. Radio Antenna required- Purchased separately through CNH Parts. For 900MHz Radio/Antenna order: LG916750 - CCD21, Satel M3-TR9 Radio iCG80 and L827067 - CA26, Antenna, for CCD15 and 4G modem. For 4xx MHz Antenna order: LG916751 - CCD22, Satel TR4+Radio iCG80 and Order 1 of the following: LG805281 CA12, Radio Antenna 406-440MHz or LG805282 CA13, Radio Antenna, 430-480MHz.	43 LB		\$64,090.00
Case	84404288	42" Heavy-Duty Coupler Bucket			\$9,389.00
	84404289	with 5 teeth (1.73 cu. yd.) 48" Heavy-Duty Coupler Bucket with 5 teeth (2.03 cu. yd.)			\$10,077.00
	84404290	54" Heavy-Duty Coupler Bucket with 6 teeth (2.33 cu. yd.)			\$10,950.00
Case	e Pin-On Bucket	ts.			
	84404275	36" Heavy-Duty Pin-On Bucket with 4 teeth (1.47 cu. yd.)			\$7,321.00
	84404276	42" Heavy-Duty Pin-On Bucket with 5 teeth (1.75 cu. yd.)			\$7,875.00
	84404277	48" Heavy-Duty Pin-On Bucket with 5 teeth (2.03 cu. yd.)			\$8,154.00
	84405399	60" Heavy-Duty Pin-On Bucket with 6 teeth (2.60 cu. yd.)			\$10,781.00
	84404278	42" HD Hi-Capacity Pin-On Bucket with 5 teeth (2.03 cu. yd.)			\$9,168.00

47848466

Multi-Fit S Hyd.Pin Grabber Coupler Kit

2,100 LB

\$9,567.00

CX350D CRAWLER EXCAVATOR US PRICE LIST

(Ex Works Port of Entry)

	(Ex Works Po	ort of Entry)	
84404279	48" HD Hi-Capacity Pin-On Bucket with 5 teeth (2.36 cu. yd.)		\$9,784.00
84404280	54" HD Hi-Capacity Pin-On Bucket with 6 teeth (2.69 cu. yd.)		\$10,461.00
84404282	36" Severe-Duty Pin-On Bucket with 4 teeth (1.47 cu. yd.)		\$8,234.00
84404284	42" Severe-Duty Pin-On Bucket with 5 teeth (1.75 cu. yd.)		\$9,206.00
84404286	48" Severe-Duty Pin-On Bucket with 5 teeth (2.03 cu. yd.)		\$10,033.00
ect Link Thumb			
47609087	KIT, THUMB, HYD, 3-TINE, use with bucket only (3 tine)	1,365 LB	\$11,840.00
47609088	KIT, THUMB, HYD, 4-TINE, use with bucket only (4 tine)	1,425 LB	\$12,836.00
47609089	KIT, THUMB, HYD, 3-TINE, use with bucket and coupler (3 tine)	1,445 LB	\$12,280.00
47609090	KIT, THUMB, HYD, 4-TINE, use with bucket and coupler (4 tine)	1,505 LB	\$13,323.00
ogressive Link 1	Thumb		
47609123	KIT, THUMB, PROG LINK, 3- use with bucket only (3 tine)	1,890 LB	\$15,080.00
47609124	KIT, THUMB, PROG LINK, 4- use with bucket and coupler (3 tine)	1,950 LB	\$15,376.00
47609125	KIT, THUMB, PROG LINK, 3- use with bucket only (4 tine)	1,970 LB	\$15,320.00
47609126	Progressive Link Thumb Kit with Coupler	2,030 LB	\$15,963.00

(This page intentionally left blank)



(Ex Works Port of Entry) Standard Equipment

ENGINE:

Isuzu AO-6HK1X

Tier 4 Final Certified

Selective Catalytic Reduction (SCR)

Diesel Oxidation Catalyst (DOC)

Cooled Exhaust Gas Recirculation

(CEGR)

Turbocharged/air cooled intercooler

Horsepower:

Net 268 (200 kW) @ 1900 RPM

Electronic fuel injection

High pressure common rail system

Neutral safety start

Auto-engine warm up

Glow-plug pre-heat

Fuel Economy Assist System (FEA)

Engine Protection Feature (EPF)

Dual-stage fuel filtration

Dual element air filter

Remote oil filter

Drain for fuel tank

Remote engine oil drain

24-volt system

Engine oil sample port

Battery disconnect switch

Air pre-cleaner (Cyclone)

High ambient temperature cooling

package

Emergency engine stop

External Fuel and DEF gauges

Fan housing

Fuel cooler

Fuel filter restriction indicator

Fuel shut-off valve

Idle start

Radiator, oil cooler, intercooler -

protective screen

FUEL ECONOMY SYSTEMS:

Engine Idle / Fuel Economy System:

Auto-idle

One-touch idle

Auto-Idle shut-down

BEC- Boom Economy Control

AEC- Auto Economy Control

SWC- Swing Relief Control

SSC- Spool Stroke Control

HYDRAULICS:

Auto power boost

Auto swing priority

Arm speed assistance (2 pump flow)

Auxiliary flow control

Auxiliary valve

Boom speed assistance (2 pump flow)

Bucket curl assist

Control levers pre-wired for auxiliary

hydraulics

Electronically controlled hydraulic

pumps

Holding valve (Boom and Arm)

Fire wall

Hydraulic filter restriction indicator

Neutral pump de-stroke

Oil cooler

Power save

Pump stand-by pressure

Auto travel speed change

Selectable work modes

Free swing - switch activated

Hydraulic oil sample port

Control pattern selector

Pre-set auxiliary pump settings

Auxiliary valve

SAHR brake



(Ex Works Port of Entry) Standard Equipment

UPPER STRUCTURE:

ISO mirrors (3)

Cab viscous-mounts (fluid)

Upper mounted work light (70 watt)

Swivel guard belly pan

Center cover (over main CV)

Fuel tank belly pan

Handrail (RH access)

ISO guard rails

Lifting eyes for counterweight

Lockable fuel cap, service doors and

tool box

ATTACHMENTS:

Boom- 35 ft. 4 in. (10.78 m)

Arm-25 ft. 0 in. (7.63 m)

Heavy-duty bucket linkage

Boom mounted work light (70 watt)

Auxiliary pipe brackets

Centralized grease fittings

Attachment cushion valve

Arm and boom regeneration

Bucket anti-clatter device

Chrome pins

Easy Maintenance System (EMS)

bushings

Teardrop pin retention keepers

OPERATOR STATION:

ROPS protection

FOPS cab (Level 1)

Pressurized cab

Face vent

Cab lights (2)

Interior dome light

One-touch lock front window

One piece window (right)

Safety glass windows

Gate lock hydraulic activation

Emergency exit and hammer

Clear (polycarbonate) roof window w/

sunshade

OPERATOR STATION (continued):

AC/heat/defrost w/ auto climate

control

LED Color monitor— 7 in (180 mm)

26 selectable languages for monitor

On-board diagnostic system

 $10 \ \mathrm{programmable}$ attachments settings

on monitor - 5 single flow, 5 dual

flow

Seatbelt- 3 in. (76 mm)

Heated high-back cloth seat with air

suspension and 650 tilt adjustment

Sliding seat - 3.54 in. (90 mm)

Adjustable armrests

Tilting consoles- 4-position

Sliding cockpit - 3.15 in. (80 mm)

Low-effort joystick controls

Controls pre-wired for auxiliary

Single pedal travel

Straight travel

AM/FM radio w/ antenna, 2 speakers

and Bluetooth capabilities

Aux-in port for personal electronics

Radio mute switch (joystick)

Rear-view & Side-view camera

Anti-theft system (start code system)

Rubber floormat

12-volt electric outlet

24-volt cigarette lighter

Windshield wiper/washer

Cup holder

Storage compartments

Warm/cool storage compartment

Travel alarm with cancel switch

Ignition keys

One key start & lock-up

Cab filter (external)

Cab handrails

Operator's manual



(Ex Works Port of Entry) Standard Equipment

UNDERCARRIAGE:

Long undercarriage
31.5 in. (800 mm) steel shoes, triple
semi-grouser
Full overlap turntable bearing tub
Double track chain guides
Hydraulic track adjustment
Sealed link chain
Steps
Carbody belly pan (swivel guard)
X-pattern carbody
Lashing points (tie downs)

EXTRA FILTER KIT:
Engine oil filter
Filter wrench

Fuel filters
Grease gun
Green plug oil drain hose for
engine oil drain
Hydraulic return filter
Pilot circuit hydraulic filter

CASE ProCare - Full Machine Protection
Factory Warranty (3-yr/3000-hr),
Planned Maintenance (3-yr/2000-hr)
and SiteWatch™ Telematics
CASE SiteWatch™ Telematics
Includes hardware and a 3-yr
advanced data subscription



(Ex Works Port of Entry) Models

COMMERCIAL MODEL	Weight	Factory Data	List Price
CX350D LR	88,200 LBS		\$538,897.00

461540 French Canadian Literature

CX350D LONG REACH CRAWLER EXCAVATOR (LR) US PRICE LIST

(Ex Works Port of Entry) Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
LIGHTS				
	ORKING LIGHTS		1	N. Ohama
488134 488135	Halogen Working Lights	+		No Charge \$2,754.00
400133	LED Working Lights 8 LED lights:			\$2,754.00
	2 LED lights are mounted on the front (1 on boom, 1 on house)			
	2 LED lights are mounted on the rear			
	(above the rear view camera)			
	1 LED light mounted on each side (2)			
	2 LED lights mounted on the top of the cab			
	2 LLD lights mounted on the top of the tab	1		
BOOMS				
2000				
SD E5311 BO	OM			
461029	Standard Long Reach Boom			No Charge
		•	•	
ARMS				
ARMS				
ARMS				
	M/DIPPERSTICK			
	M/DIPPERSTICK 7,60 M ARM			No Charge
SD_E5320 AR		L		No Charge
SD_E5320 AR 488194				No Charge
SD_E5320 AR				No Charge
SD_E5320 AR 488194				No Charge
SD_E5320 AR 488194	7,60 M ARM			No Charge
SD_E5320 AR	7,60 M ARM			No Charge No Charge
SD_E5320 AR	7,60 M ARM ACK SHOES			
SD_E5320 AR	ACK SHOES 31.5" (800 mm) TG Steel Shoes			
SD_E5320 AR	ACK SHOES 31.5" (800 mm) TG Steel Shoes Triple-Grouser Steel Shoes			No Charge
SD_E5320 AR	ACK SHOES 31.5" (800 mm) TG Steel Shoes Triple-Grouser Steel Shoes 33.5" (850 mm) TG Steel Shoes			No Charge
SD_E5320 AR	ACK SHOES 31.5" (800 mm) TG Steel Shoes Triple-Grouser Steel Shoes 33.5" (850 mm) TG Steel Shoes			No Charge
SD_E5320 AR	ACK SHOES 31.5" (800 mm) TG Steel Shoes Triple-Grouser Steel Shoes 33.5" (850 mm) TG Steel Shoes			No Charge
SD_E5320 AR	ACK SHOES 31.5" (800 mm) TG Steel Shoes Triple-Grouser Steel Shoes 33.5" (850 mm) TG Steel Shoes			No Charge
SD_E5320 AR	ACK SHOES 31.5" (800 mm) TG Steel Shoes Triple-Grouser Steel Shoes 33.5" (850 mm) TG Steel Shoes			No Charge
SD_E5320 AR	ACK SHOES 31.5" (800 mm) TG Steel Shoes Triple-Grouser Steel Shoes 33.5" (850 mm) TG Steel Shoes Triple-Grouser Steel Shoes			No Charge

No Charge

Case Max View Monitor

CX350D LONG REACH CRAWLER EXCAVATOR (LR) US PRICE LIST

(Ex Works Port of Entry)

ADDITIONAL E	EQUIPMENT CXC	
CAB OPTIONS		
SD_E5443	CAB GUARD (FOPS)	
XE544	13X No FOPS Top Cab Guard	No Charge
48107	70 FOPS Top Cab Guard	\$1,146.00
00 55444	CAR CHARR (FRONT)	
	CAB GUARD (FRONT)	No Observe
	14X No Front Guard	No Charge
46114		\$1,326.00
78198	,	\$1,973.00
40400	vertical bars (two piece/upper and lower)	000000
46102	,	\$2,324.00
40455	vertical bars (one piece/full length)	0574.00
46155		\$574.00
	Removable steel panels for front windshield	
SD F5440	RAIN DEFLECTOR	
	49X No Rain Deflector	No Charge
46155		\$380.00
40133		\$380.00
	Not for use with Front grill guard - 2 x 2 mesh option 461142,	
	Front rock guard (OPG 1) option 781986, or	
	Front rock guard (OPG 2) option 461024.	
SD F5451	SUN VISOR	
	51X No Sun Visor	No Charge
46155		\$108.00
		, , , , , , , , , , , , , , , , , , , ,
BUCKETS		
SD_E6300	EXCAVATOR BUCKET(S)	
XE630	00X No Bucket	No Charge
ADDITIONAL C	PTIONS	
SD_E5448	CATWALK	
XE544	48X No Catwalk	No Charge
46155	3 Catwalk - Left and Right Sides	\$2,110.00
	(Note: catwalk is not compliant with ISO standards)	
	FULL VIEW CAMERA	
XE973	39X No max view monitor	No Charge

\$1,700.00

(Ex Works Port of Entry)

SD_E9874 REFUEL PUMP

	XE9874X	No Refuel Pump		No Charge
Ī	481257	Refuel Pump		\$1,296.00



(Ex Works Port of Entry) Factory Supplied Attachments

Order Code	Description	Weight	Factory Data	List Price
84404166	24" Heavy-Duty Pin-On Bucket with 4 teeth (.50 cu. yd.)			\$3,997.00
84404167	30" Heavy-Duty Pin-On Bucket with 4 teeth (.84 cu. yd.)			\$4,475.00
84404168	36" Heavy-Duty Pin-On Bucket with 5 teeth (1.03 cu. yd.)			\$4,884.00
84404185	60" Ditching Pin-On Bucket (1.02 cu yd.)			\$3,620.00
84404186	72" Ditching Pin-On Bucket(1.22 cu. yd.)			\$3,921.00



(Ex Works Port of Entry) Standard Equipment

ENGINE:

Isuzu AQ-6UZ1X

Tier 4 Final Certified

Selective Catalytic Reduction - SCR

Diesel Oxidation Catalyst - DOC

Cooled Exhaust Gas Recirculation -

CEGR

Turbocharged/air cooled intercooler

Horsepower:

Net 362 (270 kW) @ 2000 RPM

Electronic fuel injection

High pressure common rail system

Neutral safety start

Auto-engine warm up

Glow-plug pre-heat

Fuel Economy Assist System - FEA

Engine Protection Feature - EPF

Dual-stage fuel filtration

Dual element air filter

Remote oil filter

Drain for fuel tank

Remote engine oil drain

500-hour engine oil change interval

24 Volt system

Engine oil sample port

Battery disconnect switch

Air pre-cleaner - Cyclone

High ambient temperature cooling

package

Emergency engine stop

External Fuel and DEF gauges

Fan housing

Fuel cooler

Fuel filter restriction indicator

Fuel shut-off valve

Idle start

Radiator, oil cooler, intercooler -

protective screen

FUEL ECONOMY SYSTEMS:

Engine Idle/Fuel Economy System:

Auto-idle

One-touch idle

Auto-idle shut-down

BEC - Boom Economy Control

AEC - Auto Economy Control

SWC - Swing Relief Control

SSC - Spool Stroke Control

HYDRAULICS:

Auto power boost

Auto swing priority

Arm speed assistance - 2 pump flow

Auxiliary flow control

Auxiliary valve

Boom speed assistance - 2 pump flow

Bucket curl assist

Control levers pre-wired for auxiliary

hydraulics

Electronically controlled hydraulic

pumps

Holding valve - Boom and Arm

Fire wall

Hydraulic filter restriction indicator

Neutral pump de-stroke

Oil cooler

Power save

Pump stand-by pressure

Auto travel speed change

Selectable work modes

Free swing - switch activated

Hydraulic oil sample port

Control pattern selector

Pre-set auxiliary pump settings

Auxiliary valve

5,000-hour hydraulic oil change interval

1,000-hour hydraulic filter change

interval

SAHR brake



OPERATOR ENVIRONMENT (cont'd):

CX490D CRAWLER EXCAVATOR US PRICE LIST

(Ex Works Port of Entry) Standard Equipment

UPPER STRUCTURE:

ISO mirrors - 3
Cab viscous-mounts (fluid)
Upper mounted work light - 70 watt
Swivel guard belly pan
Center cover - over main CV
Fuel tank belly pan
Handrail - RH access
ISO guard rails
Lifting eyes for counterweight
Lockable fuel cap, service doors and

ATTACHMENTS:

toolbox

Arm - 8 ft 4 in (2.53 m)

Heavy-duty bucket linkage

Boom mounted work light - 70 watt

Auxiliary pipe brackets

Centralized grease fittings

Attachment cushion valve

Arm and boom regeneration

Bucket anti-clatter device

Chrome pins

Easy Maintenance System (EMS)

bushings

Teardrop pin retention keepers

Boom - 21 ft 6 in (6.55 m)

OPERATOR ENVIRONMENT:

ROPS protection FOPS cab top guard - Level 1 Pressurized cab Face vent Cab lights - 2 Interior dome light One-touch lock front window One piece window - right Safety glass windows Gate lock hydraulic activation Emergency exit and hammer Clear polycarbonate roof window with sunshade AC/heat/defrost with auto climate control LED Color monitor - 7 in (180 mm)

26 selectable languages for monitor On-board diagnostic system 10 programmable attachments settings on monitor - 5 single flow, 5 dual flow Seat belt - 3 in (76 mm) Heated high-back cloth seat with air suspension and 65° tilt adjustment Sliding seat - 3.54 in (90 mm) Adjustable armrests Tilting consoles - 4-position Sliding cockpit - 3.15 in (80 mm) Low-effort joystick controls Controls pre-wired for auxiliary Single pedal travel Straight travel AM/FM radio with antenna, 2 speakers and Bluetooth capabilities Aux-in port for personal electronics Radio mute switch - joystick Rear-view camera Anti-theft system - start code system Rubber floormat 12 Volt electric outlet 24 Volt cigarette lighter Windshield wiper/washer Cup holder Storage compartments Warm/cool storage compartment Travel alarm with cancel switch Ignition keys One key start & lock-up Cab filter - external Cab handrails Operator's manual



(Ex Works Port of Entry) Standard Equipment

UNDERCARRIAGE:

Long undercarriage
35.4 in (900 mm) steel shoes,
 triple semi-grouser
Full overlap turntable bearing tub
Double track chain guides
Hydraulic track adjustment
Sealed link chain
Steps
Carbody belly pan - swivel guard
X-pattern carbody
Lashing points - tie downs
Extra Filter Kit:
 Engine oil filter
 Filter wrench
 Fuel filters

Grease gun
Green plug oil drain hose for engine
oil drain
Hydraulic return filter
Pilot circuit hydraulic filter

CASE ProCare - Full Machine Protection Factory Warranty (3-yr/3000-hr), Planned Maintenance (3-yr/2000-hr) and SiteWatch™ Telematics
CASE SiteWatch™ Telematics
Includes hardware and a 3-yr advanced data subscription



(Ex Works Port of Entry) Models

COMMERCIAL MODEL	Weight	Factory Data	List Price
CX490D STD	109,300 LB		\$711,582.00
CX490D RTC	112,400 LB		\$742,647.00



(Ex Works Port of Entry)

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
			-	

LIGHTS

SD_E5408 WORKING LIGHTS

	488134	Halogen Working Lights		No Charge
	488135	LED Working Lights		\$3,100.00
		8 LED light and 1 side camera:		
		2 LED light are mounted on the front (1 on boom, 1 on house)		
		2 LED lights are mounted on the rear		
		(above the rear view camera)		
		1 LED light mounted on each side (2)		
		2 LED lights mounted on the top of the cab		

BOOMS

SD_E5311 BOOM

	481858	Std Boom		No Charge
		22'11" (6.98 M) Standard Boom		
		For use with CX470C (Standard and RTC) Commercial Model		
	781917	No Boom		(\$16,186.00)
		Less boom, hoist and arm cylinders and plumbing.		
		Boom-foot and cylinder pins are provided.		

ARMS

SD_E5320 ARM/DIPPERSTICK

461549	11'1" (3.38 M) Heavy-duty Arm		No Charge
	For use with 22'11" Standard Boom (option 481858)		
461548	8'2" (2.50 m) HD Arm		(\$108.00)
	For use with 22'11" Standard Boom (option 481858)		
781184	13'3" (4.03 m) Std Arm		\$671.00
	For use with 22'11" Standard Boom (option 481858)		
461544	15'11" (4.85 M) Standard Arm		\$3,137.00
	For use with 22'11" Standard Boom (option 481858)		
XE5320X	No Arm/Dipperstick		(\$9,542.00)
	Less arm, bucket cylinder and linkage		

SD_E6410 AUXILIARY HYDRAULICS

XE6410X No Optional Hydraulics



CX490D CRAWLER EXCAVATOR US PRICE LIST

(Ex Works Port of Entry)

TRACK SHOES		
SD_E5199 TR	RACK SHOES	
9560007	35.4" (900 mm) Steel Shoes	No Charge
	Triple-Grouser Steel Shoes	
9560004	29.5"(750mm)Steel Shoes - 2bar	(\$1,079.00)
	Triple-Grouser Steel Shoes	
LANGUAGE		
SD_47083 OF	PERATOR'S MANUAL	
781981	English Literature	No Charge
461540	French Canadian Literature	No Charge
781980	Spanish Literature	No Charge
	<u> </u>	
ADDITIONAL EQU	JIPMENT CXC	
HYDRAULIC OPTI	ONS	

(\$13,434.00)



(Ex Works Port of Entry)

461869	MF w/ pressure setting - Prop	No Charge
	Multi-Function Auxiliary Hydraulics with Electronic Pressure	
	Control (EPC)	
	For use with multiple applications:	
	hammers/thumbs/grapples/crushers.	
	Includes in-cab Electronic Pressure Control feature	
	Pressure Control feature allows hydraulic pressure setting	
	from the cab monitor and maintaining pressure settings in	
	memory when multiple tools are used.	
	Joystick Activated with Electronic Proportional Controls	
	Provides single or dual pump, two-way flow,	
	Secondary Low-flow Auxiliary Hydraulics can be added	
	Includes in-cab electronically controlled pressure setting feature	
	Is switchable to single acting flow for hammer application.	
	Notes:	
	Not for use with other Auxiliary Hydraulics options, with the exception of Low Flow.	
	2) Heavy duty bucket linkage is standard equipment on	
	C/D series excavators.	
	3) For dealer installed auxiliary hydraulic kits contact:	
	HydrauliCircuit Technology (HCT)	
	(1-888-603-0080 or sales@hctkits.com or www.hctkits.com)	

SD E6417 SECONDARY AUXILIARY HYDRAULICS

 OD_LOTIT OL	CONDAIN ACAILIAN III DINACLICO	
XE6417X	No Low Flow Circuit	No Charge
461863	Secondary Auxiliary Hydraulics	\$11,449.00
	Secondary Low Flow Auxiliary Hydraulics	
	Provides low-flow for rotation or tilt hydraulic attachments.	
	For use with Standard Boom option 481858	
	Not for use with Offset Boom option 461025	
	Joystick Activated with Electronic Proportional Controls	
	Notes:	
	1) May be used stand alone or with any Case Excavator Auxiliary	
	Hydraulics option.	
	2) For dealer installed auxiliary hydraulic kits contact:	
	HydrauliCircuit Technology (HCT)	
	(1-888-603-0080 or sales@hctkits.com or www.hctkits.com)	

XE5449X No Rain Deflector



CX490D CRAWLER EXCAVATOR US PRICE LIST

(Ex Works Port of Entry)

CAB OPTIONS		
CD 55442 CA	D CHARD (FORC)	
	B GUARD (FOPS) No FOPS Top Cab Guard	No Charg
481070	FOPS Top Cab Guard	\$1,146.0
401070	To Top das dudid	ψ1,140.
	B GUARD (FRONT)	
+ +	No Front Guard	No Char
461142	Front Guard - Wire Mesh Screen	\$1,326.0
781986	Front Stone Guard (OPG L1)	\$1,973.0
	vertical bars (two piece/upper and lower)	
461024	Front Stone Guard (OPG L2)	\$2,324.0
	vertical bars (one piece/full length)	
461552	Vandal Guard	\$574.0
	Removable steel panels for front windshield	
SD_E5451 SU	N VISOR	
	No Sun Visor	No Char
461554	Sun Visor	\$108.0
XE6300X	No Bucket Buckets may be ordered using Order Codes listed in the	No Char
	Factory Supplied Attachments Section	
ADDITIONAL OPTI	ONS	
SD EEOOS TD	ACK CHAIN GUIDE	
461542	Double Track Chain Guide	No Char
481264	Full Track Chain Guide -3	\$4,505.0
1 10.20.	Tan Hadi Grani Galaci G	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
SD_E5302 HY	DRAULIC CWT REMOVAL DEVICE	
XE5302X	No Hyd CWT Removal Device	No Char
481263	Hydraulic CWT Removal Device	\$16,467.
SD_E5448 CA	TWALK	_ _
XE5448X	No Catwalk	No Char
461553	Catwalk - Left and Right Sides	\$2,452.
	(Note: catwalk is not compliant with ISO standards)	
SD_E5449 RA	IN DEFLECTOR	

No Charge

XE9874X No Refuel Pump

Refuel Pump

481257

CX490D CRAWLER EXCAVATOR

		(Ex Works Port of Entry)	
	461555	Rain Deflector	\$380.00
		Not for use with Front grill guard - 2 x 2 mesh option 461142,	
		Front rock guard (OPG 1) option 781986, or	
		Front rock guard (OPG 2) option 461024.	
_	T =	FETY VALVE	
╄	XE9730X	No Hose Burst Check Valve	No Charge
	481064	Hose Burst Check Valve (HBCV)	\$11,205.00
		Located on Boom and Arm Cylinder	
	SD_E9739 FU	LL VIEW CAMERA	
	XE9739X	No max view monitor	No Charge
	488055	Case Max View Monitor	\$1,907.00
	SD_E9740 SIE	DE VIEW CAMERA	
I^{-}	XE9740X	No Side View Camera	No Charge
	461560	Side View Camera	\$694.00

No Charge

\$1,296.00



(Ex Works Port of Entry) Factory Supplied Attachments

Order Code	Description	Weight	Factory Data	List Price
Case Pin On Bucke	ts			
84404291	48" Heavy-Duty Pin-On Bucket with 5 teeth (2.36 cu. yd.)			\$9,427.00
84404292	54" Heavy-Duty Pin-On Bucket with 6 teeth (2.69 cu. yd.)			\$10,059.00
84404293	60" Heavy-Duty Pin-On Bucket with 6 teeth (3.03 cu. yd.)			\$10,864.00
84404294	48" HD Hi-Capacity Pin-On Bucket with 5 teeth (2.83 cu. yd.)			\$10,545.00
84404295	54" HD Hi-Capacity Pin-On Bucket with 6 teeth (3.22 cu. yd.)			\$10,873.00
84404296	60" HD Hi-Capacity Pin-On Bucket with 6 teeth (3.62cu. yd.)			\$11,743.00
84404297	48" Severe-Duty Pin-On Bucket with 5 teeth (2.36 cu. yd.)			\$12,707.00
84404298	54" Severe-Duty Pin-On Bucket with 6 teeth (2.69 cu. yd.)			\$13,724.00
84404299	60" Severe-Duty Pin-On Bucket with 6 teeth (3.03 cu. yd.)			\$14,823.00
•			•	
47467932	72" Severe-Duty Pin-On Bucket	6,000 LB		\$25,056.00
84422403	66" Heavy Duty Pin-On Bucket"	4,674 LB		\$19,875.00
84422408	72" Heavy Duty Pin-On Bucket	4,899 LB		\$20,706.00
84422413	66" HD High Capacity Pin-On Bucket	5,080 LB		\$22,090.00
84422414	72" HD High Capacity Pin-On Bucket	6,649 LB		\$22,959.00
84422419	66" Severe-Duty Pin-On Bucket	5,650 LB		\$24,046.00



(Ex Works Port of Entry) Standard Equipment

ENGINE:

Isuzu AQ-6UZ1X

Tier 4 Final Certified

Selective Catalytic Reduction - SCR

Diesel Oxidation Catalyst - DOC

Cooled Exhaust Gas Recirculation -

CEGR

Turbocharged/air cooled intercooler

Horsepower:

Net 362 (270 kW) @ 2000 RPM

Electronic fuel injection

High pressure common rail system

Neutral safety start

Auto-engine warm up

Glow-plug pre-heat

Fuel Economy Assist System - FEA

Engine Protection Feature - EPF

Dual-stage fuel filtration

Dual element air filter

Remote oil filter

Drain for fuel tank

Remote engine oil drain

500-hour engine oil change interval

24 Volt system

Engine oil sample port

Battery disconnect switch

Air pre-cleaner - Cyclone

High ambient temperature cooling

package

Emergency engine stop

External Fuel and DEF gauges

Fan housing

Fuel cooler

Fuel filter restriction indicator

Fuel shut-off valve

Idle start

Radiator, oil cooler, intercooler -

protective screen

FUEL ECONOMY SYSTEMS:

Engine Idle/Fuel Economy System:

Auto-idle

One-touch idle

Auto-idle shut-down

BEC - Boom Economy Control

AEC - Auto Economy Control

SWC - Swing Relief Control

SSC - Spool Stroke Control

HYDRAULICS:

Auto power boost

Auto swing priority

Arm speed assistance - 2 pump flow

Auxiliary flow control

Auxiliary valve

Boom speed assistance - 2 pump flow

Bucket curl assist

Control levers pre-wired for auxiliary

hydraulics

Electronically controlled hydraulic

pumps

Holding valve - Boom and Arm

Fire wall

Hydraulic filter restriction indicator

Neutral pump de-stroke

Oil cooler

Power save

Pump stand-by pressure

Auto travel speed change

Selectable work modes

Free swing - switch activated

Hydraulic oil sample port

Control pattern selector

Pre-set auxiliary pump settings

Auxiliary valve

5,000-hour hydraulic oil change interval

1,000-hour hydraulic filter change

interval

SAHR brake



(Ex Works Port of Entry) Standard Equipment

UPPER STRUCTURE:

ISO mirrors - 3
Cab viscous-Mounts (fluid)
Upper mounted work light - 70 watt
Swivel guard belly pan
Center cover - over main CV
Fuel tank belly pan
Handrail - RH access
ISO guard rails
Lifting eyes for counterweight
Lockable fuel cap, service doors and

ATTACHMENTS:

toolbox

Arm - 8 ft 4 in (2.53 m)

Heavy-duty bucket linkage

Boom mounted work light - 70 watt

Auxiliary pipe brackets

Centralized grease fittings

Attachment cushion valve

Arm and boom regeneration

Bucket anti-clatter device

Chrome pins

Easy Maintenance System (EMS)

bushings

Teardrop pin retention keepers

Boom - 21 ft 6 in (6.55 m)

OPERATOR ENVIRONMENT:

ROPS protection FOPS cab top guard - Level 1 Pressurized cab Face vent Cab lights - 2 Interior dome light One-touch lock front window One piece window - right Safety glass windows Gate lock hydraulic activation Emergency exit and hammer Clear polycarbonate roof window with sunshade AC/heat/defrost with auto climate control LED Color monitor - 7 in (180 mm)

OPERATOR ENVIRONMENT (cont'd): 26 selectable languages for monitor On-board diagnostic system 10 programmable attachments settings on monitor - 5 single flow, 5 dual flow Seat belt - 3 in (76 mm) Heated high-back cloth seat with air suspension and 65° tilt adjustment Sliding seat - 3.54 in (90 mm) Adjustable armrests Tilting consoles - 4-position Sliding cockpit - 3.15 in (80 mm) Low-effort joystick controls Controls pre-wired for auxiliary Single pedal travel Straight travel AM/FM radio with antenna, 2 speakers and Bluetooth capabilities Aux-in port for personal electronics Radio mute switch - joystick Rear-view camera Anti-theft system - start code system Rubber floormat 12 Volt electric outlet 24 Volt cigarette lighter Windshield wiper/washer Cup holder Storage compartments Warm/cool storage compartment Travel alarm with cancel switch Ignition keys One key start & lock-up Cab filter - external Cab handrails

UNDERCARRIAGE:

Operator's manual

Long undercarriage
35.4 in (900 mm) steel shoes,
triple semi-grouser
Full overlap turntable bearing tub
Double track chain guides
Hydraulic track adjustment
Sealed link chain



(Ex Works Port of Entry) Standard Equipment

Steps
Carbody belly pan - swivel guard
X-pattern carbody
Lashing points - tie downs
Extra Filter Kit:
 Engine oil filter
 Filter wrench
 Fuel filters
 Grease gun
 Green plug oil drain hose for engine
 oil drain
 Hydraulic return filter
 Pilot circuit hydraulic filter

CASE ProCare - Full Machine Protection
Factory Warranty (3-yr/3000-hr),
Planned Maintenance (3-yr/2000-hr)
and SiteWatch™ Telematics
CASE SiteWatch™ Telematics
Includes hardware and a 3-yr
advanced data subscription



(Ex Works Port of Entry) Models

COMMERCIAL MODEL	Weight	Factory Data	List Price
CX500D ME	111,800 LB		\$713,936.00
CX500D RTC ME	114,600 LB		\$744,987.00

Triple-Grouser Steel Shoes

CX500D MASS EXCAVATION CRAWLER EXCAVATOR US PRICE LIST

(Ex Works Port of Entry) Factory Supplied Options

	B	100	F. (11.45
Order Code	Description	Weight	Factory Data	List Price
LICUTE				
LIGHTS				
SD F5408 W0	DRKING LIGHTS			
488134	Halogen Working Lights			No Charge
488135	LED Working Lights			\$3,100.00
	8 LED light and 1 side camera:			. ,
	2 LED light are mounted on the front (1 on boom, 1 on house)			
	2 LED lights are mounted on the rear			
	(above the rear view camera)			
	1 LED light mounted on each side (2)			
	2 LED lights mounted on the top of the cab			
!	9	•		
BOOMS				
2001110				
SD_E5311 BC	OOM			
461028	Mass Excavation Boom (6.58 M)			No Charge
	21' 6" (6.55 M) Mass Excavation Boom			
	For use with CX470C (Standard ME and RTC ME)			
	commercial model.			
			!	
ARMS				
ANIO				
SD F5320 AR	M/DIPPERSTICK			
461572	Mass Ex. Arm			No Charge
	Mass Excavation Arm - 2.53M (8 ft, 4in) HD			3.
	For use with 21'6" Mass Ex. Boom			
XE5320X	No Arm/Dipperstick			(\$18,235.00
	Less arm, bucket cylinder and linkage.			(+ 15,=55155
	2000 a.m., autonos oyumus ama minago		!	
TRACK SHOES				
TRACK CHOLD				
SD_E5199 TR	VCK SHOES			
9560007	35.4" (900 mm) Steel Shoes		T	No Charge
9360007	, , , , , , , , , , , , , , , , , , , ,			NO Charge
9560004	Triple-Grouser Steel Shoes 29.5"(750mm)Steel Shoes - 2bar	+		(\$1,079.00)
9560004	29.0 (700mm)oteer ondes - zuar			(\$1,079.00)



(Ex Works Port of Entry)

LANGUAGE

SD_47083 OPERATOR'S MANUAL

		781981	English Literature			No Charge
		461540	French Canadian Literature			No Charge
		781980	Spanish Literature			No Charge

ADDITIONAL EQUIPMENT CXC

HYDRAULIC OPTIONS

SD_E6410 AUXILIARY HYDRAULICS

 	<u>D_L0110 710</u>	ALLACT TI BRAGLIOG	
	XE6410X	No Optional Hydraulics	No Charge
	461865	Single Acting Auxiliary Hyd	\$10,378.00
		Single Acting Auxiliary Hydraulics	
		For use with hammers or vibratory compaction plate applications	
		Joystick activated with Electronic Proportional Controls	
		Provides single direction flow	
		Includes manually adjustable relief valve to set required pressures	
		Notes:	
		1) Not for use with other Auxiliary Hydraulic options, with the	
		exception of Low Flow.	
		2) Heavy duty bucket linkage is standard equipment on	
		C/D series excavators.	
		3) For dealer installed auxiliary hydraulic kits contact:	
		HydrauliCircuit Technology (HCT)	
		(1-888-603-0080 or sales@hctkits.com or www.hctkits.com)	

(Ex Works Port of Entry)

		(Ex Works For or Entry)		
	461871	Thumb - Proportional SW		\$7,789.00
		Double Acting Auxiliary Hydraulics		
		For use with thumb applications		
		Joystick Activated with Electronic Proportional Controls		
		Provides single pump, two-way flow		
		Hydraulic plumbing provided to the end of the boom only,		
		no piping to the arm		
		This system is not switchable to single acting flow		
		Notes:		
		1) Not for use other Auxiliary Hydraulics options with the		
		exception of Low Flow.		
		2) Heavy duty bucket linkage is standard equipment on		
		C/D series excavators.		
		3) For dealer installed auxiliary hydraulic kits contact:		
		HydrauliCircuit Technology (HCT)		
		(1-888-603-0080 or sales@hctkits.com or www.hctkits.com)		
	461869	MF w/ pressure setting - Prop		\$13,433.00
		Multi-Function Auxiliary Hydraulics with Electronic Pressure		
		Control (EPC)		
		For use with multiple applications:		
		hammers/thumbs/grapples/crushers.		
		Includes in-cab Electronic Pressure Control feature		
		Pressure Control feature allows hydraulic pressure setting		
		from the cab monitor and maintaining pressure settings in		
		memory when multiple tools are used.		
		Joystick Activated with Electronic Proportional Controls		
		Provides single or dual pump, two-way flow,		
		Secondary Low-flow Auxiliary Hydraulics can be added		
		Includes in-cab electronically controlled pressure setting feature		
		Is switchable to single acting flow for hammer application.		
		Natar		
		Notes:		
		1) Not for use with other Auxiliary Hydraulics options, with the		
		exception of Low Flow.		
		2) Heavy duty bucket linkage is standard equipment on		
		C/D series excavators.		
		3) For dealer installed auxiliary hydraulic kits contact:		
		HydrauliCircuit Technology (HCT)		
\Box		(1-888-603-0080 or sales@hctkits.com or www.hctkits.com)		

SD_E6417 SECONDARY AUXILIARY HYDRAULICS						
	XE6417X	No Low Flow Circuit			No Charge	

(Ex Works Port of Entry) \$11,449.00 461863 Secondary Auxiliary Hydraulics **Secondary Low Flow Auxiliary Hydraulics** Provides low-flow for rotation or tilt hydraulic attachments. For use with Standard Boom option 481858 Not for use with Offset Boom option 461025 **Joystick Activated with Electronic Proportional Controls** Notes: 1) May be used stand alone or with any Case Excavator Auxiliary Hydraulics option. 2) For dealer installed auxiliary hydraulic kits contact: HydrauliCircuit Technology (HCT) (1-888-603-0080 or sales@hctkits.com or www.hctkits.com) **CAB OPTIONS** SD_E5443 CAB GUARD (FOPS) XE5443X No FOPS Top Cab Guard No Charge 481070 \$1,146.00 FOPS Top Cab Guard SD_E5444 CAB GUARD (FRONT) XE5444X No Front Guard No Charge 461142 Front Guard - Wire Mesh Screen \$1,326.00 781986 Front Stone Guard (OPG L1) \$1,973.00 vertical bars (two piece/upper and lower) 461024 Front Stone Guard (OPG L2) \$2,324.00 vertical bars (one piece/full length) 461552 Vandal Guard \$574.00 Removable steel panels for front windshield SD E5451 SUN VISOR XE5451X No Sun Visor No Charge 461554 | Sun Visor \$108.00 **BUCKETS** SD_E6300 EXCAVATOR BUCKET(S) XE6300X No Charge No Bucket Buckets may be ordered using Order Codes listed in the

Factory Supplied Attachments Section

Double Track Chain Guide

Full Track Chain Guide -3

ADDITIONAL OPTIONS

481264

SD_E5206 TRACK CHAIN GUIDE

No Charge

\$4,505.00

481257

Refuel Pump



CX500D MASS EXCAVATION CRAWLER EXCAVATOR US PRICE LIST

(Ex Works Port of Entry)

SD_E5302 H	YDRAULIC CWT REMOVAL DEVICE	
XE5302X	No Hyd CWT Removal Device	No Charge
481263	Hydraulic CWT Removal Device	\$16,467.00
SD_E5448 C	ATWALK	
XE5448X	No Catwalk	No Charge
461553	Catwalk - Left and Right Sides	\$2,452.00
	(Note: catwalk is not compliant with ISO standards)	
SD_E5449 R	AIN DEFLECTOR	
XE5449X	No Rain Deflector	No Charge
461555	Rain Deflector	\$380.00
SD_E9730 S	AFETY VALVE	
XE9730X	No Hose Burst Check Valve	No Charge
481064	Hose Burst Check Valve (HBCV)	\$11,205.00
	Located on Boom and Arm Cylinder	
SD_E9739 F	ULL VIEW CAMERA	
XE9739X	No max view monitor	No Charge
488055	Case Max View Monitor	\$1,907.00
SD_E9740 S	IDE VIEW CAMERA	
XE9740X	No Side View Camera	No Charge
461560	Side View Camera	\$694.00
SD_E9874 R	EFUEL PUMP	
XE9874X	No Refuel Pump	No Charge

\$1,296.00



(Ex Works Port of Entry)

Factory Supplied Attachments

Order Code		Description	Weight	Factory Data	List Price
	47957624	54" Heavy-Duty Pin-On Bucket	5,655 LB		\$18,831.00
	47957625	60" Heavy-Duty Pin-On Bucket	5,952 LB		\$20,231.00
	47957626	66" Heavy-Duty Pin-On Bucket	6,239 LB		\$21,736.00
	47957630	54" Severe-Duty Pin-On Bucket	6,757 LB		\$22,597.00
	47957633	60" Severe-Duty Pin-On Bucket	7,154 LB		\$24,278.00
	47957634	66" Severe-Duty Pin-On Bucket	7,452 LB		\$25,956.00



Seat belt - 3 in (76 mm)

CX750D RTC **US PRICE LIST**

Standard Equipment

ENGINE:

Isuzu AQ-6WG1X turbocharged EGR with cooler, SCR System 6 Cylinder liquid cooled diesel 957 cu. in. (15.6L) displacement Common rail Injection Charge air cooling Tier 4 Final Certified Horsepower: - Net 512 (382 kW) at 1800 RPM Fuel Tank Capacity: 238 gal. (US) (900 L) Long Life Anti-freeze (protect to - 34°F) Automatic engine warm-up Auto idle warm-up/one-touch auto idle Neutral safety start Auto power boost Cold idle start Dual element air filter Emergency engine shutdown

flow

Reversible cooling fan

OPERATOR ENVIRONMENT: ROPS protection FOPS cab top guard - Level 1 Pressurized cab Face vent Cab lights - 2 Interior dome light One-touch lock front window One piece window - right Safety glass windows Gate lock hydraulic activation Emergency exit and hammer Clear polycarbonate roof window with sunshade AC/heat/defrost with auto climate LED Color monitor - 7 in (180 mm) 26 selectable languages for monitor On-board diagnostic system 10 programmable attachments settings on monitor - 5 single flow, 5 dual

Heated high-back cloth seat with air suspension and 65° tilt adjustment Sliding seat - 3.54 in (90 mm) Adjustable armrests Tilting consoles - 4-position Sliding cockpit - 3.15 in (80 mm) Low-effort joystick controls Controls pre-wired for auxiliary Single pedal travel AM/FM radio with antenna, 2 speakers and Bluetooth capabilities Aux-in port for personal electronics Radio mute switch - joystick Rear-view camera Anti-theft system - start code system Rubber floormat 12 Volt electric outlet 24 Volt cigarette lighter Windshield wiper/washer Cup holder Storage compartments Warm/cool storage compartment Travel alarm with cancel switch Ignition keys One key start & lock-up Cab filter - external Cab handrails Operator's manual

ELECTRICAL:

24 Volt system Alternator: 50 AMP Batteries: 2 Electronic Systems Monitor Work lights (70 watt) 2 Boom, 1 upper, 2 cab

UPPER STRUCTURE:

ISO mirrors - 3 Cab viscous-mounts - (fluid) Swivel guard belly pan Center cover - over main CV Fuel tank belly pan



Bucket curl assist

CX750D RTC US PRICE LIST

Standard Equipment

UPPER STRUCTURE CONT:

Handrail - RH access
ISO guard rails
Lifting eyes for counter weight
Lockable fuel cap, service doors and
toolbox

UNDERCARRIAGE:

X-pattern car-body Undercarriage:

- HD:

19' 4" (5 880 mm)

Track gauge:

- HD: 10' 10"(3 350 mm)

- Retracted: 8'10" (2 740 mm)

Shoes

- 3-bar/36" (900MM) (47 per side) Hydraulic adjustable track tension Tapered upper track frame Sealed outer flange rollers Front track guides Lower under covers

TRACK DRIVE:

Two-speed independent hydrostatic travel SAHR disc parking brake Reinforced drive motor guards

HYDRAULICS:

Auto power boost
Auto swing priority
Arm speed assist - 2 pump flow
Auxiliary flow control
Auxiliary valve
Boom speed assist - 2 pump flow

Control lever pre-wired for auxiliary hydraulics Electronically controlled hydraulics pumps Holding valve - boom and arm Fire wall Hydraulic filter restriction indicator Neutral pump de-stroke Oil cooler Power save Pump stand-by pressure Auto travel speed change Selectable work modes Free swing Hydraulic oil sample ports Control pattern selector Pre-set auxilary pump settings Auxiliary valve 5,000 hour hydraulic oil change interval 1,000 hour hydraulic filter change interval

ATTACHMENTS:

Arm: 11'6"(3.55 m)
Boom: 25'3" (7.70 M)

CASE ProCare - Full Machine Protection Factory Warranty (3-yr/3000-hr), Planned Maintenance (3-yr/2000-hr) and SiteWatch™ Telematics CASE SiteWatch™ Telematics Includes hardware and a 3-yr advanced data subscription



Models

COMMERCIAL MODEL	Weight	Factory Data	List Price
CX750D RTC	158,300 LB		\$961,442.00

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

LIGHTS

SD_E5408 WORKING LIGHTS

	488134	Halogen Working Lights		No Charge
	488135	LED Working Lights		\$3,100.00
		8 LED light and 1 side camera:		
		2 LED light are mounted on the front (1 on boom, 1 on house)		
		2 LED lights are mounted on the rear		
		(above the rear view camera)		
		1 LED light mounted on each side (2)		
		2 LED lights mounted on the top of the cab		

BOOMS

SD_E5311 BOOM

	461543	Heavy-Duty Boom		No Charge
		25'3"(7.7M)		
	781917	No Boom		(\$24,178.00)
		Less boom, hoist and arm cylinders, and plumbing. Boom		
		foot and cylinder pins are retained.		

ARMS

SD_E5320 ARM/DIPPERSTICK

	488132	11'8" (3.55M) HD ARM		No Charge
		For use with 25'3" (7.7 M) Reach Boom - 461543		
	781677	13'6" (4.11 M) Arm		\$1,553.00
		For use with 25'3" (7.7 M) Reach Boom - 461543		
	781930	16'5" (5.0 M) Arm		\$3,561.00
		For use with 25'3" (7.7 M) Reach Boom - 461543		
	XE5320X	No Arm/Dipperstick		(\$12,566.00)
		This option is less arm, bucket cylinder and linkage.		

TRACK SHOES

SD_E5199 TRACK SHOES

I	9560048	26" (650MM)Steel Shoes - 2bar		(\$4,691.00)
	9560004	29.5"(750mm)Steel Shoes - 2bar		(\$4,223.00)
Γ	9560007	35.4" (900 mm) Steel Shoes		No Charge

LANGUAGE

SD_47083 OPERATOR'S MANUAL

	461540	French Canadian Literature		No Charge
	781980	Spanish Literature		No Charge
Ī	781981	English Literature		No Charge

BUCKETS

SD_E6300 EXCAVATOR BUCKET(S)

ſ	XE6300X	No Bucket		No Charge
		Buckets may be ordered using Order Codes listed in the		
		Direct Ship Attachment Section		



\$15,046.00

\$10,950.00

No Charge

CX750D RTC US PRICE LIST

ADDITIONAL EQUIPMENT CXC

SD_E6410 AUXILIARY HYDRAULICS

excavators.

XE6410X No Optional Hydraulics

Thumb - Proportional SW

switch that controls power boost.

3/4" BSPP to SAE-12 Male JIC.

461871

MF w/ pressure setting - Prop

HYDRAULIC OPTIONS

461869

	Multi-Function Auxiliary Hydraulics with Electronic Pressure	
	Control	
	(EPC)	
	For use with multiple applications:	
	Hammers/thumbs/grapples/crushers.	
	Includes in-cab Electronic Pressure Control feature. Pressure	
	Control	
	feature allows hydraulic pressure setting from the cab monitor and	
	maintaining pressure settings in memory when multiple tools are	
	used.	
	Joystick Activated with Electronic Proportional Controls. Provides	
	single or dual pump, two-way flow, Secondary Low-flow Auxiliary	
	Hydraulics can be added Includes in-cab electronically controlled	
	pressure setting feature Is switchable to single acting flow for	
	hammer application.	
	Notes:	
	1) Not for use with other Auxiliary Hydraulics options, with the	
	exception of Low Flow.	
- 1	1 1	

2) Heavy duty bucket linkage is standard equipment on D series

(1-888-603-0080 or sales@hctkits.com or www.hctkits.com)

Recommended for use with a thumb kit. Plumbing to the end of the boom, no hydraulics provided on the arm. Actuated by trigger switches in the right and left hand controls. Right controls one-way flow, left controls opposite flow. Right hand switch is the same

Order 2 code 284600A1, Adapter fittings, from Parts to connect

(1-888-603-0080 or sales@hctkits.com or www.hctkits.com)

For dealer installed auxiliary hydraulic kits contact:

HydrauliCircuit Technology (HCT)

3) For dealer installed auxiliary hydraulic kits contact:

HydrauliCircuit Technology (HCT)



SD_E64	17 SECONDAR	Y AUXILIARY HYDRAULICS	
X	6417X No Low F	Flow Circuit	No Charge
46	1863 Seconda	ry Auxiliary Hydraulics	\$13,717.00
CAB OPTION	NS		
SD E54	43 CAB GUARD	(FOPS)	
	5443X No FOPS		No Charge
		pp Cab Guard	\$1,089.00
		use with Vandal Guard option 461552	
	44 CAB GUARD		
	5444X No Front		No Charge
		ard - Wire Mesh Screen	\$1,259.00
		one Guard (OPG L1)	\$1,973.00
		one Guard (OPG L2)	\$2,207.00
46	1552 Vandal G		\$574.00
	Remova	ble steel panels for front windshield	
ADDITION	L OPTIONS		
ADDITION	IL OF HONS		
SD F52	06 TRACK CHA	IN GUIDE	
		rack Chain Guide	No Charge
		k Chain Guide -3	\$7,573.00
	•		•
SD_E53	02 HYDRAULIC	CWT REMOVAL DEVICE	
X	5302X No Hyd (CWT Removal Device	No Charge
48	1263 Hydraulio	CWT Removal Device	\$22,217.00
	49 RAIN DEFLE		
	5449X No Rain		No Charge
46	1555 Rain Def		\$380.00
		use with Front Grill Guard or Front Rock Guard options	
	listed in	the Cab Guard Section	
CD F0	00 CAFETY //AI	NE.	
	30 SAFETY VAL	Burst Check Valve	No Chargo
		rst Check Valve (HBCV)	No Charge \$12,095.00
		on Boom and Arm Cylinder	\$12,093.00
	Located	on boom and Arm Cymider	<u>l</u>
SD F97	39 FULL VIEW	CAMERA	
		view monitor	No Charge
		x View Monitor	\$1,907.00
			1 + 1,001100
SD_E97	40 SIDE VIEW (CAMERA	
		View Camera	No Charge
		w Camera	\$694.00



Factory Supplied Attachments

Order Code	Description	Weight	Factory Data	List Price
47526679	36" Heavy-Duty Pin-On Bucket with 4 teeth, 1.94 cu. yd.	5,550 LB		\$13,409.00
47526680	42" Heavy-Duty Pin-On Bucket with 5 teeth, 2.32 cu. yd.	6,050 LB		\$14,481.00
47526684	48" Heavy-Duty Pin-On Bucket with 5 teeth, 2.68 cu. yd.	6,350 LB		\$15,642.00
47526687	54" Heavy-Duty Pin-On Bucket with 6 teeth, 3.05 cu. yd. (3.05 cu. m.)	6,750 LB		\$16,892.00
47526690	60" Heavy-Duty Pin-On Bucket with 6 teeth, 3.44 cu. yd.	7,150 LB		\$18,244.00
47526691	66" Heavy-Duty Pin-On Bucket with 7 teeth, 3.82 cu. yd.	7,750 LB		\$19,702.00
47526699	72" Heavy-Duty Pin-On Bucket with 7 teeth, 4.20 cu. yd.	8,000 LB		\$21,279.00
47526717	54" HD Hi-Capacity Pin-On Bucket with 5 teeth, 3.41 cu. yd. (2.61 cu. m.)	6,300 LB		\$17,906.00
47526724	66" HD Hi-Capacity Pin-On Bucket with 6 teeth, 4.27 cu. yd. (3.26 cu. m.)	7,100 LB		\$20,883.00
47526727	72" HD Hi-Capacity Pin-On Bucket with 7 teeth, 4.69 cu. yd. (3.59 cu. m.)	7,460 LB		\$22,553.00
47526731	36" Severe-Duty Pin-On Bucket with 4 teeth, 1.94 cu. yd. (1.48 cu. m.)	6,050 LB		\$15,644.00
47526742	42" Severe-Duty Pin-On Bucket with 5 teeth, 2.31 cu. yd. (1.77 cu. m.)	6,550 LB		\$16,871.00
47526748	48" Severe-Duty Pin-On Bucket with 5 teeth, 2.68 cu. yd. (2.05 cu. m.)	6,850 LB		\$18,125.00
47526751	54" Severe-Duty Pin-On Bucket with 6 teeth, 3.05 cu. yd. (2.33 cu. m.)	7,250 LB		\$19,723.00
47526753	60" Severe-Duty Pin-On Bucket with 6 teeth, 3.44 cu. yd. (2.63 cu. m.)	7,650 LB		\$21,243.00
47526763	66" Severe-Duty Pin-On Bucket with 7 teeth, 3.82 cu. yd. (2.92 cu. m.)	8,075 LB		\$23,046.00

Isuzu AQ-6WG1X turbocharged



Seat belt - 3 in (76 mm)

CX750D RTC ME US PRICE LIST

Standard Equipment

ENGINE:

EGR with cooler, SCR System 6 Cylinder liquid cooled diesel 957 cu. in. (15.6L) displacement Common rail Injection Charge air cooling Tier 4 Final Certified Horsepower: - Net 512 (382 kW) at 1800 RPM Fuel Tank Capacity: 238 gal. (US) (900 L) Long Life Anti-freeze (protect to - 34°F) Automatic engine warm-up Auto idle warm-up/one-touch auto idle Neutral safety start Auto power boost Cold idle start Dual element air filter Emergency engine shutdown

flow

Reversible cooling fan OPERATOR ENVIRONMENT: ROPS protection FOPS cab top guard - Level 1 Pressurized cab Face vent Cab lights - 2 Interior dome light One-touch lock front window One piece window - right Safety glass windows Gate lock hydraulic activation Emergency exit and hammer Clear polycarbonate roof window with sunshade AC/heat/defrost with auto climate LED Color monitor - 7 in (180 mm) 26 selectable languages for monitor On-board diagnostic system 10 programmable attachments settings on monitor - 5 single flow, 5 dual

Heated high-back cloth seat with air suspension and 65° tilt adjustment Sliding seat - 3.54 in (90 mm) Adjustable armrests Tilting consoles - 4-position Sliding cockpit - 3.15 in (80 mm) Low-effort joystick controls Controls pre-wired for auxiliary Single pedal travel AM/FM radio with antenna, 2 speakers and Bluetooth capabilities Aux-in port for personal electronics Radio mute switch - joystick Rear-view camera Anti-theft system - start code system Rubber floormat 12 Volt electric outlet 24 Volt cigarette lighter Windshield wiper/washer Cup holder Storage compartments Warm/cool storage compartment Travel alarm with cancel switch Ignition keys One key start & lock-up Cab filter - external Cab handrails Operator's manual

ELECTRICAL:

24 Volt system Alternator: 50 AMP Batteries: 2 Electronic Systems Monitor Work lights (70 watt) 2 Boom, 1 upper, 2 cab

UPPER STRUCTURE:

ISO mirrors - 3 Cab viscous-mounts (fluid) Swivel guard belly pan Center cover - over main CV Fuel tank belly pan Handrail - RH access



Standard Equipment

UPPER STRUCTURE(cont):

Iso guard rails
Lifting eyes for counter weight
Lockable fuel cap, service doors and
toolbox

UNDERCARRIAGE:

X-pattern car-body Undercarriage:

- HD:

19' 4" (5 880 mm)

Track gauge:

- HD: 10' 10"(3 350 mm)

- Retracted: 8'10" (2 740 mm)

Shoes

- 3-bar/36" (900MM) (47 per side) Hydraulic adjustable track tension Tapered upper track frame Sealed outer flange rollers Front track guides Lower under covers

TRACK DRIVE:

Two-speed independent hydrostatic travel SAHR disc parking brake Reinforced drive motor guards

HYDRAULICS:

Auto power boost Auto swing priority Arm speed assist - 2 pump flow Auxiliary flow control Auxiliary valve

Boom speed assist - 2 pump flow Bucket curl assist Control lever pre-wired for auxiliary hydraulics Electronically controlled hydraulics pumps Holding valve - boom and arm Fire wall Hydraulic filter restriction indicator Neutral pump de-stroke Oil cooler Power save Pump stand-by pressure Auto travel speed change Selectable work modes Free swing Hydraulic oil sample ports Control pattern selector Pre-set auxilary pump settings Auxiliary valve 5,000 hour hydraulic oil change interval 1,000 hour hydraulic filter change interval

ATTACHMENTS:

Arm: 11'6"(3.55 m)
Boom: 25'3" (7.70 M)

CASE ProCare - Full Machine Protection Factory Warranty (3-yr/3000-hr), Planned Maintenance (3-yr/2000-hr) and SiteWatch™ Telematics CASE SiteWatch™ Telematics Includes hardware and a 3-yr advanced data subscription

Models

COMMERCIAL MODEL	TECHNICAL TYPE	Weight	Factory Data	List Price
CX750D RTC ME	540425764	59,600 LB		\$974,940.00

SD_E5199 TRACK SHOES

9560004 29.5"(750mm)Steel Shoes - 2bar

9560048 26" (650MM)Steel Shoes - 2bar

9560007 35.4" (900 mm) Steel Shoes

CX750D RTC ME US PRICE LIST

Factory Supplied Options

Order Code	Description	Waight	Factory Data	List Price
Order Code	Description	Weight	Factory Data	LIST Price
LIGHTS				
<u> Попто</u>				
SD E5408 W	ORKING LIGHTS			
488134	Halogen Working Lights			No Charge
488135	LED Working Lights			\$3,100.00
	8 LED light and 1 side camera:			4 -,
	2 LED light are mounted on the front (1 on boom, 1 on house)			
	2 LED lights are mounted on the rear			
	(above the rear view camera)			
	1 LED light mounted on each side (2)			
	2 LED lights mounted on the top of the cab			
			'	
BOOMS				
2000				
SD E5311 BC	OOM			
461028	Mass Excavation Boom (6.58 M)			No Charge
781917	No Boom			(\$24,178.00)
	Less boom, hoist and arm cylinders, and plumbing. Boom			,
	foot and cylinder pins are retained.			
		•		
ARMS				
SD E5330 AE	RM/DIPPERSTICK			
				No Charge
461572	Mass Ex. Arm			INO Charue
				No Charge
461572	Mass Excavation Arm 2.90M			
461572	Mass Excavation Arm 2.90M No Arm/Dipperstick			
461572	Mass Excavation Arm 2.90M			(\$12,566.00)

(\$4,223.00)

No Charge

(\$4,691.00)

L	ANG	SUAGE							
	SD_47083 OPERATOR'S MANUAL								
		461540	French Canadian Literature			No Charge			
		781980	Spanish Literature			No Charge			
		781981	English Literature			No Charge			
В	UCŁ	KETS							
	S	D_E6300 EX	CAVATOR BUCKET(S)						
		XE6300X	No Bucket			No Charge			
			Buckets may be ordered using Order Codes listed in the						
			Direct Ship Attachment Section						
Α	DDI	TIONAL EQU	JIPMENT CXC						
	HYD	RAULIC OPTION	ONS						
						_			
	S	D_E6410 AU	XILIARY HYDRAULICS						
		461865	Single Acting Auxiliary Hyd			\$13,860.00			
			Provides single pump flow plumbing to end of arm and return to						
			tank						
			through additional filter.						
			Includes remote adjustable relief valve to match attachment						
			pressure						
			requirements.						
			·						
			Order 2 of code 284600A1, Adapter fittings, from Parts to connect						
			3/4" BSPP to SAE-12 Male JIC.						
			Recommended for heavy hammer use and thumb applications.						
			Transfer of floory flammer doe and thamb approachers.						
			Includes heavy duty bucket linkage.						
			includes heavy duty bucket illikaye.						

For dealer installed auxiliary hydraulic kits contact:

(1-888-603-0080 or sales@hctkits.com or www.hctkits.com)

HydrauliCircuit Technology (HCT)



	461869	MF w/ pressure setting - Prop		\$17,740.00
	.0.000	Multi-Function Auxiliary Hydraulics with Electronic Pressure		411 ,11000
1 1 1		Control		
		(EPC)		
		For use with multiple applications:		
		Hammers/thumbs/grapples/crushers.		
		Training of applead and a		
		Includes in-cab Electronic Pressure Control feature. Pressure		
		Control		
		feature allows hydraulic pressure setting from the cab monitor and		
		maintaining pressure settings in memory when multiple tools are		
		used.		
		Joystick Activated with Electronic Proportional Controls. Provides		
		single or dual pump, two-way flow, Secondary Low-flow Auxiliary		
		Hydraulics can be added Includes in-cab electronically controlled		
		pressure setting feature Is switchable to single acting flow for		
		hammer application.		
		Notes:		
		1) Not for use with other Auxiliary Hydraulics options, with the		
		exception of Low Flow.		
		2) Heavy duty bucket linkage is standard equipment on C/D series		
		excavators.		
		3) For dealer installed auxiliary hydraulic kits contact:		
		HydrauliCircuit Technology (HCT)		
		(1-888-603-0080 or sales@hctkits.com or www.hctkits.com)		
	461871	Thumb - Proportional SW		\$10,950.00
		Recommended for use with a thumb kit. Plumbing to the end of the		
		boom, no hydraulics provided on the arm. Actuated by trigger		
		switches in the right and left hand controls. Right controls one-way		
		flow, left controls opposite flow. Right hand switch is the same		
		switch that controls power boost.		
		Order 2 code 284600A1, Adapter fittings, from Parts to connect		
		3/4" BSPP to SAE-12 Male JIC.		
		For dealer installed auxiliary hydraulic kits contact:		
		HydrauliCircuit Technology (HCT)		
	VE0446V	(1-888-603-0080 or sales@hctkits.com or www.hctkits.com)		N. Ob
	дЕ6410X	No Optional Hydraulics		No Charge

SD_E6417 SECONDARY AUXILIARY HYDRAULICS

	XE6417X	No Low Flow Circuit		No Charge
	461863	Secondary Auxiliary Hydraulics		\$13,717.00



CAB OPTIONS		
	AB GUARD (FOPS)	No Observe
	No FOPS Top Cab Guard FOPS Top Cab Guard	No Charge
481070		\$1,089.00
	Not for use with Vandal Guard option 461552	I
SD_E5444 C	AB GUARD (FRONT)	
XE5444)	No Front Guard	No Charge
461552	Vandal Guard	\$574.00
	Removable steel panels for front windshield	
461142	Front Guard - Wire Mesh Screen	\$1,259.00
781986	Front Stone Guard (OPG L1)	\$1,973.00
461024	Front Stone Guard (OPG L2)	\$2,207.00
ADDITIONAL OP	TIONS	
SD_E5206 T	RACK CHAIN GUIDE	
461542	Double Track Chain Guide	No Charge
481264	Full Track Chain Guide -3	\$7,573.00
	YDRAULIC CWT REMOVAL DEVICE	
	No Hyd CWT Removal Device	No Charge
481263	Hydraulic CWT Removal Device	\$22,217.00
SD E5440 B	AIN DEFLECTOR	
	No Rain Deflector	No Charge
461555	Rain Deflector	\$380.00
401333	Not for use with Front Grill Guard or Front Rock Guard options	\$300.00
	listed in the Cab Guard Section	
	listed in the Cab Guard Section	<u> </u>
SD_E9730 S	AFETY VALVE	
XE9730)	No Hose Burst Check Valve	No Charge
481064	Hose Burst Check Valve (HBCV)	\$12,095.00
	Located on Boom and Arm Cylinder	
	•	•
SD_E9739 F	ULL VIEW CAMERA	
	No max view monitor	No Charge
488055	Case Max View Monitor	\$1,907.00
	IDE VIEW CAMERA	
- 	No Side View Camera	No Charge
461560	Side View Camera	\$694.00



Factory Supplied Attachments

Order Code	Description	Weight	Factory Data	List Price
47526679	36" Heavy-Duty Pin-On Bucket with 4 teeth, 1.94 cu. yd.	5,550 LB		\$13,409.00
47526680	42" Heavy-Duty Pin-On Bucket with 5 teeth, 2.32 cu. yd.	6,050 LB		\$14,481.00
47526684	48" Heavy-Duty Pin-On Bucket with 5 teeth, 2.68 cu. yd.	6,350 LB		\$15,642.00
47526687	54" Heavy-Duty Pin-On Bucket with 6 teeth, 3.05 cu. yd. (3.05 cu. m.)	6,750 LB		\$16,892.00
47526690	60" Heavy-Duty Pin-On Bucket with 6 teeth, 3.44 cu. yd.	7,150 LB		\$18,244.00
47526691	66" Heavy-Duty Pin-On Bucket with 7 teeth, 3.82 cu. yd.	7,750 LB		\$19,702.00
47526699	72" Heavy-Duty Pin-On Bucket with 7 teeth, 4.20 cu. yd.	8,000 LB		\$21,279.00
47526717	54" HD Hi-Capacity Pin-On Bucket with 5 teeth, 3.41 cu. yd. (2.61 cu. m.)	6,300 LB		\$17,906.00
47526724	66" HD Hi-Capacity Pin-On Bucket with 6 teeth, 4.27 cu. yd. (3.26 cu. m.)	7,100 LB		\$20,883.00
47526727	72" HD Hi-Capacity Pin-On Bucket with 7 teeth, 4.69 cu. yd. (3.59 cu. m.)	7,460 LB		\$22,553.00
47526731	36" Severe-Duty Pin-On Bucket with 4 teeth, 1.94 cu. yd. (1.48 cu. m.)	6,050 LB		\$15,644.00
47526742	42" Severe-Duty Pin-On Bucket with 5 teeth, 2.31 cu. yd. (1.77 cu. m.)	6,550 LB		\$16,871.00
47526748	48" Severe-Duty Pin-On Bucket with 5 teeth, 2.68 cu. yd. (2.05 cu. m.)	6,850 LB		\$18,125.00
47526751	54" Severe-Duty Pin-On Bucket with 6 teeth, 3.05 cu. yd. (2.33 cu. m.)	7,250 LB		\$19,723.00
47526753	60" Severe-Duty Pin-On Bucket with 6 teeth, 3.44 cu. yd. (2.63 cu. m.)	7,650 LB		\$21,243.00
47526763	66" Severe-Duty Pin-On Bucket with 7 teeth, 3.82 cu. yd. (2.92 cu. m.)	8,075 LB		\$23,046.00