Item		Description	MSRP usd
		T30 HYDROSEEDER	
T30	Tank Size	335 liquid capacity, 281 working capacity	22,550
	Engine	19 hp Kohler Command Gas	
	Hose Reel	electric [max storage capacity 100']	
	Hose	100' x 1-1/4" rubber hose [200 psi]	
	Nozzles	[1] wide fan, [1] narrow fan, [1] long distance	
	Mount	skid	
	Other	remote valve	
T30 options	E'll D	CH . II	400
085356	Fill Port	fillport assembly	190
061327	Airflush	airflush enabled system T60 HYDROSEEDER	1,325
Т60Т	Tank Size	600 liquid capacity, 500 working capacity	34,623
1001	Engine	23.5 hp Kohler CH730 Gas	34,023
	Hose	50' x 1-1/4" rubber hose [200 psi]	
	Nozzles	[1] wide fan, [1] narrow fan, [1] long distance	
	Mount	trailer w/ electric brakes & DOT lights	
	Hitch	standard pintle hitch [2-5/16" ball option #061448-n/c]	
	Other	remote valve & suction line valve	
T60S	Tank Size	600 liquid capacity, 500 working capacity	32,164
1003	Engine	23.5 hp Kohler CH730 Gas	32,104
	Hose	50' x 1-1/4" rubber hose [200 psi]	
	Nozzles	[1] wide fan, [1] narrow fan, [1] long distance	
	Mount	skid	
	Other	remote valve & suction line valve	
T60 options	Guici	Terriote valve & saction line valve	
061280-01	Tower/Guard Rail	operator platform and discharge gun assembly with guard rails	3,650
061210-01	Hose Reel	electric hose reel	4,500
004832-15B	Hose	150' x 1-1/4" continuous hose [200 psi] [replaces 50' hose]	860
003309-10	Hose	100' x 1-1/4" rubber hose [200 psi] with couplers	850
061326-02	Airflush	airflush [requires connection to external air compressor]	1,075
061407	Spare Tire	spare tire and wheel, mounted & bolted on	740
080533	Radio Remote	remote control-pump on/off	2,150
A5558-001	Hoist System Sub-frame	11.5' HydroSeeder lift sub-frame	Call for Price
A5567-001	FINN Mount	FINN sub-frame mount (must include applicable sub-frame)	Call for Price
		T75 HYDROSEEDER	
T75T	Tank Size	820 liquid capacity, 700 working capacity	50,325
	Engine	23.5 hp Kohler CH730 Gas	
	Tower/Guard Rail	operator platform and discharge gun assembly with guard rails	
	Hose Reel	electric	
	Hose	150' x 1-1/4" rubber hose [200 psi]	
	Nozzles	[2] wide fan, [2] narrow fan, [3] long distance	
	Mount	trailer w/ electric brakes & DOT lights	
	Hitch	standard pintle hitch [2-5/16" ball option #061448-n/c]	
T75S	Tank Size	820 liquid capacity, 700 working capacity	47,355
	Engine	23.5 hp Kohler CH730 Gas	
	Tower/Guard Rail	operator platform and discharge gun assembly with guard rails	
	Hose Reel	electric	
	Hose	150' x 1-1/4" rubber hose [200 psi]	
	Nozzles	[2] wide fan, [2] narrow fan, [3] long distance	
T75 options	Mount	skid	
061315-01	Airflush	airflush [requires connection to external air compressor]	1,075
061369	Spare Tire	spare tire and wheel, mounted & bolted on	680
061411	Surge Brakes	hydraulic surge brakes with 3" lunette [new build required]	3,710
080533	Radio Remote	remote control-pump on/off	2,150
A5562-001	Hoist System Sub-frame	14.25' HydroSeeder lift sub-frame	Call for Price
A5567-001	FINN Mount	FINN sub-frame mount (must include applicable sub-frame)	Call for Price
<u> </u>			

Item		Description	MSRP usd
		T90 & T120 HYDROSEEDER	
T90T	Tank Size	940 liquid capacity, 800 working capacity	78,474
	Engine	35.1 hp Yanmar 3TNV88C-DYEM Tier IV Final	
	Tower/Guard Rail	operator platform and discharge gun assembly with guard rails	
	Nozzles	[1] wide fan, [1] narrow fan, [2] long distance	
	Controls	ground level controls	
	Mount	trailer w/ electric brakes & DOT lights	
	Hitch	standard pintle hitch [ball hitch not optional]	
T90S	Tank Size	940 liquid capacity, 800 working capacity	72,259
	Engine	35.1 hp Yanmar 3TNV88C-DYEM Tier IV Final	
	Tower/Guard Rail	operator platform and gun assembly with FULL deck rails	
	Nozzles	[1] wide fan, [1] narrow fan, [2] long distance	
	Controls	ground level controls	
	Mount	skid	
T120T	Tank Size	1180 liquid capacity, 1000 working capacity	84,502
	Engine	35.1 hp Yanmar 3TNV88C-DYEM Tier IV Final	,
	Tower/Guard Rail	operator platform and discharge gun assembly with guard rails	
	Nozzles	[1] wide fan, [1] narrow fan, [2] long distance	
	Controls	ground level controls	
	Mount	trailer w/ electric brakes & DOT lights	
	Hitch	standard pintle hitch [ball hitch not optional]	
T120GN	Tank Size	1180 liquid capacity, 1000 working capacity	91,003
1120011	Engine	35.1 hp Yanmar 3TNV88C-DYEM Tier IV Final	31,003
	Tower/Guard Rail	operator platform and discharge gun assembly with guard rails	
	Nozzles	[1] wide fan, [1] narrow fan, [2] long distance	
	Controls	ground level controls	
	Mount	gooseneck	
T1200			70.002
T120S	Tank Size	1180 liquid capacity, 1000 working capacity	79,002
	Engine	35.1 hp Yanmar 3TNV88C-DYEM Tier IV Final	
	Tower/Guard Rail Nozzles	operator platform and discharge gun assembly with guard rails	
	Controls	[1] wide fan, [1] narrow fan, [2] long distance ground level controls	
	Mount	skid	
T90/T120 options	Woult	SNIU	
061273H-1-1/4-02	Hose Reel Package	hydraulic hose reel, 200' x 1-1/4" hose [300 psi], nozzles, valve	7,270
061401-01	Airflush	airflush [requires connection to external air compressor]	950
061023	Hardened Pump	nitride treated pump case, impeller, wear plate [new build req'd]	1,150
061111	Railing	T90T full deck railing [new build required]	1,865
061406	Skid Plate	engine compartment skid plate [new build required]	1,100
061445	Hitch Extension	T90T/T120 hitch extension 20" long	830
061405	Spare Tire	T90T spare wheel/tire, mounted	590
061274	Spare Tire	T120T spare wheel/tire, mounted	590
061040	Spare Tire	T120GN spare wheel/tire, mounted	590
061441	Stainless T90T	T90T tank & lid [stainless is blast finish, carbon parts painted black]	Call for Price
061442	Stainless T90S	T90S tank & lid [stainless is blast finish, carbon parts painted black]	Call for Price
061438	Stainless T120	T120 tank & lid [stainless is blast finish, carbon parts painted black]	Call for Price
061439	Stainless T120	T120 agitator	Call for Price
A5563-001	T90S Hoist System Sub-frame	11.5' HydroSeeder lift sub-frame w./ bracket kit	Call for Price
A5564-001	T120S Hoist System Sub-frame	14.25' HydroSeeder lift sub-frame w./ bracket kit	Call for Price
A5567-001	FINN Mount	FINN sub-frame mount (must include applicable sub-frame)	Call for Price

Item		Description	MSRP usd
· · ·		LF120 HYDROSEEDER	1113111 434
LF120	Tank Size	1180 liquid capacity, 1000 working capacity	94,364
	Engine	35.1 hp Yanmar 3TNV88C-DYEM Tier IV Final	
	Tower/Guard Rail	operator platform and discharge gun assembly with guard rails	
	Nozzles	[1] wide fan, [1] narrow fan, [2] long distance	
	Controls	ground level controls	
	Mount	trailer on heavy duty axles and high flotation tires	
	Hitch	standard pintle hitch [ball hitch not optional]	
LF120 options	Other	engine/fuel tank skid plates, full deck railings, 20" hitch extension	
061273H-1-1/4-02	Hose Reel Package	hydraulic hose reel, 200' x 1-1/4" hose [300 psi], nozzles, valve	7,270
061401-01	Airflush	airflush [requires connection to external air compressor]	950
061023	Hardened Pump	nitride treated pump case, impeller, wear plate [new build req'd]	1,150
061438	Stainless T120	T120 tank & lid [stainless is blast finish, carbon parts painted black]	Call for Price
061439	Stainless T120	T120 agitator	Call for Price
061296	Foam Fill Service	foam filling service for [4] high flotation tubeless tires	6,075
		T170 HYDROSEEDER	
T170	Tank Size	1750 liquid capacity, 1500 working capacity	101,580
	Engine	65hp Cummins Turbo Diesel QSF2.8 Tier IV Final	
	Tower/Guard Rail	operator platform and discharge gun assembly with guard rails	
	Nozzles	[2] wide fan, [2] narrow fan, [2] long distance	
T470 - m4'- m-	Mount	skid [truck mounting optional]	
7170 options 061436	Stainless T170		Call for Price
001450	Stalliless 11/0	tank & lid [stainless is blast finish, carbon parts painted black]	Call for Trice
061437	Stainless T170	agitators	Call for Price
061329H-1-1/4-01	Hose Reel Package	hydraulic hose reel [3 position pivoting, UV shield] 200' x 1-1/4" rubber hose [300 psi], nozzles, remote valve	8,830
061329H-1-1/2-01	Hose Reel Package	hydraulic hose reel [3 position pivoting, UV shield] 200' x 1-1/2"	•
061409-01	Ground Level Controls	rubber hose [300 psi], nozzles, remote valve engine throttle and clutch control from ground, with standard	9,550
		platform location	1,550
061356-01	Airflush	airflush system [requires truck air supply & addition of 3-5 gallon	
051205		auxiliary tank for proper flushing]	1,265
061306	Hardened Pump	nitride treated pump case, impeller, wear plate [new build req'd]	1,265
061300	Fill Port Add	add second fill port on drivers side at front of tank	1,265
A6306-001	Radio Remote w/out GLC	remote control for throttle and pump functions **Does NOT work w/ 061409-01: GLC Option**	4,515
A6307-001	Radio Remote w/GLC	remote control for throttle and pump functions **Includes GLC conrol box**	6,560
011562	Truck Mount Kit	truck spring mount kit	1,525
		T330 HYDROSEEDER	
T330	Tank Size	3350 liquid capacity, 3000 working capacity	137,368
	Engine	134HP John Deere 4045HFC04 Tier IV Final turbo diesel	
	Tower/Guard Rail	operator platform and discharge gun assembly with guard rails [2] wide fan, [2] narrow fan, [2] long distance	
	Nozzles Mount	skid	
	Other	5" X 2.5" centrifugal pump	
-	Other	38 gal. fuel tank	
		reversible, variable speed agitators with liquid recirculation	
		ground level controls	
		truck spring mount kit is included (FINN P/N:011562)	
T330 options			
T330SST	Stainless T330	tank & lid [stainless is blast finish, carbon parts painted black]	Call for Price
T330SSA	Stainless T330	agitators	Call for Price
T330HR125	Hose Reel Package	hydraulic hose reel, 200' x 1-1/4" rubber hose [300psi], nozzles, remote valve	8,830
T330HR150	Hose Reel Package	hydraulic hose reel, 200' x 1-1/2" rubber hose [300psi], nozzles,	·
T220PP	Padio Pomoto	remote valve	9,550
T330RR T330AF	Radio Remote Airflush	remote control for throttle and pump functions airflush system [requires truck air supply & addition of 3-5 gallon	2,690
IJJUAF	Allilusii	auxiliary tank for proper flushing	1,290
T330HP	Hardened Pump	nitride treated pump case, impeller, wear plate [new build req'd]	1,265
T330FPA	Fill Port Add	add second fill port on drivers side at front of tank [not available on	1,203
		stainless steel]	2,140

Grounds Equipment - Bid #ESCNJ 18/19-25

Item		Description	MSRP usd
T330SB	Rear Spray Bar	pressurized rear spray bar [3 nozzles]	5,110

Item		Description	MSRP usd
		TITAN HYDROSEEDER	
HT330	Tank Size	3350 gal. liquid capacity, 3000 gal. working capacity	206,355
	Engine	173HP John Deere 4045HFC06 Tier IV Final turbo diesel	
	Tower / Guard Rail	operator platform and discharge gun assembly with full guard rails	
	Nozzles	[2] wide fan, [2] narrow fan, [1] brass long distance, [1] LongShot	
	Mount	skid	
	Other	[4] function/radio remote control operation [pump speed, in/out power hose reel, on/off pump, horn]	
•		6" X 3" centrifugal pump and optional 6" X 3" vortex pump	
•		Hydrostatically powered machine functions	
		[2] variable speed and reversible helical agitators	
		50 gal. fuel tank	
		low maintenance agitator bearings	
		centralized lubrication banks	
HT400	Tank Size	3975 Gal. liquid capacity, 3600 Gal. working capacity	215,452
111400	Engine	173HP John Deere 4045HFC06 Tier IV Final turbo diesel	213,432
-	Tower / Guard Rail	operator platform and discharge gun assembly with full guard rails	
-	Nozzles	[2] wide fan, [2] narrow fan, [1] brass long distance, [1] LongShot	
-	Mount	skid	
-		[4] function/radio remote control operation [pump speed, in/out	
	Other	power hose reel, on/off pump, horn]	
		6" X 3" centrifugal pump and optional 6" X 3" vortex pump	
		Hydrostatically powered machine functions	
-		[2] variable speed and reversible helical agitators	
-		50 gal. fuel tank	
-		low maintenance agitator bearings	
•		centralized lubrication banks	
		och anged having down	
Titan Options			
VP	Vortex Pump Conversion	6" X 3", 465 gpm @ 150 psi , 1.25" solid clearance vortex pump	
	·	(replaces standard centrifugal pump)	925
SPA	Secondary Pump Add	6" X 3", 465 gpm @ 150 psi , 1.25" solid clearance vortex pump add	0.250
		[shipped loose]	8,350
В	Boom	second boom [includes [1] 50 deg wide fan, [1] 25 deg narrow fan, [1]	F 000
		brass long distance]	5,860
HR125	Hose Reel Package	hydraulic hose reel, 200' X 1-1/4" rubber hose [300 psi], nozzles,	0.070
		remote valve	8,870
HR150	Hose Reel Package	hydraulic hose reel, 200' X 1-1/2" rubber hose [300 psi], nozzles,	0.270
	-	remote valve	9,270
AF	Air Flush	airflush system [requires truck air supply & addition of 3-5 gal. aux.	1 225
FPA	Fill Dort Add	tank for proper flushing]	1,335
НР	Fill Port Add Hardened Pump	adds second fill port on drivers side tank rear	1,600
ПР	нагаеней Рипір	pump hardening process adder	2,100 Call for Price
SS1	Stainless HT330	tank [stainless is painted beige, carbon parts are painted black]	Call for Trice
cca			Call for Price
SS2	Stainless HT330	agitators [2]	
SS3	Stainless HT400	tank [stainless is painted beige, carbon parts are painted black]	Call for Price
SS4		talini (stalliness is painted beige) salven parts are painted stalling	Call for Price
	Stainless HT400	agitators [2]	
HTLP	Lighting Package	integrated work light package, with operator's platform scene lighting	1,300
SB	Spray Bar	pressurized, 3 nozzle spray bar and cab controls mounted in a free	7 100
		standign box w/ truck mounted air tap	7,180
FFP	Front Flushers	[2] flushers mounted on front corners of the tank tank, cab controls mounted in a free standing box w/ truck mounted air tap	8,220
		•	0,220
DFP	Deluxe Flusher Package	includes [2] flushers mounted on tank, rear spray bar and deluxe cab	
		controls mounted in a free standing box w/ truck mounted air tap	15,400
A4924-018	LongShot Nozzle	secondary LongShot nozzle [Distance Optimized for HT only]	1,190
	<u> </u>	, 5	

Item		Description	MSRP usd
Item		BB302 MATERIAL BLOWER	IVISKE USU
BB302	Hopper Capacity	1.5 cu. yd. with built in feed chute	85,058
55502	Engine	35.1 hp Yanmar 3TNV88C-DYEM Tier IV Final	03,030
	Blower	500 cfm @ 10 psi	
	Mount	trailer with electric brakes and DOT lights and hitch extension	
		manual reel w/ 100' x 4" and 50' x 4" standard duty hoses w/ quick	
	Hose	couplers [reel comfortably fits 100']	
		12v electrical system, 3 function/radio remote control operation	
	Other	[engine rpm and material feed] 4" poly diffuse cone	
		MBH6 MATERIAL BLOWER	
мвн6	Hopper Capacity	6 cu. yd.	135,328
A2548-001	Engine	67HP Yanmar 4TNV98CT Tier IV Final	100,010
7425-10 002	Blower	750 cfm @ 12 psi	
	Mount	Skid	
	Widdit	hydraulic reel w/ 100' x 4" and 50' x 4" standard duty hoses w/ quick	
	Hose	couplers	
		[3] function/radio remote control operation [engine rpm, material	
	Other	feed on/off, variable material control	
		6' x 4" hot air lead hose and electric tarp	
		dust suppression (requires external water source)	
MBH6 Options		dust suppression (requires external water source)	
052952	Source Duty Hose	50' x 4" severe duty extension flex hose	1,160
032932	Severe Duty Hose	30 x 4 Severe duty extension nex nose	1,100
A2578-002	Hose Swap	removes 4" hose [100' & 50'], replaces with [2 x 50'] 5" standard duty	1,125
		removes 4" hose [100' & 50'], replaces with [1 x 50'] and [1 x 100'] 4"	1,123
A2578-003	Hose Swap	severe duty	410
A2570 004	Hasa Swan	,	410
A2578-004	Hose Swap	removes 4" hose [100' & 50'], replaces with [2 x 50'] 5" severe duty	1,440
A5466-001	Lighting Package	integrated work light package	1,075
A4330-002	Feed Chute	feed chute	880
A6401-002	Trailer	trailer option	9,750
A2567-002	Hardened Airlock	airlock hardening process adder	3,335
		MBX MATERIAL BLOWER	
MBX	Hopper Capacity	10 cu. yd.	230,472
	Engine	134HP John Deere 4045HFC04 Tier IV Final turbo diesel	
	Blower	1250 cfm @ 14 psi	
	Mount	skid see chassis recommendations below	
	Hose	hydraulic reel w/ [1] 100' and [2] 50' sections x 4" standard duty hoses	
		w/ quick couplers	
		[6] function/radio remote control operation [blower rpm, material	
	Other	feed on/off, variable floor speed, in/out power hose reel, on/off seed	
		injection and emergency stop]	
		6' x 4" hot air lead hose	
		electric tarp	
		dust suppression [requires external water source or addition of on-	
		board water option below]	
MBX Options			
HC2	Hose Conversion	removes 4" standard duty hose [1] 100' & [2] 50', replaces with 5"	
		standard duty hose [1] 100' & [2] 50'	1,750
HC3	Hose Conversion	removes 4" standard duty hose [1] 100' & [2] 50', replaces with 4"	
1105	Tiose conversion	severe duty hose [1] 100' & [2] 50'	2,425
HC4	Hose Conversion	removes 4" standard duty hose [1] 100' & [2] 50', replaces with 5"	
1104	Hose conversion	severe duty hose [4] 50'	2,880
EXT6	Extension Kit	6 cu. yd. extension kit	8,600
EXT6-SL	Extension Kit	6 cu. yd. extension kit w/ side loading doors	9,800
EXT12	Extension Kit	[2] 6 cu. yd. extension kits for 12 cu. yd. additional capacity	17,200
CVT12 CI	Futancian Kit	[2] 6 cu. yd. extension kits for 12 cu. yd. additional capacity w/ side	
EXT12-SL	Extension Kit	loading doors	19,350
Floor	Floor	belt floor replaces chain floor	3,085
НА	Hardened Airlock	airlock hardening process adder	3,870
OBT	On-Board Tank	75 gal. on-board water tank for dust suppression	2,300
SI	Seed Injection	seed injection	13,500
MBLP	Lighting Package	integrated work light package	1,000
SP	Skid Plate	drop-out pan skid plate	1,200
Chassis Requirements:		class 7 (will require class 8 if future extensions are added)	1,200
cassis requirements.	MBX 10 cu. yd. + 6 cu. yd.	class 8	
	MBX 10 cu. yd. + [2] 6 cu. yd.		
	1VIDA 10 Cu. yu. + [2] 6 Cu. ya.	class 8	

Item		Description	MSRP usd
	MA	TERIAL BLOWER HOSES AND CONNECTORS	
HC4"	Hose Connector	4" threaded hose to hose spin-on connector	315
НС4"НА	Hose Connector	4" spin-on connector to hot air hose connection	480
HC5"	Hose Connector	5" threaded hose to hose spin-on connector	390
НС5"НА	Hose Connector	5" spin-on connector to hot air hose connection	1,175
	055398B	standard duty 50' x 4" hose with ends w/ quick couplers	1,050
	055399B	standard duty 100' x 4" hose with ends w/ quick couplers	1,975
	052744B	standard duty 50' x 5" hose with ends w/ quick couplers	1,860
	052745B	standard duty 100' x 5" hose with ends w/ quick couplers	2,935
	052952	severe duty 50' x 4" hose with ends w/ quick couplers	1,160
	052965	severe duty 100' x 4" hose with ends w/ quick couplers	2,150
	052958	severe duty 50' x 5" hose with ends w/ quick couplers	2,005
		Material Blower Hose Weights	
		4" FINN Standard Duty Hose = 1.16 lbs. / ft.	
		4" FINN Severe Duty Hose = 1.48 lbs. / ft.	
		5" FINN Standard Duty Hose = 1.7 lbs. / ft.	
		5" FINN Severe Duty Hose = 1.85 lbs. / ft.	

Item		Description	MSRP usd
reem		B40 STRAW BLOWER	WiSiti usu
B40	Discharge Head	360° rotation, 50° vertical travel	13,684
	Engine	20.5 hp Kohler Command Gas, electric start	
	Feed Tray	horizontal, collapsible feed tray	
	Mount	skid with forklift channels	
	Blower	17" blower fan with 6 fan blades	
B40 options			
061361	Custom Trailer Package	independent suspension, 2500 lb. rubber torsion axle, 20.5 x 8 x 10	
		highway tread tires, fenders, DOT highway lights, expanded metal	
		grating, safety rails, parking jack, 2" ball hitch, electric brakes w/	
		breakaway switch	5,000
061452	Discharge Hose	100' x 6" w/ clamp and handle	1,975
061105	Discharge Hose	50' x 6" w/ clamp and handle B70 STRAW BLOWER	1,050
B70T	Discharge Hoad	360° rotation, 50° vertical travel	12 164
Б/ОТ	Discharge Head		43,164
<u>- </u>	Engine	35.1 hp Yanmar 3TNV88C-DYEM Tier IV Final	
	Feed Tray	horizontal, collapsible feed tray adjustable height	
	Mount	trailer with electric brakes and DOT lights	
<u></u>	Blower	21" blower fan with 6 fan blades	
	Hitch	standard pintle hitch [2" ball option #061449-n/c]	
B70RH	Discharge Head	360° rotation, 50° vertical travel	40,464
	Engine	35.1 hp Yanmar 3TNV88C-DYEM Tier IV Final	
	Feed Tray	right hand feed horizontal, collapsible feed tray adjustable height	
	Mount	skid mounted	
	Blower	21" blower fan with 6 fan blades	
B70 options	5: 1		4 720
031303	Discharge Hose	50' x 8" w/ clamp and handle	1,720
222	5: 1 11 1	B230 STRAW BLOWER	70.070
B230	Discharge Head	359° horzontal rotation, 40° vertical travel	79,079
A5803-001	Engine	72 hp (53.7 kW) YANMAR 4TNV98CT-NVT Turbo Diesel	
<u></u>	Production Capacity	up to 20 tons/ hr	
<u></u>	Discharge Distance	90 ft.	
	Feed Tray	hydraulic powered conveyor chain	
	Trailer	TANDEM rubber torsion axles w/ electric brakes, DOT lights and	
<u>- </u>	Blower	ST225/90D16 load range E tires dynamically balanced 30" blower fan with 6 fan blades	
•	Other	pintle hitch	
B230 options	Otilei	pinde niten	
A5808-001	Seat Belt	seat belt	100
A5807-001	Spare Tire	spare tire and wheel mounted	590
7.5007 001	Spare The	KRIMPER	330
KR6PQ	Coulter Blades	9 blades spaced at 8"	8,410
	Ballast Boxes	2 boxes constructed from 3/16" steel	
•	Axle	1" square carbon steel gangbolt w/ locking nut and tension washer	
•	Axle Bearings	3 bearings	
	Model	6' krimper w/ 3-point hitch	
KR8PQ	Coulter Blades	12 blades spaced at 8"	15,340
KNOPU	Ballast Boxes	2 boxes constructed from 3/16" steel	15,540
	Axle	1" square carbon steel gangbolt w/ locking nut and tension washer	
•	Axle Bearings	4 bearings	
<u>. </u>	Model	8' krimper w/ 3-point hitch	
KR8HQ	Coulter Blades	12 blades spaced at 8"	17,116
	Ballast Boxes	2 boxes constructed from 3/16" steel	
	Axle	1" square carbon steel gangbolt w/ locking nut and tension washer	
	Axle Bearings	4 bearings	
	Model	8' hydraulic krimper w/ hoses and tires	
KR16HQ	Coulter Blades	24 blades [12 on main frame, 6 on each wing]	33,457
	Ballast Boxes	2 boxes constructed from 3/16" steel	
	Axle	1" square carbon steel gangbolt w/ locking nut and tension washer	
	Axle Bearings	10 bearings [6 on main frame and 2 on each wing]	
<u> </u>	Model	16' hydraulic krimper w/ hoses and tires	

Educational Services Commission of New Jersey NJ State Approved Co-op #65MCESCCPS

FINN CORPORATION DOMESTIC EQUIPMENT PRICELIST

Item		Description	MSRP usd
	GT Series -	Tractor Ground Preparation Attachments	
GTH65	Attachment Method	Category 1 tractor 3-point hitch	7,699
Pro Model	Req'd. Carrier Vehicle HP	24 - 65 hp.	
A5226-001	Finish Rake Width	78"	
	Scarifiers	(6) hydraulically adjusted scarifiers with ripping depth of 0 - 6"	
	Scarniers	and 45" scarifying width	
	Hydraulic Ports Required	(1) set of ports required (minimum)	
	Grading	55" wide free floating leveling blade and rake	
	Weight	925 lbs.	
	Pro Features	Hydraulic powered scarifiers	
		12" Foam filled gage tires, leveling rake and finish rake constructed of	
	Other	3/4" AR steel (replaceable in sections) and easily replaceable bolt on	
		scarifier teeth	
GTM65	Attachment Method	Category 1 tractor 3-point hitch	6,999
A5230-001	Req'd. Carrier Vehicle HP	24 - 65 hp.	
	Finish Rake Width	78"	
	Coarifions	(6) manually adjusted scarifiers with ripping depth of 0 - 6"	
	Scarifiers	and 45" scarifying width	
	Hydraulic Ports Required	(0) set of ports required	
	Grading	55" wide free floating leveling blade and rake	
	Weight	925 lbs.	
		12" Foam filled gage tires, leveling rake and finish rake constructed of	
	Other	3/4" AR steel (replaceable in sections) and easily replaceable bolt on	
		scarifier teeth	
GTH75	Attachment Method	Category 1 tractor 3-point hitch	8,299
Pro Model	Reg'd. Carrier Vehicle HP	35 - 75hp.	-,
A5227-001	Finish Rake Width	89"	
7.0227 002		(8) hydraulically adjusted scarifiers with ripping depth of 0 - 6"	
	Scarifiers	and 57" scarifying width	
	Hydraulic Ports Required	(1) set of ports required (minimum)	
	Grading	66" wide free floating leveling blade and rake	
	Weight	1,100 lbs.	
	Pro Features	Hydraulic powered scarifiers	
		12" Foam filled gage tires, leveling rake and finish rake constructed of	
	Other	3/4" AR steel (replaceable in sections) and easily replaceable bolt on	
	outer.	scarifier teeth	
GTM75	Attachment Method		7,699
		Category 1 tractor 3-point hitch	7,699
A5231-001	Reg'd. Carrier Vehicle HP	35 - 75hp. 89"	
	Finish Rake Width		
	Scarifiers	(8) manually adjusted scarifiers with ripping depth of 0 - 6"	
	Under die Beste Bestised	and 57" scarifying width	
	Hydraulic Ports Required	(0) set of ports required	
	Grading	66" wide free floating leveling blade and rake	
	Weight	1,100 lbs.	
	Othor	12" Foam filled gage tires, leveling rake and finish rake constructed of	
	Other	3/4" AR steel (replaceable in sections) and easily replaceable bolt on	
OTU05 4	And 1	scarifier teeth	0 = 0 =
GTH85-1	Attachment Method	Category 1 tractor 3-point hitch	8,799
Pro Model	Req'd. Carrier Vehicle HP	48 - 75hp.	
A5228-001	Finish Rake Width	101"	
	Scarifiers	(10) hydraulically adjusted scarifiers with ripping depth of 0 - 6"	
		and 70" scarifying width	
	Hydraulic Ports Required	(1) set of ports required (minimum)	
	Grading	77" wide free floating leveling blade and rake	
	Weight	1,300 lbs.	
	Pro Features	Hydraulic powered scarifiers	
	O.I.	12" Foam filled gage tires, leveling rake and finish rake constructed of	
	Other	3/4" AR steel (replaceable in sections) and easily replaceable bolt on	
		scarifier teeth	

Educational Services Commission of New Jersey NJ State Approved Co-op #65MCESCCPS

FINN CORPORATION DOMESTIC EQUIPMENT PRICELIST

Item		Description	MSRP usd
GTM85-1	Attachment Method	Category 1 tractor 3-point hitch	8,299
A5232-001	Req'd. Carrier Vehicle HP	48 - 75hp.	
	Finish Rake Width	101"	
	Scarifiers	(10) manually adjusted scarifiers with ripping depth of 0 - 6"	
		and 70" scarifying width	
	Hydraulic Ports Required	(0) set of ports required	
	Grading	77" wide free floating leveling blade and rake	
	Weight	1,300 lbs.	
	Other	12" Foam filled gage tires, leveling rake and finish rake constructed of	
	Other	3/4" AR steel (replaceable in sections) and easily replaceable bolt on scarifier teeth	
CTURE 2	A44		0.000
GTH85-2	Attachment Method	Category 2 tractor 3-point hitch	8,999
Pro Model A5229-001	Req'd. Carrier Vehicle HP Finish Rake Width	48 - 105 hp. 101"	
A5229-001	Finish Rake Width		
	Scarifiers	(10) hydraulically adjusted scarifiers with ripping depth of 0 - 6" and 70" scarifying width	
	Hydraulic Ports Required	(1) set of ports required (minimum)	
	Grading	77" wide free floating leveling blade and rake	
	Weight	1,350 lbs.	
	Pro Features	Hydraulic powered scarifiers	
		12" Foam filled gage tires, leveling rake and finish rake constructed of	
	Other	3/4" AR steel (replaceable in sections) and easily replaceable bolt on	
		scarifier teeth	
GTM85-2	Attachment Method	Category 2 tractor 3-point hitch	8,499
A5233-001	Reg'd. Carrier Vehicle HP	48 - 105 hp.	
	Finish Rake Width	101"	
	Scarifiers	(10) manually adjusted scarifiers with ripping depth of 0 - 6"	
	Scarniers	and 70" scarifying width	
	Hydraulic Ports Required	(0) set of ports required	
	Grading	77" wide free floating leveling blade and rake	
	Weight	1,350 lbs.	
		12" Foam filled gage tires, leveling rake and finish rake constructed of	
	Other	3/4" AR steel (replaceable in sections) and easily replaceable bolt on	
070 1 11		scarifier teeth	
GT Series options	Undraulia Tan Link	Toronton 2 marint hitab broduced a marrow of the distribution	
A5240-001	Hydraulic Top Link	Tractor 3-point hitch hydraulic powered top link kit	299
		(Available for Cat. 1 3-point hitch configuration and requires a dedicated set of hydraulic ports)	299
	GS Series - S	kid Steer Ground Preparation Attachments	
GSM65	Attachment Method	Skid Steer	3,299
A5235-001	Reg'd. Carrier Vehicle HP	30 - 60hp.	0,200
10200 002	Finish Rake Width	78"	
		(8) manually adjusted scarifiers with ripping depth of 0 - 5"	
	Scarifiers	and 66" scarifying width	
	Hydraulic Ports Required	(0) set of ports required	
	Weight	460 lbs.	•
	Other	Finish rake constructed of 3/4" AR steel (replaceable in sections) and	
		easily replaceable bolt on scarifier teeth	
GSH75	Attachment Method	Skid Steer	8,599
Pro Model	Req'd. Carrier Vehicle HP	40 - 100hp.	-
A5234-001	Finish Rake Width	89"	
	Scarifiers	(10) hydraulically adjusted scarifiers with ripping depth of 0 - 6" and 79" scarifying width	
	Hydraulic Ports Required	(1) set of ports required (minimum)	
	Grading	66" wide free floating leveling blade and rake	
	Weight	1,300 lbs.	
	Pro Features	Hydraulic powered scarifiers, 16" foam filled gage tires and 3/4" AR	
		steel leveling rake	
	Other	Finish rake constructed of 3/4" AR steel (replaceable in sections) and easily replaceable bolt on scarifier teeth	

Item		Description	MSRP usa
	GM Series - Mi	ni Skid Steer Ground Preparation Attachments	
GM45-1B	Attachment Method	Mini Skid Steer	2,89
A5236-001	Skid Steer Mount Plate	Bobcat Mini Skid Steer Specific	
	Req'd. Carrier Vehicle HP	24 - 60hp.	
	Finish Rake Width	54"	
	Scarifiers	(6) manually adjusted scarifiers with ripping depth of 0 - 5"	
	Scarniers	and 46" scarifying width	
	Hydraulic Ports Required	(0) set of ports required	
	Weight	340 lbs.	
	Other	Finish rake constructed of 3/4" AR steel (replaceable in sections) and	
	Otilei	easily replaceable bolt on scarifier teeth	
GM45-1U	Attachment Method	Mini Skid Steer	2,59
A5237-001	Skid Steer Mount Plate	Universal Mini Skid Steer Mount plate (Excludes Bobcat)	
	Req'd. Carrier Vehicle HP	24 - 60hp.	
	Finish Rake Width	54"	
	Caraifia na	(6) manually adjusted scarifiers with ripping depth of 0 - 5"	
	Scarifiers	and 46" scarifying width	
	Hydraulic Ports Required	(0) set of ports required	
	Weight	340 lbs.	
		Finish rake constructed of 3/4" AR steel (replaceable in sections) and	
	Other	easily replaceable bolt on scarifier teeth	
GM45-3B	Attachment Method	Mini Skid Steer	4,29
Pro Model	Skid Steer Mount Plate	Bobcat Mini Skid Steer Specific	
A5238-001	Reg'd. Carrier Vehicle HP	24 - 60hp.	
	Finish Rake Width	54"	
		(6) manually adjusted scarifiers with ripping depth of 0 - 5"	
	Scarifiers	and 46" scarifying width	
	Hydraulic Ports Required	(0) set of ports required	
	Grading	38" wide free floating leveling blade and rake	
	Weight	540 lbs.	
	Pro Features	16" Air filled gage tires and 3/4" AR steel leveling rake	
		Finish rake constructed of 3/4" AR steel (replaceable in sections) and	
	Other	easily replaceable bolt on scarifier teeth	
GM45-3U	Attachment Method	Mini Skid Steer	4,09
Pro Model	Skid Steer Mount Plate	Universal Mini Skid Steer Mount plate (Excludes Bobcat)	1,03
A5239-001	Req'd. Carrier Vehicle HP	24 - 60hp.	
7.0200 002	Finish Rake Width	54"	
		(6) manually adjusted scarifiers with ripping depth of 0 - 5"	
	Scarifiers	and 46" scarifying width	
	Hydraulic Ports Required	(0) set of ports required	
	Grading	38" wide free floating leveling blade and rake	
	Weight	540 lbs.	
	Pro Features	16" Air filled gage tires and 3/4" AR steel leveling rake	
	Tiorcatares	Finish rake constructed of 3/4" AR steel (replaceable in sections) and	
	Other	easily replaceable bolt on scarifier teeth	
GM Series options		cashy replaceable bolt on starmer teeth	
A5241-001	Conversion Kit	GM45-1B to GM45-3B & GM45-1U to GM45-3U Conversion Kit	1,69
, 132-11 UU1	CONVENSION AND	SIN-3 12 to Sin-3 32 & Givi-3 10 to Givi-3 30 Conversion Rit	1,09.