John Deere -2022 Price List 345G LC FT4 Excavator

01-Mar-2022



Code Description QTY List Price (USD)

03W0FF 345G LC FT4 Excavator 1 \$377,400.00

ENGINE:

Isuzu 6HK1XASA02, EPA FT4 / EU Stage IV emissions

Net Peak Power (ISO9249) 249 hp (186 kW)

Turbocharged, air-to-air charge air cooler

Electronic Engine Control Unit

Auto-Idle System

Full forced pressure feed type

High-pressure common rail, ULSD required, B20 approved; Mounted Fuel Cooler

Double filter with water separator, remote mounted

Full flow spin-on filter, remote mounted

Dual Element Dry-type Air Filter with Restriction Indicator

Glow Plug Start Aid

Antifreeze Protection to -34 degrees F (-37 degrees C)

Side by Side by Side Radiator, Oil Cooler, Intercooler with Dust Net

Enclosed Fan Guard

500 Hour Engine Oil Change Interval, Isolation Mounted Filter

HYDRAULICS:

Open Center, Load Sensing with Three Variable Displacement Pumps

Optional Auxilliary Hydraulic Lines with AFL Proportional Control

Hydraulic Pilot Controls

Axial Piston Swing Motor

Swing Brake Multiple Wet Disk, Spring Applied, Hydraulically Released

Auxiliary Valve Section

Adjustable Flow for Attachments Through Monitor

Boom and Arm Reduced Drift Valves

Power Boost

Auto Power Lift

Hydraulic Tank Site Gauge

5,000 Hour Hydraulic Oil Change Interval

Three variable-displacement axial-piston pumps

Heat treated, chrome-plated, polished cylinder rods, hardened steel (replaceable bushings) pivot pins

Inline DEF Filter

ELECTRICAL:

50-Amp Alternator - 24 Volt

Worklights: 5 Halogen, 1 Mounted on frame, 2 mounted on Boom, 2 mounted on top of cab

UNDERCARRIAGE:

Two Speed Propel with Auto-Shift

Axial Piston Propel Motors

Propel Motor Shields

Planetary Final Drives

Sealed Track Chain

Track Guides x3 (per side)

Provisions for Tie Downs

X-Frame Car Body

Hydraulic Track Adjuster

Eight Lower Rollers

Two Upper Rollers

Spring Applied Hydraulic Released Propel Brake

Bid Term: 2/22/19 - 2/21/21; Extended to 2/21/22; Extended to 2/21/23

UPPER STRUCTURE:

Right and Left Mirrors

Toolbox

Vandal Locks for: Cab Door, Service Doors, Fuel Cap

Counterweight, 19,136 lbs. (8,680 kg)

FRONT ATTACHMENT:

Oil Impregnated Bushings

Reinforced Resin Thrust Plates

Tungsten Carbide Thermal Coating on arm to Bucket Joint

Centralized Lubrication System

Dirt Seals on Bucket Pins

Less Bucket

OPERATOR'S STATION:

JDLink Ultimate Machine Monitoring System w/ 5-year Message Service (Available in United States and Canada only)

Adjustable Control Positions (Levers to Seat, Seat to Pedals)

4" Arm Rests Attached to Side Consoles

Pilot Control Shut-Off Lever

Short Stroke, Low Effort Pilot Levers

Switches for Auxiliary Hydraulic Control on RH Pilot Lever

Deluxe Adjustable Heated Cloth Seat with Air Suspension, Reclining Backrest, Headrest, and Adjustable Lumbar Support

Machine Information Center (MIC)

Auto-Climate Control/Air Conditioner, Heater with Pressurizer

AM-FM Radio

Rear View Camera

Windshield Wiper/Washer with Intermittent Speed

12V-60W, 5 Amp Cell Phone Power Outlet

3 In. Retractable Seat Belt

Tinted Safety Glass

Hot/Cold Box Compartment

Horn

Cup Holder

Interior Light

Coat Hook

Floor Mat

Motion Alarm with Cancel Switch

Transparent Tinted Roof Hatch with Sunshade

Four Fluid-Filled Elastic Mounts

Easy Access Air Conditioning Filter

Multifunction, Color LCD Monitor System with:

Diagnostic Capability

Systems Monitoring Capability

Multiple Language Capability

Maintenance Tracking

Engine Coolant Temperature Gauge

Engine Coolant Temperature Warning

Indicator with Audible Alarm

Engine Oil Pressure Warning

Diesel Exhaust Fluid Guage

Fuel Gauge with Low Fuel Indicator

Work Mode Indicator

Auto Idle Indicator

Alternator Charge Indicator

Air Filter Restriction Indicator

Fault Code Alert Indicator

Check Engine Indicator

Wiper Mode Indicator Work Lights On Indicator Fuel Rate Display Clock

Hour Meter

Mode Selection: One Work Mode, Three Power Modes, Numerous Attachment Modes

Auto-Climate Control/Air Conditioner, Heater with Pressurizer

03W0FF 345G LC FT4 Excavator

1 \$377,400.00

ENGINE

Engine Basic Factory Options - Required

1095 Engine Stage IV Emissions \$31,680.00

Isuzu 6HK1 7.8L

264 Net Rated hp (ISO 9249)

Turbocharger Charge Air Cooler

Electronic Engine Control Unit

Auto-Idle System

Antifreeze Protection to -34F (-37C)

Enclosed Fan Guard

Dual Element Dry-type Air Filter with Restriction Indicator

Full Flow Oil Filter Double Fuel Filter Water Separator Curved Exhaust

Automatic Belt Tension Device

Glow Plug Start Aid

Heavy Duty, Low Maintenance Batteries

50-Amp Alternator - 24 Volt 500 Hour Engine Oil Change Interval 70% (35 degrees) Off Level Capability

Engine Oil Sampling Valve

JOHN DEERE WORKSIGHT™

Machine Connectivity Basic Factory Options - Required

Machine connectivity functions require cellular coverage. Usage of JDLink /ZXLink System requires customer's acceptance of the terms of the John Deere Telematics System Contract.

Option availability limited by specific geographical regions. Please refer to region specific price pages for appropriate ordering codes.

170K JDLink™ No Added Cost

Includes integrated cab wiring harness, antenna, and JDLink™ Modem (MTG).

JDLink™ connectivity is enabled separately through the JDLink™ website. Connectivity service is subject to country availability.

UNDERCARRIAGE

	Track Shoes	Basic Factory Options - Required
3350	Triple Semi-Grouser Shoes	No Added Cost
	Track Frame	Basic Factory Options - Required
7500	1913 TRACK FRAME BOTTOM COVER SEAT SCREWS	No Added Cost
	OPERATOR'S STATION AND CONTROLS	
	Seat	Basic Factory Options - Required
4130	Seat, Heated Air-Suspension	\$976.00
	BOOM	
	Boom	Basic Factory Options - Required
6835	One Piece Boom with Arm Cylinder and Plumbing	\$29,064.00
	Grade Ready/Grade Guidance	Basic Factory Options - Required
7901	Less Grade Reference Ready Mounts	No Added Cost
	ARM	
	Arm	Basic Factory Options - Required

7160	Arm with Bucket Cylinder and Linkage 3.1 M (10 ft. 2 in.)	No Added Cost
7180	Arm with Bucket Cylinder and Linkage 3.76 M(12 Ft. 2 in.)	\$4,522.00
	HYDRAULICS	
	Auxiliary Hydraulics Basic Factory Op	otions - Required
7490	Auxiliary High-Flow Hydraulic Lines w/ AFL (Electronic Proportional Control, Pilot Level Mounted) for 3.1 M Arm (10 ft 2 in.)	\$10,800.00
7495	Auxiliary High-Flow Hydraulic Lines w/ AFL (Electronic Proportional Control, Pilot Level Mounted) for 3.75 M Arm	\$11,030.00
	BUCKETS	
	Hydraulic Thumb Kits Field Installed Attach	ments - Optional
AT379658	Hydraulic Thumb Kit, Progressive Teeth matching between the bucket and thumb will depend on the bucket width, number of teeth, and tooth spacing. Please see DMAC solution 94331 for optimum thumb and bucket teeth engagement. Only available for the following arm lengths: 300/345 3.75M (12'4") Not compatible with couplers.	
AT379659	Hydraulic Thumb Kit, Progressive for Couplers Teeth matching between the bucket and thumb will depend on the bucket width, number of teeth, and tooth spacing. Please see DMAC solution 94331 for optimum thumb and bucket teeth engagement. Only available for the following arm lengths: 300/345 3.75M (12'4") Not compatible with Hydraulic Quick Coupler (Variable-type Pin-Grabber) BYT11631.	
AT389951	Hydraulic Thumb Kit, Direct Teeth matching between the bucket and thumb will depend on the bucket width, number of teeth, and tooth spacing. Please see DMAC solution 94331 for optimum thumb and bucket teeth engagement. Not compatible with couplers.	\$10,493.00

AT339844	Deere/Hitachi Hydraulic Thumb Installation Labor for installation of Deere/Hitachi thumb at Paladin Customworks Kernersville, NC.	\$2,086.00
	Buckets, Heavy-Duty	Field Installed Attachments - Optional
BYT11166	60IN (1525MM) 2.09YD (1.60 M3) HD Bucket Includes Seven (7) TK400 Series Teeth.	\$9,331.00
BYT11165	54 In (1372 mm), 1.61 yd3 (1.23 M3) Heavy-Duty Bucket Includes Six (6) John Deere TK-Series Fanggs Teeth (TK400FD)	\$8,720.00
BYT11162	36 In (914 mm), 0.97 yd3 (0.74 M3) Heavy-Duty Bucket Includes Four (4) John Deere TK-Series Fanggs Teeth (TK400FD)	\$7,076.00
BYT11163	42 In (1067 mm), 1.19 yd3 (0.91 M3) Heavy-Duty Bucket Includes Five (5) John Deere TK-Series Fanggs Teeth (TK400FD).	\$7,783.00
BYT11164	48 In (1219 mm), 1.39 yd3 (1.06 M3) Heavy-Duty Bucket Includes Six (6) John Deere TK-Series Fanggs Teeth (TK400FD)	\$8,377.00
	Buckets, Side Cutters	Field Installed Attachments - Optional
AT342512	Side-Cutter Kit, 3 inch	\$679.00
AT342513	Side-Cutter Kit, 6 inch	\$679.00
AT342511	Edge Protector Kit	\$655.00
	MISCELLANEOUS	
	Operator Environment	Field Installed Attachments - Optional

Grounds Equipment - Bid #ESCNU 78/19-25 SD)

BYT11013	Mechanical Control Pattern Changer Kit	\$1,133.00
BYT11141	Full Length Front Guards After Serial # 020001	\$1,547.00
	Hydraulic Couplers Field Installed Attachments - Option	
AT452019	Hydraulic Quick Coupler (Non-Variable type) - Coupler and Controls Kit Includes non-variable hydraulic quick coupler with hydraulic and electrical control components	\$10,026.00
AT345608	Installation Charge for Hydraulic Quick Coupler When ordering Hydraulic Quick Coupler (Variable-type Pin-Grabber) must order both Coupler and Controls attachment kits. Installation Charge Order also requires attachment part number, SHIP-TO address for Paladin Custom Works, AND reference related machine order number. The related machine order must reference the attachment order number. Order code available only for Kernersville, North Carolina installations.	\$1,471.00
AT389949	Hydraulic Thumb Kit, Direct for Couplers Teeth matching between the bucket and thumb will depend on the bucket width, number of teeth, and tooth spacing. Please see DMAC solution 94331 for optimum thumb and bucket teeth engagement. Not compatible with Hydraulic Quick Coupler (Variable-type Pin-Grabber) BYT11631.	\$10,493.00
BYT11631	Hydraulic Quick Coupler (Variable-type Pin-Grabber) - Coupler Only Coupler kit ONLY. Includes coupler, jumper hoses, and one set of dead pins. Controls components NOT included. Also purchase Controls Kit BYT11632 (250G/ZX) or BYT11633 (300G/ZX; 345G/ZX). Not compatible with hydraulic thumb AT379652, AT379653, AT379654, or AT379655 (250G/ZX). Not compatible with hydraulic thumb AT389951, AT389948, AT379658, or AT379659 (300G/ZX; 345G/ZX).	\$13,112.00
BYT11633	Hydraulic Quick Coupler Controls Kit, (Variable-type Pin-Grabber) - Controls Kit Only Controls kit ONLY. Includes hydraulic control components, electrical control components and components to manifold on end of arm. Does not include hydraulic quick coupler - also purchase BYT11631. May not be required if replacing existing hydraulic quick coupler.	\$1,613.00
	Hydraulics Field Installed Attachme	ents - Optional
AT445803	Hydraulic Filter Restriction Indicator Kit	\$797.00
AT327659	Anti-Drift Valve with Plumbing and Hardware, Arm Cylinder	\$3,131.00

AT343990	Auxiliary Hydraulics, Attachment Combination Kit	\$595.00
	For use on 220 Mono-Boom Wheeled Excavators. Requires Auxiliary High-Flow Hydraulic Lines. Allows for a combination of attachments (i.e. hammer and thumb) to be connected to the high-flow lines, ready for operation. Kit includes parts to replace the arm tube of the high-flow hydraulic lines with a short tube and uses the existing stop valves to shut-off thumb operation when not in use.	
AT327652	Control Handle for Auxiliary Hydraulics, Left-Hand	\$530.00
	Requires control solenoid for either 1-way or 2-way auxiliary hydraulics. Recommended for use with auxiliary hydraulic lines.	
BYT11143	Hydraulic Pump, 2122 2 Pump Combined Flow	\$1,166.00
	Guards	Field Installed Attachments - Optional
AT390802	Cab FOPS Guard	\$3,259.00
	FOPS Level II. ISO 10262 Certified	

Manufacturer's Suggested List Price shown. Retail prices may vary by dealer. Unless stated otherwise, taxes, freight, setup, delivery and other dealer specific charges not included in the pricing. Options/items noted with anything other than price will have additional costs. Pricing, availability, and specifications subject to change without notice. Special program pricing may be available on certain models. See dealer for details. Prices shown are in U.S. dollars and valid only in the U.S.