### THE FOLLOWING UPDATES HAVE BEEN MADE TO THIS DOCUMENT:

Date	Description of Change
3/23/2018	Removal of Bobcat Safety Training Video
3/1/2017	Effective March ,1, 2017 Bobcat Company has updated power unit options.
01/01/2016	Effective Friday, January 1 <sup>st</sup> , 2016 Bobcat Company has adjusted the SLP of select options and power units.
01/01/2018	Added extended warranty for Bobcat engine machines
01/01/2018	Updated SLP for select machines for January 1st 2018
05/01/2018	Effective Tuesday, May 1, 2018 Bobcat Company has adjusted the SLP of select options and power units.
01/01/2019	Updated SLPs for January 1st 2019
07/06/2020	Effective Monday, July 6th, 2020 Bobcat Company has adjusted the SLP.



## STANDARD EQUIPMENT

Adjustable Vinyl Seats

All-Wheel Steer

Automatically Activated Glow Plugs

Auxiliary Hydraulics: Variable Flow with dual direction detent

Beverage Holders Bob-Tach<sup>TM</sup> Boom Float

Cargo Box Support Cruise Control Dome Light

Horsepower Management

\*Deluxe Operator Canopy includes: Front Window, Rear Window,

Front Wipers, and Electrical Power Port

Limited Slip Transaxle

Engine and Hydraulic Monitor with Shutdown

Front Work Lights

Full-time Four-Wheel Drive

Hydraulic Dump Box

Instrumentation: Hourmeter, Job Hours, Speedometer, Tachometer, Fuel Gauge, Engine Temperature Gauge, and Warning Lights

Leasting Manager Light Controlled and Life Anna Elect

Joystick, Manually Controlled with Lift Arm Float

Lift Arm Support

Parking Brake, automatic

Power Steering with Tilt Steering Wheel

Radiator Screen Lower Engine Cover Rear Receiver Hitch Seat Belts, Shoulder Harness

Spark Arrestor Muffler

Suspension, 4-wheel independent

Tires: 27 x 10.5-15 (8 ply), Lug Tread Toolcat Interlock Control System (TICS)<sup>TM</sup>

Two-Speed Transmission

Machine Warranty: 12 Months, Unlimited Hours

Bobcat Engine Warranty: Additional 12 months or total of 2000

hours after initial 12 month warranty

- \* Roll Over Protective Structure (ROPS) Meets Requirements of SAE-J1040 & ISO 3471
- Falling Object Protective Structure (FOPS) Meets Requirements of SAE-J1043 & ISO3449, Level I

## **QUICK SPECS**

Engine Model	2.4L Bobcat Engine
Horsepower	61
Engine Fuel/Cooling	Diesel/Liquid
Hydraulic Flow-Attachment	18.9 GPM
Hydraulic Flow-Attachment/High Flow	27.9 GPM
Hydraulic Pressure	3000 PSI
Travel Speed (Low)	0-8 MPH
Travel Speed (High)	0-17 MPH
Travel Speed (Reverse)	0-8 MPH
Operating Weight	5685 lbs.
Fuel Capacity	20 gal.
Dimensions (Length x Width x Height)-27 in. Tires	144.5 in. x 60 in. x 81in.
Dimensions (Length x Width x Height)- 29 in. Tires	144.5 in. x 64 in. x 82 in.
	8.25 in.
Ground Clearance – with 29 in. tires	9.2 in.
Cargo Box Specifications	
Inside Dimensions (Length x Width x Height)	56 in. x 51 in. x 10 in.
Bed Height from Ground	38 in.
Cargo Box Maximum Load	2000 lbs.
Turning Diameter-outside in AWS mode	17.5 ft.
Lift Height	84 in.
Maxiumum Reach	35 in.
Rated Operating Capacity	1500 lbs.
Tow Rating	4000 lbs.
Machine Rated Capacity	
(combined weight of load on lift-arm, cargo box load, operator and passenger)	2200 lbs.
Total Rated Capacity	
(combined weight of load on lift-arm, cargo box load, operator and passenger and tow weight)	4200 lbs.

PART	UTILITY WORK MACHINE	
Number	DESCRIPTION	SLP IN US \$
M1221	5600 TURBO UTILITY WORK MACHINE	\$54,472
PART	FACTORY INSTALLED OPTIONS	
NUMBER	DESCRIPTION	SLP IN US \$
	Individual Options	
M1221-R08-C02		\$236
M1221-R02-C03		\$4,864
	Includes doors, floor mats, cab foam, heater and air conditioning unit, three-piece headliner with radio pocket, location for speakers, and storage behind seats for a clip board, owner's manual, etc.	
M1221-P01-C01	DELUXE ROAD PACKAGE  Must also order Cab Enclosure with Heater and Air Conditioning; Includes back-up alarm, turn signals, flashers, taillights, brake lights, rear view mirror, side mirrors, horn, rear work light, and headlights  Allows Work Machine to meet most regulations for driving on local roadways. Check	\$2,322
	with local DMV to confirm all requirements for off-highway machinery on your local roads. Toolcat machines are not "automobiles" and thus do not need to be licensed to drive on local roads, but usually require lighting and mirrors included in this package.	
M1221-R07-C02		
M1221-R03-C02	HIGH FLOW PACKAGE  Includes high flow valve, larger auxiliary hoses, and high flow switch in cab; Provides 27.9 GPM for attachment operation; Must also order 7-Pin Attachment Control	\$1,736
M1221-A01-C05	* '	\$205
M1221-R06-C02		\$336
M1221-R12-C02		. ,
M1221-R15-C02	RADIO OPTION	\$533
M1221-R16-C02		\$545
	Tire Options	
M1221-R05-C04	Set of 4 Tires— In Place of Base Equipment  29 x 10.5, 8 PR, TRAC TIRES  Work Machine Width – 60"	\$546
M1221-R05-C05		\$786

PART	DEALER INSTALLED ACCESSORIES - ORDER FROM SALES			
Number	DESCRIPTION	SLP IN US \$		
The	These Spare Wheel and Tires Assemblies do NOT fit A, B or C-Series Work Machines			
7121766	27 X 10.5-15, 8 PR, TRAC TIRE ASSEMBLY - LEFT	\$351		
7121765	27 X 10.5-15, 8 PR, TRAC TIRE ASSEMBLY - RIGHT	\$351		
7115152	29 X 10.5-15, 8 PR, TRAC TIRE ASSEMBLY - LEFT	\$411		
7115156	29 X 10.5-15, 8 PR, TRAC TIRE ASSEMBLY - RIGHT	\$411		
7115158	29 X 12.5-15, 8 PR, TURF TIRE ASSEMBLY	\$438		

PART	DEALER INSTALLED ACCESSORIES – ORDER FROM PARTS	
NUMBER	DESCRIPTION	SLP IN US \$

For curren	t Dealer Installed Accessories pricing, reference BobQuote or Dealer Parts I	Department
7133350	ATTACHMENT CONTROL KIT, 7-PIN	\$
7120242	ATTACHMENT CONTROL KIT, 14-PIN	\$
7133349	BACKUP ALARM Estimated Install Time 1 hour	\$
6904762	BOBCAT OPERATOR SAFETY DVD	\$
7166194	CENTER INSULATION KIT Estimated Install Time .5 hours	\$
7239665	ENGINE BLOCK HEATER KIT Estimated Install Time 1 hour	\$
7135306	FIRE EXTINGUISHER KIT Estimated Install Time .5 hours	\$
7139070	FLOORBOARD RISER  Raises floorboard for operator comfort and pedal accessibility Estimated Install Time 1 hour	\$
7114297	HORN KIT"	\$
7118026	HOSE GUIDE KIT  Guide installed on left side of Bob-Tach to keep attachment hoses away from the front tire Estimated Install Time .5 hours	\$
7134838	KEYLESS IGNITION KIT	\$
7134486	LOWER DEBRIS GUARD	\$
6817260	MIRROR KIT, REAR VIEW  Includes mirror, mounting puck, and epoxy to attach to front window Estimated Install Time .5 h our	\$
7115060	MIRROR KIT, SIDE  Includes left and right mirrors, mounting brackets and break-away mounts Estimated Install Time 1 hour	\$
7027140	RADIO, AM/FM/WEATHER BAND/AUX-IN JACK Must also order installation kit P/N 7223953 Estimated Install Time 1 hour	\$
7223953	RADIO INSTALLATION KIT  Must be used with P/N 7027140	\$

PART	DEALER INSTALLED ACCESSORIES – ORDER FROM PARTS CONT	•
Number	DESCRIPTION	SLP IN US \$

#### For current Dealer Installed Accessories pricing, reference BobOuote or Dealer Parts Department. 7150926 REAR WINDOW GUARD For 5600 s/n A0W111661 and above Estimated Install Time .5 hour 6815257 REAR WORK LIGHTS..... Estimated Install Time 2 hours 7122379 REMOTE REAR HYDRAULICS KIT, 2.5 GPM For 5600 s/n A0W111001 and above; diverts hydraulic flow from the cargo box hydraulic system to rear poppet-style couplers. The cargo box and the remote rear hydraulics cannot be operated at the same time. Distributes a momentary flow rate of 2.5 GPM. Estimated Install Time 2 hours REMOTE REAR AUX HYDRAULICS KIT, 18 GPM..... 7242743 For 5600 s/n AHG811001 and above; diverts hydraulic flow from the front auxiliary hydraulic system to rear flush face couplers. Front and Rear Auxiliary Hydraulics cannot be operated at the same time. Distributes continuous flow up to 18 GPM Estimated Install Time 6 hours 7135380 Estimated Install Time 6 hours ROTATING BEACON ..... 6815258 Estimated Install Time 1 hour 7199661 SIDE SCREEN KIT..... Estimated Install Time .5 hour 7135575 STEP KIT ..... 6815259 STROBE LIGHT..... Estimated Install Time 1 hour SUSPENSION SEAT, DRIVER SIDE..... 7137285 Estimated Install Time 1 hour



# STANDARD EQUIPMENT

Adjustable Vinyl Seats

All-Wheel Steer

Automatically Activated Glow Plugs

Auxiliary Hydraulics:

Variable Flow with dual direction detent

Beverage Holders

Boom Float

Cab Enclosure with Heater and Air Conditioning

Cowl and Cowl Support

Cruise Control

Deluxe Operator Canopy\*:

Front Window, Rear Window

Front Wipers, and Electrical Power Port

Deluxe Road Package:

Backup alarm, turn signals, flashers, tail lights, brake lights,

Rear

Rear view mirror, side mirrors, horn, rear work lights &

headlights

Dome Light

Engine and Hydraulic Monitor with Shutdown

Front Work Lights

Full-time Four-Wheel Drive

Heavy Duty Battery

High Flow Hydraulics and Attachment Control Kit

Horsepower Management

Instrumentation:

Hourmeter, Job Hours, Speedometer, Tachometer,

Fuel Gauge, Engine Temperature Gauge, and Warning Lights

Traction Control System

Interior Trim

Joystick, Manually Controlled with Lift Arm Float

Keyless Ignition System

Lift Arm Support

Limited Slip Transaxle

Parking Brake, automatic

Power Bob-Tach<sup>TM</sup>

Power Steering with Tilt Steering Wheel

PTO Package: Rear PTO-540 RPM, PTO Shield, PTO

Tachometer

Radiator Screen

Radio W/Aux Input & Headphone Jacks

Lower Engine Cover

Receiver Hitch

Rear Remote Package: One sets of poppet-style couplers, (for use

with implement hydraulics)

Seat Belts, Shoulder Harness

Storage Bins

Suspension, 4-wheel independent

Three-Point Hitch Package: Three-Point, Depth Position

Gange

Tires: 27 x 10.5-15 (8 ply), Lug Tread

Toolcat Interlock Control System (TICS)TM

Two-Speed Transmission

Machine Warranty: 12 Months, Unlimited Hours

Bobcat Engine Warranty: Additional 12 months or total of 2000

hours after initial 12 month warranty

- \* Roll Over Protective Structure (ROPS) Meets Requirements of SAE-J1040 & ISO 3471
- \* Falling Object Protective Structure (FOPS) Meets Requirements of SAE-J1043 & ISO3449, Level I

QUICK SPECS		
Engine Model		D24NAP Turbo
Horsepower		61
Engine Fuel/Cooling		Diesel/Liquid
Hydraulic Flow-Atta	chment	18.9 GPM
Hydraulic Flow-Atta	chment/High Flow	27.9 GPM
		3000 PSI
PTO Horsepower		25 HP
PTO RPM		540
Travel Speed (Low).		0-8 MPH
Travel Speed (High)		0-17 MPH
Travel Speed (Rever	se)	0-8 MPH
Operating Weight		5835 lbs.
Fuel Capacity		20 gal.
Dimensions (Length	x Width x Height)-27 in. Tires	144.5 in. x 60 in. x 81 in.
Dimensions (Length	x Width x Height)- 29 in. Tires	144.5 in. x 64 in. x 82 in.
Ground Clearance -	with 27 in. tires	8.25 in.
Ground Clearance -	with 29 in. tires	9.2 in.
Turning Diameter-ou	tside in AWS mode	17.5 ft.
Lift Height		84 in.
Maxiumum Reach		35 in.
Rated Operating Cap	acity with Three-Point Hitch	1500 lbs.
Three-Point Hitch Li	ft Capacity at 24 inches behind lift point with loader	1775 lbs.
Tow Rating		4000 lbs.
Machine Rated Capa	city	
(combined weight of	of load onlift-arm, three-point, operator and passenger, and storage bins)	2200 lbs.
Total Rated Capacity		
(combined weight of	of load on lift-arm, three-point, operator and passenger, storage bins and tow weight).	4200 lbs.
PART	UTILITY WORK MACHINE	
Number 1	DESCRIPTION	SLP IN US \$
M1223	610 TURBO UTILITY WORK MACHINE	\$68,905
PART	FACTORY INSTALLED OPTIONS	
Number 1	DESCRIPTION	SLP IN US\$
	<u><b>Tire Options</b></u> Set of 4 Tires– In Place of Base Equipment	
M1223-R05-C04	29 X 10.5, 8 PR, TRAC TIRES	\$546
1711 <i>225</i> -1005-004	Work Machine Width – 60"	ФЭТО
M1223-R05-C05	29 x 12.5, 8 PR, TURF TIRES	\$786
	Work Machine Width – 64"; Includes wide fenders	Ψ. 30
	•	

PART	DEALER INSTALLED ACCESSORIES – ORDER FROM SALES	
Number	DESCRIPTION	SLP IN US \$
7121766	27 X 10.5-15, 8 PR, TRAC TIRE ASSEMBLY - LEFT	\$351
7121765	27 X 10.5-15, 8 PR, TRAC TIRE ASSEMBLY - RIGHT	\$351
7115152	29 X 10.5-15, 8 PR, TRAC TIRE ASSEMBLY - LEFT	\$411
7115156	29 x 10.5-15, 8 PR, TRAC TIRE ASSEMBLY - RIGHT	\$411
7115158	29 x 12.5-15, 8 PR, TURF TIRE ASSEMBLY	\$438

PART	DEALER INSTALLED ACCESSORIES - ORDER FROM PARTS	
Number	DESCRIPTION	SLP IN US \$
For curren	t Dealer Installed Accessories pricing, reference BobQuote or Dealer Parts	S Department.
7120242	ATTACHMENT CONTROL KIT, 14-PIN  Controls 14-Pin Attachments only Estimated Install Time .5 hours	\$
6904762	BOBCAT OPERATOR SAFETY DVD	\$
7135306	FIRE EXTINGUISHER KIT  Estimated Install Time .5 hours	\$
7139070	FLOORBOARD RISER  Raises floorboard for operator comfort and pedal accessibility Estimated Install Time 1 hour	\$
7118026	HOSE GUIDE KIT	<b>\$</b>
7134486	LOWER DEBRIS GUARD  Protects engine and fuel tank section under cab from mud and other debris	\$
7174730	REAR AUX ORIFICE KIT	<b>\$</b>
7257423	REAR RH REMOTE HYD KIT  Right Rear Poppet Style Hydraulic connectors For use on Serial number B2LH1101 & Above Estimated Install Time 1.0 hours	<b>\$</b>
6815258	ROTATING BEACON Estimated Install Time 1 hour	\$
7199661	SIDE SCREEN KIT Estimated Install Time .5 hours	<b>\$</b>
7135575	STEP KIT	\$
6815259	STROBE LIGHT Estimated Install Time 1 hour	\$
7137285	SUSPENSION SEAT, DRIVER SIDE Estimated Install Time 1 hour	\$