



October 9, 2019

PRODUCT AND PRICING BULLETIN

NEW HOLLAND BRAND PRODUCTS, U.S. NO. 19-56A

NEW HOLLAND DEALERS WITH MRT AGREEMENT

SUBJECT: WORKMASTER™ 95, 105, 120: INTRODUCTION EFFECTIVE 10/09/2019

The agricultural industry is constantly evolving to meet the world's shifting needs. Here at New Holland, we're focused on matching pace with those changes to help you get the job done. Together, we can make our customers' jobs easier and raise industry standards along the way.

We are pleased to announce the new WORKMASTER 95, 105 and 120 tractors. This represents the final stage of launching a WORKMASTER value line of tractors up to 100 PTO hp and is designed to complement the current lineup of PowerStar Series tractors from 72 to 100 PTO hp. This introduction provides you three models with the Best-In-Class value CAB and ROPS platforms to compete against the best of competitors in the marketplace. It also provides you with a low profile poultry configuration to allow you to get back into the poultry market where New Holland has traditionally been strong and well represented.

New Holland continuously strives to offer products to suit the needs of your customers. To stay competitive in the marketplace, review the customer segments in your primary market of responsibility, ensuring that you have a complete and thorough mix of these products.

This bulletin and the price pages may be accessed via the Dealer Portal if you have the MRT agreement with New Holland. Log on to the Dealer Portal. With the "Wholegoods" button displayed, click on "Pricing," click on "Tractors," and then click on "WORKMASTER Series." The latest published items will appear at the top of the list.

Christine Chleboun Director, Commercial Marketing New Holland, North America Dan Valen Director, Product Marketing New Holland, North America

Attachment







This NEW WORKMASTER utility product offering has been streamlined and simplified to provide you with an offering that fully targets the majority of this value market segment with seven very simple Fast Pick packages:

- 1. Standard Cab Fast Pick
- 2. Deluxe Cab Fast Pick
- 3. Standard ROPS Fast Pick
- 4. Deluxe ROPS Fast Pick
- 5. Poultry NSL Loader Fast Pick
- 6. Poultry NO Loader Fast Pick
- 7. Low Profile All Purpose Fast Pick

These packages incorporate features such as:

- Instructor Seat (Cab models only)
- 2 or 3 rear remotes
- Factory installed 632TL non-self-leveling SSL style loader with 84" bucket
- 540, 540/540E or 540/1,000 RPM PTO
- Up to 4 rear wheel weights per side
- Up to 10 front weights

An a la carte ordering option is available but will be at a premium price to the fast pick packages. This option will allow for tailoring the tractor to specific customer demands within the full product offering.

This WORKMASTER Series provides you with the best combination of comfort, simplicity and visibility in a utility tractor, with a low cost of ownership and competitive price positioning. This is an important combination of features and benefits that addresses the key attributes of a utility tractor that the customers in this market look for when making purchase decisions.

- 1. Comfort
 - a. Best-in-Class Value Cab & ROPS
 - i. Wide, flat deck platform on Cab models and wide semi-straddle deck platform on ROPS models
 - ii. Ergonomic right hand consoles
 - iii. Many comfort items as standard equipment
 - Air suspension seat (Cab models only)
 - Instructor seat (Cab models only)
- 2. Simplicity
 - a. Simple product offering
 - b. Under-hood SCR emissions system (NO REGENERATION)
 - c. Factory-installed loader
- 3. Visibility
 - a. 4 post cab with 316 degrees of visibility
 - b. Optional high-visibility panel
 - c. Low profile, integrated loader
- 4. Low Cost of Ownership
 - a. Long 600 hour engine service intervals
 - b. NO DPF to replace
 - c. 540 RPM PTO operates at a low 1,958 engine RPMs

In order to support the launch of this new WORKMASTER series, a full lineup of support materials are being developed for your reference and will be available later in Q4.





The following documents will be available in the Marketing Library section of the New Holland Library that is accessible through the Dealer Portal.

- Sales Information Document: WORKMASTER 95, 105,120
- Competitive Comparisons:
 - o vs. John Deere 5E cab
 - o vs. John Deere 5E ROPS
 - o vs. John Deere 5090EL ROPS
 - o vs. Kubota M5 cab
 - o vs. Kubota M5 ROPS
 - o vs. Kubota M5L.111 ROPS
 - o vs. Mahindra 7000 & 8000 cab
 - o vs. Mahindra 7000 ROPS
 - o vs. Massey Ferguson 4700 cab
 - vs. Massey Ferguson 4700 ROPS

In addition to these documents, a WORKMASTER Series Tractor Tool Box is currently being developed and will be available in the Document Management Center, accessible through the Dealer Portal. In order to prepare your sales team to capture competitive conquests and other utility tractor customers, this Tool Box includes a full-sized folder and pocket-sized guides which are well-organized and simple to carry.

The WORKMASTER Series Tractor Tool Box will contain the following:

- Pocket folder
 - o Includes 4 special pocket size slots for the guides below
 - 2 large pockets to be able to include information of your choice to help sell a WORKMASTER, which may include:
 - Literature (when available)
 - Sales Information Document
 - Competitive Comparisons
 - Customer Quotes
- Spec guides (Specification Comparisons)
 - o WORKMASTER 95 vs. the competition
 - WORKMASTER 105 vs. the competition
 - WORKMASTER 120 vs. the competition
- Competitive comparison guides for the WORKMASTER cab configurations
- Competitive comparison guides for the WORKMASTER all-purpose ROPS configurations
- Competitive comparison guides for the WORKMASTER Poultry ROPS configurations
- 1 Solutions guide Lists target customers and suggested WORKMASTER configurations and compatible New Holland implements and attachments for each target customer



WORKMASTER™ Series Tractor Index

EQUIPMENT DESCRIPTION	LATEST REVISION	PAGE <u>NUMBER</u>
<u>Index</u>	01/01/20	1
Models WORKMASTER 95, 105, 120 STANDARD CAB FAST PICK	01/01/20	2
WORKMASTER 95, 105, 120 A LA CARTE CAB	01/01/20	6
WORKMASTER 95, 105, 120 STANDARD ROPS FAST PICK	01/01/20	11
WORKMASTER 95, 105, 120 POULTRY NSL/NO LOADER FAST PICKS	01/01/20	15
WORKMASTER 95, 105, 120 LOW PROFILE ALL PURPOSE FAST PICK	01/01/20	21
WORKMASTER 95, 105, 120 ROPS MOWING FAST PICK	01/01/20	26
WORKMASTER 95, 105, 120 A LA CARTE ROPS	01/01/20	31
TIRE CHART	01/01/20	36

WORKMASTER 95-120 STANDARD CAB FAST PICK US PRICE LIST

AGRICULTURE

Standard Equipment

KEY SELLING POINTS:

- Best-in-Class value cab
- Instructor seat
- Air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

Workmaster 95 97 Gross Engine hp

78 PTO hp @ 2300 rpm

4 Cyl Turbocharged Engine

207cu in (3.4 L) Displacement

Workmaster 105

112 Gross Engine hp

92 PTO hp @ 2300 rpm

4 Cyl Turbocharged Engine

207cu in (3.4 L) Displacement

Workmaster 120

120 Gross Engine hp

100 PTO hp @ 2300 rpm

4 Cyl Turbocharged Engine

207cu in (3.4 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:

(CEGR + SCR + CUC)

Electronic Injection Bosch

High-pressure Common Rail System

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Powercore Dry Air Cleaner

Under Hood Muffler

Vertical Exhaust

29 gal Fuel Tank

2.9 gal DEF Tank

2 function mid mount valve & joystick

TRANSMISSION:

LH side steering column mounted

Power Shuttle

12 Forward and 12 Reverse Speeds

Creeper ready

(4) Synchronized Gears

(3) Non-synchronized Ranges

(2) clutches, 5 wet disc plates

FWD - 19 mph (30 KPH)

Speed varies with tire selection

Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering

Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip

Electro-Hydraulic engagement standard

Tread Width: 66.5 in. to 72.9 in.

REAR AXLE

Flange Type

Tread Width: 63.8 in. to 79.5 in.

HYDRAULIC SYSTEM:

Open Center System

Dual Gear Pumps

Implement Pump: 16.9 gpm (64 L)

Steering Pump: 9.7 gpm (37 L)

Total Flow: 26.6 gpm (101 L)

(2) Open Center Remote Valves with

Detent & Kickout on #2 &

Float on #1

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent

Flip-up PTO Shaft Guard

540 RPM hydraulic wet clutch

Electronic engagement

1-3/8 in. 6 splines

WORKMASTER 95-120 STANDARD CAB FAST PICK US PRICE LIST

AGRICULTURE

Standard Equipment

3-POINT LIFT SYSTEM: Right hand console mounted lever control Mechanical Draft Control 3,200 Pounds Lift Capacity Category I/II Combi Ball Ends Telescopic Stabilizers Flexible Lower Link Ends

ELECTRICAL:

(1) 900 cca Heavy-Duty Battery 120 amp Alternator 7-pin Outlet for trailer/implement lighting and signals 30 amp power plug 12V power socket (cigarette lighter)

INSTRUMENTATION:

Digital /Analog Instrumentation with warning lights for turn signals, high beam, work lights, side lights, rear PTO, 4WD, differential lock, low fuel, alternator, oil pressure, brake fluid, grid heater & hand brake Gauges for fuel level, engine temperature and tachometer Digital Readout for PTO speed, ground speed, battery, hours & DEF level percentage

LIGHTING:

Front: (2) Halogen Headlights (2) cab mounted worklights Rear: (2) cab mounted worklights Turn Signals/Flashers/Rear Lights

TIRES:

12.4x24 R1 Front 18.4X30 R1 Rear

OPERATOR PROTECTIVE STRUCTURE: CAB MODELS ROPS protected, 4 post, flat deck platform with heat and air conditioning, tinted windshield, retractable sun screen, front wiper and washer, rear wiper and washer, two doors with locks, two external mirrors, hinged rear window (opens completely) Steering Wheel - adjustable tilt Seat - Cloth covered air suspension, operator's presence sensor, retractable seat belt and arm rests Instructor Seat Suspended pedals Radio, speakers, and antenna

MISCELLANEOUS:

Pivoting Engine Hood SMV Emblem Toolbox

WARRANTY:

New Holland Standard Warranty Applies

LOADER:

632TL NON SELF-LEVELING Maximum Lift Height @ pivot pin: 134.5" Dump Clearance @ 45 deg: 98.4" Digging Depth: 5.1" Lift Capacity @ 800mm: 2,028 LBS Breakout Force @ 800mm: 3,102 LBS Reach @ Max Lift Height @ 45 deg: 37.8" Reach @ Ground Level: 87.4" Bucket Rollback Angle: 40 degrees Bucket Dump Angle: 53 degrees Skid Steer style bucket attach 84" bucket

WORKMASTER 95-120 STANDARD CAB FAST PICK US PRICE LIST

Models

COMMERCIAL MODEL	VERSION	TRACTION	Weight	Factory Data	List Price
WORKMASTER 95 TIER4	Cab	MFD	6,768 LB	9058106P10	\$74,495.00
WORKMASTER 105 TIER4	Cab	MFD	7,936 LB	9060368P10	\$77,395.00
WORKMASTER 120 TIER4	Cab	MFD	7,253 LB	9063176P10	\$80,995.00

Factory Supplied Options

Order Code Description	Weight	Factory Data	List Price
------------------------	--------	--------------	------------

PACKAGE SELECTION

SD_T9980 PACKAGING

	XF9911X	Standard Cab Fast Pick	(902886P00)	(\$3,700.00)
		Standard Cab Fast Pick pricing includes:		
		Cab with openable Black-Out panel		
		2 rear remotes		
		632LA NSL loader with SSL quick attach and 84" bucket		
		Allows for choice of the following:		
		Tires:		
		18.4-30 R1 rear with 12.4-24 R1 front OR		
		16.4-34 R1 rear with 13.6-24 R1 front		
		PTO:		
		540 OR 540/1000 RPM		
		Rear weights:		
		4 rear wheel weights OR NO rear wheel weights		



WORKMASTER 95-120 STANDARD CAB FAST PICK US PRICE LIST

TIRES				
FRONT				
FRONT				
SD_T4940 FR	ONT WHEELS AND TIRES			
4WD Front T	ïres - Ag			
8230506	FRONT 12.4 - 24			No Charge
	Requires 18.4-30 rear tires			
8230505	13.6 -24		9000171P60	\$220.00
	Requires 16.9-34 rear tires			
REAR				
REAR				
SD T4950 RE	AR WHEELS AND TIRES			
Rear tires - A				
	REAR 18.4 - 30			No Charge
	Requires 12.4-24 4WD front or 10.0-16 2WD front			
8930601	REAR 16.9 - 34		(900109P20)	(\$140.00)
	Requires 13.6-24 4WD front or 10.0-16 2WD front			
PTO				
REAR PTO				
SD_T8010 PT				
759271	540 RPM W CAP	1		No Charge
759273	540-1000 RPM W CAP	1	9000413P40	\$530.00
WEIGHTO				
WEIGHTS				
DEAD WHEEL WE	IOLITO			
REAR WHEEL WE	IGH15			
SD_T4960 WH	HEEL WEIGHTS			
762028	2X55or32Kg EACH SIDE		9000491P40	\$630.00
	2 (110 lb) rear weights per side = 220 lbs total for all rear tires			*******
	sizes except 500/60-22.5			
	·			
	2 (70 lb) rear weights per side = 140 lbs total for 500/60-22.5			
	rear tires			
			-	
OPERATOR'S MA	NUALS			
SD_T9805 OF	ERATOR MANUAL (SE			
342076	French (Canada)	1		No Charge
342077	Spanish			No Charge

8

-T1LA 01

WORKMASTER 95-120 A LA CARTE CAB US PRICE LIST

AGRICULTURE

Standard Equipment

KEY SELLING POINTS:

- Best-in-Class value cab
- Instructor seat
- Air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

Workmaster 95 97 Gross Engine hp 78 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine

207cu in (3.4 L) Displacement

Workmaster 105 112 Gross Engine hp 92 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207cu in (3.4 L) Displacement

Workmaster 120 120 Gross Engine hp 100 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207cu in (3.4 L) Displacement

ALL MODELS:

Tier B Emissions Compliant: (CEGR + SCR + CUC) Electronic Injection Bosch High-pressure Common Rail System Electric Engine Shutoff Hand and Foot Throttle Controls Grid Heater Starting Aid Powercore Dry Air Cleaner Under Hood Muffler Vertical Exhaust 29 gal Fuel Tank 2.9 gal DEF Tank 2 function mid mount valve & joystick

TRANSMISSION:

LH side steering column mounted Power Shuttle 12 Forward and 12 Reverse Speeds Creeper ready

- (4) Synchronized Gears
- (3) Non-synchronized Ranges
- (2) clutches, 5 wet disc plates

FWD - 19 mph (30 KPH) Speed varies with tire selection Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE: Limited Slip

Electro-Hydraulic engagement standard Tread Width: 63.8 in. to 72.9 in.

REAR AXLE Flange Type Tread Width: 63.9 in. to 79.7 in.

HYDRAULIC SYSTEM:

Open Center System Dual Gear Pumps Implement Pump: 16.9 gpm (64 L) Steering Pump: 9.7 gpm (37 L) Total Flow: 26.6 gpm (101 L) (2) Open Center Remote Valves with Detent & Kickout on #2 & Float on #1

REAR DIFFERENTIAL LOCK: Mechanically Engaged

PTO:

Fully Independent Flip-up PTO Shaft Guard 540 RPM hydraulic wet clutch Electronic engagement 1-3/8 in. 6 splines

WORKMASTER 95-120 A LA CARTE CAB US PRICE LIST

AGRICULTURE

Standard Equipment

3-POINT LIFT SYSTEM:
Right hand console mounted
lever control
Mechanical Draft Control
3,200 Pounds Lift Capacity
Category I/II Combi Ball Ends
Telescopic Stabilizers
Flexible Lower Link Ends

ELECTRICAL:

(1) 900 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
 and signals
30 amp power plug
12V power socket (cigarette lighter)

INSTRUMENTATION:

Digital /Analog Instrumentation with warning lights for turn signals, high beam, work lights, side lights, rear PTO, 4WD, differential lock, low fuel, alternator, oil pressure, brake fluid, grid heater & hand brake Gauges for fuel level, engine temperature and tachometer Digital Readout for PTO speed, ground speed, battery, hours & DEF level percentage

LIGHTING:

TIRES:

12.4x24 R1 Front 18.4X30 R1 Rear

OPERATOR PROTECTIVE STRUCTURE: CAB MODELS ROPS protected, 4 post, flat deck platform with heat and air conditioning, tinted windshield, retractable sun screen, front wiper and washer, rear wiper and washer, two doors with locks, two external mirrors, hinged rear window (opens completely) Steering Wheel - adjustable tilt Seat - Cloth covered air suspension, operator's presence sensor, retractable seat belt and arm rests Instructor Seat Suspended pedals Radio, speakers, and antenna

MISCELLANEOUS:

84" bucket

Pivoting Engine Hood SMV Emblem Toolbox

WARRANTY:

New Holland Standard Warranty Applies

LOADER:

632TL NON SELF-LEVELING
Maximum Lift Height @
pivot pin: 134.5"

Dump Clearance @ 45 deg: 98.4"

Digging Depth: 5.1"

Lift Capacity @ 800mm: 2,028 LBS

Breakout Force @ 800mm: 3,102 LBS

Reach @ Max Lift Height @ 45

deg: 37.8"

Reach @ Ground Level: 87.4"

Bucket Rollback Angle: 40 degrees

Bucket Dump Angle: 53 degrees

Skid Steer style bucket attach

WORKMASTER 95-120 A LA CARTE CAB US PRICE LIST

Models

COMMERCIAL MODEL	VERSION	TRACTION	Weight	Factory Data	List Price
WORKMASTER 95 TIER4	Cab	MFD	6,768 LB	9058106P10	\$74,495.00
WORKMASTER 105 TIER4	Cab	MFD	7,936 LB	9060368P10	\$77,395.00
WORKMASTER 120 TIER4	Cab	MFD	7,253 LB	9063176P10	\$80,995.00

Factory Supplied Options

Order Code Description	Weight Factory Data List Price
------------------------	--------------------------------

OPERATOR PLATFORM

SD_T9200 OPERATOR STRUCTURE #1

Cab			
762	2204 HVAC CAB 2 REMOTE PS		No Charge
	Cab with TWO rear remotes includes:		
	- Blacked out vent panel		
	- 2 rear view mirrors		
	- Air suspension seat		
	- Bluetooth radio		
	- Rear wiper/wwasher		
	- 12x12 powershuttle transmission		
762	2205 HVAC CAB 3 REMOTE PS	9000	0624P00 \$800.00
	Cab with THREE rear remotes includes:		
	- Blacked out vent panel		
	- 2 rear view mirrors		
	- Air suspension seat		
	- Bluetooth radio		
	- Rear wiper/wwasher		
	- 12x12 powershuttle transmission		
	DELAYED OPTION WILL NOT BE AVAILABLE UNTIL		
1 1 1	MID 2020 AT THE EARLIEST		

TIRES

WORKMASTER 95-120 A LA CARTE CAB US PRICE LIST

FRONT			
SD T4940 FR	ONT WHEELS AND TIRES		
4WD Front 7			
8220701	11.2 - 24	(900046P80)	(\$60.00)
	Requires 16.9-30 rear tires		
8230506	FRONT 12.4 - 24		No Charge
	Requires 18.4-30 rear tires		_
8230505	13.6 -24	9000171P60	\$220.00
	Requires 16.9-34 rear tires		
4WD Front 7		·	
8230503	FRONT 12.5 - 18	9000546P00	\$700.00
	Requires 19.5L-24 rear tires		
Rear tires - A	AR WHEELS AND TIRES		
8930602		9000234P00	\$300.00
0000005	Requires 11.2-24 4WD front or 7.50-16 2WD front		N. Observe
8930605	REAR 18.4 - 30		No Charge
0000004	Requires 12.4-24 4WD front or 10.0-16 2WD front	(0004000000)	(ft4.40.00)
8930601	REAR 16.9 - 34	(900109P20)	(\$140.00)
Rear tires - I	Requires 13.6-24 4WD front or 10.0-16 2WD front		
8930603	REAR 19.5 - 24	9000487P50	\$625.00
0930003	· · · · · · · · · · · · · · · · · · ·	9000487 F 30	φ023.00
	Requires 12.5/80-18 4WD front tires		
LOADER			
LUADER			
LOADER			
LOADLIN			

	345324	L/ LOADER FOR MMV	(905070P00)	(\$6,500.00)
		Mid Mount Valve and Joystick ONLY.		
	343422	LOADER READY 343422	(901154P40)	(\$1,480.00)
		Complete loader ready includes:		
		- Horizontal and Vertical TPS loader brackets		
		- 2 function mid mount valve and joystick		
		- Hoses from mid mount valve to vertical bracket		
		- Grill guard		
	762057	TL632 FULL NS762057		No Charge
		632TL Non self leveling loader with 84" SSL Bucket		

342077

Spanish



WORKMASTER 95-120 A LA CARTE CAB US PRICE LIST

РТО			
110			
REAR PTO			
SD_T8010 P			
759271	540 RPM W CAP		No Charge
759272	540-540E RPM W CAP	9000354P90	\$455.00
759273	540-1000 RPM W CAP	9000413P40	\$530.00
WEIGHTS			
WEIGHTO			
FRONT WEIGHT:	5		
	-		
SD T2151 V	/EIGHT PACK		
342070	110KgFCW/10X40-510kg	9000975P00	\$1,250.00
	Front carrier (154 lbs) + 10 weights (88lbs each) = 1,034 lbs		, ,
342069	110KgFC W/8X40-430kg	9000780P00	\$1,000.00
	Front carrier (154 lbs) + 8 weights (88lbs each) = 858 lbs		, ,
	/HEEL WEIGHTS		
762028	2X55or32Kg EACH SIDE	9000491P40	\$630.00
102020	2 (110 lb) rear weights per side = 220 lbs total for all rear tires	30004311 40	ψ030.00
	sizes except 500/60-22.5		
	2 (70 lb) rear weights per side = 140 lbs total for 500/60-22.5 rear tires		
759650	4X55or32Kg EACH SIDE	9000982P80	\$1,260.00
	4 (110 lb) rear weights per side = 440 lbs total for all rear tires	333332: 33	ψ.,=σσ.σσ
	sizes except 500/60-22.5		
	4 (70 lb) rear weights per side = 280 lbs total for 500/60-22.5		
	rear tires		
		1	
OPERATOR'S M	ANUAI S		
OI LIVATOR O W	ANONEO		
SD T9805 C	PERATOR MANUAL (SE		
342076	French (Canada)		No Charge
1 0-2010	· · · · · · · · (Carrada)	 	140 Onlarge

No Charge



WORKMASTER 95-120 STANDARD ROPS FASTPICK US PRICE LIST

Standard Equipment

KEY SELLING POINTS:

- Semi straddle ROPS
- Air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

Workmaster 95 97 Gross Engine hp 78 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207cu in (3.4 L) Displacement

Workmaster 105 112 Gross Engine hp 92 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207cu in (3.4 L) Displacement

Workmaster 120 120 Gross Engine hp 100 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207cu in (3.4 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:
(CEGR + SCR + CUC)

Electronic Injection Bosch
High-pressure Common Rail System

Electric Engine Shutoff
Hand and Foot Throttle Controls

Grid Heater Starting Aid

Powercore Dry Air Cleaner

Under Hood Muffler

Horizontal Rearward Exhaust

24 gal Fuel Tank

2.9 gal DEF Tank

2 function mid mount valve & joystick

TRANSMISSION:

LH side steering column mounted Power Shuttle

Creeper ready

- 12 Forward and 12 Reverse Speeds
- (4) Synchronized Gears
- (3) Non-synchronized Ranges
- (2) clutches, 5 wet disc plates FWD 19 mph (30 KPH) speed may vary Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering
Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip

Electro-Hydraulic engagement standard Tread Width: 66.5 in. to 72.9 in.

REAR AXLE

Flange Type

Tread Width: 63.8 in. to 79.5 in.

HYDRAULIC SYSTEM:

Open Center System

Dual Gear Pumps

Implement Pump: 16.9 gpm (64 L)
Steering Pump: 9.7 gpm (37 L)
Total Flow: 26.6 gpm (101 L)

(2) Open Center Remote Valves with

Detent & Kickout on #2

Float on #1

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent Flip-up PTO Shaft Guard 540 RPM hydraulic wet clutch Electronic engagement 1-3/8 in. 6 splines

WORKMASTER 95-120 STANDARD ROPS FASTPICK US PRICE LIST

Standard Equipment

3-POINT LIFT SYSTEM:
Right hand console mounted
lever control
Mechanical Draft Control
3,200 Pounds Lift Capacity
Category I/II Combi Ball Ends
Telescopic Stabilizers
Flexible Lower Link Ends

ELECTRICAL:

(1) 800 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
 and signals
30 amp power plug
12V power socket (cigarette lighter)

INSTRUMENTATION:

Digital /Analog Instrumentation with warning lights for turn signals, high beam, work lights, side lights, rear PTO, 4WD, differential lock, low fuel, alternator, oil pressure, brake fluid, grid heater & hand brake Gauges for fuel level, engine temperature and tachometer
Digital Readout for PTO speed, ground speed, battery, hours & DEF level percentage

LIGHTING:

Front: (2) Halogen Headlights
Rear: (1) Right hand fender
mounted worklights
Turn Signals/Flashers/Rear Lights

TIRES:

12.4x24 R1 Front 18.4X30 R1 Rear OPERATOR PROTECTIVE STRUCTURE:
ROPS MODELS
2-Post Foldable ROPS with ISOmounted flat deck platform
Steering Wheel - adjustable tilt
Seat - Low profile air suspension seat,
operator's presence sensor, and
retractable seat belts
Suspended pedals
Locking brake pedals

MISCELLANEOUS:

84" bucket

15

Pivoting Engine Hood SMV Emblem Toolbox

WARRANTY:

New Holland Standard Warranty Applies

LOADER:

632TL NON SELF-LEVELING
Maximum Lift Height @
pivot pin: 134.5"
Dump Clearance @ 45 deg: 98.4"
Digging Depth: 5.1"
Lift Capacity @ 800mm: 2,028 LBS
Breakout Force @ 800mm: 3,102 LBS
Reach @ Max Lift Height @ 45
deg: 37.8"
Reach @ Ground Level: 87.4"
Bucket Rollback Angle: 40 degrees
Bucket Dump Angle: 53 degrees
Skid Steer bucket attach

WORKMASTER 95-120 STANDARD ROPS FASTPICK US PRICE LIST

Models

COMMERCIAL MODEL	VERSION	TRACTION	Weight	Factory Data	List Price
WORKMASTER 95 TIER4	Rops	MFD	7,451 LB	9046694P70	\$59,865.00
WORKMASTER 105 TIER4	Rops	MFD	7,451 LB	9048956P70	\$62,765.00
WORKMASTER 120 TIER4	Rops	MFD	7,936 LB	9051764P70	\$66,365.00

Factory Supplied Options

Order Code Description	Weight	Factory Data	List Price
------------------------	--------	--------------	------------

PACKAGE SELECTION

SD_T9980 PACKAGING

	XF9913X	Standard ROPS Fast Pick	(902886P00)	(\$3,700.00)
		ROPS Standard Fast Pick pricing includes:		
		2 rear remotes		
		632LA NSL loader with SSL quick attach and 84" bucket		
		Allows for choice of the following:		
		Tires:		
		18.4-30 R1 rear with 12.4-24 R1 front OR		
		16.4-34 R1 rear with 13.6-24 R1 front		
		PTO:		
		540 OR 540/1000 RPM		
		Rear weights:		
		4 rear wheel weights OR NO rear wheel weights		

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

	4WD Front Tires - Ag						
8230506 FRONT 12.4 - 24						No Charge	
			Requires 18.4-30 rear tires				

342076

342077

French (Canada)

Spanish

WORKMASTER 95-120 STANDARD ROPS FASTPICK US PRICE LIST

AGRICULTURE

	8230505	13.6 -24	9	9000171P60	\$220.00
		Requires 16.9-34 rear tires			
	•				
RE	AR				
	SD T4950 RE	AR WHEELS AND TIRES			
	Rear tires - /	Ag			
	8930605	REAR 18.4 - 30			No Charge
		Requires 12.4-24 4WD front or 10.0-16 2WD front			-
	8930601	REAR 16.9 - 34	(!	900109P20)	(\$140.00)
		Requires 13.6-24 4WD front or 10.0-16 2WD front	'	ĺ	,
	'		'	'	
PTC)				
RE	AR PTO				
	SD_T8010 PT	·O			
	759271	540 RPM W CAP			No Charge
\vdash	759273	540-1000 RPM W CAP	,	9000413P40	\$530.00
	1 .002.0				φοσο.σο
WEI	IGHTS				
VVE	ВПІЗ				
	AR WHEEL WE	ICHTC			
	AK WHEEL WE	юпто			
	CD T4060 W/I	IFFL WEIGHTS			
	762028	HEEL WEIGHTS 2X55or32Kg EACH SIDE		9000491P40	\$630.00
	702020	_ =		9000491P40	φο30.00
		2 (110 lb) rear weights per side = 220 lbs total for all rear tires			
		sizes except 500/60-22.5			
		2 (70 lb) rear weights per side = 140 lbs total for 500/60-22.5			
Ш		rear tires			
OPE	ERATOR'S MA	NUALS			
	SD T9805 OF	PERATOR MANUAL (SE			

No Charge

No Charge



WORKMASTER 95-120 AP LOW PRO FAST PICK US PRICE LIST

Standard Equipment

KEY SELLING POINTS:

- Low profile semi straddle ROPS
- Low profile air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

Workmaster 95

97 Gross Engine hp

78 PTO hp @ 2300 rpm

4 Cyl Turbocharged Engine

207cu in (3.4 L) Displacement

Workmaster 105

112 Gross Engine hp

92 PTO hp @ 2300 rpm

4 Cyl Turbocharged Engine

207cu in (3.4 L) Displacement

Workmaster 120

120 Gross Engine hp

100 PTO hp @ 2300 rpm

4 Cyl Turbocharged Engine

207cu in (3.4 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:

(CEGR + SCR + CUC)

Electronic Injection Bosch

High-pressure Common Rail System

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Powercore Dry Air Cleaner

Under Hood Muffler

Horizontal Rearward Exhaust

24 gal Fuel Tank

2.9 gal DEF Tank

2 function mid mount valve & joystick $\,$

TRANSMISSION:

LH side steering column mounted

Power Shuttle

Creeper ready

12 Forward and 12 Reverse Speeds

- (4) Synchronized Gears
- (3) Non-synchronized Ranges
- (2) clutches, 5 wet disc plates

FWD - 19 mph (30 KPH) speed may vary

Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering

Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip

Electro-Hydraulic engagement standard

Tread Width: 63.8 in. to 71.6 in.

REAR AXLE

Flange Type

Tread Width: 63.9 in. to 79.7 in.

HYDRAULIC SYSTEM:

Open Center System

Dual Gear Pumps

Implement Pump: 16.9 gpm (64 L)

Steering Pump: 9.7 gpm (37 L)

Total Flow: 26.6 gpm (101 L)

(2) Open Center Remote Valves with

Detent & Kickout on #2

Float on #1

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent

Flip-up PTO Shaft Guard

540 RPM hydraulic wet clutch

Electronic engagement

1-3/8 in. 6 splines

WORKMASTER 95-120 AP LOW PRO FAST PICK US PRICE LIST

Standard Equipment

3-POINT LIFT SYSTEM:
Right hand console mounted
lever control
Mechanical Draft Control
3,200 Pounds Lift Capacity
Category I/II Combi Ball Ends
Telescopic Stabilizers
Flexible Lower Link Ends

ELECTRICAL:

(1) 800 cca Heavy-Duty Battery120 amp Alternator7-pin Outlet for trailer/implement lighting and signals30 amp power plug12V power socket (cigarette lighter)

INSTRUMENTATION:

Digital /Analog Instrumentation with warning lights for turn signals, high beam, work lights, side lights, rear PTO, 4WD, differential lock, low fuel, alternator, oil pressure, brake fluid, grid heater & hand brake Gauges for fuel level, engine temperature and tachometer Digital Readout for PTO speed, ground speed, battery, hours & DEF level percentage

LIGHTING:

Front: (2) Halogen Headlights
Rear: (1) Right hand fender
 mounted worklights
Turn Signals/Flashers/Rear Lights

OPERATOR PROTECTIVE STRUCTURE:
ROPS MODELS
2-Post Foldable ROPS with ISOmounted flat deck platform
Steering Wheel - adjustable tilt
Seat - Low profile air suspension seat,
operator's presence sensor, and
retractable seat belts
Suspended pedals
Locking brake pedals

TIRES:

11.5/80-15.3 R1 Front 500/60-22.5 R1 Rear OR 12.5/80-18 R4 Front 19.5L24 R4 Rear OR 11.2-24 Front 16.9x30 Rear

MISCELLANEOUS:

Pivoting Engine Hood SMV Emblem Toolbox

WARRANTY:

New Holland Standard Warranty Applies

WORKMASTER 95-120 AP LOW PRO FAST PICK US PRICE LIST

Models

COMMERCIAL MODEL	VERSION	TRACTION	Weight	Factory Data	List Price
WORKMASTER 95 TIER4	Rops	MFD	7,451 LB	9046694P70	\$59,865.00
WORKMASTER 105 TIER4	Rops	MFD	7,451 LB	9048956P70	\$62,765.00
WORKMASTER 120 TIER4	Rops	MFD	7,936 LB	9051764P70	\$66,365.00

Factory Supplied Options

Order Code Description	Weight	Factory Data	List Price
------------------------	--------	--------------	------------

PACKAGE SELECTION

SD_T9980 PACKAGING

XF9917X	Low Profile All Purpose Fast P	(902886P00)	(\$3,700.00)
	Low Profile All Purpose Fast Pick		
	Allows for choice of the following:		
	Tires:		
	1		
	16.9-30 R1 rear with 11.2-24 R1 front OR		
	19.5L27 R4 rear with 12.5-80/18 R4 front OR		
	500/60-22.5 R1 rear with 11.5/80-15.3 R1 front		
	Rear Remotes:		
	2 or 3 remotes		
	PTO:		
	540 OR 540/1000 RPM		
	Rear weights:		
	4 rear wheel weights OR NO rear wheel weights		
	Front weights:		
	8, 10 OR NO front weights		
	Mid mount valve / loader:		
	NO mid mount valve or loader OR		
	Mid mount valve with NO brackets & NO Loader OR		
	Complete loader ready (mid mount valve, hoses and brackets)		

WORKMASTER 95-120 AP LOW PRO FAST PICK US PRICE LIST

TI	RES	S				
	FRO	NT				
	S	D_T4940 FR	ONT WHEELS AND TIRES			
		4WD Front T	ires - Ag			
		8220701	11.2 - 24		(900046P80)	(\$60.00)
			Requires 16.9-30 rear tires			
		8811501	11.5/80-15.3		9000546P00	\$700.00
			Requires 500/60-22.5 rear tires			
			(ROPS ONLY)			
		4WD Front T	ires - Ind			
		8230503	FRONT 12.5 - 18		9000546P00	\$700.00
			Requires 19.5L-24 rear tires			
I	REA	.R				
	S	D_T4950 RE	AR WHEELS AND TIRES			
		Rear tires - A	Ag	_		
		8930602	REAR 16.9 - 30		9000234P00	\$300.00
			Requires 11.2-24 4WD front or 7.50-16 2WD front			
		8310501	500/60-22.5		9000487P50	\$625.00
			Requires 11.5/80-15.3 4WD front tires			
			(ROPS ONLY)			
		Rear tires - I	nd			
		8930603	REAR 19.5 - 24		9000487P50	\$625.00
			Requires 12.5/80-18 4WD front tires			
H.	YDF	RAULICS				
	REA	R REMOTES				
	S	D T8270 RE	AR REMOTES			
		762052	2 REMOTE 762052			No Charge
			2 rear remotes for Open Platform with foldable ROPS			3
			Float on remote 1			
			Extend and retract detent and kick-out on remote 2			
		762053	3 REMOTE 762053		9000624P00	\$800.00
			3 rear remotes for Open Platform with foldable ROPS			+ 223.00
			Float on remote 1 & 3			

Extend and retract detent and kick-out on remote 2

rear tires

WORKMASTER 95-120 AP LOW PRO FAST PICK US PRICE LIST

L	DAC	DER			
	_OA	DER			
	_ <u>S</u>		DADER BRACKETS		
		343422	LOADER READY 343422	(901154P40)	(\$1,480.00)
			Complete loader ready includes:		
			- Horizontal and Vertical TPS loader brackets		
			- 2 function mid mount valve and joystick		
			- Hoses from mid mount valve to vertical bracket		
			- Grill guard		
		762057	TL632 FULL NS762057		No Charge
			632TL Non self leveling loader with 84" SSL Bucket		
P.	ГО				
	REA	R PTO			
	S	D_T8010 PT			
		759271	540 RPM W CAP		No Charge
		759273	540-1000 RPM W CAP	9000413P40	\$530.00
W	EIG	HTS			
	FRO	NT WEIGHTS			
	<u>S</u>	D_T2151 WE	EIGHT PACK		
		342070	110KgFCW/10X40-510kg	9000975P00	\$1,250.00
			Front carrier (154 lbs) + 10 weights (88lbs each) = 1,034 lbs		
		342069	110KgFC W/8X40-430kg	9000780P00	\$1,000.00
			Front carrier (154 lbs) + 8 weights (88lbs each) = 858 lbs		
	REA	R WHEEL WE	IGHTS		
	S	D_T4960 WI	HEEL WEIGHTS		
		762028	2X55or32Kg EACH SIDE	9000491P40	\$630.00
			2 (110 lb) rear weights per side = 220 lbs total for all rear tires		
			sizes except 500/60-22.5		
	ıl		2 (70 lb) rear weights per side = 140 lbs total for 500/60-22.5		

New Holland 11-1-19



-T1LA 06

WORKMASTER 95-120 AP LOW PRO FAST PICK US PRICE LIST

OPERATOR'S MANUALS

SD_T9805 OPERATOR MANUAL (SE

	<u> </u>					
		342076	French (Canada)			No Charge
Г		342077	Spanish			No Charge



WORKMASTER 95-120 POULTRY FAST PICKS US PRICE LIST

Standard Equipment

KEY SELLING POINTS:

- Low profile semi straddle ROPS
- Low profile air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

Workmaster 95 97 Gross Engine hp 78 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine

207cu in (3.4 L) Displacement

Workmaster 105 112 Gross Engine hp 92 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207cu in (3.4 L) Displacement

Workmaster 120 120 Gross Engine hp 100 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207cu in (3.4 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:
 (CEGR + SCR + CUC)
Engine Reversing Fan
Electronic Injection Bosch
 High-pressure Common Rail System
Electric Engine Shutoff
Hand and Foot Throttle Controls
Grid Heater Starting Aid
Powercore Dry Air Cleaner
Under Hood Muffler
Horizontal Rearward Exhaust
24 gal Fuel Tank
2.9 gal DEF Tank
2 function mid mount valve & joystick

TRANSMISSION:

LH side steering column mounted Power Shuttle

Creeper ready

- 12 Forward and 12 Reverse Speeds
- (4) Synchronized Gears
- (3) Non-synchronized Ranges
- (2) clutches, 5 wet disc plates FWD 19 mph (30 KPH) speed may vary Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering
Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip

Electro-Hydraulic engagement standard Tread Width: 63.8 in. to 68.5 in.

REAR AXLE

Flange Type

Tread Width: 64.8 in. to 72.7 in.

HYDRAULIC SYSTEM:

Open Center System

Dual Gear Pumps

Implement Pump: 16.9 gpm (64 L)
Steering Pump: 9.7 gpm (37 L)

Total Flow: 26.6 gpm (101 L)

(2) Open Center Remote Valves with

Detent & Kickout on #2


Float on #1

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent
Flip-up PTO Shaft Guard
540 RPM hydraulic wet clutch
Electronic engagement
1-3/8 in. 6 splines



AGRICULTURE

Standard Equipment

3-POINT LIFT SYSTEM:
Right hand console mounted
lever control
Mechanical Draft Control
3,200 Pounds Lift Capacity
Category I/II Combi Ball Ends
Telescopic Stabilizers
Flexible Lower Link Ends

ELECTRICAL:

(1) 800 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
 and signals
30 amp power plug
12V power socket (cigarette lighter)

INSTRUMENTATION:

Digital /Analog Instrumentation with warning lights for turn signals, high beam, work lights, side lights, rear PTO, 4WD, differential lock, low fuel, alternator, oil pressure, brake fluid, grid heater & hand brake Gauges for fuel level, engine temperature and tachometer Digital Readout for PTO speed, ground speed, battery, hours & DEF level percentage

LIGHTING:

Front: (2) Halogen Headlights
Rear: (1) Right hand fender
mounted worklights
Turn Signals/Flashers/Rear Lights

MISCELLANEOUS:

Pivoting Engine Hood SMV Emblem Toolbox

TIRES:

11.5/80-15.3 R1 Front 500/60-22.5 R1 Rear OR 12.5/80-18 R4 Front 19.5L24 R4 Rear

OPERATOR PROTECTIVE STRUCTURE:
ROPS MODELS
2-Post Foldable ROPS with ISOmounted flat deck platform
Steering Wheel - adjustable tilt
Seat - Low profile air suspension seat,
operator's presence sensor, and
retractable seat belts
Suspended pedals
Locking brake pedals

WARRANTY:

New Holland Standard Warranty Applies

632TL NON SELF-LEVELING

LOADER:

Maximum Lift Height @
pivot pin: 134.5"

Dump Clearance @ 45 deg: 98.4"

Digging Depth: 5.1"

Lift Capacity @ 800mm: 2,028 LBS

Breakout Force @ 800mm: 3,102 LBS

Reach @ Max Lift Height @ 45

deg: 37.8"

Reach @ Ground Level: 87.4"

Bucket Rollback Angle: 40 degrees

Bucket Dump Angle: 53 degrees

Skid Steer bucket attach

84" bucket

WORKMASTER 95-120 POULTRY FAST PICKS US PRICE LIST

Models

COMMERCIAL MODEL	VERSION	TRACTION	Weight	Factory Data	List Price
WORKMASTER 95 TIER4	Rops	MFD	7,451 LB	9046694P70	\$59,865.00
WORKMASTER 105 TIER4	Rops	MFD	7,451 LB	9048956P70	\$62,765.00
WORKMASTER 120 TIER4	Rops	MFD	7,936 LB	9051764P70	\$66,365.00

Factory Supplied Options

Order Code Description	Weight	Factory Data	List Price
------------------------	--------	--------------	------------

PACKAGE SELECTION

SD_T9980 PACKAGING

XF9915X	Poultry NSL Loader Fast Pick	(900429P00)	(\$550.00)
	Poultry NSL Loader Fast Pick pricing includes:		
	Reversing engine fan		
	632LA NSL loader with SSL quick attach and 84" bucket		
	Allows for choice of the following:		
	Tires:		
	19.5L27 R4 rear with 12.5-80/18 R4 front OR		
	500/60-22.5 R1 rear with 11.5/80-15.3 R1 front		
	Rear Remotes:		
	2 or 3 remotes		
	PTO:		
	540 OR 540/1000 RPM		
	Rear weights:		
	4 rear wheel weights OR NO rear wheel weights		

WORKMASTER 95-120 POULTRY FAST PICKS US PRICE LIST

XF9916X	Poultry NO Loader Fast Pick	(906653P40)	(\$8,530.00)
	Poultry NSL Loader Fast Pick pricing includes:		
	Reversing engine fan		
	Less loader and mid mount valve		
	Allows for choice of the following:		
	Tires:		
	19.5L27 R4 rear with 12.5-80/18 R4 front OR		
	500/60-22.5 R1 rear with 11.5/80-15.3 R1 front		
	Rear Remotes:		
	2 or 3 remotes		
	PTO:		
	540 OR 540/1000 RPM		
	Rear weights:		
	4 rear wheel weights OR NO rear wheel weights		

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

4WD Front Tires - Ag					
	8811501	11.5/80-15.3		9000546P00	\$700.00
		Requires 500/60-22.5 rear tires			
		(ROPS ONLY)			
	4WD Front T	ïres - Ind			
	8230503	FRONT 12.5 - 18		9000546P00	\$700.00
		Requires 19.5L-24 rear tires			

REAR

SD_T4950 REAR WHEELS AND TIRES

Rear tires - Ag					
	8310501	500/60-22.5		9000487P50	\$625.00
		Requires 11.5/80-15.3 4WD front tires			
		(ROPS ONLY)			
	Rear tires - I	nd			
	8930603	REAR 19.5 - 24	_	9000487P50	\$625.00
		Requires 12.5/80-18 4WD front tires			

342077 Spanish

WORKMASTER 95-120 POULTRY FAST PICKS US PRICE LIST

Н	YDF	RAULICS			
	REA	R REMOTES			
	S		AR REMOTES		
		762052	2 REMOTE 762052		No Charge
			2 rear remotes for Open Platform with foldable ROPS		
			Float on remote 1		
			Extend and retract detent and kick-out on remote 2		
		762053	3 REMOTE 762053	9000624P00	\$800.00
			3 rear remotes for Open Platform with foldable ROPS		
			Float on remote 1 & 3		
			Extend and retract detent and kick-out on remote 2		
					•
P	то				
	REA	R PTO			
	s	D_T8010 PT	0		
	ΠĬ	759271	540 RPM W CAP		No Charge
		759273	540-1000 RPM W CAP	9000413P40	\$530.00
					, , , , , , , , , , , , , , , , , , , ,
W	'EIG	HTS			
	REA	R WHEEL WE	IGHTS		
	S	D_T4960 WH	HEEL WEIGHTS		
		762028	2X55or32Kg EACH SIDE	9000491P40	\$630.00
			2 (110 lb) rear weights per side = 220 lbs total for all rear tires		
			sizes except 500/60-22.5		
			·		
			2 (70 lb) rear weights per side = 140 lbs total for 500/60-22.5		
			rear tires		
0	PEF	RATOR'S MA	NUALS		
	S	D T9805 OP	ERATOR MANUAL (SE		
	ĺ	342076	French (Canada)		No Charge

No Charge



WORKMASTER 95-120 ROPS MOWING FAST PICK US PRICE LIST

Standard Equipment

KEY SELLING POINTS:

- Semi straddle ROPS
- Air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

Workmaster 95 97 Gross Engine hp 78 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207cu in (3.4 L) Displacement

Workmaster 105 112 Gross Engine hp 92 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207cu in (3.4 L) Displacement

Workmaster 120 120 Gross Engine hp 100 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207cu in (3.4 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:

(CEGR + SCR + CUC)

Electronic Injection Bosch

High-pressure Common Rail System

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Powercore Dry Air Cleaner

Under Hood Muffler

Horizontal Rearward Exhaust

24 gal Fuel Tank

2.9 gal DEF Tank

2 function mid mount valve & joystick

TRANSMISSION:

LH side steering column mounted Power Shuttle

Creeper ready

- 12 Forward and 12 Reverse Speeds
- (4) Synchronized Gears
- (3) Non-synchronized Ranges
- (2) clutches, 5 wet disc plates FWD 19 mph (30 KPH) speed may vary Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering
Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip

Electro-Hydraulic engagement standard Tread Width: 66.5 in. to 72.9 in.

REAR AXLE

Flange Type

Tread Width: 63.8 in. to 79.5 in.

HYDRAULIC SYSTEM:

Open Center System

Dual Gear Pumps

Implement Pump: 16.9 gpm (64 L)
Steering Pump: 9.7 gpm (37 L)

Total Flow: 26.6 gpm (101 L)

(3) Open Center Remote Valves with Detent & Kickout on #2

Float on #1 & #3

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent Flip-up PTO Shaft Guard 540 RPM hydraulic wet clutch Electronic engagement 1-3/8 in. 6 splines

WORKMASTER 95-120 ROPS MOWING FAST PICK US PRICE LIST

Standard Equipment

3-POINT LIFT SYSTEM:
Right hand console mounted
lever control
Mechanical Draft Control
3,200 Pounds Lift Capacity
Category I/II Combi Ball Ends
Telescopic Stabilizers
Flexible Lower Link Ends

ELECTRICAL:

(1) 800 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
 and signals
30 amp power plug
12V power socket (cigarette lighter)

INSTRUMENTATION:

Digital /Analog Instrumentation with warning lights for turn signals, high beam, work lights, side lights, rear PTO, 4WD, differential lock, low fuel, alternator, oil pressure, brake fluid, grid heater & hand brake Gauges for fuel level, engine temperature and tachometer
Digital Readout for PTO speed, ground speed, battery, hours & DEF level percentage

LIGHTING:

Front: (2) Halogen Headlights
Rear: (1) Right hand fender
mounted worklights
Turn Signals/Flashers/Rear Lights

OPERATOR PROTECTIVE STRUCTURE:

ROPS MODELS

2-Post Foldable ROPS with ISOmounted flat deck platform

Steering Wheel - adjustable tilt

Seat - Low profile air suspension seat,
operator's presence sensor, and
retractable seat belts

Suspended pedals

Locking brake pedals

TIRES:

12.4x24 R1 Front 18.4X30 R1 Rear

MISCELLANEOUS:

Pivoting Engine Hood SMV Emblem

Toolbox WARRANTY:

New Holland Standard Warranty Applies

WORKMASTER 95-120 ROPS MOWING FAST PICK US PRICE LIST

Models

COMMERCIAL MODEL	VERSION	TRACTION	Weight	Factory Data	List Price
WORKMASTER 95 TIER4	Rops	MFD	7,451 LB	9046694P70	\$59,865.00
WORKMASTER 105 TIER4	Rops	MFD	7,451 LB	9048956P70	\$62,765.00
WORKMASTER 120 TIER4	Rops	MFD	7,936 LB	9051764P70	\$66,365.00

Factory Supplied Options

Order Code Description	Weight	Factory Data	List Price
------------------------	--------	--------------	------------

PACKAGE SELECTION

SD_T9980 PACKAGING

	F9918X	ROPS Mowing Fast Pick	(908486P40)	(\$10,880.00)
		ROPS Mowing Fast Pick		
		3 rear remotes		
		NO mid mount valve or loader		
		Allows for choice of the following:		
		Tires:		
		18.4-30 R1 rear with 12.4-24 R1 front OR		
		16.4-34 R1 rear with 13.6-24 R1 front		
		PTO:		
		540 OR 540/1000 RPM		
		Rear weights:		
		4, 8 OR NO rear wheel weights		
		Front weights:		
		8, 10 OR NO front weights		
		Mid mount valve / loader:		
		NO mid mount valve or loader OR		
		Mid mount valve with NO brackets & NO Loader OR		
		Complete loader ready (mid mount valve, hoses and brackets)		

WORKMASTER 95-120 ROPS MOWING FAST PICK US PRICE LIST

TIRES			
FRONT			
SD_T4940 FR	ONT WHEELS AND TIRES		
4WD Front	Fires - Ag		
8230506	FRONT 12.4 - 24		No Charge
	Requires 18.4-30 rear tires		
8230505	13.6 -24	9000171P60	\$220.00
	Requires 16.9-34 rear tires		
REAR			
SD_T4950 RE	EAR WHEELS AND TIRES		
Rear tires -	Ag		
8930605	REAR 18.4 - 30		No Charge
	Requires 12.4-24 4WD front or 10.0-16 2WD front		
8930601	REAR 16.9 - 34	(900109P20)	(\$140.00)
	Requires 13.6-24 4WD front or 10.0-16 2WD front		
LOADER			
LOADER			
SD_T8110 LC	PADER BRACKETS		
345324	L/ LOADER FOR MMV	9001154P40	\$1,480.00
	Mid Mount Valve and Joystick ONLY.		
343422	LOADER READY 343422	9005070P00	\$6,500.00
	Complete loader ready includes:		
	- Horizontal and Vertical TPS loader brackets		
	- 2 function mid mount valve and joystick		
	- Hoses from mid mount valve to vertical bracket		
	- Grill guard		
		· · · · · · · · · · · · · · · · · · ·	
PTO			
-		-	
REAR PTO			
-			

S	D_	_T8010	PT	0

_	 <u></u>				
	759271	540 RPM W CAP			No Charge
	759272	540-540E RPM W CAP		9000354P90	\$455.00
	759273	540-1000 RPM W CAP		9000413P40	\$530.00

32

WORKMASTER 95-120 ROPS MOWING FAST PICK US PRICE LIST

WEIGHTS FRONT WEIGHTS SD_T2151 WEIGHT PACK 110KgFCW/10X40-510kg 342070 9000975P00 \$1,250.00 Front carrier (154 lbs) + 10 weights (88lbs each) = 1,034 lbs 342069 110KgFC W/8X40-430kg 9000780P00 \$1,000.00 Front carrier (154 lbs) + 8 weights (88lbs each) = 858 lbs **REAR WHEEL WEIGHTS** SD_T4960 WHEEL WEIGHTS 762028 2X55or32Kg EACH SIDE 9000491P40 \$630.00 2 (110 lb) rear weights per side = 220 lbs total for all rear tires sizes except 500/60-22.5 2 (70 lb) rear weights per side = 140 lbs total for 500/60-22.5 rear tires 759650 9000982P80 \$1,260.00 4X55or32Kg EACH SIDE 4 (110 lb) rear weights per side = 440 lbs total for all rear tires sizes except 500/60-22.5 4 (70 lb) rear weights per side = 280 lbs total for 500/60-22.5

OPERATOR'S MANUALS

SD_T9805 OPERATOR MANUAL (SE

rear tires

	342076	French (Canada)		No Charge
	342077	Spanish		No Charge



WORKMASTER 95-120 A LA CARTE ROPS US PRICE LIST

Standard Equipment

KEY SELLING POINTS:

- Semi straddle ROPS
- Air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

Workmaster 95 97 Gross Engine hp 78 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207cu in (3.4 L) Displacement

Workmaster 105 112 Gross Engine hp 92 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207cu in (3.4 L) Displacement

Workmaster 120 120 Gross Engine hp 100 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207cu in (3.4 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:

(CEGR + SCR + CUC)

Electronic Injection Bosch

High-pressure Common Rail System

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Powercore Dry Air Cleaner

Under Hood Muffler

Horizontal Rearward Exhaust

24 gal Fuel Tank

2.9 gal DEF Tank

2 function mid mount valve & joystick

TRANSMISSION:

LH side steering column mounted Power Shuttle

Creeper ready

- 12 Forward and 12 Reverse Speeds
- (4) Synchronized Gears
- (3) Non-synchronized Ranges
- (2) clutches, 5 wet disc plates FWD 19 mph (30 KPH) speed may vary Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering
Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip

Electro-Hydraulic engagement standard Tread Width: 63.8 in. to 72.9 in.

REAR AXLE

Flange Type

Tread Width: 63.9 in. to 79.7 in.

HYDRAULIC SYSTEM:

Open Center System

Dual Gear Pumps

Implement Pump: 16.9 gpm (64 L)
Steering Pump: 9.7 gpm (37 L)

Total Flow: 26.6 gpm (101 L)

(2) Open Center Remote Valves with

Detent & Kickout on #2

Float on #1

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent
Flip-up PTO Shaft Guard
540 RPM hydraulic wet clutch
Electronic engagement
1-3/8 in. 6 splines

WORKMASTER 95-120 A LA CARTE ROPS US PRICE LIST

Standard Equipment

3-POINT LIFT SYSTEM:
Right hand console mounted
lever control
Mechanical Draft Control
3,200 Pounds Lift Capacity
Category I/II Combi Ball Ends
Telescopic Stabilizers
Flexible Lower Link Ends

ELECTRICAL:

(1) 800 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
 and signals
30 amp power plug
12V power socket (cigarette lighter)

INSTRUMENTATION:

Digital /Analog Instrumentation with warning lights for turn signals, high beam, work lights, side lights, rear PTO, 4WD, differential lock, low fuel, alternator, oil pressure, brake fluid, grid heater & hand brake Gauges for fuel level, engine temperature and tachometer
Digital Readout for PTO speed, ground speed, battery, hours & DEF level percentage

TIRES:

12.4x24 R1 Front 18.4X30 R1 Rear

MISCELLANEOUS:

Pivoting Engine Hood SMV Emblem Toolbox LIGHTING:

Front: (2) Halogen Headlights
Rear: (1) Right hand fender
mounted worklights
Turn Signals/Flashers/Rear Lights

OPERATOR PROTECTIVE STRUCTURE:

ROPS MODELS
2-Post Foldable ROPS with ISOmounted flat deck platform
Steering Wheel - adjustable tilt
Seat - Low profile air suspension seat,
operator's presence sensor, and
retractable seat belts
Suspended pedals

WARRANTY:

Locking brake pedals

New Holland Standard Warranty Applies

LOADER:

632TL NON SELF-LEVELING

Maximum Lift Height @
pivot pin: 134.5"

Dump Clearance @ 45 deg: 98.4"

Digging Depth: 5.1"

Lift Capacity @ 800mm: 2,028 LBS

Breakout Force @ 800mm: 3,102 LBS

Reach @ Max Lift Height @ 45

deg: 37.8"

Reach @ Ground Level: 87.4"

Bucket Rollback Angle: 40 degrees

Bucket Dump Angle: 53 degrees

Skid Steer bucket attach

84" bucket

WORKMASTER 95-120 A LA CARTE ROPS US PRICE LIST

Models

COMMERCIAL MODEL	VERSION	TRACTION	Weight	Factory Data	List Price
WORKMASTER 95 TIER4	Rops	MFD	7,451 LB	9046694P70	\$59,865.00
WORKMASTER 105 TIER4	Rops	MFD	7,451 LB	9048956P70	\$62,765.00
WORKMASTER 120 TIER4	Rops	MFD	7,936 LB	9051764P70	\$66,365.00

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price

TIRES

FRONT

SD T4940 FRONT WHEELS AND TIRES

_	OB_THOSE TROPING WHEELS AND TIKES					
4WD Front	Tires - Ag					
8220701	11.2 - 24	(900046P80)	(\$60.00)			
	Requires 16.9-30 rear tires					
8230506	FRONT 12.4 - 24		No Charge			
	Requires 18.4-30 rear tires					
8230505	13.6 -24	9000171P60	\$220.00			
	Requires 16.9-34 rear tires					
8811501	11.5/80-15.3	9000546P00	\$700.00			
	Requires 500/60-22.5 rear tires					
	(ROPS ONLY)					
4WD Front	4WD Front Tires - Ind					
8230503	FRONT 12.5 - 18	9000546P00	\$700.00			
	Requires 19.5L-24 rear tires					

REAR

SD_T4950 REAR WHEELS AND TIRES

Rear tires - Ag						
	8930602	REAR 16.9 - 30		9000234P00	\$300.00	
		Requires 11.2-24 4WD front or 7.50-16 2WD front				
	8930605	REAR 18.4 - 30			No Charge	
		Requires 12.4-24 4WD front or 10.0-16 2WD front				

WORKMASTER 95-120 A LA CARTE ROPS US PRICE LIST

	8930601	REAR 16.9 - 34	(900109P20)	(\$140.00)
		Requires 13.6-24 4WD front or 10.0-16 2WD front		
	8310501	500/60-22.5	9000487P50	\$625.00
		Requires 11.5/80-15.3 4WD front tires		
		(ROPS ONLY)		
	Rear tires - In	nd		
	8930603	REAR 19.5 - 24	9000487P50	\$625.00
		Requires 12.5/80-18 4WD front tires		

HYDRAULICS

REAR REMOTES

SD_T8270 REAR REMOTES

	762052	2 REMOTE 762052		No Charge
		2 rear remotes for Open Platform with foldable ROPS		
		Float on remote 1		
		Extend and retract detent and kick-out on remote 2		
	762053	3 REMOTE 762053	9000624P00	\$800.00
		3 rear remotes for Open Platform with foldable ROPS		
		Float on remote 1 & 3		
		Extend and retract detent and kick-out on remote 2		

LOADER

LOADER

SD_T8110 LOADER BRACKETS

	345324	L/ LOADER FOR MMV	(905070P00)	(\$6,500.00)
		Mid Mount Valve and Joystick ONLY.		
	343422	LOADER READY 343422	(901154P40)	(\$1,480.00)
		Complete loader ready includes:		
		- Horizontal and Vertical TPS loader brackets		
		- 2 function mid mount valve and joystick		
		- Hoses from mid mount valve to vertical bracket		
		- Grill guard		
	762057	TL632 FULL NS762057		No Charge
		632TL Non self leveling loader with 84" SSL Bucket		

PTO

REAR PTO

SD_T8010 PTO

	759271	540 RPM W CAP		No Charge
	759272	540-540E RPM W CAP	9000354P90	\$455.00
	759273	540-1000 RPM W CAP	9000413P40	\$530.00

WORKMASTER 95-120 A LA CARTE ROPS US PRICE LIST

WEIGHTS				
FRONT WEIGHTS	;			
SD T2151 W	FIGHT PACK			
342070	110KgFCW/10X40-510kg		9000975P00	\$1,250.00
	Front carrier (154 lbs) + 10 weights (88lbs each) = 1,034 lbs			Ų., <u>2</u> 00.00
342069	110KgFC W/8X40-430kg		9000780P00	\$1,000.00
	Front carrier (154 lbs) + 8 weights (88lbs each) = 858 lbs			. ,
		•	•	
REAR WHEEL WE	EIGHTS			
SD_T4960 W	HEEL WEIGHTS			
762028	2X55or32Kg EACH SIDE		9000491P40	\$630.00
	2 (110 lb) rear weights per side = 220 lbs total for all rear tires			
	sizes except 500/60-22.5			
	2 (70 lb) rear weights per side = 140 lbs total for 500/60-22.5 rear tires			
759650	4X55or32Kg EACH SIDE		9000982P80	\$1,260.00
	4 (110 lb) rear weights per side = 440 lbs total for all rear tires			
	sizes except 500/60-22.5			
	4 (70 lb) rear weights per side = 280 lbs total for 500/60-22.5			

OPERATOR'S MANUALS

SD_T9805 OPERATOR MANUAL (SE

rear tires

	342076	French (Canada)		No Charge
	342077	Spanish		No Charge

WORKMASTER 95, 105 & 120 Tire Chart							
Tine Tyme	Application	Rear	Tires	Matching 4W	D Front Tires		
Tire Type	Application	Tire	Order Code	Tire	Order Code		
		16.9-30	8930602	11.2-24	8220701		
Bias	Agricultural - R1	18.4-30	8930605	12.4-24	8230506		
		16.9-34	8930601	13.6-24	8230505		
Specialty	Agricultural - R1	500/60-22.5	8310501	11.5/80-15.3	8811501		
Specialty	Industrial - R4	19.5L24	8930603	12.5/80-18	8290904		

39