CONSTRUCTION EQUIPMENT

U.S. PRICE LIST

C091

COMPACT EXCAVATORS

PL-200 MX SAP REVISION 11

EFFECTIVE JULY 9, 2021

THIS IS AN ELECTRONIC COPY ONLY - HARD COPIES WILL NOT BE DISTRIBUTED.

This price list is intended for dealers with the Compact Excavators (MX) contract only.

The prices included in this revision supersede any prices established prior to the effective date shown unless specifically identified in a price bulletin as superseding this price list.

Below is a list of Family(s) and Model(s) that are included in this price list.

Crawler Excavator (Mini)

CX17C CANOPY T4 FINAL – MX7B

CX26C CANOPY/CAB T4 FINAL – MX8B

CX30C CANOPY/CAB T4 FINAL – MX8B

CX37C CANOPY/CAB T4 FINAL – MX8B

CX57C CAB T4 FINAL – MX5B

CX60C CAB T4 FINAL – MX5B

PLEASE NOTE: Retain the price book pages of the discontinued series for your records.

Copyright 2021 By

CNH Industrial America LLC

Bid Term: 2/22/19 - 2/21/21; Extended to 2/21/22: EXtended to 2/21/23

(This page intentionally left blank)



COMPACT EXCAVATORS TABLE OF CONTENTS

COMPACT EXCAVATORS GENERAL ANNOUNCEMENTS GENERAL INFORMATION..... CX17C CANOPY T4 FINAL COMPACT EXCAVATOR Standard Features Price List Factory Supplied Attachments..... 12 Service parts..... 13 CX26C T4 FINAL COMPACT EXCAVATOR Standard Features 15 Price List 17 Factory Supplied Attachments..... 21 Service parts..... 22 CX30C T4 FINAL COMPACT EXCAVATOR Standard Features 23 Price List 25 Factory Supplied Attachments..... 28 Service parts..... 29 CX37C T4 FINAL COMPACT EXCAVATOR Standard Features 31 33 Price List Factory Supplied Attachments..... 38 Service parts..... 39 CX57C CAB T4 FINAL COMPACT EXCAVATOR Standard Features 41 Price List 43 Factory Supplied Attachments..... 47 Service parts..... 48 CX60C CAB T4 FINAL COMPACT EXCAVATOR 49 Standard Features Price List Factory Supplied Attachments..... 56

Service parts....

57



General Announcements

Pre-Configured Packages are full model packages for Short Arm or Long Arm configurations. Once a package is selected, you can then select the required Buckets/Attachments to go along with your unit. Keep in mind, it is not possible to modify (add/remove) any other vehicle options when you select a Pre-Configured package. If a Pre-Configured unit is ordered, it will help reduce lead-time. Independent option ordering is still available if the package is not desired, however you may experience a longer lead-time.

The new C Series CASE Mini-Excavator's have a different dipper ear geometry, and therefore are not directly compatible with the previous B Series buckets. However, there are new couplers that have been developed for the C Series models to provide the ability to utilize both the B and C Series buckets. See reference table for each model:

	C-Series Mini Excavator BUCKET COMPATIBILITY						
Model	Order Code	Description	B-Series Buckets	C-Series Buckets			
CX17C	48057609	Coupler, Mechanical Pin-Grabber	No	Yes			
	48057615	Coupler, Mechanical Pin-Grabber	No	Yes			
CX26C/CX30C	48094307	Coupler, Hydraulic Pin-Grabber	Yes (requires removal of spacer plates)	Yes			
CX37C	48057623	Coupler, Mechanical Pin-Grabber	Yes	Yes			
CX3/C	48058013	Coupler, Hydraulic Pin-Grabber	Yes	Yes			
	48057630	Coupler, Mechanical Pin-Grabber	No	Yes			
CX57C/CX60C	48058014	Coupler, Hydraulic Pin-Grabber	No	Yes			
	48082917	Coupler, B/C Series Universal Mechanical	Yes	Yes			

General Information

Prices shown herein are suggested prices only and in no way are they to be construed as limiting or restricting the dealer in his determination of the ultimate retail selling price. It is understood that the dealers are free to determine their selling price. Subject to any Federal, State or local laws.

Where shown herein liquid capacities are U.S. measure unless otherwise noted.

ADVANCE FREIGHT

Advance freight will be added to the machinery invoice as a separate net charge for machinery shipped from field locations or from other than specified Ex Works locations.

PRICES

Prices are Ex Works factory, where the goods are manufactured, except where noted. For detailed information concerning prices, please refer to your OPERATING GUIDE.

Prices and specifications are subject to change without notice.

CONTENTS OF ORGANIZATION

Case Construction Equipment Inc issues price lists and revisions covering each Case contract. U.S. Price List is published in U.S. funds. Canadian Price List is published in Canadian funds. Assure that you are using the correct price list. The Canadian price lists are denoted by a Maple Leaf on the price list cover page and the symbol "(CDN)" is printed at the head of the Factory Supplied Attachments List columns.

Freight, duty and sales taxes are NOT included in any wholegoods or attachment prices shown in the price list. Any appropriate freight, duty, Federal, State, and Provincial taxes will be added to the machinery invoice as separate net charges.

PROCEDURE

The price pages for each machine (or group of machines) lists both "Factory" and "Factory Supplied Attachments".

Each price list is comprised of the various machines sold under that contract. Each price book section has "Factory", "Factory Supplied Attachments", or "Third Party Supplied Attachments" pages. When ordering and pricing a machine follow the ordering instructions listed for that machine. Attachments listed following the "Factory Supplied Attachments" or "Third Party Supplied Attachments" heading are available for installation in the field.

ATTACHMENTS

Expect Attachments to be shipped within 2 -3 weeks from order entry.



General Information

DISTRIBUTION OF PRICE LISTS / REQUESTS FOR ADDITIONAL COPIES

Price lists will be provided electronically via that Dealer Portal.

Contact information for additional copies of Case Construction Equipment Price Lists

Additional price lists, divider tabs and binders may be ordered at the Document Management Center. From Dealer Portal click on Tools then Document Management Center link. Any questions you can call the Document Management Center at 262-636-7540

You will only receive price lists for contracts covered by your current Dealer Agreement with the Company.

The revisions are dated and are effective as of that date. However, PRICES ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Bid Term: 2/22/19 - 2/21/21; Extended to 2/21/22: EXtended to 2/21/23

Front working light



CX17C CANOPY US PRICE LIST

(Ex Works Port of Entry) Standard Equipment

```
ENGINE:
                                                      Pre-wired telematics ready
 Kubota D902 3 Cyl. water-
                                                    BLADE:
   cooled, mechanical injection diesel
                                                      Hydraulically controlled dozer blade
  54.8 CID (0.898L)
                                                        with adjustable width
 Tier 4 Final
 Glow plugs
                                                    UNDERCARRIAGE:
 Horsepower:
                                                      Variable undercarriage (3'3" to 4'3")
   Gross 16.8 HP (12.5 kW)/2300
                                                      Track pad width: 9" (230 mm)
   Net 15.8 HP (11.8 kW)/2300
                                                      Track length: 5'3" (1590 mm)
 Maximum Engine Torque:
                                                      Gradeability: 30 degrees
      39.49 lb ft (53.54 Nm)@1900 rpm
                                                      Ground Clearance: 6.7" (170 mm)
 Dry type air cleaner
                                                    TRACK DRIVE:
OPERATOR PROTECTIVE STRUCTURE:
                                                      Two speed auto shift travel
TOPS/FOPS:
                                                      Fully hydrostatic drive system
  Two post canopy design
                                                      Track tension adjustment
  Sound Levels:
                                                        (grease type)
      ISO 6396:2008 sound pressure
                                                      Sealed and lubricated track
     level LpA=76bB (A)
                                                    HYDRAULICS:
  Mechanical Suspension seat, with
                                                      Control pattern selector valve
     2" seat belt
                                                      Hydraulic oil filter
  Pilot operated joysticks for boom,
                                                      Total Auxiliary Flow:
     arm, bucket and swing with
                                                        7.2 gpm @ 2,466 psi
     adjustable wrist rests
                                                        (27.4 L/min @ 170 bar)
  Foot pedal for swing tower
                                                      Auxiliary valve and piping with shut
     control
                                                        off block at end of arm
                                                      Proportional auxiliary hydraulic flow
 Gauges:
  Engine coolant temperature and fuel
                                                        control
     level
                                                      Selector valve for single or
 Indicator Lights:
                                                        two-way aux flow
   Engine oil pressure, coolant
                                                      Large capacity hydraulic oil cooler
    temperature, battery
                                                      Cylinder rod protection covers
    charge, low fuel warning, engine
                                                        -Bucket, Arm, Boom and Dozer
   preheat, air cleaner warning,
                                                    UPPER:
                                                      Standard Arm: 3'2" (0.96 m)
   hyd. quick coupler
                                                      Optional Long Arm: 3'8" (1.12 m)
   lock, and high travel speed
                                                      Boom: 5'11" (1.8 m)
ELECTRICAL:
  12 Volt electrical starting system
                                                      Boom Swing: 70° left / 54° right
     includes heavy-duty battery and
                                                      Zero Tail Swing
     starting motor
                                                      Swing brake: disc type, spring applied
  40 Amp Alternator
                                                        and hydraulically released
                                                    MISCELLANEOUS:
 Battery Master Switch
 Key Start
                                                      Operating weight:
 Anti-Theft-Engine starting passwords
                                                        Canopy, short arm - 3,910 lb
 Dual 12V power plug recepticals
                                                          (1700kg)
```



(Ex Works Port of Entry) Standard Equipment

Canopy, long arm with additional
 counterweight - 4,110 lbs.
 (1790 kg)

All weights are with rubber tracks, no quick coupler, bucket, fluids, full of

fuel, and 165lb operator
Additional Counterweight - 180 lbs
Warranty - Base warranty Coverage:
 2-Year/3,000-Hour Full Machine
 Limited Warranty



(Ex Works Port of Entry) Models

COMMERCIAL MODEL	TECHNICAL TYPE	Weight	Factory Data	List Price
CX17C CANOPY	698491712-CX17C	7.672 LB	·	\$39.633.00

Packet		Description	Weight	Factory Data	List Price
CASE Long Arm [1-7]					\$639.00
SD_30180-TRAVEL ALARM		Travel Alarm			
SD_40003-COUNTERWEIGHT		Additional Counterweight.			
SD_X5406-1ST AUX HYD TWO WAYS		2Way Aux Joystick Proportional			
SD_X6100-ARM		Long Arm - 747329			
CASE Short Ar [3-8]					\$166.00
SD_30180-TRAVEL ALARM		Travel Alarm			
SD_40003-COUNTERWEIGHT		Standard Counterweight.			
SD_X5406-1ST AUX HYD TWO WAYS		2Way Aux Joystick Proportional			
SD_X6100-ARM		Short Arm - 747320			
	-				

Pre-Configured Packages are full model packages for Short Arm or Long Arm configurations. Once a package is selected, you can then select the required Buckets/Attachments to go along with your unit. Keep in mind, it is not possible to modify (add/remove) any other vehicle options when you select a Pre-Configured package. If a Pre-Configured unit is ordered, it will be matched to one that is already built and ready to ship, which will reduce the lead-time by several months. Independent Option ordering is still available if the package is not desired, however you may experience a longer lead-time.



(Ex Works Port of Entry) Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
	•			
OPERATOR'S MA	ANUAL			
SD_47181 OF	PERATOR'S MANUAL			
747480	Operators Manual - English			No Charge
747961	Operators Manual - French			No Charge
747464	Operators Manual- Spanish			No Charge
VERSION				
00 40404 05	AAW! ED TVDE			
SD_10181 CF				No Chausa
9552700	Rubber Tracks			No Charge
	One-piece molded rubber belt track w/ a steel cable core.			
	The entire track must be replaced at time of service. Select			
	this track for general use on soils & hard surfaces.			
455ITIONIAL 501				
ADDITIONAL EQI	JIPMENT MEX			
SD_30180 TR				
747994	W/O Travel Alarm		+	No Charge
747453	Travel Alarm			\$166.00
00 40000 00	NUNTERWEIGHT			
	DUNTERWEIGHT			No Channa
747995 747996	Standard Counterweight. Additional Counterweight.			No Charge \$146.00
147990	<u>-</u>			φ140.00
	Additional Bolt-on weight adds 180 lb (82 kg)			
SD_X5406 1S	ST AUX HYD TWO WAYS			
747054	2Way Aux Pedal Proportional			No Charge
747055	2Way Aux Tedar Troportional			No Charge
1 1 171000	- Erray Max objetion i Toportional	l	1	NO Onarge
SD X5413 AL	JX WORKING LIGHTS			
747243	STD Halogen Working			No Charge
747242	LED Working Lights			\$100.00
	1 3 3			Ţ.23 .00
SD_X6100 AF	RM			
747320	Short Arm - 747320			No Charge
	Please refer to the Standard pages for arm lengths			90
	page ier en in englie			

(Ex Works Port of Entry)

	747329	Long Arm - 747329		\$327.00
		Long arm increases dig depth, resulting in a reduction in		
		arm digging forces & lift capacity. Please refer to the		
L		Standard Pages for arm lengths.		

	BEACON

Г	747087	W/O - Beacon		No Charge
	747088	LED Beacon		\$280.00



(Ex Works Port of Entry) Factory Supplied Attachments

Order Code	Description	Weight	Factory Data	List Price
KLAC Buckets & 0	Coupler			
47422586	10" HD Bucket (KLAC Coupler)	88 LB		\$507.00
47422587	12" HD Bucket (KLAC Coupler)	95 LB		\$534.00
47422588	16" HD Bucket (KLAC Coupler)	106 LB		\$587.00
47422589	18" HD Bucket (KLAC Coupler)	117 LB		\$655.00
47422602	KLAC Base Plate (To adapt other buckets)	11 LB		\$237.00
48057632	Coupler (Compatible with both the B/C-Series KLAC buckets)	13 LB		\$848.00
Pin-On/Mech. Buc	ketş & Coupler			
48057605	10"HD Bucket (Pin-on/Mechanical Coupler)	79 LB		\$357.00
48057606	12"HD Bucket (Pin-on/Mechanical Coupler)	86 LB		\$384.00
48057607	16"HD Bucket (Pin-on/Mechanical Coupler)	97 LB		\$437.00
48057608	18"HD Bucket (Pin-on/Mechanical Coupler)	106 LB		\$505.00
48057609	Coupler (Only compatible with C-Series buckets) Includes 1 set of dead pins for installation into a single bucket	29 LB		\$1,535.00
48057610	Dead Pin Kit (for additional buckets) Required when ordering more than 1 bucket with a Pin-Grabber Coupler	5 LB		\$159.00

C-Series Mini Excavator BUCKET COMPATIBILITY					
Model	Order Code	Description	B-Series Buckets	C-Series Buckets	
CX17C	48057609	Coupler, Mechanical Pin-Grabber	No	Yes	
	48057615	Coupler, Mechanical Pin-Grabber	No	Yes	
CX26C/CX30C	48094307	Coupler, Hydraulic Pin-Grabber	Yes (requires removal of spacer plates)	Yes	
CX37C	48057623	Coupler, Mechanical Pin-Grabber	Yes	Yes	
CX3/C	48058013	Coupler, Hydraulic Pin-Grabber	Yes	Yes	
CX57C/CX60C	48057630	Coupler, Mechanical Pin-Grabber	No	Yes	
	48058014	Coupler, Hydraulic Pin-Grabber	No	Yes	
	48082917	Coupler, B/C Series Universal Mechanical	Yes	Yes	

CX17C Compact Excavator

P/N	Kit Name	Notes
90444176	Telematics Ready 4G	
48100304	Seat Belt 3 INCH	
48120194	Counterweight, CW04, DIA	

This table of field installed accessories is only intended to provide guidance on where field installed accessories are ordered. Dealers should reference the online PARTS catalog for each model for an up-to-date list of components, field kits and accessories. These kits are subject to change without notice. For pricing, availability and technical questions contact CNHi Parts.

Bid Term: 2/22/19 - 2/21/21; Extended to 2/21/22: EXtended to 2/21/23

(This page intentionally left blank)



(Ex Works Port of Entry) Standard Equipment

```
ENGINE:
                                                    ELECTRICAL:
 Kubota D1305 3 Cyl. water-
                                                      12 Volt electrical starting system
    cooled, mechanical injection diesel
                                                         includes heavy-duty battery and
 77.0 CID (1.261L)
                                                         starting motor
 Tier 4 Final
                                                      40 Amp Alternator
 Glow plugs
                                                      Battery Master Switch
 Horsepower:
                                                      Key Start
   Gross 24.8 HP (18.5 kW)/2300
                                                      Anti-Theft-Engine starting passwords
   Net 23.2 HP (17.3 kW)/2300
                                                      Dual 12V power plug recepticals
 Maximum Engine Torque:
                                                      Front working lights on cab & boom
     60.0 lb ft (81.4 Nm) @ 1600 rpm
                                                      Pre-wired telematics ready
 Dry type air cleaner dual element
                                                    BLADE:
OPERATOR PROTECTIVE STRUCTURE:
                                                      Hydraulically controlled dozer blade
Sound Levels:
                                                    UNDERCARRIAGE:
     ISO 6396:2008 sound pressure
                                                      Rubber tracks
                                                      Track pad width: 9.8" (250 mm)
      level LpA=77bB (A)
ROPS/FOPS:
                                                      Track length: 6'3" (1910 mm)
  Four post canopy design
                                                      Gradeability: 30 degrees
                                                      Ground Clearance: 11" (290 mm)
                                                    TRACK DRIVE:
  Enclosed Cab with overhead opening
    front window, sliding side window,
                                                      Two speed Auto shift travel
   lockable door, heater and defroster,
                                                      Fully hydrostatic drive system
   radio/USB player + 2 speakers
                                                      Track tension adjustment
  Mechanical suspension seat, with
                                                        (grease type)
     2" seat belt
                                                      Sealed and lubricated track
  Pilot operated joysticks for boom, arm
                                                    HYDRAULICS:
    bucket, and swing with adjustable
                                                      Control pattern selector valve
                                                      Hydraulic oil filter
     wrist rests
  Foot pedals for travel control and
                                                      Total Auxiliary Flow:
     swing tower control
                                                        12.5 gpm @ 2,538 psi
 Gauges:
                                                        (47.2 L/min @ 175 bar)
                                                      Main Pump: 3,130 PSI
  Engine coolant temperature and fuel
     level
                                                      Auxiliary valve and piping with shut
                                                       off block at end of arm
 Indicator Lights:
   Engine oil pressure, coolant
                                                      Proportional auxiliary hydraulic flow
    temperature, battery
                                                        control
    charge, low fuel warning, engine
                                                      Selector valve for single or
    preheat, air cleaner warning,
                                                        two-way aux flow
   hyd. quick coupler
                                                      Large capacity hydraulic oil cooler
    lock, and high travel speed
                                                      Cylinder rod protection covers
                                                        -Dozer & Boom
                                                    UPPER:
                                                      Standard Arm: 3'8" (1.12 m)
                                                      Optional Long Arm: 4'5" (1.35 m)
                                                      Boom: 6'5" (1.95 m)
```



(Ex Works Port of Entry) Standard Equipment

Boom Swing: 75° left / 50° right

Zero Tail Swing

Swing brake: disc type, spring applied

and hydraulically released
Bucket linkage with lifting hook

MISCELLANEOUS:

Operating weight:

Canopy short arm - 5,520 lbs.

(2505 kg)

Canopy, long arm, additional counterweight- 5,830 lbs.

(2645 kg)

Cab, short arm - 5,850 lbs. (2655 kg)

Cab, long arm, additional

counterweight - 6,160 lbs. (2795 kg)

All weights are with rubber tracks, no quick coupler, bucket, fluids, full of

fuel, and 165lb operator

Additional Counterweight - 286 lbs

Warranty - Base warranty Coverage:

2-Year/3,000-Hour Full Machine



(Ex Works Port of Entry) Models

COMMERCIAL MODEL	Weight	Factory Data	List Price
CX26C	8,300 LB		\$47,234.00

Packet	Description	Weight	Factory Data	List Price
CX26C CAB Lg Arm II				\$1020.00
SD_05136-RADIO OPTION	Radio and USB			
SD_30180-TRAVEL ALARM	Travel Alarm			
SD_40003-COUNTERWEIGHT	Additional Counterweight.			
SD_X5183-AIR COND/HEATER	Heater Only			
SD_X5405-2ND AUX. CIRCUIT	W/O 2nd Aux 2-Way Proportional			
SD_X5406-1ST AUX HYD TWO WAYS	2Way Aux Joystick Proportional			
SD_X6100-ARM	Arm Long w/Thumb Bracket			
SD_X6206-LINKAGE	Linkage With Hook			
SD_X6207-HYDR Q/C PROV.	W/O Q/C Provision			
SD_X6210-BEACON	LED Beacon			
		_		
CX26C CAB Sh Arm II				\$487.00
SD_05136-RADIO OPTION	Radio and USB			
SD_30180-TRAVEL ALARM	Travel Alarm			
SD_40003-COUNTERWEIGHT	Standard Counterweight.			
SD_X5183-AIR COND/HEATER	Heater Only			
SD_X5405-2ND AUX. CIRCUIT	W/O 2nd Aux 2-Way Proportional			
SD_X6100-ARM	Arm Short w/Thumb Bracket			
SD_X6206-LINKAGE	Linkage With Hook			
SD_X6207-HYDR Q/C PROV.	W/O Q/C Provision			
SD_X6210-BEACON	LED Beacon			
CX26C ROPS Lg Arm II				\$1020.00
SD_30180-TRAVEL ALARM	Travel Alarm			
SD_40003-COUNTERWEIGHT	Additional Counterweight.			
SD_X5405-2ND AUX. CIRCUIT	W/O 2nd Aux 2-Way Proportional			
SD_X5406-1ST AUX HYD TWO WAYS	2Way Aux Joystick Proportional			
SD_X6100-ARM	Arm Long w/Thumb Bracket			
SD_X6206-LINKAGE	Linkage With Hook			
SD_X6207-HYDR Q/C PROV.	W/O Q/C Provision			
SD_X6210-BEACON	LED Beacon			
		1	 	.
CX26C ROPS Sh Arm II	 			\$487.00
SD_30180-TRAVEL ALARM	Travel Alarm			
SD_40003-COUNTERWEIGHT	Standard Counterweight.			
SD_X5405-2ND AUX. CIRCUIT	W/O 2nd Aux 2-Way Proportional			
SD_X5406-1ST AUX HYD TWO WAYS	2Way Aux Joystick Proportional			



(Ex Works Port of Entry)

Packet	Description	Weight	Factory Data	List Price
SD_X6100-ARM	Arm Short w/Thumb Bracket			
SD_X6206-LINKAGE	Linkage With Hook			
SD_X6207-HYDR Q/C PROV.	W/O Q/C Provision			
SD_X6210-BEACON	LED Beacon			

Pre-Configured Packages are full model packages for Short Arm or Long Arm configurations. Once a package is selected, you can then select the required Buckets/Attachments to go along with your unit. Keep in mind, it is not possible to modify (add/remove) any other vehicle options when you select a Pre-Configured package. If a Pre-Configured unit is ordered, it will be matched to one that is already built and ready to ship, which will reduce the lead-time by several months. Independent Option ordering is still available if the package is not desired, however you may experience a longer lead-time.

747999 W/O 2nd Aux 2-Way Proportional



CX26C US PRICE LIST

(Ex Works Port of Entry) Factory Supplied Options

- accery cappaigned operation				
Order Code	Description	Weight	Factory Data	List Price
		•		
OPERATOR'S MA	ANUAL			
00 47404 0	DED ATODIO MANILIAI			
SD_4/181 O 747480	PERATOR'S MANUAL Operators Manual Facilish			No Charge
747480	Operators Manual - English Operators Manual - French			No Charge No Charge
747961	Operators Manual-Trench Operators Manual-Spanish			No Charge
1 1 747404	Operators Manuar- Spanish		<u> </u>	No Charge
VERSION				
VERSION				
SD_10181 C	RAWLER TYPE			
9552700				No Charge
0002700	One-piece molded rubber belt track w/ a steel cable core.			no onarge
	The entire track must be replaced at time of service. Select			
	this track for general use on soils & hard surfaces.			
ļ ļ	The fide to the fi		1	
ODED ATODIS DE	ROTECTIVE STRUCTURE			
OF ENATOR 3 FT	ROTECTIVE STRUCTURE			
SD_05127 C	ΔB			
747239	CANOPY 747239			No Charge
747238	CAB 747238			\$5,960.00
1 1 11200	0/15 / 1/200		<u> </u>	φο,σσσ.σσ
ADDITIONAL EQ	LIIDMENT MEY			
ADDITIONAL EQ	OIF MILITI WILA			
SD_30180 TF	PAVEL ALAPM			
747994	W/O Travel Alarm			No Charge
747453	Travel Alarm			\$207.00
1 1 141400	Traverriam		1	Ψ201.00
SD 40003 C	OUNTERWEIGHT			
	Standard Counterweight.			No Charge
747996	Additional Counterweight.			\$206.00
	Additional bolt on weight adds 286 lb (130 kg) - CX26C			+ =====
	Additional bolt on weight adds 330 lb (150 kg) - CX37C			
	CX37C - Add. Cwt comes w/ Angle Blade			
			1	
SD X5405 2I	ND AUX. CIRCUIT			
	T			

No Charge

SD_X6210 BEACON 747087 W/O -

747088

W/O - Beacon

LED Beacon

CX26C **US PRICE LIST** (Ex Works Port of Entry) 747053 \$1,633.00 2nd Aux 2-Way Proportional CX37C - if ordering Angle Blade - 2nd 2-way Aux is used for the angle circuit. Cannot order 747053 with 747981 4-way Angle Blade. NOTE: 2nd Aux INCLUDES 1st Aux hose options. SD_X5406 1ST AUX HYD TWO WAYS 747054 2Way Aux Pedal Proportional No Charge 2Way Aux Joystick Proportional No Charge 747055 SD_X5413 AUX WORKING LIGHTS 747242 LED Working Lights \$150.00 Replaces Halogen Lights on the boom and cab with LED. SD X6100 ARM 747078 Arm Short w/Thumb Bracket No Charge Please refer to the Standard pages for arm lengths 747079 \$327.00 Arm Long w/Thumb Bracket Long arm increases dig depth, resulting in a reduction in arm digging forces & lift capacity. Please refer to the Standard Pages for arm lengths. SD_X6206 LINKAGE 747062 Linkage With Hook No Charge 747063 Linkage Without Hook (\$61.00)SD_X6207 HYDR Q/C PROV. W/O Q/C Provision 747065 No Charge 747064 Hydraulic Q/C Provision \$500.00 Includes switch & hydraulic lines to end of arm. Recommended for use with Additional Counterweight.

No Charge

\$280.00



(Ex Works Port of Entry) Factory Supplied Attachments

Order Code	Description	Weight	Factory Data	List Price
KLAC Buckets & Co	upler			
48094116	12"HD Bucket (KLAC Coupler)	143 LB		\$524.00
48094117	18"HD Bucket (KLAC Coupler)	176 LB		\$625.00
48094118	24"HD Bucket (KLAC Coupler)	209 LB		\$800.00
48057633	Coupler, KLAC	71 LB		\$1,102.00
47422632	KLAC Base Plate (To adapt other buckets)	20 LB		\$285.00
Pin-On Buckets & C	oupler			
48057611	12"HD Bucket (Mech/Hyd Coupler)	121 LB		\$521.00
48057612	18"HD Bucket (Mech/Hyd Coupler)	154 LB		\$623.00
48057613	24"HD Bucket (Mech/Hyd Coupler)	185 LB		\$797.00
48057615	Coupler, Mechanical Pin-Grabber (Only compatible with the C-Series bucket) Includes 1 set of dead pins for installation into a single bucket	95 LB		\$1,538.00
48094307	Coupler, Hydraulic Pin-Grabber (Compatible with both the B/C-Series buckets, when used with a B-Series bucket, it requires the removal of the spacer plates) Includes 1 set of dead pins for installation into a single bucket Recommended for use with Additional Counterweight.	99 LB		\$3,386.00
47457879	Dead Pin Kit Required when ordering more than 1 bucket with a Pin- Grabber Coupler	8 LB		\$177.00
Thumbs				
48058019	Thumb Kit, Hyd., Short Tines (Use with direct fit, KLAC buckets and Mechanical Pin-Grabber coupler) Recommended for use with Additional Counterweight.	150 LB		\$2,248.00
48094114	Thumb Kit, Hyd., Long Tines (Use w/Hyd. Pin-Grabber coupler only) Recommended for use with Additional Counterweight.	150 LB		\$2,248.00

C-Series Mini Excavator BUCKET COMPATIBILITY				
Model	Order Code	Description	B-Series Buckets	C-Series Buckets
CX17C	48057609	Coupler, Mechanical Pin-Grabber	No	Yes
	48057615	Coupler, Mechanical Pin-Grabber	No	Yes
CX26C/CX30C	48094307	Coupler, Hydraulic Pin-Grabber	Yes (requires removal of spacer plates)	Yes
CX37C	48057623	Coupler, Mechanical Pin-Grabber	Yes	Yes
CX37C	48058013	Coupler, Hydraulic Pin-Grabber	Yes	Yes
CVETC (CVCOC	48057630	Coupler, Mechanical Pin-Grabber	No	Yes
CX57C/CX60C	48058014	Coupler, Hydraulic Pin-Grabber	No	Yes
	48082917	Coupler, B/C Series Universal Mechanical	Yes	Yes

CX26C Compact Excavator

P/N	Kit Name	Notes
90444178	MHEX Telematics Ready DIA 4G	
48118005	Travel Alarm	
90396979	1 Auxiliary 2 Way Joystick, E, DIA	
90399877	2nd Aux circuit, with Hammer Joy, E, DIA, CAS	
90358062	Counterweight, CW04, DIA	
51478711	Heavy Counterweight	
48100305	Seat Belt 3 INCH	
51638897	Quick Coupler, DIA, CASE, Double EFFEC	

This table of field installed accessories is only intended to provide guidance on where field installed accessories are ordered. Dealers should reference the online PARTS catalog for each model for an up-to-date list of components, field kits and accessories. These kits are subject to change without notice. For pricing, availability and technical questions contact CNHi Parts.

Bid Term: 2/22/19 - 2/21/21; Extended to 2/21/22: EXtended to 2/21/23



(Ex Works Port of Entry) Standard Equipment

```
ENGINE:
                                                    ELECTRICAL:
 Kubota D1305 3 Cyl. water-
                                                      12 Volt electrical starting system
    cooled, mechanical injection diesel
                                                         includes heavy-duty battery and
 77.0 CID (1.261L)
                                                         starting motor
 Tier 4 Final
                                                      40 Amp Alternator
 Glow plugs
                                                      Battery Master Switch
 Horsepower:
                                                      Key Start
   Gross 24.8 HP (18.5 kW)/2300
                                                      Anti-Theft-Engine starting passwords
   Net 23.2 HP (17.3 kW)/2300
                                                     Dual 12V power plug recepticals
 Maximum Engine Torque:
                                                      Front working lights on cab & boom
     60.0 lb ft (81.4 Nm) @ 1600 rpm
                                                     Pre-wired telematics ready
 Dry type air cleaner dual element
                                                    BLADE:
OPERATOR PROTECTIVE STRUCTURE:
                                                      Hydraulically controlled dozer blade
Sound Levels:
                                                    UNDERCARRIAGE:
     ISO 6396:2008 sound pressure
                                                     Rubber tracks
                                                      Track pad width: 11.8" (250 mm)
      level LpA=73.5bB (A)
ROPS/FOPS:
                                                      Track length: 6'6" (1910 mm)
  Four post canopy design
                                                      Gradeability: 30 degrees
                                                     Ground Clearance: 11" (290 mm)
                                                   TRACK DRIVE:
  Enclosed Cab with overhead opening
    front window, sliding side window,
                                                     Two speed Auto shift travel
   lockable door, heater and defroster,
                                                      Fully hydrostatic drive system
   radio/USB player + 2 speakers
                                                      Track tension adjustment
  Mechanical suspension seat, with
                                                        (grease type)
     2" seat belt
                                                      Sealed and lubricated track
  Pilot operated joysticks for boom, arm
                                                   HYDRAULICS:
    bucket, and swing with adjustable
                                                      Control pattern selector valve
                                                     Hydraulic oil filter
     wrist rests
  Foot pedals for travel control and
                                                      Total Auxiliary Flow:
     swing tower control
                                                        12.5 gpm @ 2,538 psi
 Gauges:
                                                        (47.2 L/min @ 175 bar)
                                                      Main Pump: 3,130 PSI
  Engine coolant temperature and fuel
     level
                                                      Auxiliary valve and piping with shut
                                                        off block at end of arm
 Indicator Lights:
   Engine oil pressure, coolant
                                                     Proportional auxiliary hydraulic flow
    temperature, battery
                                                        control
    charge, low fuel warning, engine
                                                     Selector valve for single or
    preheat, air cleaner warning,
                                                        two-way aux flow
   hyd. quick coupler
                                                     Large capacity hydraulic oil cooler
    lock, and high travel speed
                                                      Cylinder rod protection covers
                                                        -Dozer & Boom
                                                    UPPER:
                                                      Standard Arm: 3'8" (1.12 m)
                                                      Boom: 6'8" (1.95 m)
                                                      Boom Swing: 75° left / 50° right
```



(Ex Works Port of Entry) Standard Equipment

Zero Tail Swing
Swing brake: disc type, spring allied
and hydraulically released
Bucket linkage with lifting hook
MISCELLANEOUS:
Operating weight:
Canopy short arm - 6,020 lbs.
(2505 kg)
Cab, short arm - 6,350 lbs. (2655 kg)

All weights are with rubber tracks, no quick coupler, bucket, fluids, full of fuel, and 165lb operator
Additional Counterweight - 286 lbs
Warranty - Base warranty Coverage:
2-Year/3,000-Hour Full Machine
Limited Warranty



(Ex Works Port of Entry) Models

COMMERCIAL MODEL	Weight	Factory Data	List Price
CX30C	7.990 LB	·	\$53.691.00

Packet	Description	Weight	Factory Data	List Price
CX30C Cab Std Arm II				\$487.00
SD_05136-RADIO OPTION	Radio and USB			
SD_30180-TRAVEL ALARM	Travel Alarm			
SD_40003-COUNTERWEIGHT	Additional Counterweight.			
SD_X5183-AIR COND/HEATER	Heater Only			
SD_X5405-2ND AUX. CIRCUIT	W/O 2nd Aux 2-Way Proportional			
SD_X6100-ARM	Arm Short w/Thumb Bracket			
SD_X6206-LINKAGE	Linkage With Hook			
SD_X6207-HYDR Q/C PROV.	W/O Q/C Provision			
SD_X6210-BEACON	LED Beacon			
CX30C ROPS Std ArmII				\$487.00
SD_30180-TRAVEL ALARM	Travel Alarm			
SD_40003-COUNTERWEIGHT	Additional Counterweight.			
SD_X5405-2ND AUX. CIRCUIT	W/O 2nd Aux 2-Way Proportional			
SD_X5406-1ST AUX HYD TWO	2Way Aux Joystick Proportional			
WAYS				
SD_X6100-ARM	Arm Short w/Thumb Bracket			
SD_X6206-LINKAGE	Linkage With Hook			
SD_X6207-HYDR Q/C PROV.	W/O Q/C Provision			
SD_X6210-BEACON	LED Beacon			

Pre-Configured Package is full model packages for Standard Arm configurations. Once a package is selected, you can then select the required Buckets/Attachments to go along with your unit. Keep in mind, it is not possible to modify (add/remove) any other vehicle options when you select a Pre-Configured package. If a Pre-Configured unit is ordered, it will be matched to one that is already built and ready to ship, which will reduce the lead-time by several months. Independent Option ordering is still available if the package is not desired, however you may experience a longer lead-time.



(Ex Works Port of Entry) Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
ODEDATOR'S MA	ANITAT			
OPERATOR'S MA	RNUAL			
SD_47181 OF	PERATOR'S MANUAL			
747480	Operators Manual - English			No Charge
747961	Operators Manual - French			No Charge
747464	Operators Manual- Spanish			No Charge
VERSION				
VERSION				
SD_10181 CF	RAWLER TYPE			
9552700	Rubber Tracks			No Charge
	One-piece molded rubber belt track w/ a steel cable core.			
	The entire track must be replaced at time of service. Select			
	this track for general use on soils & hard surfaces.			
OPERATOR'S PR	OTECTIVE STRUCTURE			
SD_05127 CA	A.R.			
747239	CANOPY 747239			No Charge
747238	CAB 747238			\$5,711.00
1 1 17200	10/18/14/200		<u> </u>	φο,γ ττισο
ADDITIONAL EQ	UIPMENT MEX			
SD_30180 TF				
747994	W/O Travel Alarm			No Charge
747453	Travel Alarm			\$207.00
SD XE40E 2N	ID AUX. CIRCUIT			
747999	W/O 2nd Aux 2-Way Proportional			No Charge
747053	2nd Aux 2-Way Proportional			\$1,633.00
	CX37C - if ordering Angle Blade - 2nd 2-way Aux is used			ψ1,000.00
	for the angle circuit. Cannot order 747053 with 747981			
	4-way Angle Blade.			
	Thuy Aligio Blade.			
			1	

NOTE: 2nd Aux INCLUDES 1st Aux hose options.

747088

LED Beacon



CX30C US PRICE LIST

(Ex Works Port of Entry)

SD_X5406	1ST AUX HYD TWO WAYS	
74705	54 2Way Aux Pedal Proportional	No Charge
74705		No Charge
SD_X5413	AUX WORKING LIGHTS	
74724	42 LED Working Lights	\$150.00
	Replaces Halogen Lights on the boom and cab with LED.	
SD_X6100	ARM	
74707	78 Arm Short w/Thumb Bracket	No Charge
	Please refer to the Standard pages for arm lengths	
SD_X6206		
74706	62 Linkage With Hook	No Charge
74706	53 Linkage Without Hook	(\$61.00)
SD_X6207	HYDR Q/C PROV.	
74706	65 W/O Q/C Provision	No Charge
74706	64 Hydraulic Q/C Provision	\$500.00
	Includes switch & hydraulic lines to end of arm.	
	Recommended for use with Additional Counterweight.	
SD_X6210	BEACON	
74708	37 W/O - Beacon	No Charge

\$280.00



(Ex Works Port of Entry) Factory Supplied Attachments

Order Code	Description	Weight	Factory Data	List Price
1-Position Pin-On				
48190704	12" High Capacity Bucket ONLY for usage w/o a coupler.			\$773.00
48190705	18" High Capacity Bucket ONLY for usage w/o a coupler.			\$856.00
48190706	24" High Capacity Bucket ONLY for usage w/o a coupler.			\$998.00
KLAC Buckets & Co	pupler			
48094116	12"HD Bucket (KLAC Coupler)	143 LB		\$524.00
48094117	18"HD Bucket (KLAC Coupler)	176 LB		\$625.00
48094118	24"HD Bucket (KLAC Coupler)	209 LB		\$800.00
48057633	Coupler, KLAC	71 LB		\$1,102.00
47422632	KLAC Base Plate (To adapt other buckets)	20 LB		\$285.00
Pin-On Buckets & C	Coupler			
48057611	12"HD Bucket (Mech/Hyd Coupler)	121 LB		\$521.00
48057612	18"HD Bucket (Mech/Hyd Coupler)	154 LB		\$623.00
48057613	24"HD Bucket (Mech/Hyd Coupler)	185 LB		\$797.00
48057615	Coupler, Mechanical Pin-Grabber (Only compatible with the C-Series bucket) Includes 1 set of dead pins for installation into a single bucket	95 LB		\$1,538.00
48094307	Coupler, Hydraulic Pin-Grabber (Compatible with both the B/C-Series buckets, when used with a B-Series bucket, it requires the removal of the spacer plates) Includes 1 set of dead pins for installation into a single bucket Recommended for use with Additional Counterweight.	99 LB		\$3,386.00
47457879	Dead Pin Kit Required when ordering more than 1 bucket with a Pin- Grabber Coupler	8 LB		\$177.00
Thumbs				
48058019	Thumb Kit, Hyd., Short Tines (Use with direct fit, KLAC buckets and Mechanical Pin-Grabber coupler) Recommended for use with Additional Counterweight.	150 LB		\$2,248.00
48094114	Thumb Kit, Hyd., Long Tines (Use w/Hyd. Pin-Grabber coupler only) Recommended for use with Additional Counterweight.	150 LB		\$2,248.00

	C-	Series Mini Excavator BUCKET COMPATIBILIT	Υ	
Model	Order Code	Description	B-Series Buckets	C-Series Buckets
CX17C	48057609	Coupler, Mechanical Pin-Grabber	No	Yes
	48057615	Coupler, Mechanical Pin-Grabber	No	Yes
CX26C/CX30C	48094307	Coupler, Hydraulic Pin-Grabber	Yes (requires removal of spacer plates)	Yes
CX37C	48057623	Coupler, Mechanical Pin-Grabber	Yes	Yes
CASTC	48058013	Coupler, Hydraulic Pin-Grabber	Yes	Yes
0,4570,40,4500	48057630	Coupler, Mechanical Pin-Grabber	No	Yes
CX57C/CX60C	48058014	Coupler, Hydraulic Pin-Grabber	No	Yes
	48082917	Coupler, B/C Series Universal Mechanical	Yes	Yes

CX30C Compact Excavator

P/N	Kit Name	Notes
90444178	Telematics Ready DIA 4G	
48118005	Travel Alarm DIA	
90396979	1 Aux 2 Way Joystick, E, DIA	
90399880	2nd Aux Circuit, with Hammer Joy, E, DIA	
90349822	Counterweight, CW04, DIA	
48100305	Seat Belt 3 INCH	
51638905	Quick Coupler, DIA, CASE, Double EFFEC	

This table of field installed accessories is only intended to provide guidance on where field installed accessories are ordered. Dealers should reference the online PARTS catalog for each model for an up-to-date list of components, field kits and accessories. These kits are subject to change without notice. For pricing, availability and technical questions contact CNHi Parts.

(This page intentionally left blank)



(Ex Works Port of Entry) Standard Equipment

```
ENGINE:
                                                    ELECTRICAL:
 Yanmar 3TNV88F-ESHYB
                                                      12 Volt electrical starting system
    3 Cvl. water-cooled
                                                         includes heavy-duty battery and
    direct injection diesel
                                                         starting motor
    100.2 CID (1.642L)
                                                      55 Amp alternator
 Tier 4 Final
                                                      Battery master switch
 Glow plugs
                                                      Key start
 Horsepower:
                                                      Anti-theft-engine starting passwords
   Gross 24.4 HP (18.2 kW)/2200
                                                      Dual 12V power plug recepticals
   Net 23.7 HP (17.7 kW)/2200
                                                      Front working lights on cab & boom
 Maximum Engine Torque:
                                                      Auto idle feature with on/off switch
    69.4 lb ft (94.1 Nm) @ 1200 rpm
                                                      Pre-wired telematics ready
 Dry type air cleaner
                                                    BLADE:
OPERATOR PROTECTIVE STRUCTURE:
                                                      Hydraulically controlled dozer blade
Sound Levels:
                                                    UNDERCARRIAGE:
     ISO 6396:2008 sound pressure
                                                      Rubber tracks
      level LpA=75bB (A)
                                                      Track pad width: 12" (300 mm)
ROPS/FOPS:
                                                      Track length: 7'0" (2130 mm)
  Four post canopy design
                                                      Gradeability: 30 degrees
                                                      Ground clearance: 11" (290 mm)
   Enclosed cab with overhead opening
                                                    TRACK DRIVE:
    front window, sliding side window,
                                                      Two speed travel
    lockable door, heater, defroster, air
                                                      Fully hydrostatic drive system
    conditioner and radio/USB player + 2
                                                      Track tension adjustment
    speakers
                                                        (grease type)
  Mechanical suspension seat, with
                                                      Sealed and lubricated track
     2 " seat belt
                                                    HYDRAULICS:
                                                      Control pattern selector valve
  Pilot operated joysticks for boom, arm,
    bucket, and swing with adjustable
                                                      Hydraulic oil filter
     wrist rests
                                                      Total Auxiliary Flow:
  Foot pedals for travel control and
                                                        16.0 gpm @ 2,973 psi
                                                        (60.5 L/min @ 205 bar)
     swing tower control
 Gauges:
                                                      Main Pump: 3,270 PSI
  Engine Coolant temp and fuel level
                                                      Auxiliary valve and piping with shut
 Indicator Lights:
                                                        off block at end of arm
    Engine oil pressure, coolant
                                                      Proportional auxillary hydraulic flow
    temperature, battery
                                                        control
    charge, low fuel warning, engine
                                                      Selector valve for single or
   preheat, air cleaner warning,
                                                        two-way aux flow
   hyd. quick coupler
                                                      Large capacity hydraulic oil cooler
    lock, and high travel speed
                                                      Cylinder rod protection covers
                                                        -Dozer & Boom
                                                    UPPER:
                                                      Standard Arm: 4'3" (1.3 m)
                                                      Optional Long Arm: 5'3" (1.6 m)
```



(Ex Works Port of Entry) Standard Equipment

Boom: 8'2" (2.5 m)
Boom Swing: 75° left / 50° right
Zero Tail Swing
Swing brake: disc type, spring applied
and hydraulically released
Bucket linkage with lifting hook
MISCELLANEOUS:
Canopy, short arm - 7,990 lbs.
(3,625 Kg)
Canopy, long arm additional
counterweight - 8,350 lbs.

(3790 Kg.)

Cab, short arm - 8,300 lbs. (3765 kg)
Cab, long arm - additional
counterweight - 8,660 lbs.
(3930 kg)
All weights are with rubber tracks, no
quick coupler, bucket, fluids, full of
fuel, thumb bracket and 1651b
operator
Additional counterweight - 330 lbs
Warranty - Base warranty Coverage:
2-Year/3,000-Hour Full Machine



(Ex Works Port of Entry) Models

COMMERCIAL MODEL	Weight	Factory Data	List Price
CX37C	7,990 LB		\$57,550.00

Packet	Description	Weight	Factory Data	List Price
CX37C CAB Lg Angl II				\$4431.00
SD_05136-RADIO OPTION	Radio and USB			
SD_10181-CRAWLER TYPE	Rubber Tracks			
SD_30180-TRAVEL ALARM	Travel Alarm			
SD_40003-COUNTERWEIGHT	Additional Counterweight.			
SD X5183-AIR COND/HEATER	A/C AND HEATER			
SD_X5405-2ND AUX. CIRCUIT	W/O 2nd Aux 2-Way Proportional			
SD_X5406-1ST AUX HYD TWO WAYS	2Way Aux Joystick Proportional]		
SD_X6100-ARM	Arm Long w/Thumb Bracket			
SD_X6105-DOZER BLADE OPTION	4-Way Angle Dozer Blade			
SD_X6206-LINKAGE	Linkage With Hook			
SD_X6207-HYDR Q/C PROV.	W/O Q/C Provision			
SD_X6210-BEACON	LED Beacon			
•				
CX37C Cab Lg Arm II				\$1024.00
SD_05136-RADIO OPTION	Radio and USB			
SD_10181-CRAWLER TYPE	Rubber Tracks			
SD 30180-TRAVEL ALARM	Travel Alarm			
SD_40003-COUNTERWEIGHT	Additional Counterweight.			
SD_X5183-AIR COND/HEATER	A/C AND HEATER			
SD_X5405-2ND AUX. CIRCUIT	W/O 2nd Aux 2-Way Proportional			
SD_X5406-1ST AUX HYD TWO WAYS	2Way Aux Joystick Proportional			
SD_X6100-ARM	Arm Long w/Thumb Bracket			
SD_X6206-LINKAGE	Linkage With Hook			
SD_X6207-HYDR Q/C PROV.	W/O Q/C Provision			
SD_X6210-BEACON	LED Beacon			
CX37C CAB Sh Arm II				\$487.00
SD_05136-RADIO OPTION	Radio and USB			
SD_10181-CRAWLER TYPE	Rubber Tracks			
SD_30180-TRAVEL ALARM	Travel Alarm			
SD_40003-COUNTERWEIGHT	Standard Counterweight.			
SD_X5183-AIR COND/HEATER	A/C AND HEATER			
SD_X5405-2ND AUX. CIRCUIT	W/O 2nd Aux 2-Way Proportional			
SD_X5406-1ST AUX HYD TWO WAYS	2Way Aux Joystick Proportional			
SD_X6100-ARM	Arm Short w/Thumb Bracket			
SD_X6206-LINKAGE	Linkage With Hook			
SD_X6207-HYDR Q/C PROV.	W/O Q/C Provision			



(Ex Works Port of Entry)

Packet	Description	Weight	Factory Data	List Price
SD_X6210-BEACON	LED Beacon			
•				
CX37C ROPS Lg Ang II				\$4431.00
SD_10181-CRAWLER TYPE	Rubber Tracks			
SD_30180-TRAVEL ALARM	Travel Alarm			
SD_40003-COUNTERWEIGHT	Additional Counterweight.			
SD_X5405-2ND AUX. CIRCUIT	W/O 2nd Aux 2-Way Proportional			
SD_X5406-1ST AUX HYD TWO WAYS	2Way Aux Joystick Proportional			
SD_X6100-ARM	Arm Long w/Thumb Bracket			
SD_X6105-DOZER BLADE OPTION	4-Way Angle Dozer Blade			
SD_X6206-LINKAGE	Linkage With Hook			
SD_X6207-HYDR Q/C PROV.	W/O Q/C Provision			
SD_X6210-BEACON	LED Beacon			
CX37C ROPS Lg Arm II				\$1024.00
SD_10181-CRAWLER TYPE	Rubber Tracks			
SD_30180-TRAVEL ALARM	Travel Alarm			
SD_40003-COUNTERWEIGHT	Additional Counterweight.			
SD_X5405-2ND AUX. CIRCUIT	W/O 2nd Aux 2-Way Proportional			
SD_X5406-1ST AUX HYD TWO WAYS	2Way Aux Joystick Proportional			
SD_X6100-ARM	Arm Long w/Thumb Bracket			
SD_X6206-LINKAGE	Linkage With Hook			
SD_X6207-HYDR Q/C PROV.	W/O Q/C Provision			
SD_X6210-BEACON	LED Beacon			
<u> </u>			.	
CX37C ROPS Sh Arm II				\$487.00
SD_10181-CRAWLER TYPE	Rubber Tracks			
SD_30180-TRAVEL ALARM	Travel Alarm			
SD_40003-COUNTERWEIGHT	Standard Counterweight.			
SD_X5405-2ND AUX. CIRCUIT	W/O 2nd Aux 2-Way Proportional			
SD_X5406-1ST AUX HYD TWO WAYS	2Way Aux Joystick Proportional			
SD_X6100-ARM	Arm Short w/Thumb Bracket			
SD_X6206-LINKAGE	Linkage With Hook			
SD_X6207-HYDR Q/C PROV.	W/O Q/C Provision			
SD_X6210-BEACON	LED Beacon			

Pre-Configured Packages are full model packages for Short Arm or Long Arm configurations. Once a package is selected, you can then select the required Buckets/Attachments to go along with your unit. Keep in mind, it is not possible to modify (add/remove) any other vehicle options when you select a Pre-Configured package. If a Pre-Configured unit is ordered, it will be matched to one that is already built and ready to ship, which will reduce the lead-time by several months. Independent Option ordering is still available if the package is not desired, however you may experience a longer lead-time.



(Ex Works Port of Entry) Factory Supplied Options

t descriptions of money				
Order Code	Description	Weight	Factory Data	List Price
OPERATOR'S MA	NIIAI			
OI ERATOR O IMP				
SD_47181 OF 747480	PERATOR'S MANUAL Operators Manual - English	T		No Chargo
747460	Operators Manual - English Operators Manual - French			No Charge No Charge
747961	Operators Manual-Spanish			No Charge
		•		
VERSION				
SD_10181 CF	RAWLER TYPE			
9552700	Rubber Tracks	T		No Charge
3332700	One-piece molded rubber belt track w/ a steel cable core.			No onarge
	The entire track must be replaced at time of service. Select			
	this track for general use on soils & hard surfaces.			
9553700	Steel Tracks			\$1,536.00
	Steel Track chain with steel grousers/shoes. Select this track for			,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
	the most aggressive traction in soils & if there is no concern for			
	disrupting the appearance of ground conditions such as grass,			
	asphalt or concrete. This track is intended for use on soils, but			
	can be used on hard surfaces as well.			
OPERATOR'S PR	OTECTIVE STRUCTURE			
CD 05407 C/	.n			
SD_05127 CA 747239	CANOPY 747239			No Charge
747238	CANOF 1 747239 CAB 747238	+		\$9,098.00
1 1 141230	OND 141200	1	<u> </u>	ψ3,030.00
ADDITIONAL EQ	JIPMENT MEX			
SD_30180 TR			 	
747994	W/O Travel Alarm	+		No Charge
747453	Travel Alarm			\$207.00
SD_40003 CC	DUNTERWEIGHT			
747995	Standard Counterweight.			No Charge
1 1 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	1 Standard Souther Holgini	1		. No Onlarge

CX37C US PRICE LIST (Ex Works Port of Entry) 747996 Additional Counterweight. \$210.00 Additional bolt on weight adds 286 lb (130 kg) - CX26C Additional bolt on weight adds 330 lb (150 kg) - CX37C CX37C - Add. Cwt comes w/ Angle Blade SD_X5405 2ND AUX. CIRCUIT 747999 W/O 2nd Aux 2-Way Proportional No Charge 747053 \$1,892.00 2nd Aux 2-Way Proportional CX37C - if ordering Angle Blade - 2nd 2-way Aux is used for the angle circuit. Cannot order 747053 with 747981 4-way Angle Blade. NOTE: 2nd Aux INCLUDES 1st Aux hose options. SD_X5406 1ST AUX HYD TWO WAYS 747054 | 2Way Aux Pedal Proportional No Charge 747055 2Way Aux Joystick Proportional No Charge SD_X5413 AUX WORKING LIGHTS 747242 LED Working Lights \$150.00 Replaces Halogen Lights on the boom and cab with LED. SD_X6100 ARM 747078 Arm Short w/Thumb Bracket No Charge Please refer to the Standard pages for arm lengths 747079 Arm Long w/Thumb Bracket \$327.00 Long arm increases dig depth, resulting in a reduction in arm digging forces & lift capacity. Please refer to the Standard Pages for arm lengths. SD_X6105 DOZER BLADE OPTION 747232 STD DOZER BLADE 747232 No Charge 747981 \$3,407.00 4-Way Angle Dozer Blade The weight of the dozer blade option adds 220 lbs. (100 kg) & includes the additional counterweight which adds 330 lbs. (150 kg) for a total added weight of 550 lbs. (250 kg)

Option REQUIRES the additional counterweight 747996

Includes bolt-on reversible cutting edge

Linkage With Hook

Linkage Without Hook

SD_X6206 LINKAGE 747062 Linkage

SD_X6207 HYDR Q/C PROV.

747065 W/O Q/C Provision

747063

No Charge

No Charge

(\$61.00)

CX37C US PRICE LIST

(Ex Works Port of Entry)

Γ	747064	Hydraulic Q/C Provision		\$500.00
		Includes switch & hydraulic lines to end of arm.		
L		Recommended for use with Additional Counterweight.		

SU XOZIU BEAUUN	BEACC	BI	X6210	SD	
-----------------	-------	----	-------	----	--

Γ	747087	W/O - Beacon		No Charge
Γ	747088	LED Beacon		\$280.00



CX37C US PRICE LIST

(Ex Works Port of Entry) Factory Supplied Attachments

Order Code	Description	Weight	Factory Data	List Price
KLAC Buckets & C	Coupler			
47422654	12"HD Bucket (KLAC Coupler)	189 LB		\$1,008.00
47422655	18"HD Bucket (KLAC Coupler)	223 LB		\$1,091.00
47422656	24"HD Bucket (KLAC Coupler)	267 LB		\$1,233.00
47422658	36"Ditch Bucket (KLAC Coupler)	315 LB		\$1,139.00
48057634	Coupler, KLAC	43 LB		\$1,239.00
Pin-On Buckets &	Coupler			
48057617	12"HD Bucket (Pin-On & Mech/Hyd Coupler)	161 LB		\$774.00
48057619	18"HD Bucket (Pin-On & Mech/Hyd Coupler)	205 LB		\$857.00
48057620	24"HD Bucket (Pin-On & Mech/Hyd Coupler)	247 LB		\$998.00
48057621	BUCKET, 36IN, 1-POS PIN-O	331 LB		\$1,270.00
48057622	36"Ditch Bucket (Pin-On & M/H Coupler)	313 LB		\$1,054.00
48057623	Coupler, Mechanical Pin-Grabber (Compatible with both the B/C-Series buckets) Includes 1 set of dead pins for installation into a single bucket	43 LB		\$1,545.00
48058013	Coupler,Hydraulic Pin-Grabber (Compatible with both the B/C-Series buckets) Recommended for use with Additional Counterweight.	132 LB		\$3,386.00
48057624	Dead Pin Kit (for additional buckets) Required when ordering more than 1 bucket with a Pin- Grabber Coupler	11 LB		\$197.00
48057638	Ripper Tooth Pin-On	220 LB		\$929.00
Thumbs		•		,
48059646	Thumb Kit, Hyd.,Short Tines (Use with direct fit and KLAC buckets) Recommended for use with Additional Counterweight.	150 LB		\$2,350.00
48058020	Thumb Kit, Hyd.,Long Tines (Use with Mech. and Hyd. Pin-Grabber couplers) Recommended for use with Additional Counterweight.	200 LB		\$2,350.00

	C-Series Mini Excavator BUCKET COMPATIBILITY				
Model	Order Code	Description	B-Series Buckets	C-Series Buckets	
CX17C	48057609	Coupler, Mechanical Pin-Grabber	No	Yes	
	48057615	Coupler, Mechanical Pin-Grabber	No	Yes	
CX26C/CX30C	48094307	Coupler, Hydraulic Pin-Grabber	Yes (requires removal of spacer plates)	Yes	
CX37C	48057623	Coupler, Mechanical Pin-Grabber	Yes	Yes	
CX37C	48058013	Coupler, Hydraulic Pin-Grabber	Yes	Yes	
CVEZC/CVCAC	48057630	Coupler, Mechanical Pin-Grabber	No	Yes	
CX57C/CX60C	48058014	Coupler, Hydraulic Pin-Grabber	No	Yes	
	48082917	Coupler, B/C Series Universal Mechanical	Yes	Yes	

CX37C Compact Excavator

P/N	Kit Name	Notes
90445645	Telematics Ready DIA	
48118007	Travel Alarm DIA	
90396982	1 AUX 2 Way Joystick, E, DIA	
90401986	2nd Aux Circuit, with Hammer Joy, E, DIA, CAS	
48120185	Counterweight, CW04, DIA	
48100305	Seat Belt 3 INCH DIA	
51663823	Quick Coupler, DIA, CASE, Double EFFEC	
48154618	Air Conditioning and heater	
90460196	Diverter Valve	

This table of field installed accessories is only intended to provide guidance on where field installed accessories are ordered. Dealers should reference the online PARTS catalog for each model for an up-to-date list of components, field kits and accessories. These kits are subject to change without notice. For pricing, availability and technical questions contact CNHi Parts.

(This page intentionally left blank)



(Ex Works Port of Entry) Standard Equipment

ENGINE:

Yanmar 4TNV98C

4 Cyl. water-cooled,

electronic common rail diesel

203 CID (3.319L)

Tier 4 Final

Glow plugs

Horsepower:

Gross 66.9 HP (49.9 kW)/2400

Net 65.1 HP (48.5 kW)/2400

Maximum Engine Torque:

173.7 lb ft (235.4 Nm) @ 1550 rpm

Dry type air cleaner

OPERATOR PROTECTIVE STRUCTURE:

Sound Levels:

ISO 6396:2008 sound pressure

level LpA=76bB (A)

ROPS/FOPS:

Enclosed cab with overhead

opening front window, sliding side

window, lockable door, heater,

defroster and air conditioner,

radio/USB player + 2 speakers

bluetooth with remote control and

5.7" color LCD display screen

Mechanical suspension seat, with

2" seat belt, and seat heater

Pilot operated joysticks for boom, arm

bucket, and swing with adjustable

wrist rests

Foot pedals for travel control and

swing tower control

Gauges: Engine coolant temperature,

hydraulic oil temperature,

and fuel level

Indicator Lights: Hydraulic oil temp,

Air cleaner, engine stop, check

engine, water in fuel, battery

charging, emergency warning, low

fuel level, engine coolant

temperature, engine oil

pressure, DPF regeneration inhibit

warning and regeneration

acknowledge, DPF warning, and high

exhaust temparature

ELECTRICAL:

12 Volt electrical starting system

includes heavy-duty battery and

starting motor

60 Amp Alternator

Battery master switch

Key start

Anti-theft-engine starting passwords

Dual 12V power plug recepticals

Front and rear working lights

Auto idle feature with on/off switch

Pre-wired telematics ready

BLADE:

Hydraulically controlled dozer blade

UNDERCARRIAGE:

Rubber tracks

Track pad width: 15" (380 mm)

Track length: 8'4" (2530 mm)

Gradeability: 35 degrees

Ground clearance: 1'3" (380 mm)

TRACK DRIVE:

Two speed travel

Fully hydrostatic drive system

Track tension adjustment

(grease type)

Sealed and lubricated track

HYDRAULICS:

Electronic pattern change switch

inside cab controls selector valve

Hydraulic oil filter

Total Auxiliary Flow:

25.4 gpm @ 3,191 psi

(96.2 L/min @ 220 bar)

Main Pump: 3,130 PSI

Auxiliary valves and piping

for independent one way aux and

two way aux circuits.

Proportional auxiliary hydraulic flow

control



(Ex Works Port of Entry) Standard Equipment

Large capacity hydraulic oil cooler Cylinder rod protection covers -Dozer & Boom

UPPER:

Standard Arm w/Thumb bracket:

5'3" (1.6 m)

Optional Long Arm w/Thumb bracket:

6'3" (1.9 m)

Boom: 9'10" (2.5 m)

Boom Swing: 80° left / 50° right

Conventional Swing Radius

Swing brake: disc type, spring applied

and hydraulically released Bucket linkage with lifting hook

MISCELLANEOUS:

Operating weight:

Cab, short arm w/ Heavy counter-

weight - 12,270 lb (5565 kg)
Cab, long arm with Heavy

Counterweight - 12,320 lbs

(5590 kg)

All weights are with rubber tracks, no quick coupler, bucket, fluids, full of fuel, thumb bracket and 1651b

operator

Warranty - Base warranty Coverage: 2-Year/3,000-Hour Full Machine Limited Warranty



(Ex Works Port of Entry) Models

COMMERCIAL MODEL	Weight	Factory Data	List Price
CX57C CAB	12,270 LB		\$92,929.00

Packet	Description	Weight	Factory Data	List Price
CX57C Cab Lg Arm II				\$1216.00
SD_10181-CRAWLER TYPE	Rubber Tracks 400MM			
SD_30180-TRAVEL ALARM	Travel Alarm	1		
SD_40003-COUNTERWEIGHT	Additional Counterweight	1		
SD_X5405-2ND AUX. CIRCUIT	W/O 2nd Aux 2-Way Proportional	1		
SD_X5407-1ST AUX HYD CIRCUIT	2Way Aux Joystick Proportional			
SD_X5414-AUX WORKLIGHTS CAB	Working Lights			
SD X6100-ARM	Arm Long w/Thumb Bracket			
SD_X6206-LINKAGE	Linkage With Hook	1		
SD_X6207-HYDR Q/C PROV.	W/O Q/C Provision	1		
SD_X6210-BEACON	LED Beacon	1		
SD X9908-CAMERA	W/O Rear View Camera	1		
		•		
CX57C Lg Arm QC II				\$1857.00
SD_10181-CRAWLER TYPE	Rubber Tracks 400MM]		
SD_30180-TRAVEL ALARM	Travel Alarm			
SD_40003-COUNTERWEIGHT	Additional Counterweight			
SD_X5405-2ND AUX. CIRCUIT	W/O 2nd Aux 2-Way Proportional			
SD_X5407-1ST AUX HYD CIRCUIT	2Way Aux Joystick Proportional			
SD_X5414-AUX WORKLIGHTS CAB	Working Lights			
SD_X6100-ARM	Arm Long w/Thumb Bracket			
SD_X6206-LINKAGE	Linkage With Hook			
SD_X6207-HYDR Q/C PROV.	HYD Q/C PROV 2 WAY			
SD_X6210-BEACON	LED Beacon			
SD_X9908-CAMERA	W/O Rear View Camera			
		ı		
CX57C Sh Arm Acwt II				\$304.00
SD_10181-CRAWLER TYPE	Rubber Tracks 400MM			
SD_30180-TRAVEL ALARM	Travel Alarm			
SD_40003-COUNTERWEIGHT	Additional Counterweight			
SD_X5405-2ND AUX. CIRCUIT	W/O 2nd Aux 2-Way Proportional			
SD_X5407-1ST AUX HYD CIRCUIT	2Way Aux Joystick Proportional]		
SD_X5414-AUX WORKLIGHTS CAB	Working Lights			
SD_X6100-ARM	Arm Short w/Thumb Bracket			
SD_X6206-LINKAGE	Linkage With Hook			
SD_X6207-HYDR Q/C PROV.	W/O Q/C Provision			
SD_X6210-BEACON	LED Beacon			
SD_X9908-CAMERA	W/O Rear View Camera			



(Ex Works Port of Entry)

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

OPERATOR'S MANUAL

SD_47181 OPERATOR'S MANUAL

	747480	Operators Manual - English		No Charge
	747464	Operators Manual- Spanish		No Charge
	747961	Operators Manual - French		No Charge

VERSION

SD_10181 CRAWLER TYPE

9552711	Rubber Tracks 400MM		No Charge
	One-piece molded rubber belt track with a steel cable core.		
	The entire track must be replaced at time of service. Select		
	this track for general use on soils and hard surfaces.		
9552710	Rubber Link Tracks 400MM		\$11,986.00
	Steel track chain with molded rubber grousers/shoes. These		
	are also called hybrid tracks or roadliner tracks. Each Grouser/		
	shoe has a steel core completely molded in rubber and can be		
	individually replaced since they are bolted to a steel chain.		
	This track will offer the stability of a steel track with the		
	surface protection of a rubber track pad.		
9552612	Steel w/Pads 400 MM		\$4,241.00
	Steel track chain with steel grousers/shoes and bolt on rubber		
	track pads. Each rubber track pad can be individually replaced		
	or removed independently from the steel grouser/shoe. Select		
	this option to gain traction on hard surfaces such as asphalt or		
	concrete and to help protect their surface finish with the		
	rubber track pads attached. All of the rubber track pads can be		
	removed to perform as an all steel track as desired.		
9552613	Steel w/Pad Hole 400MM		\$2,200.00
	Steel track chain with steel grousers/shoes that have holes		
	to accept bolt on rubber track pads. Select this track for		
	the most aggressive traction in soils and if there is no		
	concern for disrupting the appearance of ground conditions		
	such as grass, asphalt or concrete. For added traction on		
	hard surfaces such as asphalt or concrete and to help protect		
	their surface finish it is recommended to use bolt on rubber		
	track pads.		

	(Ex Works Port of Entry)	
9552610	Steel Tracks 450 MM	\$2,320.00
	Steel track chain with steel grousers/shoes. Select this track	
	for the most aggressive traction in soils and if there is no	
	concern for disrupting the appearance of ground conditions	
	such as grass, asphalt or concrete. This track is intended for	
	use on soils, but can be used on hard surfaces as well.	
DITIONAL EQ	JIPMENT MEX	
CD 20400 TD	AVEL ALADAA	
SD_30180 TR 747453	Travel Alarm	\$304.0
747493	W/O Travel Alarm	No Charg
1 171334	W/O HaverAlaim	No onarg
SD_X5202 TF	RACK GUIDE	
747096	Full Track Guide	\$676.0
	Full track guides for steel tracks and steel tracks with bolt on	
	rubber track pads only	
747097	3-Piece Track Guide	No Charg
	3-piece track guides for steel tracks and steel tracks with bolt	
	on rubber track pads only	
	ID AUX. CIRCUIT	
747053	2nd Aux 2-Way Proportional	\$2,641.0
747999	W/O 2nd Aux 2-Way Proportional	No Charg
OD V5407 46	T ALIVEND OIDOUT	
747122	T AUX HYD CIRCUIT	No Charg
747123	2Way Aux Joystick Proportional 2Way Aux Pedal Proportional	\$646.0
14/123	2 VVay Aux 1 edai 1 Toportional	φ040.0
SD X5414 AL	JX WORKLIGHTS CAB	
747235	LED CAB WORKLIGHTS	\$150.0
	Replaces Halogen Lights on the boom and cab with LED.	
•		•
SD_X5415 RE	EAR AUX WORK LIGHTS	
747115	Rear Aux Work Lights	No Charg
SD_X6100 AF		<u> </u>
747078	Arm Short w/Thumb Bracket	No Charg
747079	Arm Long w/Thumb Bracket	\$912.0
	Long arm increases dig depth, resulting in a reduction in	
	arm digging forces & lift capacity. Please refer to the	

Standard Pages for arm lengths.

	00 1 MOL 2101	
	(Ex Works Port of Entry)	
747981	4-Way Angle Dozer Blade	\$4,100.00
	For CX60C: REQUIRES additional Counterweight 747084.	
	Added CWT is standard on CX57C. Includes bolt-on	
	reversible cutting edge.	
SD_X6206 LIN	NKAGE	
747062	Linkage With Hook	No Charge
747063	Linkage Without Hook	(\$140.00)
SD_X6207 HY	'DR Q/C PROV.	
747065	W/O Q/C Provision	No Charge
747236	HYD Q/C PROV 2 WAY	\$641.00
	For CX60C: Recommended for use with additional	
	counterweight 747084. Added CW is standard on	
	CX57C.	
SD_X6210 BE	EACON	
747088	LED Beacon	No Charge
747087	W/O - Beacon	(\$47.00)
3	ED_X6206 LIN 747062 747063 ED_X6207 HY 747065 747236 ED_X6210 BE 747088	747981 4-Way Angle Dozer Blade For CX60C: REQUIRES additional Counterweight 747084. Added CWT is standard on CX57C. Includes bolt-on reversible cutting edge. D_X6206 LINKAGE 747062 Linkage With Hook 747063 Linkage Without Hook D_X6207 HYDR Q/C PROV. 747065 W/O Q/C Provision 747236 HYD Q/C PROV 2 WAY For CX60C: Recommended for use with additional counterweight 747084. Added CW is standard on CX57C. D_X6210 BEACON 747088 LED Beacon

	SD_X9908 C	AMERA		
	747089	W/O Rear View Camera		No Charge
	747090	Rear View Camera		\$593.00



(Ex Works Port of Entry) Factory Supplied Attachments

Order Code	Description	Weight	Factory Data	List Price
in On Buckete 9	Couples			
2in-On Buckets & 48057625	12"HD Bucket (Pin-On & Mech/Hyd Coupler)	190 LB		\$931.00
48057626	18"HD Bucket (Pin-On & Mech/Hyd Coupler)	240 LB		\$1,001.00
48057627	24"HD Bucket (Pin-On & Mech/Hyd Coupler)	291 LB		\$1,143.00
48057628	36"HD Bucket (Pin-On & Mech/Hyd Coupler)	388 LB		\$1,143.00
48057629	36"Ditch Bucket (Pin-On & M/H Coupler)	313 LB		\$1,407.00
48057637	36"Cemetary Bucket (Pin-On & M/H Coupler)	305 LB		\$1,030.00
48057630	Coupler, Mechanical Pin-Grabber (Only compatible with the C-Series bucket) Includes 1 set of dead pins for installation into a single bucket	74 LB		\$1,200.00 \$1,545.00
48058014	Coupler, Hydraulic Pin-Grabber (Only compatible with the C-Series bucket)	63 LB		\$3,251.00
48082917	Coupler, B/C-Series Universal Mechanical (Compatible with both the B/C-Series buckets)	85 LB		\$824.00
48057631	PIN Required when ordering more than 1 bucket with a Pin- Grabber Coupler			\$209.00
48057639	Ripper Tooth Pin-On	220 LB		\$929.00
LAC Buckets & C	Coupler			
47422702	12"HD Bucket (KLAC Coupler)	220 LB		\$1,165.00
47422703	18"HD Bucket (KLAC Coupler)	256 LB		\$1,237.00
47422704	24"HD Bucket (KLAC Coupler)	309 LB		\$1,379.00
47422705	36"HD Bucket (KLAC Coupler)	408 LB		\$1,643.00
47422658	36"Ditch Bucket (KLAC Coupler)	315 LB		\$1,139.00
47872281	36"Cemetary Bucket (KLAC Coupler)	310 LB		\$1,200.00
48057636	Coupler, KLAC	55 LB		\$1,278.00
47422660	KLAC Base Plate (To adapt other buckets)	31 LB		\$348.00
47873455	ATTACHMENT, RIPPER TOOTH,	220 LB		\$929.00
humbs				
48058021	Thumb Kit, Hyd.,Long Tines (Use with Mech. and Hyd. Pin-Grabber couplers)	250 LB		\$2,453.00
48059650	Thumb Kit, Hyd.,Short Tines (Use with Direct Fit and Klac buckets)	250 LB		\$2,453.00

C-Series Mini Excavator BUCKET COMPATIBILITY					
Model	Order Code	Description	B-Series Buckets	C-Series Buckets	
CX17C	48057609	Coupler, Mechanical Pin-Grabber	No	Yes	
	48057615	Coupler, Mechanical Pin-Grabber	No	Yes	
CX26C/CX30C	48094307	Coupler, Hydraulic Pin-Grabber	Yes (requires removal of spacer plates)	Yes	
CX37C	48057623	Coupler, Mechanical Pin-Grabber	Yes	Yes	
CX37C	48058013	Coupler, Hydraulic Pin-Grabber	Yes	Yes	
CVETC IOVEDO	48057630	Coupler, Mechanical Pin-Grabber	No	Yes	
CX57C/CX60C	48058014	Coupler, Hydraulic Pin-Grabber	No	Yes	
	48082917	Coupler, B/C Series Universal Mechanical	Yes	Yes	

CX57C Compact Excavator

P/N	Kit Name	Notes
90444182	Telematics Ready DIA 4G	
48100303	Seat Belt, 3 INCH, DIA	
51447893	Quick Coupler Dia	

This table of field installed accessories is only intended to provide guidance on where field installed accessories are ordered. Dealers should reference the online PARTS catalog for each model for an up-to-date list of components, field kits and accessories. These kits are subject to change without notice. For pricing, availability and technical questions contact CNHi Parts.

Bid Term: 2/22/19 - 2/21/21; Extended to 2/21/22: EXtended to 2/21/23



(Ex Works Port of Entry) Standard Equipment

ENGINE:

Yanmar 4TNV98C

4 Cyl. water-cooled,

electronic common rail diesel

203 CID (3.319L)

Tier 4 Final

Glow plugs

Horsepower:

Gross 67.7 HP (48.3 kW)/2200

Net 63 HP (47 kW)/2200

Maximum Engine Torque:

173.7 lb ft (235.4 Nm) @ 1550 rpm

Dry type air cleaner

OPERATOR PROTECTIVE STRUCTURE:

Sound Levels:

ISO 6396:2008 sound pressure

level LpA=77bB (A)

ROPS/FOPS:

Enclosed cab with overhead

opening front window, sliding side

window, lockable door, heater,

defroster and air conditioner,

radio/USB player + 2 speakers

bluetooth with remote control and

5.7" color LCD display screen

Mechanical suspension seat, with

2" seat belt, and seat heater

Pilot operated joysticks for boom,

arm, bucket and swing with

adjustable wrist rests

Foot pedals for travel control and

swing tower control

Gauges: Engine coolant temperature,

hydraulic oil temperature,

and fuel level

Indicator Lights: Hydraulic oil temp,

air cleaner, engine stop, check

engine, water in fuel, battery

charging, emergency warning, low

fuel level, engine coolant

temperature, engine oil

pressure, DPF regeneration inhibit

warning and regeneration

acknowledge, DPF warning, and high

exhaust temperature

ELECTRICAL:

12 Volt electrical starting system

includes heavy-duty battery and

starting motor

60 Amp alternator

Battery master switch

Key start

Anti-theft-engine starting passwords

Dual 12V power plug recepticals

Front and rear working lights

Auto idle feature with on/off switch

Pre-wired telematics ready

BLADE:

Hydraulically controlled dozer blade

UNDERCARRIAGE:

Rubber tracks

Track pad width: 15" (380 mm)

Track length: 8'4" (2530 mm)

Gradeability: 35 degrees

Ground clearance: 1'3" (380 mm)

TRACK DRIVE:

Two speed travel

Fully hydrostatic drive system

Track tension adjustment

(grease type)

Sealed and lubricated track

HYDRAULICS:

Control pattern selector valve

Hydraulic oil filter

Total Auxiliary Flow:

24.2 gpm @ 3,191 psi

(91.6 L/min @ 220 bar)

Main Pump: 3,130 PSI

Auxiliary valves and piping

for independent one way aux and

two way aux circuits.

Proportional auxiliary hydraulic flow

control



(Ex Works Port of Entry) Standard Equipment

Large capacity hydraulic oil cooler
Cylinder rod protection covers
-Dozer & Boom

UPPER:
Standard Arm w/Thumb bracket:
4"10" (1.48 m)
Optional Long Arm w/Thumb bracket:
6'3" (1.9 m)
Boom: 9'6" (2.9 m)
Boom Swing: 70° left / 50° right
Short Tail Swing Radius
Swing brake: disc type, spring applied

and hydraulically released

Bucket linkage with lifting hook

MISCELLANEOUS:
Operating weight:
Cab, short arm - 12,940 lbs (5870 kg)
Cab, long arm with additional
counterweight - 13,760 lbs
(6090 kg)
All weights are with rubber tracks, no
quick coupler, bucket, fluids, full
of fuel, thumb bracket and 165lb
operator
Additional counterweight - 770 lbs
Warranty - Base warranty Coverage:
2-Year/3,000-Hour Full Machine
Limited Warranty



(Ex Works Port of Entry) Models

COMMERCIAL MODEL	Weight	Factory Data	List Price
CX60C CAB	12,940 LB		\$97,518.00

Packet	Description		Factory Data	List Price
CX60C Cab Lg Arm II		Weight		\$2201.00
SD_10181-CRAWLER TYPE	Rubber Tracks 400MM	7		
SD_30180-TRAVEL ALARM	Travel Alarm	1		
SD_40003-COUNTERWEIGHT	Additional Counterweight	7		
SD_X5405-2ND AUX. CIRCUIT	W/O 2nd Aux 2-Way Proportional	1		
SD_X5407-1ST AUX HYD CIRCUIT	2Way Aux Joystick Proportional	7		
SD_X5414-AUX WORKLIGHTS CAB	Working Lights	7		
SD_X6100-ARM	Arm Long w/Thumb Bracket			
SD_X6206-LINKAGE	Linkage With Hook	7		
SD_X6207-HYDR Q/C PROV.	W/O Q/C Provision	7		
SD_X6210-BEACON	LED Beacon	7		
SD_X9850-HYDRAULIC OIL	STD HYD OIL VG46	7		
SD_X9908-CAMERA	W/O Rear View Camera			
•				
CX60C Cab Sh Arm II				\$304.00
SD_10181-CRAWLER TYPE	Rubber Tracks 400MM			
SD_30180-TRAVEL ALARM	Travel Alarm			
SD_40003-COUNTERWEIGHT	Standard Counterweight.			
SD_X5405-2ND AUX. CIRCUIT	W/O 2nd Aux 2-Way Proportional			
SD_X5407-1ST AUX HYD CIRCUIT	2Way Aux Joystick Proportional			
SD_X5414-AUX WORKLIGHTS CAB	Working Lights			
SD_X6100-ARM	Arm Short w/Thumb Bracket			
SD_X6206-LINKAGE	Linkage With Hook			
SD_X6207-HYDR Q/C PROV.	W/O Q/C Provision			
SD_X6210-BEACON	LED Beacon			
SD_X9850-HYDRAULIC OIL	STD HYD OIL VG46			
SD_X9908-CAMERA	W/O Rear View Camera			
CX60C Lg Arm QC II				\$2842.00
SD_10181-CRAWLER TYPE	Rubber Tracks 400MM			
SD_30180-TRAVEL ALARM	Travel Alarm			
SD_40003-COUNTERWEIGHT	Additional Counterweight			
SD_X5405-2ND AUX. CIRCUIT	W/O 2nd Aux 2-Way Proportional			
SD_X5407-1ST AUX HYD CIRCUIT	2Way Aux Joystick Proportional			
SD_X5414-AUX WORKLIGHTS CAB	Working Lights			
SD_X6100-ARM	Arm Long w/Thumb Bracket			
SD_X6206-LINKAGE	Linkage With Hook			
SD_X6207-HYDR Q/C PROV.	HYD Q/C PROV 2 WAY			
SD_X6210-BEACON	LED Beacon			
SD_X9850-HYDRAULIC OIL	STD HYD OIL VG46	_		



(Ex Works Port of Entry)

Packet	Description	Weight	Factory Data	List Price
SD_X9908-CAMERA	W/O Rear View Camera			

Pre-Configured Packages are full model packages for Short Arm or Long Arm configurations. Once a package is selected, you can then select the required Buckets/Attachments to go along with your unit. Keep in mind, it is not possible to modify (add/remove) any other vehicle options when you select a Pre-Configured package. If a Pre-Configured unit is ordered, it will be matched to one that is already built and ready to ship, which will reduce the lead-time by several months. Independent Option ordering is still available if the package is not desired, however you may experience a longer lead-time.



(Ex Works Port of Entry)

Factory Supplied Options

Order Code Description Weight Factory Data List Price

OPERATOR'S MANUAL

SD_47181 OPERATOR'S MANUAL

	<u> </u>	=: · · · · · · · · · · · · · · · · · · ·		
	747480	Operators Manual - English		No Charge
	747464	Operators Manual- Spanish		No Charge
	747961	Operators Manual - French		No Charge

VERSION

SD_10181 CRAWLER TYPE

9552711	Rubber Tracks 400MM		No Charge
	One-piece molded rubber belt track with a steel cable core.		
	The entire track must be replaced at time of service. Select		
	this track for general use on soils and hard surfaces.		
9552710	Rubber Link Tracks 400MM		\$12,502.00
	Steel track chain with molded rubber grousers/shoes. These		
	are also called hybrid tracks or roadliner tracks. Each Grouser/		
	shoe has a steel core completely molded in rubber and can be		
	individually replaced since they are bolted to a steel chain.		
	This track will offer the stability of a steel track with the		
	surface protection of a rubber track pad.		
9552612	Steel w/Pads 400 MM		\$4,424.00
	Steel track chain with steel grousers/shoes and bolt on rubber		
	track pads. Each rubber track pad can be individually replaced		
	or removed independently from the steel grouser/shoe. Select		
	this option to gain traction on hard surfaces such as asphalt or		
	concrete and to help protect their surface finish with the		
	rubber track pads attached. All of the rubber track pads can be		
	removed to perform as an all steel track as desired.		
9552613	Steel w/Pad Hole 400MM		\$2,200.00
	Steel track chain with steel grousers/shoes that have holes		
	to accept bolt on rubber track pads. Select this track for		
	the most aggressive traction in soils and if there is no		
	concern for disrupting the appearance of ground conditions		
	such as grass, asphalt or concrete. For added traction on		
	hard surfaces such as asphalt or concrete and to help protect		
	their surface finish it is recommended to use bolt on rubber		
	track pads.		

CX60C COMPACT EXCAVATOR

	US PRICE LIST	
	(Ex Works Port of Entry)	
9552610	Steel Tracks 450 MM Steel track chain with steel grousers/shoes. Select this track for the most aggressive traction in soils and if there is no concern for disrupting the appearance of ground conditions such as grass, asphalt or concrete. This track is intended for use on soils, but can be used on hard surfaces as well.	\$2,320.00
ADDITIONAL EQ	LIIPMENT MEX	
	RAVEL ALARM	
747453	Travel Alarm	\$304.00
747994	W/O Travel Alarm	No Charge
SD 40003 C	OUNTERWEIGHT	
747084	Additional Counterweight CX60C - additional bolt-on weight that adds 770 lb (350 kg) Added CWT is standard on CX57C.	\$985.00
747995	Standard Counterweight.	No Charge
SD_X5202 T	RACK GUIDE 3-Piece Track Guide	No Charge
	3-piece track guides for steel tracks and steel tracks with bolt on rubber track pads only	
SD X5405 2	ND AUX. CIRCUIT	
747053	2nd Aux 2-Way Proportional	\$2,641.00
747999	W/O 2nd Aux 2-Way Proportional	No Charge
SD_X5407 1	ST AUX HYD CIRCUIT	
747122	2Way Aux Joystick Proportional	No Charge
SD_X5414 A	UX WORKLIGHTS CAB	
747235	LED CAB WORKLIGHTS	\$150.00
	Replaces Halogen Lights on the boom and cab with LED.	
SD_X6100 A	RM	
747078	Arm Short w/Thumb Bracket	No Charge
747079	Arm Long w/Thumb Bracket	\$912.00

Long arm increases dig depth, resulting in a reduction in arm digging forces & lift capacity. Please refer to the

Standard Pages for arm lengths.

SD_X6105 DOZER BLADE OPTION

747232 STD DOZER BLADE 747232

No Charge

747090

Rear View Camera

CX60C COMPACT EXCAVATOR US PRICE LIST

/E	\A/I	D1	- 6	F ()	
(Ex	Works	Port	of	Entry	١

	(Ex Works Port of Entry)	
747981	4-Way Angle Dozer Blade	\$4,300.00
	For CX60C: REQUIRES additional Counterweight 747084.	
	Added CWT is standard on CX57C. Includes bolt-on	
	reversible cutting edge.	
	NKAGE	
747062	Linkage With Hook	No Charge
747063	Linkage Without Hook	(\$140.00)
	YDR Q/C PROV.	
747065	W/O Q/C Provision	No Charge
747236	HYD Q/C PROV 2 WAY	\$641.00
	For CX60C: Recommended for use with additional	
	counterweight 747084. Added CW is standard on	
	CX57C.	
SD_X6210 BI	EACON	
747088	LED Beacon	No Charge
747087	W/O - Beacon	(\$47.00)
SD_X9908 C	AMERA	
747089	W/O Rear View Camera	No Charge

\$593.00



(Ex Works Port of Entry) Factory Supplied Attachments

Order Code	Description	Weight	Factory Data	List Price
Pin-On Buckets & 0	Counter			
48057625	12"HD Bucket (Pin-On & Mech/Hvd Coupler)	190 LB		\$931.00
48057626	18"HD Bucket (Pin-On & Mech/Hyd Coupler)	240 LB		\$1,001,00
48057627	24"HD Bucket (Pin-On & Mech/Hyd Coupler)	291 LB		\$1,143.00
48057628	36"HD Bucket (Pin-On & Mech/Hyd Coupler)	388 LB		\$1,407.00
48057629	36"Ditch Bucket (Pin-On & M/H Coupler)	313 LB		\$1,056.00
48057637	36"Cemetary Bucket (Pin-On& M/H Coupler)	305 LB		\$1,200.00
48057630	Coupler, Mechanical Pin-Grabber (Only compatible with the C-Series bucket) Includes 1 set of dead pins for installation into a single bucket	74 LB		\$1,545.00
48058014	Coupler, Hydraulic Pin-Grabber (Only compatible with the C-Series bucket)	63 LB	63 LB	
48082917	Coupler, B/C-Series Universal Mechanical (Compatible with both the B/C-Series buckets)	85 LB		\$824.00
48057631	PIN Required when ordering more than 1 bucket with a Pin- Grabber Coupler			\$209.00
48057639	Ripper Tooth Pin-On	220 LB		\$929.00
LAC Buckets & Co	pupler			
47422702	12"HD Bucket (KLAC Coupler)	220 LB		\$1,165.00
47422703	18"HD Bucket (KLAC Coupler)	256 LB		\$1,237.00
47422704	24"HD Bucket (KLAC Coupler)	309 LB		\$1,379.00
47422705	36"HD Bucket (KLAC Coupler)	408 LB		\$1,643.00
47422658	36"Ditch Bucket (KLAC Coupler)	315 LB		\$1,139.00
47872281	36"Cemetary Bucket (KLAC Coupler)	310 LB		\$1,200.00
48057636	Coupler, KLAC	55 LB		\$1,278.00
47422660	KLAC Base Plate (To adapt other buckets)	31 LB		\$348.00
47873455	ATTACHMENT, RIPPER TOOTH,	220 LB		\$929.00
humbs				·
48058021	Thumb Kit, Hyd.,Long Tines (Use with Mech. and Hyd. Pin-Grabber couplers)	250 LB		\$2,453.00
48059650	Thumb Kit, Hyd.,Short Tines (Use with Direct Fit and Klac buckets)	250 LB		\$2,453.00

	C-Series Mini Excavator BUCKET COMPATIBILITY				
Model	Order Code	Description	B-Series Buckets	C-Series Buckets	
CX17C	48057609	Coupler, Mechanical Pin-Grabber	No	Yes	
CX26C/CX30C	48057615	Coupler, Mechanical Pin-Grabber	No	Yes	
	48094307	Coupler, Hydraulic Pin-Grabber	Yes (requires removal of spacer plates)	Yes	
CX37C	48057623	Coupler, Mechanical Pin-Grabber	Yes	Yes	
	48058013	Coupler, Hydraulic Pin-Grabber	Yes	Yes	
CX57C/CX60C	48057630	Coupler, Mechanical Pin-Grabber	No	Yes	
	48058014	Coupler, Hydraulic Pin-Grabber	No	Yes	
	48082917	Coupler, B/C Series Universal Mechanical	Yes	Yes	