

Current Date 02Jan2019

204L FOUR WHEEL DRIVE LOADER

204L Standard Equipment

ENGINE: Yanmar 4TNV98 61 SAE Net Horsepower (45 kW) **Isolation Mounted** Meets EPA Final Tier 4 and EU Stage IIIB **Emissions** Engine Coolant -34 Degree

(-37 Degree C) Air Intake Pre Heater Coolant Recovery Tank Belt Driven Cooling Fan Spin-On Engine Oil and Fuel Filters Oil-to-Water Engine Oil Cooler Dual Safety Element Dry-Type Air Cleaner with Dust **Evacuator Valve and** Muffler, Under Hood, with Angled exhaust Stack and Diffuser

(Conforms to SAE J1308)

Enclosed Safety Fan Guard

ELECTRICAL:

12 Volt System 80 Amp Sealed Alternator (1) Battery 850 CCA, 80 Minutes Rated Reserve Capacity Master Electrical Disconnect

Switch

Blade-Type Multi-Fused Circuits battery load center bolt down main fuses Sealed External Electrical Connections Electrical Load Center In Operator Station Positive Terminal Battery Lights (Conforms to SAE J99):

Hydraulic Test Ports

AXLES: **Heavy-Duty Outboard** Planetary Final Drives Limited Slip Differential 45% Front Differential and 45% Rear Standard Differential

BRAKES: Service Brakes; Hydraulically Actuated, Self-Adjusting internal Wet Disc Brake and

Driveline Drum Brake Park Brake; Automatic Spring-Applied, Hydraulic-Released internal Wet Disc Brake

STEERING:

Hydraulic Power Steer: 40 Degrees Articulation

HYDRAULIC SYSTEM: 18 GPM (70 L/Min) Engine Mounted Gear Pump - Open

Center control valve Combined Hydrostatic/Hydraulic Oil Reservoir Sight Glass

OPERATOR'S STATION: Modular Design ROPS/FOPS Canopy/Cab, **Isolation Mounted** (Conforms to SAE J1040, J231, ISO 3471,ISO 3449) Steel Roof Left Side Access Slip-Resistant Steps and Ergonomically Located Handholds (Conforms to SAE J185)

Engine Coolant Engine Air Filter Temperature Hydraulic Oil Temperature Oil Temperature Fuel Gauge (Fuel Gauge Only - No Audible Alarm) Hourmeter Indicator Lights: Park Brake Actuated Forward-Reverse Travel I or II Speed Range Turn Signal and Hazard Lights High Beam Indicator Battery Voltage Floormat Horn, Electric (Conforms to

SAE J994, J1446)

Key Start Switch with Electric Fuel Shut-Off Power Port Interior Mounted Rearview Convex Mirror (Conforms to

SAE J985)

(2) Exterior Convex Mirrors

(Conforms to SAE J985) Built-In Operators Manual Storage Compartment Pre-wired for Beacon Cab includes Radio Speakers and Antenna

LOADER:

Hydraulic powered Attachment Coupler Z-Bar Linkage Boom Float Return to Dig Feature (visual indicator) Loader Boom Service Lock (Conforms to SAE J38)

OVERALL VEHICLE:

Tilt Steering Console (Cab

(2) Driving/(2) FrontWorking Halogen Lights(2) Front and (2) RearTurn/Flashing(2) Rear Stop Lights(2) Rear Reflectors

TRANSMISSION:
Joystick FNR (Forward
Neutral
Reverse) Control with
Electrohydraulic Third
Function Control on Joystick
Hydrostatic Transmission
with
2 Speed ranges:
Infinite Speed Control
Inching Pedal
Vertical Element, HST

Charge Pressure Filter

Oil-to-Air Cooler for

Transmission

with Bypass to Reservoir

option Only) Steering Wheel with Spinner Seat, Deluxe Deep Foam, Fabric, (Cab Option) Mechanical Suspension for Weight/ Height, Fore-Aft Adjustment, Backrest Tilts and Adjustable Arm Rests Seat, Deluxe Deep Foam, Vinyl, (Canopy Option) Mechanical Suspension for Weight/ Height, Fore-Aft Adjustment, Backrest Tilts and Adjustable Arm Rests

2 In. (51 mm) Seat Belt with Retractor (Conforms to SAE J386) Electronic Monitor System with Audible and Visual Warning:

Engine Oil Pressure

Articulation Locking Pin (Conforms to SAE J276) Oscillating Frame Articulation System Front and Rear Fenders Integral Loader Frame Lift and Engine Frame Lift Eyes and Tie Down Eyes Full Counterweight Drawbar with Pin Rear Bottom Guard Environmental Fluid Drains

Vandal Protection Locking for:
Engine Enclosure (Fuel Fill inside Engine Compartment)
Operator Enclosure
Rear Engine Access Door 13.2 Gallon (50 L) Fuel Tank
Reverse Warning Alarm (Conforms to SAE J994, J1446)

Required - You must select one from each category

BASE MACHINE

F.O.B. Baltimore, Maryland

Description Code Price 204L FOUR WHEEL DRIVE LOADER 0ADOT \$72,929.00

OPERATOR'S STATION

Description Code Price
Canopy 8419 No Added Cost

Includes fixed steering column, floormat, locking storage compartment, two front and two rear work lights, vinyl mechanical suspension seat with 2 in. (51mm) seat belt with retractors (conforms to SAE J386), one interior rear view convex mirror, two exterior convex mirrors.

Cab with Heater & Air Conditioner 8422 \$11,654.00

Fresh air heater, defroster, and pressurizer
Headliner, floor mat, and insulated floor
Tinted safety glass, front and rear
Intermittent front and rear wipers and washers
Fabric mechanical suspension seat with 2 in. (51mm) seat belt with retractors (conforms to SAE J386)
One interior rear view convex mirror
Two exterior convex mirrors
Integral front sun visor

ENGINE

	Description	Code	Price
	Engine	0924	\$3,879.00
	Yanmar 4TNV98 meets EPA FT4 and EU Stage IIIB Emissions Automatic Glow Plug Starter Protection		
	Automatic Derating for Exceeded System Temperatures Electronically Controlled Fuel Delivery System Under Hood Dual Element Air Cleaner with Restriction Indicator Dual-Stage Fuel Filter and Water Separator 500 Hour Spin-on Oil Filter		
~	RIDE CONTROL		
	Description	Code	Price
	Less Ride Control	3000	No Added Cost
_	Ride Control	3010	\$1,990.00
~	WHEELS AND TIRES		
	Description	Code	Price
	405/70R18 Firestone Duraforce	4020	\$5,149.00
	This tire option gives total machine height of 8 ft 1 inch (2468 mm) for cab option and total machine height of 8 ft (2444 mm) for the canopy option.		
	Mitas EM01	4025	\$3,960.00
	365/70R18 This tire option gives total machine height of 8 ft (2445 mm) for cab option and total machine height of 7 ft 11 inches (2421 mm) for the canopy option.		
_	400/70R20 Michelin XMCL	4030	\$6,181.00
	This tire option gives total machine height of 8 ft 2 inches (2488 mm) for cab option and total machine height of 8 ft 1 inch (2464 mm) for the canopy option.		
~	WORK LIGHTS		
	Description	Code	Price
	Halogen Work Lights	7110	No Added Cost
	Canopy 2x Front, 2x Rear Halogen WorkLights		
	Halogen Work Lights - Cab	7120	No Added Cost
	2x Front, 2x Rear Halogen WorkLights		
~	BUCKETS AND COUPLERS		
	Description	Code	Price
	Less Coupler / Coupler Ready	8545	No Added Cost
	Dealer must order and install AT412608 Integrated Skid Steer Compatible Quik Tatch Coupler or AT452289 ISO Integrated Coupler. Must also order a bucket if desired.		

iei i-z	1-19 NJ State Approved Co-op #o3MCESCCPS		
~	SPEED CONTROL		
	Description	Code	Price
	Creep/Speed Control	9300	\$2,096.00
_	Only available with Cab Option Code 8422		
~	DEALER-INSTALLED KITS		
	Description	Code	Price
	Buckets Couplers & Forks		
_	1.0 cu. yd. (0.8 cu. m.) General Purpose Bucket with Skid Shoes and Bolt-on Cutting Edge for Quik Tatch	AT413236	\$1,888.00
	74.8 in. (1.90 m) overall width Includes 2 built-in lift loops		
_	1.4 cu. yd. (1.1 cu. m.) General Purpose Bucket with Skid Shoes and Bolt-On Cutting Edge for Quik Tatch	AT413237	\$2,880.00
	86.6 in. (2.2 m) overall width Includes 2 built-in lift loops		
	Class 3 Fork Frame with 48 Fork Tines for Quik Tatch Coupler	BYT10083	\$2,243.00
	Pallet Fork Frame Kit, 48" Forks Class ITA 3B Fork Frame Frame Width 60 in. (1.5m) Tines, 4-3/4 in. x 2in x 48in (120mm x 50mm x 1220mm) Overall Length Fork Frame + Forks: 57in (1445mm)		
	Class 3 Fork Frame with 60 Fork Tines for Quik Tatch Coupler	BYT10092	\$2,461.00
	Pallet Fork Frame Kit, 60" Forks Class ITA 3B Fork Frame Frame Width 60 in. (1.5m) Tines, 4-1/2 in. x 2in x 60in (116mm x 50mm x 1524mm) Overall Length Fork Frame + Forks: 69in (1750mm)		
	ISO Coupler Kit 204L/304L	AT452289	\$1,655.00
_	Skid Steer Compatible Quik Tatch Coupler	AT412608	\$848.00
	Kits & Accessories		
	Block Heater Kit	AT427686	\$112.00
	<u>Kits & Accessories</u>		
	Beacon Light	AT438075	\$493.00
	For use with Cab code 8422		
	Beacon Light	AT443300	\$493.00

\$2,630.00

AT438074

Creep Control Kit

For use with Canopy code 8419.

For use with Cab code 8422

LED Worklight Kit (Flood)	BYT10523	\$189.00
LED Worklight Kit (Spot)	BYT10522	\$189.00
Ride Control	BYT10052	\$1,790.00
Skid Steer Quik Tatch Coupler Cover	BYT10470	\$127.00
Vandal Kit	AT438076	\$384.00
For use with Canopy code 8419. Includes 2 covers; 1 for guage, 1 for switches.		
<u>Miscellaneous</u>		
Electrical Attachment Control Kit	AT390659	\$512.00
Provides both 3 pin and 14 pin connectors and a control box.		

Copyright $\ensuremath{\mathbb{C}}$ Deere & Company. All Rights Reserved.

About Our Site | Privacy and Data | Legal | |