

Current Date 02Jan2019

244L- FOUR WHEEL DRIVE LOADER

ENGINE:

Yanmar 4TNV98CT

70 SAE Net Horsepower (52

Isolation Mounted

Turbocharged

Glow Plugs

Engine Coolant -34 Degree

F (-37 Degree C)

Coolant Recovery Tank

Proportional Speed

Hydraulic Driven Cooling

Fan

Spin-On Engine Oil and Fuel

Filters

Oil-to-Water Engine Oil

Cooler

Dual Safety Element Dry-

Type Air Cleaner with Dust

Evacuator Valve and

Pre-Screener

Muffler, Under Hood, with

Exhaust Stack

Enclosed Safety Fan Guard (Conforms to SAE J1308)

ELECTRICAL:

12 Volt System 80 Amp Sealed Alternator

(1) Battery totaling 925

CCA

Master Electrical Disconnect

Switch

Blade-Type Multi-Fused

Sealed External Electrical

Connections

Electrical Load Center In

Operator Station

Bypass Start Safety Cover

on Starter

Positive Terminal Battery

Covers

Lights (Conforms to SAE

J99):

(2) Driving/(2) Front

Working Halogen Lights

(2) Front and (2) Rear

Turn/Flashing

(2) Rear Stop Lights

(2) Rear Reflectors

BRAKES:

Service Brakes;

Hydraulically

Actuated, Self Adjusting

internal Wet Disc Brake and

Driveline Drum Brake Park Brake; Automatic

Spring-Applied,

Hydraulic-Released

internal Wet Disc Brake

STEERING:

Hydraulic Stereo Steer:

56 Degrees Articulation (28

Degrees in Each Direction) Plus an Additional 26

Degree

Rear Wheel Steer

HYDRAULIC SYSTEM:

17 GPM (65 L/Min) Engine

Mounted Gear Pump - Open

Center

Combined

Hydrostatic/Hydraulic

Oil Reservoir Sight Glass

OPERATOR'S STATION:

Modular Design ROPS/FOPS

heat and air conditioning

standard.

Isolation Mounted

(Conforms

to SAE J1040, J231, ISO

3471, ISO 3449)

Steel Roof

Left and Right Side Access

Walk Through Cab

Slip-Resistant Steps and

Ergonomically Located

Handholds (Conforms to

SAE J185)

3-Way Tilt and telescopic

Steering Console

Steering Wheel with

Spinner

I or II Speed Range Turn Signal and Hazard

Lights

High Beam Indicator

Hourmeter Speedometer Fuel Gauge

Floormat

Horn, Electric (Conforms to

SAE J994, J1446) Key Start Switch with Electric Fuel Shut-Off

Power Port

Interior Mounted Rearview

Convex Mirror (Conforms to

SAE J985)

(2) Exterior Convex Mirrors

(Conforms to SAE J985) Built-In Operator's Manual Storage Compartment

Pre-wired for Beacon and

Radio Cab includes Radio

Speakers and Antenna

LOADER:

Powered Attachment

Coupler

Z-Bar Linkage

Three Function Hydraulics,

with Joystick Pilot Control

for Boom and

Bucket and 3rd function

electrohydraulic mini joystick built in

Boom Float

Return to Dig Feature

Loader Boom Service Lock

(Conforms to SAE J38)

OVERALL VEHICLE:

Articulation Locking Pin

(Conforms to SAE J276) Oscillating Frame

Articulation System Front and Rear Fenders

Integral Loader Frame Lift & Tie Down Eyes

Integral Engine Frame Lift

Bid Term: 2/20/19 - 2/19/21

(2) Rear Work Lights

TRANSMISSION:
Single Lever Shift Control,
F-N-R and 2 Speed
automatic gear box
Hydrostatic Transmission
with Infinite Speed Control
Inching Pedal
Vertical Filter Element

AXLES:

Heavy-Duty Outboard
Planetary Final Drives
100% Manual (Push
Button)
Locking Front Differential
and Rear Standard
Differential
Grease Bank for Oscillating
Rear Axle

Seat, Deluxe Deep Foam, Fabric, Mechanical Suspension for Weight/ Height, Fore-Aft Adjustment, Backrest Tilts and Adjustable Arm Rests 2 In. (51 mm) Seat Belt Retractor (Conforms to SAE J386) Electronic Monitor System with Audible and Visual Warning: Engine Oil Pressure Engine Coolant Temperature **HST Transmission** Oil Temperature Indicator Lights: Engine Air Filter Park Brake Actuated Forward-Reverse Travel

& Tie Down Eyes Full Counterweight Drawbar with Pin Rear Bottom Guard **Environmental Fluid Drains** Vandal Protection Locking For: **Engine Enclosure** Operator Enclosure Rear Engine Access Door Fuel Fill 21.5 Gallon (80 L) Fuel Tank Reverse Warning Alarm (Conforms to SAE J994, J1446) Contact DMAC for Foam Filled or Solid Tire **Applications**

Required - You must select one from each category

BASE MACHINE

F.O.B. Baltimore, Maryland

Engine

	Description	Code	Price
	244L- FOUR WHEEL DRIVE LOADER	OAFOT	\$91,731.00
~	SEAT		
	Description	Code	Price
	Standard Cloth Seat, Mid-Back, Mechanical Suspension	2210	No Added Cost
_	Deluxe Cloth Seat, Air Suspension, High-Back with Headrest, Heated, and Lumbar	2230	\$2,250.00
_	CONTROLS		
	Description	Code	Price
	Standard Control Package	2410	No Added Cost
	Includes Rimpull Control and Inching Pedal.		
	Attachment Assist (Creep Control & Throttle Lock)	2430	\$2,049.00
_	Includes Rimpull Control and Inching Pedal.		
_	ENGINE		
	Description	Code	Price

Yanmar 4TNV98CT meets EPA FT4 and EU Stage IIIB Emissions Turbo Charged

\$4,426.00

0924

Automatic Glow Plug Starter Protection Automatic Derating for Exceeded System Temperatures Electronically Controlled Fuel Delivery System Under Hood Dual Element Air Cleaner with Restriction Indicator Dual-Stage Fuel Filter and Water Separator 500 Hour Spin-on Oil Filter

HIDK	AULIC SYSTEM AND COUPLER		
	Description There Secretion Association (SNR Control	Code	Price
	Three Function, Joystick w/FNR Control	2840	No Added Cos
	1 lever controls boom and bucket, mini-EH thumb joystick proportionally controls auxiliary function. Includes third function lines to the coupler.		
	Three Function w/High Flow Option, Joystick w/FNR Control	2842	\$4,281.00
	1 lever controls boom and bucket, mini-EH thumb joystick proportionally controls auxiliary function. Includes third function lines to the coupler. Includes third function detent.		
RIDI	E CONTROL		
	Description	Code	Price
	Less Ride Control	3000	No Added Cos
	Ride Control	3010	\$2,289.00
WHE	ELS AND TIRES		
	Description	Code	Price
	405/70R18 Firestone Duraforce	4020	\$5,372.00
	This tire option gives total machine height of 9 ft (2743 mm)		
	Mitas EM01	4025	\$4,010.00
	365/70R18 This tire option gives total machine height of 8 ft 11 in (2472 mm)		
	400/70R20 Michelin XMCL	4030	\$6,481.00
	This tire option gives total machine height of 9 ft 1 in (2774 mm)		
	400/70R20 Michelin Bibload L3	4035	\$6,481.00
	This tire option gives total machine height of 9 ft 1 in (2768 mm)		
WO	RK LIGHTS		
	Description	Code	Price
	Halogen Work Lights - Cab	7120	\$250.00
	2x Front, 2x Rear Halogen WorkLights		
	Less Work Lights (LED Kit Ready)	7140	No Added Cos
	Dealer will need to order and install BYT10522 (2xspot) and/or BYT10523 (2xflood)		

BUCKETS AND COUPLERS

Description	Code	Price
Less Coupler / Coupler Ready	8545	No Added Cost
Dealer must order and install AT412608 Integrated Skid Steer Compatible Quik Tatch Coupler or AT452288 ISO Integrated Coupler. Must also order a bucket if desired.		
Less Bucket	8550	\$1,685.00
ISO Coupler included.		
1.0 cu. yd. (0.8 cu. m.) General Purpose Bucket with Skid Shoes and Bolt-on Cutting Edge for ISO Coupler	8555	\$3,674.00
74.8 in. (1.90 m) overall width. Includes 2 built-in lift loops.		
1.4 cu. yd. (1.1 cu. m.) General Purpose Bucket with Skid Shoes and Bolt-on Cutting Edge for ISO Coupler	8560	\$4,776.00
86.6 in. (2.2 m) overall width. Includes 2 built-in lift loops.		
2.1 cu. yd. (1.6 cu. m.) Light Material Bucket with Skid Shoes and Bolt-on Cutting Edge for ISO Coupler	8565	\$5,731.00
94.5 in. (2.4 m) overall width. Includes 2 built-in lift loops. Includes Dump Control Valve Kit, AT320957.		
ional - Select as desired		
OTHER WORK TOOLS		
Description	Code	Price
Pallet Forks for Standard ISO Coupler	9200	\$1,731.00
Frame width 48 in. (~1200 mm) Tines, 4 in. x 1.8 in. x 48 in. (100 x 45 x 1200 mm)		
Front Windshield Guard	9420	\$2,147.00
Long Lead Time Item.		
DEALER-INSTALLED KITS		
Description	Code	Price
	Code	Price
Description	Code AT316647	
Description <u>Buckets & Pallet Forks</u> 1.0 cu. yd. (0.8 cu. m.) General Purpose Bucket with		
Description Buckets & Pallet Forks 1.0 cu. yd. (0.8 cu. m.) General Purpose Bucket with Skid Shoes and Bolt-on Cutting Edge for ISO Coupler * 74.8 in. (1.90 m) overall width		
Description Buckets & Pallet Forks 1.0 cu. yd. (0.8 cu. m.) General Purpose Bucket with Skid Shoes and Bolt-on Cutting Edge for ISO Coupler * 74.8 in. (1.90 m) overall width * Includes 2 built-in lift loops 1.4 cu. yd. (1.1 cu. m.) General Purpose Bucket with	AT316647	7 \$1,909.00

2.1 cu. yd. (1.6 cu. m.) Light Material Bucket with Skid Shoes and Bolt-on Cutting Edge for ISO Coupler
94.5 in. (2.4 m) overall width

94.5 in. (2.4 m) overall width Includes 2 built-in lift loops Requires Dump Control Valve Kit, AT370530		
Pallet Forks for ISO Coupler	AT321215	\$2,009.00
Class ITA 2B fork frame Frame width 49 in. (1.2 m) Tines, 4 in. x 1.8 in. x 48 in. (100 x 45 x 1200 mm)		
Buckets Couplers & Forks		
1.0 cu. yd. (0.8 cu. m.) General Purpose Bucket with Skid Shoes and Bolt-on Cutting Edge for Quik Tatch	AT413236	\$1,888.00
74.8 in. (1.90 m) overall width Includes 2 built-in lift loops		
1.4 cu. yd. (1.1 cu. m.) General Purpose Bucket with Skid Shoes and Bolt-On Cutting Edge for Quik Tatch	AT413237	\$2,880.00
86.6 in. (2.2 m) overall width Includes 2 built-in lift loops		
Class 3 Fork Frame with 48 Fork Tines for Quik Tatch Coupler	BYT10083	\$2,243.00
Pallet Fork Frame Kit, 48" Forks Class ITA 3B Fork Frame Frame Width 60 in. (1.5m) Tines, 4-3/4 in. x 2in x 48in (120mm x 50mm x 1220mm) Overall Length Fork Frame + Forks: 57in (1445mm)		
Class 3 Fork Frame with 60 Fork Tines for Quik Tatch Coupler	BYT10092	\$2,461.00
Pallet Fork Frame Kit, 60" Forks Class ITA 3B Fork Frame Frame Width 60 in. (1.5m) Tines, 4-1/2 in. x 2in x 60in (116mm x 50mm x 1524mm) Overall Length Fork Frame + Forks: 69in (1750mm)		
ISO Coupler Kit 244L/324L	AT452288	\$2,705.00
Skid Steer Compatible Quik Tatch Coupler	AT412608	\$848.00
Kits & Accessories		
Air Intake Pre-cleaner Kit	AT337325	\$176.00
Beacon Light	LW9069320	\$199.00
ISO Adapter to Quik Tatch Coupler	AT357576	\$1,584.00
Adapter for ISO Coupler to use Skid Steer Attachments		
Kits & Accessories		
Block Heater Kit	AT427686	\$112.00
<u>Kits & Accessories</u>		
LED Worklight Kit (Flood)	BYT10523	\$189.00

LED Worklight Kit (Spot)	BYT10522	\$189.00
Skid Steer Quik Tatch Coupler Cover	BYT10470	\$127.00
<u>Miscellaneous</u>		
3 in. Retractable Seat Belt	AT171619	View Price
<u>Miscellaneous</u>		
Electrical Attachment Control Kit	AT390659	\$512.00
Provides both 3 pin and 14 pin connectors and a control box.		

Copyright © Deere & Company. All Rights Reserved.

About Our Site | Privacy and Data | Legal | |