299D2

299D2 COMPACT TRACK LOADER SANFORD, NC, USA

Ship Weight lbs LIST PRICE AT DEALER

Standard Equipment:

POWERTRAIN

Cat C3.8 turbo aftercooled diesel engine -Gross horsepower per SAE J1349 98 hp (73 kW) @ 2400 RPM

- -EPA Tier 4 Final and EU Stage IV certified with aftertreatment
- -Electric fuel priming pump
- -Air inlet heater starting aid
- -Liquid cooled, direct injection

Air cleaner, dual element, radial seal S-O-S sampling valve, hydraulic oil

Filter, cartridge type, hydraulic

Filters, cartridge type, nydrau:

Filters, cartridge type, fuel

and water separator Radiator/hydraulic oil

cooler (side-by-side)

Spring applied, hydraulically released,

wet multi disc parking brakes

Hydrostatic transmission

UNDERCARRIAGE

Steel embed rubber track 15.7 in (400mm) Dual flange front idler Single flange rear idler Suspension - independent torsion axle(4) Two speed motor

HYDRAULICS

Standard flow auxiliary hydraulics with continuous flow CONTROLS:

Electro/hydraulic implement control Electro/hydraulic hydrostatic

transmission control

Speed sensor guarding

ELECTRICAL

12 volt electrical system 100 ampere alternator Ignition key start / stop / aux switch Lights:

- -Gauge backlighting
- -Two rear tail lights
- -Dome light

Backup alarm

Electrical outlet, beacon

OPERATOR ENVIRONMENT

Operator warning system indicators:

- -Air filter restriction
- -Alternator output
- -Armrest raised / operator out of seat
- -Engine coolant temperature
- -Engine oil pressure
- -Air inlet heater activation

- -Hydraulic filter restriction
- -Hydraulic oil temperature
- -Park brake engages
- -Engine emission system

Gauges: DEF level, fuel level,

hour meter and tachometer

Storage compartment with netting

Adjustable vinyl seat

Ergonomic contoured armrest

Adjustable joystick controls

Control interlock system, when operator

leaves seat or armrest raised:

- -Hydraulic system disables
- -Hydrostatic transmission disables
- -Parking brake engages

ROPS Cab, open, tilt up

FOPS, Level I

Anti-theft security system with 50 user

code capability

Top and rear windows

Floormat

Interior rear view mirror

12V electric socket

Horn

Hand (dial) & throttle electronic

FRAMES

Lift linkage, vertical path Chassis, one piece welded

Machine tie down points (4)

Belly pan cleanout

Support, lift arm

Cast rear bumper

Ventilated rear door with integrated

sealing

OTHER STANDARD EQUIPMENT

Engine enclosure - lockable

Extended life antifreeze (-37C, -34F)

Coupler, mechanical

Hydraulic oil level sight gauge

Radiator coolant level sight gauge

Radiator expansion bottle

Cat tough guard hose

Heavy duty flat faced quick disconnects

with integrated pressure release

Split d-ring to route work tool hoses

along side of left lift arm

Variable speed hydraulic cooling fan

Per SAE J818-2007 and EN 474-3:2006 and

ISO 14397-1:2007

Rated operating capacity:

At 50% Tipping Load - 4600 lb (2087 kg)

At 35% Tipping Load - 3200 lb (1451 kg)

CATERPILLAR MACHINE PRICE LIST

299D2

299D2 COM SANFORD, I	IPACT TRACK LOADER NC, USA	Ship Weight Ibs	LIST PRICE AT DEALER
	eserved for the Base Order Management Program Lane 2 when placing orders that are part of the Base Order nt program		
570-1813	299D2 CTL DCA1A	RITY CODE L2 RITY CODE L2	\$86,820
	NOTE: Please refer to the Lane 1 section to complete your ord	er.	
570-1814	LANE 1 - AVAILABLE FROM SANFORD PDC LANE 2 - AVAILABLE FROM SANFORD FACTORY USING PRIOF LANE 3 - AVAILABLE FROM SANFORD FACTORY USING PRIOF INCLUDES: 435-8999 299D2 COMPACT TRACK LOADER 421-0340 CONVERSION ARRANGEMENT 563-1163 CERTIFICATION ARR, P65 435-9050 PACKAGE, PERFORMANCE, (H2) 485-0411 CONTROL, ISO, PROP 435-8895 RIDE CONTROL, NONE 435-9153 ROPS, ENCLOSED WITH A/C (C3) 345-6359 SEAT,AIR SUSPENSION,CLOTH,HEAT 345-6240 DOOR, CAB, GLASS 345-6180 RADIO, AM/FM, BLUETOOTH 465-3705 DISPLAY, ADVANCED, LCD, CAMERA 454-6061 RUBBER BELT, 2 SPD, TF IDLERS 441-4811 BATTERY, HVY DUTY, DISC 258-4095 SEAT BELT, 2" 457-3167 FAN, HYDRAULIC, DEMAND 515-8592 QUICK COUPLER, HYDRAULIC	RITY CODE L2	\$92,940

NOTE: Please refer to the Lane 1 section to complete your order.

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY

299D2

299D2 COM SANFORD, N		o Weight os	LIST PRICE AT DEALER
522-7493	299D2 CTL DCA3	CODE L2	\$96,960
	INCLUDES: 435-8999 299D2 COMPACT TRACK LOADER 421-0340 CONVERSION ARRANGEMENT 563-1163 CERTIFICATION ARR, P65 435-8909 PACKAGE, PERFORMANCE, (H3) 485-0417 CONTROL, ISO, PROP, WT 454-6061 RUBBER BELT, 2 SPD, TF IDLERS 435-8895 RIDE CONTROL, NONE 435-9153 ROPS, ENCLOSED WITH A/C (C3) 345-6359 SEAT,AIR SUSPENSION,CLOTH,HEAT 345-6260 DOOR, CAB, POLYCARBONATE 345-6175 RADIO READY 465-3705 DISPLAY, ADVANCED, LCD, CAMERA 441-4810 BATTERY, XTRA HVY DUTY, DISC 258-4095 SEAT BELT, 2" 457-3167 FAN, HYDRAULIC, DEMAND 345-3556 HEATER, ENGINE COOLANT, 120V 515-8592 QUICK COUPLER, HYDRAULIC 495-1672 LIGHTS, HALOGEN		
	NOTE: Please refer to the Lane 1 section to complete your order.		
435-8999	299D2 COMPACT TRACK LOADER		\$87,930
0P-3620	299D2 MISC MATERIAL	OPS	NC

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY

299D2

USE	REF NO.	LANE 1	Ship Weight lbs	LIST PRICE AT DEALER
LAI	NE 1 AM-NO	RTH MANDATORY ATTACHMENTS		
(ML	JST CHOOSE	ONE FROM EACH CATEGORY)		
	LANE SELEC	TION		
YO	U MUST SELE	CT THIS REFERENCE WHEN ORDERING FROM THE	PDC.	
	0P-9001	LANE 1 ORDER	0	NC
	WARNING D	ECALS		
L	435-8842	INSTRUCTIONS, ANSI, USA		NC
L	435-8846		0	NC
	FILM GROUP	SELF LEVEL		
L	435-9238	FILM, SELF LEVEL, ANSI	0	NC
L	435-9239	FILM, SELF LEVEL, ISO	0	NC
	TRACKS			
L	454-6079	TRACK,RUBBER,450MM(17.7 IN)BAR		\$725
L	389-7672	TRACK,RUBBER,450MM(17.7IN)BLCK		\$665
	PRODUCT LI	NK .		
L	441-4818	PRODUCT LINK, CELLULAR PL240	age including lular networks Product Link's	NC

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY

299D2

USE	REF NO.	LANE 1	Ship Weight lbs	LIST PRICE AT DEALER
LANE	1 AM-NOI	RTH MANDATORY ATTACHMENTS (CONT.)	
PR	ODUCT LI	NK (Cont.)		
L	515-3153	PRODUCT LINK, CELLULAR PL240	orks to transmit Link's remote	NC
SE	RVICE INS	TRUCTIONS		
	421-8926	SERIALIZED TECHNICAL MEDIA KIT The technical media kit will include the Operations & Manual (OMM) and other media specified on the Fact List required to ship products from the manufacturismay contain multiple Operation & Maintenance Manufacturismay contain multiple Operation. Contents will vary. Any additional media or translations not included in be ordered through publications.cat.com	& Maintenance ctory Notification ng facility. Kit nuals (OMM) based on	NC
PA	CKING			
	0P-1176	CAROLINA CDC AVAILABILITY		\$1 NET
PR	ΟΤΕСΤΙΟΛ	1		
	0P-2266	SHIPPING/STORAGE PROTECTION	protection	\$207 NEI

If desired, this product can be power washed with warm soapy water prior to shipment to the customer.

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY

299D2

JSE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight Ibs	LIST PRIC
ANE	SELECTIO	N		
	0P-9002	LANE 2 ORDER	0 ment (BOM) program.	NC
	0P-9003	LANE 3 ORDER	0	NC
REGI	ONAL PAC	KAGES		
C	ONVERSIO	N ARRANGEMENTS		
	421-0340	CONVERSION ARRANGEMENTFOR USE WITH: ADSD-N, APD	0	NC
C	ERTIFICATI	ON ARRANGEMENTS/YEAR OF MANUFACT	URE	
	563-1163	CERTIFICATION ARR, P65	0	NC
	522-2549	REQUIRED for US CERTIFICATION ARR, (US/CANADA)		NC
	520-6568	Will be included in DCAs built before August 1, 2018 CERTIFICATION ARR, (CE)	ty, Stage II Sound	NC
W	ARNING D	ECALS		
	435-8842	INSTRUCTIONS, ANSI, USA		NC
ERF	ORMANCE	PACKAGES		
H	YDRAULIC	PERFORMANCE PACKAGES		
	435-8908	PACKAGE, PERFORMANCE, (H1)	0	NC
	435-9050	Self Level, None Hydraulic Controls - Standard Flow (Must select or PACKAGE, PERFORMANCE, (H2)		\$905
-	435-8909	Dual Self Level Hydraulic Controls - Standard Flow (Must select or PACKAGE, PERFORMANCE, (H3)		\$4,525
		High Flow XPS - 32 gpm (120 lpm) Dual Self Level Hydraulic Controls - High Flow (Must select one be	elow)	
FI	LM GROUP	SELF LEVEL		
	435-9238	FILM, SELF LEVEL, ANSI		NC

299D2

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
PERF	ORMANCE	PACKAGES (CONT.)		
Н	YDRAULIC	CONTROLS		
Stand	dard Flow (F0	OR USE WITH H1 & H2)		
L	485-0410	CONTROL, ISO, ON/OFF		\$226
L	485-0411	CONTROL, ISO, PROP	rols (4 button	\$435
L	485-0418	pedal functionality CONTROL, ISO, PROP, WT Cannot be used with H3. Provides ISO joystick control left hand joystick) and electronic foot throttle pedal way pedal functionality. Also includes 14 pin Work Tool of harness.	rols (4 button vith decel	\$775
High	Flow (FOR U	SE WITH H3 ONLY)		
L	485-0417	CONTROL, ISO, PROP, WT	s (4 button hand joystick)	\$880
P	OWERTRAII Select One	V		
L	435-8895	RIDE CONTROL, NONE	0	NC
L	435-8896	RIDE CONTROL	0	\$1,045
FI	ILM GROUP	RIDE CONTROL		
L	422-3445	FILM, RIDE CONTROL, ANSI	0	NC

Supersedes 02JAN2018
Caterpillar: Confidential Green
US-A-19-01 A

Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY

299D2

JSE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
EAT	URE PACK	AGES		
C	OMFORT PA	ACKAGES		
	435-9150	ROPS, OPEN (CO)	e:	NC
-	435-9151	Headliner, None ROPS, OPEN (C1) All of the following are included in this packag Deluxe Headliner & rear post trim covers Cup Holder	0	\$438
	435-9152	Seat (Must select one below) ROPS, ENCLOSED WITH HEAT (C2) All of the following are included in this packag		\$2,845
	435-9153	Deluxe Headliner & post trim covers Cup Holder Side Windows Heater and Defroster Seat (Must select one below) Door (Must select one below) ROPS, ENCLOSED WITH A/C (C3) All of the following are included in this packag Deluxe Headliner & post trim covers Cup Holder Side Windows Air Conditioner Including Heater/Defroster Seat (Must select one below) Door (Must select one below)	0 e:	\$4,895
	EAT Must select O	NE if a C1, C2 or C3 cab package was selected above.		
-	345-6329	SEAT, SUSPENSION, VINYL		\$359
	345-6349	For Use With: C1, C2 and C3 Cab Package SEAT,AIR SUSPENSION,VINYL,HEAT High back heated seat with recline, lumbar support, and adjustable Seat Mounted Controls.		\$780
	345-6359	For Use With: C1, C2 and C3 Cab Package SEAT,AIR SUSPENSION,CLOTH,HEAT	and Fully	\$805
	OOR Must select O	NE if an Enclosed ROPS was selected above.		
•	345-6240	DOOR, CAB, GLASS	0	\$108
•	345-6260	DOOR, CAB, POLYCARBONATE	0	\$214

299D2

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
FEAT	TURE PACK	AGES (CONT.)		
	ADIO Bluetooth rad	io technology enables the use of a hands free function		
	such as listen Authorization representative	ing to music and making phone calls. varies by country, please contact your Cat marketing with questions or click on the link below: r.cat.com/en/products/technology.html		
	Selection of O	NE required for C2 or C3 Comfort Package		
L	345-6175	RADIO READY	0 ble, and hardware	\$154
L	345-6180	Provides factory installed radio: Includes Bluetooth i microphone, and auxiliary inputs (USB port and aux connect external audio devices.	nterface,	\$510
A	DVANCED	MACHINE CONTROL		
L	465-3705	DISPLAY, ADVANCED, LCD, CAMERA	age display. Implement response erature gauge, on and Advanced oring. Also	\$1,140
UND	ERCARRIAC	GE		
U	NDERCARR	MAGE		
L	454-6060	RUBBER BELT, 2 SPD, D/S IDLER	0 elt with dual	NC
L	454-6061	ONLY FOR USE WITH: 435-8999 299D2 COMPACE RUBBER BELT, 2 SPD, TF IDLERS	0 elt with triple	\$1,025
T	RACKS			
L	389-7673	TRACK,RUBBER,400MM(15.7IN)BLCK	block tread. 2 SPD, D/S IDLERS	NC
L	389-7672	TRACK,RUBBER,450MM(17.7IN)BLCK	n block tread. 2 SPD, D/S IDLERS	\$665

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY

299D2

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
UND	ERCARRIAC	GE (CONT.)		
T	RACKS (Co	ont.)		
L	454-6079	TRACK,RUBBER,450MM(17.7 IN)BAR Steel embed rubber track with BAR tread provides ledisturbance and increased traction in snow. Provides 1,981mm (78 inch) machine width ONLY FOR USE WITH: 454-6060 RUBBER BELT 454-6061 RUBBER BELT	ower ground , 2 SPD, D/S IDLERS	\$725
STAF	RTERS, BAT	TERIES, & ALTERNATORS		
В	ATTERIES			
L	465-3696	BATTERY, 850 CCA, HEAVY DUTY	0	NC
L	441-4811	CANNOT BE USED WITH: EU Dealers BATTERY, HEAVY DUTY, DISC	0	\$125
L	441-4810	850 CCA with Battery Disconnect Switch BATTERY, XTRA HVY DUTY, DISC	0	\$205
OPEF	RATOR ENV	TRONMENT		
L	IGHTS			
L	495-1672	LIGHTS, HALOGEN	ts (cab mounted)	NC
L	495-1671	Two (2) forward facing adjustable LED work lights (c two (2) rear facing LED work lights (frame mounted) LED lighting advantages vs halogens: brighter work cooler, more resistant to vibration and longer life.	ab mounted) and	\$279
S	EAT BELTS			
L	258-4095	SEAT BELT, 2"	0	NC
L	258-4096	SEAT BELT, 3"	0	\$142

Supersedes 02JAN2018
Caterpillar: Confidential Green
US-A-19-01 A

Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 299D2-010

299D2

USE NO. LANE 2 / 3 MANDATORY Ship Weight LIST PRICE Ibs AT DEALER	USE NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
---	---------	----------------------	--------------------	-------------------------

TECHNOLOGY PRODUCTS

PRODUCT LINK

Product Link enables the remote transmission of information about the location, operation and condition of your equipment. Efficiently and effectively monitor the performance of your assets to help keep your jobs on schedule, maintain equipment condition and reduce the costs of owning and operating your fleet. Availability varies by country - please reference https://Dealer.cat.com/PL/Certification for certified countries. Please contact your Caterpillar marketing representative with questions.

L	441-4818	PRODUCT LINK, CELLULAR PL240	NC
L	441-4819	PRODUCT LINK, CELLULAR PL641	\$833
COOL	ING		

COOLING FAN

L	457-3167	FAN, COOLING, DEMAND	NC
		Provides variable speed hydraulic cooling fan. Sensors monitor	
		machine cooling requirements to modulate the fan speed providing	
		"on demand" cooling.	
L	457-2835	FAN,COOLING, DEMAND, REVERSING	\$840
		Reversing Fan provides automatic and manual purge modes to assist in	
		removing material from the rear door intake screen. Provides both	
		Demand Fan and Reversing Fan functionality.	

QUICK COUPLERS

L	345-4910	QUICK COUPLER, MANUAL	0	NC
L	515-8592	QUICK COUPLER, HYDRAULIC	0	\$995

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 299D2-011

299D2

USE REF NO. LANE 2 / 3 MANDATORY	Ship Weight Ibs	LIST PRICE AT DEALER
----------------------------------	--------------------	-------------------------

INSTRUCTIONS

SERVICE INSTRUCTIONS

421-8926 SERIALIZED TECHNICAL MEDIA KIT 0 NC

The technical media kit will include the Operations & Maintenance Manual (OMM) and other media specified on the Factory Notification List required to ship products from the manufacturing facility. Kit may contain multiple Operation & Maintenance Manuals (OMM) based on the final country of destination. Contents will vary. Any additional media or translations not included in the kit, should be ordered through publications.cat.com

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 299D2-012

299D2

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
SPEC	IAL ARRAN	NGEMENTS		
C 0P-0528		PAINT, CUSTOM	O notes. Custom c, high gloss custom not be cancelled.	\$1,860 NET
		Note 1: Florescent colors and matte finishes are not Note 2: Some components will NOT receive the cust The engine and items not externally visible will be p CTLs with the optional steel track undercarriage wil a black track. Cylinders, cab, coupler, radiator grill undercarriage will be painted black.	tom paint color. ainted yellow. Il be provided with	
ELEC	TRICAL			
L	309-1325	ROTATING BEACON		\$216
ОТН	ER ATTACH	HMENTS		
L	345-5234	RETURN TO DIG/WRKTL POSITIONER	urns work tool to	\$288
L	345-5148	Requires H2 or H3 performance package COUNTERWEIGHT, MACHINE, EXTERNAL Includes external weights bolted to the frame tower. Suggested for applications where additional rated of		\$1,030
L	345-3556	capacity (ROC) is needed. Machine ROC increased I HEATER, ENGINE COOLANT, 120V	by 250 lbs (113 kg).	\$195
L	457-1215	120 Volt - For additional cold weather startability. LIFTING EYES, FOUR POINT	0	\$192
L	563-7518	CANNOT BE USED WITH: TANK, WATER MOUNTING, FIRE EXTINGUISHER	0	\$200
MOD	W TOOLS			

WORK TOOLS

To view and order all available Work Tool Selections refer to WT-SSL or WT-HAMR price lists.

NOTE: Work Tools, except Hammers, are sourced via Caterpillar parts distribution system.

CMOPS orders for Compact Track Loaders and Work Tools MUST be ordered separately.

299D2

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight Ibs	LIST PRICE AT DEALER
-----	------------	---------------------	--------------------	-------------------------

FLUIDS

Recommended for use in hydraulic system where ambient temperatures are below 32 F (0 C).

FIELD INSTALLED ATTACHMENTS

Available Through Parts Distribution.

345-6070 KIT, FOPS, LEVEL 2

Falling Object Protective Structure level 2.

Provides additional overhead protection. Recommended for use in demolition applications.

Not compatible with the roof mounted Auxiliary Hydraulic Cooler.

Meets ISO 3449: 1992

Note: The part number provided is for reference only.

Individual parts must be ordered. Please reference REHS8703

for parts list and installation instructions.

474-5632 KIT, SINGLE POINT LIFT

Contains parts that attach to cab roof and allow machine to be lifted from a single point. The part number provided is for reference only. Individual parts must be ordered. Please reference REHS9970

for parts list and installation instructions.

418-5883 KIT, FOPS LEVEL 2 W/ 4 PT LIFT

This kit combines the Falling Object Protective Structure level 2 and 4 point lifting functionality. Recommended for use in applications where additional overhead protection and 4 point lifting are both desired (ov. demolition)

desired (ex. demolition).

Note: The part number provided is for reference only.

Individual parts must be ordered. Please reference REHS9989

for parts list and installation instructions.

The RETURN TO DIG/WRKTL POSITIONER feature is available as a Software Enabled Attachment (SEA) and is installed using Electronic Technician and a unique password. Cost to enable the feature via password is approximately \$221 USD Dealer Net (January, 2016). Machine must be equipped with the Electronic Self Level feature, provided in the H2 or H3 performance package to install the SEA.

299D2

USE REF NO. LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
---------------------------------	--------------------	-------------------------

FIELD INSTALLED ATTACHMENTS (CONT.)

Available Through Parts Distribution. (Cont.)

DEDICATED ALTERNATE PATTERN (H-pattern):

As of January 2018, this feature is standard from the factory. There is no cost. Using Electronic Technician the dealer can configure the machine to operate using the alternative "H" control pattern. With this feature there is no method to allow the operator to change the pattern in the cab. Refer to media number REHS8719.

SELECTABLE PATTERN CONTROL (ISO/H patterns):

This feature is a Software Enabled Attachment (SEA) and is installed using Electronic Technician and a unique password. The SEA cost to enable the feature via password is approximately \$250 USD Dealer Net (January, 2018). Allows an operator to select either standard CAT control pattern or the alternative "H" control pattern at the flip of a switch. Estimated time to install: 30 min. Refer to media number REHS8717 for appropriate parts list.

The components required are available for order from the Parts Department.

Available Through ANTARES Parts Ordering.

NOTE: US & Canada ONLY may place orders in CMOPS to be transferred via the bridge to ANTARES Parts Ordering. When ordering via CMOPS include top level reference numbers (0P-2742) and 0P number for packing.

435-9149	KIT, CAMERA REAR VIEW	\$457	NI
	For proper installation, refer to media number REHS9988.		
	Note: Requires Advanced Display		
	Estimated time to install: 1 hour 30 minutes		
484-8211	KIT, BATTERY DISCONNECT 0	\$125	NI
	For proper installation, refer to media number SEHS0193.		
	Provides components needed to install a battery disconnect switch.		
	Estimated time to install: 30 minutes		
504-1553	KIT, LICENSE PLATE	\$51	NI NET
	For proper installation, refer to media number M0067678.		NEI
	Estimated time to install: 30 minutes		
400.2604		6250	NT
499-2684	KIT, LIGHTS, LED	\$350	NI
	For proper installation, refer to media number M0066104.		
	Includes two (2) forward facing adjustable work lights (cab mounted)		
	and two (2) rear facing LED work lights (frame mounted).		
	LED lighting advantages vs halogens: brighter work site illumination,		
	cooler, more resistant to vibration and longer life.		
	Estimated time to install: 1 hour		
388-8285	KIT, FOOT THROTTLE	\$331	NI
	For proper installation, refer to media number REHS8712.		
	Estimated time to install: 1 hour 30 minutes		

Supersedes 02JAN2018
Caterpillar: Confidential Green
US-A-19-01 A

Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY

299D2

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight Ibs	LIST PRICE AT DEALER
FIELD	INSTALLE	D ATTACHMENTS (CONT.)		
		ough ANTARES Parts Ordering. (Cont.)		
	200 7075	VIT COUNTEDWEIGHT 100 LB BOC	0	¢510 NT
	388-7875	KIT, COUNTERWEIGHT, 100 LB ROC Kit provides one counterweight per side which incre Operating Capacity by approximately 100-125 lbs (4 depending on model. For maximum ROC increase, (2) 388-7875 kits. Includes Mounting hardware for counterweight per side configuration and two count configuration. Estimated time to install: 30 minutes	ases the Rated 46 - 57 kg), must order quantity of both one	\$519 NI
	388-8275	KIT, WINDOW, SIDES		\$683 NI
	514-9093	KIT, DOOR, CAB, POLYCARBONATE		\$1,785 NI
	422-3297	KIT, DOOR, CAB, GLASS		\$1,003 NI
	508-1866	KIT, AIR CONDITIONER (HTR/DFR)		\$3,051 NI
	435-9232	KIT, AIR CONDITIONER (CONVRSN)		\$2,015 NI
	435-9231	KIT, HEATER		\$1,211 NI
	527-3155	KIT, QUICK COUPLER, HYDRAULIC For proper installation refer to media number M008 Estimated time to install: 12 hours	0 1347.	\$1,078 NI
	513-5126	KIT, GUARD, COUPLER	72576. from entering the	\$199 NI
	388-8265	KIT, WT ELECTRICAL CONTROL For proper installation, refer to media number REHS Includes Work Tool Electrical switch, harness, conn hardware. Estimated time to install: 2 hours	S7806.	\$193 NI
	388-8273	KIT,WT ELECTRICAL CONTROL, DLX	S7814.	\$696 NI

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 299D2-016

Bid Term: 2/20/19 - 2/19/21

Estimated time to install: 3 hours

299D2

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
FIELD I	INSTALLE	D ATTACHMENTS (CONT.)		
Ava	ailable Thi	ough ANTARES Parts Ordering. (Cont.)		
	523-4908	KIT, DUAL SELF LEVEL	77274.	\$750 NI
	481-0031	KIT, RIDE CONTROL	0	\$1,038 NI
	435-9237	KIT, FAN, DEMAND, REVERSING	S6604. ge modes to assist in	\$857 NI
	388-8283	KIT, RADIO, READY For proper installation, refer to media number REH Provides Speakers, Wiring, Radio Box, Antenna & C required to install a single DIN radio. Estimated time to install: 1 hour	S8710.	\$149 NI
	388-8286	KIT, RADIO, AM/FM/BLUETOOTH For proper installation, refer to media number REH Includes radio with Bluetooth interface, microphone inputs (USB port and aux input jack) to connect ext devices. Requires: Radio Ready operator station. Estimated time to install: 45 minutes	S8705. e and auxiliary	\$571 NI
	498-6622	KIT, DEBRIS	67498. ers in debris material from chine frame. gned to cover the the machine as well Debris Kit is resent and should d kit.	\$1,874 NI
	472-2965	For proper installation, refer to media number REH This kit provides additional guarding for customers applications where extra safeguarding is required. provides guarding for the front work lights, rear work auxiliary hydraulic connections, work tool electrical connection and work tool coupler area. Note: If additional debris guarding is required, pleathe Debris Kit. Estimated time to install: 1.5 hours	S9959. in demanding This kit rk lights, harness	\$640 NI

Supersedes 02JAN2018
Caterpillar: Confidential Green
US-A-19-01 A

Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 299D2-017

299D2

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight Ibs	LIST PRICE AT DEALER
FIELD	INSTALLE	D ATTACHMENTS (CONT.)		
Ava	ailable Thi	ough ANTARES Parts Ordering. (Cont.)		
	421-0219	KIT, A/C BREATHER	068026. chines used in tains duct work	\$456 NI
	444-6050	KIT, TURBO DEBRIS GUARD	IS9969. ned to cover the terring the urbo Guard kit is	\$285 NI
	416-5965	For proper installation, refer to media number REF Turbine-type precleaner for the engine air filter. For dust/debris applications.	IS8735.	\$466 NI NET
	422-3323	Estimated time to install: 1 hour KIT, FRONT ROADING LIGHTS	ed mirrors. IS7836.	\$468 NI
	422-3322	KIT, LIGHTS, REAR, ROADING	IS8748. ear reflectors,	\$232 NI
	512-0356	Estimated time to install: 1.5 hours KIT, LIGHTS, REAR, WIDE MOUNT For proper installation, refer to media number MOO This kit provides components that allows the rear I relocated to mounting locations on the sides of the Estimated time to install: 30 minutes REQUIRED for Italy Roading	071898. ights to be	\$429 NI
	421-0274	KIT, LIFTING EYES, FOUR POINT For proper installation, refer to media number REH Estimated time to install: 30 minutes CANNOT BE USED WITH: TANK, WATER		\$229 NI
	422-3241	KIT, PROD LINK, CELLULAR PL641 For proper installation, refer to media number REF Product Link Pro series PL641 uses GSM and CDM to transmit location, utilization and condition infor viewing in Product Link's remote monitoring web ir technology provides capabilities for frequent tranm volumes of data. Estimated time to install: 2.5 hours	IS9952 IA 3G cellular networks mation for nterface. Cellular	\$1,024 NI

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 299D2-018

299D2

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
FIELD	INSTALLE	ED ATTACHMENTS (CONT.)		
Ava	ailable Thi	rough ANTARES Parts Ordering. (Cont.)		
	482-5132	KIT, WATER TANK, 42 US GAL, D Mounted to top of cab 42 gallon capacity Includes tank, pump, filter, lines, mounting bracke quick disconnect For proper installation, refer to media number SEH Estimated time to install: 9 hours 30 minutes For use with Water Sprinkler Kits for Angle Broom, Pick Up Broom, Utility Broom or Cold Planer	ets and (S0363.	\$1,817 NI
	527-2335	CANNOT BE USED WITH: Four Point Lifting Eyes I Single Point Lift kit or Auxiliary Hydraulic Cooler ki KIT, REMOTE GREASE (COUPLER) For proper installation, refer to media number M00 Provides remote location for lubrication of the work	it 0 984651.	\$222 NI
	541-3141	Estimated time to install: 3 hours KIT, WINTER, REAR DOOR COVER	(-25F). S8737.	\$256 NI
		Estimated time to install: 1.0 hour cepted for kit components not used or for parts	removed	

from machine during kit installation.

Shipments will be within 3 - 5 working days of order receipt for delivery by dealer parts stocking truck to dealer stocking facility.

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 299D2-019

299D2

USE REF NO. LANE 2 / 3 OPTIONAL Ship Weight LIST PRICE lbs AT DEALER

FIELD INSTALLED ATTACHMENTS (CONT.)

ENDORSED FIELD INSTALLED ATTACHMENTS

Caterpillar does not warrant, service, or assume responsibility for these attachments.

All orders, pricing confirmation, and other communication for these attachments must be directed to the listed manufacturer.

REMOTETASK TM - REMOTE CONTROL SYSTEM

Complete system for use with CAT D Series Skid Steer, Multi Terrain, and Compact Track Loaders. Allows the operator to precisely control the machine from outside the cab. Line-of-sight remote control with an approximate range of 1000 feet (300 meters). Dealer installed remote control system includes the Remote Task controller and necessary hardware to convert standard D series SSL, MTL or CTL to remote controlled machine.

NOTE: Certified for use in North America. To verify certification in other regions, please contact BCP Attachments Team. Email: bcp work tools@cat.com

Orders for the remote control system must be placed directly from:

TORC Robotics, Inc.

Tel. +1(800) 530-9285, +1(540) 443-9262

Email: sales@torcrobotics.com

PACKING

DOMESTIC PACKING

0P-0210	PACK, DOMESTIC TRUCK	NC
Only to be u	sed when ordering kits via CMOPS.	
0P-2162	PACKING, KIT	NC
PROTECTION	V	
OP-2266	SHIPPING/STORAGE PROTECTION	\$207 NET
0P-6439	CORROSION INHIBITOR	\$1,940

Supersedes 02JAN2018
Caterpillar: Confidential Green
US-A-19-01 A

Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 299D2-020