



#### Current Date 02Jan2019

## 324L - FOUR WHEEL DRIVE LOADER

#### ENGINE:

Yanmar 4TNV98CT

70 SAE Net Horsepower (52

**Isolation Mounted** 

Turbocharged

Glow Plugs

Engine Coolant -34 Degree

F (-37 Degree C)

Coolant Recovery Tank

Proportional Speed

Hydraulic Driven Cooling

Fan

Spin-On Engine Oil and Fuel

**Filters** 

Oil-to-Water Engine Oil

Cooler

Dual Safety Element Dry-

Type Air Cleaner with Dust

**Evacuator Valve and** 

Pre-Screener

Muffler, Under Hood, with

**Exhaust Stack** 

Enclosed Safety Fan Guard (Conforms to SAE J1308)

### **ELECTRICAL**:

12 Volt System

80 Amp Sealed Alternator

(1) 12 Volt, 925 CCA

Master Electrical Disconnect

Switch

Blade-Type Multi-Fused

Circuits

Sealed External Electrical

Connections

Electrical Load Center In

Operator Station

Bypass Start Safety Cover

on Starter

Positive Terminal Battery

Covers

Lights (Conforms to SAE

J99):

(2) Driving / (2) Front

Working Halogen Lights (2) Front and (2) Rear

Turn/Flashing

(2) Rear Stop Lights

(2) Rear Reflectors

(2) Rear Work Lights

**AXLES**:

Heavy-Duty Outboard Planetary Final Drives

100% Manual (Push

Button) Front Diff/Lock and Rear Std. Differential

Grease Bank for Oscillating

Rear Axle

#### **BRAKES:**

Service Brakes;

Hydraulically Actuated, Self Adjusting internal Wet

Disc Brake and Driveline

Drum Brake

Park Brake; Automatic

Spring-Applied, Hydraulic-Released internal Wet

Disc Brake

## STEERING:

Hydraulic Stereo Steer: 56 Degrees Articulation (28

Degree in Each Direction)

Plus an

Additional 26

Degree Rear Wheel Steer

OPERATOR'S STATION:

Modular Design ROPS/FOPS Cab, heat and air

conditioning standard.

**Isolation Mounted** 

(Conforms to SAE J1040,

J231, ISO 3471, ISO 3449)

Steel Roof

Left and Right Side Access

Walk Through Cab

Slip-Resistant Steps and

Ergonomically Located

Handholds (Conforms to SAE J185)

3-Way Tilt and telescopic

Steering Console

Steering Wheel with

Spinner

Seat, Deep Foam, Fabric,

Speedometer Hourmeter

Turn Signal and Hazard

Lights

High Beam Indicator

Floormat

Horn, Electric (Conforms to

SAE J994, J1446)

Key Start Switch with

Electric Fuel Shut-Off

Power Port

Interior Mounted Rearview

Convex Mirror (Conforms to

SAE J985)

Two Exterior Convex

Mirrors (Conforms to SAE

J985)

Built-In Operator's Manual

Storage Compartment and

Manual Pre-wired for Beacon and

Radio

Cab includes Radio

Speakers and Antenna

# LOADER:

Powered Attachment

Coupler

Z-Bar Linkage

Three Function Hydraulics, with Joystick Pilot Control

for Boom and

Bucket and 3rd function

electrohydraulic mini

joystick built in

Boom Float

Return to Dig (Bucket

Leveling) Feature Loader Boom Service Lock

(Conforms to SAE J38)

**OVERALL VEHICLE:** 

Articulation Locking Pin

(Conforms to SAE J276)

Oscillating Frame

**Articulation System** Front and Rear Fenders

Integral Loader Frame Lift & Tie Down Eyes

Integral Engine Frame Lift

**HYDRAULIC SYSTEM:** Joystick FNR Control with Third Function Control 24 GPM (91 L/Min) Engine Mounted Gear Pump - Open Center Combined Hydrostatic/Hydraulic Oil Reservoir with Sight Glass

TRANSMISSION: Single Lever Shift Control, F-N-R and 2 Speed automatic gear box Hydrostatic Transmission with Infinite Speed Control Inching Pedal Vertical Filter Element

Mechanical Suspension for Weight/Height, Fore-Aft Adjustment, Backrest Tilts and Adjustable Arm Rests, 2 In. (51 mm) Seat Belt with Retractor (Conforms to SAE Electronic Monitor System with Audible and Visual Warning: Engine Oil Pressure **Engine Coolant** Temperature HST Transmission Oil Temperature Indicator Lights: Engine Air Filter Fasten Seat Belt Park Brake Actuated Forward-Reverse Travel I or II Speed Range Fuel Gauge

& Tie Down Eyes Full Counterweight Drawbar with Pin Rear Bottom Guard **Environmental Fluid Drains** 

Vandal Protection Locking for: **Engine Enclosure** Operator Enclosure Rear Engine Access Door Fuel Fill 21.5 Gallon (80 L) Fuel Tank Reverse Warning Alarm (Conforms to SAE J994, J1446) Refer to Service Administration Manual for Foam Filled or Solid Tire

applications

Required - You must select one from each category

# BASE MACHINE

F.O.B. Baltimore, Maryland

Engine

	Description	Code	Price
	324L - FOUR WHEEL DRIVE LOADER	OAGOT	\$104,531.00
~	SEAT		
	Description	Code	Price
	Standard Cloth Seat, Mid-Back, Mechanical Suspension	2210	No Added Cost
	Deluxe Cloth Seat, Air Suspension, High-Back with Headrest, Heated, and Lumbar	2230	\$2,250.00
_	CONTROLS		
	Description	Code	Price
	Standard Control Package	2410	No Added Cost
	Includes Rimpull Control and Inching Pedal.		
	Attachment Assist (Creep Control & Throttle Lock)	2430	\$2,049.00
	Includes Rimpull Control and Inching Pedal.		
_	ENGINE		
	Description	Code	Price

Yanmar 4TNV98CT meets EPA FT4 and EU Stage IIIB Emissions Turbo Charged

\$4,426.00

0924

Automatic Glow Plug
Starter Protection
Automatic Derating for Exceeded System Temperatures
Electronically Controlled Fuel Delivery System

Under Hood Dual Element Air Cleaner with Restriction Indicator Dual-Stage Fuel Filter and Water Separator 500 Hour Spin-on Oil Filter

~	HYDRAULIC SYSTEM AND COUPLER		
	Description	Code	Price
	Three Function, Joystick w/FNR Control	2840	No Added Cost
	1 lever controls boom and bucket, mini-EH thumb joystick proportionally controls auxiliary function. Includes third function lines to the coupler.		
	Three Function w/High Flow Option, Joystick w/FNR Control	2842	\$4,281.00
	1 lever controls boom and bucket, mini-EH thumb joystick proportionally controls auxiliary function. Includes third function lines to the coupler. Includes third function detent.		
~	RIDE CONTROL		
	Description	Code	Price
	Less Ride Control	3000	No Added Cost
	Ride Control	3010	\$2,289.00
,	WHEELS AND TIRES		
	Description	Code	Price
	405/70R18 Firestone Duraforce	4020	\$5,372.00
	This tire option gives total machine height of 9 ft 1 in (2774 mm)		
	Mitas EM01	4025	\$5,397.00
	405/70R20 This tire option gives total machine height of 9 ft 2 in (2804 mm)		
	400/70R20 Michelin XMCL	4030	\$6,481.00
	This tire option gives total machine height of 9 ft 2 in (2804 mm)		
	400/70R20 Michelin Bibload L3	4035	\$6,481.00
	This tire option gives total machine height of 9 ft 2 in (2798 mm)		
<b>"</b>	LINKAGE		
	Description	Code	Price
	Standard Z-bar linkage	2010	No Added Cost
	Height to Hinge Pin 132 in.		
	High Lift Z-bar linkage	2020	\$2,017.00
	Height to Hinge Pin 149 in.		
	WORK LIGHTS		

	·		
	Description	Code	Price
	Halogen Work Lights - Cab	7120	\$250.00
	2x Front, 2x Rear Halogen WorkLights		
	Less Work Lights (LED Kit Ready)	7140	No Added Cost
	Dealer will need to order and install BYT10522 (2xspot) and/or BYT10523 (2xflood)		
~	BUCKETS AND COUPLERS		
	Description	Code	Price
	Less Coupler / Coupler Ready	8545	No Added Cost
	Dealer must order and install AT412608 Integrated Skid Steer Compatible Quik Tatch Coupler or AT452288 ISO Integrated Coupler. Must also order a bucket if desired.		
_	Less Bucket	8550	\$1,685.00
	ISO Coupler included.		
_	1.0 cu. yd. (0.8 cu. m.) General Purpose Bucket with Skid Shoes and Bolt-on Cutting Edge for ISO Coupler	8555	\$3,674.00
	74.8 in. (1.90 m) overall width. Includes 2 built-in lift loops.		
	1.4 cu. yd. (1.1 cu. m.) General Purpose Bucket with Skid Shoes and Bolt-on Cutting Edge for ISO Coupler	8560	\$4,776.00
	86.6 in. (2.2 m) overall width. Includes 2 built-in lift loops.		
	2.1 cu. yd. (1.6 cu. m.) Light Material Bucket with Skid Shoes and Bolt-on Cutting Edge for ISO Coupler	8565	\$5,731.00
	94.5 in. (2.4 m) overall width. Includes 2 built-in lift loops. Includes Dump Control Valve Kit, AT320957.		
_	2.6 cu. yd. (2.0 cu. m.) Light Material Bucket with Skid Shoes and Bolt-On Cutting Edge for ISO Coupler	8570	\$6,681.00
	94.5 in. (2.4 m) overall width Includes 2 built-in lift loops Includes Bucket Dump Control Valve Kit		
Opt	tional - Select as desired		
~	OTHER WORK TOOLS		
	Description	Code	e Price
	Pallet Forks for Standard ISO Coupler	9200	\$1,731.00
_	Frame width 48 in. (~1200 mm) Tines, 4 in. x 1.8 in. x 48 in. (100 x 45 x 1200 mm)		
	Front Windshield Guard	9420	\$2,147.00
_	Long Lead Time Item.		

DEALER-INSTALLED KITS

Description	Code	Price
Buckets & Pallet Forks		
1.0 cu. yd. (0.8 cu. m.) General Purpose Bucket with Skid Shoes and Bolt-on Cutting Edge for ISO Coupler	AT316647	\$1,909.00
* 74.8 in. (1.90 m) overall width * Includes 2 built-in lift loops		
1.4 cu. yd. (1.1 cu. m.) General Purpose Bucket with Skid Shoes and Bolt-On Cutting Edge for ISO Coupler	AT316646	\$2,859.00
* 86.6 in. (2.2 m) overall width * Includes 2 built-in lift loops		
2.1 cu. yd. (1.6 cu. m.) Light Material Bucket with Skid Shoes and Bolt-on Cutting Edge for ISO Coupler	AT320636	\$4,172.00
94.5 in. (2.4 m) overall width Includes 2 built-in lift loops Requires Dump Control Valve Kit, AT370530		
Pallet Forks for ISO Coupler	AT321215	\$2,009.00
Class ITA 2B fork frame Frame width 49 in. (1.2 m) Tines, 4 in. x 1.8 in. x 48 in. (100 x 45 x 1200 mm)		
Buckets Couplers & Forks		
1.0 cu. yd. (0.8 cu. m.) General Purpose Bucket with Skid Shoes and Bolt-on Cutting Edge for Quik Tatch	AT413236	\$1,888.00
74.8 in. (1.90 m) overall width Includes 2 built-in lift loops		
1.4 cu. yd. (1.1 cu. m.) General Purpose Bucket with Skid Shoes and Bolt-On Cutting Edge for Quik Tatch	AT413237	\$2,880.00
86.6 in. (2.2 m) overall width Includes 2 built-in lift loops		
2.1 cu. yd. (1.6 cu. m.) Light Material Bucket with Skid Shoes and Bolt-on Cutting Edge for Quik Tatch	AT413238	\$4,183.00
94.5 in. (2.4 m) overall width Includes 2 built-in lift loops Requires Dump Control Valve Kit LW11621918, which can be ordered in JDPoint.		
Class 3 Fork Frame with 48 Fork Tines for Quik Tatch Coupler	BYT10083	\$2,243.00
Pallet Fork Frame Kit, 48" Forks Class ITA 3B Fork Frame Frame Width 60 in. (1.5m) Tines, 4-3/4 in. x 2in x 48in (120mm x 50mm x 1220mm) Overall Length Fork Frame + Forks: 57in (1445mm)		
Class 3 Fork Frame with 60 Fork Tines for Quik Tatch Coupler	BYT10092	\$2,461.00
Pallet Fork Frame Kit, 60" Forks		

Class ITA 3B Fork Frame

Frame Width 60 in. (1.5m)

Grounds Equipment Bid #ESCNJ 18/19-25

Tines, 4-1/2 in. x 2in x 60in (116mm x 50mm x 1524mm)  Overall Length Fork Frame + Forks: 69in (1750mm)		
ISO Coupler Kit 244L/324L	AT452288	\$2,705.00
Skid Steer Compatible Quik Tatch Coupler	AT412608	\$848.00
Kits & Accessories		
Air Intake Pre-cleaner Kit	AT337325	\$176.00
Beacon Light	LW9069320	\$199.00
ISO Adapter to Quik Tatch Coupler	AT357576	\$1,584.00
Adapter for ISO Coupler to use Skid Steer Attachments		
Kits & Accessories		
Block Heater Kit	AT427686	\$112.00
Kits & Accessories		
LED Worklight Kit (Flood)	BYT10523	\$189.00
LED Worklight Kit (Spot)	BYT10522	\$189.00
Skid Steer Quik Tatch Coupler Cover	BYT10470	\$127.00
<u>Miscellaneous</u>		
3 in. Retractable Seat Belt	AT171619	View Price
<u>Miscellaneous</u>		
Electrical Attachment Control Kit	AT390659	\$512.00
Provides both 3 pin and 14 pin connectors and a control box.		

Copyright © Deere & Company. All Rights Reserved.

About Our Site | Privacy and Data | Legal | |