

### Current Date 16Nov2018

## **85G EXCAVATOR**

#### **ENGINE:**

Yanmar 4TNV98C 3.3L certified with EPA Final Tier 4 emissions 57 SAE Net HP Direct Injection Antifreeze Protection to -34 degrees F (-37 degrees C) Single Dry-Type Air Filter Electric Fuel Shutoff Low-Noise Fan with Guard Full Flow Oil Filter Heavy-Duty Low Maintenance Batteries Fuel Filter **Isolation Mounted** Radiator/Oil Cooler Trash Screen 50 Amp Alternator - 24 Volt

Automatic Belt Tension Device Water Separator

# HYDRAULICS:

Open Center with Two Variable Displacement Pumps Hydraulic Shut-Off Lever Hydraulic Pilot Controls Axial Piston Swing Motor Multiple Wet Disk Swing Brake

Boom Reduced-Drift Valves

Mechanical Pattern Changer

Hand Controlled
Proportional Auxiliary
Hydraulics Plumbed to the
End
of the Boom

UNDERCARRIAGE: 450 mm (18 In. ) Rubber Pad Track Shoes Front Track Guide Propel Motor Shield Planetary Final Drive Two-Speed Propel Axial Piston Propel Motor Back-fill Blade

UPPER STRUCTURE:
Rear-view Mirrors (right,
left, and rear)
Toolbox
Vandal Locks for:
Cab Door
Service Doors
Fuel Cap
Hydraulic Reservoir
Toolbox
Work lights:
One Mounted on Frame
One Mounted on Boom
Counterweight 3,104 lbs.

FRONT ATTACHMENTS: WC Thermal Spraying of Bucket Joint Dirt Seal on all Bucket Pins

(1,305 kg)

One Piece Swing Boom Less Bucket

OPERATOR'S STATION: Arm Rests Pilot Control Shut-Off Lever

Short Stroke, Low Effort Pilot Levers Deluxe Adjustable Cloth Seat with Suspension Multi-function, Color LCD Monitor System with: Diagnostic Capability Systems Monitoring Capability Multiple Language Capability Maintenance Tracking **Engine Coolant** Temperature Gauge **Engine Coolant** Temperature Warning Indicator with Audible Alarm

Fuel Gauge with Low Fuel Indicator
Work Mode Indicator
Auto Idle Indicator
Alternator Charge Indicator

Air Filter Restriction Indicator Fault Code Alert Indicator Check Engine Indicator Wiper Mode Indicator Work Lights On Indicator Fuel Rate Display Clock Hour Meter Mode Selection: One Work Mode Two Power Modes Numerous Attachment Modes Auto-Climate Control/Air Conditioner, Heater with Pressurizer AM-FM Radio Machine Information Center (MIC) Windshield Wiper/Washer with Intermittent Speed Cell Phone Power Outlet 2 In. Retractable Seat Belt Tinted Safety Glass Hot/Cold Box Compartment

Horn
Two Cup Holders
Interior Light
Coat Hook
Floor Mat
Motion Alarm with Cancel
Switch
Transparent Tinted Roof
Hatch with Sunshade
Four Fluid-Filled Elastic
Mounts
Easy Access Air
Conditioning Filter

Engine Oil Pressure Warning Indicator with Audible Alarm

Required - You must select one from each category

## BASE MACHINE

F.O.B. US/Canadian Port of Entry except where noted. See DEALER-INSTALLED ATTACHMENT section for additional source notes.

	Description 85G EXCAVATOR	Code 0081FF	Price \$133,087.00
~	TRACK SHOES		
	Description	Code	Price
	600 mm (24in.) Track Shoes	3205	\$1,010.00
	Triple Semi-Grouser Shoes w/ Blade Long lead time required.		
	Rubber Crawler Pads	3265	No Added Cost
	450 mm (18 In.) Rubber Pads w/ Blade Steel track shoes with vulcanized rubber pads bonded to top of shoes.		
	450 mm (18 In.) Continous Rubber Belt w/ Blade	3275	\$1,010.00
	Long lead time required.		
	450 mm (18 In.) Steel Triple Semi-Grouser Shoes w/ Blade	3215	(\$2,930.00)
~	ARM		
	Description	Code	Price
	2.12 M (6 Ft. 11 In.) Arm Assembly with Bucket Cylinder and Linkage	7060	\$6,724.00

### Optional - Select as desired

### ATTACHMENTS FOR FIELD CONVERSION

F.O.B. Dubuque, lowa for dealer-installed kits, except where noted. Some of the following kits may require additional parts for a complete installation. Prior to ordering, check the installation instructions by going to www.johndeeretechinfo.com and clicking on Library, or by clicking on this Hyperlink (<a href="Installation Bulletin Search">Installation Bulletin Search</a>), and insert the AT number to retrieve the attachment installation instruction bulletin for additional parts. Exception to above note is FRONTIER Dealer Installed Kits.

All attachments are sold as a quantity of one.

Description	Code	Price
<u>Buckets</u>		
BKH Pin-on Bucket 18 In. (457 mm) Heavy-Duty 5.1 Cu. Ft. (0.14 Cu. M.)	AT437340	\$1,309.00
Must include hydraulic coupler AT442602 if ordered for excavator usage.		
	AT437344	\$1.825.00

BKH Pin-on Bucket 24 In. (610 mm) Heavy-Duty 8.8 Cu. Ft. (0.25 Cu. M.)		
Must include hydraulic coupler AT442602 if ordered for excavator usage.		
BKH Pin-on Bucket 30 In. (762 mm) Heavy-Duty 10.0 Cu. Ft. (0.28 Cu. M.)	AT437345	\$1,799.00
Must include hydraulic coupler AT442602 if ordered for excavator usage.		
BKH Pin-on Bucket 36 In. (914 mm) Ditching 12.5 Cu. Ft. (0.35 Cu. M.)	AT437616	\$1,536.00
Must include hydraulic coupler AT442602 if ordered for excavator usage. Ditching bucket does not include teeth.		
BKH Pin-on Bucket 36 In. (914 mm) Heavy-Duty; 12.5 Cu. Ft. (0.35 Cu. M.)	AT437346	\$1,792.00
Must include hydraulic coupler AT442602 if ordered for excavator usage.		
Buckets, Ditching		
48 In (1219 mm), 0.64 yd3 (0.49 M3) Ditching Bucket	AT339015	\$2,431.00
Buckets, Heavy-Duty		
24 In (610 mm), 0.31 yd3 (0.24 M3) Heavy-Duty Bucket	AT395791	\$2,565.00
Includes Five (5) TK-Series Fanggs (TF23D)		
30 In (762 mm), 0.41 yd3 (0.31 M3) Heavy-Duty Bucket	AT395792	\$2,709.00
Includes Six (6) TK-Series Fanggs (TF23D)		
36 In (914 mm), 0.51 yd3 (0.39 M3) Heavy-Duty Bucket	AT395793	\$2,962.00
Includes Seven (7) TK-Series Fanggs (TF23D)		
<u>Hydraulic Couplers</u>		
Hydraulic Quick Coupler	AT442602	\$7,331.00
For use with John Deere backhoe buckets only. Will not interface with standard excavator buckets.  Extra pins required can be ordered through service parts: T185832 T185831		
Thumb Kit, Direct with Coupler	BYT10499	\$5,000.00
Thumb Kit, Direct without Coupler	BYT10498	\$5,000.00
<u>Hydraulics</u>		
Auxiliary Hydraulic Lines Boom to Arm	AT436726	\$1,147.00

	Requires AT434128 (ZX 85USB-5)		
	Requires AT434127 (ZX 75US-5) Requires AT434128 (85G)		
	Requires AT434127 (75G)		
	Foot Pedal Control Kit for Meterable Two-Way Hydraulics	AT356391	\$1,410.00
	Recommended: Hydraulic Filter Restriction Indicator Kit Does not require a solenoid kit.		
	Foot Pedal Switch for 1-Way Control of Auxiliary Valve	AT196587	\$515.00
	Requires a solenoid kit. Installation instructions T161995. Average installation, 1 hour. For customers who want an auxiliary valve with foot pedal control of attachments that require 1-direction on/off control without metering. Includes foot switch and wiring harness.		
	ALSO ORDER: Hydraulic Filter Restriction Indicator Kit Recommended. For a complete system, also order 1-Way or 2-Way Electric Solenoid Valves for Auxiliary Valve and Auxiliary Hydraulic Lines. Average installation, 1 hour. For customers who want an auxiliary valve with foot pedal control of attachments that require 1-direction on/off control without metering. Includes foot switch and wiring harness.		
	ALSO ORDER: Hydraulic Filter Restriction Indicator Kit Recommended. For a complete system, also order the 2-Way Electric Solenoid Valves for Auxiliary Valve and Auxiliary Hydraulic Lines.		
	Hydraulic Filter Restriction Indicator Kit	AT442872	\$774.00
	For iT4 and FT4 only.		
	Single Pedal Propel Kit	AT390776	\$2,080.00
-	REFERRAL ATTACHMENTS		
	Description	Code	Price
	G.R.Mfg.	oode	11100
	G.R. Manufacturing, Inc. * Kits listed below must be ordered through John Deere. * F.O.B. Trussville, Alabama * All kits include installation instructions * All warranty, repair parts, technical support and assistance, and sales support and assistance will be the responsibility of G.R. Manufacturing, Inc., and will be handled directly between the Dealer and G.R. Manufacturing, Inc. G.R. Manufacturing, Inc. 4800 Commerce Drive Trussville, Alabama 35173 Phone: (800)841-8001 Fax: (205)655-8005		
	Screen, Front CAB	BYT10447	\$2,346.00

Copyright  $\ensuremath{\mathbb{C}}$  Deere & Company. All Rights Reserved.

About Our Site | Privacy and Data | Legal | |