918M

918M WHEEL LOADER LEICESTER, ENGLAND

Ship Weight lbs LIST PRICE AT DEALER

Standard Equipment:

POWERTRAIN

Cat C4.4 ACERT Engine

- -Common rail fuel injection
- -U.S. EPA Tier 4 Final/ EU Stage 4
- -MLIT 2014

Caterpillar NOx Reduction System

Fuel: Ultra Low Sulphur Diesel @ <15ppm

Engine Oil: Cj-4

Electric fuel pump with 4 micron

filtration

S.O.S port, transmission oil

Hydrostatic transmission,

39 km/h (24mph)

Lube for life universal joints

Forward - Neutral - Reverse on joystick

100% locking differentials, whilst

moving

Air cleaner, radial seal, dual filters

Cooling fan, hydraulic on demand

Intergrated Cyclone pre-cleaner

HYDRAULICS

Two valve, single lever joystick Diagnostic pressure taps SOS port, hydraulic oil Variable displacement piston pump,hystat and implement.

ELECTRICAL

150 Amp alternator One 850 CCA maintenance free battery Roading lights 12 volt direct electric starting Battery disconnect switch

OPERATOR ENVIRONMENT

suppressed

Hydraulic control lever lockout

Electrohydraulic implement controls Gauges

- Engine coolant temperature
- Hydraulic oil temperature
- Fuel level
- Speedometer
- Digital Hour meter
- DEF

Operator warning system indicators:

- Brake charge pressure low
- Engine malfunction
- Park brake applied
- Electrical system voltage flow
- Hydraulic oil filter bypass
- Action indicator

Seat

- Fabric or Vinyl

- adjustable height, backrest, armrest
- Seat belt, retractable

Heater/defroster

Wiper/washer (front & rear)

Tinted front glass, laminated

Adjustable steering column

Rear window defrost

Lockable Storage box with cup holder

Internal 12V power source

External 12V power source

FLUIDS

Extended life coolant antifreeze Protected to -36C (-33F) hydraulic oil Cat Advanced Hydo 10

OTHER STANDARD EQUIPMENT

Parallel lift, Optimised Z-Bar loader Fenders, front and rear Engine enclosure - lockable Recovery hitch Vandalism protection - locked service points

REGIONAL STANDARDS(as required) Chocks Bucket tooth or edge guard Decals, roading speed Reflectors, roading Camara, rear view Beacon

918M

918M WHEEL LOADER	Ship Weight	LIST PRICE
LEICESTER, ENGLAND	lbs	AT DEALER

Lane 2 is reserved for the Base Order Management Program Please use Lane 2 when placing orders that are part of the Base Order Management program.

550-3554	918M WHEEL LOADER DCA1	\$173,610
	LANE 1 - AVAILABLE FROM CLAYTON PDC	
	INCLUDES:	
	457-1488 918M WHEEL LOADER	
	462-7421 ENGINE, C4.4, T4F, HRC	
	396-2519 POWERTRAIN, HI RIMPULL, 24MPH	
	451-4344 HYDRAULICS, 3V/1L, STD LIFT	
	463-2090 CAB, DELUXE, SINGLE BRAKE	
	539-7204 SEAT, DELUXE	
	464-9682 STEERING, STANDARD	
	462-7111 HEATER AND AIR CONDITIONER	
	423-5544 LIGHTS, ROADING, RH DIP	
	550-9815 SEAT BELT, RETRACTABLE 2"	
	308-0189 VALVE, DRAIN, ECO	
	433-3258 SECURITY SYSTEM, NONE	
	444-1001 ENG COOLANT, A/FREEZE (-50/-58F)	
	448-9539 LIGHTS, CAB, WORKING HALOGEN	
	450-5405 HYDRAULIC OIL, STANDARD	
	462-7340 BATTERY, HEAVY DUTY	
	469-5852 FENDERS, STANDARD	
	471-6212 WORKTOOL, WIRING	
	471-6764 FEATURE PACKAGE, ROAD + LOAD	
	472-2513 LOADER ARR, STD CPLR, STD LIFT	
	474-1980 ALARM, BACK-UP	
	474-1982 HEATER, ENGINE COOLANT, 120V	
	486-3775 3V, QUICK DISCONNECT PUSH FIT	
	504-4835 CAMERA, REAR VIEW	
	508-0797 PRODUCT LINK, CELLULAR, PL240	
	524-5098 FUEL, STANDARD	
457-1488	918M WHEEL LOADER	\$141,410
	LANE 2 - AVAILABLE FROM LEICESTER FACTORY	
	LANE 3 - AVAILABLE FROM LEICESTER FACTORY	

Standard machine with top speed of 24 mph (40 kph)

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY

918M

USE	REF NO.	LANE 1	Ship Weight Ibs	LIST PRICE AT DEALER
LAN	E 1 AM-NOI	RTH MANDATORY ATTACHMENTS		
L	ANE SELEC	TION		
	0P-9001	LANE 1 ORDER		NC
7	IRES			
type your Any p mach	cannot be gu tire choice, b proposed cha nine shipmen	ride tire availability limitations, tire brand and laranteed. Every effort will be made to satisfy but we reserve the right to propose alternate tires. Inge will be reviewed with the dealer prior to to the machine will ship only with the dealer proposed alternative tire.		
P	385-5822	TIRES, 17.5 R25, MX, L2 XTLA Michelin Product Code #04118 Radial, non-directional tread for traction. Cut and impact resistant. Width over tire measurement = 2300mm (91")	1,789	\$2,110
В	ucket			
Р	390-8219	BUCKET, GP, 2.2 YD3, IT, BOCE	1,393 1,393	\$6,163 \$6,163 NI
//	VSTRUCTIO	N DECALS		
L	476-2741	INSTRUCTIONS, ANSI	0	NC
L	476-2740	INSTRUCTIONS, ISO	0	NC
P	REP PACK			
L	519-5211	PREP PACK, EMC	0	NC
N	MEDIA KIT			
	421-8926	SERIALIZED TECHNICAL MEDIA KIT	uired	NC
P	acking			
	0P-0210	PACK, DOMESTIC TRUCK	0	NC

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY

918M

USE	REF NO.	LANE 1 Ship Weight lbs	t LIST PRICE AT DEALER
LANE	1 AM-NO	RTH MANDATORY ATTACHMENTS (CONT.)	
Pac	king (Co	nt.)	
	0P-4299	PACKING, LAST MILE PROGRAM	NC NC
	0G-3273	RUST PREVENTATIVE APPLICATOR	\$110 NE

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 918M-004

918M

USE REF NO. LANE 1 MANDATORY

Ship Weight lbs LIST PRICE AT DEALER

LANE 1 AM-NORTH OPTIONAL ATTACHMENTS

May select additional options (not required).

WORKTOOLS
SEE WT CWL price list to order Work Tools such as:
General Purpose Buckets with various G.E.T.
Multi Purpose Buckets with various G.E.T.
Light Material Buckets with bolt on edge
Pallet Forks & Carriages
Brooms, Angle & Pickup

918M

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight Ibs	LIST PRICE AT DEALER
LANE	SELECTIO	N		
	0P-9002	LANE 2 ORDER	0	NC
	0P-9003	Only for dealers enrolled in the Base Orders Manager LANE 3 ORDER		NC
REGIO	ONAL PAC	KAGES		
PF	REP PACK			
L	519-5211	PREP PACK, EMC	0	NC
POW	ERTRAIN			
PC	OWERTRAI	N - ENGINE		
L	462-7421	ENGINE, C4.4, T4F, HRC	0	NC
FU	JEL			
L	524-5098	FUEL, STANDARD	0	NC
L	484-5160	FUEL, COLD WEATHER	0	\$178
PC	OWERTRAI	N - GEARING		
L	396-2518	POWERTRAIN, HI RIMPULL, 12MPH	ed top speed. not require I for applications nsmission will	\$570
L	396-2519	POWERTRAIN, HI RIMPULL, 24MPH	ed top speed. t local travel selecting between	\$4,875
DI	R <i>AIN</i>			
L	308-0189	VALVE, DRAIN, ECO	uel tanks.	\$155
L	308-0190	Oil/fuel drains when drain tube is screwed into plug VALVE, DRAIN STD	0	NC

918M

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	----------------------	--------------------	-------------------------

HYDRAULICS

LOADER ARRANGEMENTS

The 910,914 & 918M is designed for Caterpillar work tools, when using third party work tools, pin on coupler, or ISO wide coupler the loader linkage could go over center when fully dumped. Refer to Special Instructions, SEHS0166 "Procedure to Modify the Linkage in order to Prevent the Linkage from Over-Centering on the 910, 914 & 918 for preventing an over center condition from occurring.

L	451-4347	LOADER ARR, PIN ON, STD LIFT	NC
		REQUIRES: 423-6175 TRANSPORT GROUP IF NO INSTALLED BUCKET SEL	ECTED.
L	472-2513	ONLY FOR USE WITH: PIN ON ATTACHMENTS LOADER ARR, STD CPLR, STD LIFT	\$2,060
-	472-2313	Standard Lift with STD coupler also called -IT- Integrated Tool	ŞZ,000
		Carrier Coupler.	
		ONLY FOR USE WITH: STANDARD WIDTH (IT) ATTACHMENTS	
L	472-2514	LOADER ARR, WIDE CPLR,STD LIFT	\$2,060
		Standard Lift with WIDE coupler also called "ISO" and is compatible	
		with the Volvo work tool interface. ONLY FOR USE WITH: WIDE COUPLER (ISO) ATTACHMENTS	
		STANDARD LIFT HYDRAULIC SYSTEMS.	
L	544-1504	LOADER, FUSION CPLR, STD LIFT	\$4,230
		Standard Lift with Fusion coupler featuring constant pressure	. ,
		coupler wedges	
		ONLY FOR USE WITH: FUSION ATTACHMENTS	
L	541-2538	LOADER ARR, PIN ON, HIGH LIFT	\$6,660
		High Lift with no coupler installed	БСФББ
		REQUIRES: 423-6175 TRANSPORT GROUP IF NO INSTALLED BUCKET SEL ONLY FOR USE WITH: PIN ON ATTACHMENTS	ECTED.
L	541-2539	LOADER ARR, STD CPLR, HIGH LIFT	\$8,720
-	041-2000	High Lift with STD coupler also called -IT- Integrated Tool Carrier	Q0,720
		Coupler.	
		ONLY FOR USE WITH: STANDARD WIDTH (IT) ATTACHMENTS	
L	541-2540	LOADER ARR, WIDE CPLR, HIGH LIFT	\$8,720
		High Lift with WIDE coupler also called "ISO" and is compatible	
		with the Volvo work tool interface.	
	544-1505	ONLY FOR USE WITH: WIDE (ISO) ATTACHMENTS	\$10,890
L	544-1505	LOADER, FUSION CPLR, HIGH LIFT	\$10,890
		wedges	
		ONLY FOR USE WITH: FUSION ATTACHMENTS	
	HYDRAULIC		
		IRING, WORKTOOL (471-6212) is recommended.(Not available	
	for Japan).	omplex hydromechanical work tools such as angle brooms,	
		snow blowers, wheel saws, and mulchers.	
	dozer blades,	show blowers, wheel saws, and indichers.	
L	451-4343	HYDRAULICS, 2V/1L	NC
		Provides standard lift and tilt hydraulic valves	
		and an electrohydraulic joystick lever control which operates both	
		lift and tilt functions.	
		ONLY FOR USE WITH: PIN ON LOADER ARRANGEMENTS ONLY.	

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY

918M

JSE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight Ibs	LIST PRICE AT DEALER
HYDF	RAULICS (CONT.)		
H	YDRAULIC	SYSTEMS (Cont.)		
_	451-4344	HYDRAULICS, 3V/1L, STD LIFT	0	\$3,190
		Provides third valve auxiliary hydraulics, controlled by proportional thumb switch on the joystick. Auxiliary terminate on the loader arms with quick disconnect of the control of the con	oy a lines couplings.	
-	451-4345	Electrohydraulic joystick lever operates both lift and HYD, 4V/1L,STD LIFT,HIGH FLOW	ctions, hes on the loader arms bystick lever or work tools	\$9,270
-	538-6260	dozer blades snow blowers, or snow wings. HYDRAULICS, 2V, COUPLER READY	0	\$545
-	543-4369	CANNOT BE USED WITH: 451-4347 LOADER ARR, HYDRAULICS, 3V/1L, HIGH LIFT	oy a lines couplings.	\$3,190
A	UX COUPLI	INGS		
-	486-3774	3V QUICK DISCONNECT SCREW FIT	ressure connectors so have	\$302
-	486-3781	threaded fittings to connect to threaded fittings on m 4V QUICK DISCONNECT SCREW FIT	ressure connectors	NC
-	486-3775	threaded fittings to connect to threaded fittings on m 3V QUICK DISCONNECT PUSH FIT	achine 0	NC
		ONLY FOR USE WITH: 451-4344 HYDRAULICS, 3 471-6252 HYDRAULICS, 3		
	486-3782	4V QUICK DISCONNECT PUSH FIT	was on EV/1L, STD LIFT, HI FLOW	\$303
STAR	RTERS, BAT	TERIES, & ALTERNATORS		
BA	ATTERY AF	RRANGEMENT		
_	462-7342	BATTERY, STANDARD	0	NC

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY

918M

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight Ibs	LIST PRICE AT DEALER
STA	RTERS, BAT	TTERIES, & ALTERNATORS (CONT.)		
В	ATTERY AF	RRANGEMENT (Cont.)		
L	462-7340	BATTERY, HEAVY DUTY Additional 855 Cold Cranking Amp, maintenance fre Mounted on right rear chassis in a battery box, outbo	e battery.	\$209
ELEC	CTRICAL			
F	ROADING LIC	GHTS		
Р	423-5544	LIGHTS, ROADING, RH DIP	0	\$745
	effectively more jobs on sched of owning and please referen- certified count	ation, and condition of your equipment. Efficiently and nitor the performance of your assets to help keep your ule, maintain equipment condition, and reduce the cost operating your fleet. Availability varies by country tice https://Dealer.cat.com/PL/Certification for tries. Please contact your Caterpillar marketing with questions.		
L	508-0797	PRODUCT LINK, CELLULAR, PL240	rk to transmit Link user	NC
L	509-6603	data transmission. PRODUCT LINK, CELLULAR, PL641	age including DMA cellular networks on for viewing	\$833
OPE	RATOR ENV	IRONMENT		
S	STEERING			
L	464-9682	STEERING, STANDARD	0	NC
L	464-9683	CANNOT BE USED WITH: EU DEALERS STEERING, SECONDARY	s of	\$1,255

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY

918M

US	REF E NO.	LANE 2 / 3 MANDATORY	Ship Weight Ibs	LIST PRICE AT DEALER
OP	ERATOR ENV	VIRONMENT (CONT.)		
L	463-2089	CANOPY, STANDARD, SINGLE BRAKE Canopy features: ROPS, FOPS, fixed steering column with FNR, gear selection, differential lock, continuous and proportional auxiliary switch (opt) in one hand, c sun visor, external knock back mirrors, interior rear lockable storage box, and suspended pedals. CANNOT BE USED BY: EU DEALERS	a,low effort joystick is flow (opt), coat hook, view mirror,	NC
L	463-2090	REQUIRES: HYDRAULIC HOSE GUARD IF 3 OR 4 VACAB, DELUXE, SINGLE BRAKE	ble steering d rear window, MP3/WMA	\$7,580
	SEATS			
L	539-7203	SEAT, VINYL	0	NC
L	539-7204	ONLY FOR USE WITH: CANOPY SEAT, DELUXE Fully adjustable air ride suspension with fabric covered seat upper, mid height backrest, mechanical lumbar support, heated cushions and armrests. ONLY FOR USE WITH: 463-2090 Cab, deluxe		\$775
L	552-3734	CANNOT BE USED WITH: CANOPY SEAT, DELUXE PLUS Fully adjustable air ride suspension with fabric covered seat upper, mid height backrest, mechanical lumbar support, heated and adjustable comfort cush and armrests. CANNOT BE USED WITH: CANOPY	l	\$1,060
	SEAT BELTS			
L	236-8015	SEAT BELT, RETRACTABLE 3"		\$244
L	550-9815	Required in British Columbia, Oregon, California SEAT BELT, RETRACTABLE 2"	0	NC
	ACCESSORY	EQUIPMENT		
L	504-4835	CAMERA, REAR VIEW	he cab.	\$1,535

Supersedes 02JAN2018
Caterpillar: Confidential Green
US-A-19-01 A

Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 918M-010

918M

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
OPER	ATOR ENV	IRONMENT (CONT.)		
A	CCESSORY	EQUIPMENT (Cont.)		
L	504-4834	MIRROR, REAR VIEW		NC
FE	EATURE PA	CKAGES		
L	471-6771	FEATURE PACKAGE, BASIC, STD LIFT	ude ontrol,	\$1,925
L	471-6764	This package includes the following for standard lift I 1) Electronic Throttle Lock 2) Automatic Ride Control 3) Variable Speed Creeper Control 4) Electronic Implement Modulation 5) Rim Pull Control(three eletronic settings to select 60%, 80% and 100% full power) 6) Return to Dig 7) Lift Kickout 8) Implement Modulation 9) Hystat Aggressiveness control Electronic Throttle Lock maintains the engine speed adjustable at any time. Creeper Control compliments Throttle Lock by controlling the ground speed regard speed. Together these two features are normally used mower or snow blower applications where high engin needed for the hydraulic power, but ground speed m Rim Pull Control reduces the amount of tire slip in perventing excessive tire wear. When the lift is pulled detent, Lift Kickout will stop the loaders arms at a pr Implement Modulation increases joystick aggressiven selections on the right console soft touch pad. Similar the Hystat Aggressiveness has three selections for she	at any RPM. Electronic less of engine I for broom, e speed is ust be slow. for underfoot, back to a eset height. hess with three rly,	\$3,680
L	559-6272	and directional change aggressiveness. FEATURE PACKAGE, BASIC,HI-LIFT Basic package for high lift linkages does not include a electronically controlled features such as Ride Control Return To Dig, Lift Kickout, Electronic Throttle Lock, Rimpull Control, Creeper Control, Implement Modula nor Drivetrain Aggressiveness control.	new bl,	\$1,925

Supersedes 02JAN2018
Caterpillar: Confidential Green
US-A-19-01 A

Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 918M-011

918M

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight Ibs	LIST PRICE AT DEALER
OPER	ATOR ENV	IRONMENT (CONT.)		
FE	ATURE PA	CKAGES (Cont.)		
L	559-6273	FEATURE PACKAGE, ROAD, HIGH LIFT	at any RPM. s Electronic lless of engine ed for broom, ne speed is	\$3,050
L	559-6274	FEATURE PACKAGE, LOAD, HIGH LIFT	oor underfoot, d back to a reset height. ness with three arly,	\$2,300
L	559-6275	FEATURE PKG, ROAD & LOAD, HL This package includes the following for high lift links 1) Electronic Throttle Lock 2) Automatic Ride Control 3) Variable Speed Creeper Control 4) Electronic Implement Modulation 5) Rim Pull Control(three eletronic settings to select 60%, 80% and 100% full power) 6) Return to Dig 7) Lift Kickout 8) Implement Modulation 9) Hystat Aggressiveness control Electronic Throttle Lock maintains the engine speed adjustable at any time. Creeper Control compliments Throttle Lock by controlling the ground speed regard speed. Together these two features are normally use mower or snow blower applications where high engin needed for the hydraulic power, but ground speed m Rim Pull Control reduces the amount of tire slip in p preventing excessive tire wear. When the lift is pulled detent, Lift Kickout will stop the loaders arms at a primplement Modulation increases joystick aggressive selections on the right console soft touch pad. Similat the Hystat Aggressiveness has three selections for shand directional change aggressiveness.	at any RPM. s Electronic fless of engine d for broom, ne speed is nust be slow. oor underfoot, d back to a reset height. ness with three urly,	\$3,680

Supersedes 02JAN2018
Caterpillar: Confidential Green
US-A-19-01 A

Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 918M-012

918M

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
OPER	ATOR ENV	IRONMENT (CONT.)		
		CONDITIONER CORDERING A CAB		
L	462-7107	HEATER	0	NC
L	462-7111	Heater/Front defroster HEATER AND AIR CONDITIONER Heater/Front defroster and air conditioner.	0	\$4,175
I	Please note: tl	ECURITY SYSTEM nis is a mandatory selection on machines with an but is NOT available on machines with a canopy.		
L	433-3258	SECURITY SYSTEM, NONE	0	NC
L	423-6165	SECURITY SYSTEM, MACHINE	Machine hine via	\$1,030
TIRES	S, RIMS, AI	ND WHEELS		
TII	RES			
type c your ti Any p	annot be guire choice, by roposed chaine shipment	ride tire availability limitations, tire brand and laranteed. Every effort will be made to satisfy but we reserve the right to propose alternate tiresinge will be reviewed with the dealer prior to t. The machine will ship only with the dealer	s.	

TIRES

acceptance of the proposed alternative tire

Р	420-3893	TIRES, 17.5-25, BS, L2 SNOW	\$1,210
		Specially designed for operation on snowy roads.	
		Directional tread pattern provides excellent traction and pulling	
		performance.	
Р	533-2713	TIRES, 17.5 R25, NK, L2 SNOW	\$4,810
		Nokian Hakkapeliitta Tire.	
		Specially designed for operation on snow and ice.	
		Non directional tread pattern with excellent self cleaning.	
Р	568-6856	TIRES, 17.5 R25, MX, XSNOW	\$5,340
		Michelin Product Code #99466	
		Michelin Xsnoplus Tire.	
		Specially designed for operation on snow and ice.	
		Non directional tread with excellent self-cleaning.	
		Width over tire measurement = 2248mm (88")	

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY

918M

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight Ibs	LIST PRICE AT DEALER
	, RIMS, AI RES (Cont	ND WHEELS (CONT.)		
P	561-7110	TIRES, 20.5 R25, MX, XSNOW Michelin Product Code #62408 Michelin Xsnoplus Tire. Specially designed for operation on snow and ice. Non directional tread pattern with excellent self-clear Oscillation limiter to maintain fender to tire clearance Width over tire measurement = 2284mm (90") NOTE: A Fusion coupler or High Lift option is require 20.5 R25 tire to allow attachments such as buckets on the ground. REQUIRES: 547-5217 FENDERS, STANDARD, 20.5 CANNOT BE USED WITH: 451-4347 LOADER ARR, R472-2513 LOADER ARR, R472-2514 LOADER ARR, R471-0854 CONV, TUV ROA471-0856 CONV, TUV ROA471-0856 CONV, TUV ROA470-6188 CONV, ITALY ROADER ARR, RATO-6188 CONV, ITALY ROADER CONV, IT	ning. e e with this to sit level OR PIN ON, STD LIFT STD CPLR, STD LIFT WIDE CPLR, STD LIFT ADING, 20KPH ADING, 40KPH	\$9,770
TIF	RES AVAIL	ABLE FROM GOODYEAR WITH 1 PIECE RIM	IS	
P	430-2658	TIRES, 17.5 R25, GY, L3 RT-3B Goodyear Product Code #606019 17.5R25 176A2 TL * UN RT-3B 6S Radial tire, non directional tread, self cleaning Superior resistance to rock cuts and penetration for use on rough terrain Width across tires 89" (2260mm)	0	\$7,930
P	385-5821	TIRES, 17.5-25, GY, L2 SGL12PR		\$26
TIF	RES AVAIL	ABLE FROM GOODYEAR WITH 3 PIECE RIM	IS	
P	430-2660	TIRES, 17.5-25, GY, L2 SGL16PR		\$2,170
Р	385-5825	Width over tire measurement = 2250mm (89") TIRES, 17.5-25, GY, L3,3PC RIM	·	\$3,395

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY

918M

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight Ibs	LIST PRICE AT DEALER
TIR	ES, RIMS, A	ND WHEELS (CONT.)		
,	TIRES AVAIL	ABLE FROM GOODYEAR WITH 3 PIECE RIM	IS (Cont.)	
P	561-7109	Goodyear Product Code #128-5164 SGL E/L-2A (Sure Grip Loader) - 12 ply rating Nylon bias, tubeless, directional and self-cleaning tre for floatation and traction. Oscillation limiter to maintain fender to tire clearanc Width over tire measurement = 2304mm (91") NOTE: A Fusion coupler or High Lift option is require 20.5 R25 tire to allow attachments such as buckets on the ground. REQUIRES: 546-5274 FENDERS, STANDARD, 20.5 CANNOT BE USED WITH: 451-4347 LOADER ARR, I 472-2513 LOADER ARR, I 472-2514 LOADER ARR, I 471-0584 CONV, TUV ROA 471-0856 CONV, TUV ROA 470-6188 CONV, ITALY ROADER CONV, ITALY R	ead e e with this to sit level OR PIN ON, STD LIFT STD CPLR, STD LIFT WIDE CPLR, STD LIFT ADING, 20KPH ADING, 40KPH	\$5,250
P	385-5823	TIRES, 17.5 R25, MX, L3 XHA2 Michelin Product Code #717546 Radial, wide lug, non-directional tread for lateral traction. Heavy shoulder and protected sidewall for heavy duty applications.	2,123	\$4,820
Р	385-5822	Width over tire measurement = 2249mm (88") TIRES, 17.5 R25, MX, L2 XTLA	1,789	\$2,110
	TIRES AVAIL	ABLE FROM MICHELIN WITH 3 PIECE RIMS		
P	385-5826	TIRES, 17.5 R25, MX,L2, XTLA Michelin Product Code #04118 Radial, non-directional tread for traction and long/ever tread wear in General applications. Cut and impact resistant. Width over tire measurement = 2300mm (91")		\$6,240

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY

918M

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight Ibs	LIST PRICE AT DEALER
		ND WHEELS (CONT.) ABLE FROM MICHELIN WITH 3 PIECE RIMS	(Cont.)	
 Р	561-7108 443-7885	TIRES, 20.5 R25, MX, XHA2 Michelin Product Code #84298 Radial, wide lug, non-directional tread for lateral traction. Heavy shoulder and protected sidewall for heavy duty applications. Oscillation limiter to maintain fender to tire clearance Width over tire measurement = 2282mm (90") NOTE: A Fusion coupler or High Lift option is require 20.5 R25 tire to allow attachments such as buckets to on the ground. REQUIRES: 546-5274 FENDERS, STANDARD, 20.5 CANNOT BE USED WITH: 451-4347 LOADER ARR, PI 472-2513 LOADER ARR, SY 472-2514 LOADER ARR, WY 471-0854 CONV, TUV ROA 471-0856 CONV, TUV ROA 470-6188 CONV, ITALY ROTIRES, 17.5X25, FLEX, SOLID PLEASE CONTACT THE FACTORY TO CHECK AVAILAF Flexport. Solid tires ideal for hard abrasive surfaces were readered.	with this o sit level IN ON, STD LIFT TD CPLR, STD LIFT TIDE CPLR, STD LIFT DING, 20KPH DING, 40KPH DADING STD LIFT0 ABILITY BEFORE ORD	\$10,690 \$8,890 ERING.
TII	DEC AVAU	puncture resistance is required. Not homologated for Recommended speed: 8 kph (5 mph) loaded, 16 kph (5 lexports supplied WITH rear metal platforms only. Width across tires 87.8" (2230mm). REQUIRES: 504-4713 FENDERS, DEFLECTORS CANNOT BE USED WITH: ANY ROADING CONVERSIONAL AND EXECUTIVE AND ASSESSED RESIDENCE FOR THE SECOND SMITH AND ASSESSED RESIDENCE.	(10 mph) unloaded. ON PACKAGE	
/ // P	561-3273	ABLE FROM BRIDGESTONE WITH 3 PIECE RITIES, 17.5-25, BS, L-3 RL 16P	0	NC
TII	RES AVAIL	ABLE FROM TRELLEBORG		
P	559-2595	TIRES, 17.5X25 TL BRAWLER, TR	5; Press on Solid	\$17,520
P	559-2597	Width across tires 2236mm (88"). TIRES, 17.5X25 TL BRAWLER, SM	Press on Solid	\$16,620

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 918M-016

918M

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRIC AT DEALEF
AUA	RDS			
	YDRAULIC Required whe CANNOT BE U	GUARDS n ordering a Canopy with 3 or 4 valve hydraulics. JSED WITH: Any Cabs		
		en ordering Third and Fourth valve, you MUST order d and Fourth Hose Guards.		
	466-2557	GUARD, HOSE, 3 VALVE, STD LIFT Provides hydraulic hose guard. ONLY FOR USE WITH: CANOPY & 451-4344 HYD: 471-6252 HYDRAULICS, 3	RAULICS, 3V/1L	NC
	466-2558	GUARD, HOSE,4 VALVE,HIGH FLOW	0 RAULICS, 4V/1L	NC
	550-7792	GUARD, HOSE, 3 VALVE, HIGH LIFT	0 RAULICS, 3V/1L	\$99
		OSE GUARDS In ordering a Canopy and a loader arrangement with cou	pler.	
	466-2559	GUARD, COUPLER HOSE	IN ON, STD LIFT	NC
THE	R ATTACH	IMENTS		
FE	NDERS			
	469-5852	Provides non-metalic front fenders to help keep the ware Rear tires have non-metalic fender extensions around and rear side of the tire to help keep both machine an ladder clean. Recommended for applications that incleans the dead of the standard part of the side of the standard part of the side of the si	vindshield clean. I the front side nd access	\$418
	469-5853	long load and carry. FENDERS, FULL COVER	keep the extensions ud flaps to nended for	\$625
	504-4713	Provides partial coverage metal front fender deflectors protection to hitch, ladder, and cab from debris throw the front tires. Removes all fender extensions around Recommended for applications such as Industrial & V	s that provides vn up or stuck in the rear tire. Waste where fenders	\$-318
	546-5274	and extensions would be a high risk of impact and da FENDERS, STANDARD, 20.5 TIRES	1	\$418

Supersedes 02JAN2018
Caterpillar: Confidential Green
US-A-19-01 A

Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 918M-017

918M

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight Ibs	LIST PRICE AT DEALER
ОТНЕ	ER ATTACH	HMENTS (CONT.)		
F	ENDERS (C	Cont.)		
L	547-5217	FENDERS, EXT COVER 20.5 TIRES	R V ROADING	\$705
FLUI	DS			
El	NGINE COO	DLANT		
L	450-5406	ENGINE COOLANT, STANDARD		\$208
L	444-1001	ENG COOLNT,A/FREEZE(-50C/-58F)		\$312
Н	YDRAULIC	OIL		
L	450-5405	HYDRAULIC OIL, STANDARD	0	\$1,135
L	444-1000	HYDRAULIC OIL, BIODEGRADABLE	0	\$1,245
DOC	UMENTATI	ON		
D	ECAL PACE	KAGES		
L	476-2741	INSTRUCTIONS, ANSI	0 e USA.	NC
INST	RUCTIONS			
//	ISTRUCTIO	NS AND OPERATION MANUALS		
	421-8926	SERIALIZED TECHNICAL MEDIA KIT Kit will include instructions and parts CD in the lega language, based on the shipping address. Any additional media such as a paper parts manual, kit, can be ordered through the media website. https://oos.midlandcorp.com/CAT/Default.aspx	lly required	NC

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 918M-018

918M

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
NOTI				
. <i>Li</i>	4NE 2/ LAN	IE 3 OPTIONAL SELECTIONS		
STAF	RTERS, BAT	TTERIES, & ALTERNATORS		
S	TARTING A	IDS		
P	474-1982	HEATER, ENGINE COOLANT, 120V		\$198
Р	474-1981	HEATER, ENGINE COOLANT, 240V	0	\$198
ELEC	TRICAL			
LI	GHTS			
Р	260-5501	BEACON, ROTATING		\$389
P	448-9539	switch, wiring, and mounting. LIGHTS, CAB, WORKING HALOGEN Four halogen floodlights mounted beneath cab roof two front, two rear.		\$600
Р	496-9971	LIGHTS, CAB, WORKING LED Four LED floodlights mounted beneath cab roof, two front, two rear.	0	\$820
A	CCESSORY	EQUIPMENT		
L	471-6212	WORKTOOL, WIRING	rk Tools.	\$360
B	ACK-UP AL	ARM		
L	474-1980	ALARM, BACK-UP	0	\$197
OPEF	RATOR ENV	IRONMENT		
A	XLE OSCAL	LATING LIMITER		
L	473-9440	Restricts the rear axle oscillation from 11 degrees of to 9 degrees. When winter tire chains are installed should be equipped with Axle Oscillations Limiters contact between the tire chains and the chassis. B CANNOT BE USED WITH: 561-7108 TIRE, 20.5 R2-561-7109 TIRE, 20.5 R2-561-7110 TIRE, 20.5 R2-	on each side , the axles to prevent olt-on design 5, MX XHA2 5, GY, SGL 12PR	\$94

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 918M-019

918M

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight Ibs	LIST PRICE AT DEALER
OPER	ATOR ENV	IRONMENT (CONT.)		
RA	ADIO PACK	(AGES		
Р	541-4413	RADIO, AM/FM BLUETOOTH		\$550
A	CCESSORY	EQUIPMENT		
Р	279-0643	BLIND, REAR		\$305
Р	471-6921	CANNOT BE USED WITH: CANOPY 463-2089 OR 46 TOOL BOX	ng grease e right side ladder.	\$615
Р	450-4690	CANNOT BE USED WITH: 525-4951 COUNTERWEIG PLATE, LICENSE	0	\$262
GUAI	RDS			
L	539-1317	GUARD, HITCH		\$690
L	539-1318	allowing visibility to service points. GUARD, POWERTRAIN	0	\$985
L	539-1320	access panel for oil changes. GUARD, DRIVE SHAFT	0	\$615
L	539-1322	shaft protection. GUARD, CRANKCASE	0	\$414
L	533-3604	to the engine components GUARD, FRONT LIGHTS	0	\$376
ОТНЕ	R ATTACH	IMENTS		
C	USTOM CO	LOR		
L	549-8076	CUSTOM COLOR	0 g CUSTOM COLOR reques	\$4,450 NET sts.

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY

918M

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight Ibs	LIST PRICE AT DEALER
-----	------------	---------------------	--------------------	-------------------------

BUCKETS

WORKTOOLS

First worktool must ordered as installed, no packing reference required.

Additional buckets must be ordered as 'not installed' and should include packing reference 0G-3281

Performance Series buckets feature a wider moldboard opening angle, longer floor and forward curving (convex) sidebars. These aggressive buckets load easier and retain material better for faster cycle times.

Offered with:

- 1) Bolt-on, reversible cutting edges for maximum durability and smooth grading.
- 2) Bolt-on teeth with pin-on tooth tips for maximum penetration and digging.

All 910/914 PS General Buckets share the following characteristics: Single piece bolt-on cutting edge = 2400mm / 95" wide 8x bolt on adaptors & long tips = 2430mm / 95" wide Performance Fill Factor = 110% (or 0.1cum/0.2cyd) of stated capacity. For correct bucket selection see OMM/specalog which shows max material densities per machine configuration per bucket size.

PIN ON BUCKETS

P	481-9759	BUCKET, GP, 1.8 YD3, PO, BOT	\$6,475 \$6,475 NI
Р	472-6537	FOR USE WITH: 451-4347 BUCKET, GP, 1.8 YD3, PO, BOCE	\$5,751 \$5,751 NI
Р	481-9763	FOR USE WITH: 451-4347 BUCKET, GP, 2.0 YD3, PO, BOT	\$6,747 \$6,747 NI
Р	472-6542	FOR USE WITH: 451-4347 BUCKET, GP, 2.0 YD3, PO, BOCE	\$6,024 \$6,024 NI
P	481-9766	FOR USE WITH: 451-4347 BUCKET, GP, 2.3 YD3, PO, BOT	\$7,106 \$7,106 NI
Р	415-5961	FOR USE WITH: 451-4347 BUCKET, GP, 2.3 YD3, PO, BOCE	\$6,382 \$6,382 NI
Р	481-9767	FOR USE WITH: 451-4347 BUCKET, GP, 2.4 YD3, PO, BOT	\$7,318 \$7,318 NI
Р	415-5927	FOR USE WITH: 451-4347 BUCKET, GP, 2.4 YD3, PO, BOCE	\$6,594 \$6,594 NI
		TOR OOD WITH, TOT TOT!	

918M

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
BUCK	KETS (CON	IT.)		
	_	KETS (Cont.)		
		•	016	¢0. 420
P	498-0033	BUCKET, LM, 3.3YD3, PO, BOCE	816	\$8,429 \$8,429 N
		Light Material bucket. Width 2550mm (100"). Incl. Bo Capacity: 2.5 m3 (3.3 yd3), fill factor 100% FOR USE WITH: 451-4347 LOADER ARR		40, 220
•	498-0036	BUCKET, LM, 3.9YD3, PO, BOCE		\$9,144
		Light Material bucket. Width 2550mm (100"). Incl. Bo Capacity: 3.0 m3 (3.9 yd3), fill factor 100% FOR USE WITH: 451-4347 LOADER ARR	878 olt-on-cutting-edge	\$9,144 N
•	498-0039	BUCKET, LM, 4.6YD3, PO, BOCE	938	\$9,853
		Light Material bucket. Width 2550mm (100"). Incl. Bo Capacity: 3.5 m3 (4.6 yd3), fill factor 100% FOR USE WITH: 451-4347 LOADER ARR	938 olt-on-cutting-edge	\$9,853 NI
17	STD COU	PLER BUCKETS		
•	481-9755	BUCKET, GP, 1.7 YD3, IT, BOT	1,129 1,129	\$6,297 \$6,297 N
_		FOR USE WITH: 472-2513	,	
•	472-6534	BUCKET, GP, 1.7 YD3, IT, BOCE	1,221	\$5,574 \$5,574 N
_	404 0700	FOR USE WITH: 472-2513	, , , , , , , , , , , , , , , , , , , ,	
•	481-9760	BUCKET, GP, 1.9 YD3, IT, BOT	1,173	\$6,647 \$6,647 N
		FOR USE WITH: 472-2513	,	
•	472-6539	BUCKET, GP, 1.9 YD3, IT, BOCE	1,265 1,265	\$5,924 \$5,924 N
		FOR USE WITH: 472-2513	,	
•	481-9762	BUCKET, GP, 2.0 YD3, IT, BOT	1,250 1,250	\$6,747 \$6,747 N
		FOR USE WITH: 472-2513	1,250	90,747 N
Р	472-6541	BUCKET, GP, 2.0 YD3, IT, BOCE		\$6,024
		FOR USE WITH: 472-2513	1,362	\$6,024 N
P	481-9764	BUCKET, GP, 2.2 YD3, IT, BOT	•	\$6,886
		FOR USE WITH: 472-2513	1,301	\$6,886 N
•	390-8219	BUCKET, GP, 2.2 YD3, IT, BOCE	1,393	\$6,163
		FOR USE WITH: 472-2513	1,393	\$6,163 N
•	492-2491	BUCKET, GP, 2.4 YD3, IT, BOCE	1,470	\$6,594
			1,470	\$6,594 N
•	498-0031	FOR USE WITH: 472-2513 BUCKET, LM, 3.3YD3, IT, BOCE		\$8,429 \$8,429 N
		Light Material bucket. Width 2550mm (100"). Incl. Bo Capacity: 2.5 m3 (3.3 yd3), fill factor 100% FOR USE WITH: 472-2513 LOADER ARR		Ψ0,427 N.

918M

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight Ibs	LIST PRICE AT DEALER
BUCK	ETS (CON	IT.)		
	-	PLER BUCKETS (Cont.)		
•	498-0034	BUCKET, LM, 3.9YD3, IT, BOCE	Q 5 <i>1</i>	\$9,144
	498-0034		854	\$9,144 N
		Light Material bucket. Width 2550mm (100"). Incl. Bo Capacity: 3.0 m3 (3.9 yd3), fill factor 100% FOR USE WITH: 472-2513 LOADER ARR		
•	498-0037	BUCKET, LM, 4.6YD3, IT, BOCE	914	\$9,853 \$9,853 N
		Light Material bucket. Width 2550mm (100"). Incl. Bo Capacity: 3.5 m3 (4.6 yd3), fill factor 100% FOR USE WITH: 472-2513 LOADER ARR	2 = -	ψ9,633 N
IS	O WIDE CO	OUPLER BUCKETS		
•	481-9756	BUCKET, GP, 1.7 YD3, ISO, BOT	1,169 1,169	\$6,297 \$6,297 N
5	472-6535	FOR USE WITH: 472-2514 BUCKET, GP, 1.7 YD3, ISO, BOCE	1 261	\$5,574
	472-0535	BUCKET, GF, 1.7 TD3, ISU, BUCE	1,261	\$5,574 N
	401 0761	FOR USE WITH: 472-2514	1 010	66 647
•	481-9761	BUCKET, GP, 1.9 YD3, ISO, BOT	1,213	\$6,647 \$6,647 N
	470.0540	FOR USE WITH: 472-2514	1 205	
•	472-6540	BUCKET, GP, 1.9 YD3, ISO, BOCE	1,305 1,305	\$5,924 \$5,924 N
		FOR USE WITH: 472-2514	·	
•	481-9765	BUCKET, GP, 2.2 YD3, ISO, BOT	1,341 1,341	\$6,886 \$6,886 N
		FOR USE WITH: 472-2514	·	
•	415-5957	BUCKET, GP, 2.2 YD3, ISO, BOCE	1,433 1,433	\$6,163 \$6,163 N
		FOR USE WITH: 472-2514	·	4 0,103 I
•	492-2492	BUCKET, GP, 2.4 YD3, ISO, BOCE	1,470 1,470	\$6,594 \$6,594 N
		FOR USE WITH: 472-2514	•	
•	498-0032	BUCKET, LM, 3.3YD3, ISO, BOCE		\$8,429 \$8,429 N
		Light Material bucket. Width 2550mm (100"). Incl. Bo		90,429 F
		Capacity: 2.5 m3 (3.3 yd3), fill factor 100% FOR USE WITH: 472-2514	3 3	
•	498-0035	BUCKET, LM, 3.9YD3, ISO, BOCE		\$9,144
		Light Material bucket. Width 2550mm (100"). Incl. Bo Capacity: 3.0 m3 (3.9 yd3), fill factor 100%		\$9,144 N
•	498-0038	FOR USE WITH: 472-2514 BUCKET, LM, 4.6YD3, ISO, BOCE	926	\$9,853
	.55 0000		926	\$9,853 N
		Light Material bucket. Width 2550mm (100"). Incl. Bo Capacity: 3.5 m3 (4.6 yd3), fill factor 100% FOR USE WITH: 472-2514	olt-on-cutting-edge	

918M

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight Ibs	LIST PRICE AT DEALER
BUCK	KETS (CON	IT.)		
IS	O WIDE CO	OUPLER BUCKETS (Flat floor)		
Р	488-7005	BUCKET, FF, 1.8 YD3, ISO, WOT		\$7,608 \$7,608 NI
Р	468-4749	FOR USE WITH: 472-2514 BUCKET, FF, 1.9 YD3, ISO, BOCE	1,492 1,492	\$6,663 \$6,663 NI
P	488-7006	FOR USE WITH: 472-2514 BUCKET, FF, 1.9 YD3, ISO, WOT	,	\$8,160 \$8,160 NI
P	468-4750	FOR USE WITH: 472-2514 BUCKET, FF, 2.0 YD3, ISO, BOCE	1,525	\$7,213
P	488-7007	FOR USE WITH: 472-2514 BUCKET, FF, 2.2 YD3, ISO, WOT		\$7,213 NI \$8,775
P	468-4751	FOR USE WITH: 472-2514 BUCKET, FF, 2.3 YD3, ISO, BOCE	1,490 1,436	\$8,775 NI \$7,828
		FOR USE WITH: 472-2514	1,436	\$7,828 NI
FU	USION BUC	KETS		
P	546-4012	BUCKET,GP,2.2 YD3,FUSION,BOCE		\$6,163 \$6,163 NI
P	546-4014	FOR USE WITH: 544-1504 LOADER, FUSION CPLR 544-1505 LOADER, FUSION CPLR, HIGH I BUCKET,GP,2.5 YD3,FUSION,BOCE	LIFT	\$6,594
•	040 4014	FOR USE WITH: 544-1504 LOADER, FUSION CPLR	1,618 R, STD LIFT	\$6,594 NI
Р	549-6912	544-1505 LOADER, FUSION CPLR, HIGH I		\$6,886 \$6,886 NI
P	549-6913	FOR USE WITH: 544-1504 LOADER, FUSION CPLR 544-1505 LOADER, FUSION CPLR, HIGH I BUCKET,GP,2.5 YD3,FUSION,BOT	LIFT	\$7,599
•	343 03 13	FOR USE WITH: 544-1504 LOADER, FUSION CPLR	2, STD LIFT	\$7,599 NI
Р	560-0128	544-1505 LOADER, FUSION CPLR, HIGH I	0	\$8,429 \$8,429 NI
P	560-0129	FOR USE WITH: 544-1504 LOADER, FUSION CPLR 544-1505 LOADER, FUSION CPLR, HIGH I BUCKET, LM, 3.9YD3,FUSION,BOCE	LIFT 0	\$9,144
_		FOR USE WITH: 544-1504 LOADER, FUSION CPLR 544-1505 LOADER, FUSION CPLR, HIGH I	LIFT	\$9,144 NI
Р	560-0130	FOR USE WITH: 544-1504 LOADER, FUSION CPLR 544-1505 LOADER, FUSION CPLR, HIGH	0 R, STD LIFT	\$9,853 \$9,853 NI

918M

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight Ibs	LIST PRICE AT DEALER
BUCK	KETS (CON	IT.)		
	ORK CARRI Please add the	AGES e packing reference 0G-3280.		
Р	390-8288	CARRIAGE, STANDARD COUPLER	lth	\$2,386 NI
P	428-2109	CARRIAGE, WIDE COUPLER	coupler	\$2,386 NI
P	532-8222	CARRIAGE, PAL C3/4, 62", FUS ONLY FOR USE WITH: 544-1504 LOADER, FUSION 544-1505 LOADER, FUSION 544-15	711 ON CPLR, STD LIFT	\$2,610 NI
		TITY OF TWO e packing reference 0G-3304 if ordered 'Not-Installed'.		
P	6W-8900	FORK TINES, 2" X 5" X 48"	251	\$718 NI
P	6W-9739	FORK TINES, 2" X 5" X 53"	343	\$743 NI
P	241-0921	FORK TINE, 2X5X48 OFFSET, RIGHT	207	\$1,572 NI
P	241-0922	FORK TINE, 2X5X48 OFFSET, LEFT	207	\$1,572 NI
Р	553-3872	FORK, PAL C3/4, 47" X 5" X 2"	199	\$765 NI
Р	553-3873	FORK, PAL C3/4, 53" X 5" X 2"	215	\$1,000 NI

FIELD INSTALLED ATTACHMENTS

KITS AVAILABLE ONLY FROM SUPERTRAK

FOB: Punta Gorda, Florida, USA

Order the following kits directly from Supertrak 800.446.9858 --- 941.505.7800 --- www.Supertrak.com Supertrak is responsible for the sales, parts, support and warranty.

All dealer net prices below are for reference only, and are subject to change by Supertrak.

Additional information and pictures are located on DEALER.CAT.COM in the Compact Wheel Loader area.

918M

USE REF LANE 2 / 3 OPTIONAL Ship Weight LIST PRICE lbs AT DEALER

FIELD INSTALLED ATTACHMENTS (CONT.)

KITS AVAILABLE ONLY FROM SUPERTRAK (Cont.)

Note: Reference application specific OSHA requirements (e.g. window mesh spacing standards), particularly in forestry applications.

CT2026-008 KIT, REAR WINDOW GUARD. 3769.92 USD NET Guards provide protection for rear lights, rear window, and rear side corner windows. 3" (75mm) mesh opening with 1/4" (6mm) wire diameter can be customized to meet the application requirements. Side and corner guards open with latches for easy cleaning. Rear center portion is fixed, yet cleaning clearance is provided. Some light welding is required. Estimated installation time: 5 hrs.

CT2026-005 KIT, FRONT WINDOW GUARD. 2650 USD NET Bolt-on kit provides upper and lower front window protection along with upper cab light guarding. 3" (75mm) mesh opening with 1/4" (6mm) wire diameter can be customized to meet the application requirements. Upper window guard opens with overcenter latches for easy window cleaning. Estimated installation time: 3 hrs

CT2026-009 KIT, CAB DOOR SCREENS. 1652.65 USD NET Guards protect the door glass from top to bottom on both side. The guards are hinged for cleaning with bolts for fasteners. 3" (75mm) mesh opening with 1/4" (6mm) wire diameter can be customized to meet the application requirements. Some light welding required.

Estimated installation time: 2.5 hrs

CT2026-007 KIT, LAMP COVER GUARD. 699.97 USD NET Bolt-on lamp guards are reversible from side to side and allow some lamp positioning adjustment. Mesh design incorporates 1" (25mm) squares.

RORO WIRIMS WITIRES

Estimated installation time: 0.5 hrs

0G-3117

PACKING

00-3117	NONO W/NIMO W/TINES	ADID MEI
	Mandatory selection for all non-European shipments.	
	CANNOT BE USED WITH: EU LAST MILE DEALERS	
0G-3281	PACK - BUCKET GROUP (WHL) 0	\$123 NET
423-6175	TRANSPORT GROUP	NC
	Required to ship a machine not fitted with either a coupler or	
	recognica to simp a macinite not need with cities a coupler of	
	an installed pin-on bucket.	

Supersedes 02JAN2018
Caterpillar: Confidential Green
US-A-19-01 A

Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 918M-026

Bid Term: 2/20/19 - 2/19/21

\$315 NET

918M

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
PACKI	NG (CON	IT.)		
	0G-3273	RUST PREVENTATIVE APPLICATOR		\$110 NET
	0G-3280	PACK, MISCELLANEOUS MATERIAL	0	\$212 NET
	0G-3304	PACKING FOR FORK /HOOKS/TINES	0	NC