988K

988K WHEEL LOADER DECATUR, IL, USA

Ship Weight lbs LIST PRICE AT DEALER

Standard Equipment:

POWERTRAIN

Advanced Productivity Electronic Control Shifting (APECS) Air to air aftercooler

Brakes, full hydraulic, enclosed, wet multiple disc service brakes

Electro hydraulic parking brake

Engine, Cat C18 w/ACERT technology

Fuel priming pump (electric)

Fuel to air cooler

Ground level engine shutoff

Guard, transmission

Hydraulically driven demand fan

Integrated braking

Radiator, Next Generation Modular (NGMR)

Separated cooling system Starting aid (ether) automatic

Throttle lock

Torque converter, impeller clutch with lock-up clutch & rimpull control system Turbine precleaner, engine air intake Transmission, planetary powershift,

4F/3R electronic control

ELECTRICAL

Alarm, back-up Alternator, 150-amp

Batteries, maintenance-free, 4-1000 CCA

Converter, 10/15-amp, 24V to 12V Lights, front & rear, access stairway,

turn signals

Starter, electric (heavy duty)

Starter lockout in bumper

Starting receptacle for emergency start

Transmission lockout in bumper

OPERATOR ENVIRONMENT

Air conditioner

Cab, sound-suppressed, pressurized, internal four-post rollover protective

structure (ROPS/FOPS), radio ready for entertainment includes antenna,

speakers, converter (12-volt 10/15-amp)

and power port

Coat and hard hat hooks

E/H tilt & lift controls (seat mounted)

Flip-up armrest

Heater and defroster

Horn, electric

Implement hydraulic lockout

Laminated glass

Light, dome (cab)

Lunchbox and beverage holders

Instrumentation, gauges:

-Engine coolant temperature

-Fuel level

-Hydraulic oil temperature

-Speedometer/Tachometer

-Torque convertor temperature

Instrumentation, warning indicators:

-Action alert system, three category

-Axle/Brake oil temperature (front/rear)

-Brake oil pressure

-Electrical system, low voltage

-Engine failure malfunction alert and

action lamp

Mirrors, rearview (externally mounted)

Parking brake status

Rimpull select switch

Seat, Cat Comfort (cloth) air suspension

STIC control system with steering lock

Tinted glass

Transmission gear (indicator)

Product Link Elite:

-VIMS

-Graphical information display

-External data port

-Customizable operator profiles

Wet-arm wipers/washers (front and rear), intermittent wipers (front and rear)

OTHER STANDARD EQUIPMENT

Automatic bucket tilt/lift kickouts electronically adjustable from cab

Counterweight

Doors, service access (locking)

Ecology drains for engine, radiator,

hydraulic tank

Economy mode with on demand throttle

Emergency platform egress

Engine, crankcase, 250 hour interval

with CJ-4 oil

Engine idle management features:

-Auto idle kickdown

-Delayed engine shutdown

-Engine idle shutdown

Fuel tank, 731 L (188 gal)

Ground level fuel fill

Ground level transmission electronic

clutch pressure control access

Hitch, drawbar with pin

Hoses, Cat XT(TM)

Hydraulic oil cooler

Hydraulic, steering and brake

filtration/screening system

Oil sampling valves

Stairway, left and right rear access

Steering, load sensing

Toe kicks

Vandalism protection caplocks

988K

988K WHEEL LOADER DECATUR, IL, USA

Ship Weight lbs

LIST PRICE AT DEALER

OTHER STANDARD EQUIPMENT (CONT.)

Venturi stack

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY

Effective 02JAN2019 988K-002

988K

		Ship Weight Ibs	LIST PRICE AT DEALER
347-5000	988K WHEEL LOADER HRC	·	\$904,750
0P-4742	988K MISCELLANEOUS MATERIAL	0	NC
	Only reference numbers under the Factory Sourced Kits sec used on a MISC order.	tion can be	

Supersedes 02JAN2018
Caterpillar: Confidential Green
US-A-19-01 A

Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 988K-003

988K

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
LANE	SELECTIO	N		
	0P-9002	LANE 2 ORDER	0	NC
	0P-9003	LANE 3 ORDER	0	NC
SPEC	IAL ARRAI	NGEMENTS		
L	OADER ARI	RANGEMENTS		
L	367-2710	LOADER, STANDARD		NC
L	367-2730	FOR USE WITH LANE 3 ONLY Specialized machine for block handling applications. lift and tilt cylinders, and extra counterweight. Other that can complement this offering are ride control an cooler. REQUIRES: 347-5000 988K WHEEL LOADER HRC 367-2726 LIFT,STANDARD 3V,BLOCK H 424-6490 LUBRICATION or 424-6495 A 347-4940 ENGINE, BRAKE 42PR or ** Tires with HLA Rims 467-5822 or 467-5833 CPM PAYLOAD W	Includes larger attachments ad axle oil IANDLER UTOLUBE	\$31,010
L	367-2720	FOR USE WITH LANE 3 ONLY Specialized machine for log loading millyard applicat larger lift and tilt cylinders, extra counterweight, swiradiator system with wider fin spacing and auto-reveattachments that can complement this offering are riaxle oil cooler. REQUIRES: 347-5000 988K WHEEL LOADER HRC 367-2705 LIFT, STANDARD 3V, MILLYA 424-6490 LUBRICATION or 424-6495 A 550-0284 LIGHTS, LED (MY, SM) 360-8193 CAMERA, REAR VISION 42PR or ** Tires with HLA Rims	ions. Includes ng out ersing fan. Other ide control and	\$40,150

Supersedes 02JAN2018
Caterpillar: Confidential Green
US-A-19-01 A

Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY

988K

JSE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRIC AT DEALER
SPEC	IAL ARRAN	IGEMENTS (CONT.)		
L	OADER ARF	RANGEMENTS (Cont.)		
	552-0032 367-2750	LOADER, STEEL MILL FOR USE WITH LANE 3 ONLY Specialized machine for steel mill slag handling appl Includes transmission and parking brake override stainless steel braided hose guarding (refer to TEKQ) platform to accommodate fire suppression systems, guard, solid metal access ladders, swing out radiato fin spacing and auto-reversing fan. Ecosafe oil is rec REQUIRES: 347-5000 988K WHEEL LOADER HRC 367-2715 LIFT, STANDARD or 367-272 548-2125 LUBRICATION or 548-2130 of 550-0284 LIGHTS, LED (MY, SM) 523-6588 CAB, STEEL MILL 441-5220 MIRRORS, STANDARD (SM) 360-8193 CAMERA, REAR VISION 519-9951 FUEL TANK, STANDARD (SM) 435-1155 GUARDS, HEAVY DUTY 541-7900 COOLER, AXLE OIL (MY, SM) 467-5822 or 467-5833 CPM PAYLOAD VERTICAL STORMS (STORMS) 557-9861 KIT, AXLE OSCILLATION STORMS	ications. ystems, steel roof, 1464), reinforced brake accumulator r system with wide ommended. 5 LIFT, HIGH r 548-2135 AUTOLUBE or 435-1223 GUARD WEIGHING	\$34,950 \$21,350
		FOR USE WITH LANE 3 ONLY Provides reversing fan feature, lower cooling fin dens core cleaning access. REQUIRES: 347-5000 988K WHEEL LOADER HRC 472-7125 or 516-3924 LIFT, EZ CLEAN 467-5822 or 467-5833 CPM PAYLOAD V 6, AND LINKAGES		
LI	FT ARRANG	GEMENTS		
	Please pay att selection.	ention to compatibility, it is dependent on Loader		
	347-4900	LIFT, STANDARD 2V		NC
	347-4910	ONLY FOR USE WITH: 367-2710 or 367-2719 LC LIFT, STANDARD 3V	ions, loading 30/40	\$9,030
	347-4920	ONLY FOR USE WITH: 367-2710 or 367-2719 LC LIFT, HIGH 2V	pplication where	\$7,960

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 988K-005

988K

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight Ibs	LIST PRICE AT DEALER
BOON	MS, STICKS	S, AND LINKAGES (CONT.)		
LII	FT ARRANG	GEMENTS (Cont.)		
-	347-4930	FOR USE WITH LANE 3 ONLY Provides high lift with 3-valve function. Recommended for loading 50/70 ton trucks or any maximum dump clearance is desired. ONLY FOR USE WITH: 367-2710 or 367-2719 LCC	application where	\$17,000
L	367-2726	LIFT, STANDARD 3V, BLOCK HANDLER FOR USE WITH LANE 3 ONLY Provides standard lift height linkage with application design, tilt lever guard, and 3V hydraulics.		\$9,030
L	367-2705	FOR USE WITH LANE 3 ONLY Provides standard lift height linkage with application and 3V hydraulics. ONLY FOR USE WITH: 367-2720 or 367-2729 LO	7,620 n specific design	\$9,030
	367-2715	LIFT, STANDARD 2V, STEEL MILL	d rear bumper	\$1,445
	367-2725	ONLY FOR USE WITH: 552-0032 or 552-0034 LC LIFT, HIGH 2V, STEEL MILL	7,813 ar bumper with	\$9,400
	472-7125	LIFT, STANDARD 2V, EZ CLEAN FOR USE WITH LANE 3 ONLY ONLY FOR USE WITH: 367-2750 LOADER, EZ C	0	\$3,450
	516-3924	ONLY FOR USE WITH: 367-2750 LOADER, EZ C. LIFT, HIGH 2V, EZ CLEAN FOR USE WITH LANE 3 ONLY ONLY FOR USE WITH: 367-2750 LOADER, EZ C.	0	\$11,400
LU	JBRICATIO	N ARRANGEMENTS		
(automatic greation the Lift Ar. Trouble free pe	option provides a LINCOLN INDUSTRIAL CORP. "CENT asing system for 18 lube locations requiring lubrication This arrangement is powered using hydraulic oil for erformance and includes a 60 lb. reservoir. Special		

guarding is added when needed to protect lines or valve components. Tank or reservoir can be filled from a remote location at ground

level or at the tank port.

Please pay attention to compatibility, it is dependent on Lift selection.

L	367-5610	LUBRICATION, STANDARD	NC
L	367-5580	AUTOLUBE, CENTROMATIC	\$15,960
		ONLY FOR USE WITH: LIFT, STANDARD	
L	367-5585	AUTOLUBE, CENTROMATIC	\$15,960
		ONLY FOR USE WITH: LIFT HIGH	

988K

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight Ibs	LIST PRICE AT DEALER
BOOI	MS, STICKS	S, AND LINKAGES (CONT.)		
L	JBRICATIO	N ARRANGEMENTS (Cont.)		
L	424-6490	LUBRICATION, STANDARD (BH, MY) FOR USE WITH LANE 3 ONLY ONLY FOR USE WITH: 367-2726 LIFT,STANDARD	O 3V,BLOCK HANDLER	NC
L	424-6495	367-2705 LIFT, STANDAR AUTOLUBE, CENTROMATIC (BH, MY) FOR USE WITH LANE 3 ONLY ONLY FOR USE WITH: 367-2726 LIFT, STANDARI 367-2705 LIFT, STANDAR	459 O 3V,BLOCK HANDLER	\$15,960
L	548-2125	LUBRICATION, STANDARD (SM)	D 2V, STEEL MILL	NC
L	548-2130	AUTOLUBE, CENTROMATIC (SM)	0	\$15,960
L	548-2135	ONLY FOR USE WITH: 367-2715 LIFT, STANDAR AUTOLUBE, CENTROMATIC (SM)	0	\$15,960
POW	ERTRAIN			
El	VGINE ARR	ANGEMENTS		
L	366-1928	ENGINE, STANDARD	OADER HRC	NC
L	347-4940	CANNOT BE USED WITH: 367-2730 LOADER, BLOC ENGINE, BRAKE		\$2,900
El	VGINE PREC	CLEANERS		
L	377-9320	PRECLEANER, STANDARD		NC
L	377-0851	PRECLEANER, DUAL	37	\$2,795
A	XLE ARRAI	NGEMENTS		
L	347-5246	AXLES, STANDARD	0	NC
L	347-5256	AXLES, NO-SPIN REAR	Vith normal hard e wear. improved traction.	\$4,780

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY

988K

USE REF LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
------------------------------	--------------------	-------------------------

SUSPENSION SYSTEMS

RIDE CONTROL

The ride control option provides a suspension system by placing two accumulators in the lift circuit. Manual off and automatic mode selection. In auto mode the suspension system engages when reaching preset value. It reduces bounce caused by bucket-induced loads when traveling loaded or unloaded. For use in high speed roading, load and carry, and any other application in which load retention, bucket spillage, or operator ride may be a problem. This option is ideal for government bid specifications.

L	347-4973	NO RIDE CONTROL	NC
L	478-3882	RIDE CONTROL	\$9,980
L	478-3884	RIDE CONTROL (EU)	\$9,980
L	541-7880	RIDE CONTROL (SM)	\$12,900
L	541-7890	RIDE CONTROL (SM) (EU)	\$12,900
HYD	RAULICS		
L	470-5053	ACCUMULATORS0 AVAILABLE FOR: ALL REGIONS EXCEPT EU	NC
L	470-5043	ACCUMULATORS (EU)	NC
LINE	GROUPS		
s	TEERING		
L	376-6936	STEERING, STANDARD	NC
L	376-6937	STEERING, SECONDARY	\$8,460

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY

988K

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
ELEC	CTRICAL			
L	IGHTS			
L	345-0538	Provides the following: Front flood/running lights (4 Halogen/all facing for Rear flood lights (4 Halogen/all facing rear) and 2 to Upper ROPS lights (6 Halogen/2 facing rear and 4 f CANNOT BE USED WITH: 367-2720 or 367-2729 LO 552-0032 or 552-0034 LO	ward) aillights acing forward) ADER, MILLYARD ADER, STEEL MILL	NC
L	360-8184	LIGHTS, HID	facing forward) and 2 taillights logen/2 facing ADER, MILLYARD	\$2,535
L	550-0283	LIGHTS, LED	d) hts g forward) ADER, MILLYARD	\$3,855
L	550-0284	LIGHTS, LED (MY, SM) FOR USE WITH LANE 3 ONLY Provides the following: Front flood/running lights (4 LED/all facing forward Rear flood lights (4 LED/all facing rear) and 2 taillig Upper ROPS lights (8 LED/2 facing rear and 6 facing ONLY FOR USE WITH: 367-2720 or 367-2729 LO 552-0032 or 552-0034 LO	d) hts ig forward) ADER, MILLYARD	\$5,160
OPE	RATOR ENV	IRONMENT		
C	AB PACKA	GES		
		t seat belts are standard. 4-point seat belts are ugh parts distribution if needed.		
L	540-2511	CAB, BASIC		\$3,170

Supersedes 02JAN2018
Caterpillar: Confidential Green
US-A-19-01 A

Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY

988K

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight Ibs	LIST PRICE AT DEALER
OPEI	RATOR ENV	IRONMENT (CONT.)		
С	AB PACKA	GES (Cont.)		
L	540-2512	CAB, BASIC PLUS INCLUDES: -Cab door, sliding window (LH) -Cab glass, standard -Cab precleaner, non-powered -Seat, heated & ventilated -Seat belt, 3", 2-point, minder -Radio, CB (ready)	0	\$4,290
L	544-1162	CANNOT BE USED WITH: 552-0032 or 552-0034 LC CAB, DELUXE INCLUDES: -Cab door, standard window (LH) -Cab glass, rubber mounted -Cab precleaner, powered -Seat, heated & ventilated -Seat belt, 3", 2-point, minder -Radio, CB (ready) CANNOT BE USED WITH: 552-0032 or 552-0034 LC	0	\$14,040
-	523-6588	CARNOT BE OSED WITH, 352-0032 of 352-0034 ECCAM, STEEL MILL INCLUDES: -Cab door, standard window (LH) (SM) -Cab glass, rubber mounted -Cab precleaner, powered -Seat, standard -Seat belt, 3", 2-point, minder -Radio, CB (ready) ONLY FOR USE WITH: 552-0032 or 552-0034 LC	0	\$11,770
N	MRRORS			
-	346-3864	MIRRORS, STANDARD	DADER, STEEL MILL	NC
•	376-7034	MIRRORS, HEATED	6	\$119
-	441-5220	MIRRORS, STANDARD (SM) FOR USE WITH LANE 3 ONLY Provides mirrors with metal back for steel mill applie ONLY FOR USE WITH: 552-0032 or 552-0034 LC	eations.	NC
//	V <i>TEGRATED</i>	OBJECT DETECTION SYSTEM		
L	360-8191	CAMERA, REAR VISION	enhance operator information only mation about	NC

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY

988K

				
USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight Ibs	LIST PRICE AT DEALER
OPE	RATOR ENV	IRONMENT (CONT.)		
		OBJECT DETECTION SYSTEM (Cont.)		
	360-8193		0	NC
_	300-6193	CAMERA, REAR VISION	enhance operat information only mation about ADER, MILLYARD ADER, STEEL MILL	NC
	372-3042	DETECTION, OBJECT (RADAR) Not available for EU. Provides an object detection system (camera & radar operator awareness of surroundings. This system us radar information in order to provide the operator wi information about the work area to the rear of the wl For a list of countries that RF radar is approved for unttps://dealer.cat.com/detect ONLY FOR USE WITH: 367-2710 or 367-2719 LO 367-2730 or 367-2739 LO	to enhance es visual and th additional neel loader. use in, visit ADER, STANDARD	\$2,795
TFC	HNOLOGY P	PRODUCTS		
	PRODUCT LII			
,	AUDUCT LII	VA		
	location, opera effectively mor on schedule, r	enables the remote transmission of information about the ation, and condition of your equipment. Efficiently and nitor performance of your assets to help keep your jobs maintain equipment condition, and reduce the costs of perating your fleet.	ne	
	https://Deale	varies by country, please reference r.cat.com/PL/Certification for certified countries. tyour Caterpillar marketing representative with		
L	509-4155	PRODUCT LINK, CELLULAR PLE641 Product Link Elite series PLE641 offers expanded co 3G UMTS and CDMA2000 as well as 2G GSM and C transmit location, utilization and condition information in Product Link's remote monitoring web interface. C provides capabilities for frequent transmission and land	verage including DMA cellular networks to on for viewing cellular technology	NC
L	509-4150	data. PRODUCT LINK, SATELLITE PLE631	work to transmit wing in Product	\$432
FUE	L SYSTEMS			
F	FUEL TANKS			
L	519-9949	FUEL TANK, NON-FAST FILL		NC

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 988K-011

988K

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight Ibs	LIST PRICE AT DEALER
	SYSTEMS UEL TANKS			
L	519-9950	FUEL TANK, FAST FILL		\$1,930
L	519-9951	FUEL TANK, STEEL MILL	er port for	\$2,235
FU	JEL LINES			
L	433-3842	FUEL LINES, NON-HEATED	0	NC
L	433-3843	FUEL LINES, HEATED	16	\$1,030

TIRES, RIMS, AND WHEELS

Due to industry-wide tire availability limitations, tire brand and type cannot be guaranteed. Every effort will be made to satisfy your tire choice. However, if the tire type cannot be supplied we will contact the dealer to propose alternatives. The dealer needs to choose between an alternative tire or a "rims only" option (where available) within 72 hours. If no response is provided by the deadline, the order will default to the alternative tire and will be changed at that point. As a consequence of a possible tire change, the total machine price will be decreased or increased depending on the price of the new tire

NOTE: All tires are tubeless, include heavy duty rims and come in a set of 4.

NOTE: 42PR tires may be used to improve lateral stability. Recommended for use with uneven floors and/or high truck loading heights with dense materials.

NOTE: Tires with HLA rims have tires mounted on rims for Heavy Load Applications. These are required for machines in block handler and millyard applications and any other application where higher loads may be encountered.

NOTE: Block Handler and Millyard orders require 42PR or ** tires with HLA rims.

988K

JSE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight Ibs	LIST PRICE AT DEALER
ΓIRES	S, RIMS, AI	ND WHEELS (CONT.)		
TI	RES AVAIL	ABLE FROM BRIDGESTONE		
•	490-7503	TIRES, 35/65-33 BS 42PR L5	Rim=28"x33" 4 piece um damage protection	\$8,180
•	452-4111	CANNOT BE USED WITH: Block Handler or Millyard TIRES, 35/65-33 BS 42PR L5 HLA	rims. d applications and	\$13,980
•	490-7504	TIRES, 35/65R33 BS VSNT ** L4	0 Rim=28"x33" 4 piece n moderate rock	\$-1,240
•	493-6840	CANNOT BE USED WITH: Block Handler or Millyard TIRES, 35/65R33 BS ** L4 HLA	rims. d applications and	\$4,560
•	499-5790	TIRES, 35/65R33 BS VSDL ** L5 Bridgestone Radial; Tread Depth=95mm (120/32"); F Suitable for severe rock environments where maximu is needed.	2,772 Rim=28"x33" Im damage protection	\$13,320
	452-4118	CANNOT BE USED WITH: Block Handler or Millyard TIRES, 35/65R33 BS ** L5 HLA Bridgestone Radial VSDL IDU with Heavy Load Appli HLA rims are required for block handler and millyard any other application where higher loads may be end	1,610 cation rims.d applications and	\$25,240
TI	RES AVAIL	ABLE FROM GOODYEAR		
•	480-9750	TIRES, 35/65R33 GY RT-5D ** L5	n=28"x33"	\$21,790
•	480-9751	CANNOT BE USED WITH: Block Handler or Millyard TIRES, 35/65R33 GY ** L5 HLA	rims. d applications and	\$27,590
TI	RES AVAIL	ABLE FROM MICHELIN		
•	396-4288	TIRES, 35/65R33 MX ** L5	/32"); Rim=28"x33" s where maximum	\$32,380
•	478-4157	CANNOT BE USED WITH: Block Handler or Millyard TIRES, 35/65R33 MX *** L4	0 Rim=28"x33" bility, and	\$10,080

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY

988K

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight Ibs	LIST PRIC
TIRES	S, RIMS, AI	ND WHEELS (CONT.)		
TI	IRES, ALLO	WANCE FOR OMISSION		
•	396-4156	RIMS ONLY, TIRES OMITTED		\$-38,340
P	442-6345	CANNOT BE USED WITH: Block Handler or Millyard or RIMS ONLY (HLA), TIRES OMITTED	9,152 required for	\$-32,540
ОТНЕ	ER ATTACH	HMENTS		
S	OUND SUP	PRESSION		
L	347-5105	NO SOUND SUPPRESSION	OADER HRC	NC
L	347-5125	SOUND SUPPRESSION	298 6	\$4,880
W	HEEL CHO	CKS		
L	541-8669	NO WHEEL CHOCKS	ADER, STANDARD or	NC
L	541-8671	NO WHEEL CHOCKS (EZ CLEAN)	0 ADER, MILLYARD or	NC
L	0P-4780	NO WHEEL CHOCKS (SM)	0	NC
L	541-8670	WHEEL CHOCKS	0 eem. ED	\$1,700
FLUI	DS			
H	YDRAULIC	OIL		
L	435-1144	HYDRAULIC OIL, STANDARD	0	NC
L	435-1164	HYDRAULIC OIL, ARCTIC	of standard	\$6,236
L	435-1154	temperature down to -40C (-40F). HYDRAULIC OIL, ECOSAFE	89	\$3,750

Supersedes 02JAN2018
Caterpillar: Confidential Green
US-A-19-01 A

Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 988K-014

988K

JSE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight Ibs	LIST PRICE AT DEALER
PEC	IAL ARRAN	IGEMENTS		
	367-5432	COOLER, AXLE OIL Axle oil cooler attachment is recommended with ride of downhill grades or any high braking applications. ONLY FOR USE WITH: 367-2710 or 367-2719 LOA 367-2730 or 367-2739 LOA	ontrol for long DER, STANDARD	\$11,200
	541-7900	COOLER, AXLE OIL	an system DER, MILLYARD DER, STEEL MILL	\$10,320
	435-1223	GUARD, HYDRAULIC TANK	19	\$146
TAR	RTERS, BAT	TERIES, & ALTERNATORS		
S	TARTING A	RRANGEMENT		
	374-6450	STARTING, COLD WEATHER		\$1,730
S	TARTING A	IDS		
	374-7404	HEATER, ENGINE COOLANT, 120V	1	\$353
LEC	TRICAL			
	376-7128	LIGHT, WARNING (LED STROBE)* ***DEALER INSTALLED ATTACHMENT***	17	\$700
PER	ATOR ENV	TRONMENT		
	504-5735	RADIO, AM/FM/AUX	0	\$735
	376-7135	RADIO, AM/FM/AUX/USB/BT/CD/SAT BlueTooth radio technology enables the use of a hands such as listening to music and making phone calls. Authorization varies by country, please contact your C representative with questions or click on the link below https://dealer.cat.com/en/products/technology.html Requires service contract with satellite radio provider.	s free function cat marketing v:	\$1,630
-	346-3863	VISOR, CAB	2	\$171
	143-3604	MIRRORS, HANDRAIL MOUNTED		\$595

988K

USE REF LANE 2 / 3 OPTIONAL Ship Weight LIST PRICE lbs AT DEALER

TECHNOLOGY PRODUCTS

SOFTWARE ENABLED ATTACHMENTS (SEA) INSTRUCTIONS

Technology apps are activated by Software Enabled Attachments (SEA). SEAs are available factory installed or can be purchased for dealer installation.

Refer to Information Release Memo (IRM) EES03 -01 (media number PELJ0138) in the Caterpillar Media Information Center for further explanation of SEAs. Select the Product Support tab and search for number PELJ0138. Refer to REHS1238 & REHS8401 for how to obtain a Factory Level Password. Contact FPS: Internet with Corporate Web Security (CWS) (https://fps.cat.com/).

CAT PRODUCTION MEASUREMENT (CPM) PAYLOAD WEIGHING SYSTEM Cat Production Measurement (CPM) includes an integrated onboard payload weighing scale. This measures and/or records:

- -Payload weight, material ID, truck ID, cycle (bucket dumps) count and fuel consumption
- -Allows on-the-go weighing of the bucket payload during the lift cycle
- -Daily payload total (tonnes/tons), productivity (tonnes/hour or tons/hour) and efficiency (tonnes/liter or tons/gal) data is reported wirelessly via Product Link to the VisionLink fleet management web portal (Cat Essentials Product Link subscription required).
- -Detailed payload, productivity & efficiency data can be downloaded to a laptop computer for analysis in the optional VIMSpc software (VIMSpc & VIMS data cable are required, but VIMS is NOT required.)
- -Payload tickets can be printed with an optional printer

Refer to the Cat Connect Payload Technologies intranet page (https://dealer.cat.com/payload) for complete technical specifications; operation, sales, marketing and technical support publications.

NOTES:

- 1) Demo and permanent software are available from the factory.
- 2) For field installation, permanent software can be purchased through the Caterpillar Feature Protection System and enabled by a dealer technician with Cat ET and an SEA password. SEA p/n 433-2014. Consult ANTARES parts distribution system for latest SEA price.
- 3) Both demo and permanent software require calibration prior to customer use.

CALIBRATION INSTRUCTIONS

This app requires calibration and set-up by either the dealer or customer. Refer to the Systems Operation Test & Adjust manual UENR7119 for system calibration, material and truck ID lists set-up and operation instructions.

988K

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight Ibs	LIST PRICI AT DEALER
TECH	INOLOGY F	PRODUCTS (CONT.)		
L	467-5822	CPM PAYLOAD WEIGHING READY	aler enabled for t be enabled by juired. chase of software	NC
L	467-5833	CPM PAYLOAD WEIGHING	0 M. Software is prior to customer	\$6,180
L	378-8634	PRINTER, PAYLOAD	5	\$2,460
COOL	LING			
L	347-5185	COOLING, HIGH AMBIENT		NC
TIRES	S, RIMS, AI	ND WHEELS		
TI	RE PRESSU	IRE MONITORING SYSTEM		
L	543-7141	MONITORING, TIRE PRESSURE	of each tire along and temperature in on is shared with ided through target range.	\$3,000
GUAF	RDS			
L	435-1165	GUARD, BOTTOM	104	\$3,020
L	372-9038	GUARD, CRANKCASE	107	\$715
L	347-5138	GUARD, STEERING CYLINDER	103	\$1,295

988K

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight Ibs	LIST PRICE AT DEALER
GUAI	RDS (CON	Т.)		
L	435-1155	GUARDS, HEAVY DUTY FOR USE WITH LANE 3 ONLY Includes a front guard and tilt cylinder rod guard, in the guards below: 435-1165 GUARD, BOTTOM 372-9038 GUARD, CRANKCASE 347-5138 GUARD, STEERING CYLINDER REQUIRED BY: 552-0032 or 552-0034 LOADER, S	addition to	\$4,790
ОТНЕ	ER ATTACH	IMENTS		
M	ISCELLANE	OUS ATTACHMENTS		
L	459-6446	COVER, INLET GRILL (CW)	weather. lF) and below. OADER HRC and	\$3,585
L	347-5028	FENDERS, ROADING		\$5,090
-	376-1572	OIL CHANGE SYSTEM, HIGH SPEED Provides remote port and components for high speed		\$585
A	GGREGATE	HANDLER		
L	481-3972	AGGREGATE HANDLER, STD LIFT	Handler, which e-handling	\$13,770
L	481-3973	AGGREGATE HANDLER, HIGH LIFT	Handler, which e-handling	\$21,210

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 988K-018

988K

USE REF LANE 2 / 3 OPTIONAL Ship Weight LIST PRICE Ibs AT DEALER

BUCKETS

For questions on buckets intended for Machine Orders please contact your Marketing Subsidiary Machine Coordinator.

Loose buckets should be ordered on a MISC Order through Caterpillar Work Tools - Wamego using source code OP-0672. For availability of loose buckets please email worktools@cat.com.

If you are going to order a loose bucket from CWTS and a machine from Aurora and if you need them shipped at the same time then you need to cross-reference the MSO's with each other.

"GET" is NOT automatically included on bucket orders. "GET" must be entered on the order with your bucket selection, unless text for bucket states otherwise. Please make the "GET" selection from the "GET" listed immediately following the bucket listing. Rock bucket selections list "GET" for spade or straight edge.

Material density will determine the appropriate capacity bucket. Refer to the Specalog. Exceeding maximum payload may cause loader instability.

All listed Maximum Recommended Material Densities are based on the maximum gross weight that the 988K is rated for minus the weight of the bucket and all required G.E.T. at 100% fill factor.

EXPORT ORDERS - If you are ordering a LOADER, STANDARD & BUCKET, then you must order your BUCKET as Not Installed (NI).

GENERAL PURPOSE BUCKETS

Use for excavating and bank loading material requiring breakout force as well as stockpile / rehandling applications. Includes casted corner in sidebar for Corner Guard System GET.

P	347-4980	BUCKET-GP, 152" 9.00 YD3	\$47,653 \$47,653 NI
		Maximum Recommended Material Density: 1660 kg/m3 (2800 lb/yd3)	
		6.7M3(8.7YD3) w/bolt-on adapters, K110, 3988mm (157") wide	
		6.9M3(9.0YD3) w/bolt-on adapters & segments, K110, 3988mm (157") wide	
		6.9M3(9.0YD3) w/bolt-on cutting edge system, 3962mm (156") wide	
Р	347-4990	BUCKET-GP, 152" 10.00YD3	\$50,201
		10,536	\$50,201 NI
		Maximum Recommended Material Density: 1510 kg/m3 (2550 lb/yd3)	
		7.4M3(9.7YD3) w/bolt-on adapters, K110, 3988mm (157") wide	
		7.6M3(10.0YD3) w/bolt-on adapters & segments, K110, 3988mm (157") wide	
		7.6M3(10.0YD3) w/bolt-on cutting edge system, 3962mm (156") wide	

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 988K-019

988K

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight Ibs	LIST PRICE AT DEALER
BUC	KETS (CON	IT.)		
G	SENERAL PU	IRPOSE BUCKETS (Cont.)		
•	435-4029	BUCKET-GP, 152" 11.00 YD3	11,005	\$51,649 \$51,649 NI
)	472-0120	Maximum Recommended Material Density: 1450 k 8.2M3(10.7YD3) w/bolt-on adapters, K110, 3988n 8.4M3(11.0YD3) w/bolt-on adapters & segments, I 8.4M3(11.0YD3) w/bolt-on cutting edge system, 38 BUCKET-GP, 152" 12.50YD3	nm (157") wide K110, 3988mm (157") wide 962mm (156") wide 11,828	\$55,761
		Maximum Recommended Material Density: 1590 kg 9.3M3(12.2YD3) w/bolt-on adapters, K110, 3988ng 9.6M3(12.5YD3) w/bolt-on adapters & segments, Ig 9.6M3(12.5YD3) w/bolt-on cutting edge system, 38 REQUIRES: 481-3972 AGGREGATE HANDLER, ST 481-3973 AGGREGATE HANDLER, HI	nm (157") wide K110, 3988mm (157") wide 962mm (156") wide CD LIFT or	\$55,761 NI
G	_	ERAL PURPOSE BUCKETS anting hardware)		
•	208-5262	CUTTING EDGE, BOLT-ON		\$2,736
	174-7950	GUARD, CORNER	304	\$1,057
	232-0167	ADAPTERS, BOLT ON, SET OF 8	555	\$3,968
	217-4652	SEGMENTS, BOLT-ON, SET OF 7	695	\$1,897
•	309-1123	TIP, PENETRATION	mpact, low-to-moderate	\$128
	309-1127	TIP, GENERAL DUTY Recommended for general application in moderate conditions. Good penetration, (2) self-sharpening concly FOR USE WITH: K110 adapters	impact and abrasive	\$129
•	309-1122	TIP, EXTRA DUTY	nore wear material in	\$163
		ONLY FOR USE WITH: K110 adapters		

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY

988K

USE REF NO. LANE 2 / 3 OPTIONAL	p Weight LIST PRI lbs AT DEALI	
---------------------------------	-----------------------------------	--

BUCKETS (CONT.)

ROCK BUCKETS

Use for bank or face loading in most tough digging conditions.

For GCN1 dealers only:

Buckets in this section need to be ordered through a separate CMOPS order to CWTS, even if required for a new machine order. Please include the machine MSO on your bucket order. Please communicate with your local Sales Rep to confirm bucket price before placing your order into the system.

Р	498-9988	BUCKET-ROCK, 158" 8.30YD3	\$65,307
		10,781	\$65,307 NI
		SPADE EDGE	
		Maximum Recommended Material Density: 1771 kg/m3 (2985 lb/yd3)	
		INCLUDES: (8) weld-on double strap Advansys adapters, outer side wear	
		plates, and 35mm bolt-on heel plates.	
		OPTIONAL: sidebar protectors and base edge wear plates	
		REQUIRES: (8) Advansys 130 tips and (1) segment group	
Р	498-9990	BUCKET-ROCK, 158" 9.00YD3	\$67,390 \$67,390 NI
		SPADE EDGE	40.,000
		Maximum Recommended Material Density: 1643 kg/m3 (2769 lb/yd3)	
		INCLUDES: (8) weld-on double strap Advansys adapters, outer side wear	
		plates, and 35mm bolt-on heel plates.	
		OPTIONAL: sidebar protectors and base edge wear plates	
		REQUIRES: (8) Advansys 130 tips and (1) segment group	
Р	498-9992	BUCKET-ROCK, 158" 10.00YD3	\$70,728
•	+30-333 <u>2</u>	11,627	\$70,728 NI
		SPADE EDGE	970,720 NI
		Maximum Recommended Material Density: 1491 kg/m3 (2514 lb/yd3)	
		INCLUDES: (8) double strap Advansys adapters, outer side wear	
		plates, and 35mm bolt-on heel plates.	
		OPTIONAL: sidebar protectors and base edge wear plates	
		REQUIRES: (8) Advansys 130 tips and (1) segment group	
	OFT (DOO	W DUOWETO	

GET for ROCK BUCKETS

	(includes mou	inting hardware)	
P	109-9051	SEGMENT, BOLT-ON, SET OF 7	\$2,232
Р	107-3533	40mm thick. Use with SPADE buckets. SEGMENTS,HD, BOLT-ON, SET OF 7	\$2,460
Р	124-6346	45mm thick. Use with SPADE buckets. SEGMENTS,H.A.,BOLT-ON,SET OF 7	\$2,679
	124-0340	45mm thick, Half Arrow. Use with SPADE buckets.	Ψ2,079
Р	232-0161	SEGMENTS,H.A.,BOLT-ON,SET OF 7	\$2,849
		Includes 45mm thick half-arrow protectors and top-mounted wear plates.	
Р	381-4095	TIP, HEAVY PENETRATION	\$350
Р	381-4096	ONLY FOR USE WITH: Advansys 130 adapters TIP, HEAVY ABRASION	\$379
_	000 0704	ONLY FOR USE WITH: Advansys 130 adapters	4000
Р	368-3791	TIP, HEAVY DUTY	\$290
P	368-3857	TIP, HVY DUTY LONG LIFE (ARM)59	\$521
		ONLY FOR USE WITH: Advansys 130 adapters	

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 988K-021

988K

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight Ibs	LIST PRICE AT DEALER
BUCK	ETS (CON	IT.)		
GE	T for ROC	K BUCKETS (Cont.)		
P	486-6524	TIP HEAVY ABR LONG LIFE (ARM)	69	\$682
	368-3859	TIP, SHORT	45	\$197
	381-4094	ONLY FOR USE WITH: Advansys 130 adapters TIP, GENERAL DUTY	51	\$228
	368-3860	TIP, COAL	44	\$197
	356-6437	PROTECTORS, SIDEBAR, SET OF 2		\$1,118
	494-8224	PROTECTORS, SIDEBAR, SET OF 4		\$2,265
	364-6636	ONLY FOR USE WITH: ROCK BUCKETS ONLY PLATE GP-WEAR	195	\$535
HE	AVY DUT	Y ROCK BUCKETS		
	Jse for bank of	or face loading in high abrasion and moderate impact		
	498-9994	BUCKET-ROCK, 160" 8.30YD3	14,072 m3 (2985 lb/yd3) ters, cutting edge dius liner, f arrow segment	\$78,378 \$78,378 NI
HE	AVY DUT	Y GRANITE BUCKETS		
•	498-9996	BUCKET-ROCK, 157" 8.30YD3	16, 455 16, 455	\$90,776 \$90,776 NI
		SPADE EDGE Maximum Recommended Material Density: 1658 kg/ INCLUDES: (7) weld-on Advansys 130 flushmount ac cutting edge with weld-on base edge end protection a full shell liner, inside and outside wear plates, bolt-or edge protection, (1) 45mm bolt-on half arrow segmen covers, 25mm bolt-on base edge bottom wear plates, (2) sets of sidebar protectors, 30-Series MAWPs for b protection and a stronger rock guard design. RECUMES: (7) Advances 130 tips	m3 (2795 lb/yd3) lapters on a 64mm thick dapter covers, n top cutting t group with top heel shrouds,	

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 988K-022

REQUIRES: (7) Advansys 130 tips

988K

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight Ibs	LIST PRICE AT DEALER
BUCK	KETS (CON	IT.)		
IR	ON ORE BU	JCKETS		
P	498-9998	BUCKET-ROCK, 154" 6.20YD3	12,767 12,767	\$69,969 \$69,969 NI
		Iron ore design w/ lower capacity SPADE EDGE		
		Maximum Recommended Material Density: 2412 kg INCLUDES: (7) weld-on Advansys 130 double strap thick cutting edge with weld-on base edge end prote radius liner, inside and outside wear plates, (1) 75m arrow segment group, 22mm bolt-on base edge bott 35mm weld-on heel plates, (2) sets of sidebar protect REQUIRES: (7) Advansys 130 tips	adapters on a 64mm ection floor liner, nm bolt-on half com wear plates,	
		ROCK / HD GRANITE / IRON ORE BUCKETS unting hardware)		
P	381-4095	TIP, HEAVY PENETRATION		\$350
P	381-4096	ONLY FOR USE WITH: Advansys 130 adapters TIP, HEAVY ABRASION	easier-to-penetrate	\$379
SE	ERRATED E	DGE BUCKETS		
P	416-5162	BUCKET-ROCK, 156" 9.0 YD3	12,421 12,421	\$62,107 \$62,107 NI
		SERRATED V-SPADE EDGE Maximum Recommended Material Density: 1660 kg	g/m3 (2800 lb/yd3)	
P	428-9115	BUCKET-ROCK, 156" 8.30 YD3		\$60,007 \$60,007 NI
		SERRATED V-SPADE EDGE Maximum Recommended Material Density: 1810 kg	g/m3 (3050 lb/yd3)	
C	OAL BUCKI	ETS		
P	433-4750	BUCKET-COAL, 162" 15.0 YD3	13,278	\$50,029
		STRAIGHT EDGE Maximum Recommended Material Density: 1130 kg INCLUDES: Bolt-On Cutting Edge (BOCE)	13,278 g/m3 (1910 lb/yd3)	\$50,029 NI
•	433-4740	BUCKET-COAL, 162" 17.0 YD3	14,186 14,186	\$56,558 \$56,558 NI
		STRAIGHT EDGE Maximum Recommended Material Density: 900 kg/ INCLUDES: Bolt-On Cutting Edge (BOCE)	m3 (1520 lb/yd3)	·

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY

988K

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
BUC	CKETS (CON	IT.)		
9	SPECIAL APP	PLICATION BUCKETS		
P	421-6100	BUCKET-SLAG, 159" 8.30 YD3	18,638 g/m3 (2925 lb/yd3)	\$76,415 \$76,415 NI
Р	435-1810	protection BUCKET-SLAG, 154" 7.00 YD3	16,828 g/m3 (3210 lb/yd3) n half arrow	\$71,540 \$71,540 NI
(GET for SPEC	CIAL APPLICATION BUCKETS		
Р	61-6420	TIP, ABRASION, HEAVY DUTY	125 1 60 SLAG BUCKET ONLY	\$561
FLU	IDS			
A	4 <i>NTIFREEZE</i>			
	Different lubri	chine includes antifreeze protection to -34C (-29F). icants are also required for extreme temperatures. o operation and maintenance manual.		
Р	0P-2411	COOLANT, -50C (-58F)	0	\$520 NET

FACTORY SOURCED KITS

OBJECT DETECTION KITS

Please consult the DETECTCAT retrofit price list for dealer installed Object Detection kits on Large Wheel Loaders.

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 988K-024

988K

USE REF NO. LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
---------------------------------	--------------------	-------------------------

FACTORY SOURCED KITS (CONT.)

RETRO-FIT KITS for CURRENT 988K

If ordering on a MISC MSO, you need to use 0P-4742 for TOP LEVEL and 0P-0812 for PACKING.

Kits must be ordered as NOT-INSTALLED.

No returns on Kit components or for parts removed.

С	557-9861	KIT, AXLE OSCILLATION STOP
С	560-2915	KIT, TIRE PRESSURE MONITORING
С	563-3197	KIT, WHEEL CHOCKS
С	516-3925	KIT, TIRE HANDLER (SL)
С	513-5313	KIT, AGGREGATE HANDLER (SL)
С	513-5314	KIT, AGGREGATE HANDLER (HL)
С	498-9814	KIT, RIDE CONTROL (STANDARD)

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY

988K

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight Ibs	LIST PRICE AT DEALER
FACT	ORY SOUP	RCED KITS (CONT.)		
RE	ETRO-FIT K	ITS for CURRENT 988K (Cont.)		
С	471-9675	KIT, COVER, INLET GRILL (CW)	ill covers 4F) and below.	\$3,940 NI
С	450-9894	WIT, AUTOLUBE	g, for field	\$16,970 NI
С	521-5061	KIT, AUTOLUBE	00738 & up, L8X00001 g, for field	\$16,970 NI & up
С	450-9895	KIT, CPM PAYLOAD	estem. cails. arge of LP \$4,148.30 be provided with	\$1,395 NI
С	450-9896	KIT, THIRD VALVE	00001 & up, L8X00001	\$9,600 NI & up
С	476-9627	KIT, SECONDARY STEERING		\$8,990 NI & up
С	476-9606	KIT, AXLE OIL COOLER	0 00001 & up, L8X00001	\$10,690 NI & up
С	458-3099	KIT, ROADING FENDERS	00001 & up, L8X00001	\$5,600 NI & up
С	476-9647	KIT, ENGINE PRECLEANER (DUAL)	0	\$3,080 NI
С	458-3103	KIT, CAB PRECLEANER (POWERED)	0 00001 & up, L8X00001	\$7,120 NI & up

988K

USE REF LANE 2 / 3 OPTIONAL Ship Weight LIST PRICE lbs AT DEALER

FACTORY SOURCED KITS (CONT.)

COMMAND FOR LOADING KIT

Command for loading enables remote operation of the Cat 988K. In order to promote safety with minimal impact to productivity, Command for loading removes the operator from the cab of a machine. The Command for loading Operator Console utilizes seamless integration of new on-board hardware with familiar controls to allow the operator to have full functionality of the machine from a safe distance. Command for loading is currently compatible with 988K. The Operator Console is extremely portable and is carried using a shoulder harness.

SOFTWARE ENABLED ATTACHMENT (SEA)

When quoting always include the price of the Software Enabled Attachment (SEA) even though it is not ordered at the same time as the installation kits. The on-board systems will not function until the SEA is activated. Once the system is installed, activation requires dealer support through Caterpillar Electronic Technician (Dealer Version), communication adapter, and authority to request factory passwords form the Caterpillar Factory Password System (FPS).

When the factory password is generated at the request of the service technician, a purchase order will automatically be generated in the ANTARES system by FPS.

Refer to Information Release Memo (IRM) EES03-01 (PELJ0138) in the Global Sales Library (GSL) for further explanation of SEA's. Refer to RESH1238 for how to obtain a Factory Level Password from https://fps.cat.com/.

SEA's cannot be ordered directly in ANTARES. They can only be ordered using the Factory Password System (see instructions above). WARNING: If you order directly in ANTARES, you may get invoiced twice.

BASE ON BOARD INSTALLATION KIT

The following field retrofit kit includes: on-cab lighting, electronics bay, wiring harness, bumper lockout service panel, and mounting hardware.

> 988K Ser# TWX00001 & up, T8E00001 & up Includes REHSXXXX Special Instruction (English only). REQUIRES: 1 OF 2 BELOW FROM PARTS DEPARTMENT: 545-8018 KIT, CONSOLE INSTALL (2.4GHZ) or 545-8019 KIT, CONSOLE INSTALL (900MHZ)

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 988K-027

988K

USE REF NO. LANE 2 / 3 OPTIONAL Ship Weight LIST PRICE AT DEALER

FACTORY SOURCED KITS (CONT.)

OPERATOR CONTROL KITS

The new Gen 3 console is designed to easily transfer control between machines that are equipped with Command for loading. In addition, the Gen 3 console has improved ergonomics, battery life, and serviceability. Gen 3 consoles are available in two frequency ranges: 900 MHz (902-928 MHz) or 2.4 GHz (2403.1-2478.6 MHz) to provide site and/or country specific requirement.

Approved countries:

900 MHz: United States and Canada. 2.4 GHz: United States Canada, Australia, New Zealand, Peru, Chile, Columbia, Mongolia, Brazil, Mexico, Indonesia, Russia, European Union, Japan, China, Ukraine, South Africa, Democratic Republic of the Congo, and Saudi Arabia.

For the latest approved country listing, please visit: https://dealer.cat.com/cda/layout?m=423015&x=7&id=2678888

The following Generation 3 Console kits contain one operator console, two rechargeable Lithium Ion console batteries, one DC battery charger, one AC battery charger, shoulder harness, 3 smart cards with pouch, system carrying case, Operations and Maintenance Manual, Quick Reference Guide, Trouble Shooting Guide, and Special Instructions.

NOTE:

545-8018

Ρ

The ON-BOARD INSTALLTION KIT is available from the factory only. The CONSOLE INSTALL KITS are available from parts department only.

			1122
Р	545-8019	KIT, CONSOLE INSTALL (900 GHZ)	\$17,390 NI NET
INS	TRUCTIONS		
Р	504-1365	FILM, AM-NORTH	NC
Р	347-5045	FILMS, ANSI	NC

KIT, CONSOLE INSTALL (2.4 GHZ)

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 988K-028

\$17,390 NI

NET

988K

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
PACKI	NG			
MUS	T SELECT	ONE		
	0P-0294	PACK, DOMESTIC TRUCK	0	NC
	0P-0201	DOMESTIC TRUCK, TIRE REMOVAL	0	\$610 NET
	0P-2829	PACK, DOMESTIC TRUCK	0	\$262 NET
	0P-0812	PACK, MISC SHIPMENTS		NC
TRA	NSPORT	GROUP		
Р	451-7913	TRANSPORT, BUCKET (NI) / OMIT	on your machine	NC