AP555F

AP555F ASPHALT PAVER MINNEAPOLIS, MN, USA (SAP) Ship Weight lbs

LIST PRICE AT DEALER

Standard Equipment:

POWERTRAIN

CAT turbo-charged diesel engine Air cleaner, dry-type dual element with integral precleaner Air-to-air after cooler (ATAAC) Belt, automatic tensioner Demand fan Fuel filter / water separator Fuel priming pump, electric Propel system - direct hydrostatic, dual path drive, electronic control Dual braking systems (service & parking) Dual propel pump and motor system Propel modes, pave/travel/maneuver Speed control system

ELECTRICAL

Alarm, back-up Alternator, 100-amp Batteries, two maintenance free, 1000 CCA each CAT ET diagnostic connector Integrated 70 KW generator Horn, forward warning Machine security system wire-ready Product link ready Remote jump start receptacle Starting and charging system, 24-volt Plug and play aftermarket grade and slope ready machine wiring

OPERATOR ENVIRONMENT

Electronic monitoring and warning system with advanced element diagnostics Automatic engine speed control Dual, swing-out operator stations -Control console, tilting

- -Propel console, tilting
- -Cup holder
- -Ground speed indicator
- -Propel lever with speed control dial
- -Steering wheel, spring return

12 V aux power port

Hopper wing control, independent

Hour meter

Instrumentation, dual LCD touchscreens

Lockable vandalism guards

Platform handrails / guardrails

Power assist steering

Thottle control, high/low idle,

ECO-mode and variable, electronic

APPLICATION SPECIFIC COMPONENTS

Adjustable height augers, hydraulic cast ni-hard steel, split segment, 406 mm (16 in) diameter Electronic auger/feeder control system -Gateless feeder system -Manual override

-Reversible

-Variable speed

Heavy-duty feeder flight bars, forged steel, bushed roller chain

High-hardness, abrasion resistant drag

pans, replaceable

Hopper, 6.36 cu m (224.6 cu ft) capacity

Outboard feeder drives

Remote mounted bearing lube points

FLUIDS

Extended life coolant with protection to -37C (-35F)

OTHER STANDARD EQUIPMENT

Doors, service access, hinged, locking Filters, hydraulic, grouped Fuel tank with sediment drain, 190 L (50 gal) Grouped lube points Pressure test ports, hydraulic quick-connect Screed counter balance Screed lock pins Sight gauges: -engine coolant -pump drive -material feed planetaries

Slow moving vehicle sign (for AM-N)

S.O.S. sampling ports

Sound-suppression insulation kit

Steering guide (1)

Tow point indicator scales, lower Vandalism protection caplocks

AP555F

AP555F ASPHALT PAVER MINNEAPOLIS, MN, USA (SAP) Ship Weight

LIST PRICE AT DEALER

Lane 2 is reserved for the Base Order Management Program. Please use Lane 2 when placing orders that are part of the **Base Order Management Program.**

451-9232

\$300,700

LANE 2 - AVAILABLE FROM MINNEAPOLIS FACTORY LANE 3 - AVAILABLE FROM MINNEAPOLIS FACTORY

Mobil-trac System. Fully bogied undercarriage with rubber coated steel mid-wheels. Single-speed planetaries and two speed motors. Automatic track tensioning, hydraulic. MUST select rubber belt from Mandatory Attachment section.

For use with Tier 4F EPA/STG IV EU, aftertreatment and DEF systems.

OP-3695

NC

AVAILABLE FROM MINNEAPOLIS FACTORY Only reference numbers that have the text

"ALSO AVAILABLE ON A MISCELLANEOUS ORDER" can be used on a MISC order.

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A

Subject to change without notice Printed in USA
U. S. DOLLAR CURRENCY

Effective 02JAN2019 AP555F-002

AP555F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
LANE	SELECTIO	DN .		
	0P-9002 0P-9003	LANE 2 ORDER	ment (BOM) program.	NC NC
FEAT	URE PACK	AGES		
		RON CONTROL		
L	433-7572	APRON, MANUAL FOLD	ut. Apron provides	NC
L	512-6398	either a standard profile or low profile hopper. APRON, STR HYD FOLD, MTS	cross the front nising hoppers. (20.75") and a side v side profile	\$6,620
H	OPPER FLA	SHING		
L	424-9173	FLASHING, MANUAL FOLD		NC
L	503-4771	ONLY FOR USE WITH: 433-7572 APRON, MANUA FLASHING, STR HYD FOLD, MTS	pillage from	NC
T	RUCK INTE	RFACE		
L	488-9800	PUSH ROLLER, OSCILLATING	1,165 pivot pading.	\$4,860 \$4,860 NI
L	447-9863	CANNOT BE USED WITH: 448-5079 HITCH, HYDRAU HITCH, HYD PREP, TRACTOR		\$1,430 \$1,430 NI
L	448-5079	ONLY FOR USE WITH: 488-9800 PUSH ROLLER, 488-5079 HITCH, HYDRAU HITCH, HYDRAULIC TRUCK	ULIC TRUCK 1,050 0	\$17,240 \$17,240 NI
		when unloading. Actuated from operator's console. Includes scrapers to minimize material accumulation Also includes truck hitch valve and hydraulic hoses. REQUIRES: 447-9863 HITCH, HYD PREP, TRACTOR	n.	

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 AP555F-003

AP555F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
FEAT	URE PACK	AGES (CONT.)		
M	AINFRAME	EXTENSIONS		
L	447-9864	EXTENSION, MAINFRAME, POWER	284 284	\$6,410 \$6,410 NI
L	447-9867	ALSO AVAILABLE ON A MISCELLANEOUS ORDER Pair of hydraulically powered mainframe extensions material delivery to endgate and facilitate frequent swidth changes. Extends 0.46 m (18") past mainfram CANNOT BE USED WITH: CONTROL, FEEDER, PAD CANNOT BE USED WITH: NON-COMMERCIAL WIDE CANNOT BE USED WITH: EXTENSION 2'6" MAINFR MAINFRAME, NO POWER EXTENSION	to direct creed e. DDLE E WIDTH PAVING PACK AME30	
A	UGER EXTE	• •	, boloeted.	
Р	416-4109	EXTENSION, 6" AUGER, PAIR	55	\$1,005 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER For paving base tractor width to base tractor width 14'. Includes a LH and RH 152 mm (6") auger extension FOR USE WITH: ALL SCREEDS AND ALSO FOR TRASCREED TO MEET MINIMUM PAVING REQUIREME	on. ACTORS ORDERED WIT	
P	438-6252	AUGER 18" EXTENSION PER SIDE		\$2,425 NI
Р	416-4110	Wide Width Paving packages. KIT, AUGER AND MAINFRAME EXT ALSO AVAILABLE ON A MISCELLANEOUS ORDER Recommended if paving base tractor width plus 1.8 base tractor width plus 2.4 m (8') wide. Includes a p and right) of 152 mm (6") auger extensions, two pair right) of 305 mm (1') auger extensions and a pair of hinged 610 mm (2') mainframe extensions to facilitat screed width changes. RECOMMENDED FOR USE WITH: ALL SCREEDS w Wide Width Paving packages.	m (6') to air (left es (left and foldable, te frequent	\$5,290 NI
S	CREED INT	ERFACE PACKAGES		
L	447-9858	ADAPTER, VIBE SCREED		NC
L	447-9859	CANNOT BE USED WITH: 522-1493 SCREED, SE50 ADAPTER, TAMP/VIBE SCREED	re and hoses	\$2,060

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 AP555F-004

AP555F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
FEAT	TURE PACK	AGES (CONT.)		
И	ASH DOW	N SYSTEMS		
L	452-8185	TANK, WASHDOWN ALSO AVAILABLE ON A MISCELLANEOUS ORDER 30 L (8 gal) tank with integral pump mounted below RH side. Intended for use with ecological cleaning flu Includes pump.	86 deck on	\$2,510 \$2,510 NI
L	453-1070	PUMP, DIESEL		\$765
L	327-9167	taken directly from paver fuel tank. COVER, NO WASHDOWN	0	NC
POW	ERTRAIN			
E	NGINE			
L	443-0751	ENGINE, C4.4 T4F / STG IV EU	nent and DEF system.	NC
UND	ERCARRIAC	GE .		
M	ITS UNDER	CARRIA GE		
L	321-2443	TRACK, MTS, TREADBAR		\$21,270
L	321-2429	TRACK, MTS, SMOOTH		\$21,690
ELEC	TRICAL			
LI	GHTING			
Р	455-7858	LIGHTS, WORKING		\$760
Р	455-7857	Four 24V halogen floodlamps. Two front and two reat LIGHTS, ROADING		\$1,215
F	EEDER CON	ITROL SENSORS		
P	416-1465	CONTROL, FEEDER, PADDLE	et amount gers.	\$2,365 NI

AP555F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight Ibs	LIST PRICE AT DEALER
ELE	CTRICAL (C	CONT.)		
F	FEEDER CON	ITROL SENSORS (Cont.)		
P	416-1467	SENSOR, FEEDER, SONIC	t set amount	\$3,890 NI
P	435-0910	of material ahead of the screed. Located at end of au SENSOR, AUG SONIC, CONV PADDLE	ors and two cally actuate	\$6,260 NI
P	465-1275	SENSOR, AUG SONIC, CONV SONIC ALSO AVAILABLE ON A MISCELLANEOUS ORDER Four, proportional, non-contacting auger and convesensors that automatically actuate the feeders to mapreset amount of material ahead of the screed.	yor sonic	\$7,650 NI
OPE	RATOR ENV	TRONMENT		
5	STEERING C	ONTROL		
L	416-4118	STEERING, SPRING RETURN		NC
L	416-4119	Conventional type, spring return controlled steering STEERING , FRICTION		\$4,515
L	DECEL PEDA	L		
P	416-1453	PEDALS, DECELERATOR	2 n,	\$1,725 \$1,725 NI
L	416-1454	to decrease the propel speed setting. COVER, NO DECEL PEDAL	5	NC
5	SEAT			
L	416-1446	SEAT, VINYL SUSPENSION		NC
L	416-1447	Retractable 76 mm (3") seat belt. SEAT, VINYL, DELUXE	lip-up armrests.	\$1,475

Supersedes 02JAN2018
Caterpillar: Confidential Green
US-A-19-01 A

Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 AP555F-006

AP555F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
OPE	RATOR ENV	IRONMENT (CONT.)		
V	ENTILATION Required for U	N SYSTEM J.S. market only		
L	445-5894	VENTILATION SYSTEM, NO CANOPY Asphalt fumes extraction with hydraulically driven fa CANNOT BE USED WITH: 434-0040 HARD TOP CAN	ın.	\$8,350
L	445-5895	VENTILATION SYSTEM, CANOPY FOR USE WITH LANE 3 ONLY Asphalt fumes extraction with hydraulically driven fa ONLY FOR USE WITH: 434-0040 HARD TOP CAN		\$8,350
TECH	HNOLOGY F	PRODUCTS		
P	location, opera effectively mor jobs on sched of owning and please referen	enables the remote transmission of information about the ation, and condition of your equipment. Efficiently and nitor the performance of your assets to help keep your ule, maintain equipment condition, and reduce the cost operating your fleet. Availability varies by country - ice https://Dealer.cat.com/PL/Certification for certifed ase contact your Caterpillar marketing representative	e	
P	456-4096	PRODUCT LINK, CELLULAR PL641	rage including DMA cellular networks on for echnology	NC
P	456-4097	volumes of data. PRODUCT LINK, SATELLITE PL631	rk to transmit g in Product	\$432
Р	490-6572	coverage. PRODUCT LINK, SATELLITE PLE631	ork to transmit g in	\$575 NET
P	490-6573	PRODUCT LINK, CELLULAR PLE641 FOR USE WITH LANE 3 ONLY Product Link Elite series PLE641 offers expanded cor 3G UMTS and CDMA2000 as well as 2G GSM and CI to transmit location, utilization and health informatio viewing in Product Link user applications. Cellular te provides capabilities for frequent transmission and la volumes of data.	verage including MDA cellular networks on for echnology	\$264 NET
C	CONTROL C	YLINDERS		
L	453-8319	CYLINDER KIT, STANDARD		NC

Supersedes 02JAN2018
Caterpillar: Confidential Green
US-A-19-01 A

Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 AP555F-007

AP555F

USE REF NO. LANE 2 / 3 MANDATORY	Ship Weight Ibs	LIST PRICE AT DEALER
----------------------------------	--------------------	-------------------------

OTHER ATTACHMENTS

COMMISSIONING SUPPORT

NOTE: It is recommended that startup and commissioning of machines be included as part of the machine sale. The net charge covers a three day commissioning event. Trained personnel cover proper machine setup, basic maintenance, operation and application on a customer's jobsite. To request and schedule a machine commissioning event, dealers will need to contact the Caterpillar Paving Technical Training group by filling out the outline request

form.

URL:https://dealer.cat.com/PavingOnDemand

as required for the USA.

	0P-2586	COMMISSIONING, NEEDED	\$6,330 NET \$6,330 NI NET
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER	
		Commissioning Needed, trained personnel are required to properly commission the machine.	
	0P-2587	COMMISSIONING, NOT NEEDED	NC
INS	STRUCTIONS		
	PICTOGRAPH	H FILMS	
L	453-9945	INSTRUCTIONS, NORTH AMERICAN	NC

PAINT

L	567-0751	PAINT, STANDARD, ANSI/ISO	NC
		Provides standard Caterpillar Yellow and Black paint scheme.	
		Select this option for when custom paint is not desired.	
		Films are provided in the pictograph film selection above.	
L	566-2438	PAINT, CUSTOM, ANSI	\$204
		Machine is provided with required safety and regulatory ANSI	
		films installed, and provides necessary loose films for	
		application by the dealership after custom paint is applied.	
		ONLY FOR USE WITH: 453-9945 INSTRUCTIONS, NORTH AMERICAN	

ANSI picto warning decals using symbols plus the word "WARNING"

REQUIRES: 451-9232 AP555F MTS ASPHALT PAVER, HRC

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A

Subject to change without notice Printed in USA
U. S. DOLLAR CURRENCY

Effective 02JAN2019 AP555F-008

AP555F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
ELEC	TRICAL			
PO	OWER DIST	RIBUTION		
		one power supply per order.		
Р	416-2013	PANEL, POWER SUPPLY		\$6,620 \$6,620 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Electrical distribution panel with a total output of 6.6 kVA continuous with 8 kVA start-up capability, protected by a circuit breaker at the panel, provides power for ex-factory installed lighting and customer work tools. Includes eight 120 V outlets. Mounted or RH side of safety railing behind operator station.	1	
LI	GHTING			
P	198-8284	LIGHT, HAZARD		\$740 NI
Р	363-7444	CANNOT BE USED WITH: 434-0040 HARD TOP CAN LIGHT, HAZARD, CANOPY	0	\$339 NI
Р	418-0539	Two LED amber beacon lights mounted to the hard to ONLY FOR USE WITH: 523-4277 WIRING, LIGHT LIGHTS, HID/LED, CANOPY	S/HAZARD READY	\$1,660 \$1,660 NI
Р	523-4277	FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Six LED lights, two forward facing and four rear facin mounted to the hard top canopy. ONLY FOR USE WITH: 523-4277 WIRING, LIGHT WIRING, LIGHTS/HAZARD READY FOR USE WITH LANE 3 ONLY Wiring and mounting plates installed in hard top fibe canopy to accept LED lights for night paving and am REQUIRES: 434-0040 HARD TOP CANOPY	S/HAZARD CANOPY0 erglass	\$354
OPER	RATOR ENV	IRONMENT		
		PROTECTION		
L	434-0040	FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Hardtop canopy to provide paver operator sun and r protection. Raises or lowers by folding manually. ONLY FOR USE WITH: 445-5895 VENTILATION S 447-9862 COVER, NO VE	0 ain SYSTEM, CANOPY or	\$5,790 \$5,790 NI
L	463-6568	WINDSHIELD, DUAL WINDOW	194	\$4,800

Supersedes 02JAN2018
Caterpillar: Confidential Green
US-A-19-01 A

Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 AP555F-009

AP555F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight Ibs	LIST PRICE AT DEALER
OPER	RATOR ENV	TRONMENT (CONT.)		
0	PERATOR F	PROTECTION (Cont.)		
Р	187-6649	UMBRELLA, CAT	ain protection.	\$179 NI
TECH	INOLOGY F	PRODUCTS		
G	RADE AND	SLOPE CONTROLS		
Р	416-2003	CONTROL, BASE CAT G&S SYSTEM	0	\$8,280 \$8,280 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Cat Grade and slope controller, power supply, harr mounting provisions for grade sensors. User interface integrated in existing screed display Only LANE 2 & 3 machine orders with a screed are from the factory. FOR GRADE/GRADE OPERATION MUST HAVE TW FOR GRADE/SLOPE OPERATION MUST HAVE ON SLOPE SENSOR. MUST BE ORDERED WITH A TRACTOR OR SCREE	ness, and s. calibrated VO GRADE SENSORS E GRADE SENSOR AND	
Р	362-8687	SCREED ORDERS ONLY. FOR NI ORDERS MUST I SENSOR, SLOPE	PROVIDE TRACTOR S/N	\$2,820 NI
P	416-2006	ONLY ONE SLOPE SENSOR PER MACHINE ORDER ONLY FOR USE WITH: 416-2003 CONTROL, BASENSOR, GRADE, SONIC	SE CAT G&S SYSTEM	\$4,600 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Contact-free tracing of ground or stringline with se to minimize effect of short surface irregularities and Includes one sonic tracer consisting of five mainter ceramic sensors with automatic temperature comp coily cable, sensor pole, two support arms and mor Unit is 28 cm (11 in) long. FOR GRADE/GRADE OPERATION ORDER QTY 2 ONLY FOR USE WITH: 416-2003 CONTROL, BA	t lf-averaging d objects. nance-free pensation, unting hardware.	. ,

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 AP555F-010

AP555F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
		PRODUCTS (CONT.) SLOPE CONTROLS (Cont.)		
P	459-6770	SENSOR, GRADE, SONIC, EXTEND	R lf-averaging d objects. nance-free ensation, coily t. The square ately 26" to 46"	\$4,600 NI
P	416-2007	SENSOR, GRADE, MECHANICAL	ensor ily cable, ware.	\$3,215 NI
P	513-0333	SENSOR, GRADE, MECH, EXTEND FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Mechanically traces the ground or stringline. Inclu- proportional contacting mechanical sensor with on riding shoe attachment, coily cable, sensor pole, ar sensor mount. The square tubing telescoping mour approximately 26" to 46" and mounts on the endga FOR GRADE/GRADE OPERATION ORDER QTY 2 ONLY FOR USE WITH: 416-2003 CONTROL, BA	des one e wand and one da telescoping nt has a range of	\$3,215 NI
L	LEVELING DE	EVICES		
P	417-1907	BEAM, SONIC AVERAGING, CAT G&S	or enhanced venness of the ver the ngth of lity and umes customer must be ow arm support KE A COMPLETE	\$17,100 NI

Supersedes 02JAN2018
Caterpillar: Confidential Green
US-A-19-01 A

Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 AP555F-011

AP555F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight Ibs	LIST PRICE AT DEALER
TECH	INOLOGY F	PRODUCTS (CONT.)		
LE	EVELING DI	EVICES (Cont.)		
P	491-0721	CASE, SONIC SENSOR	R location for ors. This case is RAGING, CAT G&S on	\$247 NI
OTHE	R ATTACH	HMENTS		
0	THER TRAC	CTOR ATTACHMENTS		
L	480-0259	PLOW, TRACK	80 Can be secured	\$2,335 \$2,335 NI
Р	438-6149	life. EXTENSION, 1' AUGER LH	2	\$780 NI
P	438-6150	One 305 mm (1') auger extension and mounting ha EXTENSION, 1' AUGER RH	70	\$780 NI
P	416-4130	One 305 mm (1') auger extension and mounting ha EXTENSION, 2'6" AUGER LH	150	\$1,645 NI
Р	416-4131	One 755 mm (2' 6") auger extension and mounting EXTENSION , 2'6" AUGER RH	150	\$1,645 NI
P	215-7553	One 755 mm (2' 6") auger extension and mounting EXTENSION , 0-2' MAINFRAME , PAIR ALSO AVAILABLE ON A MISCELLANEOUS ORDER Consists of a pair of hinged mainframe extensions 0 mm (0 ft) to 610 mm (2') to facilitate frequent screenings. Bolts to mainframe. Does not raise and lounless the customer has auger extensions the prefix the KIT, AUGER AND MAINFRAME EXT		\$1,265 NI
P	416-1189	Included in: KIT AUGER AND MAINFRAME EXT KIT, 9'10" AUG, MAINFRAME EXT FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Recommended for wide width paving with Weiler so with 3' of extensions on each side of the screed. Includes two 755 mm (2'6") left hand augers and to right hand augers, two augers support bearings and braces, four 788 mm (2'7") mainframe extensions, mainframe extension mounts.	R creeds equipped wo 755 mm (2'6") nd mainframe	\$13,750 NI

Supersedes 02JAN2018
Caterpillar: Confidential Green
US-A-19-01 A

Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 AP555F-012

AP555F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight Ibs	LIST PRICE AT DEALER
ОТНЕ	ER ATTACH	IMENTS (CONT.)		
		CTOR ATTACHMENTS (Cont.)		
		, ,		
P	438-6255	EXTENSION, 1' MAINFRAME		\$408 NI
		One 305 mm (1') fixed mainframe extension and mo		
		FOR DUAL MAINFRAME EXTENSIONS ORDER QTY	7.2	
P	416-4129	EXTENSION, 2'6" MAINFRAME		\$650 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		One 788 mm (2' 7") fixed mainframe extension and hardware.	mounting	
		FOR DUAL MAINFRAME EXTENSIONS ORDER QTY	7 2	
		CANNOT BE USED WITH: 447-9864 EXTENSION, M	MAINFRAME, POWER	
Р	493-3538	KIT, ANGLED DEFLECTOR		\$292 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Single plate angled deflector kit for the front of the		
		housing and a standard auger segment for the right		
		kit changes material flow from feeding from both sid		
_		right material flow.		
P	273-9969	GUIDE, STEERING		\$675 NI
		Second, adjustable position steering guide with indi		
P	450-8058	INDICATOR, TOW POINT	6	\$670
		Pair of tow point height gauges mounted on top of p	oaver deck.	·
P	458-4087	KIT, UPTIME	5	\$870 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Consists of critical spare parts to ensure maximum Items come packed in a lockable tool box and each	part is clearly	
		identified. Kit includes: O-rings, relays, sensors, po		
		sensors, and fuses.		
P	416-4128	SPRAY WAND	15	\$467 NI
		FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Includes 9 m (30') hose, spray wand and quick-con		
		ONLY FOR USE WITH: 452-8185 TANK, WASHD		
		453-1070 PUMP, DIESEI		
P	463-6563	CANNOT BE USED WITH: 463-6563 HOSE, REEL W		ė1 000
r	403-0003	HOSE, REEL WITH WAND	60	\$1,880 \$1,880 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		4 2 7 3 3 3 3 3 3 3 3 3 3
		Includes 9 m (30') hose on self-storing reel with spr	ay wand	
		mounted to left-hand handrail at rear of tractor.	ONIM	
		ONLY FOR USE WITH: 452-8185 TANK, WASHD 453-1070 PUMP, DIESEI		
		CANNOT BE USED WITH: 416-4128 SPRAY WAND	2	
P	460-2964	PLATE, HOPPER, MAN APRON	0	\$1,705 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Includes two hopper floor plate inserts to eliminate in the front of the hopper. Poisses the truels entry be		
		in the front of the hopper. Raises the truck entry he 1.5", but minimizes material build up in the hopper		
		flashing supplied with the machine.	. 0200 410	
		ONLY WORKS WITH MANUAL APRONS		

AP555F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight Ibs	LIST PRICE AT DEALER
ОТНЕ	ER ATTACH	IMENTS (CONT.)		
0	THER TRAC	CTOR ATTACHMENTS (Cont.)		
Р	490-4132	VISORS, DISPLAY, TRACTOR	0	\$805 \$805 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes two folding visors that shade the tractor d sunlight. The visors fold back to allow the installativandal covers.	isplays from	
P	485-2960	MOUNT, CANOPY, TEMP SCAN		\$2,660 NI
		Includes the necessary hardware to mount a Moba temperature scanner and display to a paver with ca REQUIRES: 434-0040 CANOPY, HARD TOP	Pave Scan infrared anopy.	
Р	491-5820	MOUNT, TEMP SCAN		\$3,020 NI
		Includes the necessary hardware to mount a Moba temperature scanner and display to a paver with no CANNOT BE USED WITH: 434-0040 CANOPY, HAR	o canopy.	
P	505-0166	DEFLECTOR, CONVEYOR	under the head	\$510 NI
_		in over feed conditions such as wide width or deep the removal of the production deflector.	paving. Requires	
P	460-2967	FLASHING, SIDE ALSO AVAILABLE ON A MISCELLANEOUS ORDER Rubber flashing for use with rubber flashing option Tivar. Includes two folded rubber flashing pieces the sides of hopper above the standard flashing. Reduct spillage between the sides of hopper and truck box ONLY FOR USE WITH: 424-9173 FLASHING, MA	ns and manual fold nat mount on the nes material ANUAL FOLD or	\$755 NI
BA	4 <i>LLAST PA</i>	CKAGES		
P	435-1041	BALLAST, 2 PLATE BUMPER	335	\$970 \$970 NI
		FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Adds 151 kg (333 lb) of steel plate mounted to the f for improved tractive effort and stability for wide wi Limits bumper oscillation in some bumper position CANNOT BE USED WITH: 435-1043 BALLAST, 6 PI 435-1042 BALLAST, 4 PI	front bumper dth paving. s. LATE BUMPER or	

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY

488-6301 BALLAST, 8 PLATE BUMPER

Effective 02JAN2019 AP555F-014

AP555F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight Ibs	LIST PRICE AT DEALER
OTHER	R ATTACH	IMENTS (CONT.)		
BA	LLAST PA	CKAGES (Cont.)		
Р	435-1042	BALLAST, 4 PLATE BUMPER	668	\$1,945
			0	\$1,945 NI
		FOR USE WITH LANE 3 ONLY		
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Adds 303 kg (668 lb) of steel plate mounted to the f for improved tractive effort and stability for wide wide		
		Limits bumper oscillation in some bumper positions		
		CANNOT BE USED WITH: 435-1043 BALLAST, 6 PI		
		435-1041 BALLAST, 2 PI		
		488-6301 BALLAST, 8 PI		
•	435-1043	BALLAST, 6 PLATE BUMPER	776	\$2,270
			0	\$2,270 NI
		FOR USE WITH LANE 3 ONLY		
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Adds 352 kg (777 lb) of steel plate mounted to the f		
		for improved tractive effort and stability for wide wide Limits bumper oscillation in some bumper positions		
		CANNOT BE USED WITH: 435-1042 BALLAST, 4 PI		
		435-1041 BALLAST, 2 PI		
		488-6301 BALLAST, 8 PI		
•	488-6301	BALLAST, 8 PLATE BUMPER	1,008	\$2,940
			1,008	\$2,940 NI
		FOR USE WITH LANE 3 ONLY		
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Adds 418 kg (921 lb) of steel plate mounted to the f		
		for improved tractive effort and stability for wide wide and use with the tamper screed.	ath paving	
		Limits bumper oscillation in some bumper positions	2	
		CANNOT BE USED WITH: 435-1041 BALLAST, 2 PI		
		435-1042 BALLAST, 4 PI		
		435-1043 BALLAST, 6 PI	ATE BUMPER	
P	493-3514	BALLAST, BUMPER	0	\$314
			0	\$314 NI
		FOR USE WITH LANE 3 ONLY		
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Adds 50 kg (111 lb) of steel plate mounted to the fro		
		for improved tractive effort and stability for wide wie Limits bumper oscillation in some bumper positions	aui paving.	
		REQUIRES: 488-6301 BALLAST, 8 PLATE BUMPER		

AP555F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight Ibs	LIST PRICE AT DEALER
OTHE	R ATTACH	IMENTS (CONT.)		
LE	VELING DI	EVICES		
P	109-5623	FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER 30' long multi-pad aluminum beam (measured fromost pivot pin) that runs along the outside of the the screed. Utilizes a combination of beams and shon pins to provide the optimum reference for grade sub-beams with two shoes each attach to both the of the main beam. A string line runs along the top from front to rear. The whole unit is to be positionalong the paver and the grade sensor (not provide tow arm and senses the midpoint of the string. The pulled by the paver and increases the sensing lengthe high and low points in the reference surface to self-leveling characteristics of the paver. Includes that had a sense to self-leveling characteristics of the paver. Includes that the property of the paver and rideability. Go matching. Primarily for highways and paving jobs with long primarily for highways and paving jobs with long primarily for highways and paving jobs with long primarily sense.	m front to rear- cractor and noes that pivot e controls. Two front and rear of the beam ed mid way d) mounts on the e leveler gets gth. It averages maximize the mounting od for joint	\$8,030 NI
P	109-5622	difficulty in maneuvering. LEVELER, 40' OUTBOARD FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER SAME AS LEVELER, 30' OUTBOARD above except multi-pad aluminum beam. Capable of producing and more level surface than the 30' leveler but is re-	R for 40' long an even flatter	\$8,250 NI
P	109-5625	transportable. LEVELER, FORE'N AFT FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER 12' long multi-pad aluminum beam (measured fro rear-most pivot pin) that mounts ahead and inboa Two sub-beams with two shoes each that pivot on to the main beam. This leveler gets pulled by the padditional towed shoe attaches to the screed and rA string line gets stretched between the front inboaleveler. A grade sensor (not provided) mounts on the senses the string midpoint. During paving the from average out the high and low points of the reference the aft leveler responds to height changes in the machine screed. Includes mounting hardware. Best for high jobs with long pulls. Not as effective as an outboar Used when outboard referencing is not practical direstrictions.	m front to rd of the screed. pins attach eaver. An rides on the mat. ard and aft he tow arm and at leveler will ee surface while hat behind the hways and paving d leveler.	\$7,870 NI

Supersedes 02JAN2018
Caterpillar: Confidential Green
US-A-19-01 A

Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 AP555F-016

AP555F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
APPL	ICATION S	PECIFIC COMPONENTS		
SI	E50 V and	SE50 VT SCREED SELECTIONS		
Р	428-4845	SCREED, SE50 V	7,239	\$82,240 \$82,240 NI
P	522-1493	ALSO AVAILABLE ON A MISCELLANEOUS ORDER Double extending vibratory screed. Provides paving 2.55 m to 5.00 m (8' 4.3" to 16' 4.8"). Includes elected elements with automatic regulators on all screed princludes dual color displays for controlling screed vibe speeds, counterbalance pressure and optional Slope control in both metric and SI units. Screed pris 13 mm (0.5"). Hydraulic extensions require man of extension controls. Electric extension slope control Main screed has electric powered crown. SCREED, SE50 VT	g widths from ctric heating clates. Also temperature, I Cat Grade and clate thickness datory selection crol is standard.	\$94,590 \$94,590 NI
	ONTROL C		,	
L	437-0067	CYLINDER KIT, STANDARD	0	NC
	ICTO LABEL Selection requ	.S ired with SCREED, SE50 V and SCREED, SE50 VT		
L	449-8858	FILM GP US	"WARNING" as	NC

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 AP555F-017

Bid Term: 2/20/19 - 2/19/21

522-1493 SCREED, SE50 VT

AP555F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight Ibs	LIST PRICE AT DEALER
APF	LICATION S	PECIFIC COMPONENTS (CONT.)		
1	EXTENSION (Selection requ	CONTROLS ired with SCREED, SE50 V and SCREED, SE50 VT		
L	450-6610	Provides hydraulic motor power for raising and low height relative to the main screed. FOR USE WITH ALL MANUAL ENDGATES REQUIRED BY: 428-4845 SCREED, SE50 V or 522-1493 SCREED, SE50 VT		\$3,230
L	473-3320	Provides hydraulic motor power for raising and low extension height relative to the main screed. FOR USE WITH ALL POWER ENDGATES REQUIRED BY: 428-4845 SCREED, SE50 V or 522-1493 SCREED, SE50 VT		\$6,460
;	SCREED END Selection requ	OGATES hired with SCREED, SE50 V and SE50 VT		
		nd powered endgates have an upward travel of ove grade and 150 mm (6") below grade.		
L	538-9613			NC
L	523-4576	ENDGATE, POWER	ear skis and two Igate. FOR POWER ENDGATE or	\$8,270
1	ENDGATE HE	EATER OPTIONS		
L	490-1681	HEATER, ENDGATE		\$2,110
		ALSO AVAILABLE ON MISCELLANEOUS ORDER Includes heating elements for the wear skis. ONLY FOR USE WITH: 482-4845 SCREED, SE56 553-6011 SCREED, SE56		\$2,110 NI
L	438-1030	HEATER, ENDGATE, FOLDING	hoes on	\$2,350 \$2,350 NI

AP555F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
APPL	ICATION S	PECIFIC COMPONENTS (CONT.)		
FC	OLDING HE	ATER OPTION		
L	443-3557	SCREED ENDGATES, FOLDING	O 0	\$5,160 \$5,160 NI
		Foldable endgates to allow narrowest transport wid ONLY FOR USE WITH: 438-1030 HEATER, END		
SE	50 V AND	SE50 VT OPTIONAL ATTACHMENTS		
Р	467-0083	VISORS, DISPLAY	lisplay from	\$323
Р	473-3322	CONTROL, PENDANT		\$2,330
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Two removable pendant controls with coily cord. A of optional powered endgate, screed width, and ma and pause of the feeders system. ONLY FOR USE WITH: 428-4845 SCREED, SE5	llows adjustment anual override	\$2,330 N
P	473-3330	CONTROL, PENDANT	0 R Allows adjustment anual override	\$2,330 \$2,330 N
P	480-7055	MOUNT, SWIVEL CONTROLS	0 R the left and vn and also	\$1,255 N
•	467-4275	UMBRELLA, SCREED OPERATOR	35 R perator sun and rain Includes plete machine, er qty 2.	\$323 N
•	472-0510	SHOE, WIDE	Red to replace (88 mm) wide.	\$855 N

Supersedes 02JAN2018
Caterpillar: Confidential Green
US-A-19-01 A

Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 AP555F-019

AP555F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight Ibs	LIST PRICE AT DEALER
APPL	ICATION S	PECIFIC COMPONENTS (CONT.)		
		SE50 VT OPTIONAL ATTACHMENTS (Cont.)		
P	472-0512	FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Consists of two vertical endgate shoes that can be used to re the standard endgate shoe. The vertical edge shoes also have mounting tabs welded to the outside of the vertical structure vertical shoe is 5 mm thick and has 16 mm of clearance from bottom wear surface up to the mounting tabs. At the mounti total width is 50 mm. The vertical endgate shoes do not work	eplace e the e. The n the ing tabs	\$755 NI
P	467-4575	endgate heaters. SHOE, SAFETY EDGE	ed.	\$855 NI
P	490-2550	PACKAGE, CUT OFF SHOE FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER One 1' plate and one 2' plate to reduce paving widths in 3" increments. ONLY FOR USE WITH: 428-4845 SCREED, SE50 V or 522-1493 SCREED, SE50 VT	0	\$2,090 NI
P	486-4622	EXTENSION, 9.8" SCREED		\$4,280 NI
P	486-4620	ONLY FOR USE WITH: 428-4845 SCREED, SE50 V EXTENSION, 2' 5.5" SCREED		\$5,670 NI
SE	E50 V EXTE	ENSION PACKAGES		
P	473-8992	PACKAGE, COMMERCIAL + 1' 7.7"	anical 250 mm	\$12,690 NI

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 AP555F-020

AP555F

REF Ship Weight LIST PRICE LANE 2 / 3 OPTIONAL **USE** NO. AT DEALER APPLICATION SPECIFIC COMPONENTS (CONT.) SE50 V EXTENSION PACKAGES (Cont.) Ρ \$16,920 NI 477-1128 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes a pair (left and right) of 152 mm (6") auger extensions, two pairs (left and right) of 305 mm (1') auger extensions and a pair of foldable, hinged 610 mm (2') mainframe extensions to facilitate frequent screed width changes. Also includes two 1.25 m (4' 1") prestrikeoffs and two 750 mm (2' 5.5") heated-vibratory screed extensions. NOTE: Must remove EXTENSION, MAINFRAME POWER if equipped. Installation limits travel speed to 10 kph (6.2 mph) ONLY FOR USE WITH: 428-4845 SCREED, SE50 V and 435-1041 BALLAST, 2 PLATE BUMPER or 435-1042 BALLAST, 4 PLATE BUMPER or 435-1043 BALLAST, 6 PLATE BUMPER or 488-6301 BALLAST, 8 PLATE BUMPER or 493-3514 BALLAST, BUMPER 475-2632 \$25,390 NI FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes two 755 mm (2'6") left hand augers and two 755 mm (2'6") right hand augers, two auger support bearings and mainframe braces, four 788 mm (2'7") mainframe extensions, two mainframe extension mounts, two 750 mm (2' 5.5") heated-vibratory screed extensions, prestrikeoffs and one tube for front mounting support of reference NOTE: Must remove EXTENSION, MAINFRAME POWER if equipped. Installation limits travel speed to 10 kph (6.2 mph) ONLY FOR USE WITH: 428-4845 SCREED, SE50 V and 435-1042 BALLAST, 4 PLATE BUMPER or 435-1043 BALLAST, 6 PLATE BUMPER or 488-6301 BALLAST, 8 PLATE BUMPER or 493-3514 BALLAST, BUMPER SE50 VT EXTENSION PACKAGES Ρ 470-9479 \$11,320 NI FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes: KIT, AUGER AND MAINFRAME EXT and two mechanical 250 mm (9.8") bolt on heated extensions. NOTE: Must remove EXTENSION, MAINFRAME POWER from paver,

Supersedes 02JAN2018
Caterpillar: Confidential Green
US-A-19-01 A

Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY

522-1493 SCREED, SE50 VT

Effective 02JAN2019 AP555F-021

Bid Term: 2/20/19 - 2/19/21

if equipped, prior to installing this package.

ONLY FOR USE WITH:

AP555F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
APPL	ICATION S	PECIFIC COMPONENTS (CONT.)		
SI	E50 VT EX	TENSION PACKAGES (Cont.)		
P	477-1130	PACKAGE, COMMERCIAL + 4'11"	R 1.25 m (4'1") catory screed	\$25,740 NI
		Installation limits travel speed to 10 kph (6.2 mph) ONLY FOR USE WITH: 522-1493 SCREED, SE5 435-1042 BALLAST, 4 P. 435-1043 BALLAST, 6 P.	0 VT and LATE BUMPER or	
P	475-2633	PACKAGE, BASE WIDTH + 4'11". FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes two 0.75 m (2'6") left hand augers and two right hand augers, two auger support bearings and four 0.79 m (2'7") mainframe extensions, two main mounts, two 0.75 m (2' 5.5") heated-vibratory/tamextensions, two 1.25 m (4'1") prestrikeoffs, and one front mounting support of reference ski. NOTE: Must remove EXTENSION, MAINFRAME PO Installation limits travel speed to 10 kph (6.2 mph) ONLY FOR USE WITH: 522-1493 SCREED, SE5 435-1043 BALLAST, 6 P 488-6301 BALLAST, 8 P 493-3514 BALLAST, BU	2,754 0 0.75 m (2'6") d mainframe braces, frame extension per screed e tube for WER if equipped. O VT and LATE BUMPER or LATE BUMPER or	\$34,210 NI
P	476-6892	PACKAGE, BASE WIDTH + 8' 2" FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes three 0.75 m (2'6") left hand augers and the right hand augers, two auger support bearings and six 0.79 m (2'7") mainframe extensions, two mainfres mounts, two 1.25 m (4' 1.2") heated-vibratory/tampextensions, prestrikeoffs, and one tube for front most reference ski. NOTE: Must remove EXTENSION, MAINFRAME POInstallation limits travel speed to 10 kph (6.2 mph) ONLY FOR USE WITH: 522-1493 SCREED, SE5 488-6301 BALLAST, 8 P. 493-3514 BALLAST, BUILDING AVAILABLE ONLY FOR USE WITH: 523-1493 SCREED, SE5	hree 0.75 m (2'6") I mainframe braces, rame extension per screed bunting support WER if equipped.	\$57,010 NI

Supersedes 02JAN2018
Caterpillar: Confidential Green
US-A-19-01 A

Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Effective 02JAN2019 AP555F-022

AP555F

REF Ship Weight LIST PRICE LANE 2 / 3 OPTIONAL USE NO. AT DEALER

APPLICATION SPECIFIC COMPONENTS (CONT.)

FRONT MOUNT SCREED SUPPORT

The following Weiler screed selections are the only available configurations from the factory. For all other configurations please contact Weiler directly through their website: www.weilerproduct.com. Parts and warranty for all Weiler products, including the below selections, are administered through Weiler. All other optional attachments such as extensions, should be ordered through Weiler. Screeds ordered from Weiler must be installed at Weiler or the Caterpillar dealership.

L 495-8979 \$132,250 \$132,250 NI

> Double extending front mounted extension vibratory screed. Provides paving widths from 8' to 15'6". Includes electric heating elements with automatic regulators on all screed plates. Also includes dual color displays for controlling screed temperature, vibe speeds, counterbalance pressure and optional Cat Grade and Slope control in both metric and SI units. Hydraulic extensions have hydraulic power for height and slope. Main screed crown is hydraulic. Includes display visors, pendant controls and heated endgates. REQUIRES: 495-9001 THICKNESS SCREWS, CCW or

495-9002 THICKNESS SCREWS, CW

ONLY FOR USE WITH: 453-8319 CYLINDER KIT, STANDARD CANNOT BE USED WITH: 428-4845 SCREED, SE50 V or 522-1493 SCREED, SE50 VT or

495-8978 SCREED, WEILER SE8F, 12" BERM

495-8978 \$139,500 \$139,500 NI 0

> Double extending front mounted extension vibratory screed. Provides paving widths from 8' to 15'6". Includes electric heating elements with automatic regulators on all screed plates. Also includes dual color display for controlling screed temperature, vibe speed, counterbalance pressure and optional Cat Grade and Slope control in both metric and SI units. Hydraulic extensions have hydraulic power for height and slope. Main screed crown is hydraulic. Includes display visors, pendant controls and heated endgates. Includes left and right berm attachments in the extensions. REQUIRES: 495-9001 THICKNESS SCREWS, CCW or

495-9002 THICKNESS SCREWS, CW ONLY FOR USE WITH: 453-8319 CYLINDER KIT, STANDARD CANNOT BE USED WITH: 428-4845 SCREED, SE50 V or

> 522-1493 SCREED, SE50 VT or 495-8979 SCREED, WEILER SE8F, BASIC

THICKNESS SCREWS

MUST SELECT ONE WITH WEILER SCREED

495-9001 NC

Two ACME RH threaded screws (8tpi). Counter-clockwise turn

increases paving depth.

495-8979 SCREED, WEILER SE8F, BASIC or ONLY FOR USE WITH: 495-8978 SCREED, WEILER SE8F, 12" BERM

Supersedes 02JAN2018 Caterpillar: Confidential Green US-A-19-01 A

Subject to change without notice Printed in USA
U. S. DOLLAR CURRENCY

Effective 02JAN2019 AP555F-023

AP555F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight Ibs	LIST PRICE AT DEALER			
APPL	APPLICATION SPECIFIC COMPONENTS (CONT.)						
TF	HICKNESS	SCREWS (Cont.)					
Р	495-9002	THICKNESS SCREWS, CW	urn increases ILER SE8F, BASIC or	NC			
		495-8978 SCREED, WEI	LER SE8F, 12" BERM				
FACT	ORY SOUP	RCED KITS					
P	496-9628	FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Field installed four forward facing and four rear fac LED lights, mounted to the hard top canopy. Dealer installation of front, outermost light bracket ONLY FOR USE WITH: 523-4277 WIRING, LIGH 434-0040 HARD TOP CA	R cing, t is required. ITS/HAZARD READY	\$1,875 NI			
P	496-9649	FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Field installed includes wiring and eight LED lights to the rear of the tractor and four mounted to the s to illuminate the screed in low light conditions. Dealer installation required.	0 R s, four mounted	\$2,275 NI			
PACK	KING						
PA	ACKING						
	0P-0210	PACK, DOMESTIC TRUCK	0	NC			
M	ISCELLANE	EOUS PACKING					
	0P-3651	PACKING, MISC MATERIAL		NC			

Supersedes 02JAN2018
Caterpillar: Confidential Green
US-A-19-01 A

Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY