CONSTRUCTION EQUIPMENT

U.S. PRICE LIST

C075

COMPACT EXCAVATORS

PL-200 MX SAP REVISION 5

EFFECTIVE JANUARY 1, 2019

THIS IS AN ELECTRONIC COPY ONLY - HARD COPIES WILL NOT BE DISTRIBUTED.

This price list is intended for dealers with the Compact Excavators (MX) contract only.

The prices included in this revision supersede any prices established prior to the effective date shown unless specifically identified in a price bulletin as superseding this price list.

Below is a list of Family(s) and Model(s) that are included in this price list.

Crawler Excavator (Mini)

CX17C CANOPY T4 FINAL - MX7A

CX26C CANOPY T4 FINAL – MX8A

CX26C CAB T4 FINAL - MX8A

CX30C CANOPY T4 FINAL – MX8A

CX30C CAB T4 FINAL – MX8A

CX33C CANOPY T4 FINAL - MX8A

CX37C CANOPY T4 FINAL - MX8A

CX37C CAB T4 FINAL - MX8A

CX57C CAB T4 FINAL – MX5B

CX60C CAB T4 FINAL - MX5B

PLEASE NOTE: Retain the price book pages of the discontinued series for your records.

Copyright 2019 By

CNH Industrial America LLC



(This page intentionally left blank)



COMPACT EXCAVATORS TABLE OF CONTENTS

COMPACT EXCAVATORS GENERAL ANNOUNCEMENTS GENERAL INFORMATION..... CX17C CANOPY T4 FINAL COMPACT EXCAVATOR Standard Features Price List 11 Factory Supplied Attachments..... 14 CX26C CANOPY T4 FINAL COMPACT EXCAVATOR Standard Features 15 Price List 17 Factory Supplied Attachments..... 20 CX26C CAB T4 FINAL COMPACT EXCAVATOR Standard Features 21 23 Price List Factory Supplied Attachments.... 26 CX30C CANOPY T4 FINAL COMPACT EXCAVATOR Standard Features 27 Price List 29 Factory Supplied Attachments..... 32 CX30C Cab T4 FINAL COMPACT EXCAVATOR Standard Features 33 Price List 35 Factory Supplied Attachments..... 38 CX33C CANOPY T4 FINAL COMPACT EXCAVATOR 39 Standard Features Price List 41 Factory Supplied Attachments..... 44 CX37C CANOPY T4 FINAL COMPACT EXCAVATOR Standard Features 45 Price List 47 Factory Supplied Attachments..... 51 CX37C CAB T4 FINAL COMPACT EXCAVATOR Standard Features 53 Price List 55 Factory Supplied Attachments..... 59 CX57C CAB T4 FINAL COMPACT EXCAVATOR Standard Features 61 Price List 63 Factory Supplied Attachments.... 67 CX60C CAB T4 FINAL COMPACT EXCAVATOR 69 Standard Features 71 Price List Factory Supplied Attachments..... 75 Service Parts DIA List..... 76



(This page intentionally left blank)



General Announcements

Pre-Configured Packages are full model packages for Short Arm or Long Arm configurations. Once a package is selected, you can then select the required Buckets/Attachments to go along with your unit. Keep in mind, it is not possible to modify (add/remove) any other vehicle options when you select a Pre-Configured package. If a Pre-Configured unit is ordered, it will help reduce lead-time. Independent option ordering is still available if the package is not desired, however you may experience a longer lead-time.

The new C Series CASE Mini-Excavator's have a different dipper ear geometry, and therefore are not directly compatible with the previous B Series buckets. However, there are new couplers that have been developed for the C Series models to provide the ability to utilize both the B and C Series buckets. See reference table for each model:

C-Series Mini Excavator BUCKET COMPATIBILITY				
Model	del Order Code Description		B-Series Buckets	C-Series Buckets
CX17C	48057609	Coupler, Mechanical Pin-Grabber	No	Yes
	48057615	Coupler, Mechanical Pin-Grabber	No	Yes
CX26C/CX30C	48094307	Coupler, Hydraulic Pin-Grabber	Yes (requires removal of spacer plates)	Yes
evane/evane	48057623	Coupler, Mechanical Pin-Grabber	Yes	Yes
CX33C/CX37C	48058013	Coupler, Hydraulic Pin-Grabber	Yes	Yes
	48057630	Coupler, Mechanical Pin-Grabber	No	Yes
CX57C/CX60C	48058014	Coupler, Hydraulic Pin-Grabber	No	Yes
CAST CYCAGGC	48082917	Coupler, B/C Series Universal Mechanical	Yes	Yes



(This page intentionally left blank)



General Information

Prices shown herein are suggested prices only and in no way are they to be construed as limiting or restricting the dealer in his determination of the ultimate retail selling price. It is understood that the dealers are free to determine their selling price. Subject to any Federal, State or local laws.

Where shown herein liquid capacities are U.S. measure unless otherwise noted.

ADVANCE FREIGHT

Advance freight will be added to the machinery invoice as a separate net charge for machinery shipped from field locations or from other than specified Ex Works locations.

PRICES

Prices are Ex Works factory, where the goods are manufactured, except where noted. For detailed information concerning prices, please refer to your OPERATING GUIDE.

Prices and specifications are subject to change without notice.

CONTENTS OF ORGANIZATION

Case Construction Equipment Inc issues price lists and revisions covering each Case contract. U.S. Price List is published in U.S. funds. Canadian Price List is published in Canadian funds. Assure that you are using the correct price list. The Canadian price lists are denoted by a Maple Leaf on the price list cover page and the symbol "(CDN)" is printed at the head of the Factory Supplied Attachments List columns.

Freight, duty and sales taxes are NOT included in any wholegoods or attachment prices shown in the price list. Any appropriate freight, duty, Federal, State, and Provincial taxes will be added to the machinery invoice as separate net charges.

PROCEDURE

The price pages for each machine (or group of machines) lists both "Factory" and "Factory Supplied Attachments".

Each price list is comprised of the various machines sold under that contract. Each price book section has "Factory", "Factory Supplied Attachments", or "Third Party Supplied Attachments" pages. When ordering and pricing a machine follow the ordering instructions listed for that machine. Attachments listed following the "Factory Supplied Attachments" or "Third Party Supplied Attachments" heading are available for installation in the field.

ATTACHMENTS

Expect Attachments to be shipped within 2 -3 weeks from arrival to port.



General Information

DISTRIBUTION OF PRICE LISTS / REQUESTS FOR ADDITIONAL COPIES

Price lists will be provided electronically via the Dealer Portal.

Contact information for additional copies of Case Construction Equipment Price Lists

Additional price lists, divider tabs and binders may be ordered at the Document Management Center. From Dealer Portal click on Tools then Document Management Center link. Any questions you can call the Document Management Center at 262-636-7540

You will only receive price lists for contracts covered by your current Dealer Agreement with the Company.

The revisions are dated and are effective as of that date. However, PRICES ARE SUBJECT TO CHANGE WITHOUT NOTICE.



Standard Equipment

```
ENGINE:
                                                      Pre-wired telematics ready
 Kubota D902 3 Cyl. water-
                                                    BLADE:
    cooled, mechanical injection diesel
                                                      Hydraulically controlled dozer blade
  54.8 CID (0.898L)
                                                        with adjustable width
  Tier 4 Final
 Glow plugs
                                                    UNDERCARRIAGE:
 Horsepower:
                                                      Variable undercarriage (3'3" to 4'3")
   Gross 16.8 HP (12.5 kW)/2300
                                                      Track pad width: 9" (230 mm)
   Net 15.8 HP (11.8 kW)/2300
                                                      Track length: 5'3" (1590 mm)
 Maximum Engine Torque:
                                                      Gradeability: 30 degrees
      39.49 lb ft (53.54 Nm)@1900 rpm
                                                      Ground Clearance: 6.7" (170 mm)
 Dry type air cleaner
                                                    TRACK DRIVE:
OPERATOR PROTECTIVE STRUCTURE:
                                                      Two speed auto shift travel
TOPS/FOPS:
                                                      Fully hydrostatic drive system
  Two post canopy design
                                                      Track tension adjustment
  Sound Levels:
                                                        (grease type)
      ISO 6396:2008 sound pressure
                                                      Sealed and lubricated track
      level LpA=76bB (A)
                                                    HYDRAULICS:
  Mechanical Suspension seat, with
                                                      Control pattern selector valve
     2" seat belt
                                                      Hydraulic oil filter
  Pilot operated joysticks for boom,
                                                      Total Auxiliary Flow:
     arm, bucket and swing with
                                                        7.2 gpm @ 2,466 psi
     adjustable wrist rests
                                                        (27.4 L/min @ 170 bar)
  Foot pedal for swing tower
                                                      Auxiliary piping capped at end of
     control
                                                      Proportional auxiliary hydraulic flow
 Gauges:
  Engine coolant temperature and fuel
                                                        control
                                                      Selector valve for single or
     level
 Indicator Lights:
                                                        two-way aux flow
   Engine oil pressure, coolant
                                                      Large capacity hydraulic oil cooler
    temperature, battery
                                                      Cylinder rod protection covers
                                                        -Dozer and Boom
    charge, low fuel warning, engine
   preheat, air cleaner warning,
                                                    UPPER:
                                                      Standard Arm: 3'2" (0.96 m)
   hyd. quick coupler
                                                      Optional Long Arm: 3'8" (1.12 m)
   lock, and high travel speed
                                                      Boom: 5'11" (1.8 m)
ELECTRICAL:
  12 Volt electrical starting system
                                                      Boom Swing: 70° left / 54° right
     includes heavy-duty battery and
                                                      Zero Tail Swing
     starting motor
                                                    MISCELLANEOUS:
  40 Amp Alternator
                                                      Operating weight:
                                                        Canopy, short arm - 3,910 lb
 Battery Master Switch
 Key Start
                                                          (1700kg)
 Anti-Theft-Engine starting passwords
                                                        Canopy, long arm with additional
                                                          counterweight - 4,110 lbs.
 Dual 12V power plug recepticals
 Front working light
                                                          (1790 kg)
```



Standard Equipment

All weights are with rubber tracks, no quick coupler, bucket, fluids, full of fuel, and 165lb operator

Additional Counterweight - 180 lbs Warranty - Base warranty Coverage: 2-Year/3,000-Hour Full Machine Limited Warranty



Models

COMMERCIAL MODEL	TECHNICAL TYPE	Weight	Factory Data	List Price
CX17C CANOPY	698891711	3,910 LBS.		\$31,534.00

Packet	Description	Weight	Factory Data	List Price
CX17C Long Arm Pack				\$638.00
SD_30180-TRAVEL ALARM	Travel Alarm			
SD_40003-COUNTERWEIGHT	Additional Counterweight.			
SD_X5406-1ST AUX HYD TWO WAYS	2Way Aux Joystick Proportional			
SD_X6100-ARM	Long Arm - 747329			
SD_X6207-HYDR Q/C PROV.	W/O Q/C Provision			
CX17C Short Arm Pack				\$166.00
SD_30180-TRAVEL ALARM	Travel Alarm			
SD_40003-COUNTERWEIGHT	Standard Counterweight.			
SD_X5406-1ST AUX HYD TWO WAYS	2Way Aux Joystick Proportional			
SD_X6100-ARM	Short Arm - 747320			
SD_X6207-HYDR Q/C PROV.	W/O Q/C Provision			
		·	·	·

Pre-Configured Packages are full model packages for Short Arm or Long Arm configurations. Once a package is selected, you can then select the required Buckets/Attachments to go along with your unit. Keep in mind, it is not possible to modify (add/remove) any other vehicle options when you select a Pre-Configured package. If a Pre-Configured unit is ordered, it will be matched to one that is already built and ready to ship, which will reduce the lead-time by several months. Independent Option ordering is still available if the package is not desired, however you may experience a longer lead-time.



Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
OPERATOR'S MA	NUAL			
05 /5/0/ 05				
	PERATOR'S MANUAL			No Chausa
747480 747961	Operators Manual - English			No Charge
747961	Operators Manual - French Operators Manual- Spanish			No Charge No Charge
147404	Operators Manual- Spanish			No Charge
VEDCION				
VERSION				
SD 10181 CF				
9552700	Rubber Tracks			No Charge
9332700	One-piece molded rubber belt track w/ a steel cable core.			No Charge
	The entire track must be replaced at time of service. Select			
	this track for general use on soils & hard surfaces.			
	this track for general use on sons & natu surfaces.			
ADDITIONAL FOL	UDMENT MEY			
ADDITIONAL EQ	JIPMENI MEX			
OD 00400 TE	AN/EL ALADM			
SD_30180 TR				No Channa
747994	W/O Travel Alarm			No Charge
747453	Travel Alarm			\$166.00
CD 40002 CC	NUNTERWEIGHT			
747995	DUNTERWEIGHT Standard Counterweight.			No Charge
747995	Additional Counterweight.			\$146.00
147990	Additional Bolt-on weight adds 180 lb (82 kg)			Ψ140.00
	Additional Boil-on weight adds 160 ib (62 kg)			
SD X5406 19	ST AUX HYD TWO WAYS			
747233	1ST AUX PLUGS PEDAL			No Charge
747233	1ST AUX PLUGS JOYST			No Charge
747254	2Way Aux Joystick Proportional		+	\$198.00
'-1'000	1st Aux Hydraulic hoses and shut off block from boom			ψ100.00
	to end of arm.			
	to one or arms			
SD_X6100 AF	RM			
747320	Short Arm - 747320			No Charge
'7''520	0110171111 171020			140 Onlarge

Please refer to the Standard pages for arm lengths

747070 Beacon

TBD



CX17C CANOPY US PRICE LIST

		COT RICE LIGI	
	747329	Long Arm - 747329	\$327.00
		Long arm increases dig depth, resulting in a reduction in	
		arm digging forces & lift capacity. Please refer to the	
		Standard Pages for arm lengths.	
\top	SD_X6207 HY	/DR Q/C PROV. W/O Q/C Provision	No Charge
	747063	Hydraulic Q/C Provision	\$500.00
		Includes switch & hydraulic lines to end of arm	
	SD X6210 BE	EACON	
	XX6210X		No Charge



Factory Supplied Attachments

(Order Code	Description	Weight	Factory Data	List Price
KLAC	Buckets & Cou	ıpler			
	47422586	10" HD Bucket (KLAC Coupler)	88 LB		\$507.00
	47422587	12" HD Bucket (KLAC Coupler)	95 LB		\$534.00
	47422588	16" HD Bucket (KLAC Coupler)	106 LB		\$587.00
	47422589	18" HD Bucket (KLAC Coupler)	117 LB		\$655.00
	47422602	KLAC Base Plate (To adapt other buckets)	11 LB		\$237.00
	48057632	QUICK-HITCH (Compatible with both the B/C-Series KLAC buckets)	13 LB		\$848.00
Pin-O	n/Mech. Bucket	s & Coupler			
	48057605	10"HD Bucket (Pin-on/Mechanical Coupler)	79 LB		\$357.00
	48057606	12"HD Bucket (Pin-on/Mechanical Coupler)	86 LB		\$384.00
	48057607	16"HD Bucket (Pin-on/Mechanical Coupler)	97 LB		\$437.00
	48057608	18"HD Bucket (Pin-on/Mechanical Coupler)	106 LB		\$505.00
	48057609	QUICK-HITCH (Only compatible with C-Series buckets) Includes 1 set of dead pins for installation into a single bucket	29 LB		\$1,535.00
	48057610	Dead Pin Kit (for additional buckets) Required when ordering more than 1 bucket with a Pin-Grabber Coupler	5 LB		\$159.00

	C-Series Mini Excavator BUCKET COMPATIBILITY				
Model	Order Code	Description	B-Series Buckets	C-Series Buckets	
CX17C	48057609	Coupler, Mechanical Pin-Grabber	No	Yes	
	48057615	Coupler, Mechanical Pin-Grabber	No	Yes	
CX26C	48094307	Coupler, Hydraulic Pin-Grabber	Yes (requires removal of spacer plates)	Yes	
CX33C/CX37C	48057623	Coupler, Mechanical Pin-Grabber	Yes	Yes	
CASSC/CAS/C	48058013	Coupler, Hydraulic Pin-Grabber	Yes	Yes	
over a love a a	48057630	Coupler, Mechanical Pin-Grabber	No	Yes	
CX57C/CX60C	48058014	Coupler, Hydraulic Pin-Grabber	No	Yes	
	48082917	Coupler, B/C Series Universal Mechanical	Yes	Yes	



(Ex Works) Standard Equipment

```
ENGINE:
                                                      Pre-wired telematics ready
 Kubota D1305 3 Cyl. water-
                                                    BLADE:
    cooled, mechanical injection diesel
                                                      Hydraulically controlled dozer blade
 77.0 CID (1.261L)
                                                    UNDERCARRIAGE:
 Tier 4 Final
                                                      Rubber tracks
 Glow plugs
                                                      Track pad width: 9.8" (250 mm)
 Horsepower:
                                                      Track length: 6'3" (1910 mm)
   Gross 24.8 HP (18.5 kW)/2300
                                                      Gradeability: 30 degrees
   Net 23.2 HP (17.3 kW)/2300
                                                      Ground Clearance: 11" (290 mm)
                                                    TRACK DRIVE:
 Maximum Engine Torque:
      60.0 lb ft (81.4 Nm) @ 1600 rpm
                                                      Two speed Auto shift travel
 Dry type air cleaner dual element
                                                      Fully hydrostatic drive system
OPERATOR PROTECTIVE STRUCTURE:
                                                      Track tension adjustment
Sound Levels:
                                                        (grease type)
                                                      Sealed and lubricated track
     ISO 6396:2008 sound pressure
                                                    HYDRAULICS:
      level LpA=77bB (A)
ROPS/FOPS:
                                                      Control pattern selector valve
  Four post canopy design
                                                      Hydraulic oil filter
  Mechanical suspension seat, with
                                                      Total Auxiliary Flow:
     2" seat belt
                                                        12.5 gpm @ 2,538 psi
                                                        (47.2 L/min @ 175 bar)
  Pilot operated joysticks for boom, arm
                                                      Main Pump: 3,130 PSI
    bucket, and swing with adjustable
     wrist rests
                                                      Auxiliary piping capped at end of
  Foot pedals for travel control and
     swing tower control
                                                      Proportional auxiliary hydraulic flow
 Gauges:
                                                        control
  Engine coolant temperature and fuel
                                                      Selector valve for single or
                                                        two-way aux flow
     level
 Indicator Lights:
                                                      Large capacity hydraulic oil cooler
   Engine oil pressure, coolant
                                                      Cylinder rod protection covers
    temperature, battery
                                                        -Dozer & Boom
    charge, low fuel warning, engine
                                                    UPPER:
   preheat, air cleaner warning,
                                                      Standard Arm: 3'8" (1.12 m)
   hyd. quick coupler
                                                      Optional Long Arm: 4'5" (1.35 m)
                                                      Boom: 6'5" (1.95 m)
   lock, and high travel speed
                                                      Boom Swing: 75° left / 50° right
ELECTRICAL:
  12 Volt electrical starting system
                                                      Zero Tail Swing
     includes heavy-duty battery and
                                                      Bucket linkage with lifting hook
     starting motor
                                                    MISCELLANEOUS:
  40 Amp Alternator
                                                      Operating weight:
                                                        Canopy short arm- 5,520 lbs.
 Battery Master Switch
 Key Start
                                                          (2505 kg)
 Anti-Theft-Engine starting passwords
                                                        Canopy, long arm, additional
                                                          counterweight- 5,830 lbs.
 Dual 12V power plug recepticals
 Front working light
                                                          (2645 kg)
```



(Ex Works) Standard Equipment

All weights are with rubber tracks, no quick coupler, bucket, fluids, full of fuel, and 165lb operator

Additional Counterweight - 286 lbs Warranty - Base warranty Coverage: 2-Year/3,000-Hour Full Machine Limited Warranty



(Ex Works) Models

COMMERCIAL MODEL	Weight	Factory Data	List Price
CX26C CANOPY	5,520 LBS.		\$39,407.00

Packet	Description	Weight	Factory Data	List Price
CX26C Long Arm Pack			_	\$1020.00
SD_30180-TRAVEL ALARM	Travel Alarm			
SD_40003-COUNTERWEIGHT	Additional Counterweight.			
SD_X5405-2ND AUX. CIRCUIT	W/O 2nd Aux 2-Way Proportional			
SD_X5406-1ST AUX HYD TWO WAYS	2Way Aux Joystick Proportional			
SD_X5414-AUX WORKLIGHTS CAB	Working Lights			
SD_X5430-THUMB CYL BRACKET	W/O Thumb Bracket			
SD_X6100-ARM	Long Arm - 747329			
SD_X6206-LINKAGE	Linkage With Hook			
SD_X6207-HYDR Q/C PROV.	W/O Q/C Provision			
SD_X6210-BEACON	Beacon			
CX26C Short Arm Pack				\$487.00
SD_30180-TRAVEL ALARM	Travel Alarm			
SD_40003-COUNTERWEIGHT	Standard Counterweight.			
SD_X5405-2ND AUX. CIRCUIT	W/O 2nd Aux 2-Way Proportional			
SD_X5406-1ST AUX HYD TWO WAYS	2Way Aux Joystick Proportional			
SD_X5414-AUX WORKLIGHTS CAB	Working Lights			
SD_X5430-THUMB CYL BRACKET	W/O Thumb Bracket			
SD_X6100-ARM	Short Arm - 747320			
SD_X6206-LINKAGE	Linkage With Hook	_		
SD_X6207-HYDR Q/C PROV.	W/O Q/C Provision	_		
SD_X6210-BEACON	Beacon			

Pre-Configured Packages are full model packages for Short Arm or Long Arm configurations. Once a package is selected, you can then select the required Buckets/Attachments to go along with your unit. Keep in mind, it is not possible to modify (add/remove) any other vehicle options when you select a Pre-Configured package. If a Pre-Configured unit is ordered, it will be matched to one that is already built and ready to ship, which will reduce the lead-time by several months. Independent Option ordering is still available if the package is not desired, however you may experience a longer lead-time.



(Ex Works)

Factory Supplied Options

accord complete a complete and					
Order Code	Description	Weight	Factory Data	List Price	
OPERATOR'S MA	ANUAL				
SD 47181 O	PERATOR'S MANUAL				
747480	Operators Manual - English			No Charge	
747961	Operators Manual - French			No Charge	
747464	Operators Manual- Spanish			No Charge	
VERSION					
	RAWLER TYPE				
9552700				No Charge	
	One-piece molded rubber belt track w/ a steel cable core.				
	The entire track must be replaced at time of service. Select				
	this track for general use on soils & hard surfaces.				
ADDITIONAL FO	HIDMFNT MEV				
ADDITIONAL EQ	UIPMENT MEX				
SD_30180 TF	RAVEL ALARM				
747994	W/O Travel Alarm			No Charge	
747453	Travel Alarm			\$207.00	
	•	•		·	
SD_40003 C	OUNTERWEIGHT				
747995	Standard Counterweight.			No Charge	
747996	Additional Counterweight.			\$206.00	
	Additional bolt on weight adds 286 lb (130 kg) - CX26C				
	Additional bolt on weight adds 330 lb (150 kg) - CX37C				
	CX37C - Add. Cwt comes w/ Angle Blade				
	ND AUX. CIRCUIT			7	
747999	W/O 2nd Aux 2-Way Proportional			No Charge	
747053	2nd Aux 2-Way Proportional			\$1,633.00	
	CX37C - if ordering Angle Blade - 2nd 2-way Aux is used				
	for the angle circuit. Cannot order 747053 with 747981				
	4-way Angle Blade.				
1 1 1		1	1		

NOTE: 2nd Aux INCLUDES 1st Aux hose options.

XX6210X W/O Beacon

Beacon

747070



CX26C CANOPY US PRICE LIST

(Ex Works)

747233	1ST AUX PLUGS PEDAL	No Charge
747234	1ST AUX PLUGS JOYST	No Charge
747055	2Way Aux Joystick Proportional	\$198.00
	1st Aux Hydraulic hoses and shut off block from boom	
	to end of arm.	
05 1/2/00 -	WWW 2014 2014 27	
	HUMB CYL BRACKET	
747059	W/O Thumb Bracket	No Charge
747058	Thumb Bracket	\$443.00
SD_X6100 AF	RM	
747320	Short Arm - 747320	No Charge
	Please refer to the Standard pages for arm lengths	
747329	Long Arm - 747329	\$327.00
	Long arm increases dig depth, resulting in a reduction in	
	arm digging forces & lift capacity. Please refer to the	
	Standard Pages for arm lengths.	
•		•
SD_X6206 LI	NKAGE	
747062	Linkage With Hook	No Charge
747063	Linkage Without Hook	(\$61.00)
	YDR Q/C PROV.	
747065	W/O Q/C Provision	No Charge
747064	Hydraulic Q/C Provision	\$500.00
I	Includes switch & hydraulic lines to end of arm	

No Charge \$280.00



(Ex Works)

Factory Supplied Attachments

Orde	er Code	Description	Weight	Factory Data	List Price
(LAC Bu	ckets & Co	oupler			
48	094116	12"HD Bucket (KLAC Coupler)	143 LB		\$524.00
48	094117	18"HD Bucket (KLAC Coupler)	176 LB		\$625.00
48	094118	24"HD Bucket (KLAC Coupler)	209 LB		\$800.00
48	057633	Coupler, KLAC	71 LB		\$1,102.00
47	422632	KLAC Base Plate (To adapt other buckets)	20 LB		\$285.00
Pin-On Bu	uckets & C	Coupler			
-	057611	12"HD Bucket (Mech/Hyd Coupler)	121 LB		\$521.00
48	057612	18"HD Bucket (Mech/Hyd Coupler)	154 LB		\$623.00
48	057613	24"HD Bucket (Mech/Hyd Coupler)	185 LB		\$797.00
48	057615	Coupler, Mechanical Pin-Grabber (Only compatible with the C-Series bucket) Includes 1 set of dead pins for installation into a single bucket	95 LB		\$1,538.00
48	094307	Coupler,Hydraulic Pin-Grabber (Compatible with both the B/C-Series buckets, when used with a B-Series bucket, it requires the removal of the spacer plates) Includes 1 set of dead pins for installation into a single bucket	99 LB		\$3,386.00
47	457879	Dead Pin Kit Required when ordering more than 1 bucket with a Pin- Grabber Coupler	8 LB		\$177.00
humbs					
1	058019	Thumb Kit, Hyd., Short Tines (Use with direct fit, KLAC buckets and Mechanical Pin-Grabber coupler)	150 LB		\$2,248.00
48	094114	Thumb Kit, Hyd., Long Tines (Use w/Hyd. Pin-Grabber coupler only)	150 LB		\$2,248.00

	C-Series Mini Excavator BUCKET COMPATIBILITY						
Model	Order Code	Description	B-Series Buckets	C-Series Buckets			
CX17C	48057609	Coupler, Mechanical Pin-Grabber	No	Yes			
	48057615	Coupler, Mechanical Pin-Grabber	No	Yes			
CX26C	48094307	Coupler, Hydraulic Pin-Grabber	Yes (requires removal of spacer plates)	Yes			
CX33C/CX37C	48057623	Coupler, Mechanical Pin-Grabber	Yes	Yes			
CASSC/CAS/C	48058013	Coupler, Hydraulic Pin-Grabber	Yes	Yes			
aveza laveno	48057630	Coupler, Mechanical Pin-Grabber	No	Yes			
CX57C/CX60C	48058014	Coupler, Hydraulic Pin-Grabber	No	Yes			
	48082917	Coupler, B/C Series Universal Mechanical	Yes	Yes			



(Ex Works) Standard Equipment

```
ENGINE:
                                                      Anti-theft-engine starting passwords
 Kubota D1305 3 Cyl. water-
                                                      Dual 12V power plug recepticals
    cooled, mechanical injection diesel
                                                      Front working Light
 77.0 CID (1.261L)
                                                      Pre-wired telematics ready
 Tier 4 Final
                                                    BLADE:
 Glow plugs
                                                      Hydraulically controlled dozer blade
 Horsepower:
                                                    UNDERCARRIAGE:
   Gross 24.8 HP (18.5 kW)/2300
                                                      Rubber tracks
   Net 23.2 HP (17.3 kW)/2300
                                                      Track pad width: 9.8" (250 mm)
 Maximum Engine Torque:
                                                      Track length: 6'3" (1910 mm)
      60.0 lb ft (81.4 Nm) @ 1600 rpm
                                                      Gradeability: 30 degrees
 Dry type air cleaner dual element
                                                      Ground clearance: 11" (290 mm)
OPERATOR PROTECTIVE STRUCTURE:
                                                    TRACK DRIVE:
Sound Levels:
                                                      Two speed auto shift travel
     ISO 6396:2008 sound pressure
                                                      Fully hydrostatic drive system
      level LpA=77bB (A)
                                                      Track tension adjustment
ROPS/FOPS:
                                                        (grease type)
                                                      Sealed and lubricated track
  Enclosed Cab with overhead opening
     front window, sliding side window,
                                                    HYDRAULICS:
     lockable door, heater and defroster,
                                                      Control pattern selector valve
     radio/USB player + 2 speakers
                                                      Hydraulic oil filter
  Mechanical suspension seat, with
                                                      Total Auxiliary Flow:
    2" seat belt
                                                        12.5 gpm @ 2,538 psi
  Pilot operated joysticks for boom,
                                                        (47.2 L/min @ 175 bar)
     arm, bucket and swing with
                                                      Main Pump: 3,130 PSI
     adjustable wrist rests
                                                      Auxiliary piping capped at end of
  Foot pedals for travel control and
     swing tower control
                                                      Proportional auxiliary hydraulic flow
Gauges:
                                                        control
  Engine coolant temperature and fuel
                                                      Selector valve for single or
     level
                                                        two-way aux flow
 Indicator Lights:
                                                      Large capacity hydraulic oil cooler
    Engine oil pressure, coolant
                                                      Cylinder rod protection covers
                                                        -Dozer & Boom
    temperature, battery
                                                    UPPER:
    charge, low fuel warning, engine
                                                      Standard Arm: 3'8" (1.12 m)
    preheat, air cleaner warning,
   hyd. quick coupler
                                                      Optional Long Arm: 4'5" (1.35 m)
   lock, and high travel speed
                                                      Boom: 6'5" (1.95 m)
ELECTRICAL:
                                                      Boom Swing: 75° left / 50° right
                                                      Zero Tail Swing
  12 Volt electrical starting system
                                                      Bucket Linkage with lifting hook
     includes heavy-duty battery and
                                                    MISCELLANEOUS:
     starting motor
  40 Amp Alternator
                                                      Operating weight:
 Battery master switch
                                                        Cab, short arm - 5,850 lbs (2655 kg)
                                                        Cab, long arm, additional
 Key start
```



(Ex Works) Standard Equipment

counterweight- 6,160 lbs (2795 kg) All weights are with rubber tracks, no quick coupler, bucket, fluids, full of fuel, and 165lb operator

Additional Counterweight - 286 lbs Warranty - Base warranty Coverage: 2-Year/3,000-Hour Full Machine Limited Warranty



(Ex Works) Models

COMMERCIAL MODEL	Weight	Factory Data	List Price
CX26C CAB	5,850 LBS.		\$44,240.00

Packet	Description	Weight	Factory Data	List Price
CX26C CAB Long Arm			_	\$1020.00
SD_05136-RADIO OPTION	Radio and USB			
SD_30180-TRAVEL ALARM	Travel Alarm			
SD_40003-COUNTERWEIGHT	Additional Counterweight.			
SD_X5183-AIR COND/HEATER	Heater Only			
SD_X5405-2ND AUX. CIRCUIT	W/O 2nd Aux 2-Way Proportional			
SD_X5406-1ST AUX HYD TWO WAYS	2Way Aux Joystick Proportional			
SD_X5414-AUX WORKLIGHTS CAB	Working Lights			
SD_X5430-THUMB CYL BRACKET	W/O Thumb Bracket			
SD_X6100-ARM	Long Arm - 747329			
SD_X6206-LINKAGE	Linkage With Hook			
SD_X6207-HYDR Q/C PROV.	W/O Q/C Provision			
SD_X6210-BEACON	Beacon			
CX26C CAB Short Arm				\$487.00
SD_05136-RADIO OPTION	Radio and USB			
SD_30180-TRAVEL ALARM	Travel Alarm			
SD_40003-COUNTERWEIGHT	Standard Counterweight.			
SD_X5183-AIR COND/HEATER	Heater Only			
SD_X5406-1ST AUX HYD TWO WAYS	2Way Aux Joystick Proportional			
SD_X5414-AUX WORKLIGHTS CAB	Working Lights			
SD_X5430-THUMB CYL BRACKET	W/O Thumb Bracket			
SD_X6100-ARM	Short Arm - 747320			
SD_X6206-LINKAGE	Linkage With Hook			
SD_X6207-HYDR Q/C PROV.	W/O Q/C Provision			
SD_X6210-BEACON	Beacon			

Pre-Configured Packages are full model packages for Short Arm or Long Arm configurations. Once a package is selected, you can then select the required Buckets/Attachments to go along with your unit. Keep in mind, it is not possible to modify (add/remove) any other vehicle options when you select a Pre-Configured package. If a Pre-Configured unit is ordered, it will be matched to one that is already built and ready to ship, which will reduce the lead-time by several months. Independent Option ordering is still available if the package is not desired, however you may experience a longer lead-time.



(Ex Works)

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
OPERATOR'S MA	ANUAL			
SD 47181 OF	PERATOR'S MANUAL			
747480	Operators Manual - English			No Charge
747961	Operators Manual - French			No Charge
747464	Operators Manual- Spanish			No Charge
VERSION				
	RAWLER TYPE			
9552700				No Charge
	One-piece molded rubber belt track w/ a steel cable core.			
	The entire track must be replaced at time of service. Select			
	this track for general use on soils & hard surfaces.			
ADDITIONAL EQ	UIPMENT MEX			
CD 20400 TE	DAVEL ALADM			
SD_30180 TF 747994	W/O Travel Alarm			No Charge
747994	Travel Alarm	-		\$207.00
1 1 141400	Havorriann		11_	Ψ207.00
SD 40003 CO	DUNTERWEIGHT			
747995	Standard Counterweight.			No Charge
747996	Additional Counterweight.			\$206.00
	Additional bolt on weight adds 286 lb (130 kg) - CX26C			
	Additional bolt on weight adds 330 lb (150 kg) - CX37C			
	CX37C - Add. Cwt comes w/ Angle Blade			
	,		'	
SD_X5405 2N	ND AUX. CIRCUIT			
747999	W/O 2nd Aux 2-Way Proportional			No Charge
747053	2nd Aux 2-Way Proportional			\$1,633.00
	CX37C - if ordering Angle Blade - 2nd 2-way Aux is used			
	for the angle circuit. Cannot order 747053 with 747981			
	4-way Angle Blade.			

NOTE: 2nd Aux INCLUDES 1st Aux hose options.

XX6210X W/O Beacon

Beacon

747070



CX26C CAB US PRICE LIST

(Ex Works)

747233	1ST AUX PLUGS PEDAL	No Charge
747234	1ST AUX PLUGS JOYST	No Charge
747055	2Way Aux Joystick Proportional	\$198.00
	1st Aux Hydraulic hoses and shut off block from boom	
	to end of arm.	
OD V5400 T	WIND OW DDAGKET	
	HUMB CYL BRACKET	N. Observe
747059	W/O Thumb Bracket	No Charge
747058	Thumb Bracket	\$443.00
SD_X6100 AI	RM	
747320	Short Arm - 747320	No Charge
	Please refer to the Standard pages for arm lengths	
747329	Long Arm - 747329	\$327.00
	Long arm increases dig depth, resulting in a reduction in	
	arm digging forces & lift capacity. Please refer to the	
	Standard Pages for arm lengths.	
SD_X6206 LI		
	Linkage With Hook	No Charge
747062	Linkage Without Hook	(\$61.00)
747062		
747063	VDR O/C PROV	
747063 SD_X6207 H	YDR Q/C PROV. W/O Q/C Provision	No Charge
747063	YDR Q/C PROV. W/O Q/C Provision Hydraulic Q/C Provision	No Charge \$500.00

Page	25	of	76
------	----	----	----

No Charge \$280.00



(Ex Works) Factory Supplied Attachments

Order Code	Description	Weight	Factory Data	List Price
(LAC Buckets & Co	oupler			
48094116	12"HD Bucket (KLAC Coupler)	143 LB		\$524.00
48094117	18"HD Bucket (KLAC Coupler)	176 LB		\$625.00
48094118	24"HD Bucket (KLAC Coupler)	209 LB		\$800.00
48057633	Coupler, KLAC	71 LB		\$1,102.00
47422632	KLAC Base Plate (To adapt other buckets)	20 LB		\$285.00
Pin-On Buckets & C	Coupler			
48057611	12"HD Bucket (Mech/Hyd Coupler)	121 LB		\$521.00
48057612	18"HD Bucket (Mech/Hyd Coupler)	154 LB		\$623.00
48057613	24"HD Bucket (Mech/Hyd Coupler)	185 LB		\$797.00
48057615	Coupler, Mechanical Pin-Grabber (Only compatible with the C-Series bucket) Includes 1 set of dead pins for installation into a single bucket	95 LB		\$1,538.00
48094307	Coupler,Hydraulic Pin-Grabber (Compatible with both the B/C-Series buckets, when used with a B-Series bucket, it requires the removal of the spacer plates) Includes 1 set of dead pins for installation into a single bucket	99 LB		\$3,386.00
47457879	Dead Pin Kit Required when ordering more than 1 bucket with a Pin- Grabber Coupler	8 LB		\$177.00
Thumbs				
48058019	Thumb Kit, Hyd., Short Tines (Use with direct fit, KLAC buckets and Mechanical Pin-Grabber coupler)	150 LB		\$2,248.00
48094114	Thumb Kit, Hyd., Long Tines (Use w/Hyd. Pin-Grabber coupler only)	150 LB		\$2,248.00

	C-Series Mini Excavator BUCKET COMPATIBILITY						
Model	Order Code	Description	B-Series Buckets	C-Series Buckets			
CX17C	48057609	Coupler, Mechanical Pin-Grabber	No	Yes			
	48057615	Coupler, Mechanical Pin-Grabber	No	Yes			
CX26C	48094307	Coupler, Hydraulic Pin-Grabber	Yes (requires removal of spacer plates)	Yes			
CX33C/CX37C	48057623	Coupler, Mechanical Pin-Grabber	Yes	Yes			
CASSC/CAS/C	48058013	Coupler, Hydraulic Pin-Grabber	Yes	Yes			
over a loveno	48057630	Coupler, Mechanical Pin-Grabber	No	Yes			
CX57C/CX60C	48058014	Coupler, Hydraulic Pin-Grabber	No	Yes			
	48082917	Coupler, B/C Series Universal Mechanical	Yes	Yes			



(Ex Works) Standard Equipment

```
ENGINE:
                                                      Pre-wired telematics ready
 Kubota D1305 3 Cyl. water-
                                                    BLADE:
    cooled, mechanical injection diesel
                                                      Hydraulically controlled dozer blade
 77.0 CID (1.261L)
                                                    UNDERCARRIAGE:
 Tier 4 Final
                                                      Rubber tracks
 Glow plugs
                                                      Track pad width: 11.8" (250 mm)
 Horsepower:
                                                      Track length: 6'6" (1910 mm)
   Gross 24.8 HP (18.5 kW)/2300
                                                      Gradeability: 30 degrees
   Net 23.2 HP (17.3 kW)/2300
                                                      Ground Clearance: 11" (290 mm)
                                                    TRACK DRIVE:
 Maximum Engine Torque:
      60.0 lb ft (81.4 Nm) @ 1600 rpm
                                                      Two speed Auto shift travel
 Dry type air cleaner dual element
                                                      Fully hydrostatic drive system
OPERATOR PROTECTIVE STRUCTURE:
                                                      Track tension adjustment
Sound Levels:
                                                        (grease type)
                                                      Sealed and lubricated track
     ISO 6396:2008 sound pressure
                                                    HYDRAULICS:
      level LpA=73.5bB (A)
ROPS/FOPS:
                                                      Control pattern selector valve
  Four post canopy design
                                                      Hydraulic oil filter
  Mechanical suspension seat, with
                                                      Total Auxiliary Flow:
     2" seat belt
                                                        12.5 gpm @ 2,538 psi
  Pilot operated joysticks for boom, arm
                                                        (47.2 L/min @ 175 bar)
                                                      Main Pump: 3,130 PSI
    bucket, and swing with adjustable
     wrist rests
                                                      Auxiliary piping capped at end of
  Foot pedals for travel control and
     swing tower control
                                                      Proportional auxiliary hydraulic flow
 Gauges:
                                                        control
  Engine coolant temperature and fuel
                                                      Selector valve for single or
                                                        two-way aux flow
     level
 Indicator Lights:
                                                      Large capacity hydraulic oil cooler
   Engine oil pressure, coolant
                                                      Cylinder rod protection covers
    temperature, battery
                                                        -Dozer & Boom
    charge, low fuel warning, engine
                                                    UPPER:
   preheat, air cleaner warning,
                                                      Standard Arm: 3'8" (1.12 m)
                                                      Boom: 6'8" (1.95 m)
   hyd. quick coupler
                                                      Boom Swing: 75° left / 50° right
   lock, and high travel speed
ELECTRICAL:
                                                      Zero Tail Swing
                                                      Bucket linkage with lifting hook
  12 Volt electrical starting system
     includes heavy-duty battery and
                                                    MISCELLANEOUS:
     starting motor
                                                      Operating weight:
                                                        Canopy short arm- 6,020 lbs.
  40 Amp Alternator
 Battery Master Switch
                                                          (2505 kg)
 Key Start
 Anti-Theft-Engine starting passwords
 Dual 12V power plug recepticals
 Front working light
```



(Ex Works) Standard Equipment

All weights are with rubber tracks, no quick coupler, bucket, fluids, full of fuel, and 165lb operator

Additional Counterweight - 286 lbs Warranty - Base warranty Coverage: 2-Year/3,000-Hour Full Machine Limited Warranty



(Ex Works) Models

COMMERCIAL MODEL	Weight	Factory Data	List Price
CX30C CANOPY	6,306 LBS.		\$44,836.00
Includes the following Equipment Additional Counterweight. (747996)	\$206.00		

Packet	Description	Weight	Factory Data	List Price
CX30C Rops Std Arm				\$693.00
SD_30180-TRAVEL ALARM	Travel Alarm			
SD_40003-COUNTERWEIGHT	Additional Counterweight.			
SD_X5405-2ND AUX. CIRCUIT	W/O 2nd Aux 2-Way Proportional			
SD_X5406-1ST AUX HYD TWO WAYS	2Way Aux Joystick Proportional			
SD_X5414-AUX WORKLIGHTS CAB	Working Lights]		
SD_X5430-THUMB CYL BRACKET	W/O Thumb Bracket]		
SD_X6100-ARM	Short Arm - 747320			
SD_X6206-LINKAGE	Linkage With Hook			
SD_X6207-HYDR Q/C PROV.	W/O Q/C Provision			
SD_X6210-BEACON	Beacon			
SD_X9725-HOMOLOGATION	W/O CE HOM NAFTA AEM			
SD_X6210-BEACON				

Pre-Configured Package is full model packages for Standard Arm configurations. Once a package is selected, you can then select the required Buckets/Attachments to go along with your unit. Keep in mind, it is not possible to modify (add/remove) any other vehicle options when you select a Pre-Configured package. If a Pre-Configured unit is ordered, it will be matched to one that is already built and ready to ship, which will reduce the lead-time by several months. Independent Option ordering is still available if the package is not desired, however you may experience a longer lead-time.

to end of arm.



CX30C CANOPY US PRICE LIST

(Ex Works)

Factory Supplied Options

	, , , ,						
0	rder Code	Description	Weight	Factory Data	List Price		
OPE	ERATOR'S MA	ANUAL					
		PERATOR'S MANUAL		1			
	747480	Operators Manual - English			No Charge		
	747961	Operators Manual - French			No Charge		
ш	747464	Operators Manual- Spanish			No Charge		
VEF	RSION						
	SD_10181 CF	T		T			
	9552700				No Charge		
		One-piece molded rubber belt track w/ a steel cable core.					
		The entire track must be replaced at time of service. Select					
		this track for general use on soils & hard surfaces.					
ADI	DITIONAL EQ	UIPMENT MEX					
	SD_30180 TF	RAVEL ALARM					
	747994	W/O Travel Alarm			No Charge		
	747453	Travel Alarm			\$207.00		
	SD_X5405 2N	ND AUX. CIRCUIT			1		
	747999	W/O 2nd Aux 2-Way Proportional			No Charge		
	747053	2nd Aux 2-Way Proportional			\$1,633.00		
		CX37C - if ordering Angle Blade - 2nd 2-way Aux is used					
		for the angle circuit. Cannot order 747053 with 747981					
		4-way Angle Blade.					
		NOTE: 2nd Aux INCLUDES 1st Aux hose options.					
	SD_X5406 1S	ST AUX HYD TWO WAYS					
	747233	1ST AUX PLUGS PEDAL			No Charge		
	747234	1ST AUX PLUGS JOYST			No Charge		
	747055	2Way Aux Joystick Proportional			\$198.00		
		1st Aux Hydraulic hoses and shut off block from boom					
	1	to and of ann		1			



(Ex Works)

SD X5430 TI	HUMB CYL BRACKET	
747059	W/O Thumb Bracket	No Charge
747058	Thumb Bracket	\$443.00
SD_X6100 AI	RM	
747320	Short Arm - 747320	No Charge
	Please refer to the Standard pages for arm lengths	
SD_X6206 LI	NKAGE	
747062	Linkage With Hook	No Charge
747063	Linkage Without Hook	(\$61.00)
SD_X6207 H	YDR Q/C PROV.	
747065	W/O Q/C Provision	No Charge
747064	Hydraulic Q/C Provision	\$500.00
	Includes switch & hydraulic lines to end of arm	
SD_X6210 BI	EACON	
XX6210X	W/O Beacon	No Charge
747070	Beacon	\$280.00



(Ex Works)

Factory Supplied Attachments

Order Code	Description	Weight	Factory Data	List Price
I-Position Pin-On				
48190704	12" Bucket 1-POS PIN-ON			\$773.00
	ONLY for usage w/o a coupler.			
48190705	18" Bucket 1-POS PIN-ON			\$856.00
	ONLY for usage w/o a coupler.			
48190706	24" Bucket 1 POS PIN-ON			\$998.00
	ONLY for usage w/o a coupler.			
(LAC Buckets & Co	pupler			
48094116	12"HD Bucket (KLAC Coupler)	143 LB		\$524.00
48094117	18"HD Bucket (KLAC Coupler)	176 LB		\$625.00
48094118	24"HD Bucket (KLAC Coupler)	209 LB		\$800.00
48057633	Coupler, KLAC	71 LB		\$1,102.00
47422632	KLAC Base Plate (To adapt other buckets)	20 LB		\$285.00
Pin-On Buckets & C	Coupler 12"HD Bucket (Mech/Hyd Coupler)	121 LB		\$521.00
- 				Ŧ
48057612	18"HD Bucket (Mech/Hyd Coupler)	154 LB		\$623.00
48057613	24"HD Bucket (Mech/Hyd Coupler)	185 LB		\$797.00
48057615	Coupler, Mechanical Pin-Grabber (Only compatible with the C-Series bucket) Includes 1 set of dead pins for installation into a single bucket	95 LB		\$1,538.00
48094307	Coupler, Hydraulic Pin-Grabber (Compatible with both the B/C-Series buckets, when used with a B-Series bucket, it requires the removal of the spacer plates) Includes 1 set of dead pins for installation into a single bucket	99 LB		\$3,386.00
47457879	Dead Pin Kit Required when ordering more than 1 bucket with a Pin- Grabber Coupler	8 LB		\$177.00
humbs				
48058019	Thumb Kit, Hyd., Short Tines (Use with direct fit, KLAC buckets and Mechanical Pin-Grabber coupler)	150 LB		\$2,248.00
48094114	Thumb Kit, Hyd., Long Tines (Use w/Hyd. Pin-Grabber coupler only)	150 LB		\$2,248.00

C-Series Mini Excavator BUCKET COMPATIBILITY				
Model	Order Code	Description	B-Series Buckets	C-Series Buckets
CX17C	48057609	Coupler, Mechanical Pin-Grabber	No	Yes
	48057615	Coupler, Mechanical Pin-Grabber	No	Yes
CX26C	48094307	Coupler, Hydraulic Pin-Grabber	Yes (requires removal of spacer plates)	Yes
CX33C/CX37C	48057623	Coupler, Mechanical Pin-Grabber	Yes	Yes
сиоос/сиоле	48058013	Coupler, Hydraulic Pin-Grabber	Yes	Yes
aveza loveno	48057630	Coupler, Mechanical Pin-Grabber	No	Yes
CX57C/CX60C	48058014	Coupler, Hydraulic Pin-Grabber	No	Yes
	48082917	Coupler, B/C Series Universal Mechanical	Yes	Yes

Key start



CX30C CAB US PRICE LIST

(Ex Works) Standard Equipment

```
ENGINE:
                                                      Anti-theft-engine starting passwords
 Kubota D1305 3 Cyl. water-
                                                      Dual 12V power plug recepticals
    cooled, mechanical injection diesel
                                                      Front working Light
 77.0 CID (1.261L)
                                                      Pre-wired telematics ready
 Tier 4 Final
                                                    BLADE:
 Glow plugs
                                                      Hydraulically controlled dozer blade
 Horsepower:
                                                    UNDERCARRIAGE:
    Gross 24.8 HP (18.5 kW)/2300
                                                      Rubber tracks
   Net 23.2 (17.3 kW)/2300
                                                      Track pad width: 11.8" (250 mm)
 Maximum Engine Torque:
                                                      Track length: 6'6" (1910 mm)
      60.0 lb ft (81.4 Nm) @ 1600 rpm
                                                      Gradeability: 30 degrees
 Dry type air cleaner dual element
                                                      Ground clearance: 11" (290 mm)
OPERATOR PROTECTIVE STRUCTURE:
                                                    TRACK DRIVE:
Sound Levels:
                                                      Two speed auto shift travel
     ISO 6396:2008 sound pressure
                                                      Fully hydrostatic drive system
      level LpA=73.5bB (A)
                                                      Track tension adjustment
ROPS/FOPS:
                                                        (grease type)
                                                      Sealed and lubricated track
  Enclosed Cab with overhead opening
     front window, sliding side window,
                                                    HYDRAULICS:
     lockable door, heater and defroster,
                                                      Control pattern selector valve
     radio/USB player + 2 speakers
                                                      Hydraulic oil filter
  Mechanical suspension seat, with
                                                      Total Auxiliary Flow:
    2" seat belt
                                                        12.5 gpm @ 2,538 psi
  Pilot operated joysticks for boom,
                                                        (47.2 L/min @ 175 bar)
     arm, bucket and swing with
                                                      Main Pump: 3,130 PSI
     adjustable wrist rests
                                                      Auxiliary piping capped at end of
  Foot pedals for travel control and
     swing tower control
                                                      Proportional auxiliary hydraulic flow
Gauges:
                                                        control
  Engine coolant temperature and fuel
                                                      Selector valve for single or
     level
                                                        two-way aux flow
 Indicator Lights:
                                                      Large capacity hydraulic oil cooler
    Engine oil pressure, coolant
                                                      Cylinder rod protection covers
                                                        -Dozer & Boom
    temperature, battery
                                                    UPPER:
    charge, low fuel warning, engine
                                                      Standard Arm: 3'8" (1.12 m)
    preheat, air cleaner warning,
   hyd. quick coupler
                                                      Boom: 6'8" (1.95 m)
   lock, and high travel speed
                                                      Boom Swing: 75° left / 50° right
ELECTRICAL:
                                                      Zero Tail Swing
  12 Volt electrical starting system
                                                      Bucket Linkage with lifting hook
     includes heavy-duty battery and
                                                    MISCELLANEOUS:
     starting motor
                                                      Operating weight:
  40 Amp Alternator
                                                        Cab, short arm - 6,350 lbs (2655 kg)
 Battery master switch
```



(Ex Works) Standard Equipment

All weights are with rubber tracks, no quick coupler, bucket, fluids, full of fuel, and 165lb operator

Additional Counterweight - 286 lbs Warranty - Base warranty Coverage: 2-Year/3,000-Hour Full Machine Limited Warranty



(Ex Works) Models

COMMERCIAL MODEL	Weight	Factory Data	List Price
CX30C CAB	6,636 LBS.		\$49,340.00
Includes the following Equipment Additional Counterweight. (747996)	\$206.00		

Packet	Description	Weight	Factory Data	List Price
CX30C Cab Std Arm				\$693.00
SD_05136-RADIO OPTION	Radio and USB			
SD_30180-TRAVEL ALARM	Travel Alarm			
SD_40003-COUNTERWEIGHT	Additional Counterweight.			
SD_X5183-AIR COND/HEATER	Heater Only			
SD_X5406-1ST AUX HYD TWO WAYS	2Way Aux Joystick Proportional			
SD_X5414-AUX WORKLIGHTS CAB	Working Lights			
SD_X5430-THUMB CYL BRACKET	W/O Thumb Bracket			
SD_X6100-ARM	Short Arm - 747320			
SD_X6206-LINKAGE	Linkage With Hook			
SD_X6207-HYDR Q/C PROV.	W/O Q/C Provision			
SD_X6210-BEACON	Beacon			
SD_X9725-HOMOLOGATION	W/O CE HOM NAFTA AEM			

Pre-Configured Package is full model packages for Standard Arm configurations. Once a package is selected, you can then select the required Buckets/Attachments to go along with your unit. Keep in mind, it is not possible to modify (add/remove) any other vehicle options when you select a Pre-Configured package. If a Pre-Configured unit is ordered, it will be matched to one that is already built and ready to ship, which will reduce the lead-time by several months. Independent Option ordering is still available if the package is not desired, however you may experience a longer lead-time.

to end of arm.



CX30C CAB US PRICE LIST

(Ex Works)

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
OPERATOR'S MA	ANIIAI			
or Environce in	IIIO/IL			
T T T	PERATOR'S MANUAL		1	
747480	Operators Manual - English			No Charge
747961	Operators Manual - French			No Charge
747464	Operators Manual- Spanish			No Charge
VERSION				
SD_10181 CI	RAWLER TYPE			
9552700	Rubber Tracks			No Charge
	One-piece molded rubber belt track w/ a steel cable core.			
	The entire track must be replaced at time of service. Select			
	this track for general use on soils & hard surfaces.			
ADDITIONAL EQ	UIPMENT MEX			
SD_30180 TF	RAVEL ALARM			
SD_30180 TF	RAVEL ALARM W/O Travel Alarm			No Charge
747994	W/O Travel Alarm			
747994 747453 SD_X5405 21	W/O Travel Alarm Travel Alarm D AUX. CIRCUIT			\$207.00
747994 747453 SD_X5405 2t 747999	W/O Travel Alarm Travel Alarm ID AUX. CIRCUIT W/O 2nd Aux 2-Way Proportional			\$207.00 No Charge
747994 747453 SD_X5405 21	W/O Travel Alarm Travel Alarm ND AUX. CIRCUIT W/O 2nd Aux 2-Way Proportional 2nd Aux 2-Way Proportional			\$207.00 No Charge
747994 747453 SD_X5405 2t 747999	W/O Travel Alarm Travel Alarm ID AUX. CIRCUIT W/O 2nd Aux 2-Way Proportional			\$207.00 No Charge
747994 747453 SD_X5405 2t 747999	W/O Travel Alarm Travel Alarm ND AUX. CIRCUIT W/O 2nd Aux 2-Way Proportional 2nd Aux 2-Way Proportional			\$207.00 No Charge
747994 747453 SD_X5405 2t 747999	W/O Travel Alarm Travel Alarm ND AUX. CIRCUIT W/O 2nd Aux 2-Way Proportional 2nd Aux 2-Way Proportional CX37C - if ordering Angle Blade - 2nd 2-way Aux is used			\$207.00 No Charge
747994 747453 SD_X5405 2h 747999	W/O Travel Alarm Travel Alarm ND AUX. CIRCUIT W/O 2nd Aux 2-Way Proportional 2nd Aux 2-Way Proportional CX37C - if ordering Angle Blade - 2nd 2-way Aux is used for the angle circuit. Cannot order 747053 with 747981 4-way Angle Blade.			No Charge \$207.00 No Charge \$1,633.00
747994 747453 SD_X5405 2t 747999	W/O Travel Alarm Travel Alarm ND AUX. CIRCUIT W/O 2nd Aux 2-Way Proportional 2nd Aux 2-Way Proportional CX37C - if ordering Angle Blade - 2nd 2-way Aux is used for the angle circuit. Cannot order 747053 with 747981			\$207.00 No Charge
747994 747453 SD_X5405 21 747999 747053	W/O Travel Alarm Travel Alarm ND AUX. CIRCUIT W/O 2nd Aux 2-Way Proportional 2nd Aux 2-Way Proportional CX37C - if ordering Angle Blade - 2nd 2-way Aux is used for the angle circuit. Cannot order 747053 with 747981 4-way Angle Blade.			\$207.00 No Charge
747994 747453 SD_X5405 21 747999 747053	W/O Travel Alarm Travel Alarm ND AUX. CIRCUIT W/O 2nd Aux 2-Way Proportional 2nd Aux 2-Way Proportional CX37C - if ordering Angle Blade - 2nd 2-way Aux is used for the angle circuit. Cannot order 747053 with 747981 4-way Angle Blade. NOTE: 2nd Aux INCLUDES 1st Aux hose options.			\$207.00 No Charge
747994 747453 SD_X5405 2N 747999 747053 SD_X5406 1S	W/O Travel Alarm Travel Alarm ND AUX. CIRCUIT W/O 2nd Aux 2-Way Proportional 2nd Aux 2-Way Proportional CX37C - if ordering Angle Blade - 2nd 2-way Aux is used for the angle circuit. Cannot order 747053 with 747981 4-way Angle Blade. NOTE: 2nd Aux INCLUDES 1st Aux hose options.			\$207.00 No Charge \$1,633.00 No Charge
747994 747453 SD_X5405 2N 747999 747053 SD_X5406 1S 747233	W/O Travel Alarm Travel Alarm ND AUX. CIRCUIT W/O 2nd Aux 2-Way Proportional 2nd Aux 2-Way Proportional CX37C - if ordering Angle Blade - 2nd 2-way Aux is used for the angle circuit. Cannot order 747053 with 747981 4-way Angle Blade. NOTE: 2nd Aux INCLUDES 1st Aux hose options. ST AUX HYD TWO WAYS 1ST AUX PLUGS PEDAL			\$207.00 No Charge \$1,633.00



(Ex Works)

SD :	X5430 TH	UMB CYL BRACKET	
	747059	W/O Thumb Bracket	No Charge
	747058	Thumb Bracket	\$443.00
SD_X	X6100 AR	M	
	747320	Short Arm - 747320	No Charge
		Please refer to the Standard pages for arm lengths	
SD_X	X6206 LIN	IKAGE	
	747062	Linkage With Hook	No Charge
	747063	Linkage Without Hook	(\$61.00)
SD_	X6207 HY	DR Q/C PROV.	
	747065	W/O Q/C Provision	No Charge
	747064	Hydraulic Q/C Provision	\$500.00
		Includes switch & hydraulic lines to end of arm	
SD_	X6210 BE	ACON	
	XX6210X	W/O Beacon	No Charge
	747070	Beacon	\$280.00



(Ex Works)

Factory Supplied Attachments

	Order Code	Description	Weight	Factory Data	List Price
1-Pc	osition Pin-On				
	48190704	12" Bucket 1-POS PIN-ON			\$773.00
_		ONLY for usage w/o a coupler.			
	48190705	18" Bucket 1-POS PIN-ON			\$856.00
4		ONLY for usage w/o a coupler.			
	48190706	24" Bucket 1 POS PIN-ON			\$998.00
		ONLY for usage w/o a coupler.			
(LA	AC Buckets & Co	upler			
	48094116	12"HD Bucket (KLAC Coupler)	143 LB		\$524.00
	48094117	18"HD Bucket (KLAC Coupler)	176 LB		\$625.00
	48094118	24"HD Bucket (KLAC Coupler)	209 LB		\$800.00
	48057633	Coupler, KLAC	71 LB		\$1,102.00
	47422632	KLAC Base Plate (To adapt other buckets)	20 LB		\$285.00
Pin-	On Buckets & C	· · · · · · · · · · · · · · · · · · ·	-		
4	48057611	12"HD Bucket (Mech/Hyd Coupler)	121 LB		\$521.00
_	48057612	18"HD Bucket (Mech/Hyd Coupler)	154 LB		\$623.00
4	48057613	24"HD Bucket (Mech/Hyd Coupler)	185 LB		\$797.00
	48057615	Coupler, Mechanical Pin-Grabber (Only compatible with the C-Series bucket) Includes 1 set of dead pins for installation into a single bucket	95 LB		\$1,538.00
	48094307	Coupler,Hydraulic Pin-Grabber (Compatible with both the B/C-Series buckets, when used with a B-Series bucket, it requires the removal of the spacer plates) Includes 1 set of dead pins for installation into a single bucket	99 LB		\$3,386.00
	47457879	Dead Pin Kit Required when ordering more than 1 bucket with a Pin- Grabber Coupler	8 LB		\$177.00
「hu	mbs				
	48058019	Thumb Kit, Hyd.,Short Tines (Use with direct fit, KLAC buckets and Mechanical Pin-Grabber coupler)	150 LB		\$2,248.00
	48094114	Thumb Kit, Hyd., Long Tines (Use w/Hyd. Pin-Grabber coupler only)	150 LB		\$2,248.00

	C-Series Mini Excavator BUCKET COMPATIBILITY					
Model	Order Code	Description	B-Series Buckets	C-Series Buckets		
CX17C	48057609	Coupler, Mechanical Pin-Grabber	No	Yes		
	48057615	Coupler, Mechanical Pin-Grabber	No	Yes		
CX26C	48094307	Coupler, Hydraulic Pin-Grabber	Yes (requires removal of spacer plates)	Yes		
CX33C/CX37C	48057623	Coupler, Mechanical Pin-Grabber	Yes	Yes		
CADDC/CAD7C	48058013	Coupler, Hydraulic Pin-Grabber	Yes	Yes		
avezo loveno	48057630	Coupler, Mechanical Pin-Grabber	No	Yes		
CX57C/CX60C	48058014	Coupler, Hydraulic Pin-Grabber	No	Yes		
	48082917	Coupler, B/C Series Universal Mechanical	Yes	Yes		

ENGINE:

Auto idle feature with on/off switch



CX33C CANOPY US PRICE LIST

(Ex Works) Standard Equipment

```
Yanmar 3TNV88F-ESHYB
                                                      Pre-wired telematics ready
    3 Cyl. water-cooled,
                                                    BLADE:
    direct injection diesel
                                                      Hydraulically controlled dozer blade
    100.2 CID (1.642 L)
                                                    UNDERCARRIAGE:
 Tier 4 Final
                                                      Rubber tracks
 Glow plugs
                                                      Track pad width: 12" (300 mm)
                                                      Track length: 7'0" (2130 mm)
 Horsepower:
   Gross 24.4 HP (18.2 kW)/2200
                                                      Gradeability: 30 degrees
   Net 23.7 HP (17.7 kW)/2200
                                                      Ground clearance: 11" (290 mm)
 Maximum Engine Torque:
                                                   TRACK DRIVE:
      69.4 lb ft (94.1 Nm) @ 1200 rpm
                                                      Two speed auto shift travel
 Dry type air cleaner
                                                     Fully hydrostatic drive system
OPERATOR PROTECTIVE STRUCTURE:
                                                     Track tension adjustment
Sound Levels:
                                                        (grease type)
     ISO 6396:2008 sound pressure
                                                      Sealed and lubricated track
      level LpA=75bB (A)
                                                    HYDRAULICS:
ROPS/FOPS:
                                                      Control pattern selector valve
  Four post canopy design
                                                     Hydraulic oil filter
  Mechanical suspension seat, with
                                                      Total Auxiliary Flow:
     2" seat belt
                                                        16.0 gpm @ 2,973 psi
  Pilot operated joysticks for boom, arm,
                                                        (60.5 L/min @ 205 bar)
    bucket, and swing with adjustable
                                                     Main Pump: 3,270 PSI
     wrist rests
                                                      Auxiliary piping capped at end of
  Foot pedals for travel control and
     swing tower control
                                                      Proportional auxiliary hydraulic flow
 Gauges:
                                                        control
                                                      Selector valve for single or two way
  Engine coolant temperature and fuel
     level
                                                        aux flow
 Indicator Lights:
                                                     Large capacity hydraulic oil cooler
    Engine oil pressure, coolant
                                                     Cylinder rod protection covers
    temperature, battery charge,
                                                        -Dozer & Boom
    low fuel warning, engine preheat,
                                                   UPPER:
                                                      Standard Arm: 4'3" (1.3 m)
    air cleaner warning, hyd. quick
                                                      Boom: 7'10" (2.38 m)
    coupler lock, and high travel speed
                                                     Boom Swing: 75° left / 50° right
ELECTRICAL:
  12 Volt electrical starting system
                                                      Zero Tail Swing
     includes heavy-duty battery and
                                                      Swing brake: disc type, spring applied
     starting motor
                                                        and hydraulically released
                                                      Bucket linkage with lifting hook
  50 Amp alternator
                                                   MISCELLANEOUS:
 Battery master switch
 Key start
                                                      Operating weight:
 Anti-theft-engine starting passwords
                                                        Canopy, short arm - 7,110 lbs.
 Dual 12V power plug recepticals
                                                          (3225 kg)
 Front working Light
```



(Ex Works) Standard Equipment

All weights are with rubber tracks, no quick coupler, bucket, fluids, full of fuel, and 165lb operator

Additional counterweight - 286 lbs Warranty - Base warranty Coverage: 2-Year/3,000-Hour Full Machine Limited Warranty



(Ex Works)

Models

COMMERCIAL MODEL	Weight	Factory Data	List Price
CX33C CANOPY	7,396 LBS.		\$49,762.00
Includes the following Equipment			
Additional Counterweight. (747996)	\$206.00		

Description	Weight	Factory Data	List Price
			\$693.00
Rubber Tracks			
Travel Alarm			
Additional Counterweight.			
W/O 2nd Aux 2-Way Proportional			
2Way Aux Joystick Proportional			
Working Lights			
W/O Thumb Bracket			
Short Arm - 747320			
Linkage With Hook			
W/O Q/C Provision			
Beacon			
	Rubber Tracks Travel Alarm Additional Counterweight. W/O 2nd Aux 2-Way Proportional 2Way Aux Joystick Proportional Working Lights W/O Thumb Bracket Short Arm - 747320 Linkage With Hook W/O Q/C Provision	Rubber Tracks Travel Alarm Additional Counterweight. W/O 2nd Aux 2-Way Proportional 2Way Aux Joystick Proportional Working Lights W/O Thumb Bracket Short Arm - 747320 Linkage With Hook W/O Q/C Provision	Rubber Tracks Travel Alarm Additional Counterweight. W/O 2nd Aux 2-Way Proportional 2Way Aux Joystick Proportional Working Lights W/O Thumb Bracket Short Arm - 747320 Linkage With Hook W/O Q/C Provision

Pre-Configured Package is full model packages for Standard Arm configurations. Once a package is selected, you can then select the required Buckets/Attachments to go along with your unit. Keep in mind, it is not possible to modify (add/remove) any other vehicle options when you select a Pre-Configured package. If a Pre-Configured unit is ordered, it will be matched to one that is already built and ready to ship, which will reduce the lead-time by several months. Independent Option ordering is still available if the package is not desired, however you may experience a longer lead-time.

747233 1ST AUX PLUGS PEDAL



CX33C CANOPY US PRICE LIST

(Ex Works)

Factory Supplied Options

	Description	Weight	Factory Data	List Price
PERATOR'S MA	ANUAL			
SD 47181 O	PERATOR'S MANUAL			
747480	Operators Manual - English			No Charg
747961	Operators Manual - French			No Charg
747464	Operators Manual- Spanish			No Charg
ERSION				
SD_10181 CF	RAWLER TYPE			
9552700	Rubber Tracks			No Char
	One-piece molded rubber belt track w/ a steel cable core.			
	The entire track must be replaced at time of service. Select			
	this track for general use on soils & hard surfaces.			
9553700	Steel Tracks			\$1,322.0
	Steel Track chain with steel grousers/shoes. Select this track for			
	the most aggressive traction in soils & if there is no concern for			
	disrupting the appearance of ground conditions such as grass,			
	asphalt or concrete. This track is intended for use on soils, but			
	can be used on hard surfaces as well.			
	UDAFAIT MEV			
DDITIONAL EQ	UIPMENT MEX			
DDITIONAL EQ	UIPMENT MEX			
SD_30180 TF				
				No Charg
SD_30180 TF	RAVEL ALARM			No Charç \$207.0
SD_30180 TF 747994 747453	RAVEL ALARM W/O Travel Alarm			
SD_30180 TF 747994 747453	RAVEL ALARM W/O Travel Alarm Travel Alarm			
SD_30180 TF 747994 747453 SD_X5405 2h	RAVEL ALARM W/O Travel Alarm Travel Alarm D AUX. CIRCUIT			\$207.0
SD_30180 TF 747994 747453 SD_X5405 2N 747999	RAVEL ALARM W/O Travel Alarm Travel Alarm ND AUX. CIRCUIT W/O 2nd Aux 2-Way Proportional			\$207.0 No Char
SD_30180 TF 747994 747453 SD_X5405 2N 747999	RAVEL ALARM W/O Travel Alarm Travel Alarm ND AUX. CIRCUIT W/O 2nd Aux 2-Way Proportional 2nd Aux 2-Way Proportional			\$207. No Char
SD_30180 TF 747994 747453 SD_X5405 2N 747999	RAVEL ALARM W/O Travel Alarm Travel Alarm ND AUX. CIRCUIT W/O 2nd Aux 2-Way Proportional 2nd Aux 2-Way Proportional CX37C - if ordering Angle Blade - 2nd 2-way Aux is used			\$207.0 No Charg

No Charge



	(Ex Works)	
74723	1ST AUX PLUGS JOYST	No Charge
74705	2Way Aux Joystick Proportional	\$198.00
	1st Aux Hydraulic hoses and shut off block from boom	
	to end of arm.	
SD_X5430	THUMB CYL BRACKET	1
74705		No Charge
74705	58 Thumb Bracket	\$443.00
SD_X6100	ARM	
74732	20 Short Arm - 747320	No Charge
	Please refer to the Standard pages for arm lengths	
SD_X6206	LINKAGE	,
74706	S2 Linkage With Hook	No Charge
74706	3 Linkage Without Hook	(\$61.00)
SD_X6207	HYDR Q/C PROV.	
74706	85 W/O Q/C Provision	No Charge
74706	Hydraulic Q/C Provision	\$500.00
	Includes switch & hydraulic lines to end of arm	
SD_X6210	BEACON	
	10X W/O Beacon	No Charge
74707	70 Beacon	\$280.00



(Ex Works)

Factory Supplied Attachments

Order Code	Description	Weight	Factory Data	List Price
KLAC Buckets & Co	oupler			
47422654	12"HD Bucket (KLAC Coupler)	189 LB		\$1,008.00
47422655	18"HD Bucket (KLAC Coupler)	223 LB		\$1,091.00
47422656	24"HD Bucket (KLAC Coupler) For CX33C models this size bucket is intended for useage w/o a coupler or thumb to achieve the optimal performance. Always reference model lifting capacities when configuring units with attachments.	267 LB		\$1,233.00
48057634	Coupler, KLAC	43 LB		\$1,239.00
Pin-On Buckets & C	•	<u>. T</u>		
48057617	12"HD Bucket (Pin-On & Mech/Hyd Coupler)	161 LB		\$774.00
48057619	18"HD Bucket (Pin-On & Mech/Hyd Coupler)	205 LB		\$857.00
48057620	24"HD Bucket (Pin-On & Mech/Hyd Coupler) For CX33C models this size bucket is intended for useage w/o a coupler or thumb to achieve the optimal performance. Always reference model lifting capacities when configuring units with attachments.	247 LB		\$998.00
48057623	Coupler, Mechanical Pin-Grabber (Compatible with both the B/C-Series buckets) Includes 1 set of dead pins for installation into a single bucket	43 LB		\$1,545.00
48058013	Coupler, Hydraulic Pin-Grabber (Compatible with both the B/C-Series buckets)	132 LB		\$3,386.00
48057624	Dead Pin Kit (for additional buckets) Required when ordering more than 1 bucket with a Pin- Grabber Coupler	11 LB		\$197.00
48057638	Ripper Tooth Pin-On	220 LB		\$929.00
Thumbs		<u>.</u>		
48059646	Thumb Kit, Hyd.,Short Tines (Use with direct fit and KLAC buckets)	150 LB		\$2,350.00
48058020	Thumb Kit, Hyd.,Long Tines (Use with Mech. and Hyd. Pin-Grabber couplers)	200 LB		\$2,350.00

	C-Series Mini Excavator BUCKET COMPATIBILITY					
Model	Order Code	Description	B-Series Buckets	C-Series Buckets		
CX17C	48057609	Coupler, Mechanical Pin-Grabber	No	Yes		
	48057615	Coupler, Mechanical Pin-Grabber	No	Yes		
CX26C	48094307	Coupler, Hydraulic Pin-Grabber	Yes (requires removal of spacer plates)	Yes		
CX33C/CX37C	48057623	Coupler, Mechanical Pin-Grabber	Yes	Yes		
CASSC/CAS/C	48058013	Coupler, Hydraulic Pin-Grabber	Yes	Yes		
CX57C/CX60C	48057630	Coupler, Mechanical Pin-Grabber	No	Yes		
	48058014	Coupler, Hydraulic Pin-Grabber	No	Yes		
	48082917	Coupler, B/C Series Universal Mechanical	Yes	Yes		

ENGINE:

Auto idle feature with on/off switch



CX37C CANOPY. US PRICE LIST

(Ex Works) Standard Equipment

```
Yanmar 3TNV88F-ESHYB
                                                      Pre-wired telematics ready
    3 Cvl. water-cooled
                                                    BLADE:
    direct injection diesel
                                                      Hydraulically controlled dozer blade
    100.2 CID (1.642L)
                                                    UNDERCARRIAGE:
  Tier 4 Final
                                                      Rubber tracks
  Glow plugs
                                                      Track pad width: 12" (300 mm)
                                                      Track length: 7'0" (2130 mm)
 Horsepower:
    Gross 24.4 HP (18.2 kW)/2200
                                                      Gradeability: 30 degrees
    Net 23.7 HP (17.7 kW)/2200
                                                      Ground clearance: 11" (290 mm)
  Maximum Engine Torque:
                                                    TRACK DRIVE:
    69.4 lb ft (94.1 Nm) @ 1200 rpm
                                                      Two speed travel
  Dry type air cleaner
                                                      Fully hydrostatic drive system
OPERATOR PROTECTIVE STRUCTURE:
                                                      Track tension adjustment
Sound Levels:
                                                        (grease type)
      ISO 6396:2008 sound pressure
                                                      Sealed and lubricated track
      level LpA=75bB (A)
                                                    HYDRAULICS:
 ROPS/FOPS:
                                                      Control pattern selector valve
   Four post canopy design
                                                      Hydraulic oil filter
   Mechanical suspension seat, with
                                                      Total Auxiliary Flow:
     2 " seat belt
                                                        16.0 gpm @ 2,973 psi
   Pilot operated joysticks for boom, arm,
                                                        (60.5 L/min @ 205 bar)
     bucket, and swing with adjustable
                                                      Main Pump: 3,270 PSI
     wrist rests
                                                      Auxiliary piping capped at end of
   Foot pedals for travel control and
     swing tower control
                                                      Proportional auxillary hydraulic flow
 Gauges:
                                                        control
   Engine Coolant temp and fuel level
                                                      Selector valve for single or
 Indicator Lights:
                                                        two-way aux flow
    Engine oil pressure, coolant
                                                      Large capacity hydraulic oil cooler
    temperature, battery
                                                      Cylinder rod protection covers
    charge, low fuel warning, engine
                                                        -Dozer & Boom
    preheat, air cleaner warning,
                                                    UPPER:
                                                      Standard Arm: 4'3" (1.3 m)
   hyd. quick coupler
                                                      Optional Long Arm: 5'3" (1.6 m)
    lock, and high travel speed
                                                      Boom: 8'2" (2.5 m)
ELECTRICAL:
  12 Volt electrical starting system
                                                      Boom Swing: 75° left / 50° right
     includes heavy-duty battery and
                                                      Zero Tail Swing
     starting motor
                                                      Swing brake: disc type, spring applied
  55 Amp alternator
                                                        and hydraulically released
                                                      Bucket linkage with lifting hook
  Battery master switch
                                                    MISCELLANEOUS:
  Key start
  Anti-theft-engine starting passwords
                                                        Canopy, short arm - 7,990 lbs.
 Dual 12V power plug recepticals
                                                          (3,625 \text{ Kg})
  Front working light
```



(Ex Works) Standard Equipment

Canopy, long arm additional
 counterweight - 8,350 lbs.
 (3790 Kg.)
All weights are with rubber tracks, no
 quick coupler, bucket, fluids, full of

fuel, thumb bracket and 165lb
 operator
Additional counterweight - 330 lbs
Warranty - Base warranty Coverage:
 2-Year/3,000-Hour Full Machine



(Ex Works) Models

COMMERCIAL MODEL	Weight	Factory Data	List Price
CX37C CANOPY.	7,990 LBS.		\$50,457.00

Packet	Description	Weight	Factory Data	List Price
CX37C Long Arm Pack				\$1467.00
SD_10181-CRAWLER TYPE	Rubber Tracks			
SD_30180-TRAVEL ALARM	Travel Alarm			
SD_40003-COUNTERWEIGHT	Additional Counterweight.			
SD_X5405-2ND AUX. CIRCUIT	W/O 2nd Aux 2-Way Proportional			
SD_X5406-1ST AUX HYD TWO WAYS	2Way Aux Joystick Proportional			
SD_X5414-AUX WORKLIGHTS CAB	Working Lights			
SD_X5430-THUMB CYL BRACKET	Thumb Bracket			
SD_X6100-ARM	Long Arm - 747329			
SD_X6206-LINKAGE	Linkage With Hook			
SD_X6207-HYDR Q/C PROV.	W/O Q/C Provision			
SD_X6210-BEACON	Beacon			
		Г	1 1	
CX37C Short Arm Pack		_		\$931.00
SD_10181-CRAWLER TYPE	Rubber Tracks			
SD_30180-TRAVEL ALARM	Travel Alarm			
SD_40003-COUNTERWEIGHT	Standard Counterweight.			
SD_X5405-2ND AUX. CIRCUIT	W/O 2nd Aux 2-Way Proportional			
SD_X5406-1ST AUX HYD TWO WAYS	2Way Aux Joystick Proportional			
SD_X5414-AUX WORKLIGHTS CAB	Working Lights			
SD_X5430-THUMB CYL BRACKET	Thumb Bracket			
SD_X6100-ARM	Short Arm - 747320			
SD_X6206-LINKAGE	Linkage With Hook			
SD_X6207-HYDR Q/C PROV.	W/O Q/C Provision			
SD_X6210-BEACON	Beacon			
CX37C.Rops Long Angl				\$4870.00
SD_10181-CRAWLER TYPE	Rubber Tracks			
SD_30180-TRAVEL ALARM	Travel Alarm			
SD_40003-COUNTERWEIGHT	Additional Counterweight.			
SD_X5405-2ND AUX. CIRCUIT	W/O 2nd Aux 2-Way Proportional			
SD_X5406-1ST AUX HYD TWO WAYS	2Way Aux Joystick Proportional			
SD_X5414-AUX WORKLIGHTS CAB	Working Lights			
SD_X5430-THUMB CYL BRACKET	Thumb Bracket			
SD_X6100-ARM	Long Arm - 747329			
SD_X6105-DOZER BLADE OPTION	4-Way Angle Dozer Blade			
SD_X6206-LINKAGE	Linkage With Hook			
SD_X6207-HYDR Q/C PROV.	W/O Q/C Provision			



(Ex Works)

Packet	Description	Weight	Factory Data	List Price
SD_X6210-BEACON	Beacon			

Pre-Configured Packages are full model packages for Short Arm or Long Arm configurations. Once a package is selected, you can then select the required Buckets/Attachments to go along with your unit. Keep in mind, it is not possible to modify (add/remove) any other vehicle options when you select a Pre-Configured package. If a Pre-Configured unit is ordered, it will be matched to one that is already built and ready to ship, which will reduce the lead-time by several months. Independent Option ordering is still available if the package is not desired, however you may experience a longer lead-time.

747999 W/O 2nd Aux 2-Way Proportional



CX37C CANOPY. US PRICE LIST

(Ex Works)

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
PERATOR'S MA	NUAL			
SD 47181 OI	PERATOR'S MANUAL			
747480	Operators Manual - English			No Char
747961	Operators Manual - Erigilish			No Char
747464	Operators Manual- Spanish			No Char
	operatore mariaa. Operator	· I	!	110 01141
RSION				
SD_10181 CF	RAWLER TYPE			
9552700	Rubber Tracks			No Char
	One-piece molded rubber belt track w/ a steel cable core.			
	The entire track must be replaced at time of service. Select			
	this track for general use on soils & hard surfaces.			
9553700	Steel Tracks			\$1,536.
	Steel Track chain with steel grousers/shoes. Select this track for			
	the most aggressive traction in soils & if there is no concern for			
	disrupting the appearance of ground conditions such as grass,			
	asphalt or concrete. This track is intended for use on soils, but			
	can be used on hard surfaces as well.			
•				
DITIONAL EQ	JIPMENT MEX			
SD_30180 TF	AVEL ALARM			
747994	W/O Travel Alarm			No Char
747453	Travel Alarm			\$207.
SD_40003 C	DUNTERWEIGHT			
747995	Standard Counterweight.			No Char
747996	Additional Counterweight.			\$210.
747990	Additional bolt on weight adds 286 lb (130 kg) - CX26C			
747996				
747990	Additional bolt on weight adds 330 lb (150 kg) - CX37C CX37C - Add. Cwt comes w/ Angle Blade			

No Charge

SD X6210 BEACON

747070

XX6210X W/O Beacon

Beacon



CX37C CANOPY. **US PRICE LIST** (Ex Works) 747053 2nd Aux 2-Way Proportional \$1,892.00 CX37C - if ordering Angle Blade - 2nd 2-way Aux is used for the angle circuit. Cannot order 747053 with 747981 4-way Angle Blade. NOTE: 2nd Aux INCLUDES 1st Aux hose options. SD_X5406 1ST AUX HYD TWO WAYS 747233 1ST AUX PLUGS PEDAL No Charge 747234 1ST AUX PLUGS JOYST No Charge 747055 \$198.00 2Way Aux Joystick Proportional 1st Aux Hydraulic hoses and shut off block from boom to end of arm. SD_X5430 THUMB CYL BRACKET 747059 W/O Thumb Bracket No Charge 747058 Thumb Bracket \$443.00 SD_X6100 ARM Short Arm - 747320 747320 No Charge Please refer to the Standard pages for arm lengths 747329 Long Arm - 747329 \$327.00 Long arm increases dig depth, resulting in a reduction in arm digging forces & lift capacity. Please refer to the Standard Pages for arm lengths. SD_X6105 DOZER BLADE OPTION 747232 STD DOZER BLADE 747232 No Charge 747981 4-Way Angle Dozer Blade \$3,407.00 The weight of the dozer blade option adds 220 lbs. (100 kg) & includes the additional counterweight which adds 330 lbs. (150 kg) for a total added weight of 550 lbs. (250 kg) Option REQUIRES the additional counterweight 747996 Includes bolt-on reversible cutting edge SD_X6206 LINKAGE 747062 Linkage With Hook No Charge 747063 Linkage Without Hook (\$61.00)SD_X6207 HYDR Q/C PROV. 747065 W/O Q/C Provision No Charge 747064 Hydraulic Q/C Provision \$500.00 Includes switch & hydraulic lines to end of arm

No Charge

\$280.00



(Ex Works)

Factory Supplied Attachments

Order Code	Description	Weight	Factory Data	List Price
_AC Buckets & Co	pupler			
47422654	12"HD Bucket (KLAC Coupler)	189 LB		\$1,008.00
47422655	18"HD Bucket (KLAC Coupler)	223 LB		\$1,091.00
47422656	24"HD Bucket (KLAC Coupler) For CX33C models this size bucket is intended for useage w/o a coupler or thumb to achieve the optimal performance. Always reference model lifting capacities when configuring units with attachments.	267 LB		\$1,233.00
47422658	36"Ditch Bucket (KLAC Coupler)	315 LB		\$1,139.00
48057634	Coupler, KLAC	43 LB		\$1,239.00
n-On Buckets & C	Coupler			
48057617	12"HD Bucket (Pin-On & Mech/Hyd Coupler)	161 LB		\$774.00
48057619	18"HD Bucket (Pin-On & Mech/Hyd Coupler)	205 LB		\$857.00
48057620	24"HD Bucket (Pin-On & Mech/Hyd Coupler) For CX33C models this size bucket is intended for useage w/o a coupler or thumb to achieve the optimal performance. Always reference model lifting capacities when configuring units with attachments.	247 LB		\$998.00
48057621	36"HD Bucket (Pin-On & Mech/Hyd Coupler)	331 LB		\$1,270.00
48057622	36"Ditch Bucket (Pin-On & M/H Coupler)	313 LB		\$1,054.00
48057623	Coupler, Mechanical Pin-Grabber (Compatible with both the B/C-Series buckets) Includes 1 set of dead pins for installation into a single bucket	43 LB		\$1,545.00
48058013	Coupler, Hydraulic Pin-Grabber (Compatible with both the B/C-Series buckets)	132 LB		\$3,386.00
48057624	Dead Pin Kit (for additional buckets) Required when ordering more than 1 bucket with a Pin- Grabber Coupler	11 LB		\$197.00
48057638	Ripper Tooth Pin-On	220 LB		\$929.00
numbs				
48059646	Thumb Kit, Hyd., Short Tines (Use with direct fit and KLAC buckets)	150 LB		\$2,350.00
48058020	Thumb Kit, Hyd.,Long Tines (Use with Mech. and Hyd. Pin-Grabber couplers)	200 LB		\$2,350.00

	C-Series Mini Excavator BUCKET COMPATIBILITY					
Model	Order Code	Description	B-Series Buckets	C-Series Buckets		
CX17C	48057609	Coupler, Mechanical Pin-Grabber	No	Yes		
	48057615	Coupler, Mechanical Pin-Grabber	No	Yes		
CX26C	48094307	Coupler, Hydraulic Pin-Grabber	Yes (requires removal of spacer plates)	Yes		
CX33C/CX37C	48057623	Coupler, Mechanical Pin-Grabber	Yes	Yes		
CASSC/CAS/C	48058013	Coupler, Hydraulic Pin-Grabber	Yes	Yes		
ove 30 love no	48057630	Coupler, Mechanical Pin-Grabber	No	Yes		
CX57C/CX60C	48058014	Coupler, Hydraulic Pin-Grabber	No	Yes		
	48082917	Coupler, B/C Series Universal Mechanical	Yes	Yes		



(This page intentionally left blank)



(Ex Works) Standard Equipment

ENGINE:	Anti-theft-engine starting passwords
Yanmar 3TNV88F-ESHYB	Dual 12V power plug recepticals
3 Cyl. water-cooled	Front working Light
direct injection diesel	Auto idle feature with on/off switch
100.2 CID (1.642L)	Pre-wired telematics ready
Tier 4 Final	
Glow plugs	BLADE:
Horsepower:	Hydraulically controlled dozer blade
Gross 24.4 HP (18.2 kW)/2200	UNDERCARRIAGE:
Net 23.7 HP (17.7 kW)/2200	Rubber tracks
Maximum Engine Torque:	Track pad width: 12" (300 mm)
69.4 lb ft (94.1 Nm) @ 1200 rpm	Track length: 7'0" (2130 mm)
Dry type air cleaner	Gradeability: 30 degrees
OPERATOR PROTECTIVE STRUCTURE:	Ground Clearance: 11" (290 mm)
Sound Levels:	TRACK DRIVE:
ISO 6396:2008 sound pressure	Two speed travel
level LpA=75bB (A)	Fully hydrostatic drive system
ROPS/FOPS:	Track tension adjustment
Enclosed cab with overhead opening	(grease type)
front window, sliding side window,	Sealed and lubricated track
lockable door, heater, defroster, air	HYDRAULICS:
conditioner and radio/USB player + 2	Control pattern selector valve
speakers	Hydraulic oil filter
Mechanical suspension seat, with	Total Auxiliary Flow:
2" seat belt	16.0 gpm @ 2,973 psi
Pilot operated joysticks for boom, arm,	(60.5 L/min @ 205 bar)
bucket and swing with adjustable	Main Pump: 3,270 PSI
wrist rests	Auxiliary piping capped at end of
Foot pedals for travel control and	boom
swing tower control	Proportional auxillary hydraulic flow
Gauges:	control
Engine coolant temp and fuel level	Selector valve for single or
Indicator Lights:	two-way aux flow
Engine oil pressure, coolant	Large capacity hydraulic oil cooler
temperature, battery charge, low fuel	Cylinder rod protection covers
warning, engine preheat, air cleaner	-Dozer & Boom
warning, hyd. quick coupler lock, and	UPPER:
high travel speed	Standard Arm: 4'3" (1.3 m)
ELECTRICAL:	Optional Long Arm: 5'3" (1.6 m)
12 Volt electrical starting system	Boom: 8'2" (2.5 m)
includes heavy-duty battery and	Boom Swing: 75° left / 50° right
starting motor	Zero Tail Swing
55 Amp alternator	Swing brake: disc type, spring applied
Battery master switch	and hydraulically released
Key start	Bucket linkage with lifting hook



(Ex Works) Standard Equipment

MISCELLANEOUS:

Cab, shot arm - 8,300 lbs (3765 kg)
Cab, long arm, additional
 counterweight - 8660 lbs (3930 kg)
All weights are with rubber tracks, no
 quick coupler, bucket, fluids, full of

fuel, thumb bracket and 165lb
operator
Additional counterweight - 330lbs
Warranty - Base warranty Coverage:
 2-Year/3,000-Hour Full Machine



(Ex Works) Models

COMMERCIAL MODEL	Weight	Factory Data	List Price
CX37C CAB.	8,300 LBS.		\$59,555.00

Packet	Description	Weight	Factory Data	List Price
CX37C CAB Long Arm				\$1467.00
SD_05136-RADIO OPTION	Radio and USB	1		
SD_10181-CRAWLER TYPE	Rubber Tracks	1		
SD_30180-TRAVEL ALARM	Travel Alarm	1		
SD_40003-COUNTERWEIGHT	Additional Counterweight.	1		
SD X5183-AIR COND/HEATER	A/C AND HEATER	7		
SD_X5405-2ND AUX. CIRCUIT	W/O 2nd Aux 2-Way Proportional	1		
SD_X5406-1ST AUX HYD TWO WAYS	2Way Aux Joystick Proportional			
SD_X5414-AUX WORKLIGHTS CAB	Working Lights	1		
SD_X5430-THUMB CYL BRACKET	Thumb Bracket	7		
SD_X6100-ARM	Long Arm - 747329	1		
SD_X6206-LINKAGE	Linkage With Hook	1		
SD_X6207-HYDR Q/C PROV.	W/O Q/C Provision	7		
SD_X6210-BEACON	Beacon	1		
CX37C CAB Short Arm				\$931.00
SD_05136-RADIO OPTION	Radio and USB	7		
SD_10181-CRAWLER TYPE	Rubber Tracks	7		
SD 30180-TRAVEL ALARM	Travel Alarm	7		
SD_40003-COUNTERWEIGHT	Standard Counterweight.	7		
SD_X5183-AIR COND/HEATER	A/C AND HEATER	1		
SD_X5405-2ND AUX. CIRCUIT	W/O 2nd Aux 2-Way Proportional	1		
SD_X5406-1ST AUX HYD TWO WAYS	2Way Aux Joystick Proportional			
SD_X5414-AUX WORKLIGHTS CAB	Working Lights	1		
SD_X5430-THUMB CYL BRACKET	Thumb Bracket	1		
SD_X6100-ARM	Short Arm - 747320	1		
SD_X6206-LINKAGE	Linkage With Hook			
SD_X6207-HYDR Q/C PROV.	W/O Q/C Provision			
SD_X6210-BEACON	Beacon			
CX37C.Cab Long Angl				\$4870.00
SD_05136-RADIO OPTION	Radio and USB			
SD_10181-CRAWLER TYPE	Rubber Tracks	_		
SD_30180-TRAVEL ALARM	Travel Alarm	_		
SD_40003-COUNTERWEIGHT	Additional Counterweight.	╛		
SD_X5183-AIR COND/HEATER	A/C AND HEATER			
SD_X5405-2ND AUX. CIRCUIT	W/O 2nd Aux 2-Way Proportional			
SD_X5406-1ST AUX HYD TWO WAYS	2Way Aux Joystick Proportional			

Bid Term: 2/20/19 - 2/19/21



(Ex Works)

Packet		Description	Weight	Factory Data	List Price
SD_X5414-AUX WORKLIGHTS CAB		Working Lights			
SD_X5430-THUMB CYL BRACKET		Thumb Bracket			
SD_X6100-ARM		Long Arm - 747329			
SD_X6105-DOZER BLADE OPTION		4-Way Angle Dozer Blade			
SD_X6206-LINKAGE		Linkage With Hook			
SD_X6207-HYDR Q/C PROV.		W/O Q/C Provision			
SD_X6210-BEACON		Beacon			

Pre-Configured Packages are full model packages for Short Arm or Long Arm configurations. Once a package is selected, you can then select the required Buckets/Attachments to go along with your unit. Keep in mind, it is not possible to modify (add/remove) any other vehicle options when you select a Pre-Configured package. If a Pre-Configured unit is ordered, it will be matched to one that is already built and ready to ship, which will reduce the lead-time by several months. Independent Option ordering is still available if the package is not desired, however you may experience a longer lead-time.

747999 W/O 2nd Aux 2-Way Proportional



CX37C CAB. US PRICE LIST

(Ex Works)

Factory Supplied Options

	Description	Weight	Factory Data	List Price
PERATOR'S MA	NUAL			
05 47404 05	EDATORIO MANUAL			
SD_47181 OF 747480	ERATOR'S MANUAL Operators Manual - English			No Charg
747460	Operators Manual - English Operators Manual - French			No Char
747961	Operators Manual- Spanish			No Char
1 141404	Орегасого манцаг- оранкоп		1	NO Charg
ERSION				
SD_10181 CR	AWLER TYPE			
9552700	Rubber Tracks			No Char
	One-piece molded rubber belt track w/ a steel cable core.			
	The entire track must be replaced at time of service. Select			
	this track for general use on soils & hard surfaces.			
9553700	Steel Tracks			\$1,536.
	Steel Track chain with steel grousers/shoes. Select this track for			
	the most aggressive traction in soils & if there is no concern for			
	disrupting the appearance of ground conditions such as grass,			
	asphalt or concrete. This track is intended for use on soils, but			
	can be used on hard surfaces as well.			
DDITIONAL EQU	JIPMENT MEX			
SD_30180 TR	AVEL ALARM			
747994	W/O Travel Alarm			No Char
	Travel Alarm			\$207.
747453				
747453				
SD_40003 CC	UNTERWEIGHT	1		
SD_40003 CC	Standard Counterweight.			No Char
SD_40003 CC	Standard Counterweight. Additional Counterweight.			No Char \$210.
SD_40003 CC	Standard Counterweight. Additional Counterweight. Additional bolt on weight adds 286 lb (130 kg) - CX26C			
SD_40003 CC	Standard Counterweight. Additional Counterweight.			

No Charge

SD X6210 BEACON

747070

XX6210X W/O Beacon

Beacon



CX37C CAB. **US PRICE LIST** (Ex Works) 747053 2nd Aux 2-Way Proportional \$1,892.00 CX37C - if ordering Angle Blade - 2nd 2-way Aux is used for the angle circuit. Cannot order 747053 with 747981 4-way Angle Blade. NOTE: 2nd Aux INCLUDES 1st Aux hose options. SD_X5406 1ST AUX HYD TWO WAYS 747233 1ST AUX PLUGS PEDAL No Charge 747234 1ST AUX PLUGS JOYST No Charge 747055 \$198.00 2Way Aux Joystick Proportional 1st Aux Hydraulic hoses and shut off block from boom to end of arm. SD_X5430 THUMB CYL BRACKET 747059 W/O Thumb Bracket No Charge 747058 Thumb Bracket \$443.00 SD_X6100 ARM Short Arm - 747320 747320 No Charge Please refer to the Standard pages for arm lengths 747329 Long Arm - 747329 \$327.00 Long arm increases dig depth, resulting in a reduction in arm digging forces & lift capacity. Please refer to the Standard Pages for arm lengths. SD_X6105 DOZER BLADE OPTION 747232 STD DOZER BLADE 747232 No Charge 747981 4-Way Angle Dozer Blade \$3,407.00 The weight of the dozer blade option adds 220 lbs. (100 kg) & includes the additional counterweight which adds 330 lbs. (150 kg) for a total added weight of 550 lbs. (250 kg) Option REQUIRES the additional counterweight 747996 Includes bolt-on reversible cutting edge SD_X6206 LINKAGE 747062 Linkage With Hook No Charge 747063 Linkage Without Hook (\$61.00)SD_X6207 HYDR Q/C PROV. 747065 W/O Q/C Provision No Charge 747064 Hydraulic Q/C Provision \$500.00 Includes switch & hydraulic lines to end of arm

No Charge

\$280.00



(Ex Works)

Factory Supplied Attachments

Order Code	Description	Weight	Factory Data	List Price
KLAC Buckets & Co	pupler			
47422654	12"HD Bucket (KLAC Coupler)	189 LB		\$1,008.00
47422655	18"HD Bucket (KLAC Coupler)	223 LB		\$1,091.00
47422656	24"HD Bucket (KLAC Coupler) For CX33C models this size bucket is intended for useage w/o a coupler or thumb to achieve the optimal performance. Always reference model lifting capacities when configuring units with attachments.	267 LB		\$1,233.00
47422658	36"Ditch Bucket (KLAC Coupler)	315 LB		\$1,139.00
48057634	Coupler, KLAC	43 LB		\$1,239.00
Pin-On Buckets & C	Coupler			
48057617	12"HD Bucket (Pin-On & Mech/Hyd Coupler)	161 LB		\$774.00
48057619	18"HD Bucket (Pin-On & Mech/Hyd Coupler)	205 LB		\$857.00
48057620	24"HD Bucket (Pin-On & Mech/Hyd Coupler) For CX33C models this size bucket is intended for useage w/o a coupler or thumb to achieve the optimal performance. Always reference model lifting capacities when configuring units with attachments.	247 LB		\$998.00
48057621	36"HD Bucket (Pin-On & Mech/Hyd Coupler)	331 LB		\$1,270.00
48057622	36"Ditch Bucket (Pin-On & M/H Coupler)	313 LB		\$1,054.00
48057623	Coupler, Mechanical Pin-Grabber (Compatible with both the B/C-Series buckets) Includes 1 set of dead pins for installation into a single bucket	43 LB		\$1,545.00
48058013	Coupler,Hydraulic Pin-Grabber (Compatible with both the B/C-Series buckets)	132 LB		\$3,386.00
48057624	Dead Pin Kit (for additional buckets) Required when ordering more than 1 bucket with a Pin- Grabber Coupler	11 LB		\$197.00
48057638	Ripper Tooth Pin-On	220 LB		\$929.00
Γhumbs				
48059646	Thumb Kit, Hyd.,Short Tines (Use with direct fit and KLAC buckets)	150 LB		\$2,350.00
48058020	Thumb Kit, Hyd.,Long Tines (Use with Mech. and Hyd. Pin-Grabber couplers)	200 LB		\$2,350.00

	C-Series Mini Excavator BUCKET COMPATIBILITY					
Model	Order Code	Description	B-Series Buckets	C-Series Buckets		
CX17C	48057609	Coupler, Mechanical Pin-Grabber	No	Yes		
	48057615	Coupler, Mechanical Pin-Grabber	No	Yes		
CX26C	48094307	Coupler, Hydraulic Pin-Grabber	Yes (requires removal of spacer plates)	Yes		
CX33C/CX37C	48057623	Coupler, Mechanical Pin-Grabber	Yes	Yes		
Chooc Chorc	48058013	Coupler, Hydraulic Pin-Grabber	Yes	Yes		
ove zo loveno	48057630	Coupler, Mechanical Pin-Grabber	No	Yes		
CX57C/CX60C	48058014	Coupler, Hydraulic Pin-Grabber	No	Yes		
	48082917	Coupler, B/C Series Universal Mechanical	Yes	Yes		



(This page intentionally left blank)

Bid Term: 2/20/19 - 2/19/21



Standard Equipment

ENGINE:

Yanmar 4TNV98C

4 Cyl. water-cooled,

electronic common rail diesel

203 CID (3.319L)

Tier 4 Final

Glow plugs

Horsepower:

Gross 66.9 HP (49.9 kW)/2400

Net 65.1 HP (48.5 kW)/2400

Maximum Engine Torque:

173.7 lb ft (235.4 Nm) @ 1550 rpm

Dry type air cleaner

OPERATOR PROTECTIVE STRUCTURE:

Sound Levels:

ISO 6396:2008 sound pressure

level LpA=76bB (A)

ROPS/FOPS:

Enclosed cab with overhead

opening front window, sliding side

window, lockable door, heater,

defroster and air conditioner,

radio/USB player + 2 speakers

bluetooth with remote control and

5.7" color LCD display screen

Mechanical suspension seat, with

2" seat belt, and seat heater

Pilot operated joysticks for boom, arm

bucket, and swing with adjustable

wrist rests

Foot pedals for travel control and

swing tower control

Gauges: Engine coolant temperature,

hydraulic oil temperature,

and fuel level

Indicator Lights: Hydraulic oil temp,

Air cleaner, engine stop, check

engine, water in fuel, battery

charging, emergency warning, low

fuel level, engine coolant

temperature, engine oil

pressure, DPF regeneration inhibit

warning and regeneration

acknowledge, DPF warning, and high

exhaust temparature

ELECTRICAL:

12 Volt electrical starting system

includes heavy-duty battery and

starting motor

60 Amp Alternator

Battery master switch

Key start

Anti-theft-engine starting passwords

Dual 12V power plug recepticals

Front and rear working lights

Auto idle feature with on/off switch

Pre-wired telematics ready

BLADE:

Hydraulically controlled dozer blade

UNDERCARRIAGE:

Rubber tracks

Track pad width: 15" (380 mm)

Track length: 8'4" (2530 mm)

Gradeability: 35 degrees

Ground clearance: 1'3" (380 mm)

TRACK DRIVE:

Two speed travel

Fully hydrostatic drive system $\,$

Track tension adjustment

(grease type)

Sealed and lubricated track

HYDRAULICS:

Control pattern selector valve

Hydraulic oil filter

Total Auxiliary Flow:

25.4 gpm @ 3,191 psi

(96.2 L/min @ 220 bar)

Main Pump: 3,130 PSI

Auxiliary valves and piping

for independent one way aux and

two way aux circuits.

Proportional auxiliary hydraulic flow

control



Standard Equipment

Large capacity hydraulic oil cooler Cylinder rod protection covers -Boom

UPPER:

Standard Arm w/Thumb bracket: $5'3"\ (1.6\ m)$ Optional Long Arm w/Thumb bracket:

6'3" (1.9 m) Boom: 9'10" (2.5 m)

Boom Swing: 80° left / 50° right

Conventional Swing Radius

Swing brake: disc type, spring applied

and hydraulically released
Bucket linkage with lifting hook

MISCELLANEOUS:

Operating weight:

Cab, short arm w/ Heavy counterweight - 12,270 lb (5565 kg)
Cab, long arm with Heavy
 Counterweight - 12,320 lbs
 (5590 kg)

All weights are with rubber tracks, no quick coupler, bucket, fluids, full of fuel, thumb bracket and 1651b operator

Warranty - Base warranty Coverage: 2-Year/3,000-Hour Full Machine Limited Warranty



Models

COMMERCIAL MODEL	Weight	Factory Data	List Price
CX57C CAB	12,270 LB		\$81,822.00
Includes the following Equipment			
Additional Counterweight (747084)	\$676.00		

Packet	Description	Weight	Factory Data	List Price
CX57C CAB Long Arm				\$1216.00
SD_10181-CRAWLER TYPE	Rubber Tracks 400MM			
SD_30180-TRAVEL ALARM	Travel Alarm			
SD_40003-COUNTERWEIGHT	Additional Counterweight			
SD_X5405-2ND AUX. CIRCUIT	W/O 2nd Aux 2-Way Proportional			
SD_X5407-1ST AUX HYD CIRCUIT	2Way Aux Joystick Proportional			
SD_X5414-AUX WORKLIGHTS CAB	Working Lights			
SD_X6100-ARM	Arm Long w/Thumb Bracket			
SD_X6206-LINKAGE	Linkage With Hook			
SD_X6207-HYDR Q/C PROV.	W/O Q/C Provision			
SD_X6210-BEACON	Beacon			
SD_X9908-CAMERA	W/O Rear View Camera			
CX57C.Short Arm Acwt				\$304.00
SD_10181-CRAWLER TYPE	Rubber Tracks 400MM			
SD_30180-TRAVEL ALARM	Travel Alarm			
SD_40003-COUNTERWEIGHT	Additional Counterweight			
SD_X5405-2ND AUX. CIRCUIT	W/O 2nd Aux 2-Way Proportional			
SD_X5407-1ST AUX HYD CIRCUIT	2Way Aux Joystick Proportional			
SD_X5414-AUX WORKLIGHTS CAB	Working Lights			
SD_X6100-ARM	Arm Short w/Thumb Bracket			
SD_X6206-LINKAGE	Linkage With Hook			
SD_X6207-HYDR Q/C PROV.	W/O Q/C Provision			
SD_X6210-BEACON	Beacon			
SD_X9908-CAMERA	W/O Rear View Camera			

Pre-Configured Packages are full model packages for Short Arm or Long Arm configurations. Once a package is selected, you can then select the required Buckets/Attachments to go along with your unit. Keep in mind, it is not possible to modify (add/remove) any other vehicle options when you select a Pre-Configured package. If a Pre-Configured unit is ordered, it will be matched to one that is already built and ready to ship, which will reduce the lead-time by several months. Independent Option ordering is still available if the package is not desired, however you may experience a longer lead-time.



Factory Supplied Options

Order Code Description Weigh	ht Factory D	ata List Price
------------------------------	--------------	----------------

OPERATOR'S MANUAL

SD_47181 OPERATOR'S MANUAL

	747480	Operators Manual - English		No Charge
	747464	Operators Manual- Spanish		No Charge
	747961	Operators Manual - French		No Charge

VERSION

SD_10181 CRAWLER TYPE

9552711	Rubber Tracks 400MM		No Charge
	One-piece molded rubber belt track with a steel cable core.		
	The entire track must be replaced at time of service. Select		
	this track for general use on soils and hard surfaces.		
9552710	Rubber Link Tracks 400MM		\$11,986.00
	Steel track chain with molded rubber grousers/shoes. These		
	are also called hybrid tracks or roadliner tracks. Each Grouser/		
	shoe has a steel core completely molded in rubber and can be		
	individually replaced since they are bolted to a steel chain.		
	This track will offer the stability of a steel track with the		
	surface protection of a rubber track pad.		
9552612	Steel w/Pads 400 MM		\$4,241.00
	Steel track chain with steel grousers/shoes and bolt on rubber		
	track pads. Each rubber track pad can be individually replaced		
	or removed independently from the steel grouser/shoe. Select		
	this option to gain traction on hard surfaces such as asphalt or		
	concrete and to help protect their surface finish with the		
	rubber track pads attached. All of the rubber track pads can be		
	removed to perform as an all steel track as desired.		
9552613	Steel w/Pad Hole 400MM		\$2,200.00
	Steel track chain with steel grousers/shoes that have holes		
	to accept bolt on rubber track pads. Select this track for		
	the most aggressive traction in soils and if there is no		
	concern for disrupting the appearance of ground conditions		
	such as grass, asphalt or concrete. For added traction on		
	hard surfaces such as asphalt or concrete and to help protect		
	their surface finish it is recommended to use bolt on rubber		
	track pads.		

Hydraulic Q/C Provision

W/O Q/C Provision

747064

747065



CX57C COMPACT EXCAVATOR US PRICE LIST

0550040	Charl Treates 450 MM	#2 200 00
9552610	Steel Tracks 450 MM	\$2,320.00
	Steel track chain with steel grousers/shoes. Select this track	
	for the most aggressive traction in soils and if there is no	
	concern for disrupting the appearance of ground conditions	
	such as grass, asphalt or concrete. This track is intended for	
	use on soils, but can be used on hard surfaces as well.	
ADDITIONAL EQU	JIPMENT MEX	
SD_30180 TR		
747453	Travel Alarm	\$304.00
747994	W/O Travel Alarm	No Charge
SD_X5202 TR	ACK GUIDE	
747096	Full Track Guide	\$676.00
	Full track guides for steel tracks and steel tracks with bolt on	
	rubber track pads only	
747097	3-Piece Track Guide	No Charge
	3-piece track guides for steel tracks and steel tracks with bolt	
	on rubber track pads only	
SD X5405 2N	D AUX. CIRCUIT	
747053	2nd Aux 2-Way Proportional	\$2,641.00
747999	W/O 2nd Aux 2-Way Proportional	No Charge
CD VE407 40	T AUX HYD CIRCUIT	
SD_X5407 1S 747122	2Way Aux Joystick Proportional	No Charge
747122	2Way Aux Pedal Proportional	\$646.00
147123	Zway Aux Fedai Fiopotional	\$040.00
	AR AUX WORK LIGHTS	
747115	Rear Aux Work Lights	No Charge
SD_X6100 AR	M	
747078	Arm Short w/Thumb Bracket	No Charge
747079	Arm Long w/Thumb Bracket	\$912.00
	Long arm increases dig depth, resulting in a reduction in	40.12.00
	arm digging forces & lift capacity. Please refer to the	
	Standard Pages for arm lengths.	
		·
SD_X6206 LIN		No Chara
747062	Linkage With Hook	No Charge
747063	Linkage Without Hook	(\$140.00)
SD_X6207 HY	DR Q/C PROV.	
<u> </u>		

\$641.00

No Charge



SD_X6210 BEACON

	747070	Beacon		No Charge
	747087	W/O - Beacon		(\$47.00)

SD_X9908 CAMERA

	747089	W/O Rear View Camera		No Charge
Ī	747090	Rear View Camera		\$593.00



Factory Supplied Attachments

Order Code	Description	Weight	Factory Data	List Price
in-On Buckets & 0	Coupler			
48057625	12"HD Bucket (Pin-On & Mech/Hyd Coupler)	190 LB		\$931.00
48057626	18"HD Bucket (Pin-On & Mech/Hyd Coupler)	240 LB		\$1,001.00
48057627	24"HD Bucket (Pin-On & Mech/Hyd Coupler)	291 LB		\$1,143.00
48057628	36"HD Bucket (Pin-On & Mech/Hyd Coupler)	388 LB		\$1,407.00
48057629	36"Ditch Bucket (Pin-On & M/H Coupler)	313 LB		\$1,056.00
48057637	36"Cemetary Bucket (Pin-On& M/H Coupler)	305 LB		\$1,200.00
48057630	Coupler, Mechanical Pin-Grabber (Only compatible with the C-Series bucket) Includes 1 set of dead pins for installation into a single bucket	74 LB		\$1,545.00
48058014	Coupler, Hydraulic Pin-Grabber (Only compatible with the C-Series bucket)	63 LB		\$3,251.00
48082917	Coupler, B/C-Series Universal Mechanical (Compatible with both the B/C-Series buckets)	85 LB		\$824.00
48057631	PIN Required when ordering more than 1 bucket with a Pin- Grabber Coupler			\$209.00
48057639	Ripper Tooth Pin-On	220 LB		\$929.00
LAC Buckets & C	oupler	•		
47422702	12"HD Bucket (KLAC Coupler)	220 LB		\$1,165.00
47422703	18"HD Bucket (KLAC Coupler)	256 LB		\$1,237.00
47422704	24"HD Bucket (KLAC Coupler)	309 LB		\$1,379.00
47422705	36"HD Bucket (KLAC Coupler)	408 LB		\$1,643.00
47422658	36"Ditch Bucket (KLAC Coupler)	315 LB		\$1,139.00
47872281	36"Cemetary Bucket (KLAC Coupler)	310 LB		\$1,200.00
48057636	Coupler, KLAC	55 LB		\$1,278.00
47422660	KLAC Base Plate (To adapt other buckets)	31 LB		\$348.00
47873455	ATTACHMENT, RIPPER TOOTH,	220 LB		\$929.00
humbs				·
48058021	Thumb Kit, Hyd.,Long Tines (Use with Mech. and Hyd. Pin-Grabber couplers)	250 LB		\$2,453.00
48059650	Thumb Kit, Hyd.,Short Tines (Use with Direct Fit and Klac buckets)	250 LB		\$2,453.00

	C-	Series Mini Excavator BUCKET COMPATIBILI	TY	
Model	Order Code	Description	B-Series Buckets	C-Series Buckets
CX17C	48057609	Coupler, Mechanical Pin-Grabber	No	Yes
	48057615	Coupler, Mechanical Pin-Grabber	No	Yes
CX26C	48094307	Coupler, Hydraulic Pin-Grabber	Yes (requires removal of spacer plates)	Yes
CX33C/CX37C	48057623	Coupler, Mechanical Pin-Grabber	Yes	Yes
CASSC/CAS/C	48058013	Coupler, Hydraulic Pin-Grabber	Yes	Yes
over a love a a	48057630	Coupler, Mechanical Pin-Grabber	No	Yes
CX57C/CX60C	48058014	Coupler, Hydraulic Pin-Grabber	No	Yes
	48082917	Coupler, B/C Series Universal Mechanical	Yes	Yes



(This page intentionally left blank)



Standard Equipment

ENGINE:

Yanmar 4TNV98C

4 Cyl. water-cooled,

electronic common rail diesel

203 CID (3.319L)

Tier 4 Final

Glow plugs

Horsepower:

Gross 67.7 HP (48.3 kW)/2200

Net 63 HP (47 kW)/2200

Maximum Engine Torque:

173.7 lb ft (235.4 Nm) @ 1550 rpm

Dry type air cleaner

OPERATOR PROTECTIVE STRUCTURE:

Sound Levels:

ISO 6396:2008 sound pressure

level LpA=77bB (A)

ROPS/FOPS:

Enclosed cab with overhead

opening front window, sliding side

window, lockable door, heater,

defroster and air conditioner,

radio/USB player + 2 speakers

bluetooth with remote control and

5.7" color LCD display screen

Mechanical suspension seat, with

2" seat belt, and seat heater

Pilot operated joysticks for boom,

arm, bucket and swing with

adjustable wrist rests

Foot pedals for travel control and

swing tower control

Gauges: Engine coolant temperature,

hydraulic oil temperature,

and fuel level

Indicator Lights: Hydraulic oil temp,

air cleaner, engine stop, check

engine, water in fuel, battery

charging, emergency warning, low

fuel level, engine coolant

temperature, engine oil

pressure, DPF regeneration inhibit

warning and regeneration

acknowledge, DPF warning, and high

exhaust temperature

ELECTRICAL:

12 Volt electrical starting system

includes heavy-duty battery and

starting motor

60 Amp alternator

Battery master switch

Key start

Anti-theft-engine starting passwords

Dual 12V power plug recepticals

Front and rear working lights

Auto idle feature with on/off switch

Pre-wired telematics ready

BLADE:

Hydraulically controlled dozer blade

UNDERCARRIAGE:

Rubber tracks

Track pad width: 15" (380 mm)

Track length: 8'4" (2530 mm)

Gradeability: 35 degrees

Ground clearance: 1'3" (380 mm)

TRACK DRIVE:

Two speed travel

Fully hydrostatic drive system

Track tension adjustment

(grease type)

Sealed and lubricated track

HYDRAULICS:

Control pattern selector valve

Hydraulic oil filter

Total Auxiliary Flow:

24.2 gpm @ 3,191 psi

(91.6 L/min @ 220 bar)

Main Pump: 3,130 PSI

Auxiliary valves and piping

for independent one way aux and

two way aux circuits.

Proportional auxiliary hydraulic flow

control



Standard Equipment

Large capacity hydraulic oil cooler
Cylinder rod protection covers
-Boom

UPPER:
Standard Arm w/Thumb bracket:
4"10" (1.48 m)
Optional Long Arm w/Thumb bracket:
6'3" (1.9 m)
Boom: 9'6" (2.9 m)
Boom Swing: 70° left / 50° right
Short Tail Swing Radius
Swing brake: disc type, spring applied and hydraulically released

Bucket linkage with lifting hook

MISCELLANEOUS:
Operating weight:
Cab, short arm - 12,940 lbs (5870 kg)
Cab, long arm with additional
counterweight - 13,430 lbs
(6090 kg)
All weights are with rubber tracks, no
quick coupler, bucket, fluids, full
of fuel, thumb bracket and 1651b
operator
Additional counterweight - 440 lbs
Warranty - Base warranty Coverage:
2-Year/3,000-Hour Full Machine
Limited Warranty



Models

COMMERCIAL MODEL	Weight	Factory Data	List Price
CX60C CAB	12,940 LB		\$85,835.00

Packet	Description	Weight	Factory Data	List Price
CX60C CAB Long Arm				\$2066.00
SD_10181-CRAWLER TYPE	Rubber Tracks 400MM			
SD_30180-TRAVEL ALARM	Travel Alarm			
SD_40003-COUNTERWEIGHT	Additional Counterweight			
SD_X5405-2ND AUX. CIRCUIT	W/O 2nd Aux 2-Way Proportional			
SD_X5407-1ST AUX HYD CIRCUIT	2Way Aux Joystick Proportional			
SD_X5414-AUX WORKLIGHTS CAB	Working Lights			
SD_X6100-ARM	Arm Long w/Thumb Bracket			
SD_X6206-LINKAGE	Linkage With Hook			
SD_X6207-HYDR Q/C PROV.	W/O Q/C Provision			
SD_X6210-BEACON	Beacon			
SD_X9850-HYDRAULIC OIL	STD HYD OIL VG46			
SD_X9908-CAMERA	W/O Rear View Camera			
CX60C CAB Short Arm				\$304.00
SD_10181-CRAWLER TYPE	Rubber Tracks 400MM			
SD_30180-TRAVEL ALARM	Travel Alarm			
SD_40003-COUNTERWEIGHT	Standard Counterweight.			
SD_X5405-2ND AUX. CIRCUIT	W/O 2nd Aux 2-Way Proportional			
SD_X5407-1ST AUX HYD CIRCUIT	2Way Aux Joystick Proportional			
SD_X5414-AUX WORKLIGHTS CAB	Working Lights			
SD_X6100-ARM	Arm Short w/Thumb Bracket			
SD_X6206-LINKAGE	Linkage With Hook			
SD_X6207-HYDR Q/C PROV.	W/O Q/C Provision			
SD_X6210-BEACON	Beacon			
SD_X9850-HYDRAULIC OIL	STD HYD OIL VG46			
SD_X9908-CAMERA	W/O Rear View Camera			

Pre-Configured Packages are full model packages for Short Arm or Long Arm configurations. Once a package is selected, you can then select the required Buckets/Attachments to go along with your unit. Keep in mind, it is not possible to modify (add/remove) any other vehicle options when you select a Pre-Configured package. If a Pre-Configured unit is ordered, it will be matched to one that is already built and ready to ship, which will reduce the lead-time by several months. Independent Option ordering is still available if the package is not desired, however you may experience a longer lead-time.

Bid Term: 2/20/19 - 2/19/21



Factory Supplied Options

Order Code Description	Weight	Factory Data	List Price
------------------------	--------	--------------	------------

OPERATOR'S MANUAL

SD_47181 OPERATOR'S MANUAL

	747480	Operators Manual - English		No Charge
	747464	Operators Manual- Spanish		No Charge
	747961	Operators Manual - French		No Charge

VERSION

SD_10181 CRAWLER TYPE

9552711	Rubber Tracks 400MM	No Charge
	One-piece molded rubber belt track with a steel cable core.	
	The entire track must be replaced at time of service. Select	
	this track for general use on soils and hard surfaces.	
9552710	Rubber Link Tracks 400MM	\$12,502.00
	Steel track chain with molded rubber grousers/shoes. These	
	are also called hybrid tracks or roadliner tracks. Each Grouser/	
	shoe has a steel core completely molded in rubber and can be	
	individually replaced since they are bolted to a steel chain.	
	This track will offer the stability of a steel track with the	
	surface protection of a rubber track pad.	
9552612	Steel w/Pads 400 MM	\$4,424.00
	Steel track chain with steel grousers/shoes and bolt on rubber	
	track pads. Each rubber track pad can be individually replaced	
	or removed independently from the steel grouser/shoe. Select	
	this option to gain traction on hard surfaces such as asphalt or	
	concrete and to help protect their surface finish with the	
	rubber track pads attached. All of the rubber track pads can be	
	removed to perform as an all steel track as desired.	
9552613	Steel w/Pad Hole 400MM	\$2,200.00
	Steel track chain with steel grousers/shoes that have holes	
	to accept bolt on rubber track pads. Select this track for	
	the most aggressive traction in soils and if there is no	
	concern for disrupting the appearance of ground conditions	
	such as grass, asphalt or concrete. For added traction on	
	hard surfaces such as asphalt or concrete and to help protect	
	their surface finish it is recommended to use bolt on rubber	
	track pads.	

747064 Hydraulic Q/C Provision

W/O Q/C Provision

747065



CX60C COMPACT EXCAVATOR US PRICE LIST

SD_30180 TRAVEL ALARM 747453 Travel Alarm 747994 W/O Travel Alarm SD_40003 COUNTERWEIGHT 747084 Additional Counterweight CX60C - additional bolt-on weight that adds 440 lb (200 kg) 747995 Standard Counterweight. SD_X5202 TRACK GUIDE 747097 3-Piece Track Guide 3-piece track guides for steel tracks and steel tracks with bolt on rubber track pads only SD_X5405 2ND AUX. CIRCUIT 747053 2nd Aux 2-Way Proportional 747999 W/O 2nd Aux 2-Way Proportional SD_X5407 1ST AUX HYD CIRCUIT 747122 2Way Aux Joystick Proportional SD_X6100 ARM 747078 Arm Short w/Thumb Bracket Long arm increases dig depth, resulting in a reduction in arm digging forces & lift capacity. Please refer to the Standard Pages for arm lengths. SD_X6206 LINKAGE	\$304. No Char \$850. No Char \$2,641. No Char No Char No Char \$912.
concern for disrupting the appearance of ground conditions such as grass, asphalt or concrete. This track is intended for use on soils, but can be used on hard surfaces as well. DOITIONAL EQUIPMENT MEX SD 30180 TRAVEL ALARM	No Char \$850. No Char \$2,641. No Char No Char
such as grass, asphalt or concrete. This track is intended for use on soils, but can be used on hard surfaces as well. DDITIONAL EQUIPMENT MEX SD_30180	No Char \$850. No Char \$2,641. No Char No Char
use on soils, but can be used on hard surfaces as well. DDITIONAL EQUIPMENT MEX SD_30180 TRAVEL ALARM 747453 Travel Alarm	No Char \$850. No Char \$2,641. No Char No Char
SD_30180_TRAVEL_ALARM 747453	No Char \$850. No Char \$2,641. No Char No Char
SD 30180 TRAVEL ALARM	No Char \$850. No Char \$2,641. No Char No Char
Tavel Alarm T47994 W/O Travel Alarm SD_40003 COUNTERWEIGHT 747084 Additional Counterweight CX60C - additional bolt-on weight that adds 440 lb (200 kg) 747995 Standard Counterweight. SD_X5202 TRACK GUIDE 747097 3-Piece Track Guide 3-piece track guides for steel tracks and steel tracks with bolt on rubber track pads only SD_X5405 2ND AUX. CIRCUIT 747053 2nd Aux 2-Way Proportional 747999 W/O 2nd Aux 2-Way Proportional SD_X5407 1ST AUX HYD CIRCUIT 747122 2Way Aux Joystick Proportional SD_X6100 ARM 747078 Arm Short w/Thumb Bracket Long arm increases dig depth, resulting in a reduction in arm digging forces & lift capacity. Please refer to the Standard Pages for arm lengths.	No Char \$850. No Char \$2,641. No Char No Char
T47453	No Char \$850. No Char \$2,641. No Char No Char
T47453 Travel Alarm T47994 W/O Travel Alarm SD_40003 COUNTERWEIGHT 747084 Additional Counterweight CX60C - additional bolt-on weight that adds 440 lb (200 kg) 747995 Standard Counterweight. SD_X5202 TRACK GUIDE 747097 3-Piece Track Guide 3-piece track guides for steel tracks and steel tracks with bolt on rubber track pads only SD_X5405 2ND AUX. CIRCUIT 747053 2nd Aux 2-Way Proportional 747999 W/O 2nd Aux 2-Way Proportional SD_X5407 1ST AUX HYD CIRCUIT 747122 2Way Aux Joystick Proportional SD_X6100 ARM 747078 Arm Short w/Thumb Bracket Long arm increases dig depth, resulting in a reduction in arm digging forces & lift capacity. Please refer to the Standard Pages for arm lengths.	No Char \$850. No Char \$2,641. No Char No Char
T47994 W/O Travel Alarm	No Char \$850. No Char \$2,641. No Char No Char
SD_40003 COUNTERWEIGHT 747084 Additional Counterweight CX60C - additional bolt-on weight that adds 440 lb (200 kg) 747995 Standard Counterweight. SD_X5202 TRACK GUIDE 747097 3-Piece Track Guide 3-piece track guides for steel tracks and steel tracks with bolt on rubber track pads only SD_X5405 2ND AUX. CIRCUIT 747053 2nd Aux 2-Way Proportional 747999 W/O 2nd Aux 2-Way Proportional SD_X5407 1ST AUX HYD CIRCUIT 747122 2Way Aux Joystick Proportional SD_X6100 ARM 747078 Arm Short w/Thumb Bracket Long arm increases dig depth, resulting in a reduction in arm digging forces & lift capacity. Please refer to the Standard Pages for arm lengths.	\$850. No Char \$2,641. No Char No Char
747084 Additional Counterweight CX60C - additional bolt-on weight that adds 440 lb (200 kg) 747995 Standard Counterweight. SD_X5202 TRACK GUIDE 747097 3-Piece Track Guide 3-piece track guides for steel tracks and steel tracks with bolt on rubber track pads only SD_X5405 2ND AUX. CIRCUIT 747053 2nd Aux 2-Way Proportional 747999 W/O 2nd Aux 2-Way Proportional SD_X5407 1ST AUX HYD CIRCUIT 747122 2Way Aux Joystick Proportional SD_X6100 ARM 747078 Arm Short w/Thumb Bracket Long arm increases dig depth, resulting in a reduction in arm digging forces & lift capacity. Please refer to the Standard Pages for arm lengths.	No Char \$2,641. No Char No Char
747084 Additional Counterweight CX60C - additional bolt-on weight that adds 440 lb (200 kg) 747995 Standard Counterweight. SD_X5202 TRACK GUIDE 747097 3-Piece Track Guide 3-piece track guides for steel tracks and steel tracks with bolt on rubber track pads only SD_X5405 2ND AUX. CIRCUIT 747053 2nd Aux 2-Way Proportional 747999 W/O 2nd Aux 2-Way Proportional SD_X5407 1ST AUX HYD CIRCUIT 747122 2Way Aux Joystick Proportional SD_X6100 ARM 747078 Arm Short w/Thumb Bracket Long arm increases dig depth, resulting in a reduction in arm digging forces & lift capacity. Please refer to the Standard Pages for arm lengths.	No Char \$2,641. No Char No Char
CX60C - additional bolt-on weight that adds 440 lb (200 kg) 747995	No Char \$2,641. No Char No Char
SD_X5202 TRACK GUIDE 747097 3-Piece Track Guide 3-piece track guides for steel tracks and steel tracks with bolt on rubber track pads only SD_X5405 2ND AUX. CIRCUIT 747053 2nd Aux 2-Way Proportional 747999 W/O 2nd Aux 2-Way Proportional SD_X5407 1ST AUX HYD CIRCUIT 747122 2Way Aux Joystick Proportional SD_X6100 ARM 747078 Arm Short w/Thumb Bracket Long arm increases dig depth, resulting in a reduction in arm digging forces & lift capacity. Please refer to the Standard Pages for arm lengths.	\$2,641. No Char
SD_X5202 TRACK GUIDE 747097 3-Piece Track Guide 3-piece track guides for steel tracks and steel tracks with bolt on rubber track pads only SD_X5405 2ND AUX. CIRCUIT 747053 2nd Aux 2-Way Proportional 747999 W/O 2nd Aux 2-Way Proportional SD_X5407 1ST AUX HYD CIRCUIT 747122 2Way Aux Joystick Proportional SD_X6100 ARM 747078 Arm Short w/Thumb Bracket 747079 Arm Long w/Thumb Bracket Long arm increases dig depth, resulting in a reduction in arm digging forces & lift capacity. Please refer to the Standard Pages for arm lengths.	\$2,641. No Char
747097 3-Piece Track Guide 3-piece track guides for steel tracks and steel tracks with bolt on rubber track pads only SD_X5405 2ND AUX. CIRCUIT 747053 2nd Aux 2-Way Proportional 747999 W/O 2nd Aux 2-Way Proportional SD_X5407 1ST AUX HYD CIRCUIT 747122 2Way Aux Joystick Proportional SD_X6100 ARM 747078 Arm Short w/Thumb Bracket Long arm increases dig depth, resulting in a reduction in arm digging forces & lift capacity. Please refer to the Standard Pages for arm lengths.	\$2,641. No Char No Char
747097 3-Piece Track Guide 3-piece track guides for steel tracks and steel tracks with bolt on rubber track pads only SD_X5405 2ND AUX. CIRCUIT 747053 2nd Aux 2-Way Proportional 747999 W/O 2nd Aux 2-Way Proportional SD_X5407 1ST AUX HYD CIRCUIT 747122 2Way Aux Joystick Proportional SD_X6100 ARM 747078 Arm Short w/Thumb Bracket Long arm increases dig depth, resulting in a reduction in arm digging forces & lift capacity. Please refer to the Standard Pages for arm lengths.	\$2,641. No Char No Char
3-piece track guides for steel tracks and steel tracks with bolt on rubber track pads only SD_X5405 2ND AUX. CIRCUIT 747053 2nd Aux 2-Way Proportional 747999 W/O 2nd Aux 2-Way Proportional SD_X5407 1ST AUX HYD CIRCUIT 747122 2Way Aux Joystick Proportional SD_X6100 ARM 747078 Arm Short w/Thumb Bracket Long arm increases dig depth, resulting in a reduction in arm digging forces & lift capacity. Please refer to the Standard Pages for arm lengths. SD_X6206 LINKAGE	\$2,641. No Char No Char
SD_X5405 2ND AUX. CIRCUIT 747053 2nd Aux 2-Way Proportional 747999 W/O 2nd Aux 2-Way Proportional SD_X5407 1ST AUX HYD CIRCUIT 747122 2Way Aux Joystick Proportional SD_X6100 ARM 747078 Arm Short w/Thumb Bracket Long arm increases dig depth, resulting in a reduction in arm digging forces & lift capacity. Please refer to the Standard Pages for arm lengths.	No Char
SD_X5405 2ND AUX. CIRCUIT 747053 2nd Aux 2-Way Proportional 747999 W/O 2nd Aux 2-Way Proportional SD_X5407 1ST AUX HYD CIRCUIT 747122 2Way Aux Joystick Proportional SD_X6100 ARM 747078 Arm Short w/Thumb Bracket 747079 Arm Long w/Thumb Bracket Long arm increases dig depth, resulting in a reduction in arm digging forces & lift capacity. Please refer to the Standard Pages for arm lengths. SD_X6206 LINKAGE	No Char
747053 2nd Aux 2-Way Proportional 747999 W/O 2nd Aux 2-Way Proportional SD_X5407 1ST AUX HYD CIRCUIT 747122 2Way Aux Joystick Proportional SD_X6100 ARM 747078 Arm Short w/Thumb Bracket 1747079 Arm Long w/Thumb Bracket Long arm increases dig depth, resulting in a reduction in arm digging forces & lift capacity. Please refer to the Standard Pages for arm lengths.	No Char
SD_X5407 1ST AUX HYD CIRCUIT 747122 2Way Aux Joystick Proportional SD_X6100 ARM 747078 Arm Short w/Thumb Bracket 747079 Arm Long w/Thumb Bracket Long arm increases dig depth, resulting in a reduction in arm digging forces & lift capacity. Please refer to the Standard Pages for arm lengths.	No Char
SD_X5407 1ST AUX HYD CIRCUIT 747122 2Way Aux Joystick Proportional SD_X6100 ARM 747078 Arm Short w/Thumb Bracket 747079 Arm Long w/Thumb Bracket Long arm increases dig depth, resulting in a reduction in arm digging forces & lift capacity. Please refer to the Standard Pages for arm lengths. SD_X6206 LINKAGE	No Char
T47122 2Way Aux Joystick Proportional SD_X6100 ARM 747078 Arm Short w/Thumb Bracket 747079 Arm Long w/Thumb Bracket Long arm increases dig depth, resulting in a reduction in arm digging forces & lift capacity. Please refer to the Standard Pages for arm lengths.	No Char
T47122 2Way Aux Joystick Proportional SD_X6100 ARM 747078 Arm Short w/Thumb Bracket 747079 Arm Long w/Thumb Bracket Long arm increases dig depth, resulting in a reduction in arm digging forces & lift capacity. Please refer to the Standard Pages for arm lengths.	No Char
SD_X6100 ARM 747078 Arm Short w/Thumb Bracket 747079 Arm Long w/Thumb Bracket Long arm increases dig depth, resulting in a reduction in arm digging forces & lift capacity. Please refer to the Standard Pages for arm lengths.	No Char
747078 Arm Short w/Thumb Bracket 747079 Arm Long w/Thumb Bracket Long arm increases dig depth, resulting in a reduction in arm digging forces & lift capacity. Please refer to the Standard Pages for arm lengths.	
747078 Arm Short w/Thumb Bracket 747079 Arm Long w/Thumb Bracket Long arm increases dig depth, resulting in a reduction in arm digging forces & lift capacity. Please refer to the Standard Pages for arm lengths.	
747079 Arm Long w/Thumb Bracket Long arm increases dig depth, resulting in a reduction in arm digging forces & lift capacity. Please refer to the Standard Pages for arm lengths. SD_X6206 LINKAGE	
Long arm increases dig depth, resulting in a reduction in arm digging forces & lift capacity. Please refer to the Standard Pages for arm lengths. SD_X6206 LINKAGE	\$912.
arm digging forces & lift capacity. Please refer to the Standard Pages for arm lengths. SD_X6206 LINKAGE	
SD_X6206 LINKAGE	
SD_X6206 LINKAGE	
747062 Linkage With Hook	No Char
747063 Linkage Without Hook	(\$140.0

\$641.00

No Charge



SD_X6210 BEACON

	747070	Beacon		No Charge
	747087	W/O - Beacon		(\$47.00)

SD_X9908 CAMERA

	747089	W/O Rear View Camera		No Charge
Ī	747090	Rear View Camera		\$593.00



Factory Supplied Attachments

Order Code	Description	Weight	Factory Data	List Price
in-On Buckets & 0	Coupler			
48057625	12"HD Bucket (Pin-On & Mech/Hyd Coupler)	190 LB		\$931.00
48057626	18"HD Bucket (Pin-On & Mech/Hyd Coupler)	240 LB		\$1,001.00
48057627	24"HD Bucket (Pin-On & Mech/Hyd Coupler)	291 LB		\$1,143.00
48057628	36"HD Bucket (Pin-On & Mech/Hyd Coupler)	388 LB		\$1,407.00
48057629	36"Ditch Bucket (Pin-On & M/H Coupler)	313 LB		\$1,056.00
48057637	36"Cemetary Bucket (Pin-On& M/H Coupler)	305 LB		\$1,200.00
48057630	Coupler, Mechanical Pin-Grabber (Only compatible with the C-Series bucket) Includes 1 set of dead pins for installation into a single bucket	74 LB		\$1,545.00
48058014	Coupler, Hydraulic Pin-Grabber (Only compatible with the C-Series bucket)	63 LB		\$3,251.00
48082917	Coupler, B/C-Series Universal Mechanical (Compatible with both the B/C-Series buckets)	85 LB		\$824.00
48057631	PIN Required when ordering more than 1 bucket with a Pin- Grabber Coupler			\$209.00
48057639	Ripper Tooth Pin-On	220 LB		\$929.00
LAC Buckets & Co	oupler			
47422702	12"HD Bucket (KLAC Coupler)	220 LB		\$1,165.00
47422703	18"HD Bucket (KLAC Coupler)	256 LB		\$1,237.00
47422704	24"HD Bucket (KLAC Coupler)	309 LB		\$1,379.00
47422705	36"HD Bucket (KLAC Coupler)	408 LB		\$1,643.00
47422658	36"Ditch Bucket (KLAC Coupler)	315 LB		\$1,139.00
47872281	36"Cemetary Bucket (KLAC Coupler)	310 LB		\$1,200.00
48057636	Coupler, KLAC	55 LB		\$1,278.00
47422660	KLAC Base Plate (To adapt other buckets)	31 LB		\$348.00
47873455	ATTACHMENT, RIPPER TOOTH,	220 LB		\$929.00
humbs				
48058021	Thumb Kit, Hyd.,Long Tines (Use with Mech. and Hyd. Pin-Grabber couplers)	250 LB		\$2,453.00
48059650	Thumb Kit, Hyd.,Short Tines (Use with Direct Fit and Klac buckets)	250 LB		\$2,453.00

	C-Series Mini Excavator BUCKET COMPATIBILITY							
Model	Order Code	Description B-Ser Buck		C-Series Buckets				
CX17C	48057609	Coupler, Mechanical Pin-Grabber	No	Yes				
	48057615	Coupler, Mechanical Pin-Grabber	No	Yes				
CX26C	48094307	Coupler, Hydraulic Pin-Grabber	Yes (requires removal of spacer plates)	Yes				
CX33C/CX37C	48057623	Coupler, Mechanical Pin-Grabber	Yes	Yes				
CASSC/CAS7C	48058013	Coupler, Hydraulic Pin-Grabber	Yes	Yes				
eveza leveza	48057630	Coupler, Mechanical Pin-Grabber	No	Yes				
CX57C/CX60C	48058014	Coupler, Hydraulic Pin-Grabber	No	Yes				
	48082917	Coupler, B/C Series Universal Mechanical	Yes	Yes				



Service Parts DIA Kits

Updated January 2019	С	С	С	С	С	С	С
	x	X	х	х	Х	Х	Х
	1	2	3	3	3	5	6
	7	6	0	3	7	7	0
		С	c	С	C	С	С

			С	С	С	С	С	_ C	С
Туре	Part Number	DESCRIPTION							
Telematics	48041548	Telematics, Inst. Instruction p/n 48045133	Х						
Telematics	48041549	Telematics, Inst. Instruction p/n 48179901		Х	X	X	Х		
Telematics	48041551	Telematics, Inst. Instruction p/n 48045137						Х	
Telematics	48071951	Telematics, Inst. Instruction p/n 48173065 S/N range before 0055							X
Telematics	48105205	Telematics, Inst. Instruction p/n 48105208 S/N range after 0056							Х
Hydraulics	48160505	Hyd Quick Coupler Provision, Inst. Instruction p/n 47899431	X						
Hydraulics	48160524	Hyd Quick Coupler Provision, Inst. Instruction p/n 47790740		X					
Hydraulics	48160530	Hyd Quick Coupler Provision, Inst. Instruction p/n 47790740			Х				
Hydraulics	48160535	Hyd Quick Coupler Provision, Inst. Instruction p/n 47760654				Х			
Hydraulics	48160582	Hyd Quick Coupler Provision, Inst. Instruction p/n 47760654					Х		
Hydraulics	51447893	Hyd Quick Coupler Provision, Inst. Instruction p/n 51447902						Х	
Hydraulics	51502078	Bucket/arm cylinder rod covers, Inst. Instruction p/n 51503097	Х						
Hydraulics	48100296	2nd Aux 2-Way Circuit, Inst. Instruction p/n 47760002		Х					
Hydraulics	48100297	2nd Aux 2-Way Circuit, Inst. Instruction p/n 47760002			Х				
Hydraulics	48100300	2nd Aux 2-Way Circuit, Inst. Instruction p/n 47760208				X			
Hydraulics	48100302	2nd Aux 2-Way Circuit, Inst. Instruction p/n 47760208					Х		
Operational	48120194	Additional Counterweight, Inst. Instruction p/n 48120189	X						
Operational	48120192	Additional Counterweight, Inst. Instruction p/n 48120189			Х				
Operational	48118003	Travel Alarm, Inst. Instruction p/n 48117996	X						
Operational	48118005	Travel Alarm, Inst. Instruction p/n 48178344			Х				
Operational	48152807	Boom/Arm Holding Valves (Object Handling), Inst. Instruction p/n 47790107		Х					
Operational	48153030	Boom/Arm Holding Valves (Object Handling) - ROPS, Inst. Instruction p/n 47790107			Х				
Operational	48153031	Boom/Arm Holding Valves (Object Handling) - CAB, Inst. Instruction p/n 47790107			Х				
Operational	48153036	Boom/Arm Holding Valves (Object Handling) - CAB, Inst. Instruction p/n 47790107				Х			
Operational	48153038	Boom/Arm Holding Valves (Object Handling) - CAB, Inst. Instruction p/n 47790107					Х		
Cab	48100304	Seat Belt 3", Inst. Instruction p/n 47989463	Х						
Cab	48100303	Seat Belt 3", Inst. Instruction p/n 47992927						Х	Х