Landscaping

### **PB1001 Integral One Bottom Turning Plow**

Equipment for Base Machine

Hitch:
Lift-type, Category I,
not iMatch Compatible
One, 14 In. (355.6 mm) Moldboard
Transport Length:
45 In. (1,143 mm)
Transport Width:
33 In. (838.2 mm)
Transport Height:
40.5 In. (1,028.7 mm)
Tractor Engine HP Range:
25 - 50 HP

Moldboard Dimensions: 14 In. (355.6 mm) (W) x 21 In. (533.4 mm) (L) x 16 In. (406.4 mm) (H) Parking Stand Included

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
3431XF		PB1001 Integral One Bottom Turning Plow Order in multiples of two.	848.00
		OPERATOR'S MANUAL AND DECALS	
904J		French OM & Decal Kit (PB10)	13.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5TITE511154	<b>Miscellaneous</b> French Kit - Includes Operator's Manual, Parts Catalog and Safety Decals <i>PB1001 and PB1002</i>	15.60

## PB1001 Integral One Bottom Turning Plow Continued

ΤI	ΗІ	S	PA	GE	INT	ΈN	JTI(	ANC	LLY I	LEFT	BLA	١N٨	Κ

Landscaping

### **PB1002 Integral Two Bottom Turning Plow**

**Equipment for Base Machine** 

Hitch:
Lift-type, Category I,
not iMatch Compatible
Two, 14 In. (355.6 mm) Moldboards
Transport Length:
71 In. (1,803.4 mm)
Transport Width:
40 In. (1,016 mm)
Transport Height:
40.5 In. (1,028.7 mm)
Tractor Engine HP Range:

PB1001 and PB1002

25 - 50 HP Moldboard Dimensions: 14 In. (355.6 mm) (W) x 21 In. (533.4 mm) (L) x 16 In. (406.4 mm) (H)

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	٦
		Select Offe Code From Each Required Category	_
		BASE MACHINE	
3432XF		PB1002 Integral Two Bottom Turning Plow Order in multiples of two.	1,405.00
		OPERATOR'S MANUAL AND DECALS	
904J		French OM & Decal Kit (PB10)	13.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5TITE511154	Miscellaneous French Kit - Includes Operator's Manual, Parts Catalog and Safety Decals	15.60

## PB1002 Integral Two Bottom Turning Plow Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Landscaping

### **BB2048 Standard Duty Box Blade**

**Equipment for Base Machine** 

3-Point Hitch:
Category I
iMatch Compatible: Yes
Working Width: 48 In.
Tractor HP: 17 to 45 HP
Tailgate: Fixed
Shipping Weight:
758 lbs. - (Pair)
Shanks: (4) Replaceable
Shank Type:
3-Position with Holes and 1/2 In. Pin
Scarifier Points:
Replaceable, Hardened Steel
End Plate Thickness: 3/8 In.
Moldboard Thickness: 3/16 In.

Moldboard Type: Formed Back
Mast: Bolt-up with 1/4 In. Plates
Duty: Standard Duty
Cutting Edges:
(2) 1/2 In. x 6 In. Reversible
Assembly/Set up Time:
30 Minutes (Approximate) - Per Pair
Approximate Operating Weight: 355 lbs.
Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
4044		BASE MACHINE	4.040.00
1041XF		BB2048 Standard Duty Box Blade Order in multiples of two.	1,040.00
		OPERATOR'S MANUAL AND DECALS	
9200		French Operator's Manual and Decal Kit (BB20 and BB21 Series)	49.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5WS101371	Miscellaneous French Operator's Manual and Decal Kit (BB20, BB21 and BB20L Series)	53.76

## BB2048 Standard Duty Box Blade Continued

THIS PAGE INTENTIONALLY LEFT BLANK

03 December	2018	US &	Canada

Landscaping

#### BB2048L Limited Category I Standard Duty Box Blade

**Equipment for Base Machine** 

Capacity:
6.6 Cubic Foot
Tractor HP (Maximum): 25 HP
Cutting Edges:
(2) 1/2 In. x 6 Reversible
Scarifier Shanks:
3-Position with Holes
Scarifier Shank Points:
3 Replaceable, Hardened Points
Beam Size: 4 In. x 4 In. x 1/4 In.
Beam Reinforcement:
3/8 In. x 1 In. Bar Inside Tube
End Plate Thickness: 3/16 In.
Working Width: 48 In.
Height: 14 In.
Depth: 17 In.
Tailgate: Fixed

3-Point Hitch:
Limited Category I (Aftermarket
Category 0 Lift Pins Available)
Mast Design:
Bolt-up with 1/4 In. Plates
Moldboard Thickness: 7 Gauge
Assembly/Set-up Time:
30 Minutes (Approximate)
Approximate Operating Weight: 275 lbs.
Shipping Weight: 636 lbs.
Packaged 2 per Pallet

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1051XF		BB2048L Limited Category I Standard Duty Box Blade Order in multiples of two.	876.00
		OPERATOR'S MANUAL AND DECALS	
9200		French Operator's Manual and Decal Kit (BB20 and BB21 Series)	49.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5WS101371	Miscellaneous French Operator's Manual and Decal Kit (BB20, BB21 and BB20L Series)	53.76

## BB2048L Limited Category I Standard Duty Box Blade Continued

THIS	S PA	AGF.	INTFI	NTIC	DNALLY	I FFT	BLANK	(
1 1 11		<b>'</b>						•

Landscaping

### **BB2060 Standard Duty Box Blade**

**Equipment for Base Machine** 

3-Point Hitch:
Category I
iMatch Compatible: Yes
Working Width: 60 In.
Tractor HP: 19 to 55 HP
Tailgate: Fixed
Shipping Weight:
918 lbs. - (Pair)
Shanks: (4) Replaceable
Shank Type:
3-Position with Holes and 1/2 In. Pin
Scarifier Points:
Replaceable, Hardened Steel
End Plate Thickness: 3/8 In.
Moldboard Thickness: 3/16 In.

Moldboard Type: Formed Back
Mast: Bolt-up with 1/4 In. Plates
Duty: Standard Duty
Cutting Edges:
(2) 1/2 In. x 6 In. Reversible
Assembly/Set-Up Time:
30 Minutes (Approximate) - Per Pair
Approximate Operating Weight: 425 lbs.
Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1042XF		BB2060 Standard Duty Box Blade Order in multiples of two.	1,130.00
		OPERATOR'S MANUAL AND DECALS	
9200		French Operator's Manual and Decal Kit (BB20 and BB21 Series)	49.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5WS101371	Miscellaneous French Operator's Manual and Decal Kit (BB20, BB21 and BB20L Series)	53.76

## BB2060 Standard Duty Box Blade Continued

THIS	S PA	AGF.	INTFI	NTIC	DNALLY	I FFT	BLANK	(
1 1 11		<b>'</b>						•

Landscaping

### **BB2065 Standard Duty Box Blade**

**Equipment for Base Machine** 

3-Point Hitch:
Category I
IMatch Compatible: Yes
Working Width: 66 In.
Tractor HP: 23 to 55 HP
Tailgate: Fixed
Shipping Weight:
988 lbs. - (Pair)
Shanks: (4) Replaceable
Shank Type:
3-Position with Holes and 1/2 In. Pin
Scarifier Points:
Replaceable, Hardened Steel
End Plate Thickness: 3/8 In.
Moldboard Thickness: 3/16 In.

Moldboard Type: Formed Back
Mast: Bolt-up with 1/4 In. Plates
Duty: Standard Duty
Cutting Edges:
(2) 1/2 In. x 6 In. Reversible
Assembly/Set up Time:
30 Minutes (Approximate) - Per Pair
Approximate Operating Weight: 460 lbs.
Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1043XF		BB2065 Standard Duty Box Blade Order in multiples of two.	1,233.00
		OPERATOR'S MANUAL AND DECALS	
9200		French Operator's Manual and Decal Kit (BB20 and BB21 Series)	49.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5WS101371	Miscellaneous French Operator's Manual and Decal Kit (BB20, BB21 and BB20L Series)	53.76

## BB2065 Standard Duty Box Blade Continued

THIS	S PA	AGF.	INTFI	NTIC	DNALLY	I FFT	BLANK	(
1 1 11		<b>'</b>						•

Landscaping

### **BB2072 Standard Duty Box Blade**

**Equipment for Base Machine** 

3-Point Hitch:
Category I
iMatch Compatible: Yes
Working Width: 72 In.
Tractor HP: 27 to 55 HP
Tailgate: Fixed
Shipping Weight:
1056 lbs. - (Pair)
Shanks: (5) Replaceable
Shank Type:
3-Position with Holes and 1/2 In. Pin
Scarifier Points:
Replaceable, Hardened Steel
End Plate Thickness: 3/8 In.
Moldboard Thickness: 3/16 In.

Moldboard Type: Formed Back
Mast: Bolt-up with 1/4 In. Plates
Duty: Standard Duty
Cutting Edges:
(2) 1/2 In. x 6 In. Reversible
Assembly/Set up Time:
30 Minutes (Approximate) - Per Pair
Approximate Operating Weight: 494 lbs.
Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1044XF		BB2072 Standard Duty Box Blade Order in multiples of two.	1,306.00
		OPERATOR'S MANUAL AND DECALS	
9200		French Operator's Manual and Decal Kit (BB20 and BB21 Series)	49.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5WS101371	Miscellaneous French Operator's Manual and Decal Kit (BB20, BB21 and BB20L Series)	53.76

## BB2072 Standard Duty Box Blade Continued

THIS PAGE INTENTIONALLY LEFT BLANK

03 December	2018	US &	Canada

Landscaping

#### **BB2172 Medium Duty Box Blade**

**Equipment for Base Machine** 

3-Point Hitch:
Category I
Working Width: 72 In.
Height: 33-1/2 In.
Depth: 31 In.
Capacity:
19 Cubic Foot
Tractor HP: 70 HP Maximum
Tailgate:
Floating/Removable
Shanks:
(6) Replaceable
Beam Size:
4 In. x 4 In. x 1/4 In.
Beam Reinforcement:
1 In. x 3/8 In. Backing Strip
End Plate Thickness:
3/8 In. with a 3/8 In. x 3 In.
Reinforced Bottom Edge

Moldboard Thickness: 3/16 In.
Duty: Medium
Cutting Edges:
(2) 1/2 In. x 6 In. Reversible
Assembly/Set-Up Time:
15 Minutes (Approximate)
Operating Weight:
585 lbs. (Approximate)
Shipping Weight:
675 lbs. (Approximate)
Packaged 1 Per Pallet
Mast: Bolt-up with 3/8 In. Plates
Warranty: 1 Year

	Attachment		List Price Suggested
Code	Identifier	Description	USD (\$)
			1
		Select One Code From Each Required Category	
		DACE MACHINE	
		BASE MACHINE	
1061XF		BB2172 Medium Duty Box Blade	1,735.00
		OPERATOR'S MANUAL AND DECALS	
9200		French Operator's Manual and Decal Kit (BB20 and BB21 Series)	49.00
		ATTACHMENTS FOR FIELD CONVERSION	
		ATTACHMENTO FOR FILLE CONVERCION	
		Miscellaneous	
	5WS101371	French Operator's Manual and Decal Kit (BB20, BB21 and BB20L Series)	53.76

### BB2172 Medium Duty Box Blade Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Landscaping

#### **BB2184 Medium Duty Box Blade**

**Equipment for Base Machine** 

3-Point Hitch:
Category I, iMatch Compatible
(Quick-Attach System)
Working Width: 84 In.
Height: 33-1/2 In.
Depth: 31 In.
Capacity: 22.3 Cubic Foot
Tractor HP (Maximum): 70 HP
Tailgate:
Floating/Removable
Shanks: (7) Replaceable
Beam Size: 4 In. x 4 In. x 1/4 In.
Beam Reinforcement:
1 In. x 3/8 In. Backing Strip
End Plate Thickness:
3/8 In. with a 3/8 In. x 3 In.
Reinforced Bottom Edge
Duty: Medium

Moldboard Thickness: 3/16 In.
Cutting Edges:
(2) 1/2 In. x 6 In. Reversible
Assembly/Set-Up Time:
15 Minutes (Approximate)
Operating Weight:
667 lbs. (Approximate)
Shipping Weight:
757 lbs. (Approximate)
Packaged 1 Per Pallet
Mast: Bolt-up with 3/8 In. Plates
Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	

	BASE MACHINE	
1062XF	BB2184 Medium Duty Box Blade	1,901.00
	OPERATOR'S MANUAL AND DECALS	
9200	French Operator's Manual and Decal Kit (BB20 and BB21 Series)	49.00
	ATTACHMENTS FOR FIELD CONVERSION	
5WS101371	Miscellaneous French Operator's Manual and Decal Kit (BB20, BB21 and BB20L Series)	53.76

### BB2184 Medium Duty Box Blade Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Landscaping

#### BB4160 - 5 Ft. Hydraulic Scarifier Box Blade - Low Back

**Equipment for Base Machine** 

Tailgate: Hinged, Floating Grading and Leveling: Fine, Precision Grading and Leveling Tractor Compatibility: Category I iMatch Compatible Beam Type: Tubular Scarifier Beam Scarifier Shanks: Notched 3 Position Points: Heat Treated Points Box Design: Low Back Hydraulic Opening: Hydraulically Operated Scarifier Bar Hydraulic Kit: Pin Kit And Hydraulic Hose Kit Included Capacity (Cubic Foot): 21.8 Cubic Foot Tractor HP: Up to 50 HP Cutting Edges:
(2) 1/2 In. x 6 In. Reversible Scarifier Shanks: (6) Replaceable Beam Size: Main Beam - 4 In. x 4 In. x 1/4 In. Shank Beam - 4 In.  $\times$  4 In.  $\times$  1/4 In.

Beam Reinforcement:
1/2 In. x 3/4 In. Bar
End Plate Thickness: 3/8 In.
Working Width: 60 In.
Height: 20 In.
Depth: 33 In.
Duty: Medium
Hitch Type:
Category I iMatch Compatible
Mast Design:
Welded 3/8 In. Plate
Assembly/Set-Up Time: 30 Minutes
Operating Weight: 725 lbs.
Shipping Weight: 725 lbs.
Shipping Weight: 765 lbs.
Shipping per Crate:
Packaged 1 Per Pallet
Warranty: 1 Year Warranty
Moldboard Thickness: 3/16 In.
Manufacturer Model: TB30-60H
Paint Color: Green

			List Price
	Attachment		Suggested
Code	Identifier	Description	USD (\$)

Select One Code From Each Required Category

#### **BASE MACHINE**

1101XF

BB4160 - 5 Ft. Hydraulic Scarifier Box Blade - Low Back

3,166.00

## BB4160 - 5 Ft. Hydraulic Scarifier Box Blade - Low Back Continued

ΤI	ΗІ	S	PA	GE	INT	ΈN	JTI(	ANC	LLY I	LEFT	BLA	١N٨	Κ

20

Landscaping

#### BB4166 - 5 Ft. 6 In. Hydraulic Scarifier Box Blade - Low Back

**Equipment for Base Machine** 

Tailgate: Hinged, Floating Grading and Leveling: Fine, Precision Grading and Leveling Tractor Compatibility: Category I iMatch Compatible Beam Type: Tubular Scarifier Beam Scarifier Shanks: Notched 3 Position Points: Heat Treated Points Box Design: Low Back Hydraulic Opening: Hydraulically Operated Scarifier Bar Hydraulic Kit: Pin Kit and Hydraulic Hose Kit Included Capacity (Cubic Foot):
24 Cubic Foot Tractor HP: Up to 50 HP Cutting Edges:
(2) 1/2 In. x 6 In. Reversible Scarifier Shanks: (6) Replaceable Beam Size: Main Beam - 4 In. x 4 In. x 1/4 In. Shank Beam - 4 In.  $\times$  4 In.  $\times$  1/4 In.

Beam Reinforcement:
1/2 In. x 3/4 In. Bar
End Plate Thickness: 3/8 In.
Working Width: 66 In.
Height: 20 In.
Depth: 33 In.
Duty: Medium
Hitch Type:
Category I iMatch Compatible
Mast Design:
Welded 3/8 In. Plate
Assembly/Set-Up Time: 30 Minutes
Operating Weight: 772 lbs.
Shipping Weight: 812 lbs.
Shipping beight: 812 lbs.
Shipping per Crate:
Packaged 1 Per Pallet
Warranty: 1 Year Warranty
Moldboard Thickness: 3/16 In.
Manufacturer Model: TB30-66H
Paint Color: Green

			List Price
	Attachment		Suggested
Code	Identifier	Description	USD (\$)

Select One Code From Each Required Category

#### **BASE MACHINE**

1102XF

BB4166 - 5 Ft. 6 In. Hydraulic Scarifier Box Blade - Low Back

3,272.00

## BB4166 - 5 Ft. 6 In. Hydraulic Scarifier Box Blade - Low Back Continued

THIS PAGE INTENTIONALLY LEFT BLANK

22

#### Landscaping

#### BB4172 - 6 Ft. Hydraulic Scarifier Box Blade - Low Back

**Equipment for Base Machine** 

Tailgate: Hinged, Floating Grading and Leveling: Fine, Precision Grading and Leveling Tractor Compatibility: Category I iMatch Compatible Beam Type: Tubular Scarifier Beam Scarifier Shanks: Notched 3 Position Points: Heat Treated Points Box Design: Low Back Hydraulic Opening: Hydraulically Operated Scarifier Bar Hydraulic Kit: Pin Kit and Hydraulic Hose Kit Included Capacity (Cubic Foot): 26.2 Cubic Foot Tractor HP: Up to 50 HP Cutting Edges:
(2) 1/2 In. x 6 In. Reversible Scarifier Shanks: (6) Replaceable Beam Size: Main Beam - 4 In. x 4 In. x 1/4 In. Shank Beam - 4 In.  $\times$  4 In.  $\times$  1/4 In.

Beam Reinforcement:
1/2 In. x 3/4 In. Bar
End Plate Thickness: 3/8 In.
Working Width: 72 In.
Height: 20 In.
Depth: 33 In.
Duty: Medium
Hitch Type:
Category I iMatch Compatible
Mast Design:
Welded 3/8 In. Plate
Assembly/Set-Up Time: 30 Minutes
Operating Weight: 815 lbs.
Shipping Weight: 815 lbs.
Shipping Weight: 855 lbs.
Shipping per Crate:
Packaged 1 Per Pallet
Warranty: 1 Year Warranty
Moldboard Thickness: 3/16 In.
Manufacturer Model: TB30-72H
Paint Color: Green

			List Price
	Attachment		Suggested
Code	Identifier	Description	USD (\$)

Select One Code From Each Required Category

#### **BASE MACHINE**

1103XF

BB4172 - 6 Ft. Hydraulic Scarifier Box Blade - Low Back Green only.

3,316.00

## BB4172 - 6 Ft. Hydraulic Scarifier Box Blade - Low Back Continued

ΤI	ΗІ	S	PA	GE	INT	ΈN	JTI(	ANC	LLY I	LEFT	BLA	١N٨	Κ

24

Landscaping

#### BB4178 - 6 Ft. 6 In. Hydraulic Scarifier Box Blade - Low Back

**Equipment for Base Machine** 

Tailgate: Hinged, Floating Grading and Leveling: Fine, Precision Grading and Leveling Tractor Compatibility:
Category I and II, iMatch and Quick Coupler Compatible Beam Type: Tubular Scarifier Beam Scarifier Shanks: Notched 3 Position Points: Heat Treated Points Box Design: Low Back Hydraulic Opening: Hydraulically Operated Scarifier Bar Hydraulic Kit:
Pin Kit and Hydraulic Hose Kit Included
Capacity (Cubic Foot):
28.3 Cubic Foot
Tractor HP: Up to 90 HP
Cutting Edges:
(2) 1/2 The reference Scalifier Ball (2) 1/2 In. x 6 In. Reversible Scarifier Shanks: (8) Replaceable Beam Size: Main Beam - 4 In.  $\times$  4 In.  $\times$  1/4 In. Shank Beam - 4 In.  $\times$  4 In.  $\times$  1/4 In.

Beam Reinforcement:
1/2 In. x 3/4 In. Bar
End Plate Thickness: 1/2 In.
Working Width: 78 In.
Height: 20 In.
Depth: 33 In.
Duty: Heavy
Hitch Type:
Category I and II, iMatch and
Quick Coupler Compatible
Mast Design:
Welded 1/2 In. Plate
Assembly/Set-Up Time: 30 Minutes
Operating Weight: 1016 lbs.
Shipping Weight: 1056 lbs.
Shipping per Crate:
Packaged 1 Per Pallet
Warranty: 1 Year Warranty
Moldboard Thickness: 1/4 In.
Manufacturer Model: TB30-78H
Paint Color:
Construction Yellow (Optional Green)

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1104XF		BB4178 - 6 Ft. 6 In. Hydraulic Scarifier Box Blade - Low Back	3,774.00
		COLOR	
1000		Green	In Base Price
1010		Construction Yellow	No Added Cost

## BB4178 - 6 Ft. 6 In. Hydraulic Scarifier Box Blade - Low Back Continued

THIS	S PA	AGF.	INTFI	NTIC	DNALLY	I FFT	BLANK	(
1 1 11		<b>'</b>						•

Landscaping

### BB4184 - 7 Ft. Hydraulic Scarifier Box Blade - Low Back

**Equipment for Base Machine** 

Tailgate:
Hinged, Floating Grading and Leveling: Fine, Precision Grading And Leveling Tractor Compatibility: Category I and II, iMatch and Quick Coupler Compatible Beam Type: Tubular Scarifier Beam Scarifier Shanks: Notched 3 Position Points: Heat Treated Points Box Design: Low Back Hydraulic Opening: Hydraulically Operated Scarifier Bar Hydraulic Kit:
Pin Kit and Hydraulic Hose Kit Included
Capacity (Cubic Foot):
30.5 Cubic Foot
Tractor HP: Up to 90 HP
Cutting Edges:
(2) 1/2 The reference Scalifier Ball (2) 1/2 In. x 6 In. Reversible Scarifier Shanks: (8) Replaceable Beam Size: Main Beam - 4 In.  $\times$  4 In.  $\times$  1/4 In. Shank Beam - 4 In.  $\times$  4 In.  $\times$  1/4 In.

Beam Reinforcement:
1/2 In. x 3/4 In. Bar
End Plate Thickness: 1/2 In.
Working Width: 84 In.
Height: 20 In.
Depth: 33 In.
Duty: Heavy
Hitch Type:
Category I and II, iMatch and
Quick Coupler Compatible
Mast Design:
Welded 1/2 In. Plate
Assembly/Set-Up Time: 30 Minutes
Operating Weight: 1052 lbs.
Shipping Weight: 1052 lbs.
Shipping weight: 1092 lbs.
Shipping per Crate:
Packaged 1 Per Pallet
Warranty: 1 Year Warranty
Moldboard Thickness: 1/4 In.
Manufacturer Model: TB30-84H
Paint Color:
Construction Yellow (Optional Green)

	Attachment		List Price Suggested
Code	Identifier	Description	USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1105XF		BB4184 - 7 Ft. Hydraulic Scarifier Box Blade - Low Back	3,925.00
		COLOR	
1000		Green	In Base Price
1010		Construction Yellow	No Added Cost

## BB4184 - 7 Ft. Hydraulic Scarifier Box Blade - Low Back Continued

THIS	S PA	AGF.	INTFI	NTIC	DNALLY	I FFT	BLAN	≺
1 1 11		<b>'</b>						

28

#### Landscaping

### BB4196 - 8 Ft. Hydraulic Scarifier Box Blade - Low Back

**Equipment for Base Machine** 

Tailgate:
Hinged, Floating Grading and Leveling: Fine, Precision Grading and Leveling Tractor Compatibility: Category I and II, iMatch and Quick Coupler Compatible Beam Type: Tubular Scarifier Beam Scarifier Shanks: Notched 3 Position Points: Heat Treated Points Box Design: Low Back Hydraulic Opening: Hydraulically Operated Scarifier Bar Hydraulic Kit:
Pin Kit and Hydraulic Hose Kit Included
Capacity (Cubic Foot):
34.9 Cubic Foot
Tractor HP: Up to 90 HP
Cutting Edges:
(2) 1/2 The reference Scalifier Ball (2) 1/2 In. x 6 In. Reversible Scarifier Shanks: (8) Replaceable Beam Size: Main Beam - 4 In.  $\times$  4 In.  $\times$  1/4 In. Shank Beam - 4 In.  $\times$  4 In.  $\times$  1/4 In.

Beam Reinforcement:
1/2 In. x 3/4 In. Bar
End Plate Thickness: 1/2 In.
Working Width: 96 In.
Height: 20 In.
Depth: 33 In.
Duty: Heavy
Hitch Type:
Category I and II, iMatch and
Quick Coupler Compatible
Mast Design:
Welded 1/2 In. Plate
Assembly/Set-Up Time: 30 Minutes
Operating Weight: 1146 lbs.
Shipping Weight: 1186 lbs.
Shipping per Crate:
Packaged 1 Per Pallet
Warranty: 1 Year Warranty
Moldboard Thickness: 1/4 In.
Manufacturer Model: TB30-96H
Paint Color:
Construction Yellow (Optional Green)

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1106XF		BB4196 - 8 Ft. Hydraulic Scarifier Box Blade - Low Back	4,054.00
		COLOR	
1000		COLOR Green	In Base Price

## BB4196 - 8 Ft. Hydraulic Scarifier Box Blade - Low Back Continued

THIS PAGE INTENTIONALLY LEFT BLANK

30

Landscaping

#### BB4278H - 6 Ft. 6 In. Hydraulic Scarifier Box Blade - High Back

**Equipment for Base Machine** 

Tailgate: Hinged, Floating Grading and Leveling: Fine, Precision Grading and Leveling Tractor Compatibility: Category I and II, iMatch and Quick Coupler Compatible Beam Type: Tubular Scarifier Beam Scarifier Shanks: Notched 3 Position Points: Heat Treated Points Box Design: High Back Hydraulic Opening: Hydraulically Operated Scarifier Bar Hydraulic Kit:
Pin Kit and Hydraulic Hose Kit Included
Capacity (Cubic Foot):
32 Cubic Foot Tractor HP: Up to 90 HP Cutting Edges: (2) 1/2 In. x 6 In. Reversible Scarifier Shanks: (8) Replaceable Beam Size: Main Beam - 5 In. x 5 In. x 1/4 In. Shank Beam - 5 In. x 5 In. x 1/4 In. Beam Reinforcement:

Construction Yellow

1010

1/2 In. x 1 In. Bar
End Plate Thickness: 1/2 In.
Working Width: 78 In.
Height:
20 In. Front, 26 In. Rear
Depth: 33 In.
Duty: Heavy
Hitch Type:
Category I and II, iMatch and
Quick Coupler Compatible
Mast Design:
Welded 1/2 In. Plate
Assembly/Set-Up Time: 30 Minutes
Operating Weight: 1160 lbs.
Shipping Weight: 1200 lbs.
Shipping per Crate:
Packaged 1 Per Pallet
Warranty: 1 Year Warranty
Moldboard Thickness: 1/4 In.
Manufacturer Model: TB40-78H
Paint Color:
Construction Yellow (Optional Green)

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
1111XF		BASE MACHINE BB4278H - 6 Ft. 6 In. Hydraulic Scarifier Box Blade - High Back	4,012.00
1000		COLOR Green	In Base Price

No Added Cost

## BB4278H - 6 Ft. 6 In. Hydraulic Scarifier Box Blade - High Back Continued

TΙ	ΗІ	S	PA	GE	INT	ΕN	TIC	DNALL	Y LEF	ТΒІ	LAN	K

32

Landscaping

### BB4284H - 7 Ft. Hydraulic Scarifier Box Blade - High Back

**Equipment for Base Machine** 

Tailgate: Hinged, Floating Grading and Leveling: Fine, Precision Grading and Leveling Tractor Compatibility: Category I and II, iMatch and Quick Coupler Compatible Beam Type: Tubular Scarifier Beam Scarifier Shanks: Notched 3 Position Points: Heat Treated Points Box Design: High Back Hydraulic Opening: Hydraulically Operated Scarifier Bar Hydraulic Kit: Pin Kit and Hydraulic Hose Kit Included Capacity (Cubic Foot): 34.5 Cubic Foot Tractor HP: Up to 90 HP Cutting Edges: (2) 1/2 In. x 6 In. Reversible Scarifier Shanks: (8) Replaceable Beam Size: Main Beam - 5 In.  $\times$  5 In.  $\times$  1/4 In. Shank Beam - 5 In.  $\times$  5 In.  $\times$  1/4 In. Beam Reinforcement:

Construction Yellow

1010

1/2 In. x 1 In. Bar
End Plate Thickness: 1/2 In.
Working Width: 84 In.
Height:
20 In. Front, 26 In. Rear
Depth: 33 In.
Duty: Heavy
Hitch Type:
Category I and II, iMatch and
Quick Coupler Compatible
Mast Design:
Welded 1/2 In. Plate
Assembly/Set-Up Time: 30 Minutes
Operating Weight: 1200 lbs.
Shipping Weight: 1240 lbs.
Shipping per Crate:
Packaged 1 Per Pallet
Warranty: 1 Year Warranty
Moldboard Thickness: 1/4 In.
Manufacturer Model: TB40-84H
Paint Color:
Construction Yellow (Optional Green)

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
1112XF		BASE MACHINE  BB4284H - 7 Ft. Hydraulic Scarifier Box Blade - High Back	4,077.00
1000		COLOR Green	In Base Price

No Added Cost

## BB4284H - 7 Ft. Hydraulic Scarifier Box Blade - High Back Continued

THIS PAGE INTENTIONALLY LEFT BLANK

#### Landscaping

### BB4296H - 8 Ft. Hydraulic Scarifier Box Blade - High Back

**Equipment for Base Machine** 

Tailgate: Hinged, Floating Grading and Leveling: Fine, Precision Grading and Leveling Tractor Compatibility: Category I and II, iMatch and Quick Coupler Compatible Beam Type: Tubular Scarifier Beam Scarifier Shanks: Notched 3 Position Points: Heat Treated Points Box Design: High Back Hydraulic Opening: Hydraulically Operated Scarifier Bar Hydraulic Kit: Pin Kit and Hydraulic Hose Kit Included Capacity (Cubic Foot): 39.4 Cubic Foot Tractor HP: Up to 90 HP Cutting Edges: (2) 1/2 In. x 6 In. Reversible Scarifier Shanks: (8) Replaceable Beam Size: Main Beam - 5 In.  $\times$  5 In.  $\times$  1/4 In. Shank Beam - 5 In.  $\times$  5 In.  $\times$  1/4 In. Beam Reinforcement:

Construction Yellow

1010

1/2 In. x 1 In. Bar
End Plate Thickness: 1/2 In.
Working Width: 96 In.
Height:
20 In. Front, 26 In. Rear
Depth: 33 In.
Duty: Heavy
Hitch Type:
Category I and II, iMatch and
Quick Coupler Compatible
Mast Design:
Welded 1/2 In. Plate
Assembly/Set-Up Time: 30 Minutes
Operating Weight: 1310 lbs.
Shipping Weight: 1350 lbs.
Shipping per Crate:
Packaged 1 Per Pallet
Warranty: 1 Year Warranty
Moldboard Thickness: 1/4 In.
Manufacturer Model: TB4096H
Paint Color:
Construction Yellow (Optional Green)

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1113XF		BB4296H - 8 Ft. Hydraulic Scarifier Box Blade - High Back	4,360.00
		COLOR	
1000		Green	In Base Price

No Added Cost

## BB4296H - 8 Ft. Hydraulic Scarifier Box Blade - High Back Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Landscaping

#### **BB3272 BOX BLADE W/SCARIFIER**

**Equipment for Base Machine** 

Tailgate: Hinged Tailgate Grading and Leveling: Fine, Precision Grading and Leveling Tractor Compatibility: Balanced Design Beam Type: Tubular Scarifier Beam Scarifier Shanks: Notched 3 Position Points: Heat Treated Points Box Design: High Capacity Box, No Gussets or Obstructions Hydraulic Opening: NA Hydraulic Kit: NA Capacity (Cubic Foot): 21 Cubic Foot Tractor HP: 80 HP Maximum Cutting Edges:
(2) 1/2 In. x 6 In. Reversible Scarifier Shanks: (7) Replaceable Beam Size: 4 In. x 4 In. x 3/8 In.

Beam Reinforcement: Yes End Plate Thickness: 1/2 In. Working Width: 72 In.
Height: 20 In.
Depth: 26-1/2 In.
Duty: Construction Grade
Hitch Type: Category I and Category II Quick Hitch Compatible Mast Design: Welded Assembly/Set-Up Time: 15 Minutes Operating Weight: 790 lbs. Shipping Weight: 830 lbs. Shipping per Crate: Packaged 1 Per Pallet Warranty: 1 Year Warranty Moldboard Thickness: 1/4 In. Manufacturer Model: New Paint Color: Construction Yellow

			List Price
	Attachment		Suggested
Code	Identifier	Description	USD (\$)

Select One Code From Each Required Category

#### **BASE MACHINE**

1081XF BB3272 BOX BLADE W/SCARIFIER

Construction yellow.

2,412.00

## **BB3272 BOX BLADE W/SCARIFIER**

Continued

ΤI	ΗІ	S	PA	GE	INT	ΈN	JTI(	ANC	LLY I	LEFT	BLA	١N٨	Κ

Landscaping

#### **BB3284 BOX BLADE W/SCARIFIER**

**Equipment for Base Machine** 

Tailgate: Hinged Tailgate Grading and Leveling: Fine, Precision Grading and Leveling Tractor Compatibility: Balanced Design Beam Type: Tubular Scarifier Beam Scarifier Shanks: Notched 3 Position Points: Heat Treated Points Box Design: High Capacity Box, No Gussets or Obstructions Hydraulic Opening: NA Hydraulic Kit: NA Capacity (Cubic Foot): 24.50 Cubic Foot Tractor HP: 80 HP Maximum Cutting Edges:
(2) 1/2 In. x 6 In. Reversible Scarifier Shanks: (8) Replaceable Beam Size: 4 In. x 4 In. x 3/8 In.

Beam Reinforcement: Yes
End Plate Thickness: 1/2 In.
Working Width: 84 In.
Height: 20 In.
Depth: 26-1/2 In.
Duty: Construction Grade
Hitch Type:
Category I and Category II
Quick Hitch Compatible
Mast Design: Welded
Assembly/Set-Up Time: 15 Minutes
Operating Weight: 885 lbs.
Shipping Weight: 925 lbs.
Shipping Weight: 925 lbs.
Shipping per Crate:
Packaged 1 Per Pallet
Warranty: 1 Year Warranty
Moldboard Thickness: 1/4 In.
Manufacturer Model: New
Paint Color: Construction Yellow

List Price
Attachment Suggested
Code Identifier Description USD (\$)

Select One Code From Each Required Category

#### **BASE MACHINE**

1082XF BB3284 BOX BLADE W/SCARIFIER

Construction yellow.

2,646.00

## **BB3284 BOX BLADE W/SCARIFIER**

Continued

THIS	S PA	AGF.	INTFI	NTIC	DNALLY	I FFT	BLANK	(
1 1 11		<b>'</b> O'						•

Landscaping

#### **BB3296 BOX BLADE W/SCARIFIER**

**Equipment for Base Machine** 

Tailgate: Hinged Tailgate Grading and Leveling: Fine, Precision Grading and Leveling Tractor Compatibility: Balanced Design Beam Type: Tubular Scarifier Beam Scarifier Shanks: Notched 3 Position Points: Heat Treated Points Box Design: High Capacity Box, No Gussets or Obstructions Hydraulic Opening: NA Hydraulic Kit: NA Capacity (Cubic Foot): 28 Cubic Foot Tractor HP: 80 HP Maximum Cutting Edges:
(2) 1/2 In. x 6 In. Reversible Scarifier Shanks: (9) Replaceable Beam Size: 4 In. x 4 In. x 3/8 In.

Beam Reinforcement: Yes End Plate Thickness: 1/2 In. Working Width: 96 In.
Height: 20 In.
Depth: 26-1/2 In.
Duty: Construction Grade
Hitch Type: Category I and Category II Quick Hitch Compatible Mast Design: Welded Assembly/Set-Up Time: 15 Minutes Operating Weight: 1010 lbs. Shipping Weight: 1050 lbs. Shipping per Crate: Packaged 1 Per Pallet Warranty: 1 Year Warranty Moldboard Thickness: 1/4 In. Manufacturer Model: New Paint Color: Construction Yellow

			List Price
	Attachment		Suggested
Code	Identifier	Description	USD (\$)

Select One Code From Each Required Category

#### **BASE MACHINE**

1083XF BB3296 BOX BLADE W/SCARIFIER

Construction yellow.

2,927.00

## **BB3296 BOX BLADE W/SCARIFIER**

Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Landscaping

## **BB5060 Standard Duty Box Blade**

**Equipment for Base Machine** 

3-Point Hitch:
 Category I
iMatch Compatible: Yes
Working Width: 61.5 In.
Tractor HP: 56 PTO HP max;
 see compatibility charts for
 specific model of tractors
Tailgate: Fixed
Shipping Weight:
 894 lbs. - (Pair)
Shanks: (5) Replaceable
Shank Type:
 3-Position with Holes and 1/2 In. Pin
Scarifier Points:
 Hardened Steel
End Plate Thickness: 3/8 In.

Moldboard Thickness: 3/16 In.
Moldboard Type: Formed Back
Mast: Welded
Duty: Standard Duty
Cutting Edges:
(2) 3/8 In. x 6 In. Reversible
Assembly/Set-Up Time:
15 Minutes (Approximate) - Per Pair
Approximate Operating Weight: 418 lbs.
Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
1641XF		BASE MACHINE  BB5060 Standard Duty Box Blade	1,004.00
10-171		Order in multiples of two.	1,004.00

## BB5060 Standard Duty Box Blade Continued

THIS PAGE INTENTIONALLY LEFT BLANK

03 December	2018	US &	Canada

Landscaping

## **BB5072 Standard Duty Box Blade**

**Equipment for Base Machine** 

3-Point Hitch:
 Category I
iMatch Compatible: Yes
Working Width: 73.5 In.
Tractor HP: 56 PTO HP max;
 see compatibility charts for
 specific model of tractors
Tailgate: Fixed
Shipping Weight:
 1,006 lbs. - (Pair)
Shanks: (6) Replaceable
Shank Type:
 3-Position with Holes and 1/2 In. Pin
Scarifier Points:
 Hardened Steel
End Plate Thickness: 3/8 In.

Moldboard Thickness: 3/16 In.
Moldboard Type: Formed Back
Mast: Welded
Duty: Standard Duty
Cutting Edges:
 (2) 3/8 In. x 6 In. Reversible
Assembly/Set-Up Time:
 15 Minutes (Approximate) - Per Pair
Approximate Operating Weight: 474 lbs.
Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	]
1642XF		BASE MACHINE  BB5072 Standard Duty Box Blade  Order in multiples of two.	1,161.00

## BB5072 Standard Duty Box Blade Continued

THIS	S PA	AGF.	INTFI	NTIC	DNALLY	I FFT	BLANK	(
1 1 11		<b>'</b> O'						•

Landscaping

## **BB5084 Standard Duty Box Blade**

**Equipment for Base Machine** 

3-Point Hitch:
 Category I
iMatch Compatible: Yes
Working Width: 88.5 In.
Tractor HP: 56 PTO HP max;
 see compatibility charts for
 specific model of tractors
Tailgate: Fixed
Shipping Weight:
 1,078 lbs. - (Pair)
Shanks: (6) Replaceable
Shank Type:
 3-Position with Holes and 1/2 In. Pin
Scarifier Points:
 Hardened Steel
End Plate Thickness: 3/8 In.

Moldboard Thickness: 3/16 In.
Moldboard Type: Formed Back
Mast: Welded
Duty: Standard Duty
Cutting Edges:
(2) 3/8 In. x 6 In. Reversible
Assembly/Set-Up Time:
15 Minutes (Approximate) - Per Pair
Approximate Operating Weight: 510 lbs.
Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
1643XF		BASE MACHINE BB5084 Standard Duty Box Blade Order in multiples of two.	1,327.00

## BB5084 Standard Duty Box Blade Continued

ΤI	ΗІ	S	PA	GE	INT	ΈN	JTI(	ANC	LLY I	LEFT	BLA	١N٨	Κ

Landscaping

## **BB5096 Standard Duty Box Blade**

**Equipment for Base Machine** 

3-Point Hitch:
 Category I
iMatch Compatible: Yes
Working Width: 97.5 In.
Tractor HP: 56 PTO HP max;
 see compatibility charts for
 specific model of tractors
Tailgate: Fixed
Shipping Weight:
 1,262 lbs. - (Pair)
Shanks: (7) Replaceable
Shank Type:
 3-Position with Holes and 1/2 In. Pin
Scarifier Points:
 Hardened Steel
End Plate Thickness: 3/8 In.

Moldboard Thickness: 3/16 In.
Moldboard Type: Formed Back
Mast: Welded
Duty: Standard Duty
Cutting Edges:
(2) 3/8 In. x 6 In. Reversible
Assembly/Set-Up Time:
15 Minutes (Approximate) - Per Pair
Approximate Operating Weight: 602 lbs.
Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
1644XF		BASE MACHINE  BB5096 Standard Duty Box Blade  Order in multiples of two.	1,485.00

## BB5096 Standard Duty Box Blade Continued

THIS PAGE INTENTIONALLY LEFT BLANK

03 December	2018	US &	Canada

Landscaping

### BB5048L Limited Category 1 Economy Duty Box Blade

**Equipment for Base Machine** 

3-Point Hitch:
Limited Category I
iMatch Compatible: Yes
Working Width: 50 In.
Tractor HP: 18 PTO HP max;
see compatibility charts for
specific model of tractors
Tailgate: Fixed
Shipping Weight:
778 lbs. - (Pair)
Shanks: (5) Replaceable
Shank Type:
3-Position with Holes and 1/2 In. Pin
Scarifier Points:
Hardened Steel
End Plate Thickness: 5/16 In.

Moldboard Thickness: 3/16 In.
Moldboard Type: Formed Back
Mast: Bolt On
Duty: Economy Duty
Cutting Edges:
(2) 3/8 In. x 6 In. Reversible
Assembly/Set-Up Time:
15 Minutes (Approximate) - Per Pair
Approximate Operating Weight: 360 lbs.
Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
	12011110	2000-ipinon	332 ( <del>4)</del>
		Select One Code From Each Required Category	
		BASE MACHINE	
1741XF		BB5048L Limited Category 1 Economy Duty Box Blade Order in multiples of two.	850.00

## BB5048L Limited Category 1 Economy Duty Box Blade Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Landscaping

#### BB5060L Limited Category 1 Economy Duty Box Blade

**Equipment for Base Machine** 

3-Point Hitch:
 Limited Category I
iMatch Compatible: Yes
Working Width: 62 In.
Tractor HP: 18 PTO HP max;
 see compatibility charts for
 specific model of tractors
Tailgate: Fixed
Shipping Weight:
 868 lbs. - (Pair)
Shanks: (5) Replaceable
Shank Type:
 3-Position with Holes and 1/2 In. Pin
Scarifier Points:
 Hardened Steel
End Plate Thickness: 5/16 In.

Moldboard Thickness: 3/16 In.
Moldboard Type: Formed Back
Mast: Bolt On
Duty: Economy Duty
Cutting Edges:
(2) 3/8 In. x 6 In. Reversible
Assembly/Set-Up Time:
15 Minutes (Approximate) - Per Pair
Approximate Operating Weight: 405 lbs.
Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	

1742XF

BB5060L Limited Category 1 Economy Duty Box Blade *Order in multiples of two*.

936.00

## BB5060L Limited Category 1 Economy Duty Box Blade Continued

THIS	S PA	AGF.	INTFI	NTIC	DNALLY	I FFT	BLANK	(
1 1 11		<b>'</b> O'						•

Landscaping

## LL1160 - 5 Ft. Drawn Box Scraper

**Equipment for Base Machine** 

Working Width: 60 In.
Machine Width: 61 In.
Machine Length: 98 In.
Machine Height: 29.5 In.
Approximate Operating Weight: 612 lbs.
Tractor HP (Maximum): 20 to 50 HP
Tailgate: Fixed
Shanks: 6 (Replaceable)
End Plate Thickness: 3/8 In.
Single Hydraulic Cylinder:
3 In. Bore x 8 In. Stroke
Tires (2): Pneumatic
Wheels (2):
6 In. Wide x 10 In. Diameter

Cutting Edge:
5/8 In. Thick x 6 In. Tall
Safety Chains: Yes - Required
Color: Construction Yellow
Assembly/Set-Up Time:
15 Minutes (Approximate)
Duty: Standard Duty
Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
1471XF		BASE MACHINE LL1160 - 5 Ft. Drawn Box Scraper	4,482.00

## LL1160 - 5 Ft. Drawn Box Scraper Continued

## THIS PAGE INTENTIONALLY LEFT BLANK

### Landscaping

#### LL1172 - 6 Ft. Drawn Box Scraper

**Equipment for Base Machine** 

Working Width: 72 In.
Machine Width: 73 In.
Machine Length: 98 In.
Machine Height: 29.5 In.
Approximate Operating Weight: 735 lbs.
Tractor HP (Maximum): 20 to 50 HP
Tailgate: Fixed
Shanks: 6 (Replaceable)
End Plate Thickness: 3/8 In.
Single Hydraulic Cylinder:
3 In. Bore x 8 In. Stroke
Tires (2): Pneumatic
Wheels (2):
6 In. Wide x 10 In. Diameter

Cutting Edge:
5/8 In. Thick x 6 In. Tall
Safety Chains: Yes - Required
Color: Construction Yellow
Assembly/Set-Up Time:
15 Minutes (Approximate)
Duty: Standard Duty
Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	

#### **BASE MACHINE**

1472XF LL1172 - 6 Ft. Drawn Box Scraper 4,687.00

## LL1172 - 6 Ft. Drawn Box Scraper Continued

THIS	S PA	AGF.	INTFI	NTIC	DNALLY	I FFT	BLANK	(
1 1 11		<b>'</b> O'						•

### Landscaping

#### LL1208 - 8 Ft. Drawn Box Scraper

**Equipment for Base Machine** 

Working Width: 96 In.
Machine Width: 96.3 In.
Machine Length: 144 In.
Machine Height: 36 In.
Approximate Operating Weight: 1500 lbs.
Tractor HP (Maximum): 35 to 100 HP
Tailgate: Fixed
Lift Axle: Standard Lift Rockshaft
End Plate Thickness: 3/8 In.
Hydraulic Lift Cylinder:
3 In. Bore x 8 In. Stroke
Tires (2): Pneumatic -9.5L15 Implement Tires
Wheels (2):
8 In. Wide x 15 In. Diameter

Cutting Edge:
5/8 In. Thick x 6 In. Tall
Safety Chains: Yes - Required
Color: Construction Yellow
Assembly/Set-Up Time:
60 Minutes (Approximate)
Duty: Standard Duty
Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	]
		BASE MACHINE	
1541XF		LL1208 - 8 Ft. Drawn Box Scraper Hydraulic tilt axle, 9.5L-15 wheels and tires, lift cylinder, hydraulic hoses, and SCV connectors are in base equipment.	7,508.00
		AXLE OPTION	
1060		Tilt Axle with Cylinder	No Added Cost
1065		Less Tilt Axle with Cylinder	-945.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5DDA00100	Miscellaneous 9.5L-15 Tires on 6-Bolt Rims (2)	947.79
	5DDA00096	LL12 Series - Lift Cylinder Kit	685.11
	5DDA00098	LL12 Series - Tilt Cylinder Kit	716.53
	5DDA00097	LL12 Series - Turnbuckle	230.90
	5DDA00094	Tilt Axle with Cylinder (LL1208 and LL1210)	1,754.02

## LL1208 - 8 Ft. Drawn Box Scraper Continued

## THIS PAGE INTENTIONALLY LEFT BLANK

### Landscaping

#### LL1210 - 10 Ft. Drawn Box Scraper

**Equipment for Base Machine** 

Working Width: 120 In.
Machine Width: 120.3 In.
Machine Length: 144 In.
Machine Height: 36 In.
Approximate Operating Weight: 1600 lbs.
Tractor HP (Maximum): 35 to 125 HP
Tailgate: Fixed
Lift Axle: Standard Lift Rockshaft
End Plate Thickness: 3/8 In.
Hydraulic Lift Cylinder:
3 In. Bore x 8 In. Stroke
Tires (2): Pneumatic -9.5L15 Implement Tires
Wheels (2):
8 In. Wide x 15 In. Diameter

Cutting Edge:
5/8 In. Thick x 6 In. Tall
Safety Chains: Yes - Required
Color: Construction Yellow
Assembly/Set-Up Time:
60 Minutes (Approximate)
Duty: Standard Duty
Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1542XF		LL1210 - 10 Ft. Drawn Box Scraper Hydraulic tilt axle, 9.5L-15 wheels and tires, lift cylinder, hydraulic hoses, and SCV connectors are in base equipment.	8,034.00
		AXLE OPTION	
1060		Tilt Axle with Cylinder	No Added Cost
1065		Less Tilt Axle with Cylinder	-945.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5DDA00100	Miscellaneous 9.5L-15 Tires on 6-Bolt Rims (2)	947.79
	5DDA00096	LL12 Series - Lift Cylinder Kit	685.11
	5DDA00098	LL12 Series - Tilt Cylinder Kit	716.53
	5DDA00097	LL12 Series - Turnbuckle	230.90
	5DDA00094	Tilt Axle with Cylinder (LL1208 and LL1210)	1,754.02

## LL1210 - 10 Ft. Drawn Box Scraper Continued

THIS	S PA	AGF.	INTFI	NTIC	DNALLY	I FFT	BLANK	(
1 1 11		<b>'</b> O'						•

### Landscaping

#### LL1212 - 12 Ft. Drawn Box Scraper

**Equipment for Base Machine** 

Working Width: 144 In.
Machine Width: 143 In.
Machine Length: 144 In.
Machine Height: 36 In.
Approximate Operating Weight: 1700 lbs.
Tractor HP (Maximum): 35 to 125 HP
Tailgate: Fixed
Lift Axle: Standard Lift Rockshaft
End Plate Thickness: 3/8 In.
Hydraulic Lift Cylinder:
3 In. Bore x 8 In. Stroke
Tires (2): Pneumatic -9.5L15 Implement Tires
Wheels (2):
8 In. Wide x 15 In. Diameter

Cutting Edge:
5/8 In. Thick x 6 In. Tall
Safety Chains: Yes - Required
Color: Construction Yellow
Assembly/Set-Up Time:
60 Minutes (Approximate)
Duty: Standard Duty
Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1543XF		LL1212 - 12 Ft. Drawn Box Scraper Hydraulic tilt axle, 9.5L-15 wheels and tires, lift cylinder, hydraulic hoses, and SCV connectors are in base equipment.	8,226.00
		AXLE OPTION	
1060		Tilt Axle with Cylinder	No Added Cost
1065		Less Tilt Axle with Cylinder	-973.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5DDA00100	Miscellaneous 9.5L-15 Tires on 6-Bolt Rims (2)	947.79
	5DDA00096	LL12 Series - Lift Cylinder Kit	685.11
	5DDA00098	LL12 Series - Tilt Cylinder Kit	716.53
	5DDA00098 5DDA00097	LL12 Series - Tilt Cylinder Kit  LL12 Series - Turnbuckle	716.53 230.90

## LL1212 - 12 Ft. Drawn Box Scraper Continued

ΤI	ΗІ	S	PA	GE	INT	ΈN	JTI(	ANC	LLY I	LEFT	BLA	١N٨	Κ

### Landscaping

## LL1372 - 6 Ft. Drawn Box Scraper

**Equipment for Base Machine** 

Working Width: 72 In.
Machine Width: 74 In.
Machine Length: 165 In.
Machine Height: 49 In.
Approximate Operating Weight: 1600 lbs.
Tractor HP (Maximum): 35 to 100
Tailgate: Fixed
End Plate Thickness: 1/2 In.
Dual Hydraulic Cylinders: 3 In. Bore x
8 In. Stroke (1 Rear SCV Required)
Tires (4): Pneumatic
Wheels (4):
6 In. Wide x 10 In. Diameter

6 In. Wide x 10 In. Diameter Cutting Edge: 5/8 In. Thick x 6 In. Tall

Safety Chains: Yes - Required Color: Construction Yellow Assembly/Set-Up Time:
30 Minutes (Approximate)
Shipping Configuration: 2 Pieces (Box Blade and Tongue) Duty: Medium Duty

Warranty: 6 Months

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1481XF		LL1372 - 6 Ft. Drawn Box Scraper	8,621.00
		SCARIFIER BAR	
1000		Scarifier Bar Attachment	2,468.00
1095		Less Scarifier Bar Attachment	In Base Price
		REAR SMOOTH ROLLER	
2000		Rear Smooth 12 In. Drum Roller Attachment	2,962.00
2095		Less Rear Smooth Roller	In Base Price
		ATTACHMENTS - ORDER AS DESIRED	
9000		Rear Hitch Assembly	246.00
9030		Double Rear 12 In. Diameter Basket Roller	2,963.00
9040		3 Bar Spring Tine Harrow	2,346.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5DDA00020	Miscellaneous 3 Bar Spring Tine Harrow - 6 Ft.	2,533.85
	5DDA00017	Double Rear 12 In. Diameter Basket Roller Pulverizer - 6 Ft.	3,199.93
	5DDA00007	Rear Hitch Assembly (LL13 Series)	265.68
	5DDA00023	Rear Smooth 12 In. Drum Roller Attachment - 6 Ft.	3,412.32
	5DDA00029	Scarifier Bar Attachment - 6 Ft.	2,843.60

## LL1372 - 6 Ft. Drawn Box Scraper

Continued

### Landscaping

## LL1384 - 7 Ft. Drawn Box Scraper

**Equipment for Base Machine** 

Working Width: 84 In.
Machine Width: 86 In.
Machine Length: 165 In.
Machine Height: 49 In.
Approximate Operating Weight: 1866 lbs.
Tractor HP (Maximum): 35 to 125 HP
Tailgate: Fixed
End Plate Thickness: 1/2 In.
Dual Hydraulic Cylinders: 3 In. Bore x
8 In. Stroke (1 Rear SCV Required)
Tires (4): Pneumatic
Wheels (4):
6 In. Wide x 10 In. Diameter

6 In. Wide x 10 In. Diameter Cutting Edge: 5/8 In. Thick x 6 In. Tall

Safety Chains: Yes - Required Color: Construction Yellow Assembly/Set-Up Time:
30 Minutes (Approximate)
Shipping Configuration: 2 Pieces (Box Blade and Tongue) Duty: Medium Duty

Warranty: 6 Months

Code	Attachment Identifier	Description	List Price Suggested USD (\$)	
		Select One Code From Each Required Category		
		BASE MACHINE		
1482XF		LL1384 - 7 Ft. Drawn Box Scraper	8,755.00	
		SCARIFIER BAR		
1000		Scarifier Bar Attachment	2,468.00	
1095		Less Scarifier Bar Attachment	In Base Price	
		REAR SMOOTH ROLLER		
2000		Rear Smooth 12 In. Drum Roller Attachment	3,129.00	
2095		Less Rear Smooth Roller	In Base Price	
		ATTACHMENTS - ORDER AS DESIRED		
9000		Rear Hitch Assembly	246.00	
9030		Double Rear 12 In. Diameter Basket Roller	3,126.00	
9040		3 Bar Spring Tine Harrow	2,549.00	
		ATTACHMENTS FOR FIELD CONVERSION		
	5DDA00021	Miscellaneous 3 Bar Spring Tine Harrow - 7 Ft.	2,753.34	
	5DDA00018	Double Rear 12 In. Diameter Basket Roller Pulverizer - 7 Ft.	3,376.58	
	5DDA00007	Rear Hitch Assembly (LL13 Series)	265.68	
	5DDA00024	Rear Smooth 12 In. Drum Roller Attachment - 7 Ft.	3,604.27	
	5DDA00029	Scarifier Bar Attachment - 6 Ft.	2,843.60	

## LL1384 - 7 Ft. Drawn Box Scraper Continued

Bid Term: 2/20/19 - 2/19/21

### Landscaping

## LL1396 - 8 Ft. Drawn Box Scraper

**Equipment for Base Machine** 

Working Width: 96 In.
Machine Width: 98 In.
Machine Length: 165 In.
Machine Height: 49 In.
Approximate Operating Weight: 2133 lbs.
Tractor HP (Maximum): 35 to 125 HP
Tailgate: Fixed
End Plate Thickness: 1/2 In.
Dual Hydraulic Cylinders: 3 In. Bore x
8 In. Stroke (1 Rear SCV Required)
Tires (4): Pneumatic
Wheels (4):
6 In. Wide x 10 In. Diameter

6 In. Wide x 10 In. Diameter Cutting Edge: 5/8 In. Thick x 6 In. Tall

Safety Chains: Yes - Required Color: Construction Yellow Assembly/Set-Up Time:
30 Minutes (Approximate)
Shipping Configuration: 2 Pieces (Box Blade and Tongue) Duty: Medium Duty Warranty: 6 Months

Code	Attachment Identifier	Description	List Price Suggested USD (\$)	
		Select One Code From Each Required Category		
		BASE MACHINE		
1483XF		LL1396 - 8 Ft. Drawn Box Scraper	9,130.00	
		SCARIFIER BAR		
1000		Scarifier Bar Attachment	2,387.00	
1095		Less Scarifier Bar Attachment	In Base Price	
		REAR SMOOTH ROLLER		
2000		Rear Smooth 12 In. Drum Roller Attachment	3,374.00	
2095		Less Rear Smooth Roller	In Base Price	
		ATTACHMENTS - ORDER AS DESIRED		
9000		Rear Hitch Assembly	246.00	
9030		Double Rear 12 In. Diameter Basket Roller	3,293.00	
9040		3 Bar Spring Tine Harrow	2,741.00	
		ATTACHMENTS FOR FIELD CONVERSION		
	5DDA00022	Miscellaneous 3 Bar Spring Tine Harrow - 8 Ft.	2,959.95	
	5DDA00019	Double Rear 12 In. Diameter Basket Roller Pulverizer - 8 Ft.	3,556.28	
	5DDA00007	Rear Hitch Assembly (LL13 Series)	265.68	
	5DDA00025	Rear Smooth 12 In. Drum Roller Attachment - 8 Ft.	3,887.28	
	5DDA00028	Scarifier Bar Attachment - 8 Ft.	2,749.54	

## LL1396 - 8 Ft. Drawn Box Scraper Continued

### Landscaping

## CA2048E - 4 Ft. Economy Core Aerator

**Equipment for Base Machine** 

Reduces Hard Layer Compaction and Increases Turf Vitality
3/8 In. Formed Category I "A" Frame
2 Bronze Bushings per Rotor for
Wear Resistance on Shaft
3-Point Hitch: Category I
Working Width: 48 In.
Tractor HP: 20 to 50 HP
Spoons:
(48) 3/4 In. Case Hardened Steel
Spoon Penetration: 4-1/2 In.
Spoons Per Hub: 6
Approximate Shipping Weight: 400 lbs.

Overall Width: 54 In.
iMatch Compatible (Quick-Attach System)
Assembly/Set-Up Time:
10 Minutes (Approximate)
Approximate Operating Weight: 284 lbs.
1 Year Warranty

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1141XF		CA2048E - 4 Ft. Economy Core Aerator Order optional weight tanks as attachments.	2,430.00
		STEEL WEIGHT TANK	
9000		Steel Weight Tank (Each order is a quantity of 2 tanks, 2 tanks required per Machine) For sand only. (CA2048E)	609.00
		OPERATOR'S MANUAL AND DECALS	
9200		French Operator's Manual and Decal Kit	No Charge
		ATTACHMENTS FOR FIELD CONVERSION	
	5BP950958B	Miscellaneous French Manual Decal (CA20 Series)	0.02
	5BP0099731	Steel Weight Tank CA2048E, Quantity 1 (2 Required Per Machine) For sand only.	338.20

## CA2048E - 4 Ft. Economy Core Aerator Continued

TΙ	ΗІ	S	PA	GE	INT	ΕN	TIC	DNALL	Y LEF	ТΒІ	LAN	K

#### Landscaping

#### CA2060 - 5 Ft. Standard Duty Core Aerator

**Equipment for Base Machine** 

Reduces Hard Layer Compaction and Increases Turf Vitality
3/8 In. Formed Category I "A" Frame
- Can Hold (2) 170 lb. Sand
Containers - OPTIONAL
2 Bronze Bushings per Rotor for
Wear Resistance on Shaft
3-Point Hitch: Category I and Category II
Working Width: 60 In.
Weight Tray: (2) 19 In. x 21 In.
Tractor HP: 25 to 70 HP
Spoons:
(80) 3/4 In. Case Hardened Steel
Spoon Penetration: 4-1/2 In.

Spoons Per Hub: 8
iMatch Compatible (Quick-Attach System)
Shipping Weight: 500 lbs.
Overall Width: 65 In.
Assembly/Set-Up Time:
10 Minutes (Approximate)
1 Year Warranty

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1131XF		CA2060 - 5 Ft. Standard Duty Core Aerator Order optional weight tanks as attachments.	3,262.00
		STEEL WEIGHT TANK	
9000		Steel Weight Tank (Each order is a quantity of 2 tanks, 2 tanks required per Machine) For sand only. (CA2060)	720.00
		OPERATOR'S MANUAL AND DECALS	
9200		French Operator's Manual and Decal Kit	No Charge
		ATTACHMENTS FOR FIELD CONVERSION	
	5BP950958B	Miscellaneous French Manual Decal (CA20 Series)	0.02
	5BP0099734	Steel Weight Tank CA2060, Quantity 1 (2 Required Per Machine) For sand only.	409.20

## CA2060 - 5 Ft. Standard Duty Core Aerator Continued

THIS PAGE INTENTIONALLY LEFT BLANK

#### Landscaping

#### CA2060E - 5 Ft. Economy Core Aerator

**Equipment for Base Machine** 

Reduces Hard Layer Compaction and Increases Turf Vitality
3/8 In. Formed Category I "A" Frame
- Can Hold (2) 125 lb. Sand
Containers - OPTIONAL
2 Bronze Bushings per Rotor for
Wear Resistance on Shaft
3-Point Hitch: Category I
Working Width: 60 In.
Weight Tray: (2) 19 In. x 15 In.
Tractor HP: 20 to 50 HP
Spoons:
(60) 3/4 In. Case Hardened Steel
Spoon Penetration: 4-1/2 In.

Spoons Per Hub: 6
iMatch Compatible (Quick-Attach System)
Approximate Shipping Weight: 400 lbs.
Overall Width: 65 In.
Assembly/Set-Up Time:
10 Minutes (Approximate)
Approximate Operating Weight: 357 lbs.
1 Year Warranty

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1142XF		CA2060E - 5 Ft. Economy Core Aerator Order optional weight tanks as attachments.	2,594.00
		STEEL WEIGHT TANK	
9000		Steel Weight Tank (Each order is a quantity of 2 tanks, 2 tanks required per Machine) For sand only. (CA2060E)	641.00
		OPERATOR'S MANUAL AND DECALS	
9200		French Operator's Manual and Decal Kit	No Charge
		ATTACHMENTS FOR FIELD CONVERSION	
	5BP950958B	Miscellaneous French Manual Decal (CA20 Series)	0.02
	5BP0099732	Steel Weight Tank CA2060E, Quantity 1 (2 Required Per Machine) For sand only.	360.62

## CA2060E - 5 Ft. Economy Core Aerator Continued

ΤI	ΗІ	S	PA	GE	INT	ΈN	JTI(	ANC	LLY I	LEFT	BLA	١N٨	Κ

Landscaping

### CA2072 - 6 Ft. Standard Duty Core Aerator

**Equipment for Base Machine** 

Reduces Hard Layer Compaction and Increases Turf Vitality
3/8 In. Formed Category I "A" Frame
- Can Hold (2) 220 lb.
Sand Containers - OPTIONAL
2 Bronze Bushings per Rotor for
Wear Resistance on Shaft
3-Point Hitch:
Category I and Category II
Working Width: 72 In.
Weight Tray: (2) 25 In. x 21 In.
Tractor HP: 25 to 70 HP
Spoons:
(96) 3/4 In. Case Hardened Steel
Spoon Penetration: 4-1/2 In.

Spoons Per Hub: 8 Shipping Weight: 600 lbs. Overall Width: 78 In. iMatch Compatible (Quick-Attach System) Assembly/Set-Up Time: 10 Minutes (Approximate) Approximate Operating Weight: 549 lbs. 1 Year Warranty

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1132XF		CA2072 - 6 Ft. Standard Duty Core Aerator Order optional weight tanks as attachments.	3,648.00
		STEEL WEIGHT TANK	
9000		Steel Weight Tank (Each order is a quantity of 2 tanks, 2 tanks required per Machine) For sand only. (CA2072)	775.00
		OPERATOR'S MANUAL AND DECALS	
9200		French Operator's Manual and Decal Kit	No Charge
		ATTACHMENTS FOR FIELD CONVERSION	
	5BP950958B	Miscellaneous French Manual Decal (CA20 Series)	0.02
	5BP0099735	Steel Weight Tank CA2072, Quantity 1 (2 Required Per Machine) For sand only.	584.84

## CA2072 - 6 Ft. Standard Duty Core Aerator Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Landscaping

#### CA2072E - 6 Ft. Economy Core Aerator

**Equipment for Base Machine** 

Reduces Hard Layer Compaction and Increases Turf Vitality
3/8 In. Formed Category I "A" Frame
- Can Hold (2) 160 lb. Sand
Containers - OPTIONAL
2 Bronze Bushings per Rotor for
Wear Resistance on Shaft
3-Point Hitch: Category I
Working Width: 72 In.
Weight Tray: (2) 25 In. x 15 In.
Tractor HP: 20 to 50 HP
Spoons:
(72) 3/4 In. Case Hardened Steel
Spoon Penetration: 4-1/2 In.

Spoons Per Hub: 6
iMatch Compatible (Quick-Attach System)
Approximate Shipping Weight: 450 lbs.
Overall Width: 78 In.
Assembly/Set-Up Time:
10 Minutes (Approximate)
Approximate Operating Weight: 401 lbs.
1 Year Warranty

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	]
		BASE MACHINE	
1143XF		CA2072E - 6 Ft. Economy Core Aerator Order optional weight tanks as attachments.	2,837.00
		STEEL WEIGHT TANK	
9000		Steel Weight Tank (Each order is a quantity of 2 tanks, 2 tanks required per Machine) For sand only. (CA2072E)	682.00
		OPERATOR'S MANUAL AND DECALS	
9200		French Operator's Manual and Decal Kit	No Charge
		ATTACHMENTS FOR FIELD CONVERSION	
	5BP950958B	Miscellaneous French Manual Decal (CA20 Series)	0.02
	5BP0099733	Steel Weight Tank CA2072E, Quantity 1 (2 Required Per Machine) For sand only.	379.31

## CA2072E - 6 Ft. Economy Core Aerator Continued

ΤI	ΗІ	S	PA	GE	INT	ΈN	JTI(	ANC	LLY I	LEFT	BLA	١N٨	Κ

#### **PC1001 Integral One Row Cultivator**

Equipment for Base Machine

Hitch:
Lift-type, Category I,
iMatch Compatible
Working Row Width:
30 to 60 In. (762 to 1524 mm)
Transport Length:
37 In. (939.8 mm)
Transport Width:
50.5 In. (1,282.7 mm)
Transport Height:
36 In. (914.4 mm)
Tractor Engine HP Range:

25 - 45 HP Standard Tines: 6 Curved and Reversible Tines, 1.75 In. (44.45 mm) x 10 In. (254 mm) Tine Spacing: Adjustable Parking Stand Included

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	]
		BASE MACHINE	
3441XF		PC1001 Integral One Row Cultivator Order in multiples of two.	465.00
		OPERATOR'S MANUAL AND DECALS	
904K		French OM & Decal Kit (PC10)	13.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5TITE511154	<b>Miscellaneous</b> French Kit - Includes Operator's Manual, Parts Catalog and Safety Decals <i>PC1001 and PC1072</i>	15.60

## PC1001 Integral One Row Cultivator Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Landscaping

#### PC1072 - 6 Ft. Integral Field Cultivator (13 S-tines)

**Equipment for Base Machine** 

Hitch:
Lift-type, Category I,
iMatch Compatible
Working Width:
72 In. (1,828.8 mm)
Transport Length:
37.5 In. (952.5 mm)
Transport Width:
73.25 In. ( 1,860.6 mm)
Transport Height:
39 In. (990.6 mm)
Tractor Engine HP Range:

25 - 45 HP Standard Tines: 13 Curved and Reversible Tines, 1.25 In. (31.75 mm) x 8 In. (203.2 mm) Tine Spacing: Adjustable

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
3442XF		PC1072 - 6 Ft. Integral Field Cultivator (13 S-tines)  Order in multiples of two.	917.00
		OPERATOR'S MANUAL AND DECALS	
904K		French OM & Decal Kit (PC10)	13.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5TITE511154	<b>Miscellaneous</b> French Kit - Includes Operator's Manual, Parts Catalog and Safety Decals <i>PC1001 and PC1072</i>	15.60

## PC1072 - 6 Ft. Integral Field Cultivator (13 S-tines) Continued

THIS PAGE INTENTIONALLY LEFT BLANK

### Landscaping

#### BL1130 - 3 Pt. Mount Debris Blower - U.S.

**Equipment for Base Machine** 

Function: Debris Blower Function: Debris Blower
Length: 47 1/8 In. (1,197 mm)
Width: 50 In. (1,270 mm)
Height: 48 3/4 In. (1,238.3 mm)
Operating Weight: 689 lb. (312.5 kg)
Fan Diameter: 29 1/2 In. (749.3 mm)
Fan Width: 10 in. (254 mm)
Number of Fan Blades: 12
Fan Speed: 1455 RPM
Air Flow: 6,061 cfm (171 cu. meter per minute)
Air Velocity: 141 mph (227 kph)

Air Velocity: 141 mph (227 kph) Air Velocity: 12,400 fpm (3,779.5 mpm)

Outlet Size: 10 5/8 x 6 5/8 In. (269.9 x 168.3 mm) Air Direction: left or right by moving lever Cat. 1 & 2, iMatch and Quick Hitch Compatible Pneumatic gauge wheel standard Approximate Set-Up Time: 30 Minutes

			List Price
	Attachment		Suggested
Code	Identifier	Description	USD (\$)

Select One Code From Each Required Category

#### **BASE MACHINE**

1571XF BL1130 - 3 Pt. Mount Debris Blower - U.S. 5,576.00

### BL1130 - 3 Pt. Mount Debris Blower - U.S. Continued

THIS PAGE INTENTIONALLY LEFT BLANK

03 December	2018	US &	Canada

**List Price** 

#### FRONTIER PRODUCTS

#### Landscaping

#### BL2130 - Hydraulic Loader Mount Debris Blower with HP2025 Hydraulic Power Unit -U.S.

#### **Equipment for Base Machine**

Function: Debris Blower Length: 47 1/8 In. (1,197 mm) Width: 50 In. (1,270 mm)

Height: 48 3/4 In. (1,238.3 mm)

Operating Weight: 689 lb. (312.5 kg)

Fan Diameter: 29 1/2 In. (749.3 mm) Fan Width: 10 in. (254 mm) Number of Fan Blades: 12 Fan Speed: 1455 RPM Air Flow: 6,061 cfm (171 cu. meter per minute) Air Velocity: 141 mph (227 kph) Air Velocity: 12,400 fpm (3,779.5 mpm) Outlet Size: 10 5/8 x 6 5/8 In. (269.9 x 168.3 mm)

Air Direction: left or right by moving lever

Pneumatic gauge wheel standard Approximate Set-Up Time: 30 Minutes Function: Hydraulic Power Unit

Pressure: 2700 psi Flow: 16 gpm

Reservoir Capacity: 15 gal. System Capacity: 17 gal. System Features: Pressure relieve valve, filter, temperature and oil level gauge, and thermal protection switch Hoses, Tips, and Brackets included Tractor RPM: 540 RPM PTO Manufacturer: Comer Parking Stand: Standard Hitch Category: Category I Quick Hitch Compatibility: iMatch Compatible Approximate Set-Up Time: 120 Minutes

Code	Attachment Identifier	Description	Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1581XF		BL2130 - Hydraulic Loader Mount Debris Blower with HP2025 Hydraulic Power Unit - U.S. Must be used with HP2025 or HP2134 Hydraulic Power Pack Units.	12,195.00
		HYDRAULIC POWER UNITS	_
1000		HP2025 - Hydraulic Power Unit, 25 HP Requires wiring harness, 5RDF0039, when changing front implement attachments.	In Base Price
1010		HP2134 - Hydraulic Power Unit, 34 HP Requires wiring harness, 5RDF0039, when changing front implement attachments.	111.00
1095		Less HP2025 Hydraulic Power Unit	-6,856.00
		OIL COOLER	
2000		Oil Cooler for HP2025 and HP2134 Hydraulic Power Units Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.  Not available with option Code 1095.	In Base Price
2095		Less Oil Cooler	-1,751.00
		WIRING HARNESS	
9040		Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors Includes complete wiring harness from battery to switch in the console. Not available with option Code 1095.	97.00

#### ATTACHMENTS FOR FIELD CONVERSION

Landscaping

## BL2130 - Hydraulic Loader Mount Debris Blower with HP2025 Hydraulic Power Unit - U.S.

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		ATTACHMENTS FOR FIELD CONVERSIONContinued	
	5RDF0038	Miscellaneous Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors Includes complete wiring harness from battery to switch in the console.	102.14
	5RDF0036	Oil Cooler for HP2025 and HP2134 Hydraulic Power Units Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.	1,766.36
	5RDF0078	Wiring Harness for HP2025 and HP2134 Hydraulic Power Units to control Loader Mounted Attachment Includes complete wiring harness from switch in the console to 3 cavities connectors for front implements.	147.74

#### Landscaping

### LP1048L - 4 Ft. Limited Category 1 3-Point Land Plane

**Equipment for Base Machine** 

Working Width: 48 in.
Overall Dimensions: H 32 in. x W 53 in. x L 45 in.
Shipping Weight: 363 lbs.
End Plate Thickness: 3/16 in.
Hitch: Limited Category 1
Lower Lift Pin Height: 12 in.
Cutting Edges: (2) 3/8 in. x 6 in., Reversible,
Replaceable
Skid Shoes: Steel, welded, 3/8 in. thick, 2 in.
wide, 38 in. long

Assembly/Set-Up Time: 30 Minutes Operating Weight: 347 lbs. Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
2551XF		LP1048L - 4 Ft. Limited Category 1 3-Point Land Plane	1,082.00
		DESTINATION	
0202		United States	In Base Price
0184		Canada	No Added Cost
0205		Quebec, Canada	No Added Cost
		OPERATOR'S MANUAL AND DECALS	
0409		LP10L/ENGLISH OM	In Base Price
0413		LP10L/FRENCH OM/DECAL KIT Bundle Number: 5TL16333	No Added Cost
0437		LP10L/SPANISH OM/DECAL KIT Bundle Number: 5TL16334	No Added Cost
		ATTACHMENTS FOR FIELD CONVERSION	
	5TL16333	Miscellaneous LP10L/FRENCH OM/DECAL KIT	60.48
	5TL16334	LP10L/SPANISH OM/DECAL KIT	60.48

## LP1048L - 4 Ft. Limited Category 1 3-Point Land Plane Continued

THIS	S PA	AGF.	INTFI	NTIC	DNALLY	I FFT	BLANK	(
1 1 11		<b>'</b>						•

List Dalas

Bid Term: 2/20/19 - 2/19/21

#### FRONTIER PRODUCTS

#### Landscaping

### LP1060L - 5 Ft. Limited Category 1 3-Point Land Plane

**Equipment for Base Machine** 

Working Width: 60 in.
Overall Dimensions: H 32 in. x W 65 in. x L 45 in.
Shipping Weight: 392 lbs.
End Plate Thickness: 3/16 in.
Hitch: Limited Category 1
Lower Lift Pin Height: 12 in.
Cutting Edges: (2) 3/8 in. x 6 in., Reversible,
Replaceable
Skid Shoes: Steel, welded, 3/8 in. thick, 2 in.
wide, 38 in. long

Assembly/Set-Up Time: 30 Minutes Operating Weight: 376 lbs. Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
2561XF		LP1060L - 5 Ft. Limited Category 1 3-Point Land Plane	1,150.00
		DESTINATION	
0202		United States	In Base Price
0184		Canada	No Added Cost
0205		Quebec, Canada	No Added Cost
		OPERATOR'S MANUAL AND DECALS	
0409		LP10L/ENGLISH OM	In Base Price
0413		LP10L/FRENCH OM/DECAL KIT Bundle Number: 5TL16333	No Added Cost
0437		LP10L/SPANISH OM/DECAL KIT Bundle Number: 5TL16334	No Added Cost
		ATTACHMENTS FOR FIELD CONVERSION	
		AT TACISMENTO FOR FILED CONVERCION	
	5TL16333	Miscellaneous LP10L/FRENCH OM/DECAL KIT	60.48
	5TL16334	LP10L/SPANISH OM/DECAL KIT	60.48

## LP1060L - 5 Ft. Limited Category 1 3-Point Land Plane Continued

THIS	S PA	AGF.	INTFI	NTIC	DNALLY	I FFT	BLANK	(
1 1 11		<b>'</b>						•

### Landscaping

#### **LP1048 Standard Drawn Land Plane**

**Equipment for Base Machine** 

Working Width: 48 In.
Shipping Weight: 445 lbs.
End Plate Thickness: 3/16 In.
Duty: Light Duty
Cutting Edges: (2)
Assembly/Set-Up Time: 15 Minutes
Approximate Operating Weight: 365 lbs.

Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1441XF		LP1048 Standard Drawn Land Plane	1,469.00
		ATTACHMENTS FOR FIELD CONVERSION	

Miscellaneous

5TL15746 French Kit - Includes Operator's Manual and Safety Decals 49.28

### LP1048 Standard Drawn Land Plane Continued

THIS PAGE INTENTIONALLY LEFT BLANK

03 December 2018 US & Canada

Landscaping

#### **LP1060 Standard Drawn Land Plane**

**Equipment for Base Machine** 

Working Width: 60 In.
Shipping Weight: 495 lbs.
End Plate Thickness: 3/16 In.
Duty: Light Duty
Cutting Edges: (2)
Assembly/Set-Up Time: 15 Minutes
Approximate Operating Weight: 415 lbs.

Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	_
1442XF		LP1060 Standard Drawn Land Plane	1,438.00
		ATTACHMENTS FOR FIELD CONVERSION	

Miscellaneous

5TL15746 French Kit - Includes Operator's Manual and Safety Decals 49.28

## LP1060 Standard Drawn Land Plane Continued

THIS PAGE INTENTIONALLY LEFT BLANK

03	December	2018	US 8	& Canada	

Landscaping

#### LP1160 - 5 Ft. 3-Point Land Plane

**Equipment for Base Machine** 

3-Point Hitch: Category I

iMatch Compatible (Quick-Attach System)
Working Width: 60 In.
Tractor HP Recommendation: 18 to 50 HP

1451XF

Skid Shoes: Weld on, 3/16 In. Shipping Weight: 573 lbs. End Plate Thickness: 3/16 In. Duty: Standard Duty Cutting Edges: (2) Reversible

Assembly/Set-Up Time: 10 Minutes Approximate Operating Weight: 520 lbs. Warranty: 1 Year

Code	Attachment Identifier	Description	Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	

### ATTACHMENTS FOR FIELD CONVERSION

Miscellaneous

5TL15746 French Kit - Includes Operator's Manual and Safety Decals

LP1160 - 5 Ft. 3-Point Land Plane

49.28

1,471.00

List Balas

#### LP1160 - 5 Ft. 3-Point Land Plane Continued

ΤI	ΗІ	S	PA	GE	INT	ΈN	JTI(	ANC	LLY I	LEFT	BLA	١N٨	Κ

#### LP1172 - 6 Ft. 3-Point Land Plane

**Equipment for Base Machine** 

3-Point Hitch: Category I

iMatch Compatible (Quick-Attach System)
Working Width: 72 In.
Tractor HP Recommendation: 18 to 50 HP

Skid Shoes: Weld on, 3/16 In. Shipping Weight: 628 lbs.
End Plate Thickness: 3/16 In. Duty: Standard Duty
Cutting Edges: (2) Reversible

Assembly/Set-Up Time: 10 Minutes

Approximate Operating Weight: 548 lbs. Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
 1452XF		BASE MACHINE  LP1172 - 6 Ft. 3-Point Land Plane	1,569.00

#### ATTACHMENTS FOR FIELD CONVERSION

Miscellaneous

5TL15746 French Kit - Includes Operator's Manual and Safety Decals 49.28

#### LP1172 - 6 Ft. 3-Point Land Plane Continued

ΤI	ΗІ	S	PA	GE	INT	ΈN	JTI(	ANC	LLY I	LEFT	BLA	١N٨	Κ

### LP1184 - 7 Ft. 3-Point Land Plane

**Equipment for Base Machine** 

3-Point Hitch: Category I and II iMatch Compatible (Quick-Attach System) Working Width: 84 In. Tractor HP Recommendation: 22 to 75 HP

Skid Shoes: Weld on, 3/16 In. Shipping Weight: 684 lbs. End Plate Thickness: 3/16 In. Duty: Standard Duty Cutting Edges: (2) Reversible

Assembly/Set-Up Time: 10 Minutes Approximate Operating Weight: 604 lbs. Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
1453XF		BASE MACHINE  LP1184 - 7 Ft. 3-Point Land Plane	1,724.00

#### ATTACHMENTS FOR FIELD CONVERSION

Miscellaneous

5TL15746 French Kit - Includes Operator's Manual and Safety Decals 49.28

#### LP1184 - 7 Ft. 3-Point Land Plane Continued

TΙ	ΗІ	S	PA	GE	INT	ΕN	TIC	DNALL	Y LEF	ТΒІ	LAN	K

#### Landscaping

#### LP1196 - 8 Ft. 3-Point Land Plane

**Equipment for Base Machine** 

3-Point Hitch: Category I and II iMatch Compatible (Quick-Attach System) Working Width: 96 In. Tractor HP Recommendation: 22 to 75 HP Skid Shoes: Weld on, 3/16 In. Shipping Weight: 732 lbs. End Plate Thickness: 3/16 In. Duty: Standard Duty Cutting Edges: (2) Reversible Assembly/Set-Up Time:

Unit Arrives Fully Assembled Approximate Operating Weight: 652 lbs. Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1454XF		I P1196 - 8 Ft. 3-Point I and Plane	1.808.00

#### ATTACHMENTS FOR FIELD CONVERSION

Miscellaneous

5TL15746 French Kit - Includes Operator's Manual and Safety Decals

49.28

#### LP1196 - 8 Ft. 3-Point Land Plane Continued

THIS	S PA	AGF.	INTFI	NTIC	DNALLY	I FFT	BLAN	≺
1 1 11		<b>'</b>						

#### Landscaping

#### LP1207 - 7 Ft. Heavy Duty 3-Point Land Plane

**Equipment for Base Machine** 

Working Width: 84 In.
Shipping Weight: 1,048 lbs.
Operating Weight: 998 lbs.
3 Pt. Cat. 1 & 2
iMatch Compatible (Quick-Attach System)
Cat. 2 Quick Couple Compatible (Quick-Attach System)
Implement Code: 57.6
End Plate Thickness: 3/16 In.
Duty: Heavy Duty
Cutting Edges: (2) 1/2 x 6 in. Reversible
Adjustable Skid Shoes
Skid Shoe Thickness: 3/8 in.

Scarifier Shanks: (4) Available -Optional Assembly/Set-Up Time: 15 Minutes Warranty: 1 Year

Ballasting may be required. Please see your tractor operator's manual and your John Deere dealer.

			List Price
	Attachment		Suggested
Code	Identifier	Description	USD (\$)

Select One Code From Each Required Category

#### **BASE MACHINE**

1631XF LP1207 - 7 Ft. Heavy Duty 3-Point Land Plane 2,922.00

#### ATTACHMENTS FOR FIELD CONVERSION

Miscellaneous

5TL1207KT Scarifier Kit (LP1207) 226.80

## LP1207 - 7 Ft. Heavy Duty 3-Point Land Plane Continued

THIS PAGE INTENTIONALLY LEFT BLANK

#### Landscaping

#### LP1208 - 8 Ft. Heavy Duty 3-Point Land Plane

**Equipment for Base Machine** 

Working Width: 96 In.
Shipping Weight: 1,160 lbs.
Operating Weight: 1,110 lbs.
3 Pt. Cat. 1 & 2
iMatch Compatible (Quick-Attach System)
Cat. 2 Quick Couple Compatible (Quick-Attach System)
Implement Code: 64.1
End Plate Thickness: 3/16 In.
Duty: Heavy Duty
Cutting Edges: (2) 1/2 x 6 in. Reversible
Adjustable Skid Shoes
Skid Shoe Thickness: 3/8 in.

Scarifier Shanks: (6) Available -Optional Assembly/Set-Up Time: 15 Minutes Warranty: 1 Year

Ballasting may be required. Please see your tractor operator's manual and your John Deere dealer.

			List Price
	Attachment		Suggested
Code	Identifier	Description	USD (\$)

Select One Code From Each Required Category

#### **BASE MACHINE**

1632XF LP1208 - 8 Ft. Heavy Duty 3-Point Land Plane 3,242.00

#### ATTACHMENTS FOR FIELD CONVERSION

Miscellaneous

5TL1208KT Scarifier Kit (LP1208) 339.12

## LP1208 - 8 Ft. Heavy Duty 3-Point Land Plane Continued

THIS PAGE INTENTIONALLY LEFT BLANK

#### Landscaping

#### LP1210 - 10 Ft. Heavy Duty 3-Point Land Plane

**Equipment for Base Machine** 

Working Width: 120 In.
Shipping Weight: 1,304 lbs.
Operating Weight: 1,254 lbs.
3 Pt. Cat. 2
Cat. 2 Quick Couple Compatible (Quick-Attach System)
Implement Code: 72.4
End Plate Thickness: 3/16 In.
Duty: Heavy Duty
Cutting Edges: (2) 1/2 x 6 in. Reversible
Adjustable Skid Shoes

Skid Shoe Thickness: 3/8 in.

Scarifier Shanks: (8) Available -Optional Assembly/Set-Up Time: 15 Minutes Warranty: 1 Year

Ballasting may be required. Please see your tractor operator's manual and your John Deere dealer.

		List Price
Attachme Code Identifier	nt Description	Suggested USD (\$)

Select One Code From Each Required Category

#### **BASE MACHINE**

1633XF LP1210 - 10 Ft. Heavy Duty 3-Point Land Plane 3,662.00

#### ATTACHMENTS FOR FIELD CONVERSION

Miscellaneous

5TL1210KT Scarifier Kit (LP1210) 449.28

## LP1210 - 10 Ft. Heavy Duty 3-Point Land Plane Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Landscaping

### LR2060L - 5 Ft. Standard Duty Landscape Rake - Limited Category I

**Equipment for Base Machine** 

Tine Dimensions:
5/16 In. x 1 In. x 12 In. Spring Steel
Tine Spacing: 30 at 1 In.
Working Width: 60 In.
Tractor HP (Maximum): 25 HP
Parking Stand - Standard
Raking Positions:
5 Forward (0, 15, 30 Degrees),
5 Reverse (0, 15 Degrees)
3-Point Hitch:
Limited Category I (Aftermarket
Category 0 Lift Pins Available)
Pivot: 360 Degrees

Operating Weight: 168 lbs. Shipping Weight: 422 lbs. (Quantity of 2) Assembly/Set-Up Time: 30 Minutes Packaged Two Per Crate Gauge Wheels: Optional Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)

Select One Code From Each Required Category

#### **BASE MACHINE**

1191XF LR2060L - 5 Ft. Standard Duty Landscape Rake - Limited Category I 832.00

Order in multiples of two.

#### ATTACHMENTS FOR FIELD CONVERSION

Miscellaneous

5WS343465 Dual Gauge Wheel Kit (LR2060L) 480.60

## LR2060L - 5 Ft. Standard Duty Landscape Rake - Limited Category I Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Landscaping

### LR2072 - 6 Ft. Standard Duty Landscape Rake

**Equipment for Base Machine** 

Duty: Standard Duty
Rake Width: 72 In.
3-Point Hitch:
Category I
Tractor HP:
19 to 40 HP
Tine Dimension:
5/16 In. x 1 In. Spring Steel
Tine Spacing: 36 at 1 In.
Raking Positions:
5 Forward (0, 15, 30 Degree) Each Side
- 3 Reverse (0, 15 Degree) Each Side
Parking Stand: Standard
Approximate Operating Weight: 200 lbs.
Shipping Weight:

486 lbs. (Quantity 2)
Assembly/Set-Up Time:
30 Minutes (Approximate)
Pivot: 360 Degrees
Packaged 2 per Crate
Gauge Wheel Kit
 (Includes Two Wheels and Arms): Optional
Warranty: 1 Year

Code	Attachment Identifier	Description	Suggested USD (\$)
		Select One Code From Each Required Category	
1181XF		BASE MACHINE  LR2072 - 6 Ft. Standard Duty Landscape Rake	963.00
LIGIAE		LN2012 - 0 Ft. Statitualu Duty Latituscape Nake	903.00

#### ATTACHMENTS FOR FIELD CONVERSION

Miscellaneous

5WS341775 Dual Gauge Wheel Kit (LR2072, LR2084, LR2172, LR2184 and LR2196)

513.00

## LR2072 - 6 Ft. Standard Duty Landscape Rake Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Landscaping

### LR2084 - 7 Ft. Standard Duty Landscape Rake

**Equipment for Base Machine** 

Duty: Standard Duty
Rake Width: 84 In.
3-Point Hitch:
Category I
Tractor HP:
19 to 40 HP
Tine Dimension:
5/16 In. x 1 In. Spring Steel
Tine Spacing: 42 at 1 In.
Raking Positions:
5 Forward (0, 15, 30 Degree) Each Side
- 3 Reverse (0, 15 Degree) Each Side
Parking Stand: Standard
Pivot: 360 Degrees
Approximate Operating Weight:

221 lbs.
Approximate Shipping Weight:
528 lbs. (Quantity 2)
Assembly/Set-Up Time:
30 Minutes (Approximate)
Packaged 2 per Crate
Gauge Wheel Kit
(Includes Two Wheels and Arms): Optional
Warranty: 1 Year

ment er Description	Suggested USD (\$)
Select One Code From Each Required Category	]
BASE MACHINE  LR2084 - 7 Ft. Standard Duty Landscape Rake	1,087.00
	Select One Code From Each Required Category  BASE MACHINE

#### ATTACHMENTS FOR FIELD CONVERSION

Miscellaneous

5WS341775 Dual Gauge Wheel Kit (LR2072, LR2084, LR2172, LR2184 and LR2196)

513.00

## LR2084 - 7 Ft. Standard Duty Landscape Rake Continued

THIS PAGE INTENTIONALLY LEFT BLANK

513.00

### FRONTIER PRODUCTS

Landscaping

### LR2172 - 6 Ft. Medium Duty Landscape Rake

**Equipment for Base Machine** 

Duty: Medium Duty
Rake Width: 72 In.
3-Point Hitch:
Category I
Tractor HP:
23 to 55 HP
Tines Dimension:
5/16 In. x 1 In. Spring Steel
Tine Spacing: 36 at 1 In.
Raking Positions:
5 Forward (0, 15, 30 Degree) Each Side
- 3 Reverse (0, 15 Degree) Each Side
Parking Stand: Standard
Approximate Operating Weight: 282 lbs.

5WS341775

Approximate Shipping Weight: 368 lbs.
Assembly/Set-Up Time:
30 Minutes (Approximate)
Gauge Wheel Assembly Kit
(Two Wheels and Arms): Optional
6 Ft. Flip Down Grader Blade: Optional
Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
1201XF		BASE MACHINE  LR2172 - 6 Ft. Medium Duty Landscape Rake	1,324.00
120 171		ATTACHMENTS FOR FIELD CONVERSION	.,02.100
	5WS341986	Miscellaneous 6 Ft. Flip Down Blade (LR2172)	332.64

Dual Gauge Wheel Kit (LR2072, LR2084, LR2172, LR2184 and LR2196)

## LR2172 - 6 Ft. Medium Duty Landscape Rake Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Landscaping

### LR2184 - 7 Ft. Medium Duty Landscape Rake

**Equipment for Base Machine** 

Duty: Medium Duty
Rake Width: 84 In.
3-Point Hitch:
Category I
Tractor HP:
23 to 55 HP
Tine Dimension:
5/16 In. x 1 In. Spring Steel
Tine Spacing: 42 at 1 In.
Raking Positions:
5 Forward (0, 15, 30 Degree) Each Side
- 3 Reverse (0, 15 Degree) Each Side
Parking Stand: Standard
Approximate Operating Weight: 307 lbs.

Approximate Shipping Weight: 393 lbs. Assembly/Set-Up Time: 30 Minutes (Approximate) Gauge Wheel Assembly Kit (Two Wheels and Arms): Optional 7 Ft. Flip Down Grader: Optional Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
1202XF		BASE MACHINE  LR2184 - 7 Ft. Medium Duty Landscape Rake	1,425.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous	
	5WS341987	7 Ft. Flip Down Blade (LR2184)	345.60

## LR2184 - 7 Ft. Medium Duty Landscape Rake Continued

THIS PAGE INTENTIONALLY LEFT BLANK

513.00

### FRONTIER PRODUCTS

#### Landscaping

#### LR2196 - 8 Ft. Medium Duty Landscape Rake

**Equipment for Base Machine** 

Duty: Medium Duty
Rake Width: 96 In.
3-Point Hitch:
Category I
Tractor HP: 27 to 55 HP
Tines Dimension:
5/16 In. x 1 In. Spring Steel
Tine Spacing: 48 at 1 In.
Raking Positions:
5 Forward (0, 15, 30 Degree) Each Side
- 3 Reverse (0, 15 Degree) Each Side
Approximate Operating Weight: 332 lbs.
Approximate Shipping Weight: 418 lbs.

5WS341775

Parking Stand: Standard Assembly/Set-Up Time: 30 Minutes (Approximate) Gauge Wheel Assembly Kit (Two Wheels and Arms): Optional 8 Ft. Flip Down Grader: Optional Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1203XF		LR2196 - 8 Ft. Medium Duty Landscape Rake	1,522.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5WS341988	Miscellaneous 8 Ft. Flip Down Blade (LR2196)	396.36

Dual Gauge Wheel Kit (LR2072, LR2084, LR2172, LR2184 and LR2196)

## LR2196 - 8 Ft. Medium Duty Landscape Rake Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Landscaping

### LR5060 - 5 Ft. Standard Duty Landscape Rake

**Equipment for Base Machine** 

Duty: Standard Duty Rake Width: 60 In. 3-Point Hitch: Category I Tractor HP: 15 to 35 HP Tine Dimension:
5/16 In. x 1 In. Spring Steel
Tine Spacing: 36 at 1 In. Raking Positions: 5 Forward (0, 15, 30 Degree) Each Side - 5 Reverse (0, 15, 30 Degree) Each Side Parking Stand: Standard Approximate Operating Weight: 248 lbs.

Shipping Weight: 554 lbs. (Quantity 2) Assembly/Set-Up Time: 15 Minutes (Approximate) Pivot: 360 Degrees Packaged 2 per Crate Gauge Wheel Kit: NA Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		DAGE MACHINE	

#### **BASE MACHINE**

1661XF LR5060 - 5 Ft. Standard Duty Landscape Rake

Order in multiples of two.

813.00

## LR5060 - 5 Ft. Standard Duty Landscape Rake Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Landscaping

### LR5072 - 6 Ft. Standard Duty Landscape Rake

**Equipment for Base Machine** 

Duty: Standard Duty
Rake Width: 72 In.
3-Point Hitch:
Category I
Tractor HP:
20 to 38 HP
Tine Dimension:
5/16 In. x 1 In. Spring Steel
Tine Spacing: 36 at 1 In.
Raking Positions:
5 Forward (0, 15, 30 Degree) Each Side
- 5 Reverse (0, 15, 30 Degree) Each Side
Parking Stand: Standard
Approximate Operating Weight: 272 lbs.

Shipping Weight:
602 lbs. (Quantity 2)
Assembly/Set-Up Time:
15 Minutes (Approximate)
Pivot: 360 Degrees
Packaged 2 per Crate
Gauge Wheel Kit: NA
Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	

#### BASE MACHINE

1662XF LR5072 -

LR5072 - 6 Ft. Standard Duty Landscape Rake *Order in multiples of two*.

880.00

## LR5072 - 6 Ft. Standard Duty Landscape Rake Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Landscaping

### LR5084 - 7 Ft. Standard Duty Landscape Rake

**Equipment for Base Machine** 

Duty: Standard Duty
Rake Width: 84 In.
3-Point Hitch:
Category I
Tractor HP:
20 to 50 HP
Tine Dimension:
5/16 In. x 1 In. Spring Steel
Tine Spacing: 36 at 1 In.
Raking Positions:
5 Forward (0, 15, 30 Degree) Each Side
- 5 Reverse (0, 15, 30 Degree) Each Side
Parking Stand: Standard
Approximate Operating Weight: 287 lbs.

Shipping Weight:
632 lbs. (Quantity 2)
Assembly/Set-Up Time:
15 Minutes (Approximate)
Pivot: 360 Degrees
Packaged 2 per Crate
Gauge Wheel Kit: NA
Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
1663XF		BASE MACHINE  LR5084 - 7 Ft. Standard Duty Landscape Rake  Order in multiples of two.	927.00

## LR5084 - 7 Ft. Standard Duty Landscape Rake Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Landscaping

### LR5096 - 8 Ft. Standard Duty Landscape Rake

**Equipment for Base Machine** 

Duty: Standard Duty Rake Width: 96 In. 3-Point Hitch: Category I Tractor HP: 20 to 50 HP Tine Dimension:
5/16 In. x 1 In. Spring Steel
Tine Spacing: 36 at 1 In. Raking Positions: 5 Forward (0, 15, 30 Degree) Each Side - 5 Reverse (0, 15, 30 Degree) Each Side Parking Stand: Standard Approximate Operating Weight: 324 lbs.

Shipping Weight: 706 lbs. (Quantity 2) Assembly/Set-Up Time: 15 Minutes (Approximate) Pivot: 360 Degrees Packaged 2 per Crate Gauge Wheel Kit: NA Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	

1664XF LR5096 - 8 Ft. Standard Duty Landscape Rake

Order in multiples of two.

## LR5096 - 8 Ft. Standard Duty Landscape Rake Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Landscaping

### LR5048L - 4 Ft. Limited Category 1 Economy Duty Landscape Rake

**Equipment for Base Machine** 

Duty: Economy Duty
Rake Width: 48 In.
3-Point Hitch:
Limited Category I
Tractor HP: 18 PTO HP Max
Tine Dimension:
5/16 In. x 1 In. Spring Steel
Tine Spacing: 24 at 1 In.
Raking Positions:
5 Forward (0, 15, 30 Degree) Each Side
- 5 Reverse (0, 15, 30 Degree) Each Side
Parking Stand: Standard
Approximate Operating Weight: 186 lbs.
Shipping Weight:

430 lbs. (Quantity 2)
Assembly/Set-Up Time:
15 Minutes (Approximate) - Per Pair
Pivot: 360 Degrees
Packaged 2 per Crate
Gauge Wheel Kit: Yes
Warranty: 1 Year

			List Price
	Attachment		Suggested
Code	Identifier	Description	USD (\$)

Select One Code From Each Required Category

#### **BASE MACHINE**

1761XF LR5048L - 4 Ft. Limited Category 1 Economy Duty Landscape Rake

Order in multiples of two.

648.00

#### ATTACHMENTS FOR FIELD CONVERSION

Miscellaneous

5TITE511225 LR50L Gauge Wheel Kit

Includes two solid wheels, two mounting brackets, and hardware.

267.98

## LR5048L - 4 Ft. Limited Category 1 Economy Duty Landscape Rake Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Landscaping

### LR5060L - 5 Ft. Limited Category 1 Economy Duty Landscape Rake

**Equipment for Base Machine** 

Duty: Economy Duty
Rake Width: 60 In.
3-Point Hitch:
Limited Category I
Tractor HP: 18 PTO HP Max
Tine Dimension:
5/16 In. x 1 In. Spring Steel
Tine Spacing: 30 at 1 In.
Raking Positions:
5 Forward (0, 15, 30 Degree) Each Side
- 5 Reverse (0, 15, 30 Degree) Each Side
Parking Stand: Standard
Approximate Operating Weight: 205 lbs.
Shipping Weight:

468 lbs. (Quantity 2)
Assembly/Set-Up Time:
15 Minutes (Approximate) - Per Pair
Pivot: 360 Degrees
Packaged 2 per Crate
Gauge Wheel Kit: Yes
Warranty: 1 Year

			List Price
	Attachment		Suggested
Code	Identifier	Description	USD (\$)

Select One Code From Each Required Category

#### **BASE MACHINE**

1762XF LR5060L - 5 Ft. Limited Category 1 Economy Duty Landscape Rake

 $Order\ in\ multiples\ of\ two.$ 

746.00

#### ATTACHMENTS FOR FIELD CONVERSION

Miscellaneous

5TITE511225 LR50L Gauge Wheel Kit

Includes two solid wheels, two mounting brackets, and hardware.

267.98

## LR5060L - 5 Ft. Limited Category 1 Economy Duty Landscape Rake Continued

THIS PAGE INTENTIONALLY LEFT BLANK

#### Landscaping

### **PM1001 Integral Middle Buster**

**Equipment for Base Machine** 

Hitch:
Lift-type, Category I,
iMatch Compatible
Working Depth:
Up to 12 In. (304.8 mm)
Transport Length:
15 In. (381 mm)
Transport Width:
32 In. (812.8 mm)
Transport Height:
32 In. (812.8 mm)

Tractor Engine HP Range: 25 - 45 HP Blade: Double-Wing Cutting Blade, 19 In. (482.6 mm) x 11 In. (279.4 mm)

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
3461XF		PM1001 Integral Middle Buster Order in multiples of two.	267.00
		OPERATOR'S MANUAL AND DECALS	
904L		French OM & Decal Kit (PM10)	13.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5TITE511154	<b>Miscellaneous</b> French Kit - Includes Operator's Manual, Parts Catalog and Safety Decals <i>PM1001</i>	15.60

Bid Term: 2/20/19 - 2/19/21

### PM1001 Integral Middle Buster Continued

THIS	S PA	AGF.	INTFI	NTIC	DNALLY	I FFT	BLAN	<
1 1 111		<b>'</b>						

### PHA006 Post Hole Auger 6 In. for PHD100

Equipment for Base Machine

Diameter: 6 In.
Length: 36 In.
Weight: 24 lbs.
Flighting Type: Single
Flighting Thickness: 3/16 In.
Compatible With Digger Model Number(s): PHD100

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
1211XF		BASE MACHINE PHA006 Post Hole Auger 6 In. for PHD100	332.00

## PHA006 Post Hole Auger 6 In. for PHD100 Continued

THIS PAGE INTENTIONALLY LEFT BLANK

### PHA009 Post Hole Auger 9 In. for PHD100

Equipment for Base Machine

Diameter: 9 In.
Length: 36 In.
Weight: 42 lbs.
Flighting Type: Double
Flighting Thickness: 3/16 In.
Compatible With Digger Model Number(s): PHD100

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
1212XF		BASE MACHINE PHA009 Post Hole Auger 9 In. for PHD100	354.00

## PHA009 Post Hole Auger 9 In. for PHD100 Continued

THIS PAGE INTENTIONALLY LEFT BLANK

### PHA012 Post Hole Auger 12 In. for PHD100

Equipment for Base Machine

Diameter: 12 In.
Length: 36 In.
Weight: 52 lbs.
Flighting Type: Double
Flighting Thickness: 3/16 In.
Compatible With Digger Model Number(s): PHD100

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
1213XF		BASE MACHINE PHA012 Post Hole Auger 12 In. for PHD100	441.00

## PHA012 Post Hole Auger 12 In. for PHD100 Continued

THIS PAGE INTENTIONALLY LEFT BLANK

### PHA106 Post Hole Auger 6 In. for PHD200/300/400

Equipment for Base Machine

Diameter: 6 In.
Length: 48 In.
Weight: 32 lbs.
Flighting Type: Single
Flighting Thickness: 3/16 In.
Compatible With Digger Model Number(s):
PHD200, PHD300, PHD400

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
1214XF		BASE MACHINE PHA106 Post Hole Auger 6 In. for PHD200/300/400	333.00

## PHA106 Post Hole Auger 6 In. for PHD200/300/400 Continued

THIS PAGE INTENTIONALLY LEFT BLANK

## PHA109 Post Hole Auger 9 In. for PHD200/300/400

Equipment for Base Machine

Diameter: 9 In.
Length: 48 In.
Weight: 55 lbs.
Flighting Type: Double
Flighting Thickness: 3/16 In.
Compatible With Digger Model Number(s):
PHD200, PHD300, PHD400

Attachment Identifier	Description	List Price Suggested USD (\$)
	Select One Code From Each Required Category	
	BASE MACHINE PHA109 Post Hole August 9 In for PHD200/300/400	350.00
		Select One Code From Each Required Category

# PHA109 Post Hole Auger 9 In. for PHD200/300/400 Continued

THIS PAGE INTENTIONALLY LEFT BLANK

## PHA112 Post Hole Auger 12 In. for PHD200/300/400

Equipment for Base Machine

Diameter: 12 In.
Length: 48 In.
Weight: 55 lbs.
Flighting Type: Double
Flighting Thickness: 3/16 In.
Compatible With Digger Model Number(s):
PHD200, PHD300, PHD400

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
1216XF		BASE MACHINE PHA112 Post Hole Auger 12 In. for PHD200/300/400	426.00

# PHA112 Post Hole Auger 12 In. for PHD200/300/400 Continued

THIS PAGE INTENTIONALLY LEFT BLANK

## PHA118 Post Hole Auger 18 In. for PHD300/400

Equipment for Base Machine

Diameter: 18 In.
Length: 48 In.
Weight: 80 lbs.
Flighting Type: Double
Flighting Thickness: 1/4 In.
Compatible With Digger Model Number(s):
PHD300, PHD400

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
1217XF		BASE MACHINE PHA118 Post Hole Auger 18 In. for PHD300/400	575.00

# PHA118 Post Hole Auger 18 In. for PHD300/400 Continued

THIS PAGE INTENTIONALLY LEFT BLANK

## PHA124 Post Hole Auger 24 In. for PHD300/400

Equipment for Base Machine

Diameter: 24 In. Length: 48 In. Weight: 105 lbs. Flighting Type: Double Flighting Thickness: 1/4 In. Compatible With Digger Model Number(s): PHD300, PHD400

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
1218XF		BASE MACHINE PHA124 Post Hole Auger 24 In. for PHD300/400	813.00

# PHA124 Post Hole Auger 24 In. for PHD300/400 Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Landscaping

## PHA130 Post Hole Auger 30 In. for PHD300/400

Equipment for Base Machine

Diameter: 30 In.
Length: 44 In.
Weight: 213 lbs.
Flighting Type:
Double (15 In. and 30 In.)
Flighting Thickness: 5/16 In.
Compatible With Digger Model Number(s):

PHD300, PHD400

	ttachment lentifier	Description	List Price Suggested USD (\$)
	[	Select One Code From Each Required Category	
1219XF	F	PHA130 Post Hole Auger 30 In. for PHD300/400 Tapered flighting for planting trees.	1,631.00

# PHA130 Post Hole Auger 30 In. for PHD300/400 Continued

THIS PAGE INTENTIONALLY LEFT BLANK

### Landscaping

## PHD100 Post Hole Digger Up to 25HP Category I Hitch

Equipment for Base Machine

Boom OD: 2-7/8 In.
Yoke OD: 2-3/8 In.
Auger Speed: 180 RPM
Gearbox Gear Ratio: 3:1
Gearbox HP Rating: 25 HP
PTO HP Range: 18-25 HP
3-Point Hitch Category: Category I
Works with Auger Model Numbers:
PHA006, PHA009, PHA012

Weight: 112 lbs. Shipping Weight (2 per Crate): 330 lbs. Set-Up Time: 20 Minutes

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1221XF		PHD100 Post Hole Digger Up to 25HP Category I Hitch Order in multiples of two.	1,181.00
9000		HOOKUP STAND Hook-Up Stand For customer use.	499.00
9200		OPERATOR'S MANUAL AND DECALS French Operator's Manual and Decal Kit  ATTACHMENTS FOR FIELD CONVERSION	No Charge
	5BP950960B	Miscellaneous French OM & Decal Kit Post Hole Diggers Destination of Quebec only. Includes French safety decals and manul.	0.02
	5BP480099851	Post Hole Digger Hookup Stand For customer use.	526.92

# PHD100 Post Hole Digger Up to 25HP Category I Hitch Continued

THIS PAGE INTENTIONALLY LEFT BLANK

**List Price** 

#### FRONTIER PRODUCTS

### Landscaping

## PHD200 Post Hole Digger Up to 40HP Category I Hitch

Equipment for Base Machine

Boom OD: 3-1/2 In.
Yoke OD: 2-7/8 In.
Auger Speed: 180 RPM
Gearbox Gear Ratio: 3:1
Gearbox HP Rating: 40 HP
PTO HP Range: 18-40 HP
3-Point Hitch Category: Category I
Works with Auger Model Numbers:
PHA106, PHA109, PHA112

Weight: 200 lbs. Shipping Weight (2 per Crate): 470 lbs. Set-Up Time: 20 Minutes

Code	Attachment Identifier Description		Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1222XF		PHD200 Post Hole Digger Up to 40HP Category I Hitch Order in multiples of two.	1,291.00
		POST HOLE DIGGER DOWN FORCE KIT	
9010		Post Hole Digger Down Force Kit For PHD200	740.00
		HOOKUP STAND	
9000		Hook-Up Stand For customer use.	499.00
		OPERATOR'S MANUAL AND DECALS	
9200		French Operator's Manual and Decal Kit	No Charge
		ATTACHMENTS FOR FIELD CONVERSION	
	5BP950960B	Miscellaneous French OM & Decal Kit Post Hole Diggers Destination of Quebec only. Includes French safety decals and manul.	0.02
	5BP0099154	Post Hole Digger Down Force Kit PHD200	799.20
	5BP480099851	Post Hole Digger Hookup Stand For customer use.	526.92

# PHD200 Post Hole Digger Up to 40HP Category I Hitch Continued

THIS PAGE INTENTIONALLY LEFT BLANK

### Landscaping

## PHD300 Post Hole Digger Up to 50HP Category I & II Hitch

**Equipment for Base Machine** 

Boom OD: 3-1/2 In. Reinforced Yoke OD: 2-7/8 In. Reinforced Auger Speed: 154 RPM Gearbox Gear Ratio: 3.5:1 Gearbox HP Rating: 50 HP PTO HP Range: 18-50 HP 3-Point Hitch Category: Category I or II Works with Auger Model Numbers: PHA106, PHA109, PHA112, PHA118, PHA124, PHA132

Weight: 230 lbs. Shipping Weight (2 per Crate): 550 lbs. Set-Up Time: 20 Minutes

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1223XF		PHD300 Post Hole Digger Up to 50HP Category I & II Hitch Order in multiples of two.	1,558.00
		POST HOLE DIGGER DOWN FORCE KIT	
9010		Post Hole Digger Down Force Kit For PHD300 and PHD400	761.00
		HOOKUP STAND	
9000		Hook-Up Stand For customer use.	499.00
		POST HOLE DIGGER AUGER POSITIONING HANDLE	
9020		Post Hole Digger Auger Positioning Handle	179.00
		OPERATOR'S MANUAL AND DECALS	
9200		French Operator's Manual and Decal Kit	No Charge
		ATTACHMENTS FOR FIELD CONVERSION	
	5BP950960B	Miscellaneous French OM & Decal Kit Post Hole Diggers Destination of Quebec only. Includes French safety decals and manul.	0.02
	5BP48PHD003	Post Hole Digger Auger Positioning Handle	188.72
	5BP0099155	Post Hole Digger Down Force Kit (PHD300 & PHD400)	821.88
	5BP480099851	Post Hole Digger Hookup Stand For customer use.	526.92

Bid Term: 2/20/19 - 2/19/21

# PHD300 Post Hole Digger Up to 50HP Category I & II Hitch Continued

THIS PAGE INTENTIONALLY LEFT BLANK

**List Price** 

### FRONTIER PRODUCTS

### Landscaping

## PHD400 Post Hole Digger Up to 90HP Category I & II Hitch

**Equipment for Base Machine** 

Boom OD: 3-1/2 In. Reinforced Yoke OD: 2-7/8 In. Reinforced Auger Speed: 135 RPM Gearbox Gear Ratio: 4:1 Gearbox HP Rating: 90 HP PTO HP Range: 40-90 HP 3-Point Hitch Category: Category I or II Works with Auger Model Numbers: PHA106, PHA109, PHA112, PHA118, PHA124, PHA132

Weight: 260 lbs. Shipping Weight (2 per Crate): 610 lbs. Set-Up Time: 20 Minutes

Code	Attachment Identifier	Description	Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1224XF		PHD400 Post Hole Digger Up to 90HP Category I & II Hitch Order in multiples of two.	1,887.00
		POST HOLE DIGGER DOWN FORCE KIT	
9010		Post Hole Digger Down Force Kit For PHD300 and PHD400	761.00
		HOOKUP STAND	
9000		Hook-Up Stand For customer use.	499.00
		POST HOLE DIGGER AUGER POSITIONING HANDLE	
9020		Post Hole Digger Auger Positioning Handle	179.00
		OPERATOR'S MANUAL AND DECALS	
9200		French Operator's Manual and Decal Kit	No Charge
		ATTACHMENTS FOR FIELD CONVERSION	
	5BP950960B	Miscellaneous French OM & Decal Kit Post Hole Diggers Destination of Quebec only. Includes French safety decals and manul.	0.02
	5BP48PHD003	Post Hole Digger Auger Positioning Handle	188.72
	5BP0099155	Post Hole Digger Down Force Kit (PHD300 & PHD400)	821.88
	5BP480099851	Post Hole Digger Hookup Stand For customer use.	526.92

# PHD400 Post Hole Digger Up to 90HP Category I & II Hitch Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Landscaping

#### **PR1148 - 48 In. Power Rake**

**Equipment for Base Machine** 

Function: Landscaping and Site Development Hitch Compatibility: Category I and iMatch Compatible Rotor: Cylindrical with Welded Carbide Teeth Carbide Teeth per Rotor: 76
Depth Control: Dual Independently Adjustable Gauge Wheels
Gauge Wheel Description: 13 x 5.00-6 Gauge Wheel Height Adjustment: Manual Split Clamp Angle Adjustment: Hydraulic Hydraulic Cylinder Manufacturer: Best Metal Ind.
Hydraulic Cylinder Description: 1.50 In. Hydraulic Cylinder Description: 1.5

Bore 0.75 In. Rod 6.00 In. Stroke
Working Angles R or L: 0-15 Degrees
Height: 34 In.

Transport Width: 54 In. Working Width: 48 In.
Working Width at Maximum Angle: 46 In. Roll-Back Barrier Range: 5/16 In. to 3-3/16 In. Length: 54 In. Side Drive: Chain ASA 50-2 Chain Case Lube: Cenex 365 #00 Fluid grease Tubing Size: 3 In. x 3 In.

Tubing Wall Thickness: 3/16 In. Tractor PTO Speed (RPM): 540 Driveline Manufacturer: Weasler Primary Driveline Description: 14R with Cut-out Clutch Secondary Driveline Description: 1-3/8 In. - 6 Splines Direct to Chain Case Clutch/Torque Setting (Number): 316 Tractor PTO HP Requirements Minimum-Maximum: 15-22 HP Tractor Hydraulic Requirements: 1500 PSI Gearbox Manufacturer: Weasler Gearbox Description: Straight Bevel Gear in Oil Bath Gearbox Oil Recommendation: 85-90W Gearbox Reduction: 2:1 Rotor Speed (RPM): 285 Rotor Direction of Rotation: Against DOT Approximate Operating Weight: 500 lbs. Approximate Shipping Weight: 700 lbs. Parking Stand: Standard Approximate Set-Up Time: 20 Minutes Warranty: 1 Year

			List Price
	Attachment		Suggested
Code	Identifier	Description	USD (\$)

Select One Code From Each Required Category

#### **BASE MACHINE**

1231XF PR1148 - 48 In. Power Rake 9,291.00

# PR1148 - 48 In. Power Rake Continued

## THIS PAGE INTENTIONALLY LEFT BLANK

#### FRONTIER PRODUCTS

#### Landscaping

#### **PR1160 - 60 In. Power Rake**

**Equipment for Base Machine** 

Function: Landscaping and Site Development Hitch Compatibility: Category I and iMatch Compatible Rotor: Cylindrical with Welded Carbide Teeth Carbide Teeth per Rotor: 88
Depth Control: Dual Independently Adjustable Gauge Wheels
Gauge Wheel Description: 13 X 5.00-6 Gauge Wheel Height Adjustment: Manual Split Clamp Angle Adjustment: Hydraulic Hydraulic Cylinder Manufacturer: Best Metal Ind.
Hydraulic Cylinder Description: 1.50 In. Hydraulic Cylinder Description: 1.5 Bore 0.75 In. Rod 6.00 In. Stroke Working Angles R or L: 0-15 Degrees Height: 36 In. Transport Width: 64 In. Working Width: 56 In.
Working Width at Maximum Angle: 54 In. Roll-Back Barrier Range: 5/16 In. to 3-3/16 In. Length: 55 In. Side Drive: Chain ASA 50-2 Chain Case Lube: Cenex 365 #00 Fluid Grease Tubing Size: 3 In. x 3 In. Tubing Wall Thickness: 3/16 In.

Tractor PTO Speed (RPM): 540 Driveline Manufacturer: Weasler Primary Driveline Description: 14R Secondary Driveline Description: 1-3/8 In. 6 Splines to Chain Case with Friction Clutch Clutch/Torque Setting (Number): 508 Tractor PTO HP Requirements Minimum-Maximum: 18-35 HP Tractor Hydraulic Requirements: 1500 PSI Gearbox Manufacturer: Superior Gearbox Description: Straight Bevel Gear in Oil Bath Gearbox Oil Recommendation: 85-90W Gearbox Reduction: 2:1 Rotor Speed (RPM): 285 Rotor Speed (RPM). 285 Rotor Direction of Rotation: Against DOT Approximate Operating Weight: 550 lbs. Approximate Shipping Weight: 750 lbs. Parking Stand: Standard Approximate Set-Up Time: 20 Minutes Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)

# Select One Code From Each Required Category

#### **BASE MACHINE**

1232XF	PR1160 - 60 In. Power Rake	9,879.00

#### **GRASS SEED ATTACHMENT**

9000 **Grass Seed Attachment** 6,425.00 For PR1160

#### ATTACHMENTS FOR FIELD CONVERSION

#### Miscellaneous

5SPPS50814 Grass Seed Attachment for PR1160 6,939.00

## PR1160 - 60 In. Power Rake Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Landscaping

#### **PR1172 - 72 In. Power Rake**

**Equipment for Base Machine** 

Function: Landscaping and Site Development Hitch Compatibility: Category I and iMatch Compatible Rotor: Cylindrical with Welded Carbide Teeth Carbide Teeth per Rotor: 114
Depth Control: Dual Independently Adjustable Gauge Wheels
Gauge Wheel Description: 16.5 x 6.5-8 Gauge Wheel Height Adjustment: Manual Split Clamp Angle Adjustment: Hydraulic Hydraulic Cylinder Manufacturer: Best Metal Ind.
Hydraulic Cylinder Description: 1.50 In. Bore 0.75 In. Rod 8.00 In. Stroke Working Angles R or L: 0-15 Degrees Height: 40 In. Transport Width: 81 In. Working Width: 72 In.
Working Width at Maximum Angle: 69.5 In. Working width at Maximum Ar Roll-Back Barrier Range: 5/16 In. to 2-15/16 In. Length: 62 In. Side Drive: Chain ASA 60-2 Chain Case Lube: Cenex 365 #00 Fluid Grease Tubing Size: 3 In. x 3 In.

Tubing Wall Thickness: 1/4 In.
Tractor PTO Speed (RPM): 540
Driveline Manufacturer: Weasler
Primary Driveline Description: 14R
Secondary Driveline Description: 35R with Friction Clutch
Clutch/Torque Setting (Number): 1016
Tractor PTO HP Requirements
Minimum-Maximum: 30-40 HP
Tractor Hydraulic Requirements: 1500 PSI
Gearbox Manufacturer: Superior
Gearbox Description:
Straight Bevel Gear in Oil Bath
Gearbox Oil Recommendation: 85-90W
Gearbox Reduction: 2:1
Rotor Speed (RPM): 270
Rotor Direction of Rotation: Against DOT
Approximate Operating Weight: 830 lbs.
Approximate Shipping Weight: 1100 lbs.
Parking Stand: Standard
Approximate Set-Up Time:
45 Minutes
Warranty: 1 Year

			List Price
	Attachment		Suggested
Code	Identifier	Description	USD (\$)

Select One Code From Each Required Category

#### **BASE MACHINE**

1233XF PR1172 - 72 In. Power Rake 10,991.00

#### **GRASS SEED ATTACHMENT**

9000 Grass Seed Attachment 6,771.00 For PR1172

#### ATTACHMENTS FOR FIELD CONVERSION

Miscellaneous

5SPPS60814 Grass Seed Attachment for PR1172 7,312.68

# PR1172 - 72 In. Power Rake Continued

## THIS PAGE INTENTIONALLY LEFT BLANK

Landscaping

#### **PR1184 - 84 In. Power Rake**

**Equipment for Base Machine** 

Function: Landscaping and
Site Development
Hitch Compatibility:
Category I, Category II,
iMatch, Quick Coupler Compatible
Rotor: Cylindrical with
Welded Carbide Teeth
Carbide Teeth per Rotor: 132
Depth Control: Dual Independently
Adjustable Gauge Wheels
Gauge Wheel Description: 16.5 x 6.5-8
Gauge Wheel Description: 16.5 x 6.5-8
Gauge Wheel Height Adjustment:
Manual Split Clamp
Angle Adjustment: Hydraulic
Hydraulic Cylinder Manufacturer:
Best Metal Ind.
Hydraulic Cylinder Description: 2.00 In.
Bore 1.25 In. rod 8.00 In. Stroke
Working Angles R or L: 0-15 Degrees
Height: 44 In.
Transport Width: 93 In.
Working Width: 84 In.
Working Width: 84 In.
Working Width: 84 In.
Roll-Back Barrier Range:
5/16 In. to 4-11/16 In.
Length: 70 In.
Side Drive: Chain ASA 60-2H
Chain Case Lube:
Cenex 365 #00 Fluid Grease
Tubing Size: 4 In. x 4 In.

Tubing Wall Thickness: 5/16 In. Tractor PTO Speed (RPM): 540 Driveline Manufacturer: Weasler Primary Driveline Description: 35E Secondary Driveline Description: 44E with Friction Clutch (1-3/4 In. 20 Splines) Clutch/Torque Setting (Number): 1695
Tractor PTO HP Requirements Minimum-Maximum: 42-80 HP Tractor Hydraulic Requirements: 1500 PSI Gearbox Manufacturer: Superior Gearbox Description: Straight Bevel Gear in Oil Bath Gearbox Oil Recommendation: 85-90W Gearbox Reduction: 2:1 Rotor Speed (RPM): 270 Rotor Direction of Rotation: Against DOT Approximate Operating Weight: 1260 lbs. Approximate Shipping Weight: 1700 lbs. Parking Stand: Standard Parking Stand: Standard Approximate Set-Up Time: 60 Minutes Warranty: 1 Year

			List Price
	Attachment		Suggested
Code	Identifier	Description	USD (\$)

Select One Code From Each Required Category

#### **BASE MACHINE**

1234XF PR1184 - 84 In. Power Rake 14,362.00

## PR1184 - 84 In. Power Rake Continued

## THIS PAGE INTENTIONALLY LEFT BLANK

### Landscaping

### RB2060 - 5 Ft. Standard Duty Rear Blade

**Equipment for Base Machine** 

3-Point Hitch: Category I
Working Width: 60 In.
Operational Weight: 249 lbs.
Tractor HP: 19 to 45 HP
Tilt Positions: Three
Offset: 12 In. Left or Right
Shipping Weight:
588 lbs. for Quantity 2
Pivot: 360 Degrees
Parking Stand: Standard
Packaged 2 Per Crate
Moldboard Height: 14 In.
Moldboard Length: 60 In.
Moldboard Thickness: 3/16 In.
Duty: Standard Duty

Cutting Edge:
1/2 In. x 6 In. Reversible
Assembly/Set-Up Time: 15 Minutes
Angle - Forward:
0, 15 and 30 Degrees Each Side
Angle - Reverse:
0 and 15 Degrees Each Side
Skid Shoes: Optional

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1281XF		RB2060 - 5 Ft. Standard Duty Rear Blade Order in multiples of two.	772.00
		OPERATOR'S MANUAL AND DECALS	
9200		French Operator's Manual and Decal Kit (RB20 Series)	49.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5WS346765	Miscellaneous End Plate Kit (RB2060, RB2072 and RB2084)	168.48
	5WS101376	French Operator's Manual and Decal Kit (RB20 and RB20L Series)	54.88
	5WS346745	Skid Shoes Kit (RB2060, RB2072 and RB2084)	258.12

# RB2060 - 5 Ft. Standard Duty Rear Blade Continued

TΙ	ΗІ	S	PA	GE	INT	ΈN	ITI(	DNAI	LLY L	_EFT	BLA	١N١	Κ

### Landscaping

## RB2060L - 5 Ft. Rear Blade - Limited Category I

**Equipment for Base Machine** 

Cutting Edge:
1/2 In. x 6 In. Reversible
Angle Pivot: 360 Degrees
Angle - Forward:
0, 15 and 30 Degrees Each Side
Angle - Reverse:
0, 15 and 30 Degrees Each Side
Moldboard Thickness: 7 Gauge
Moldboard Length: 60 In.
Moldboard Height: 11 In.
Tractor HP (Maximum): 25 HP
3-Point Hitch:
Limited Category I (Aftermarket
Category 0 Lift Pins Available)

Parking Stand - Standard Skid Shoe Bundle: Optional Operating Weight: 155 lbs. Shipping Weight: 402 lbs. (Quantity of 2) Packaged Two Per Crate Assembly/Set-Up Time: 30 Minutes Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1291XF		RB2060L - 5 Ft. Rear Blade - Limited Category I Order in multiples of two.	551.00
		OPERATOR'S MANUAL AND DECALS	
9200		French Operator's Manual and Decal Kit (RB20 Series)	49.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5WS101376	Miscellaneous French Operator's Manual and Decal Kit (RB20 and RB20L Series)	54.88
	5WS343435	Skid Shoes Kit (RB2060L)	59.36

Bid Term: 2/20/19 - 2/19/21

# RB2060L - 5 Ft. Rear Blade - Limited Category I Continued

THIS PAGE INTENTIONALLY LEFT BLANK

### Landscaping

## RB2072 - 6 Ft. Standard Duty Rear Blade

**Equipment for Base Machine** 

3-Point Hitch: Category I
Shipping Weight:
660 lbs. (Quantity 2)
Moldboard Height: 14 In.
Moldboard Length: 72 In.
Moldboard Thickness: 1/4 In.
Duty: Standard Duty
Cutting Edge:
1/2 In. x 6 In. Reversible
Angle: 360 Degrees
Angle - Reverse:
0 and 15 Degrees Each Side
Approximate Operating Weight: 285 lb.
Offset: 12 In. Left or Right

Tractor HP: 23 to 55 HP
Tilt: 3-Positions
Angle - Forward:
0, 15, and 30 Degrees Each Side
Skid Shoe Bundle: Optional
End Plate Bundle: Optional
Assembly/Set-Up Time:
15 Minutes (Approximate)

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1282XF		RB2072 - 6 Ft. Standard Duty Rear Blade Order in multiples of two.	857.00
		OPERATOR'S MANUAL AND DECALS	
9200		French Operator's Manual and Decal Kit (RB20 Series)	49.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5WS346765	Miscellaneous End Plate Kit (RB2060, RB2072 and RB2084)	168.48
	5WS101376	French Operator's Manual and Decal Kit (RB20 and RB20L Series)	54.88
	5WS346745	Skid Shoes Kit (RB2060, RB2072 and RB2084)	258.12

Bid Term: 2/20/19 - 2/19/21

# RB2072 - 6 Ft. Standard Duty Rear Blade Continued

THIS	S PA	AGF.	INTFI	NTIC	DNALLY	I FFT	BLAN	<
1 1 111		<b>'</b> O'						

### Landscaping

### RB2084 - 7 Ft. Standard Duty Rear Blade

**Equipment for Base Machine** 

3-Point Hitch: Category I
Tractor HP: 27 to 55 HP
Tilt: 3 Position
Shipping Weight:
700 lbs. (Quantity 2)
Offset:
12 Inches, Left or Right
Moldboard Thickness: 1/4 In.
Moldboard Length: 84 In.
Moldboard Height: 14 In.
Duty: Standard Duty
Cutting Edge:
1/2 In. x 6 In. Reversible
Approximate Operating Weight: 305 lbs.
Angle: 360 Degrees

Angle - Reverse:
0 and 15 Degrees Each Side
Angle - Forward:
0, 15, and 30 Degrees Each Side
Skid Shoe Bundle: Optional
End Plate Bundle: Optional
Assembly/Set-Up Time:
15 Minutes (Approximate)

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1283XF		RB2084 - 7 Ft. Standard Duty Rear Blade Order in multiples of two.	935.00
		OPERATOR'S MANUAL AND DECALS	
9200		French Operator's Manual and Decal Kit (RB20 Series)	49.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5WS346765	Miscellaneous End Plate Kit (RB2060, RB2072 and RB2084)	168.48
	5WS101376	French Operator's Manual and Decal Kit (RB20 and RB20L Series)	54.88
	5WS346745	Skid Shoes Kit (RB2060, RB2072 and RB2084)	258.12

Bid Term: 2/20/19 - 2/19/21

# RB2084 - 7 Ft. Standard Duty Rear Blade Continued

THIS PAGE INTENTIONALLY LEFT BLANK

**List Price** 

## FRONTIER PRODUCTS

### Landscaping

### RB2160 - 5 Ft. Medium Duty Rear Blade

**Equipment for Base Machine** 

Hitch: 3-Point Category I and iMatch
Working Width: 60 In.
Working Weight: 392 lbs.
Tractor HP:
65 HP (Maximum - 2WD)
60 HP (Maximum - 4WD)
Tilt: 3 Positions,
Up to 22 degrees Up or Down
Shipping Weight: 426 lbs.
Angle/Pivot: 360 Degrees
Moldboard Height: 17 In.
Moldboard Thickness: 1/4 In.
Duty: Medium Duty
Cutting Edge:
1/2 In. x 6 In. Reversible

Assembly/Set-Up Time: 60 Minutes
Angle - Forward:
3 Positions, Up to 53 Degrees Each Side
Angle - Reverse:
3 Positions, Up to 53 Degrees Each Side
Skid Shoes (Pair): Optional
End Plates (Pair): Optional
Parking Stand: Standard
Offset: 6 In. or 12 In. Left or Right

	Attachment		Suggested
Code	Identifier	Description	USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1301XF		RB2160 - 5 Ft. Medium Duty Rear Blade	1,179.00
		ATTACHMENTS FOR FIELD CONVERSION	

Miscellaneous

5TMC6200001 End Plates - Pair (RB21 Series) 113.12

5TMC6100001 Skid Shoes - Pair (RB21 Series) 125.44

# RB2160 - 5 Ft. Medium Duty Rear Blade Continued

THIS PAGE INTENTIONALLY LEFT BLANK

List Price

113.12

125.44

Bid Term: 2/20/19 - 2/19/21

#### FRONTIER PRODUCTS

#### Landscaping

#### RB2172 - 6 Ft. Medium Duty Rear Blade

**Equipment for Base Machine** 

Hitch: 3-Point Category I and iMatch
Working Width: 72 In.
Working Weight: 422 lbs.
Tractor HP:
65 HP (Maximum - 2WD)
60 HP (Maximum - 4WD)
Tilt: 3 Positions,
Up to 22 degrees Up or Down
Shipping Weight: 456 lbs.
Angle/Pivot: 360 Degrees
Moldboard Height: 17 In.
Moldboard Thickness: 1/4 In.
Duty: Medium Duty
Cutting Edge:
1/2 In. x 6 In. Reversible

5TMC6200001

5TMC6100001

End Plates - Pair (RB21 Series)

Skid Shoes - Pair (RB21 Series)

Assembly/Set-Up Time: 60 Minutes
Angle - Forward:
3 Positions, Up to 53 Degrees Each Side
Angle - Reverse:
3 Positions, Up to 53 Degrees Each Side
Skid Shoes (Pair): Optional
End Plates (Pair): Optional
Parking Stand: Standard
Offset: 6 In. or 12 In. Left or Right

Code	Attachment Identifier	Description	Suggested USD (\$)
		2.000 <b>.</b>	2 3 2 (4)
		Select One Code From Each Required Category	
		BASE MACHINE	
1302XF		RB2172 - 6 Ft. Medium Duty Rear Blade	1,250.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous	

## RB2172 - 6 Ft. Medium Duty Rear Blade Continued

THIS PAGE INTENTIONALLY LEFT BLANK

#### Landscaping

#### RB2184 - 7 Ft. Medium Duty Rear Blade

**Equipment for Base Machine** 

Hitch: 3-Point Category I and iMatch
Working Width: 84 In.
Working Weight: 448 lbs.
Tractor HP:
65 HP (Maximum - 2WD)
60 HP (Maximum - 4WD)
Tilt: 3 Positions,
Up to 22 degrees Up or Down
Shipping Weight: 482 lbs.
Angle/Pivot: 360 Degrees
Moldboard Height: 17 In.
Moldboard Thickness: 1/4 In.
Duty: Medium Duty
Cutting Edge:
1/2 In. x 6 In. Reversible

Assembly/Set-Up Time: 60 Minutes Angle - Forward: 3 Positions, Up to 53 Degrees Each Side Angle - Reverse: 3 Positions, Up to 53 Degrees Each Side Skid Shoes (Pair): Optional End Plates (Pair): Optional Parking Stand: Standard Offset - 6 In. or 12 In. Left or Right

Code	Attachment Identifier	Description	List Price Suggested USD (\$)

Select One Code From Each Required Category

#### **BASE MACHINE**

1303XF RB2184 - 7 Ft. Medium Duty Rear Blade 1,325.00

#### ATTACHMENTS FOR FIELD CONVERSION

Miscellaneous

5TMC6200001 End Plates - Pair (RB21 Series) 113.12

5TMC6100001 Skid Shoes - Pair (RB21 Series) 125.44

## RB2184 - 7 Ft. Medium Duty Rear Blade Continued

THIS PAGE INTENTIONALLY LEFT BLANK

#### Landscaping

#### RB2196 - 8 Ft. Medium Duty Rear Blade

**Equipment for Base Machine** 

Hitch: 3-Point Category I and iMatch
Working Width: 96 In.
Working Weight: 476 lbs.
Tractor HP:
65 HP (Maximum - 2WD)
60 HP (Maximum - 4WD)
Tilt: 3 Positions,
Up to 22 degrees Up or Down
Shipping Weight: 510 lbs.
Angle/Pivot: 360 Degrees
Moldboard Height: 17 In.
Moldboard Thickness: 1/4 In.
Duty: Medium Duty
Cutting Edge:
1/2 In. x 6 In. Reversible

Assembly/Set-Up Time: 60 Minutes Angle - Forward: 3 Positions, Up to 53 Degrees Each Side Angle - Reverse: 3 Positions, Up to 53 Degrees Each Side Skid Shoes (Pair): Optional End Plates (Pair): Optional Parking Stand: Standard Offset - 6 In. or 12 In. Left or Right

Code	Attachment Identifier	Description	List Price Suggested USD (\$)

Select One Code From Each Required Category

#### **BASE MACHINE**

1304XF RB2196 - 8 Ft. Medium Duty Rear Blade 1,384.00

#### ATTACHMENTS FOR FIELD CONVERSION

Miscellaneous

5TMC6200001 End Plates - Pair (RB21 Series) 113.12

5TMC6100001 Skid Shoes - Pair (RB21 Series) 125.44

## RB2196 - 8 Ft. Medium Duty Rear Blade Continued

THIS PAGE INTENTIONALLY LEFT BLANK

#### Landscaping

#### RB2160H - 5 Ft. Medium Duty Hydraulic Rear Blade

**Equipment for Base Machine** 

Hitch: 3-Point Category I and iMatch
Working Width: 60 in. (1,524 mm)
Working Weight: 379 lbs. (171.9 kg)
Tractor HP:
50 HP (37.3 kW) (Maximum - 2WD)
45 HP (33.6 kW) (Maximum - 4WD)
Tilt: 3 Positions,
Up to 20 degrees Up or Down
Shipping Weight: 459 lbs. (208.2 kg)
Angle/Pivot: 360 Degrees
Moldboard Height: 15 in. (381 mm)
Moldboard Thickness: 1/4 in. 6.35 mm)
Duty: Medium Duty
Cutting Edge:
1/2 x 6 in. Reversible (12.7 x 152.4 mm)

Assembly/Set-Up Time: 60 Minutes
Angle - Forward:
Hydraulic, Up to 40 Degrees Each Side
Angle - Reverse:
Hydraulic, Up to 40 Degrees Each Side
Skid Shoes (Pair): Optional
End Plates (Pair): Optional
Parking Stand: Standard
Offset: 6 in. or 12 in. Left or Right (152.4 mm or 304.8 mm)

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1551XF		RB2160H - 5 Ft. Medium Duty Hydraulic Rear Blade Includes one cylinder.	1,533.00
		END PLATES	
9010		End Plates (Pair)	76.00
		SKID SHOES	
9000		Skid Shoes (Pair)	79.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5TMKMCN021	<b>Miscellaneous</b> End Plates (Pair)	85.12
	5TMKHCN101	Hydraulic Cylinder Kit Includes one cylinder.	658.80
	5TMKMCN022	Skid Shoes (Pair)	88.48

## RB2160H - 5 Ft. Medium Duty Hydraulic Rear Blade Continued

THIS PAGE INTENTIONALLY LEFT BLANK

#### Landscaping

#### RB2172H - 6 Ft. Medium Duty Hydraulic Rear Blade

**Equipment for Base Machine** 

Hitch: 3-Point Category I and iMatch
Working Width: 72 in. (1,828.8 mm)
Working Weight: 405 lbs. (183.7 kg)
Tractor HP:
50 HP (37.3 kW) (Maximum - 2WD)
45 HP (33.6 kW) (Maximum - 4WD)
Tilt: 3 Positions,
Up to 20 degrees Up or Down
Shipping Weight: 489 lbs. (221.8 kg)
Angle/Pivot: 360 Degrees
Moldboard Height: 15 in. (381 mm)
Moldboard Thickness: 1/4 in. 6.35 mm)
Duty: Medium Duty
Cutting Edge:
1/2 x 6 in. Reversible (12.7 x 152.4 mm)

Assembly/Set-Up Time: 60 Minutes
Angle - Forward:
Hydraulic, Up to 40 Degrees Each Side
Angle - Reverse:
Hydraulic, Up to 40 Degrees Each Side
Skid Shoes (Pair): Optional
End Plates (Pair): Optional
Parking Stand: Standard
Offset: 6 in. or 12 in. Left or Right (152.4 mm or 304.8 mm)

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1552XF		RB2172H - 6 Ft. Medium Duty Hydraulic Rear Blade Includes one cylinder.	1,643.00
		END PLATES	
9010		End Plates (Pair)	76.00
		SKID SHOES	
9000		Skid Shoes (Pair)	79.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5TMKMCN021	Miscellaneous End Plates (Pair)	85.12
	5TMKHCN101	Hydraulic Cylinder Kit Includes one cylinder.	658.80
	5TMKMCN022	Skid Shoes (Pair)	88.48

## RB2172H - 6 Ft. Medium Duty Hydraulic Rear Blade Continued

THIS PAGE INTENTIONALLY LEFT BLANK

#### Landscaping

#### RB2184H - 7 Ft. Medium Duty Hydraulic Rear Blade

**Equipment for Base Machine** 

Hitch: 3-Point Category I and iMatch
Working Width: 84 in. (2,133.6 mm)
Working Weight: 431 lbs. (195.5 kg)
Tractor HP:
50 HP (37.3 kW) (Maximum - 2WD)
45 HP (33.6 kW) (Maximum - 4WD)
Tilt: 3 Positions,
Up to 20 degrees Up or Down
Shipping Weight: 515 lbs. (233.6 kg)
Angle/Pivot: 360 Degrees
Moldboard Height: 15 in. (381 mm)
Moldboard Thickness: 1/4 in. 6.35 mm)
Duty: Medium Duty
Cutting Edge:
1/2 x 6 in. Reversible (12.7 x 152.4 mm)

Assembly/Set-Up Time: 60 Minutes
Angle - Forward:
Hydraulic, Up to 40 Degrees Each Side
Angle - Reverse:
Hydraulic, Up to 40 Degrees Each Side
Skid Shoes (Pair): Optional
End Plates (Pair): Optional
Parking Stand: Standard
Offset: 6 in. or 12 in. Left or Right (152.4 mm or 304.8 mm)

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1553XF		RB2184H - 7 Ft. Medium Duty Hydraulic Rear Blade Includes one cylinder.	1,714.00
		END PLATES	
9010		End Plates (Pair)	76.00
		SKID SHOES	
9000		Skid Shoes (Pair)	79.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5TMKMCN021	<b>Miscellaneous</b> End Plates (Pair)	85.12
	5TMKHCN101	Hydraulic Cylinder Kit Includes one cylinder.	658.80
	5TMKMCN022	Skid Shoes (Pair)	88.48

## RB2184H - 7 Ft. Medium Duty Hydraulic Rear Blade Continued

THIS PAGE INTENTIONALLY LEFT BLANK

#### Landscaping

#### RB2196H - 8Ft. Medium Duty Hydraulic Rear Blade

**Equipment for Base Machine** 

Hitch: 3-Point Category I and iMatch
Working Width: 96 in. (2,438.4 mm)
Working Weight: 456 lbs. (206.8 kg)
Tractor HP:
50 HP (37.3 kW) (Maximum - 2WD)
45 HP (33.6 kW) (Maximum - 4WD)
Tilt: 3 Positions,
Up to 20 degrees Up or Down
Shipping Weight: 543 lbs. (246.3 kg)
Angle/Pivot: 360 Degrees
Moldboard Height: 15 in. (381 mm)
Moldboard Thickness: 1/4 in. 6.35 mm)
Duty: Medium Duty
Cutting Edge:
1/2 x 6 in. Reversible (12.7 x 152.4 mm)

Assembly/Set-Up Time: 60 Minutes
Angle - Forward:
Hydraulic, Up to 40 Degrees Each Side
Angle - Reverse:
Hydraulic, Up to 40 Degrees Each Side
Skid Shoes (Pair): Optional
End Plates (Pair): Optional
Parking Stand: Standard
Offset: 6 in. or 12 in. Left or Right (152.4 mm or 304.8 mm)

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	]
		BASE MACHINE	
1554XF		RB2196H - 8Ft. Medium Duty Hydraulic Rear Blade Includes one cylinder.	1,822.00
		END PLATES	
9010		End Plates (Pair)	76.00
		SKID SHOES	
9000		Skid Shoes (Pair)	79.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5TMKMCN021	<b>Miscellaneous</b> End Plates (Pair)	85.12
	5TMKHCN101	Hydraulic Cylinder Kit Includes one cylinder.	658.80
	5TMKMCN022	Skid Shoes (Pair)	88.48

## RB2196H - 8Ft. Medium Duty Hydraulic Rear Blade Continued

ΤI	ΗІ	S	PA	GE	INT	ΈN	JTI(	ANC	LLY I	LEFT	BLA	١N٨	Κ

140.00

#### FRONTIER PRODUCTS

#### Landscaping

#### RB2272 - 6 Ft. Medium Plus Rear Blade

**Equipment for Base Machine** 

Hitch:
3 Point Category II and
ASAE Category II Quick Coupler
Tractor HP:
80 HP (Maximum - 2WD)
70 HP (Maximum - 4WD)
Shipping Weight: 795 lbs.
Moldboard Height: 19 In.
Duty: Medium Plus Duty
Assembly/Set-Up Time: 120 Minutes
Cutting Edge:
1/2 In. x 6 In. Reversible
Angle/Pivot: 360 Degrees
Moldboard Thickness: 1/4 In.
Moldboard Thickness: 1/4 In.
Moldboard Thickness: 1/4 In.
Approximate Operating Weight: 738 lb.
Offset: 9 In. or 18 In. Left or Right

5TMC6100002

Skid Shoes - Pair

Tilt: 3 Positions, Up to 23 Degrees, Up or Down Angle-Forward: 3 Positions, Up to 45 Degrees Each Side Angle-Reverse: 3 Positions, Up to 45 Degrees Each Side Skid Shoes (Pair): Optional End Plates (Pair): Optional Hydraulic Offset Kit: Optional (Hoses and Fittings Included) Parking Stand: Standard

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1311XF		RB2272 - 6 Ft. Medium Plus Rear Blade	2,264.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5TMC6200003	Miscellaneous End Plates - Pair	150.08

### RB2272 - 6 Ft. Medium Plus Rear Blade Continued

THIS PAGE INTENTIONALLY LEFT BLANK

03 December	2018 l	JS &	Canada

#### Landscaping

#### RB2284 - 7 Ft. Medium Plus Rear Blade

**Equipment for Base Machine** 

Hitch:
3 Point Category II and
ASAE Category II Quick Coupler
Tractor HP:
80 HP (Maximum - 2WD)
70 HP (Maximum - 4WD)
Shipping Weight: 812 lbs.
Moldboard Height: 19 In.
Duty: Medium Plus Duty
Assembly/Set-Up Time: 120 Minutes
Cutting Edge:
1/2 In. x 6 In. Reversible
Angle/Pivot: 360 Degrees
Moldboard Thickness: 1/4 In.
Moldboard Length: 84 In.
Approximate Operating Weight: 755 lbs.
Offset: 9 In. or 18 In. Left or Right

Tilt: 3 Positions,
Up to 23 Degrees, Up or Down
Angle-Forward:
3 Positions, Up to 45 Degrees Each Side
Angle-Reverse:
3 Positions, Up to 45 Degrees Each Side
Skid Shoes (Pair): Optional
End Plates (Pair): Optional
Hydraulic Offset Kit:
Optional (Hoses and Fittings Included)
Parking Stand: Standard

Code	Attachment Identifier	Description	List Price Suggested USD (\$)

Select One Code From Each Required Category

#### **BASE MACHINE**

10101/5	DDOOR TEN MILL DI D. D. L.	0.440.00
1312XF	RB2284 - 7 Ft. Medium Plus Rear Blade	2.449.00

#### ATTACHMENTS FOR FIELD CONVERSION

Miscellaneous

5TMC6200003 End Plates - Pair 150.08

5TMC6300073 Hydraulic Cylinder Kit 564.84

Offset or Tilt - Includes 1 Cylinder (RB23 Series).

5TMC6100002 Skid Shoes - Pair 140.00

### RB2284 - 7 Ft. Medium Plus Rear Blade Continued

THIS PAGE INTENTIONALLY LEFT BLANK

. . . . . .

#### FRONTIER PRODUCTS

#### Landscaping

#### RB2296 - 8 Ft. Medium Plus Rear Blade

**Equipment for Base Machine** 

Hitch:
3 Point Category II and
ASAE Category II Quick Coupler
Tractor HP:
80 HP (Maximum - 2WD)
70 HP (Maximum - 4WD)
Shipping Weight: 829 lbs.
Moldboard Height: 19 In.
Duty: Medium Plus Duty
Assembly/Set-Up Time: 120 Minutes
Cutting Edge:
1/2 In. x 6 In. Reversible
Angle/Pivot: 360 Degrees
Moldboard Thickness: 1/4 In.
Moldboard Length: 96 In.
Approximate Operating Weight: 772 lbs.
Offset: 9 In. or 18 In. Left or Right

Tilt: 3 Positions, Up to 23 Degrees, Up or Down Angle-Forward: 3 Positions, Up to 45 Degrees Each Side Angle-Reverse: 3 Positions, Up to 45 Degrees Each Side Skid Shoes (Pair): Optional End Plates (Pair): Optional Hydraulic Offset Kit: Optional (Hoses and Fittings Included) Parking Stand: Standard

		ATTACHMENTS FOR FIELD CONVERSION	
1313XF		RB2296 - 8 Ft. Medium Plus Rear Blade	2,562.00
		BASE MACHINE	
		Select One Code From Each Required Category	
Code	Attachment Identifier	Description	Suggested USD (\$)

5TMC6200003	Miscellaneous End Plates - Pair	150.08
5TMC6300073	Hydraulic Cylinder Kit Offset or Tilt - Includes 1 Cylinder (RB23 Series).	564.84
5TMC6100002	Skid Shoes - Pair	140.00

### RB2296 - 8 Ft. Medium Plus Rear Blade Continued

ΤI	ΗІ	S	PA	GE	INT	ΈN	JTI(	ANC	LLY I	LEFT	BLA	١N٨	Κ

#### Landscaping

#### RB2307 - 7 Ft. Heavy Duty Rear Blade

**Equipment for Base Machine** 

Hitch:
3-Point Category II and
ASAE Category II Quick Coupler
Tractor HP:
120 HP (Maximum - 2WD)
110 HP (Maximum - 4WD)
Tilt: 3 Positions,
Up to 23 Degrees Up or Down
Shipping Weight: 1117 lbs.
Offset: 9 In. or 18 In. Left or Right
Moldboard Thickness: 5/16 In.
Moldboard Length: 84 In.
Moldboard Height: 19 In.
Duty: Heavy Duty
Cutting Edge:
1/2 In. x 6 In. Reversible
Approximate Operating Weight: 1060 lbs.
Assembly/Set-Up Time:

120 Minutes (Approximate)
Angle: 360 Degrees
Angle - Forward:
3 Positions, Up to 45 Degrees Each Side
Angle - Reverse:
3 Positions, Up to 45 Degrees Each Side
Skid Shoes (Pair): Optional
End Plates (Pair): Optional
Parking Stand: Standard
Hydraulic Tilt, Angle and Offset Kits:
Optional (Hoses and Fittings Included)

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1321XF		RB2307 - 7 Ft. Heavy Duty Rear Blade	2,783.00
		HYDRAULIC KITS	
1000		Manual Kit	In Base Price
1010		Hydraulic Cylinder Kit, Angle - Offset - Tilt <i>Includes 3 cylinders</i> .	1,482.00
		HYDRAULIC KITS	
9020		Hydraulic Diverter Kit	471.00
		END PLATES	
9010		End Plates (Pair)	134.00
		SKID SHOES	
9000		Skid Shoes (Pair)	125.00
		OPERATOR'S MANUAL AND DECALS	
9200		French Operator's Manual and Decal Kit (RB23 Series)	No Charge
		ATTACHMENTS FOR FIELD CONVERSION	
	5TMC6200003	Miscellaneous End Plates - Pair	150.08

5TMC0040025K French Operator's Manual and Decal Kit

Rear Blades RB2307, RB2308, RB2309 and RB2310.

7.20

### RB2307 - 7 Ft. Heavy Duty Rear Blade

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
	5TMC6300073	ATTACHMENTS FOR FIELD CONVERSIONContinued Hydraulic Cylinder Kit Offset or Tilt - Includes 1 Cylinder (RB23 Series).	564.84
	5TMC6300083	Hydraulic Cylinder Kit - Angle - Includes 1 Cylinder (RB23 Series)	578.88
	5TMC6300051	Hydraulic Diverter Kit (RB23 Series)	508.68
	5TMC6100002	Skid Shoes - Pair	140.00

Liet Dries

#### FRONTIER PRODUCTS

#### Landscaping

#### RB2308 - 8 Ft. Heavy Duty Rear Blade

**Equipment for Base Machine** 

Hitch:
3-Point Category II and
ASAE Category II Quick Coupler
Tractor HP:
120 HP (Maximum - 2WD)
110 HP (Maximum - 4WD)
Tilt: 3 Positions,
Up to 23 Degrees Up or Down
Shipping Weight: 1196 lbs.
Offset: 9 In. or 18 In. Left or Right
Moldboard Thickness: 5/16 In.
Moldboard Length: 96 In.
Moldboard Height: 19 In.
Duty: Heavy Duty
Cutting Edge:
1/2 In. x 6 In. Reversible
Approximate Operating Weight: 1139 lbs.
Assembly/Set-Up Time:

120 Minutes (Approximate)
Angle: 360 Degrees
Angle - Forward:
3 Positions, Up to 45 Degrees Each Side
Angle - Reverse:
3 Positions, Up to 45 Degrees Each Side
Skid Shoes (Pair): Optional
End Plates (Pair): Optional
Parking Stand: Standard
Hydraulic Tilt, Angle and Offset Kits:
Optional (Hoses and Fittings Included)

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	]
		BASE MACHINE	
1322XF		RB2308 - 8 Ft. Heavy Duty Rear Blade	3,028.00
		HYDRAULIC KITS	
1000		Manual Kit	In Base Price
1010		Hydraulic Cylinder Kit, Angle - Offset - Tilt <i>Includes 3 cylinders</i> .	1,482.00
		HYDRAULIC KITS	
9020		Hydraulic Diverter Kit	471.00
		END PLATES	
9010		End Plates (Pair)	134.00
		SKID SHOES	
9000		Skid Shoes (Pair)	125.00
		OPERATOR'S MANUAL AND DECALS	
9200		French Operator's Manual and Decal Kit (RB23 Series)	No Charge
		ATTACHMENTS FOR FIELD CONVERSION	
	5TMC6200003	Miscellaneous End Plates - Pair	150.08

5TMC0040025K French Operator's Manual and Decal Kit

Rear Blades RB2307, RB2308, RB2309 and RB2310.

7.20

### RB2308 - 8 Ft. Heavy Duty Rear Blade

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
	5TMC6300073	ATTACHMENTS FOR FIELD CONVERSIONContinued Hydraulic Cylinder Kit Offset or Tilt - Includes 1 Cylinder (RB23 Series).	564.84
	5TMC6300083	Hydraulic Cylinder Kit - Angle - Includes 1 Cylinder (RB23 Series)	578.88
	5TMC6300051	Hydraulic Diverter Kit (RB23 Series)	508.68
	5TMC6100002	Skid Shoes - Pair	140.00

#### Landscaping

#### RB2309 - 9 Ft. Heavy Duty Rear Blade

**Equipment for Base Machine** 

Hitch:
3-Point Category II and
ASAE Category II Quick Coupler
Tractor HP:
120 HP (Maximum - 2WD)
110 HP (Maximum - 4WD)
Tilt: 3 Positions,
Up to 23 Degrees Up or Down
Shipping Weight: 1297 lbs.
Offset: 9 In. or 18 In. Left or Right
Moldboard Thickness: 5/16 In.
Moldboard Length: 108 In.
Moldboard Height: 19 In.
Duty: Heavy Duty
Cutting Edge:
1/2 In. x 6 In. Reversible
Approximate Operating Weight: 1240 lbs.
Assembly/Set-Up Time:

120 Minutes (Approximate)
Angle: 360 Degrees
Angle - Forward:
3 Positions, Up to 45 Degrees Each Side
Angle - Reverse:
3 Positions, Up to 45 Degrees Each Side
Skid Shoes (Pair): Optional
End Plates (Pair): Optional
Parking Stand: Standard
Hydraulic Tilt, Angle and Offset Kits:
Optional (Hoses and Fittings Included)

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1323XF		RB2309 - 9 Ft. Heavy Duty Rear Blade	3,171.00
		HYDRAULIC KITS	
1000		Manual Kit	In Base Price
1010		Hydraulic Cylinder Kit, Angle - Offset - Tilt Includes 3 cylinders.	1,482.00
		HYDRAULIC KITS	
9020		Hydraulic Diverter Kit	471.00
		END PLATES	
9010		End Plates (Pair)	134.00
		SKID SHOES	
9000		Skid Shoes (Pair)	125.00
		OPERATOR'S MANUAL AND DECALS	
9200		French Operator's Manual and Decal Kit (RB23 Series)	No Charge
		ATTACHMENTS FOR FIELD CONVERSION	
	5TMC6200003	Miscellaneous End Plates - Pair	150.08

5TMC0040025K French Operator's Manual and Decal Kit

Rear Blades RB2307, RB2308, RB2309 and RB2310.

7.20

### RB2309 - 9 Ft. Heavy Duty Rear Blade

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
	5TMC6300073	ATTACHMENTS FOR FIELD CONVERSIONContinued Hydraulic Cylinder Kit Offset or Tilt - Includes 1 Cylinder (RB23 Series).	564.84
	5TMC6300083	Hydraulic Cylinder Kit - Angle - Includes 1 Cylinder (RB23 Series)	578.88
	5TMC6300051	Hydraulic Diverter Kit (RB23 Series)	508.68
	5TMC6100002	Skid Shoes - Pair	140.00

Bid Term: 2/20/19 - 2/19/21

#### Landscaping

#### RB2310 - 10 Ft. Heavy Duty Rear Blade

**Equipment for Base Machine** 

Hitch:
3-Point Category II and
ASAE Category II Quick Coupler
Tractor HP:
120 HP (Maximum - 2WD)
110 HP (Maximum - 4WD)
Tilt: 3 Positions,
Up to 23 Degrees Up or Down
Shipping Weight: 1357 lbs.
Offset: 9 In. or 18 In. Left or Right
Moldboard Thickness: 5/16 In.
Moldboard Length: 120 In.
Moldboard Height: 19 In.
Duty: Heavy Duty
Cutting Edge:
1/2 In. x 6 In. Reversible
Approximate Operating Weight: 1300 lbs.
Assembly/Set-Up Time:

120 Minutes (Approximate)
Angle: 360 Degrees
Angle - Forward:
3 Positions, Up to 45 Degrees Each Side
Angle - Reverse:
3 Positions, Up to 45 Degrees Each Side
Skid Shoes (Pair): Optional
End Plates (Pair): Optional
Parking Stand: Standard
Hydraulic Tilt, Angle and Offset Kits:
Optional (Hoses and Fittings Included)

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1324XF		RB2310 - 10 Ft. Heavy Duty Rear Blade	3,264.00
		HYDRAULIC KITS	
1000		Manual Kit	In Base Price
1010		Hydraulic Cylinder Kit, Angle - Offset - Tilt <i>Includes 3 cylinders</i> .	1,482.00
		HYDRAULIC KITS	
9020		Hydraulic Diverter Kit	471.00
		END PLATES	
9010		End Plates (Pair)	134.00
		SKID SHOES	
9000		Skid Shoes (Pair)	125.00
		OPERATOR'S MANUAL AND DECALS	
9200		French Operator's Manual and Decal Kit (RB23 Series)	No Charge
		ATTACHMENTS FOR FIELD CONVERSION	
	5TMC6200003	Miscellaneous End Plates - Pair	150.08

5TMC0040025K French Operator's Manual and Decal Kit

Rear Blades RB2307, RB2308, RB2309 and RB2310.

7.20

### RB2310 - 10 Ft. Heavy Duty Rear Blade

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
	5TMC6300073	ATTACHMENTS FOR FIELD CONVERSIONContinued Hydraulic Cylinder Kit Offset or Tilt - Includes 1 Cylinder (RB23 Series).	564.84
	5TMC6300083	Hydraulic Cylinder Kit - Angle - Includes 1 Cylinder (RB23 Series)	578.88
	5TMC6300051	Hydraulic Diverter Kit (RB23 Series)	508.68
	5TMC6100002	Skid Shoes - Pair	140.00

**List Price** 

#### FRONTIER PRODUCTS

#### Landscaping

#### RB2408 - 8 Ft. Heavy Plus Rear Blade

**Equipment for Base Machine** 

Hitch:

3-Point Category II, III and
ASAE Quick Coupler Category II, III
Tractor HP:

160 HP (Maximum - 2WD)
145 HP (Maximum - 4WD)
Tilt: 2 Positions,
Up to 15 Degrees, Up or Down
Shipping Weight: 1554 lbs.
Offset:

0 In. to 28 In. Right,
0 In. to 26 In. Left
Moldboard Thickness: 5/16 In.
Moldboard Length: 96 In.
Moldboard Height: 19 In.
Duty: Heavy Plus Duty
Cutting Edge:
1/2 In. x 6 In. Reversible
Assembly/Set-Up Time:
180 Minutes (Approximate)

Approximate Operating Weight: 1451 lbs.
Angle: 360 Degrees
Angle Forward:
4 Positions, Up to 26 Degrees Right
5 Positions, Up to 38 Degrees Left
Angle Reverse:
4 Positions, Up to 26 Degrees Right
5 Positions, Up to 26 Degrees Right
5 Positions, Up to 38 Degrees Left
Parking Stand: Standard
Skid Shoe Bundle: Optional
End Plate Bundle: Optional
Tailwheel: Optional
Hydraulic Tilt and Offset Kits:
Optional (Hoses and Fittings Included)

Code	Attachment Identifier	Description	Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1331XF		RB2408 - 8 Ft. Heavy Plus Rear Blade	4,918.00
		HYDRAULIC KITS	
1000		Manual Kit Includes quantity 1 hydraulic angle cylinder, mechanical offset link, mechanical tilt link.	In Base Price
1010		Hydraulic Cylinder Kit, Angle - Offset - Tilt <i>Includes 3 cylinders</i> .	1,005.00
		HYDRAULIC KITS	
9020		Hydraulic Diverter Kit	446.00
9030		Hydraulic Relief Kit	725.00
9040		Hydraulic Tailwheel Kit, Single Gauge Wheel	1,201.00
9050		Hydraulic Tailwheel Kit, Dual Gauge Wheel	1,542.00
		SKID SHOES	
9000		Skid Shoes (Pair)	42.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5TMC6200004	Miscellaneous End Plates - Pair (RB24 Series)	160.16
	5TMC6300053	Hydraulic Cylinder Kit - Offset or Angle - Includes 1 Cylinder (RB24 Series)	623.16

### RB2408 - 8 Ft. Heavy Plus Rear Blade

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
	5TMC6300063	ATTACHMENTS FOR FIELD CONVERSIONContinued Hydraulic Cylinder Kit - Tilt - Includes 1 Cylinder (RB24 Series)	444.96
	5TMC6600051	Hydraulic Diverter Kit (RB24 Series)	481.68
	5TMC6600061	Hydraulic Relief Kit (RB24 Series)	783.00
	5TMC6100003	Skid Shoes - Pair (RB24 Series)	47.04
	5TMC6600002	TailWheel Kit - Dual Gauge Wheel - Hydraulic (RB24 Series)	1,665.36
	5TMC6600001	TailWheel Kit - Single Gauge Wheel - Hydraulic (RB24 Series)	1,297.08

**List Price** 

#### FRONTIER PRODUCTS

#### Landscaping

#### RB2409 - 9 Ft. Heavy Plus Rear Blade

**Equipment for Base Machine** 

Hitch:

3-Point Category II, III and
ASAE Quick Coupler Category II, III
Tractor HP:

160 HP (Maximum - 2WD)
145 HP (Maximum - 4WD)
Tilt: 2 Positions,
Up to 15 Degrees, Up or Down
Shipping Weight: 1604 lbs.
Offset:
0 In. to 28 In. Right
0 In. to 26 In. Left
Moldboard Thickness: 5/16 In.
Moldboard Length: 108 In.
Moldboard Height: 19 In.
Duty: Heavy Plus Duty
Cutting Edge:
1/2 In. x 6 In. Reversible
Assembly/Set-Up Time:
180 Minutes (Approximate)

Approximate Operating Weight: 1501 lbs.
Angle: 360 Degrees
Angle Forward:
4 Positions, Up to 26 Degrees Right
5 Positions, Up to 38 Degrees Left
Angle Reverse:
4 Positions, Up to 26 Degrees Right
5 Positions, Up to 26 Degrees Right
5 Positions, Up to 38 Degrees Left
Parking Stand: Standard
Skid Shoe Bundle: Optional
End Plate Bundle: Optional
Tailwheel: Optional
Hydraulic Tilt and Offset Kits:
Optional (Hoses and Fittings Included)

Code	Attachment Identifier	Description	Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1332XF		RB2409 - 9 Ft. Heavy Plus Rear Blade	5,017.00
		HYDRAULIC KITS	
1000		Manual Kit Includes quantity 1 hydraulic angle cylinder, mechanical offset link, mechanical tilt link.	In Base Price
1010		Hydraulic Cylinder Kit, Angle - Offset - Tilt <i>Includes 3 cylinders</i> .	1,005.00
		HYDRAULIC KITS	
9020		Hydraulic Diverter Kit	446.00
9030		Hydraulic Relief Kit	725.00
9040		Hydraulic Tailwheel Kit, Single Gauge Wheel	1,201.00
9050		Hydraulic Tailwheel Kit, Dual Gauge Wheel	1,542.00
		SKID SHOES	
9000		Skid Shoes (Pair)	42.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5TMC6200004	<b>Miscellaneous</b> End Plates - Pair (RB24 Series)	160.16
	5TMC6300053	Hydraulic Cylinder Kit - Offset or Angle - Includes 1 Cylinder (RB24 Series)	623.16

### RB2409 - 9 Ft. Heavy Plus Rear Blade

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
	5TMC6300063	ATTACHMENTS FOR FIELD CONVERSIONContinued Hydraulic Cylinder Kit - Tilt - Includes 1 Cylinder (RB24 Series)	444.96
	5TMC6600051	Hydraulic Diverter Kit (RB24 Series)	481.68
	5TMC6600061	Hydraulic Relief Kit (RB24 Series)	783.00
	5TMC6100003	Skid Shoes - Pair (RB24 Series)	47.04
	5TMC6600002	TailWheel Kit - Dual Gauge Wheel - Hydraulic (RB24 Series)	1,665.36
	5TMC6600001	TailWheel Kit - Single Gauge Wheel - Hydraulic (RB24 Series)	1,297.08

#### Landscaping

#### RB2410 - 10 Ft. Heavy Plus Rear Blade

**Equipment for Base Machine** 

Hitch:

3-Point Category II, III and
ASAE Quick Coupler Category II, III
Tractor HP:

160 HP (Maximum - 2WD)
145 HP (Maximum - 4WD)
Tilt: 2 Positions,
Up to 15 Degrees, Up or Down
Shipping Weight: 1653 lbs.
Offset:
0 In. to 28 In. Right
0 In. to 26 In. Left
Moldboard Thickness: 5/16 In.
Moldboard Length: 120 In.
Moldboard Height: 19 In.
Duty: Heavy Plus Duty
Cutting Edge:
1/2 In. x 6 In. Reversible
Assembly/Set-Up Time:
180 Minutes (Approximate)

Approximate Operating Weight: 1550 lbs.
Angle: 360 Degrees
Angle Forward:
4 Positions, Up to 26 Degrees Right
5 Positions, Up to 38 Degrees Left
Angle Reverse:
4 Positions, Up to 26 Degrees Right
5 Positions, Up to 26 Degrees Right
5 Positions, Up to 38 Degrees Left
Parking Stand: Standard
Skid Shoe Bundle: Optional
End Plates Bundle: Optional
Tailwheel: Optional
Hydraulic Tilt and Offset Kits:
Optional (Hoses and Fittings Included)

Code	Attachment Identifier	Description	List Price Suggested USD (\$)	
		Select One Code From Each Required Category		
		BASE MACHINE		
1333XF		RB2410 - 10 Ft. Heavy Plus Rear Blade	5,126.00	
		HYDRAULIC KITS		
1000		Manual Kit Includes quantity 1 hydraulic angle cylinder, mechanical offset link, mechanical tilt link.	In Base Price	
1010		Hydraulic Cylinder Kit, Angle - Offset - Tilt <i>Includes 3 cylinders</i> .	1,005.00	
		HYDRAULIC KITS		
9020		Hydraulic Diverter Kit	446.00	
9030		Hydraulic Relief Kit	725.00	
9040		Hydraulic Tailwheel Kit, Single Gauge Wheel	1,201.00	
9050		Hydraulic Tailwheel Kit, Dual Gauge Wheel	1,542.00	
9000		SKID SHOES Skid Shoes (Pair)	42.00	
		ATTACHMENTS FOR FIELD CONVERSION		
	5TMC6200004	Miscellaneous End Plates - Pair (RB24 Series)	160.16	
	5TMC6300053	Hydraulic Cylinder Kit - Offset or Angle - Includes 1 Cylinder (RB24 Series)	623.16	

### RB2410 - 10 Ft. Heavy Plus Rear Blade

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
	5TMC6300063	ATTACHMENTS FOR FIELD CONVERSIONContinued Hydraulic Cylinder Kit - Tilt - Includes 1 Cylinder (RB24 Series)	444.96
	5TMC6600051	Hydraulic Diverter Kit (RB24 Series)	481.68
	5TMC6600061	Hydraulic Relief Kit (RB24 Series)	783.00
	5TMC6100003	Skid Shoes - Pair (RB24 Series)	47.04
	5TMC6600002	TailWheel Kit - Dual Gauge Wheel - Hydraulic (RB24 Series)	1,665.36
	5TMC6600001	TailWheel Kit - Single Gauge Wheel - Hydraulic (RB24 Series)	1,297.08

Landscaping

#### RB5060 - 5 Ft. Standard Duty Rear Blade

**Equipment for Base Machine** 

3-Point Hitch:
Category I
Working Width: 60 In.
Operational Weight: 308 lbs.
Tractor HP: 20 to 56 HP
Tilt Positions: Seven
Offset: 12 In. Left or Right
Shipping Weight:
674 lbs. for Quantity 2
Pivot: 360 Degrees
Parking Stand: Standard
Packaged 2 Per Crate
Moldboard Height: 14.5 In.
Moldboard Thickness: 1/4 In.

Duty: Standard Duty
Cutting Edge:
3/8 In. x 6 In. Reversible
Assembly/Set-Up Time: 15 Minutes
Angle - Forward:
0, 15 and 30 Degrees Each Side
Angle - Reverse:
0, 15 and 30 Degrees Each Side
Skid Shoes: NA

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1651XF		RB5060 - 5 Ft. Standard Duty Rear Blade Order in multiples of two.	780.00

## RB5060 - 5 Ft. Standard Duty Rear Blade Continued

TΙ	ΗІ	S	PA	GE	INT	ΕN	TIC	DNALL	Y LEF	ТΒІ	LAN	K

#### Landscaping

#### RB5072 - 6 Ft. Standard Duty Rear Blade

**Equipment for Base Machine** 

3-Point Hitch:
Category I
Working Width: 72 In.
Operational Weight: 332 lbs.
Tractor HP: 20 to 56 HP
Tilt Positions: Seven
Offset: 12 In. Left or Right
Shipping Weight:
722 lbs. for Quantity 2
Pivot: 360 Degrees
Parking Stand: Standard
Packaged 2 Per Crate
Moldboard Height: 14.5 In.
Moldboard Thickness: 1/4 In.

Duty: Standard Duty
Cutting Edge:
3/8 In. x 6 In. Reversible
Assembly/Set-Up Time: 15 Minutes
Angle - Forward:
0, 15 and 30 Degrees Each Side
Angle - Reverse:
0, 15 and 30 Degrees Each Side
Skid Shoes: NA

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
10701/5		BASE MACHINE	
1652XF		RB5072 - 6 Ft. Standard Duty Rear Blade  Order in multiples of two.	839.00

# RB5072 - 6 Ft. Standard Duty Rear Blade Continued

THIS	S PA	AGF.	INTFI	NTIC	DNALLY	I FFT	BLANK	(
1 1 11		<b>'</b>						•

#### Landscaping

#### RB5084 - 7 Ft. Standard Duty Rear Blade

**Equipment for Base Machine** 

3-Point Hitch:
Category I
Working Width: 84 In.
Operational Weight: 348 lbs.
Tractor HP: 20 to 56 HP
Tilt Positions: Seven
Offset: 12 In. Left or Right
Shipping Weight:
754 lbs. for Quantity 2
Pivot: 360 Degrees
Parking Stand: Standard
Packaged 2 Per Crate
Moldboard Height: 14.5 In.
Moldboard Thickness: 1/4 In.

Duty: Standard Duty
Cutting Edge:
3/8 In. x 6 In. Reversible
Assembly/Set-Up Time: 15 Minutes
Angle - Forward:
0, 15 and 30 Degrees Each Side
Angle - Reverse:
0, 15 and 30 Degrees Each Side
Skid Shoes: NA

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
1653XF		BASE MACHINE  RB5084 - 7 Ft. Standard Duty Rear Blade  Order in multiples of two.	897.00

# RB5084 - 7 Ft. Standard Duty Rear Blade Continued

Landscaping

#### RB5096 - 8 Ft. Standard Duty Rear Blade

**Equipment for Base Machine** 

3-Point Hitch:
Category I
Working Width: 96 In.
Operational Weight: 380 lbs.
Tractor HP: 20 to 56 HP
Tilt Positions: Seven
Offset: 12 In. Left or Right
Shipping Weight:
818 lbs. for Quantity 2
Pivot: 360 Degrees
Parking Stand: Standard
Packaged 2 Per Crate
Moldboard Height: 14.5 In.
Moldboard Thickness: 1/4 In.

Duty: Standard Duty
Cutting Edge:
3/8 In. x 6 In. Reversible
Assembly/Set-Up Time: 15 Minutes
Angle - Forward:
0, 15 and 30 Degrees Each Side
Angle - Reverse:
0, 15 and 30 Degrees Each Side
Skid Shoes: NA

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1654XF		RB5096 - 8 Ft. Standard Duty Rear Blade Order in multiples of two.	965.00

# RB5096 - 8 Ft. Standard Duty Rear Blade Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Landscaping

#### RB5048L - 4 Ft. Limited Category 1 Economy Duty Rear Blade

**Equipment for Base Machine** 

3-Point Hitch:
Category I
Working Width: 48 In.
Operational Weight: 186 lbs.
Tractor HP: 18 PTO HP Max
Tilt Positions: None
Offset: None
Shipping Weight:
430 lbs. for Quantity 2
Pivot: 360 Degrees
Parking Stand: Standard
Packaged 2 Per Crate
Moldboard Height: 14.5 In.
Moldboard Length: 48 In.
Moldboard Thickness: 1/4 In.
Duty: Economy Duty

Cutting Edge:
3/8 In. x 6 In. Reversible
Assembly/Set-Up Time: 15 Minutes
(Approximate) - Per Pair
Angle - Forward:
0, 15 and 30 Degrees Each Side
Angle - Reverse:
0, 15 and 30 Degrees Each Side
Skid Shoes: NA

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
1751VE		BASE MACHINE  DEFO491 4 Ft Limited Cotegory 4 Fearness Duty Page Blade	540.00
1751XF		RB5048L - 4 Ft. Limited Category 1 Economy Duty Rear Blade Order in multiples of two.	519.00

# RB5048L - 4 Ft. Limited Category 1 Economy Duty Rear Blade Continued

ΤI	ΗІ	S	PA	GE	INT	ΈN	JTI(	ANC	LLY I	LEFT	BLA	١N٨	Κ

Landscaping

### RB5060L - 5 Ft. Limited Category 1 Economy Duty Rear Blade

**Equipment for Base Machine** 

3-Point Hitch:
Category I
Working Width: 60 In.
Operational Weight: 205 lbs.
Tractor HP: 18 PTO HP Max
Tilt Positions: None
Offset: None
Shipping Weight:
468 lbs. for Quantity 2
Pivot: 360 Degrees
Parking Stand: Standard
Packaged 2 Per Crate
Moldboard Height: 14.5 In.
Moldboard Length: 60 In.
Moldboard Thickness: 1/4 In.
Duty: Economy Duty

Cutting Edge:
3/8 In. x 6 In. Reversible
Assembly/Set-Up Time: 15 Minutes
(Approximate) - Per Pair
Angle - Forward:
0, 15 and 30 Degrees Each Side
Angle - Reverse:
0, 15 and 30 Degrees Each Side
Skid Shoes: NA

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
1752XF		BASE MACHINE  RB5060L - 5 Ft. Limited Category 1 Economy Duty Rear Blade  Order in multiples of two.	584.00

# RB5060L - 5 Ft. Limited Category 1 Economy Duty Rear Blade Continued

ΤI	ΗІ	S	PA	GE	INT	ΈN	JTI(	ANC	LLY I	LEFT	BLA	١N٨	Κ

List Drice

#### FRONTIER PRODUCTS

#### Landscaping

#### SW2160 - 60 In. Hydraulic, 300 Series Carrier Loader Mount Rotary Broom

**Equipment for Base Machine** 

Function: Sweeping

Working Width: 60 In. (1,524 mm)

Working Width at Max Angle: 55 In. (1,397 mm) Transport Width: 72 In. (1,828.8 mm)

Operating Weight: 860 lb. (390 kg.) Standard Bristle Material: Poly, 50/50 Steel/Poly

Available as Replacement Brush Speed: 160 RPM

Brush Diameter: 32 In. (812.8 mm) Angle Range: 23 degrees left or right

Hood Thickness: 14 gauge

Side Frame Thickness: 3/16 In. (4.8 mm)

Parking Stands Included

Approximate Set-Up Time: 30 Minutes

Function: Hydraulic Power Unit

Pressure: 2700 psi Flow: 16 gpm

Reservoir Capacity: 15 gal.

System Capacity: 17 gal.

System Features: Pressure relieve valve, filter,

temperature

and oil level gauge, and thermal protection switch

Hoses, Tips, and Brackets included Tractor RPM: 540 RPM

PTO Manufacturer: Comer Parking Stand: Standard Hitch Category: Category Quick Hitch Compatibility:

iMatch Compatible

Approximate Set-Up Time: 120 Minutes

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1591XF		SW2160 - 60 In. Hydraulic, 300 Series Carrier Loader Mount Rotary Broom With Hydraulic Angle Adjustment and HP2025 Hydraulic Power Unit - U.S. Must only be used with HP2025 Hydraulic Power Pack Unit.	13,211.00
		HYDRAULIC POWER UNITS	
1000		HP2025 - Hydraulic Power Unit, 25 HP Includes wiring harness to control the loader mounted implement.	In Base Price
1095		Less Hydraulic Power Unit HP2025	-6,856.00
		OIL COOLER	
2000		Oil Cooler for HP2025 and HP2134 Hydraulic Power Units Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat. Not available with option Code 1095.	In Base Price
2095		Less Oil Cooler	-1,751.00
9000		DUST DEFLECTOR Steel/Rubber Dust Deflector Kit SW2160	278.00
9010		DUST SUPPRESSION KIT SW21 Dust Suppression Kit Includes 60 gallon water tank, electric pump, nozzles, hoses and fittings, electrical harness with switch and installation instructions. Requires the steel/rubber dust deflector kit.	1,952.00

## Landscaping

# SW2160 - 60 In. Hydraulic, 300 Series Carrier Loader Mount Rotary Broom Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		DUST SUPPRESSION KITContinued	
		LAWN DETHATCHING KIT	
9030		SW21 Lawn Dethatching Kit Includes support components, hardware and installation instruction. Gauge wheel kit required. Compatible with dust suppression kit.	417.00
9040		Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors Includes complete wiring harness from battery to switch in the console. Not available with option Code 1095.	97.00
		GAUGE WHEELS	
9020		SW21 Gauge Wheel Kit Includes two pairs 8 In. diameter by 3.5 In. wide solid wheels, mounting brackets and hardware.	667.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5RDF0038	Miscellaneous Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors Includes complete wiring harness from battery to switch in the console.	102.14
	5RDF0036	Oil Cooler for HP2025 and HP2134 Hydraulic Power Units Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.	1,766.36
	5RDF0035	SW21 Dust Suppression Kit Includes 60 gallon water tank, electric pump, nozzles, hoses and fittings, electrical harness with switch and installation instructions. Requires the steel/rubber dust deflector kit.	2,143.92
	5RDF0033	SW21 Gauge Wheel Kit Includes two pairs 8 In. diameter by 3.5 In. wide solid wheels, mounting brackets and hardware.	732.15
	5RDF0034	SW21 Lawn Dethatching Kit Requires gauge wheel kit, compatible with dust suppression kit.	458.00
	5RDF0043	SW2160 50/50 Poly/Steel Wafter Brush Replacement Kit Includes required quantity of wafters to replace entire brush.	563.06
	5RDF0030	SW2160 Dust Deflector Kit	306.97
	5RDF0040	SW2160 Poly Wafter Brush Replacement Kit Includes required quantity of wafters to replace entire brush.	563.06
	5RDF0078	Wiring Harness for HP2025 and HP2134 Hydraulic Power Units to control Loader Mounted Attachment Includes complete wiring harness from switch in the console to 3 cavities connectors for front implements.	147.74

PTO Manufacturer: Comer Parking Stand: Standard Hitch Category: Category I

#### FRONTIER PRODUCTS

#### Landscaping

## SW2172 - 72 In. Hydraulic, 300/400 Series Carrier Loader Mount Rotary Broom Equipment for Base Machine

Function: Sweeping Working Width: 72 In. (1,828.8 mm) Working Width at Max Angle: 66 In. (1,676.4 mm) Transport Width: 84 In. (2,133.6 mm) Operating Weight: 890 lb. (403.7 kg.) Standard Bristle Material: Poly, 50/50 Steel/Poly Available as Replacement Brush Speed: 160 RPM Brush Diameter: 32 In. (812.8 mm) Angle Range: 23 degrees left or right Hood Thickness: 14 gauge Side Frame Thickness: 3/16 In. (4.8 mm) Parking Stands Included Approximate Set-Up Time: 30 Minutes Function: Hydraulic Power Unit Pressure: 2700 psi Flow: 16 gpm Reservoir Capacity: 15 gal. System Capacity: 17 gal. System Features: Pressure relieve valve, filter, temperature and oil level gauge, and thermal protection switch Hoses, Tips, and Brackets included Tractor RPM: 540 RPM

Quick Hitch Compatibility: iMatch Compatible Approximate Set-Up Time: 120 Minutes Optional: Function: Hydraulic Power Unit Pressure: 2700 psi Flow: 16 gpm Reservoir Capacity: 15 gal. System Capacity: 17 gal. System Features: Pressure relieve valve, filter, temperature and oil level gauge, and thermal protection switch Hoses, Tips, and Brackets included Tractor RPM: 540 RPM PTO Manufacturer: Comer Parking Stand: Standard Hitch Category: Category Quick Hitch Compatibility: iMatch Compatible Approximate Set-Up Time: 120 Minutes

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1592XF		SW2172 - 72 In. Hydraulic, 300/400 Series Carrier Loader Mount Rotary Broom With Hydraulic Angle Adjustment and HP2025 Hydraulic Power Unit - U.S. Must be used with either the HP2025 or HP2134 Hydraulic Power Pack Units.	13,487.00
		HYDRAULIC POWER UNITS	
1000		HP2025 - Hydraulic Power Unit, 25 HP Includes wiring harness to control the loader mounted implement.	In Base Price
1095		Less Hydraulic Power Unit HP2025	-6,856.00
1010		HP2134 - Hydraulic Power Unit, 34 HP Includes wiring harness to control the loader mounted implement.	111.00
		OIL COOLER	
2000		Oil Cooler for HP2025 and HP2134 Hydraulic Power Units Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.  Not available with option Code 1095.	In Base Price
2095		Less Oil Cooler	-1,751.00

Bid Term: 2/20/19 - 2/19/21

#### FRONTIER PRODUCTS

## Landscaping

# SW2172 - 72 In. Hydraulic, 300/400 Series Carrier Loader Mount Rotary Broom Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		DUST DEFLECTOR	
9000		Steel/Rubber Dust Deflector Kit SW2172	251.00
9010		<b>DUST SUPPRESSION KIT</b> SW21 Dust Suppression Kit Includes 60 gallon water tank, electric pump, nozzles, hoses and fittings, electrical harness with switch and installation instructions. Requires the steel/rubber dust deflector kit.	1,952.00
		LAWN DETHATCHING KIT	
9030		SW21 Lawn Dethatching Kit Includes support components, hardware and installation instruction. Gauge wheel kit required. Compatible with dust suppression kit.	417.00
9040		Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors Includes complete wiring harness from battery to switch in the console. Not available with option Code 1095.	97.00
9020		GAUGE WHEELS SW21 Gauge Wheel Kit	667.00
		Includes two pairs 8 In. diameter by 3.5 In. wide solid wheels, mounting brackets and hardware.  ATTACHMENTS FOR FIELD CONVERSION	
	5RDF0038	Miscellaneous Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors Includes complete wiring harness from battery to switch in the console.	102.14
	5RDF0036	Oil Cooler for HP2025 and HP2134 Hydraulic Power Units Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.	1,766.36
	5RDF0035	SW21 Dust Suppression Kit Includes 60 gallon water tank, electric pump, nozzles, hoses and fittings, electrical harness with switch and installation instructions. Requires the steel/rubber dust deflector kit.	2,143.92
	5RDF0033	SW21 Gauge Wheel Kit Includes two pairs 8 In. diameter by 3.5 In. wide solid wheels, mounting brackets and hardware.	732.15
	5RDF0034	SW21 Lawn Dethatching Kit Requires gauge wheel kit, compatible with dust suppression kit.	458.00
	5RDF0044	SW2172 50/50 Poly/Steel Wafter Brush Replacement Kit Includes required quantity of wafters to replace entire brush.	664.84
	5RDF0031	SW2172 Dust Deflector Kit	275.78

Bid Term: 2/20/19 - 2/19/21

## FRONTIER PRODUCTS

## Landscaping

# SW2172 - 72 In. Hydraulic, 300/400 Series Carrier Loader Mount Rotary Broom Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
	5RDF0041	ATTACHMENTS FOR FIELD CONVERSIONContinued SW2172 Poly Wafter Brush Replacement Kit Includes required quantity of wafters to replace entire brush.	664.84
	5RDF0078	Wiring Harness for HP2025 and HP2134 Hydraulic Power Units to control Loader Mounted Attachment Includes complete wiring harness from switch in the console to 3 cavities connectors for front implements.	147.74

SW2172 - 72 In. Hydraulic, 300/400 Series Carrier Loader Mount Rotary Broom Continued

THIS PAGE INTENTIONALLY LEFT BLANK

List Balas

#### FRONTIER PRODUCTS

#### Landscaping

#### SW2184 - 84 In. Hydraulic, 400 Series Carrier Loader Mount Rotary Broom

**Equipment for Base Machine** 

Function: Sweeping

Working Width: 84 In. (2,133.6 mm)

Working Width: 64 In. (2,133.0 mm)
Working Width at Max Angle: 77 In. (1,955.8 mm)
Transport Width: 96 In. (2,438.4 mm)
Operating Weight: 920 lb. (417.3 kg.)
Standard Bristle Material: Poly, 50/50 Steel/Poly

Available as Replacement Brush Speed: 160 RPM

Brush Diameter: 32 In. (812.8 mm) Angle Range: 23 degrees left or right

Hood Thickness: 14 gauge

Side Frame Thickness: 3/16 In. (4.8 mm) Parking Stands Included

Approximate Set-Up Time: 30 Minutes Function: Hydraulic Power Unit

Pressure: 2700 psi

Flow: 16 gpm

Reservoir Capacity: 15 gal.

System Capacity: 17 gal.

System Features: Pressure relieve valve, filter,

temperature

and oil level gauge, and thermal protection switch

Hoses, Tips, and Brackets included Tractor RPM: 540 RPM

PTO Manufacturer: Comer Parking Stand: Standard Hitch Category: Category Quick Hitch Compatibility:

iMatch Compatible

Approximate Set-Up Time: 120 Minutes

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1593XF		SW2184 - 84 In. Hydraulic, 400 Series Carrier Loader Mount Rotary Broom With Hydraulic Angle Adjustment and HP2134 Hydraulic Power Unit - U.S. Must only be used with HP2134 Hydraulic Power Pack Unit.	14,247.00
		HYDRAULIC POWER UNITS	
1095		Less Hydraulic Power Unit HP2134	-6,974.00
1010		HP2134 - Hydraulic Power Unit, 34 HP Includes wiring harness to control the loader mounted implement.	In Base Price
		OIL COOLER	
2000		Oil Cooler for HP2025 and HP2134 Hydraulic Power Units Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat. Not available with option Code 1095.	In Base Price
2095		Less Oil Cooler	-1,751.00
9000		DUST DEFLECTOR Steel/Rubber Dust Deflector Kit SW2184	251.00
9010		DUST SUPPRESSION KIT SW21 Dust Suppression Kit Includes 60 gallon water tank, electric pump, nozzles, hoses and fittings, electrical harness with switch and installation instructions. Requires the steel/rubber dust deflector kit.	1,952.00

## Landscaping

# SW2184 - 84 In. Hydraulic, 400 Series Carrier Loader Mount Rotary Broom Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		DUST SUPPRESSION KITContinued	
		LAWN DETHATCHING KIT	
9030		SW21 Lawn Dethatching Kit Includes support components, hardware and installation instruction. Gauge wheel kit required. Compatible with dust suppression kit.	417.00
9040		Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors Includes complete wiring harness from battery to switch in the console. Not available with option Code 1095.	97.00
		GAUGE WHEELS	
9020		SW21 Gauge Wheel Kit Includes two pairs 8 In. diameter by 3.5 In. wide solid wheels, mounting brackets and hardware.	667.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5RDF0038	Miscellaneous Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors Includes complete wiring harness from battery to switch in the console.	102.14
	5RDF0036	Oil Cooler for HP2025 and HP2134 Hydraulic Power Units Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.	1,766.36
	5RDF0035	SW21 Dust Suppression Kit Includes 60 gallon water tank, electric pump, nozzles, hoses and fittings, electrical harness with switch and installation instructions. Requires the steel/rubber dust deflector kit.	2,143.92
	5RDF0033	SW21 Gauge Wheel Kit Includes two pairs 8 In. diameter by 3.5 In. wide solid wheels, mounting brackets and hardware.	732.15
	5RDF0034	SW21 Lawn Dethatching Kit Requires gauge wheel kit, compatible with dust suppression kit.	458.00
	5RDF0045	SW2184 50/50 Poly/Steel Wafter Brush Replacement Kit Includes required quantity of wafters to replace entire brush.	779.76
	5RDF0032	SW2184 Dust Deflector Kit	275.78
	5RDF0042	SW2184 Poly Wafter Brush Replacement Kit Includes required quantity of wafters to replace entire brush.	778.11
	5RDF0078	Wiring Harness for HP2025 and HP2134 Hydraulic Power Units to control Loader Mounted Attachment Includes complete wiring harness from switch in the console to 3 cavities connectors for front implements.	147.74

Bid Term: 2/20/19 - 2/19/21

Drive Chain: ASA 80 Blades/Rotor: 4 Adjustable Offset: 4 In. (101.6 mm)

1357XF

### FRONTIER PRODUCTS

Landscaping

### RT1142 - 42 In. Standard Duty Rotary Tiller

**Equipment for Base Machine** 

Working Width: Tractor PTO HP (Minimum): 10 HP (7.5 kW)
Tractor PTO HP (Minimum): 25 HP (18.6 kW) Blade Shape: C Skid Shoes: Adjustable Rear Door Support: Chain Parking Stand Included Gearbox Speed: Single Rotor Speed: 254 RPM Rotor Flanges: 5

Max Working Depth: 6.3 In. (160 mm) Outside to Outside Width: 46 In. (1,168.4 mm) Driveline Protection: Shear Bolt Tillage Depth Control: Skid Shoes Hitch: Category I, iMatch Compatible Frame: Heavy Duty Single Layer

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	

#### ATTACHMENTS FOR FIELD CONVERSION

Miscellaneous

5MHF20020375 French Kit - For RT1142, RT1149, RT1157, RT1165. and RT1265

RT1142 - 42 In. Standard Duty Rotary Tiller

Includes Operators Manual, Parts Catalog, and Safety Decals.

2,252.00

# RT1142 - 42 In. Standard Duty Rotary Tiller Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Rotor Speed: 208 RPM Rotor Flanges: 6 Drive Chain: ASA 80 Blades/Rotor: 4 Adjustable Offset: 8 In. (203.2 mm)

#### FRONTIER PRODUCTS

#### Landscaping

#### RT1149 - 49 In. Standard Duty Rotary Tiller

**Equipment for Base Machine** 

Working Width:
49 In. (1,244.6 mm)
Tractor PTO Speed: 540 RPM
Tractor PTO HP (Minimum): 20 HP (14.9 kW)
Tractor PTO HP (Minimum): 25 HP (18.6 kW)
Blade Shape: C
Skid Shoes: Adjustable
Rear Door Support: Chain
Parking Stand Included
Gearbox Speed: Single

Max Working Depth:
6.3 In. (160 mm)
Outside to Outside Width:
54 In. (1,371.6 mm)
Driveline Protection: Friction Clutch
Tillage Depth Control: Skid Shoes
Hitch:
Category I, iMatch Compatible
Frame: Heavy Duty Single Layer

List Price
Attachment Suggested
Code Identifier Description USD (\$)

Select One Code From Each Required Category

#### **BASE MACHINE**

1358XF RT1149 - 49 In. Standard Duty Rotary Tiller 2,405.00

#### ATTACHMENTS FOR FIELD CONVERSION

#### Miscellaneous

5MHF20020375 French Kit - For RT1142, RT1149, RT1157, RT1165. and RT1265 Includes Operators Manual, Parts Catalog, and Safety Decals.

68.32

# RT1149 - 49 In. Standard Duty Rotary Tiller Continued

THIS PAGE INTENTIONALLY LEFT BLANK

#### Landscaping

#### RT1157 - 57 In. Standard Duty Rotary Tiller

**Equipment for Base Machine** 

Working Width:

Tractor PTO HP (Maximum): 25 HP (18.6 kW)
Tractor PTO HP (Maximum): 40 HP (29.8 kW)

Blade Shape: C Skid Shoes: Adjustable Rear Door Support: Chain Parking Stand Included Gearbox Speed: Single Rotor Speed: 208 RPM Rotor Flanges: 7

Drive Chain: ASA 80 Blades/Rotor: 6 Adjustable Offset: 19 In. (482.6 mm) Max Working Depth:

7.0 In. (177.8 mm) Outside to Outside Width: 62 In. (1,574.8 mm)

Driveline Protection: Friction Clutch Tillage Depth Control: Skid Shoes

Hitch:

Category I or II, iMatch and Quick Coupler Compatible

Frame:

Heavy Duty and Bent Frame with Extra Thickness Above Rotor

			List Price
	Attachment		Suggested
Code	Identifier	Description	USD (\$)

Select One Code From Each Required Category

#### **BASE MACHINE**

1359XF 2,978.00 RT1157 - 57 In. Standard Duty Rotary Tiller

#### ATTACHMENTS FOR FIELD CONVERSION

#### Miscellaneous

5MHF20020375 French Kit - For RT1142, RT1149, RT1157, RT1165. and RT1265

Includes Operators Manual, Parts Catalog, and Safety Decals.

68.32

# RT1157 - 57 In. Standard Duty Rotary Tiller Continued

THIS PAGE INTENTIONALLY LEFT BLANK

#### Landscaping

#### RT1165 - 65 In. Standard Duty Rotary Tiller

**Equipment for Base Machine** 

Working Width:

65 In. (1,651 mm) Tractor PTO Speed: 540 RPM

Tractor PTO HP (Minimum): 30 HP (22.4 kW)
Tractor PTO HP (Maximum): 40 HP (29.8 kW)

Blade Shape: C Skid Shoes: Adjustable Rear Door Support: Chain Parking Stand Included Gearbox Speed: Single Rotor Speed: 208 RPM Rotor Flanges: 8 Drive Chain: ASA 80 Blades/Rotor: 6 Adjustable Offset: 23 In. (584.2 mm)

Max Working Depth:

7.0 In. (177.8 mm) Outside to Outside Width: 70 In. (1,778 mm) Driveline Protection: Friction Clutch Tillage Depth Control: Skid Shoes Hitch: Category I or II, iMatch and Quick Coupler Compatible Frame:

Heavy Duty and Bent Frame with Extra Thickness Above Rotor

			List Price
	Attachment		Suggested
Code	Identifier	Description	USD (\$)

Select One Code From Each Required Category

#### **BASE MACHINE**

135AXF 3,534.00 RT1165 - 65 In. Standard Duty Rotary Tiller

#### ATTACHMENTS FOR FIELD CONVERSION

#### Miscellaneous

5MHF20020375 French Kit - For RT1142, RT1149, RT1157, RT1165. and RT1265

Includes Operators Manual, Parts Catalog, and Safety Decals.

68.32

# RT1165 - 65 In. Standard Duty Rotary Tiller Continued

THIS PAGE INTENTIONALLY LEFT BLANK

#### Landscaping

#### RT1173 - 73 In. Standard Duty Rotary Tiller

**Equipment for Base Machine** 

Working Width:

Tractor PTO HP (Maximum): 45 HP (33.6 kW)
Tractor PTO HP (Maximum): 60 HP (44.7 kW)

Blade Shape: C Skid Shoes: Adjustable Rear Door Support: Spring Parking Stand Included Gearbox Speed: Single Rotor Speed: 228 RPM Rotor Flanges: 10 Side Drive: Gear

Blades/Rotor: 6

Adjustable Lower Hitches

Max Working Depth:

8.7 In. (221 mm) Outside to Outside Width: 78 In. (1,981.2 mm) Driveline Protection: Friction Clutch Tillage Depth Control: Skid Shoes Hitch: Category II, Quick Coupler Compatible Frame: Heavy Duty and Bent Frame with

Extra Thickness Above Rotor

**List Price** Suggested Attachment Identifier **USD** (\$) Code Description

Select One Code From Each Required Category

**BASE MACHINE** 

135BXF RT1173 - 73 In. Standard Duty Rotary Tiller 4,515.00

#### ATTACHMENTS FOR FIELD CONVERSION

Miscellaneous

MHF20020376 French Kit - For RT1173, RT1181, RT2283, RT2283C, RT1273, and RT2293

Includes Operators Manual, Parts Catalog, and Safety Decals.

70.56

# RT1173 - 73 In. Standard Duty Rotary Tiller Continued

THIS PAGE INTENTIONALLY LEFT BLANK

### Landscaping

#### RT1181 - 81 In. Standard Duty Rotary Tiller

**Equipment for Base Machine** 

Working Width:

R1 In. (2,057.4 mm)
Tractor PTO Speed: 540 RPM
Tractor PTO HP (Minimum): 50 HP (37.3 kW)
Tractor PTO HP (Maximum): 60 HP (44.7kW)

Blade Shape: C Skid Shoes: Adjustable Parking Stand Included Gearbox Speed: Single Rotor Speed: 228 RPM Rotor Flanges: 11 Side Drive: Gear Blades/Rotor: 6

Rear Door Support: Spring

Max Working Depth: 7.9 In. (200.7 mm) Outside to Outside Width: 86 In. (2,184.4 mm) Driveline Protection: Friction Disc Tillage Depth Control: Skid Shoes Hitch: Category II, Quick Coupler Compatible

**List Price** Suggested Attachment USD (\$) Code Identifier Description

Select One Code From Each Required Category

**BASE MACHINE** 

135CXF RT1181 - 81 In. Standard Duty Rotary Tiller 4,994.00

#### ATTACHMENTS FOR FIELD CONVERSION

Miscellaneous

MHF20020376 French Kit - For RT1173, RT1181, RT2283, RT2283C, RT1273, and RT2293

Includes Operators Manual, Parts Catalog, and Safety Decals.

70.56

# RT1181 - 81 In. Standard Duty Rotary Tiller Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Landscaping

#### RT1265 - 65 In. Medium Duty Rotary Tiller

**Equipment for Base Machine** 

Working Width:
65 In. (165 cm)
Tractor PTO Speed: 540 RPM
Tractor PTO HP (Minimum):
30 HP (22 kW)
Tractor PTO HP (Maximum):
60 HP (44 kW)
Blade Shape: L
Skid Shoes: Adjustable
Rear Door Support: Chain
Parking Stand Included
Gearbox Speed: Single
Rotor Speed: 208 RPM
Rotor Flanges: 8
Blades/Rotor: 6
Max Working Depth:

7.9 In. (20 cm)
Outside to Outside Width:
70 In. (178 cm)
Driveline Protection: Friction Clutch
Tillage Depth Control: Skid Shoes
Hitch: Category I or II, iMatch
and Quick Coupler Compatible
Frame:
Heavy Duty and Bent Frame with
Extra Thickness Above Rotor

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
136AXF		BASE MACHINE  RT1265 - 65 In. Medium Duty Rotary Tiller Skid shoes in base. No Roller Option.	4,264.00

#### ATTACHMENTS FOR FIELD CONVERSION

#### Miscellaneous

5MHF20020375 French Kit - For RT1142, RT1149, RT1157, RT1165. and RT1265 Includes Operators Manual, Parts Catalog, and Safety Decals.

68.32

# RT1265 - 65 In. Medium Duty Rotary Tiller Continued

THIS PAGE INTENTIONALLY LEFT BLANK

#### Landscaping

#### RT1273 - 73 In. Medium Duty Rotary Tiller

**Equipment for Base Machine** 

Working Width:
73 In. (185 cm)
Tractor PTO speed: 540 RPM
Tractor PTO HP (Minimum):
30 HP (22 kW)
Tractor PTO HP (Maximum):
80 HP (59 kW)
Blade Shape: L
Skid Shoes: Adjustable
Side Drive: Gear
Rear Door Support: Chain
Parking Stand Included
Gearbox Speed: Single
Rotor Speed: 213 RPM
Rotor Flanges: 8
Blades/Rotor: 6
Adjustable Lower Hitches
Max Working Depth:
8.7 In. (22 cm)

Outside to Outside Width:
77 In. (196 cm)
Driveline Protection:
Friction Clutch
Tillage Depth Control:
Skid Shoes
Hitch: Category II,
Quick Coupler Compatible
Frame:
Double-Wall Frame Construction
Above Rotor for Strength and
Rock Protection

Code	Attachment Identifier	Description	List Price Suggested USD (\$)

Select One Code From Each Required Category

#### **BASE MACHINE**

136BXF

RT1273 - 73 In. Medium Duty Rotary Tiller Skid shoes in base. No Roller Option.

6,854.00

#### ATTACHMENTS FOR FIELD CONVERSION

#### Miscellaneous

MHF20020376

French Kit - For RT1173, RT1181, RT2283, RT2283C, RT1273, and RT2293 *Includes Operators Manual, Parts Catalog, and Safety Decals.* 

70.56

# RT1273 - 73 In. Medium Duty Rotary Tiller Continued

THIS PAGE INTENTIONALLY LEFT BLANK

#### Landscaping

## RT2283 - 83 In. Medium Duty Rotary Tiller

**Equipment for Base Machine** 

Working Width:
83 In. (210 cm)
Tractor PTO Speed: 540 RPM
Tractor PTO HP (Minimum):
60 HP (44kW)
Tractor PTO HP (Maximum):
100 HP (74 kW)
Blade Shape: L
Skid Shoes: Adjustable
Side Drive: Gear
Rear Door Support: Chain
Parking Stand Included
Gearbox Speed: Multi
Rotor Speed: Multi
Rotor Speed: 140-714-215
(Factory Setting)-266 RPM
Rotor Flanges: 9
Blades/Rotor: 6
Adjustable Lower Hitches
Max Working Depth:

10.6 In. (27 cm)
Outside to Outside Width:
88 In. (224 cm)
Driveline Protection: Friction Clutch
Tillage Depth Control: Skid Shoes,
Cage Roller Optional
Hitch: Category II,
Quick Coupler Compatible
Frame:
Double-Wall Frame Construction
Above Rotor for Strength and
Rock Protection

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1671XF		RT2283 - 83 In. Medium Duty Rotary Tiller Skid shoes in base. Roller Optional.	8,465.00
		DEPTH CONTROL SYSTEM	
1000		Skid Shoe	In Base Price
1010		Cage Roller Manual Adjustment	2,087.00
1020		Cage Roller Hydraulic Adjustment	2,305.00
8010		LEFT DISC Left Disc For RT22, and RT23.	774.00
8000		RIGHT DISC Right Disc For RT22, and RT23.	774.00
		ATTACHMENTS FOR FIELD CONVERSION	
	MHF20020376	Miscellaneous French Kit - For RT1173, RT1181, RT2283, RT2283C, RT1273, and RT2293 Includes Operators Manual, Parts Catalog, and Safety Decals.	70.56
	5MH99500264	Left Disc (RT22, RT23, RC22 Series and Also RT1310R)	835.92

### RT2283 - 83 In. Medium Duty Rotary Tiller

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
	5MH99500263	ATTACHMENTS FOR FIELD CONVERSIONContinued Right Disc (RT22, RT23, RC22 Series and Also RT1310R)	835.92

#### Landscaping

## RT2293 - 93 In. Medium Duty Rotary Tiller

**Equipment for Base Machine** 

Working Width:
93 In. (235 cm)
Tractor PTO Speed: 540 RPM
Tractor PTO HP (Minimum):
70 HP (52 kW)
Tractor PTO HP (Maximum):
100 HP (74 kW)
Blade Shape: L
Skid Shoes: Adjustable
Side Drive: Gear
Rear Door Support: Chain
Parking Stand Included
Gearbox Speed: Multi
Rotor Speed: Multi
(Factory Setting)-266 RPM
Rotor Flanges: 10
Blades/Rotor: 6
Adjustable Lower Hitches
Max Working Depth:

10.6 In. (27 cm)
Outside to Outside Width:
98 In. (249 cm)
Driveline Protection: Friction Clutch
Tillage Depth Control: Skid Shoes,
Cage Roller Optional
Hitch: Category II,
Quick Coupler Compatible
Frame:
Double-Wall Frame Construction
Above Rotor for Strength and
Rock Protection

Attachment Code Identifier		Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1672XF		RT2293 - 93 In. Medium Duty Rotary Tiller Skid shoes in base. Roller Optional.	9,021.00
		DEPTH CONTROL SYSTEM	
1000		Skid Shoe	In Base Price
1010		Cage Roller Manual Adjustment	2,577.00
1020		Cage Roller Hydraulic Adjustment	2,670.00
8010		LEFT DISC Left Disc For RT22, and RT23.	774.00
8000		RIGHT DISC Right Disc For RT22, and RT23.	774.00
		ATTACHMENTS FOR FIELD CONVERSION	
	MHF20020376	Miscellaneous French Kit - For RT1173, RT1181, RT2283, RT2283C, RT1273, and RT2293 Includes Operators Manual, Parts Catalog, and Safety Decals.	70.56
	5MH99500264	Left Disc (RT22, RT23, RC22 Series and Also RT1310R)	835.92

Landscaping

### RT2293 - 93 In. Medium Duty Rotary Tiller

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
	5MH99500263	ATTACHMENTS FOR FIELD CONVERSIONContinued Right Disc (RT22, RT23, RC22 Series and Also RT1310R)	835.92

#### Landscaping

## RT2383 - 82 In. Heavy Duty Rotary Tiller

**Equipment for Base Machine** 

Working Width:
82 In. (208 cm)
Tractor PTO Speed: 540 RPM
Tractor PTO HP (Minimum):
60 HP (44 kW)
Tractor PTO HP (Maximum):
130 HP (96 kW)
Blade Shape: L
Skid Shoes: Adjustable
Side Drive: Gear
Rear Door Support:
Metal Rod with Double Spring
Parking Stand Included
Gearbox Speed: Multi
Rotor Speed:
175-214-262 (Factory Setting)-143 RPM
Rotor Flanges: 9
Blades/Rotor: 6
Max Working Depth:

10.6 In. (27 cm)
Outside to Outside Width:
88 In. (224 cm)
Driveline Protection: Friction Clutch
Tillage Depth Control: Skid Shoes,
Cage Roller Optional
Hitch: Category II,
Quick Coupler Compatible
Frame:
Double-Wall Frame Construction
Above Rotor for Strength and
Rock Protection

Attachment Code Identifier		Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1683XF		RT2383 - 82 In. Heavy Duty Rotary Tiller Skid shoes in base. Roller Optional.	9,653.00
		DEPTH CONTROL SYSTEM	
1000		Skid Shoe	In Base Price
1010		Cage Roller Manual Adjustment	2,087.00
1020		Cage Roller Hydraulic Adjustment	2,305.00
8010		LEFT DISC Left Disc For RT22, and RT23.	774.00
8000		RIGHT DISC Right Disc For RT22, and RT23.	774.00
		ATTACHMENTS FOR FIELD CONVERSION	
	MHF20020454	Miscellaneous French Kit - For RT2308, RT2383, and RT2310 Includes Operators Manual, Parts Catalog, and Safety Decals.	126.56
	5MH99500264	Left Disc (RT22, RT23, RC22 Series and Also RT1310R)	835.92

Landscaping

## RT2383 - 82 In. Heavy Duty Rotary Tiller

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
	5MH99500263	ATTACHMENTS FOR FIELD CONVERSIONContinued Right Disc (RT22, RT23, RC22 Series and Also RT1310R)	835.92

#### Landscaping

#### RT2308 - 102 In. Heavy Duty Rotary Tiller

**Equipment for Base Machine** 

Working Width:
102 In. (260 cm)
Tractor PTO Speed: 540 RPM
Tractor PTO HP (Minimum):
80 HP (59 kW)
Tractor PTO HP (Maximum):
130 HP (96 kW)
Blade Shape: L
Skid Shoes: Adjustable
Side Drive: Gear
Rear Door Support:
Metal Rod with Double Spring
Parking Stand Included
Gearbox Speed: Multi
Rotor Speed: 175-214-262
(Factory Setting)-143 RPM
Rotor Flanges: 11
Blades/Rotor: 6
Max Working Depth:

10.6 In. (27 cm)
Outside to Outside Width:
108 In. (274 cm)
Driveline Protection: Friction Clutch
Tillage Depth Control: Skid Shoes,
Cage Roller Optional
Hitch: Category II,
Quick Coupler Compatible
Frame:
Double-Wall Frame Construction
Above Rotor for Strength and
Rock Protection

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	]
		BASE MACHINE	
1681XF		RT2308 - 102 In. Heavy Duty Rotary Tiller Skid shoes in base. Roller Optional.	10,734.00
		DEPTH CONTROL SYSTEM	
1000		Skid Shoe	In Base Price
1010		Cage Roller Manual Adjustment	2,452.00
1020		Cage Roller Hydraulic Adjustment	2,806.00
8010		LEFT DISC Left Disc For RT22, and RT23.	774.00
8000		RIGHT DISC Right Disc For RT22, and RT23.	774.00
8020		ROTOR FLANGE REINFORCEMENT KIT Rotor Flange Reinforcement Kit	758.00
		ATTACHMENTS FOR FIELD CONVERSION	

## RT2308 - 102 In. Heavy Duty Rotary Tiller

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		ATTACHMENTS FOR FIELD CONVERSION Continued	
	MHF20020454	Miscellaneous French Kit - For RT2308, RT2383, and RT2310 Includes Operators Manual, Parts Catalog, and Safety Decals.	126.56
	5MH99500264	Left Disc (RT22, RT23, RC22 Series and Also RT1310R)	835.92
	5MH99500263	Right Disc (RT22, RT23, RC22 Series and Also RT1310R)	835.92
	5MH99525575	Rotor Flange Reinforcement Kit (RT2308)	818.64

#### Landscaping

## RT2310 - 121 In. Heavy Duty Rotary Tiller

**Equipment for Base Machine** 

Working Width:
121 In. (310 cm)
Tractor PTO Speed: 540 RPM
Tractor PTO HP (Minimum):
100 HP (75 kW)
Tractor PTO HP (Maximum):
130 HP (96 kW)
Blade Shape: L
Skid Shoes: Adjustable
Side Drive: Gear
Rear Door Support:
Metal Rod with Double Spring
Parking Stand Included
Gearbox Speed: Multi
Rotor Speed: 175-214-262
(Factory Setting)-143 RPM
Rotor Flanges: 13
Blades/Rotor: 6

Max Working Depth:

10.6 In. (27 cm)
Outside to Outside Width:
128 In. (325 cm)
Driveline Protection: Friction Clutch
Tillage Depth Control: Skid Shoes,
Cage Roller Optional
Hitch: Category II,
Quick Coupler Compatible
Frame:
Double-Wall Frame Construction
Above Rotor for Strength and
Rock Protection

Attachment Code Identifier		Description	List Price Suggested USD (\$)			
		Select One Code From Each Required Category				
		BASE MACHINE				
1682XF		RT2310 - 121 In. Heavy Duty Rotary Tiller Skid shoes in base. Roller Optional.	12,151.00			
		DEPTH CONTROL SYSTEM				
1000		Skid Shoe	In Base Price			
1010		Cage Roller Manual Adjustment	2,765.00			
1020		Cage Roller Hydraulic Adjustment	3,136.00			
8010		LEFT DISC Left Disc For RT22, and RT23.	774.00			
8000		RIGHT DISC Right Disc For RT22, and RT23.	774.00			
		ATTACHMENTS FOR FIELD CONVERSION				
	MHF20020454	Miscellaneous French Kit - For RT2308, RT2383, and RT2310 Includes Operators Manual, Parts Catalog, and Safety Decals.	126.56			
	5MH99500264	Left Disc (RT22, RT23, RC22 Series and Also RT1310R)	835.92			

## RT2310 - 121 In. Heavy Duty Rotary Tiller

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
	5MH99500263	ATTACHMENTS FOR FIELD CONVERSIONContinued Right Disc (RT22, RT23, RC22 Series and Also RT1310R)	835.92

511.97

#### FRONTIER PRODUCTS

#### Landscaping

## SP2048B - 4 Ft. Standard Duty Soil Pulverizer - Bar Type

**Equipment for Base Machine** 

3-Point Hitch: Category I
Working Width: 48 In.
Tractor HP (Maximum): 30 to 45 HP
Approximate Shipping Weight: 550 lbs.
Scarifying Teeth - Rear:
(8) 1/2 In x 2 In. Bar Type
Scarifying Teeth - Front:
(9) 1/2 In. x 2 In. Bar Type
Roller Pins: 70
Roller Pin Size: 3/8 In. x 1 In.
Roller Diameter: 5-9/16 In.
Height: 39 In.
H-Beam Dimensions: 10 In. x 10 In.

5BP0099887

Second Roller Assembly (SP2048B)

5 In. diameter.

Duty: Standard Duty Compression Springs: (2) 160 lbs. Assembly/Set-Up Time: 10 Minutes (Approximate) Approximate Operating Weight: 496 lbs. 2nd Roller Assembly 48 In.: Optional

Attachment Code Identifier		Description	List Price Suggested USD (\$)	
	Select One Code From Each Required Category			
		BASE MACHINE		
1401XF		SP2048B - 4 Ft. Standard Duty Soil Pulverizer - Bar Type	2,276.00	
		SECOND ROLLER ASSEMBLY		
9000		Second Roller Assembly SP2048B 5 In. diameter.	399.00	
		ATTACHMENTS FOR FIELD CONVERSION		
		ATTACHWENTS FOR FIELD CONVERSION		
		Miscellaneous		

# SP2048B - 4 Ft. Standard Duty Soil Pulverizer - Bar Type Continued

THIS	S PA	AGF.	INTFI	NTIC	DNALLY	I FFT	BLANK	(
1 1 11		<b>'</b> O'						•

262

754.88

#### FRONTIER PRODUCTS

#### Landscaping

### SP2060B - 5 Ft. Standard Duty Soil Pulverizer - Bar Type

**Equipment for Base Machine** 

3-Point Hitch: Category I
Working Width: 60 In.
Tractor HP (Maximum): 30 to 45 HP
Approximate Shipping Weight: 702 lbs.
Scarifying Teeth - Rear:
(10) 1/2 In. x 2 In. Bar Type
Scarifying Teeth - Front:
(11) 1/2 In. x 2 In. Bar Type
Roller Pins: 88
Roller Pin Size: 3/8 In. x 1 In.
Roller Diameter: 5-9/16 In.
Height: 39 In.
H-Beam Dimensions: 10 In. x 10 In.

5BP0099636

Second Roller Assembly (SP2060B)

5 In. diameter.

Duty: Standard Duty Compression Springs: (2) 160 lbs. Assembly/Set-Up Time: 10 Minutes (Approximate) Approximate Operating Weight: 652 lbs. 2nd Roller Assembly 60 In.: Optional

Attachment Code Identifier		Description	List Price Suggested USD (\$)		
	Select One Code From Each Required Category				
		BASE MACHINE			
1403XF		SP2060B - 5 Ft. Standard Duty Soil Pulverizer - Bar Type	2,384.00		
		SECOND ROLLER ASSEMBLY			
9000		Second Roller Assembly SP2060B 5 In. diameter.	497.00		
		ATTACHMENTS FOR FIELD CONVERSION			
		,,			
		Miscellaneous			

# SP2060B - 5 Ft. Standard Duty Soil Pulverizer - Bar Type Continued

THIS	S PA	AGF.	INTFI	NTIC	DNALLY	I FFT	BLANK	(
1 1 11		<b>'</b> O'						•

264

203.67

#### FRONTIER PRODUCTS

#### Landscaping

#### SP2072B - 6 Ft. Standard Duty Soil Pulverizer - Bar Type

**Equipment for Base Machine** 

3-Point Hitch: Category I
Working Width: 72 In.
Tractor HP (Maximum): 30 to 45 HP
Approximate Shipping Weight: 729 lbs.
Scarifying Teeth - Rear:
(12) 1/2 In. x 2 In. Bar Type
Scarifying Teeth - Front:
(13) 1/2 In. x 2 In. Bar Type
Roller Pins: 106
Roller Pin Size: 3/8 In. x 1 In.
Roller Diameter: 5-9/16 In.
Height: 39 In.
H-Beam Dimensions: 10 In. x 10 In.

5BP0099637

Second Roller Assembly (SP2072B)

5 In. diameter.

Duty: Standard Duty Compression Springs: (2) 160 lbs. Assembly/Set-Up Time: 10 Minutes (Approximate) Approximate Operating Weight: 679 lbs. 2nd Roller Assembly 72 In.: Optional

List Price Suggested USD (\$)
2,516.00
2,010.00
705.00

# SP2072B - 6 Ft. Standard Duty Soil Pulverizer - Bar Type Continued

THIS	S PA	AGF.	INTFI	NTIC	DNALLY	I FFT	BLANK	(
1 1 11		<b>'</b> O'						•

266

1,027.68

#### FRONTIER PRODUCTS

Landscaping

### SP2272B - 6 Ft. Heavy Duty Soil Pulverizer - Bar Type

**Equipment for Base Machine** 

3-Point Hitch: Category I
Working Width: 72 In.
Tractor HP (Maximum): 30 to 70 HP
Shipping Weight: 846 lbs.
Scarifying Teeth - Rear:
(12) 1/2 In. x 2 In. Bar Type
Scarifying Teeth - Front:
(13) 1/2 In. x 2 In. Bar Type
Roller Pins: 106
Roller Pin Size: 3/8 In. x 1 In.
Roller Diameter: 6-5/8 In.
Height: 39 In.
H-Beam Dimensions: 12 In. x 11.5 In.

5BP0099646

Second Roller Assembly (SP2272B)

5-9/16 In. diameter.

Duty: Heavy Duty Compression Springs: (2) 160 lbs. Assembly/Set-Up Time: 10 Minutes (Approximate) Approximate Operating Weight: 781 lbs. 2nd Roller Assembly 72 In.: Optional

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
1411XF		BASE MACHINE  SP2272B - 6 Ft. Heavy Duty Soil Pulverizer - Bar Type	3,097.00
			5,001.00
9000		SECOND ROLLER ASSEMBLY Second Roller Assembly SP2272B 5-9/16 In. diameter.	898.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous	

# SP2272B - 6 Ft. Heavy Duty Soil Pulverizer - Bar Type Continued

THIS PAGE INTENTIONALLY LEFT BLANK

268

Landscaping

#### SP2284B - 7 Ft. Heavy Duty Soil Pulverizer - Bar Type

**Equipment for Base Machine** 

3-Point Hitch: Category I
Working Width: 84 In.
Tractor HP (Maximum): 30 to 70 HP
Shipping Weight: 940 lbs.
Scarifying Teeth - Rear:
(14) 1/2 In. x 2 In. Bar Type
Scarifying Teeth - Front:
(15) 1/2 In. x 2 In. Bar Type
Roller Pins: 124
Roller Pin Size: 3/8 In. x 1 In.
Roller Diameter: 6-5/8 In.
Height: 39 In.
H-Beam Dimensions: 12 In. x 11.5 In.

5BP0099647

Second Roller Assembly (SP2284B)

5-9/16 In. diameter.

Duty: Heavy Duty Compression Springs: (2) 160 lbs. Assembly/Set-Up Time: 10 Minutes (Approximate) Approximate Operating Weight: 875 lbs. 2nd Roller Assembly 84 In.: Optional

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
1412XF		BASE MACHINE  SP2284B - 7 Ft. Heavy Duty Soil Pulverizer - Bar Type	3,309.00
		SECOND ROLLER ASSEMBLY	·
9000		Second Roller Assembly SP2284B 5-9/16 In. diameter.	960.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous	

263.46

# SP2284B - 7 Ft. Heavy Duty Soil Pulverizer - Bar Type Continued

THIS PAGE INTENTIONALLY LEFT BLANK

270

Landscaping

#### SS1022B Broadcast Spreader - Pull Type Hitch

**Equipment for Base Machine** 

Hopper Material: Steel
Hopper Weight Capacity: 226 lbs.
Hopper Volume Capacity: 3.5 Cubic Ft.
Machine Weight: 62 lbs.
Shipping Weight (Per Pair): 200 lbs.
Swath Spread: 20 Ft.
Hopper Width: 32 In.
Hopper Height: 39.6 In.
Tractor PTO HP Range: 16-30 HP
PTO RPM: NA (Ground Driven)
PTO Shaft Category (Heavy Duty

Shielded 1-3/8 In.): NA (Ground Driven)
3-Point Hitch Category: Single Point
iMatch Compatible Note: Must be Ordered from
Factory as iMatch: NA
(Single Point Hitch) iMatch Compatible: No

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
3061XF		SS1022B Broadcast Spreader - Pull Type Hitch 226 lb. capacity. Order in multiples of two.	805.00
		HOPPER COVER	
9010		Hopper Cover SS1022B and SS1023B	250.00
		DEFLECTOR SHIELD	
9070		Deflector Shield SS1022B and SS1035B	100.00
		REMOTE GATE CONTROL	
9080		Remote Gate Control SS1022B, SS1023B and SS1035B	356.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5BPAA1120	Miscellaneous Deflector Shield (SS1022B/SS1035B)	108.52
	5BP0099720	Hopper Cover (SS1022B/SS1023B)	272.81
	5BP0099856	Remote Gate Control (SS1022B/SS1023B/SS1035B)	418.54

# SS1022B Broadcast Spreader - Pull Type Hitch Continued

THIS PAGE INTENTIONALLY LEFT BLANK

272

#### Landscaping

## SS1023B Broadcast Spreader - 3-Point PTO Category I Non-iMatch

**Equipment for Base Machine** 

Hopper Material: Steel
Hopper Weight Capacity: 226 lbs.
Hopper Volume Capacity: 3.5 Cubic Ft.
Machine Weight: 81 lbs. Shipping Weight (Per Pair): 232 lbs. Swath Spread: 23 Ft. Hopper Width: 32 In. Hopper Height: 31 In. Tractor PTO HP Range: 16-30 HP PTO RPM: 540 RPM

Shielded 1-3/8 In.) 3-Point Hitch: Category 0 and I iMatch Compatible Note: Must be Ordered from Factory as iMatch: NA (Single Point Hitch) iMatch Compatible: No

PTO Shaft Category I (Heavy Duty

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
3062XF		SS1023B Broadcast Spreader - 3-Point PTO Category I Non-iMatch 226 lb. capacity. Order in multiples of two.	797.00
9010		HOPPER COVER Hopper Cover	250.00
3010		SS1022B and SS1023B	250.00
9070		DEFLECTOR SHIELD  Deflector Shield  SS1023B, SS1036B and SS2036B	102.00
9080		REMOTE GATE CONTROL  Remote Gate Control  SS1022B, SS1023B and SS1035B	356.00
9090		TUMBLING WHEEL AGITATOR Tumbling Wheel Agitator (SS1023B) SS1023B	80.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5BP0099524	Miscellaneous Deflector Shield (SS1023B/SS1036B/SS2036B)	261.59
	5BP0099720	Hopper Cover (SS1022B/SS1023B)	272.81
	5BP0099856	Remote Gate Control (SS1022B/SS1023B/SS1035B)	418.54
	5BP0099979	Tumbling Style Wheel Agitator (SS1023B)	375.57

Bid Term: 2/20/19 - 2/19/21

# FRONTIER PRODUCTS Landscaping

# SS1023B Broadcast Spreader - 3-Point PTO Category I Non-iMatch Continued

Landscaping

#### SS1035B Broadcast Spreader - Pull Type Hitch

**Equipment for Base Machine** 

Hopper Material: Steel
Hopper Weight Capacity: 362 lbs.
Hopper Volume Capacity: 5.6 Cubic Ft.
Machine Weight: 84 lbs.
Shipping Weight (Per Pair): 250 lbs.
Swath Spread: 20 Ft.
Hopper Width: 35 In.
Hopper Height: 45 In.
Tractor PTO HP Range: 16-45 HP
PTO RPM: NA (Ground Driven)
PTO Shaft Category (Heavy Duty

Shielded 1-3/8 In.): NA (Ground Driven)
3-Point Hitch Category: NA (Single Point Hitch)
iMatch Compatible Note: Must be Ordered from
Factory as iMatch: NA
(Single Point Hitch) iMatch Compatible: No

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
3068XF		SS1035B Broadcast Spreader - Pull Type Hitch 362 lb. capacity. Order in multiples of two.	1,079.00
		HOPPER COVER	
9010		Hopper Cover SS1035B, SS1036B and SS2036B	261.00
		DEFLECTOR SHIELD	
9070		Deflector Shield SS1022B and SS1035B	100.00
		REMOTE GATE CONTROL	
9080		Remote Gate Control SS1022B, SS1023B and SS1035B	356.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5BPAA1120	Miscellaneous Deflector Shield (SS1022B/SS1035B)	108.52
	5BP0099721	Hopper Cover (SS1035B/SS1036B/SS2036B)	282.15
	5BP0099856	Remote Gate Control (SS1022B/SS1023B/SS1035B)	418.54

# SS1035B Broadcast Spreader - Pull Type Hitch Continued

THIS PAGE INTENTIONALLY LEFT BLANK

276

**List Price** 

#### FRONTIER PRODUCTS

#### Landscaping

## SS1036B Broadcast Spreader - 3-Point PTO Category I Non-iMatch

**Equipment for Base Machine** 

Hopper Material: Steel
Hopper Weight Capacity: 362 lbs.
Hopper Volume Capacity: 5.6 Cubic Ft.
Machine Weight: 102 lbs.
Shipping Weight (Per Pair): 290 lbs.
Swath Spread: 23 Ft.
Hopper Width: 35 In.
Hopper Height: 34 In.
Tractor PTO HP Range: 16-45 HP
PTO RPM: 540 RPM
PTO Shaft Category I (Heavy Duty

Shielded 1-3/8 In.)
3-Point Hitch: Category 0 and I
iMatch Compatible Note: Must be Ordered from
Factory as iMatch: No
(Single Point hitch) iMatch Compatible: No

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
3069XF		SS1036B Broadcast Spreader - 3-Point PTO Category I Non-iMatch 362 lb. capacity. Order in multiples of two.	833.00
9010		HOPPER COVER Hopper Cover SS1035B, SS1036B and SS2036B	261.00
9070		DEFLECTOR SHIELD  Deflector Shield  SS1023B, SS1036B and SS2036B	102.00
9080		REMOTE GATE CONTROL  Remote Gate Control  SS1036B, SS2036B, SS1067B and SS2067B	356.00
9090		TUMBLING WHEEL AGITATOR Tumbling Wheel Agitator (SS1023B) SS1036B, SS2036B, SS1067B and SS2067B	80.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5BP0099524	Miscellaneous Deflector Shield (SS1023B/SS1036B/SS2036B)	261.59
	5BP0099721	Hopper Cover (SS1035B/SS1036B/SS2036B)	282.15
	5BP0099850	Remote Gate Control (SS1036B/SS2036B/SS1067B/SS2067B)	373.70
	5BP0099978	Tumbling Style Wheel Agitator (SS1036B/SS2036B/SS1067B/SS2067B)	87.19

# SS1036B Broadcast Spreader - 3-Point PTO Category I Non-iMatch Continued

#### Landscaping

#### SS1067B Broadcast Spreader - 3-Point PTO Category I

**Equipment for Base Machine** 

Hopper Material: Steel
Hopper Weight Capacity: 678 lbs.
Hopper Volume Capacity: 10.6 Cubic Ft.
Machine Weight: 125 lbs.
Shipping Weight (Per Pair): 320 lbs.
Swath Spread: 46 Ft.
Hopper Width: 42 In.
Hopper Height: 40 In.
Tractor PTO HP Range: 16-55 HP
PTO RPM: 540 RPM
PTO Shaft Category I (Heavy Duty

Shielded 1-3/8 In.)
3-Point Hitch: Category I
iMatch Compatible (Note: Must be Ordered
from Factory as iMatch): Optional

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
3063XF		SS1067B Broadcast Spreader - 3-Point PTO Category I 678 lb. capacity. Order in multiples of two.	905.00
		AMS I-FEATURES	
1000		iMatch Compatible Leave quantity blank. The system will automatically populate the correct quantity.	9.00
1010		Non-iMatch Compatible  Leave quantity blank. The system will automatically populate the correct quantity.	In Base Price
9010		HOPPER COVER Hopper Cover SS1067B and SS2067B	267.00
9070		DEFLECTOR SHIELD  Deflector Shield  SS1067B and SS2067B	194.00
9080		REMOTE GATE CONTROL  Remote Gate Control  SS1036B, SS2036B, SS1067B and SS2067B	356.00
9090		TUMBLING WHEEL AGITATOR Tumbling Wheel Agitator (SS1023B) SS1036B, SS2036B, SS1067B and SS2067B	80.00
9100		SIDEROW DISCHARGE Siderow Discharge (SS1067B and SS2067B)	407.00

Bid Term: 2/20/19 - 2/19/21

### FRONTIER PRODUCTS

## Landscaping

### SS1067B Broadcast Spreader - 3-Point PTO Category I

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		SIDEROW DISCHARGEContinued	
		ATTACHMENTS FOR FIELD CONVERSION	
	5BP0099638	Miscellaneous Deflector Shield (SS1067B/SS2067B)	958.54
	5BP0099722	Hopper Cover (SS1067B, SS2067B, andSS1079P with 9Ft. Hopper)	291.49
	5BP0099850	Remote Gate Control (SS1036B/SS2036B/SS1067B/SS2067B)	373.70
	5BP0099458	Siderow Discharge (SS1067B/SS2067B)	704.43
	5BP0099978	Tumbling Style Wheel Agitator (SS1036B/SS2036B/SS1067B/SS2067B)	87.19

**List Price** 

Bid Term: 2/20/19 - 2/19/21

#### FRONTIER PRODUCTS

#### Landscaping

## SS2036B Broadcast Spreader - Poly Hopper - 3-Point PTO Category I Non-iMatch

**Equipment for Base Machine** 

Hopper Material: Polyethylene
Hopper Weight Capacity: 362 lbs.
Hopper Volume Capacity: 5.6 Cubic Ft.
Machine Weight: 102 lbs.
Shipping Weight (Per Pair): 290 lbs.
Swath Spread: 23 Ft.
Hopper Width: 35 In.
Hopper Height: 34 In.
Tractor PTO HP Range: 16-45 HP
PTO RPM: 540 RPM
PTO Shaft Category I (Heavy Duty

Shielded 1-3/8 In.)
3-Point Hitch: Category 0 and I
iMatch Compatible Note: Must be Ordered from
Factory as iMatch: No
(Single Point hitch) iMatch Compatible: No

Code	Attachment Identifier	Description	Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
3071XF		SS2036B Broadcast Spreader - Poly Hopper - 3-Point PTO Category I Non-iMatch Stainless steel bottom and nylon spreading disc. 362 lb. capacity. Order in multiples of two.	1,064.00
		HOPPER COVER	
9010		Hopper Cover SS1035B, SS1036B and SS2036B	261.00
		DEFLECTOR SHIELD	
9070		Deflector Shield SS1023B, SS1036B and SS2036B	102.00
		REMOTE GATE CONTROL	
9080		Remote Gate Control SS1036B, SS2036B, SS1067B and SS2067B	356.00
		TUMBLING WHEEL AGITATOR	
9090		Tumbling Wheel Agitator (SS1023B) SS1036B, SS2036B, SS1067B and SS2067B	80.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5BP0099524	Miscellaneous Deflector Shield (SS1023B/SS1036B/SS2036B)	261.59
	5BP0099721	Hopper Cover (SS1035B/SS1036B/SS2036B)	282.15
	5BP0099850	Remote Gate Control (SS1036B/SS2036B/SS1067B/SS2067B)	373.70

# SS2036B Broadcast Spreader - Poly Hopper - 3-Point PTO Category I Non-iMatch Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
	5BP0099978	ATTACHMENTS FOR FIELD CONVERSIONContinued Tumbling Style Wheel Agitator (SS1036B/SS2036B/SS1067B/SS2067B)	87.19

#### Landscaping

#### SS2067B Broadcast Spreader - Poly Hopper - 3-Point PTO Category I

**Equipment for Base Machine** 

Hopper Material: Polyethylene
Hopper Weight Capacity: 678 lbs.
Hopper Volume Capacity: 10.6 Cubic Ft.
Machine Weight: 125 lbs.
Shipping Weight (Per Pair): 320 lbs.
Swath Spread: 46 Ft.
Hopper Width: 42 In.
Hopper Height: 40 In.
Tractor PTO HP Range: 16-55 HP
PTO RPM: 540 RPM
PTO Shaft Category I (Heavy Duty

Shielded 1-3/8 In.)
3-Point Hitch: Category 1
iMatch Compatible (Note: Must be Ordered from Factory as iMatch): Optional

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
3072XF		SS2067B Broadcast Spreader - Poly Hopper - 3-Point PTO Category I Stainless steel bottom and spreading disc. 678 lb. capacity. Order in multiples of two.	1,383.00
		AMS I-FEATURES	
1000		iMatch Compatible Leave quantity blank. The system will automatically populate the correct quantity.	9.00
1010		Non-iMatch Compatible  Leave quantity blank. The system will automatically populate the correct quantity.	In Base Price
9010		HOPPER COVER Hopper Cover SS1067B and SS2067B	267.00
9070		DEFLECTOR SHIELD  Deflector Shield  SS1067B and SS2067B	194.00
9080		REMOTE GATE CONTROL  Remote Gate Control  SS1036B, SS2036B, SS1067B and SS2067B	356.00
9090		TUMBLING WHEEL AGITATOR Tumbling Wheel Agitator (SS1023B) SS1036B, SS2036B, SS1067B and SS2067B	80.00
9100		SIDEROW DISCHARGE Siderow Discharge (SS1067B and SS2067B)	407.00

## Landscaping

# SS2067B Broadcast Spreader - Poly Hopper - 3-Point PTO Category I Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		SIDEROW DISCHARGEContinued	
		ATTACHMENTS FOR FIELD CONVERSION	
	5BP0099638	Miscellaneous Deflector Shield (SS1067B/SS2067B)	958.54
	5BP0099722	Hopper Cover (SS1067B, SS2067B, andSS1079P with 9Ft. Hopper)	291.49
	5BP0099850	Remote Gate Control (SS1036B/SS2036B/SS1067B/SS2067B)	373.70
	5BP0099458	Siderow Discharge (SS1067B/SS2067B)	704.43
	5BP0099978	Tumbling Style Wheel Agitator (SS1036B/SS2036B/SS1067B/SS2067B)	87.19

#### Landscaping

## SS1079P Pendular Spreader - 3-Point PTO Category I

**Equipment for Base Machine** 

Hopper Weight Capacity: 576 or 820 lbs. Hopper Volume Capacity: 9 Cubic Ft. or 12.8 Cubic

3-Point Hitch: Category I iMatch Compatible: Yes

9050

Machine Weight: 250 lbs. Swath Spread Range: 17-47 Ft. Load Height: 43 In.

Tractor HP Range: 20-60 HP PTO RPM: 540 RPM

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
3064XF		SS1079P Pendular Spreader - 3-Point PTO Category I	2,839.00
		HOPPER SIZE	
6900		9 Cu. Ft. Hopper (SS1079P)	In Base Price
6912		12.8 Cu. Ft. Hopper (SS1079P)	357.00
		HOPPER COVER	
9010		Hopper Cover	267.00
9551		Hopper Cover (SS1079P with 9 Ft. Hopper)	267.00
9550		Hopper Cover (SS1079P with 12 Ft. Hopper)	276.00
		AGITATOR EXTENSION	
9000		Agitator Extension SS1079P	184.00
		SALT AND SAND SPOUT	
9020		Salt and Sand Spout (SS1079P, SS1116P, SS1180P and SS1220P)	315.00
		RUBBER INSERT	
9030		Rubber Insert (SS1079P, SS1116P, SS1180P and SS1220P)	113.00
		LEFT-RIGHT DIRECTIONAL ATTACHMENT CONVERSION KIT	
9040		L/R Direct Att (SS1079P, SS1116P, SS1180P and SS1220P)	76.00
		LOCK NUT FOR SPOUT	
9110		Lock Nut for Spout (SS1079P, SS1116P, SS1180P, SS1220P)	51.00
		HYDRAULIC GATE CONTROL	
0050		Undergolia Cata Cantral (CC4070D, CC4440D, CC4400D and CC4220D)	700.00

Hydraulic Gate Control (SS1079P, SS1116P, SS1180P and SS1220P)

709.00

## Landscaping

### SS1079P Pendular Spreader - 3-Point PTO Category I

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		FILTER GRATE	
9060		Filter Grate SS1079P	487.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous	
	5BP0099453	Agitator Extension (SS1079P)	192.46
	5BP0099913	Filter Grate (SS1079P)	151.14
	5BP0099722	Hopper Cover (SS1067B, SS2067B, andSS1079P with 9Ft. Hopper)	291.49
	5BP0099723	Hopper Cover (SS1079P with 12 Ft. Hopper)	291.49
	5BP0099456	Hydraulic Gate Control (SS1079P)	743.67
	5BP0095370	Left/Right Directional Attachment	461.53
	5BP0014984	Lock Nut for Spout (SS1079P, SS1116P, SS1180P, SS1220P)	52.32
	5BP0099451	Rubber Insert	330.73
	5BP0099452	Salt and Sand Spout	192.46

#### Landscaping

### SS1116P Pendular Spreader - 3-Point PTO Category I or II

**Equipment for Base Machine** 

Hopper Weight Capacity: 1168 lbs. Hopper Volume Capacity: 22.5 Cubic Ft. Machine Weight: 321 lbs. Swath Spread Range: 17-47 Ft. Load Height: 38 Tm

Load Height: 38 In. Tractor HP Range: 20-60 HP PTO RPM: 540 RPM

Three Point Hitch: Category I or II

iMatch Compatible: No

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
3065XF		SS1116P Pendular Spreader - 3-Point PTO Category I or II 1168 lb. capacity.	3,796.00
		HOPPER COVER	
9010		Hopper Cover SS1116P	321.00
		AGITATOR EXTENSION	
9000		Agitator Extension SS1116P, SS1180P and SS1220P	184.00
		SALT AND SAND SPOUT	
9020		Salt and Sand Spout (SS1079P, SS1116P, SS1180P and SS1220P)	315.00
		RUBBER INSERT	
9030		Rubber Insert (SS1079P, SS1116P, SS1180P and SS1220P)	113.00
		LEFT-RIGHT DIRECTIONAL ATTACHMENT CONVERSION KIT	
9040		L/R Direct Att (SS1079P, SS1116P, SS1180P and SS1220P)	76.00
		LOCK NUT FOR SPOUT	
9110		Lock Nut for Spout (SS1079P, SS1116P, SS1180P, SS1220P)	51.00
		HYDRAULIC GATE CONTROL	
9050		Hydraulic Gate Control (SS1079P, SS1116P, SS1180P and SS1220P)	709.00
		FILTER GRATE	
9060		Filter Grate SS1116P, SS1180P and SS1220P	440.00

# SS1116P Pendular Spreader - 3-Point PTO Category I or II Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		ATTACHMENTS FOR FIELD CONVERSION	
	5BP0099454	Miscellaneous Agitator Extension (SS1116P/SS1180P/SS1220P)	743.67
	5BP0095410	Filter Grill (SS1116P/SS1180P/SS1220P)	122.08
	5BP0099725	Hopper Cover (SS1116P)	328.86
	5BP0099457	Hydraulic Control (SS1116P/SS1180P/SS1220P)	433.49
	5BP0095370	Left/Right Directional Attachment	461.53
	5BP0014984	Lock Nut for Spout (SS1079P, SS1116P, SS1180P, SS1220P)	52.32
	5BP0099451	Rubber Insert	330.73
	5BP0099452	Salt and Sand Spout	192.46

#### Landscaping

### SS1180P Pendular Spreader - 3-Point PTO Category I or II

**Equipment for Base Machine** 

Hopper Weight Capacity: 1808 lbs.
Hopper Volume Capacity: 34.7 Cubic Ft.
Machine Weight: 339 lbs.
Swath Spread Range: 17-47 Ft.
Load Height: 43 In.
Tractor HP Range: 20-60 HP
PTO RPM: 540 RPM
Three Point Hitch: Category I or II

Three Point Hitch: Category I or II

iMatch Compatible: No

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
3066XF		SS1180P Pendular Spreader - 3-Point PTO Category I or II 1808 lb. capacity.	4,391.00
		HOPPER COVER	
9010		Hopper Cover For SS1180P.	329.00
		AGITATOR EXTENSION	
9000		Agitator Extension SS1116P, SS1180P and SS1220P	184.00
		SALT AND SAND SPOUT	
9020		Salt and Sand Spout (SS1079P, SS1116P, SS1180P and SS1220P)	315.00
		RUBBER INSERT	
9030		Rubber Insert (SS1079P, SS1116P, SS1180P and SS1220P)	113.00
		LEFT-RIGHT DIRECTIONAL ATTACHMENT CONVERSION KIT	
9040		L/R Direct Att (SS1079P, SS1116P, SS1180P and SS1220P)	76.00
		LOCK NUT FOR SPOUT	
9110		Lock Nut for Spout (SS1079P, SS1116P, SS1180P, SS1220P)	51.00
		HYDRAULIC GATE CONTROL	
9050		Hydraulic Gate Control (SS1079P, SS1116P, SS1180P and SS1220P)	709.00
		FILTER GRATE	
9060		Filter Grate SS1116P, SS1180P and SS1220P	440.00

### SS1180P Pendular Spreader - 3-Point PTO Category I or II

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous	
	5BP0099454	Agitator Extension (SS1116P/SS1180P/SS1220P)	743.67
	5BP0095410	Filter Grill (SS1116P/SS1180P/SS1220P)	122.08
	5BP0099726	Hopper Cover (SS1180P)	343.81
	5BP0099457	Hydraulic Control (SS1116P/SS1180P/SS1220P)	433.49
	5BP0095370	Left/Right Directional Attachment	461.53
	5BP0014984	Lock Nut for Spout (SS1079P, SS1116P, SS1180P, SS1220P)	52.32
	5BP0099451	Rubber Insert	330.73
	5BP0099452	Salt and Sand Spout	192.46

#### Landscaping

### SS1220P Pendular Spreader - 3-Point PTO Category I or II

**Equipment for Base Machine** 

Hopper Weight Capacity: 2205 lbs.
Hopper Volume Capacity: 42.4 Cubic Ft.
Machine Weight: 343 lbs.
Swath Spread Range: 17-47 Ft.
Load Height: 47 In.
Tractor HP Range: 20-60 HP
PTO RPM: 540 RPM
Three Point Hitch: Category I or II

Three Point Hitch: Category I or II

iMatch Compatible: No

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
3067XF		SS1220P Pendular Spreader - 3-Point PTO Category I or II 2205 lb. capacity.	4,845.00
		HOPPER COVER	
9010		Hopper Cover For SS1120P.	345.00
		AGITATOR EXTENSION	404.00
9000		Agitator Extension SS1116P, SS1180P and SS1220P	184.00
		SALT AND SAND SPOUT	
9020		Salt and Sand Spout (SS1079P, SS1116P, SS1180P and SS1220P)	315.00
		RUBBER INSERT	
9030		Rubber Insert (SS1079P, SS1116P, SS1180P and SS1220P)	113.00
		LEFT-RIGHT DIRECTIONAL ATTACHMENT CONVERSION KIT	
9040		L/R Direct Att (SS1079P, SS1116P, SS1180P and SS1220P)	76.00
		LOCK NUT FOR SPOUT	
9110		Lock Nut for Spout (SS1079P, SS1116P, SS1180P, SS1220P)	51.00
		HYDRAULIC GATE CONTROL	
9050		Hydraulic Gate Control (SS1079P, SS1116P, SS1180P and SS1220P)	709.00
		FILTER GRATE	
9060		Filter Grate SS1116P, SS1180P and SS1220P	440.00

## SS1220P Pendular Spreader - 3-Point PTO Category I or II

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		ATTACHMENTS FOR FIELD CONVERSION	
	5BP0099454	Miscellaneous Agitator Extension (SS1116P/SS1180P/SS1220P)	743.67
	5BP0095410	Filter Grill (SS1116P/SS1180P/SS1220P)	122.08
	5BP0099727	Hopper Cover (SS1220P)	319.52
	5BP0099457	Hydraulic Control (SS1116P/SS1180P/SS1220P)	433.49
	5BP0095370	Left/Right Directional Attachment	461.53
	5BP0014984	Lock Nut for Spout (SS1079P, SS1116P, SS1180P, SS1220P)	52.32
	5BP0099451	Rubber Insert	330.73
	5BP0099452	Salt and Sand Spout	192.46

Bid Term: 2/20/19 - 2/19/21

#### Landscaping

# SS3067B Broadcast Spreader - Poly Hopper - 3-Point PTO Category I Non-iMatch Equipment for Base Machine

Hopper Material: Polyethylene
Hopper Weight Capacity: 860 lbs.
Hopper Volume Capacity: 10 Cubic Ft.
Machine Weight: 128 lbs.
Shipping Weight (Per Pair): 300 lbs.
Swath Spread: 49 Ft.
Hopper Width: 42 In.
Hopper Height: 42 In.
Tractor PTO HP Range: 20-60 HP
PTO RPM: 540 RPM

PTO Shaft Category I (Heavy Duty

Shielded 1-3/8 In.) 3-Point Hitch: Category 1 iMatch Compatible: No Ships to dealer assembled

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	

#### **BASE MACHINE**

1621XF SS3067B Broadcast Spreader - Poly Hopper - 3-Point PTO Category I Non-iMatch Order in multiples of two. 778.00

SS3067B Broadcast Spreader - Poly Hopper - 3-Point PTO Category I Non-iMatch Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Landscaping

### **PS1001 Integral Subsoiler**

Equipment for Base Machine

Hitch:
Lift-type, Category I,
iMatch Compatible
Working Depth:
Up to 24 In. (609.6 mm)
Transport Length:
16 In. (406.4 mm)
Transport Width:
32.5 In. (825.5 mm)
Transport Height:
49 In. (1,244.6 mm)

Tractor Engine HP Range:
25 - 45 HP
Point:
Reversible, Rectangular Sloped Point,
2.5625 In. (65.1 mm) x 12 In. (304.8 mm)

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
3451XF		PS1001 Integral Subsoiler Order in multiples of two.	299.00
		OPERATOR'S MANUAL AND DECALS	
904M		French OM & Decal Kit (PS10)	13.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5TITE511154	<b>Miscellaneous</b> French Kit - Includes Operator's Manual, Parts Catalog and Safety Decals <i>PS1001</i>	15.60

#### PS1001 Integral Subsoiler Continued

### THIS PAGE INTENTIONALLY LEFT BLANK

#### Landscaping

#### DT1136 - 3 pt. Standard Duty Trencher

**Equipment for Base Machine** 

Hitch: 3-Point Category I and iMatch
Working Depth at 65 Degree Digging angle: 36 in. (914.4 mm)
Chain Width: 6 in. (152.4 mm)
Working Weight: 650 lbs. (294.8 kg)
Tractor PTO HP:
15 HP (11.2 kW) Minimum
30 HP (22.3 kW) Maximum
Recommended Trenching Angle: 65 Degrees
Headshaft Height: 8.5 in. (215.9 mm)
Shipping Weight: 730 lbs. (331.1 kg)
Overall Length: 79 in. (2,006.6 mm)
Overall Width: 38 in. (965.2 mm)

Overall Height: 29 in. (736.6 mm)
Discharge Auger: 14 in. (355.6 mm)
Spoil Discharge Reach: 21 in. (533.4 mm)
540 RPM Rear PTO
Slip Clutch Overload Protection
Parking Stand: Standard
Rear Hydraulics Required

			List Price
	Attachment		Suggested
Code	Identifier	Description	USD (\$)

Select One Code From Each Required Category

#### **BASE MACHINE**

1561XF DT1136 - 3 pt. Standard Duty Trencher

Includes 36 in. boom, crummer, and chain.

8,047.00

# DT1136 - 3 pt. Standard Duty Trencher Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Landscaping

### WC1103 Wood Chipper, 3-Point, PTO Drive, Gravity Feed 3 In. Capacity

**Equipment for Base Machine** 

Using a Belt Drive System
PTO Speed Increased from
540 to 1380-1920 RPM's at Rotor
(Depending on Model)
High Speed Design Requires Less Horsepower
than Direct Drive Models
Double Sided A8 Tool Steel Knives
Adjustable Hardened Anvil

SMV is Standard Equipment 1 Year Parts and Labor Warranty

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1501XF		WC1103 Wood Chipper, 3-Point, PTO Drive, Gravity Feed 3 In. Capacity	3,850.00
904P		OPERATOR'S MANUAL AND DECALS French Operators Manual and Decal Kit	78.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5PQ903177	Miscellaneous French Operators Manual & Decal Kit WC1103 Wood Chipper Destination of Quebec only. Includes French safety decals and manual.	87.36

Bid Term: 2/20/19 - 2/19/21

# WC1103 Wood Chipper, 3-Point, PTO Drive, Gravity Feed 3 In. Capacity Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Landscaping

### WC1105 Wood Chipper, 3-Point, PTO Drive, Gravity Feed 5 In. Capacity

**Equipment for Base Machine** 

Using a Belt Drive System
PTO Speed Increased from
540 to 1380-1920 RPM's at Rotor
(Depending on Model)
High Speed Design Requires Less Horsepower
than Direct Drive Models
Double Sided A8 Tool Steel Knives
Adjustable Hardened Anvil

SMV is Standard Equipment 1 Year Parts and Labor Warranty

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
1502XF		BASE MACHINE  WC1105 Wood Chipper, 3-Point, PTO Drive, Gravity Feed 5 In. Capacity	5,376.00
			5,5.5.5.5
		OPERATOR'S MANUAL AND DECALS	
904P		French Operators Manual and Decal Kit	91.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5PQ903178	Miscellaneous French Operators Manual & Decal Kit WC1105 Wood Chipper Destination of Quebec only. Includes French safety decals and manual.	101.92

# WC1105 Wood Chipper, 3-Point, PTO Drive, Gravity Feed 5 In. Capacity Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Landscaping

## WC1205 Wood Chipper, 3-Point, PTO Drive, Hydraulic Feed 5 In. Capacity

**Equipment for Base Machine** 

Using a Belt Drive System
PTO Speed Increased from
540 to 1380-1920 RPM's at Rotor
(Depending on Model)
Hydraulic Feed
High Speed Design Requires Less Horsepower
than Direct Drive Models
Double Sided A8 Tool Steel Knives
Adjustable Hardened Anvil

SMV is Standard Equipment 1 Year Parts and Labor Warranty

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1511XF		WC1205 Wood Chipper, 3-Point, PTO Drive, Hydraulic Feed 5 In. Capacity Requires continuous flow from the tractor.	8,189.00
		HYDRAULICS	
8000		Self-Contained Hydraulics	1,043.00
		FEEDING	
8010		Auto Feed (Speed Control)	1,278.00
		OPERATOR'S MANUAL AND DECALS	
904P		French Operators Manual and Decal Kit	105.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5PQ903179	Miscellaneous French Operators Manual & Decal Kit WC1205 Wood Chipper Destination of Quebec only. Includes French safety decals and manual.	117.60

WC1205 Wood Chipper, 3-Point, PTO Drive, Hydraulic Feed 5 In. Capacity Continued

ΤI	ΗІ	S	PA	GE	INT	ΈN	JTI(	ANC	LLY I	LEFT	BLA	١N٨	Κ

Landscaping

### WC1208 Wood Chipper, Pull Type, PTO Drive, Hydraulic Feed 8 In. Capacity

**Equipment for Base Machine** 

Using a Belt Drive System
PTO Speed Increased from
540 to 2050 RPM's at Rotor
(Depending on Model)
Hydraulic Feed
High Speed Design Requires Less Horsepower
than Direct Drive Models
Drum-Style Rotor
Double Sided A8 Tool Steel Knives

Adjustable Hardened Anvil SMV is Standard Equipment 1 Year Parts and Labor Warranty

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
1513XF		WC1208 Wood Chipper, Pull Type, PTO Drive, Hydraulic Feed 8 In. Capacity Requires continuous flow from the tractor.	16,653.00
		HYDRAULICS	
8000		Self-Contained Hydraulics	1,372.00
		FEEDING	
8010		Auto Feed (Speed Control)	1,392.00
		OPERATOR'S MANUAL AND DECALS	
904P		French Operators Manual and Decal Kit	105.00
		ATTACHMENTS FOR FIELD CONVERSION	
	5PQ903185	Miscellaneous French Operators Manual & Decal Kit WC1208 Wood Chipper Destination of Quebec only. Includes French safety decals and manual.	117.60

WC1208 Wood Chipper, Pull Type, PTO Drive, Hydraulic Feed 8 In. Capacity
Continued

THIS	S PA	AGF.	INTFI	NTIC	DNALLY	I FFT	BLAN	≺
1 1 11		<b>'</b> O'						