1.7m (66 in.) Straight Blade

Equipment for Base Machine

66 in. (1.7m) wide straight blade Five-position manual angling Two adjusting skid shoes Trip protection Replaceable cutting edge

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
8018M		1.7m (66 in.) Straight Blade For XUV550, XUV550 S4, XUV560, XUV560 S4, XUV590, XUV590 S4, RSX850i, RSX860 Includes front blade, lift arms, and lift components. A winch is needed for blade lift operations, and 2 in. front receiver hitch is needed for mounting the winch (if not already installed). RSX850i/860 also requires Blade Mount Adapter Kit	1,150.00
		DESTINATION	
001A		US/Canada	In Base Price
		LIFT FRAME KITS	
3153		Blade Mount Adapter Kit Required on RSX850i/860, NOT required on XUV550, XUV550 S4, XUV560, XUV560 S4, XUV590, XUV590 S4	192.00
3160		Less Implement Lift Frame Kit For use on XUV550, XUV550 S4, XUV560, XUV560 S4, XUV590, XUV590 S4	In Base Price
		ATTACHMENTS FOR FIELD CONVERSION	
	BM23363	Drawbar 50.8-mm (2-in.) Front Receiver Hitch and Recovery Loops	121.99
	BM23029	Plow Markers Plow Markers For use on HPX Gas/Diesel Utility Vehicles. For use on XUV 620i, 850D Utility Vehicles. For use on XUV 625i, 825i, 855D Utility Vehicles. (Excludes S4 versions) For use on XUV 550 Utility Vehicles. (Includes S4 versions) For use on TS, TX, TH, Utility Vehicles. (Includes gas and Diesel versions) For use on M-Gator A2 Utility Vehicles. For use on 4x2, 6x4 Utility Vehicles. (Includes Turf/Trail, Diesel versions) For use on CS, CX Utility Vehicles. For use on RSX 850i Utility Vehicles.	42.80
	BM24723	Winch WARN ProVantage 1587.573-kg (3500-lb) Winch Requires winch mounting kit and also requires 2 In. Front Receiver Hitch with Recovery Loops for mounting. For use on XUV 625i, 825i, 855D Utility Vehicles. (Includes S4 versions)	628.09

1.7m (66 in.) Straight Blade

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
	BM24019	ATTACHMENTS FOR FIELD CONVERSION Continued Warn Winch (3,000 lbs) - S4 Requires 5.08 cm (2 In.) Front Receiver Hitch with Recovery Loops (BM23363) for mounting.	924.49
	BM25079	Winch Mounting Kit Winch Mounting Kit Requires WARN ProVantage 3500 lb Winch. Kit includes wire harnesses and all necessary hardware to mount winch to bumper.	194.74

1.82m (72 in.) Straight Blade

Equipment for Base Machine

72-Inch (182.88 cm) Wide Straight Blade Three-Position Manual Angling Quick Installation Frame and Hydraulic Lift Two Adjustable Skid Shoes Trip Protection Replaceable Cutting Edge The Above Specifications are Indicative of the Base Feature Machine only and may Differ if Alternative Options/Attachments are Ordered.

Pricing and Specifications are Recommended only and are Subject to Change without Notice.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
8019M		1.82m (72 in.) Straight Blade For T-Series Gator Utility Vehicles (unless noted below), Model Year 2018 and older HPX, XUV625, XUV825, XUV855 & M-Gators.	661.00
		Not compatible with - XUV835, XUV865 - XUV825i S4, XUV855D S4.	
		 TE Model Year 2016 and newer TH Diesel Models This price does NOT include the Mandatory and Recommended Optional Ordering codes. 	
		DESTINATION	
001A		US/Canada	In Base Price
		LIFT FRAME KITS	
3150		Implement Lift Frame Kit Lift frame for MY18+ HPX and All 825/855 Models	540.00
3151		Implement Lift Frame Kit Lift frame for T Series unless noted in base code notes and A-1 Models	465.00
3152		Implement Lift Frame Kit Lift frame for 620i, 850D, and MY17 and older HPX Models	540.00
3160		Less Implement Lift Frame Kit	In Base Price
		POWER / HYDRAULIC LIFT KITS	
3171		Hydraulic Implement Lift Kit Hydraulic Implement Lift -620i, 850D, MY17 and older HPX Models Front Blade Adaptor Required (Included in Option Code)	943.00
3172		Hydraulic Implement Lift Kit Hydraulic Implement Lift - T-SERIES (Unless noted in base code)	748.00
3173		Hydraulic Implement Lift Kit Hydraulic Implement Lift - 625, 855, 825, A2, A3 and MY18+ HPX Models	866.00
3180		Less Hydraulic Implement Lift Kit	In Base Price

1.82m (72 in.) Straight Blade

		oonaod	
Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		ATTACHMENTS FOR FIELD CONVERSION	
	BM24354	Blade Adapter Kit for Hydraulic Implement Lift For use on HPX Gas/Diesel Utility Vehicles. For use on XUV 620i, 850D Utility Vehicles.	85.60
	BM22606	Hydraulic Implement Lift Kit For use on HPX, XUV 620i, 625i, 825i, 850D, 855D and Military A2 & A3 Utility Vehicles, excludes S4 versions. If using on XUV 620i, 850D and HPX Utility Vehicles must order Adapter Kit (BM24354).	964.07
	VGB10086	Bumper Implement Lift Frame Kit For use on TS, TX, TX Turf, TE, and TH Utility Vehicles. (Includes gas and Diesel versions). Not compatible with 2016 and newer TH 6X4 Diesel Utility Vehicles. For use on M-Gator A1 Utility Vehicles.	517.89
	BM23081	Implement Lift Frame Kit For use on XUV 625i, 825i, 855D, and A2 Utility Vehicles. (Excludes S4 versions)	601.34
	BM24344	Implement Lift Frame Kit For use on HPX Gas/Diesel Utility Vehicles. For use on XUV 620i, 850D Utility Vehicles.	601.34
	BM21459	Power Implement Lift Kit For use on TS, TX, TX Turf, and TH Utility Vehicles. (Includes gas and Diesel versions). Not compatible with 2016 and newer TH 6X4 Diesel Utility Vehicles. For use on M-Gator A1 Utility Vehicles.	832.46
	BM23029	Plow Markers Plow Markers For use on HPX Gas/Diesel Utility Vehicles. For use on XUV 620i, 850D Utility Vehicles. For use on XUV 625i, 825i, 855D Utility Vehicles. (Excludes S4 versions) For use on XUV 550 Utility Vehicles. (Includes S4 versions) For use on TS, TX, TH, Utility Vehicles. (Includes gas and Diesel versions) For use on M-Gator A2 Utility Vehicles. For use on A22, 6x4 Utility Vehicles. For use on CS, CX Utility Vehicles. For use on RSX 850i Utility Vehicles.	42.80
	VGB10544	Suspension Heavy-Duty Front Suspension For use on HPX Gas/Diesel Utility Vehicles. For use on XUV 620i, 625i, 850D, and 855D Utility Vehicles. Recommended for Crossover Vehicles equipped with Front Blade or Cab.	272.86
	TY15650	Tire Chains Rear Tire Chains, 25x11-12 (pair)	86.88
	TY25800	Tire Chains (for HPAP 24x10.5-10 or HPAT 24x12-10)	88.25
	TY25802	Tire Chains (for HPAT 24x9.5-10)	121.99
	TY25814	Tire Chains (for Turf/Hard Surface 24x12.00-10)	96.38
	TY24328	Tire chains (pair) for 24x12-12 tires For Turf and Knobby Tires. Not Intended for use on all Four Rear Tires.	89.40
	TY25326	Tire chains (pair) for 26x10.5-12 tires	89.40

1.82m (72 in.) Straight Blade

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
	TY15958	ATTACHMENTS FOR FIELD CONVERSION Continued Tire chains (pair) for 26x12-12 tires	97.67

1.82m (72 in.) V-Blade

Equipment for Base Machine

72 inch (1.82m) wide adjustable V-blade Converts from V-position to an inverted scoop to a straight blade Quick installation Frame and Hydraulic lift

Two adjustable skid shoes Trip protection Replaceable cutting edge

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
801AM		1.82m (72 in.) V-Blade For T-Series Gator Utility Vehicles (unless noted below), Model Year 2018 and older HPX, XUV625, XUV825, XUV855 & M-Gators.	825.00
		Not compatible with - XUV835, XUV865 - XUV825i S4, XUV855D S4 TE	
		 - 1E - Model Year 2016 and newer TH Diesel Models This price does NOT include the Mandatory and Recommended Optional Ordering codes. 	
		DESTINATION	
001A		US/Canada	In Base Price
		LIFT FRAME KITS	
3150		Implement Lift Frame Kit Lift frame for MY18+ HPX and All 825/855 Models	540.00
3151		Implement Lift Frame Kit Lift frame for T Series unless noted in base code notes and A-1 Models	465.00
3152		Implement Lift Frame Kit Lift frame for 620i, 850D, and MY17 and older HPX Models	540.00
3160		Less Implement Lift Frame Kit	In Base Price
		POWER / HYDRAULIC LIFT KITS	
3171		Hydraulic Implement Lift Kit Hydraulic Implement Lift -620i, 850D, MY17 and older HPX Models Front Blade Adaptor Required (Included in Option Code)	943.00
3172		Hydraulic Implement Lift Kit Hydraulic Implement Lift - T-SERIES (Unless noted in base code)	748.00
3173		Hydraulic Implement Lift Kit Hydraulic Implement Lift - 625, 855, 825, A2, A3 and MY18+ HPX Models	866.00
3180		Less Hydraulic Implement Lift Kit	In Base Price

ATTACHMENTS FOR FIELD CONVERSION

1.82m (72 in.) V-Blade

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		ATTACHMENTS FOR FIELD CONVERSION Continued	
	BM24354	Blade Adapter Kit for Hydraulic Implement Lift For use on HPX Gas/Diesel Utility Vehicles. For use on XUV 620i, 850D Utility Vehicles.	85.60
	BM22606	Hydraulic Implement Lift Kit For use on HPX, XUV 620i, 625i, 825i, 850D, 855D and Military A2 & A3 Utility Vehicles, excludes S4 versions. If using on XUV 620i, 850D and HPX Utility Vehicles must order Adapter Kit (BM24354).	964.07
	VGB10086	Bumper Implement Lift Frame Kit For use on TS, TX, TX Turf, TE, and TH Utility Vehicles. (Includes gas and Diesel versions). Not compatible with 2016 and newer TH 6X4 Diesel Utility Vehicles. For use on M-Gator A1 Utility Vehicles.	517.89
	BM23081	Implement Lift Frame Kit For use on XUV 625i, 825i, 855D, and A2 Utility Vehicles. (Excludes S4 versions)	601.34
	BM24344	Implement Lift Frame Kit For use on HPX Gas/Diesel Utility Vehicles. For use on XUV 620i, 850D Utility Vehicles.	601.34
	BM21459	Power Implement Lift Kit For use on TS, TX, TX Turf, and TH Utility Vehicles. (Includes gas and Diesel versions). Not compatible with 2016 and newer TH 6X4 Diesel Utility Vehicles. For use on M-Gator A1 Utility Vehicles.	832.46
	BM23029	Plow Markers Plow Markers For use on HPX Gas/Diesel Utility Vehicles. For use on XUV 620i, 850D Utility Vehicles. For use on XUV 625i, 825i, 855D Utility Vehicles. (Excludes S4 versions) For use on XUV 550 Utility Vehicles. (Includes S4 versions) For use on TS, TX, TH, Utility Vehicles. (Includes gas and Diesel versions) For use on M-Gator A2 Utility Vehicles. For use on 4x2, 6x4 Utility Vehicles. (Includes Turf/Trail, Diesel versions) For use on CS, CX Utility Vehicles. For use on RSX 850i Utility Vehicles.	42.80
	VGB10544	Suspension Heavy-Duty Front Suspension For use on HPX Gas/Diesel Utility Vehicles. For use on XUV 620i, 625i, 850D, and 855D Utility Vehicles. Recommended for Crossover Vehicles equipped with Front Blade or Cab.	272.86
	TY15650	Tire Chains Rear Tire Chains, 25x11-12 (pair)	86.88
	TY25800	Tire Chains (for HPAP 24x10.5-10 or HPAT 24x12-10)	88.25
	TY25802	Tire Chains (for HPAT 24x9.5-10)	121.99
	TY25814	Tire Chains (for Turf/Hard Surface 24x12.00-10)	96.38
	TY24328	Tire chains (pair) for 24x12-12 tires For Turf and Knobby Tires. Not Intended for use on all Four Rear Tires.	89.40
	TY25326	Tire chains (pair) for 26x10.5-12 tires	89.40

1.82m (72 in.) V-Blade

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
	TY15958	ATTACHMENTS FOR FIELD CONVERSION Continued Tire chains (pair) for 26x12-12 tires	97.67

1.82m (72 in.) Winch Operated Straight Blade

Equipment for Base Machine

1.8m (72 in.) wide winch operated straight blade
Made from thick heavy gauge steel with heavy-duty ribbing for rigidity
Low friction black powdercoat finish
Five-position manual angling

Two adjustable skid shoes Trip protection Replaceable steel cutting edge with optional poly and rubber wear bars

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
801BM		1.82m (72 in.) Winch Operated Straight Blade For XUV835, XUV865 only. A winch is needed for blade lift operations if not already installed. Roof/OPS mounted auxiliary lights are recommended if used at night or in conditions where good artificial light does not exist. Includes blade, blade frame, push tubes, large roller fairlead for winch, and shift lever mounted winch controls. Requires blade undercarriage (Option Code 3154) if not already installed on the vehicle Heavy duty front suspension recommended, heavy duty rear suspension also recommended when installing a full cab, sprayer or spreader on all E and M-spec open station vehicles. M-spec cab and R-spec vehicles come from the factory with heavy duty suspension already standard.	1,600.00
		DESTINATION	
001A		US/Canada	In Base Price
		LIFT FRAME KITS	
3154		Undercarriage mount For use on XUV835, XUV865 only Required with initial blade install on XUV835 and XUV865. Option not needed if undercarriage mount was previously installed on vehicle.	In Base Price
		ATTACHMENTS FOR FIELD CONVERSION	
	BM26266	Harnesses E-spec Attachment Harness	266.43
	BM26268	Front Attachment Harness (dash port)	129.47
	BM26740	Front Cab Attachment Harness	70.61
	BM26739	Rear Cab Attachment Harness	70.61

1.82m (72 in.) Winch Operated Straight Blade

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		ATTACHMENTS FOR FIELD CONVERSION Continued	
	BM26185	Lighting Beacon Light E-spec vehicles require E-spec Attachments Harness, Roof Attachments Harness, Rear Cab Harness M-spec open station vehicles require Roof Attachments Harness, Rear Cab Harness M-spec cab vehicles require Rear Cab Harness R-spec vehicles come pre-wired for Beacon Light	257.87
	BM26215	LED Driving Lights (2 Lights) To mount lights to front of OPS: E-spec vehicles require E-spec Attachments Harness, Roof Attachments Harness, Front Cab Harness M-spec open station vehicles require Roof Attachments Harness, Front Cab Harness M-spec cab and R-spec vehicles come pre-wired for OPS mounted lights	359.51
	BM26216	LED Work Lights (2 Lights) To mount lights to front of OPS: E-spec vehicles require E-spec Attachments Harness, Roof Attachments Harness, Front Cab Harness M-spec open station vehicles require Roof Attachments Harness, Front Cab Harness M-spec cab and R-spec vehicles come pre-wired for OPS mounted lights To mount lights to rear of OPS: E-spec vehicles require E-spec Attachments Harness, Roof Attachments Harness, Rear Cab Harness M-spec open station vehicles require Roof Attachments Harness, Rear Cab Harness M-spec cab vehicles require Rear Cab Harness R-spec vehicles come pre-wired for OPS mounted lights	359.51
	BM26401	Miscellaneous POLY WEAR BAR - WINCH BLADE	347.76
	BM26756	RUBBER WEAR BAR - WINCH BLADE	347.76
	BM26397	Plow Markers Plow Markers	47.09
	LP49055	Spreaders 3 cu. ft. Salt Spreader E-spec vehicles require E-spec Attachments Harness, Dash Port Harness M-spec, R-spec vehicles require Dash Port Harness	849.00
	LP53512	5 cu. ft. Drop Spreader E-spec vehicles require E-spec Attachments Harness, Dash Port Harness M-spec, R-spec vehicles require Dash Port Harness	3,250.00
	BM26395	Suspension Heavy Duty Front Shocks Recommended on XUV835E, XUV865E, XUV835M open station, XUV865M open station	272.86
	BM26308	Heavy Duty Rear Shocks Recommended on XUV835E, XUV865E, XUV835M open station, XUV865M open station	311.37
	BM26251	Winch WARN ProVantage 2041 kg (4500 lb) Winch Requires Winch Mounting Kit. E-spec vehicles require E-spec Attachments Harness	742.59
	BM26252	Winch Mounting Kit 4500LB Winch Mounting Kit Required to mount winch to front of chassis.	194.74

1.82m (72 in.) Hydraulic Straight Blade

Equipment for Base Machine

1.82 m (72 in.) wide hydraulic blade Plow width: 1.6 m (64 in.) full angle Plow height: 0.6 m (23.5 in.) Powder-coated steel flared moldboard with four vertical reinforcement ribs Quick installation/removal with quick hitch pins

Plugs directly into vehicle winch harness (standard on M and R spec vehicles, E spec vehicles require E-spec Attachment Harness)
Two adjustable skid shoes
Full-trip moldboard with two coil springs
Replaceable high carbon steel wear edge

Standard plow markers

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
801EM		1.82m (72 in.) Hydraulic Straight Blade For XUV835, XUV865 only. Roof/OPS mounted auxiliary lights are recommended if used at night or in conditions where good artificial light does not exist. Includes blade, and hydraulic unit. Requires undercarriage mount and joystick controller (Option Code 3154) if not already installed on the vehicle E-spec vehicles require E-spec Attachment Harness and Dash Port Attachment Harness M-spec and R-spec vehicles require Dash Port Attachment Harness Heavy duty front suspension recommended, heavy duty rear suspension also recommended when installing a full cab, sprayer, or spreader on all E and M-spec open station vehicles. M-spec cab and R-spec vehicles come from the factory with heavy duty suspension already standard. Not for use with Terrahawk tires	3,800.00
		DESTINATION	
001A		US/Canada Requires option code 0409 English operator's manual	In Base Price
		OPERATOR'S MANUAL	
0409		English operator's manual	In Base Price
		LIFT FRAME KITS	
3154		Undercarriage mount For use on XUV835, XUV865 only Required with initial blade install on XUV835 and XUV865. Option not needed if undercarriage mount was previously installed on vehicle. Includes joystick controller	In Base Price
		ATTACHMENTS FOR FIELD CONVERSION	
	BM26266	Harnesses E-spec Attachment Harness	266.43
	BM26268	Front Attachment Harness (dash port)	129.47
	BM26740	Front Cab Attachment Harness	70.61

1.82m (72 in.) Hydraulic Straight Blade

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
	BM26739	ATTACHMENTS FOR FIELD CONVERSION Continued Rear Cab Attachment Harness	70.61
	BM26267	Roof Attachment Harness	86.67
	BM26185	Lighting Beacon Light E-spec vehicles require E-spec Attachments Harness, Roof Attachments Harness, Rear Cab Harness M-spec open station vehicles require Roof Attachments Harness, Rear Cab Harness M-spec cab vehicles require Rear Cab Harness R-spec vehicles come pre-wired for Beacon Light	257.87
	BM26215	LED Driving Lights (2 Lights) To mount lights to front of OPS: E-spec vehicles require E-spec Attachments Harness, Roof Attachments Harness, Front Cab Harness M-spec open station vehicles require Roof Attachments Harness, Front Cab Harness M-spec cab and R-spec vehicles come pre-wired for OPS mounted lights	359.51
	BM26216	LED Work Lights (2 Lights) To mount lights to front of OPS: E-spec vehicles require E-spec Attachments Harness, Roof Attachments Harness, Front Cab Harness M-spec open station vehicles require Roof Attachments Harness, Front Cab Harness M-spec cab and R-spec vehicles come pre-wired for OPS mounted lights To mount lights to rear of OPS: E-spec vehicles require E-spec Attachments Harness, Roof Attachments Harness, Rear Cab Harness M-spec open station vehicles require Roof Attachments Harness, Rear Cab Harness M-spec cab vehicles require Rear Cab Harness R-spec vehicles come pre-wired for OPS mounted lights	359.51
	LP49055	Spreaders 3 cu. ft. Salt Spreader E-spec vehicles require E-spec Attachments Harness, Dash Port Harness M-spec, R-spec vehicles require Dash Port Harness	849.00
	LP53512	5 cu. ft. Drop Spreader E-spec vehicles require E-spec Attachments Harness, Dash Port Harness M-spec, R-spec vehicles require Dash Port Harness	3,250.00
	BM26395	Suspension Heavy Duty Front Shocks Recommended on XUV835E, XUV865E, XUV835M open station, XUV865M open station	272.86
	BM26308	Heavy Duty Rear Shocks	311.37

Recommended on XUV835E, XUV865E, XUV835M open station, XUV865M open station

1.82m (72 in.) Hydraulic V-Blade

Equipment for Base Machine

1.82 m (72 in.) wide hydraulic operated V-blade Plow width: 1.7 m (66 in.) full angle, 1.5 m (61 in.) scoop, 1.7 m (66 in.) full V Powder-coated steel flared moldboard with six vertical reinforcement ribs 65 cm (25.75 in.) center height to 74 cm (29.25 in.) at the outer edge Quick installation/removal with

quick hitch pins
Plugs directly into vehicle
winch harness (standard on M and
R spec vehicles, E spec vehicles
require E-spec Attachment
Harness)
Two adjustable skid shoes
Independent trip-edge protection
Replaceable high carbon steel
wear edge
Standard plow markers
Quick, double acting hydraulic

cylinders for back dragging performance

			List Price
Code	Attachment Identifier	Description	Suggested USD (\$)
		Select One Code From Each Required Category	
		BASE MACHINE	
801DM		1.82m (72 in.) Hydraulic V-Blade For XUV835, XUV865 only. Roof/OPS mounted auxiliary lights are recommended if used at night or in conditions where good artificial light does not exist. Includes V-blade, and hydraulic unit. Requires undercarriage mount and joystick controller (Option Code 3154) if not already installed on the vehicle E-spec vehicles require E-spec Attachment Harness and Dash Port Attachment Harness M-spec and R-spec vehicles require Dash Port Attachment Harness Heavy duty front suspension recommended, heavy duty rear suspension also recommended when installing a full cab, sprayer, or spreader on all E and M-spec open station vehicles. M-spec cab and R-spec vehicles come from the factory with heavy duty suspension already standard. Not for use with Terrahawk tires	4,500.00
		DESTINATION	
001A		US/Canada	In Base Price
		LIFT FRAME KITS	
3154		Undercarriage mount For use on XUV835, XUV865 only Required with initial blade install on XUV835 and XUV865. Option not needed if undercarriage mount was previously installed on vehicle. Includes joystick controller	In Base Price
3154		For use on XUV835, XUV865 only Required with initial blade install on XUV835 and XUV865. Option not needed if undercarriage mount was previously installed on vehicle.	In Base Price
3154	BM26266	For use on XUV835, XUV865 only Required with initial blade install on XUV835 and XUV865. Option not needed if undercarriage mount was previously installed on vehicle. Includes joystick controller	
3154	BM26266 BM26268	For use on XUV835, XUV865 only Required with initial blade install on XUV835 and XUV865. Option not needed if undercarriage mount was previously installed on vehicle. Includes joystick controller ATTACHMENTS FOR FIELD CONVERSION Harnesses	266.43
3154		For use on XUV835, XUV865 only Required with initial blade install on XUV835 and XUV865. Option not needed if undercarriage mount was previously installed on vehicle. Includes joystick controller ATTACHMENTS FOR FIELD CONVERSION Harnesses E-spec Attachment Harness	266.43 129.47
3154	BM26268	For use on XUV835, XUV865 only Required with initial blade install on XUV835 and XUV865. Option not needed if undercarriage mount was previously installed on vehicle. Includes joystick controller ATTACHMENTS FOR FIELD CONVERSION Harnesses E-spec Attachment Harness Front Attachment Harness (dash port)	266.43 129.47 70.61 70.61

1.82m (72 in.) Hydraulic V-Blade

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
	BM26185	ATTACHMENTS FOR FIELD CONVERSION Continued Lighting Beacon Light E-spec vehicles require E-spec Attachments Harness, Roof Attachments Harness, Rear Cab Harness M-spec open station vehicles require Roof Attachments Harness, Rear Cab Harness M-spec cab vehicles require Rear Cab Harness R-spec vehicles come pre-wired for Beacon Light	257.87
	BM26215	LED Driving Lights (2 Lights) To mount lights to front of OPS: E-spec vehicles require E-spec Attachments Harness, Roof Attachments Harness, Front Cab Harness M-spec open station vehicles require Roof Attachments Harness, Front Cab Harness M-spec cab and R-spec vehicles come pre-wired for OPS mounted lights	359.51
	BM26216	LED Work Lights (2 Lights) To mount lights to front of OPS: E-spec vehicles require E-spec Attachments Harness, Roof Attachments Harness, Front Cab Harness M-spec open station vehicles require Roof Attachments Harness, Front Cab Harness M-spec cab and R-spec vehicles come pre-wired for OPS mounted lights To mount lights to rear of OPS: E-spec vehicles require E-spec Attachments Harness, Roof Attachments Harness, Rear Cab Harness M-spec open station vehicles require Roof Attachments Harness, Rear Cab Harness M-spec cab vehicles require Rear Cab Harness R-spec vehicles come pre-wired for OPS mounted lights	359.51
	LP49055	Spreaders 3 cu. ft. Salt Spreader E-spec vehicles require E-spec Attachments Harness, Dash Port Harness M-spec, R-spec vehicles require Dash Port Harness	849.00
	LP53512	5 cu. ft. Drop Spreader E-spec vehicles require E-spec Attachments Harness, Dash Port Harness M-spec, R-spec vehicles require Dash Port Harness	3,250.00
	BM26395	Suspension Heavy Duty Front Shocks Recommended on XUV835E, XUV865E, XUV835M open station, XUV865M open station	272.86
	BM26308	Heavy Duty Rear Shocks Recommended on XIIV835F, XIIV865F, XIIV835M open station, XIIV865M open station	311.37

Recommended on XUV835E, XUV865E, XUV835M open station, XUV865M open station