

**AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS**

**HX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades
- 6 wheels
Continued**

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
DESTINATION ...Continued...			
0192		Haiti	No Added Cost
0194		Jamaica	No Added Cost
0201		Trinidad & Tobago	No Added Cost
0203		Puerto Rico	No Added Cost
0183		Belize	No Added Cost
0185		Costa Rica	No Added Cost
0189		El Salvador	No Added Cost
0191		Guatemala	No Added Cost
0193		Honduras	No Added Cost
0196		Nicaragua	No Added Cost
0197		Panama	No Added Cost
0211		Bolivia	No Added Cost
0213		Chile	No Added Cost
0214		Colombia	No Added Cost
0215		Ecuador	No Added Cost
0216		Guyana	No Added Cost
0217		Paraguay	No Added Cost
0218		Peru	No Added Cost
0219		Suriname	No Added Cost
0221		Venezuela	No Added Cost

FRONT SAFETY SHIELD

1600		Front Safety Shield - Chain	In Base Price
1620		Front Safety Shield - Second Row Chain	141.00

REAR SAFETY SHIELD

1700		Rear Safety Shield - Chain	In Base Price
1720		Rear Safety Shield - Second Row Chain	141.00

DRIVELINES

1010		Constant Velocity with Lock-Slide Collar Driveline, Cat. 5, 1000 RPM, 1-3/8 In.	In Base Price
------	--	---	---------------

**AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS**

**HX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades
- 6 wheels
Continued**

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
DRIVELINES ...Continued...			
1030		Constant Velocity with Lock-Slide Collar Driveline, Cat. 5, 1000 RPM, 1-3/4 In.	54.00
OPERATOR'S MANUAL, DECALS, AND LANGUAGE			
9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge
WALKING TANDEM			
9080		Walking Tandem Kit <i>Note: Kit just for centre section. For full coverage order 1 additional kit and 2 additional tires</i>	1,800.00
SEVERE DUTY TIRES			
9023		Dual Wing Wheel Spindles, Hubs and 21" x 7" x 12" 16 PR SevereDuty Ag Tires <i>Can also be used to provide dual wheels for center section.</i>	930.00
INDEPENDENT CONTROL VALVE			
9030		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	822.00
WING CYLINDER HOSE			
9050		Extra Wing Cylinder Hose	96.00
SPREADING CONTROL KIT			
9010		Spreading Control Kit	626.00
SHREDDING KIT			
9011		Shredding Attachment Kit	1,583.00
ATTACHMENTS FOR FIELD CONVERSION			
Drivelines			
BP18400		Constant Velocity with Lock-Slide Collar Driveline, Category 5, 1000 RPM - 34.925 mm (1 3/8 in.)	1,453.10
BP18401		Constant Velocity with Lock-Slide Collar Driveline, Category 5, 1000 RPM - 44.45 mm (1 3/4 in.)	1,514.70
Hitches			
BE24260		Safety chain for towed equipment, 4535.924 kg (10,000 lb) <i>Order from JD Otunwa Works.</i>	44.00

**AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS**

**HX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades
- 6 wheels
Continued**

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
ATTACHMENTS FOR FIELD CONVERSION ...Continued...			
		INDEPENDENT CONTROL VALVE	
BW15063		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	904.20
		Laminated Tires	
AW30717		533.4 mm (21 in.) by 133.35 mm (5.25 in.) by 228.6 mm (9 in.) Laminated Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	140.80
		Miscellaneous	
AW32489		Bag of Hardware - For Shredding Attachment Kit	95.70
W49089		Deck Ring <i>Nine required.</i>	68.72
W50394		HX20 Center Section Wheel Spindle for 38 In. Rows <i>Two required.</i>	260.09
BWA1489		Shredding Attachment Kit	1,630.84
BW15812		Stalk Shredder Attachment <i>For CX20 / HX20</i>	335.50
		OPERATOR'S MANUAL, DECALS, AND LANGUAGE	
BW14560		French Operator's Manual and Decal Kit	No Charge
BW15680		Spanish Operator's Manual and Decal Kit	No Charge
		SEVERE DUTY TIRES	
BWA1245		Dual Wing Wheel Spindles, Hubs and 21" x 7" x 12" 16 PR SevereDuty Ag Tires <i>Can also be used to provide dual wheels for center section.</i>	1,023.00
		SPREADING CONTROL KIT	
BP18444		Spreading Control Kit	688.60
		Safety Shields	
BW15672		Front Safety Shield - Second Row Chain	655.60
BW15673		Rear Safety Shield - Second Row Chain	460.90
		Severe Duty Tires	
AW34778		533.4 mm (21 in.) by 177.8 mm (7 in.) by 304.8 mm (12 in.) 16 PR Severe Duty AG Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	227.70

AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS

**HX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades
- 6 wheels**
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
ATTACHMENTS FOR FIELD CONVERSION ...Continued...			
		WALKING TANDEM	
BP18538		Walking Tandem Kit <i>Note: Kit just for centre section. For full coverage order 1 additional kit and 2 additional tires</i>	1,980.00
		WING CYLINDER HOSE	
BW14559		Extra Wing Cylinder Hose	105.60
		Weight Box	
AW30669		Weight Box <i>To replace left wing for conversion from 20 Ft. to 13.5 Ft. flex wing. See parts catalog for other parts needed for conversion.</i>	9,628.91

AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS

**HX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades
- 6 wheels**
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

**AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS**

**HX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades
- 6 Foam Filled wheels
Equipment for Base Machine**

<p>Pull Type Double Deck Design Easy Clean Dome Shaped Top Deck Deck Thickness: Upper Deck Thickness: 0.118 In. (3.0mm) Lower Deck Thickness: 0.138 In. (3.5mm) Four Gear cases Peak Horsepower Rating: Splitter 300 HP (223 kW) Wing 210 HP (156 kW) Continuous Horsepower Rating: Splitter 250 HP (186 kW) Wing 150 HP (111 kW) 1-3/4 In. Gear case Input Shafts 3 In. Brush Cutting Capacity Unibody Frame: 10.5 In. (267mm) Body Depth 1/4 In. (6mm) Side Skirt Thickness 20 Ft. (6.1m) Cutting Width Blade Tip Speed: 16,327 fpm, 82.9 m/s 3-Section Flexible 90 Degrees Up for transportation 22 Degrees Down, working angles 45 Degrees Up, working angles Level Lift (Fore/Aft and Side-to-Side) Lift and Fold Hydraulics Lift Cylinder Depth Stops Double Leveling Rods Easy Adjust Wing Leveling Turnbuckles Adjustable Wheel Spacing</p>	<p>(Refer to Ag Sales Manual for available row spacing, especially for ridge-till applications) Six Foam Filled Wheels - 21" x 7" x 12" 16 PR Severe Duty Ag Tires Constant Velocity and Lock-Slide Collar Tractor-to-Cutter Driveline Three Slip Clutches, Factory Preset, Front and Rear Safety Shields - Chains Bolt-On Wear Shoes Safety Tow Chain Hitch Integrated Jack Stand, Implement Jack SMV Emblem and Support Transport light kit - to comply with regulations Fully Assembled Heavy Duty Rating Intermittent, Greaseable Hinges Tubular Telescoping Driveshaft Members Standard Self-Level Hitch Clevis 30mm Pivot Pins with Single Bushings Standard Spring Suspension 4-Bolt Wheel Hubs Simultaneous Wing Lift Front and rear safety shields reduce the risk of thrown objects which could be hazardous.</p>
---	---

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

<i>EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario</i>			
224KP		HX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades - 6 Foam Filled wheels <i>Serial Number POHX20G006500 and above.</i>	28,141.00

DESTINATION

0202		United States	In Base Price
0184		Canada	No Added Cost
0195		Mexico	No Added Cost
0220		Uruguay	No Added Cost

FRONT SAFETY SHIELD

1600		Front Safety Shield - Chain	In Base Price
------	--	-----------------------------	---------------

**AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS**

**HX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades
- 6 Foam Filled wheels**
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
FRONT SAFETY SHIELD ...Continued...			
1620		Front Safety Shield - Second Row Chain	141.00
REAR SAFETY SHIELD			
1700		Rear Safety Shield - Chain	In Base Price
1720		Rear Safety Shield - Second Row Chain	141.00
DRIVELINES			
1010		Constant Velocity with Lock-Slide Collar Driveline, Cat. 5, 1000 RPM, 1-3/8 In.	In Base Price
1030		Constant Velocity with Lock-Slide Collar Driveline, Cat. 5, 1000 RPM, 1-3/4 In.	54.00
OPERATOR'S MANUAL, DECALS, AND LANGUAGE			
9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge
WALKING TANDEM			
9080		Walking Tandem Kit <i>Note: Kit just for centre section. For full coverage order 1 additional kit and 2 additional tires</i>	1,800.00
SEVERE DUTY TIRES			
9026		Dual Wing Wheel Spindles, Hubs and 21" x 7" x 12" 16 PR Foam filled SevereDuty Ag Tires	1,043.00
INDEPENDENT CONTROL VALVE			
9030		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	822.00
WING CYLINDER HOSE			
9050		Extra Wing Cylinder Hose	96.00
SPREADING CONTROL KIT			
9010		Spreading Control Kit	626.00
SHREDDING KIT			
9011		Shredding Attachment Kit	1,583.00
ATTACHMENTS FOR FIELD CONVERSION			
BW15063		INDEPENDENT CONTROL VALVE Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	904.20

**AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS**

**HX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades
- 6 Foam Filled wheels**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
ATTACHMENTS FOR FIELD CONVERSION ...Continued...			
		OPERATOR'S MANUAL, DECALS, AND LANGUAGE	
BW14560		French Operator's Manual and Decal Kit	No Charge
BW15680		Spanish Operator's Manual and Decal Kit	No Charge
		SEVERE DUTY TIRES	
BP18696		Dual Wing Wheel Spindles, Hubs and 21" x 7" x 12" 16 PR Foam filled SevereDuty Ag Tires	See Parts
		SPREADING CONTROL KIT	
BP18444		Spreading Control Kit	688.60
		WALKING TANDEM	
BP18538		Walking Tandem Kit <i>Note: Kit just for centre section. For full coverage order 1 additional kit and 2 additional tires</i>	1,980.00
		WING CYLINDER HOSE	
BW14559		Extra Wing Cylinder Hose	105.60

AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS

**HX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades
- 6 Foam Filled wheels**

Continued

THIS PAGE INTENTIONALLY LEFT BLANK

**AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS**

CX20 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6 wheels

Equipment for Base Machine

Pull Type
Double Deck Design
Easy Clean Dome Shaped Top Deck
Deck Thickness:
Upper Deck Thickness: 0.138 In. (3.5mm)
Lower Deck Thickness: 0.18 In. (4.5mm)
Four Gear cases
Peak Horsepower Rating:
Splitter 300 HP (223 kW)
Wing 216 HP (159 kW)
Continuous Horsepower Rating:
Splitter 250 HP (186 kW)
Wing 160 HP (119 kW)
1-3/4 In. Gear case Input Shafts
4 In. Brush Cutting Capacity
Unibody Frame:
10.5 In. (267mm) Body Depth
1/4 In. (6mm) Side Skirt Thickness
20 Ft. (6.1 m) Cutting Width
Blade Tip Speed:
16,327 fpm, 82.9 m/s
3-Section Flexible 90 Degrees Up for transportation
22 Degrees Down, working angles
45 Degrees Up, working angles
Level Lift (Fore/Aft and Side-to-Side)
Lift and Fold Hydraulics
Lift Cylinder Depth Stops
Double Leveling Rods
Easy Adjust Wing Leveling Turnbuckles
Adjustable Wheel Spacing
(Refer to Ag Sales Manual for available

row spacing, especially for ridge-till applications)
Six Wheels - 26" x 9" x 14.5" 24 Ply
"Fat Boy" Severe Duty Ag Tires
Constant Velocity and Lock-Slide Collar
Tractor-to-Cutter Driveline
Three Slip Clutches, Factory Preset,
Front and Rear Safety Shields - Chains
Bolt-On Wear Shoes
Safety Tow Chain
Hitch Integrated Jack Stand, Implement Jack
SMV Emblem and Support
Transport light kit comply with regulation
Fully Assembled
Commercial Duty Rating
Deck Rings
Continuous, Full Length, Greaseable Hinges
Splined Telescoping Driveshaft Members
Ball Type Self Level Hitch Clevis
30mm Pivot Pins with Double Bushings
Air Cushioned Suspension with
Shock Absorbers
5-Bolt Wheel Hubs
Independent Wing Lift
Front and rear safety shields reduce the risk of thrown objects which could be hazardous.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario

2268P		CX20 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6 wheels <i>Serial Number POCX20F005000 and above.</i>	34,484.00
-------	--	--	-----------

DESTINATION

0202	United States	In Base Price
0184	Canada	No Added Cost
0195	Mexico	No Added Cost
0220	Uruguay	No Added Cost
0182	Barbados	No Added Cost
0188	Dominican Republic	No Added Cost

**AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS**

**CX20 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6
wheels
Continued**

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
DESTINATION ...Continued...			
0192		Haiti	No Added Cost
0194		Jamaica	No Added Cost
0201		Trinidad & Tobago	No Added Cost
0203		Puerto Rico	No Added Cost
0183		Belize	No Added Cost
0185		Costa Rica	No Added Cost
0189		El Salvador	No Added Cost
0191		Guatemala	No Added Cost
0193		Honduras	No Added Cost
0196		Nicaragua	No Added Cost
0197		Panama	No Added Cost
0211		Bolivia	No Added Cost
0213		Chile	No Added Cost
0214		Colombia	No Added Cost
0215		Ecuador	No Added Cost
0216		Guyana	No Added Cost
0217		Paraguay	No Added Cost
0218		Peru	No Added Cost
0219		Suriname	No Added Cost
0221		Venezuela	No Added Cost

FRONT SAFETY SHIELD

1600		Front Safety Shield - Chain	In Base Price
1620		Front Safety Shield - Second Row Chain	141.00

REAR SAFETY SHIELD

1700		Rear Safety Shield - Chain	In Base Price
1720		Rear Safety Shield - Second Row Chain	141.00

DRIVELINES

**AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS**

**CX20 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6
wheels
Continued**

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
DRIVELINES ...Continued...			
1010		Constant Velocity with Lock-Slide Collar Driveline, Cat. 5, 1000 RPM, 1-3/8 In.	In Base Price
1030		Constant Velocity with Lock-Slide Collar Driveline, Cat. 5, 1000 RPM, 1-3/4 In.	54.00
OPERATOR'S MANUAL, DECALS, AND LANGUAGE			
9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge
WALKING TANDEM			
9070		Walking Tandem Kit <i>Kit just for center section. For full coverage order 1 additional kit and 2 additional tires. Machine is not available with the walking tandem installed, kit to be installed by the dealer.</i>	1,852.00
SEVERE DUTY TIRES			
9025		Dual Wing Wheel Spindles, Hubs and 26" x 9" x 14.5" 24 PR "Fat Boy" Severe Duty Ag Tires	1,008.00
INDEPENDENT CONTROL VALVE			
9030		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	822.00
ATTACHMENTS FOR FIELD CONVERSION			
Drivelines			
BP18400		Constant Velocity with Lock-Slide Collar Driveline, Category 5, 1000 RPM - 34.925 mm (1 3/8 in.)	1,453.10
BP18401		Constant Velocity with Lock-Slide Collar Driveline, Category 5, 1000 RPM - 44.45 mm (1 3/4 in.)	1,514.70
BP18398		Standard Driveline with Clutch and Lock-Slide Collar - 1000 RPM 1-3/4 Power Take-Off (PTO)	1,372.80
BP18397		Standard Driveline with Clutch and Lock-Slide Collar - 1000 RPM 1-3/8 Power Take-Off (PTO)	1,141.80
Hitches			
BE24260		Safety chain for towed equipment, 4535.924 kg (10,000 lb) <i>Order from JD Otumwa Works.</i>	44.00
INDEPENDENT CONTROL VALVE			
BW15063		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	904.20

**AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS**

**CX20 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6
wheels
Continued**

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
ATTACHMENTS FOR FIELD CONVERSION ...Continued...			
		Miscellaneous	
W50393		CX20 Center Section Wheel Spindle for 38 In. Rows <i>Two required.</i>	250.28
		OPERATOR'S MANUAL, DECALS, AND LANGUAGE	
BW14560		French Operator's Manual and Decal Kit	No Charge
BW15680		Spanish Operator's Manual and Decal Kit	No Charge
		SEVERE DUTY TIRES	
BWA1247		Dual Wing Wheel Spindles, Hubs and 26" x 9" x 14.5" 24 PR "Fat Boy" Severe Duty Ag Tires	1,108.80
		Safety Shields	
BW15672		Front Safety Shield - Second Row Chain	655.60
BW15673		Rear Safety Shield - Second Row Chain	460.90
		WALKING TANDEM	
BP18539		Walking Tandem Kit <i>Kit just for center section. For full coverage order 1 additional kit and 2 additional tires. Machine is not available with the walking tandem installed, kit to be installed by the dealer.</i>	2,037.20
		Weight Box	
AW30669		Weight Box <i>To replace left wing for conversion from 20 Ft. to 13.5 Ft. flex wing. See parts catalog for other parts needed for conversion.</i>	9,628.91
		Wheels and Tires	
AW34779		26" x 9" x 14.5" 24 PR "Fat Boy" Severe Duty Ag Tire and Wheel	281.60
BW14522		Dual Wing Wheel Spindles and Hubs	550.00
AW33092		Tire and tube kit for 26" x 9" x 14.5" 'Fat Boy' Severe Duty Ag Tire	310.84

**AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS**

**CX20 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6
Foam Filled wheels
Equipment for Base Machine**

Pull Type
Double Deck Design
Easy Clean Dome Shaped Top Deck
Deck Thickness:
Upper Deck Thickness: 0.138 In. (3.5mm)
Lower Deck Thickness: 0.18 In. (4.5mm)
Four Gear cases
Peak Horsepower Rating:
Splitter 300 HP (223 kW)
Wing 216 HP (159 kW)
Continuous Horsepower Rating:
Splitter 250 HP (186 kW)
Wing 160 HP (119 kW)
1-3/4 In. Gear case Input Shafts
4 In. Brush Cutting Capacity
Unibody Frame:
10.5 In. (267mm) Body Depth
1/4 In. (6mm) Side Skirt Thickness
20 Ft. (6.1 m) Cutting Width
Blade Tip Speed:
16,327 fpm, 82.9 m/s
3-Section Flexible 90 Degrees Up for transportation
22 Degrees Down, working angles
45 Degrees Up, working angles
Level Lift (Fore/Aft and Side-to-Side)
Lift and Fold Hydraulics
Lift Cylinder Depth Stops
Double Leveling Rods
Easy Adjust Wing Leveling Turnbuckles
Adjustable Wheel Spacing
(Refer to Ag Sales Manual for available

row spacing, especially for ridge-till applications)
Six Foam Filled Wheels - 26" x 9" x 14.5" 24 Ply
"Fat Boy" Severe Duty Ag Tires
Constant Velocity and Lock-Slide Collar
Tractor-to-Cutter Driveline
Three Slip Clutches, Factory Preset,
Front and Rear Safety Shields - Chains
Bolt-On Wear Shoes
Safety Tow Chain
Hitch Integrated Jack Stand, Implement Jack
SMV Emblem and Support
Transport light kit comply with regulation
Fully Assembled
Commercial Duty Rating
Deck Rings
Continuous, Full Length, Greaseable Hinges
Splined Telescoping Driveshaft Members
Ball Type Self Level Hitch Clevis
30mm Pivot Pins with Double Bushings
Air Cushioned Suspension with
Shock Absorbers
5-Bolt Wheel Hubs
Independent Wing Lift
Front and rear safety shields reduce the risk of thrown objects which could be hazardous.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario

226AP		CX20 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6 Foam Filled wheels <i>Serial Number POCX20F005000 and above.</i>	34,832.00
-------	--	--	-----------

DESTINATION

0202	United States	In Base Price
0184	Canada	No Added Cost
0195	Mexico	No Added Cost
0220	Uruguay	No Added Cost

FRONT SAFETY SHIELD

1600	Front Safety Shield - Chain	In Base Price
------	-----------------------------	---------------

**AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS**

**CX20 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6
Foam Filled wheels**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
FRONT SAFETY SHIELD ...Continued...			
1620		Front Safety Shield - Second Row Chain	141.00
REAR SAFETY SHIELD			
1700		Rear Safety Shield - Chain	In Base Price
1720		Rear Safety Shield - Second Row Chain	141.00
DRIVELINES			
1010		Constant Velocity with Lock-Slide Collar Driveline, Cat. 5, 1000 RPM, 1-3/8 In.	In Base Price
1030		Constant Velocity with Lock-Slide Collar Driveline, Cat. 5, 1000 RPM, 1-3/4 In.	54.00
OPERATOR'S MANUAL, DECALS, AND LANGUAGE			
9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge
WALKING TANDEM			
9070		Walking Tandem Kit <i>Kit just for center section. For full coverage order 1 additional kit and 2 additional tires. Machine is not available with the walking tandem installed, kit to be installed by the dealer.</i>	1,852.00
SEVERE DUTY TIRES			
9027		Dual Wing Wheel Spindles, Hubs and 26" x 9" x 14.5" 24 PR Foam Filled "Fat Boy" Severe Duty Ag Tires	1,008.00
INDEPENDENT CONTROL VALVE			
9030		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	822.00
ATTACHMENTS FOR FIELD CONVERSION			
	Drivelines		
BP18399		Constant Velocity with Lock-Slide Collar Driveline, Category 5, 540 RPM - 34.925 mm (1 3/8 in.)	1,471.80
	Hitches		
BE24260		Safety chain for towed equipment, 4535.924 kg (10,000 lb) <i>Order from JD Otumwa Works.</i>	44.00
	INDEPENDENT CONTROL VALVE		
BW15063		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	904.20

AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS

**CX20 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6
Foam Filled wheels**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
ATTACHMENTS FOR FIELD CONVERSION ...Continued...			
		LAMINATED TIRES	
BWA1246		Dual Wing Wheel Spindles, Hubs and 21.0" x 5.25" x 9.0" Puncture Proof Laminated Tires	849.20
		OPERATOR'S MANUAL, DECALS, AND LANGUAGE	
BW14560		French Operator's Manual and Decal Kit	No Charge
BW15680		Spanish Operator's Manual and Decal Kit	No Charge
		SEVERE DUTY TIRES	
BWA1247		Dual Wing Wheel Spindles, Hubs and 26" x 9" x 14.5" 24 PR "Fat Boy" Severe Duty Ag Tires	1,108.80
		Safety Shields	
BW15670		Front Safety Shield - Second Row Chain	509.30
BW15671		Rear Safety Shield - Second Row Chain	397.10
		WALKING TANDEM	
BP18539		Walking Tandem Kit <i>Kit just for center section. For full coverage order 1 additional kit and 2 additional tires. Machine is not available with the walking tandem installed, kit to be installed by the dealer.</i>	2,037.20
		Weight Box	
AW33895		Weight Box <i>To replace left wing for conversion from 15 Ft. to 10 Ft. flex wing. See parts catalog for other parts needed for conversion.</i>	3,842.74
		Wheels and Tires	
AW30747		21.0" x 5.25" x 9.0" Laminated Tire and Wheel	157.87
AW34779		26" x 9" x 14.5" 24 PR "Fat Boy" Severe Duty Ag Tire and Wheel	281.60

AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS

**CX20 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6
Foam Filled wheels**

Continued

THIS PAGE INTENTIONALLY LEFT BLANK

**AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS**

**CX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades
- 6 wheels**

Equipment for Base Machine

Pull Type
Double Deck Design
Easy Clean Dome Shaped Top Deck
Deck Thickness:
Upper Deck Thickness: 0.138 In. (3.5mm)
Lower Deck Thickness: 0.18 In. (4.5mm)
Four Gear cases
Peak Horsepower Rating:
Splitter 300 HP (223 kW)
Wing 216 HP (159 kW)
Continuous Horsepower Rating:
Splitter 250 HP (186 kW)
Wing 160 HP (119 kW)
1-3/4 In. Gear case Input Shafts
4 In. Brush Cutting Capacity
Unibody Frame:
10.5 In. (267mm) Body Depth
1/4 In. (6mm) Side Skirt Thickness
20 Ft. (6.1 m) Cutting Width
Blade Tip Speed:
16,327 fpm, 82.9 m/s
3-Section Flexible 90 Degrees Up for transportation
22 Degrees Down, working angles
45 Degrees Up, working angles
Level Lift (Fore/Aft and Side-to-Side)
Lift and Fold Hydraulics
Lift Cylinder Depth Stops
Double Leveling Rods
Easy Adjust Wing Leveling Turnbuckles
Adjustable Wheel Spacing
(Refer to Ag Sales Manual for available

row spacing, especially for ridge-till applications)
Six Wheels - 26" x 9" x 14.5" 24 Ply
"Fat Boy" Severe Duty Ag Tires
Constant Velocity and Lock-Slide Collar
Tractor-to-Cutter Driveline
Three Slip Clutches, Factory Preset,
Front and Rear Safety Shields - Chains
Bolt-On Wear Shoes
Safety Tow Chain
Hitch Integrated Jack Stand, Implement Jack
SMV Emblem and Support
Transport light kit comply with regulation
Fully Assembled
Commercial Duty Rating
Deck Rings
Continuous, Full Length, Greaseable Hinges
Splined Telescoping Driveshaft Members
Ball Type Self Level Hitch Clevis
30mm Pivot Pins with Double Bushings
Air Cushioned Suspension with
Shock Absorbers
5-Bolt Wheel Hubs
Independent Wing Lift
Front and rear safety shields reduce the risk of thrown objects which could be hazardous.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario

2269P		CX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades - 6 wheels <i>Serial Number POCX20F005000 and above.</i>	35,328.00
-------	--	--	-----------

DESTINATION

0202	United States	In Base Price
0184	Canada	No Added Cost
0195	Mexico	No Added Cost
0220	Uruguay	No Added Cost
0182	Barbados	No Added Cost
0188	Dominican Republic	No Added Cost

**AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS**

**CX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades
- 6 wheels
Continued**

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
DESTINATION ...Continued...			
0192		Haiti	No Added Cost
0194		Jamaica	No Added Cost
0201		Trinidad & Tobago	No Added Cost
0203		Puerto Rico	No Added Cost
0183		Belize	No Added Cost
0185		Costa Rica	No Added Cost
0189		El Salvador	No Added Cost
0191		Guatemala	No Added Cost
0193		Honduras	No Added Cost
0196		Nicaragua	No Added Cost
0197		Panama	No Added Cost
0211		Bolivia	No Added Cost
0213		Chile	No Added Cost
0214		Colombia	No Added Cost
0215		Ecuador	No Added Cost
0216		Guyana	No Added Cost
0217		Paraguay	No Added Cost
0218		Peru	No Added Cost
0219		Suriname	No Added Cost
0221		Venezuela	No Added Cost

FRONT SAFETY SHIELD

1600		Front Safety Shield - Chain	In Base Price
1620		Front Safety Shield - Second Row Chain	141.00

REAR SAFETY SHIELD

1700		Rear Safety Shield - Chain	In Base Price
1720		Rear Safety Shield - Second Row Chain	141.00

DRIVELINES

**AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS**

**CX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades
- 6 wheels
Continued**

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
DRIVELINES ...Continued...			
1010		Constant Velocity with Lock-Slide Collar Driveline, Cat. 5, 1000 RPM, 1-3/8 In.	In Base Price
1030		Constant Velocity with Lock-Slide Collar Driveline, Cat. 5, 1000 RPM, 1-3/4 In.	54.00
OPERATOR'S MANUAL, DECALS, AND LANGUAGE			
9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge
WALKING TANDEM			
9070		Walking Tandem Kit <i>Kit just for center section. For full coverage order 1 additional kit and 2 additional tires. Machine is not available with the walking tandem installed, kit to be installed by the dealer.</i>	1,852.00
SEVERE DUTY TIRES			
9025		Dual Wing Wheel Spindles, Hubs and 26" x 9" x 14.5" 24 PR "Fat Boy" Severe Duty Ag Tires	1,008.00
INDEPENDENT CONTROL VALVE			
9030		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	822.00
SHREDDING KIT			
9011		Shredding Attachment Kit	1,583.00
ATTACHMENTS FOR FIELD CONVERSION			
Drivelines			
BP18400		Constant Velocity with Lock-Slide Collar Driveline, Category 5, 1000 RPM - 34.925 mm (1 3/8 in.)	1,453.10
BP18401		Constant Velocity with Lock-Slide Collar Driveline, Category 5, 1000 RPM - 44.45 mm (1 3/4 in.)	1,514.70
Hitches			
BE24260		Safety chain for towed equipment, 4535.924 kg (10,000 lb) <i>Order from JD Ottumwa Works.</i>	44.00
INDEPENDENT CONTROL VALVE			
BW15063		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	904.20
Miscellaneous			
AW32489		Bag of Hardware - For Shredding Attachment Kit	95.70

**AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS**

**CX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades
- 6 wheels
Continued**

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		ATTACHMENTS FOR FIELD CONVERSION ...Continued...	
W50393		CX20 Center Section Wheel Spindle for 38 In. Rows <i>Two required.</i>	250.28
BWA1489		Shredding Attachment Kit	1,630.84
BW15812		Stalk Shredder Attachment <i>For CX20 / HX20</i>	335.50
		OPERATOR'S MANUAL, DECALS, AND LANGUAGE	
BW14560		French Operator's Manual and Decal Kit	No Charge
BW15680		Spanish Operator's Manual and Decal Kit	No Charge
		SEVERE DUTY TIRES	
BWA1247		Dual Wing Wheel Spindles, Hubs and 26" x 9" x 14.5" 24 PR "Fat Boy" Severe Duty Ag Tires	1,108.80
		Safety Shields	
BW15672		Front Safety Shield - Second Row Chain	655.60
BW15673		Rear Safety Shield - Second Row Chain	460.90
		WALKING TANDEM	
BP18539		Walking Tandem Kit <i>Kit just for center section. For full coverage order 1 additional kit and 2 additional tires. Machine is not available with the walking tandem installed, kit to be installed by the dealer.</i>	2,037.20
		Weight Box	
AW30669		Weight Box <i>To replace left wing for conversion from 20 Ft. to 13.5 Ft. flex wing. See parts catalog for other parts needed for conversion.</i>	9,628.91
		Wheels and Tires	
AW34779		26" x 9" x 14.5" 24 PR "Fat Boy" Severe Duty Ag Tire and Wheel	281.60
BW14522		Dual Wing Wheel Spindles and Hubs	550.00
AW33092		Tire and tube kit for 26" x 9" x 14.5" "Fat Boy" Severe Duty Ag Tire	310.84

**AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS**

**CX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades
- 6 Foam Filled wheels
Equipment for Base Machine**

Pull Type
Double Deck Design
Easy Clean Dome Shaped Top Deck
Deck Thickness:
Upper Deck Thickness: 0.138 In. (3.5mm)
Lower Deck Thickness: 0.18 In. (4.5mm)
Four Gear cases
Peak Horsepower Rating:
Splitter 300 HP (223 kW)
Wing 216 HP (159 kW)
Continuous Horsepower Rating:
Splitter 250 HP (186 kW)
Wing 160 HP (119 kW)
1-3/4 In. Gear case Input Shafts
4 In. Brush Cutting Capacity
Unibody Frame:
10.5 In. (267mm) Body Depth
1/4 In. (6mm) Side Skirt Thickness
20 Ft. (6.1 m) Cutting Width
Blade Tip Speed:
16,327 fpm, 82.9 m/s
3-Section Flexible 90 Degrees Up for transportation
22 Degrees Down, working angles
45 Degrees Up, working angles
Level Lift (Fore/Aft and Side-to-Side)
Lift and Fold Hydraulics
Lift Cylinder Depth Stops
Double Leveling Rods
Easy Adjust Wing Leveling Turnbuckles
Adjustable Wheel Spacing
(Refer to Ag Sales Manual for available

row spacing, especially for ridge-till applications)
Six Foam Filled Wheels - 26" x 9" x 14.5" 24 Ply
"Fat Boy" Severe Duty Ag Tires
Constant Velocity and Lock-Slide Collar
Tractor-to-Cutter Driveline
Three Slip Clutches, Factory Preset,
Front and Rear Safety Shields - Chains
Bolt-On Wear Shoes
Safety Tow Chain
Hitch Integrated Jack Stand, Implement Jack
SMV Emblem and Support
Transport light kit comply with regulation
Fully Assembled
Commercial Duty Rating
Deck Rings
Continuous, Full Length, Greaseable Hinges
Splined Telescoping Driveshaft Members
Ball Type Self Level Hitch Clevis
30mm Pivot Pins with Double Bushings
Air Cushioned Suspension with
Shock Absorbers
5-Bolt Wheel Hubs
Independent Wing Lift
Front and rear safety shields reduce the risk of thrown objects which could be hazardous.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario

226BP		CX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades - 6 Foam Filled wheels <i>Serial Number POCX20F005000 and above.</i>	35,678.00
-------	--	--	-----------

DESTINATION

0202	United States	In Base Price
0184	Canada	No Added Cost
0195	Mexico	No Added Cost
0220	Uruguay	No Added Cost

FRONT SAFETY SHIELD

1600	Front Safety Shield - Chain	In Base Price
------	-----------------------------	---------------

**AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS**

**CX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades
- 6 Foam Filled wheels**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
FRONT SAFETY SHIELD ...Continued...			
1620		Front Safety Shield - Second Row Chain	141.00
REAR SAFETY SHIELD			
1700		Rear Safety Shield - Chain	In Base Price
1720		Rear Safety Shield - Second Row Chain	141.00
DRIVELINES			
1010		Constant Velocity with Lock-Slide Collar Driveline, Cat. 5, 1000 RPM, 1-3/8 In.	In Base Price
1030		Constant Velocity with Lock-Slide Collar Driveline, Cat. 5, 1000 RPM, 1-3/4 In.	54.00
OPERATOR'S MANUAL, DECALS, AND LANGUAGE			
9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge
WALKING TANDEM			
9070		Walking Tandem Kit <i>Kit just for center section. For full coverage order 1 additional kit and 2 additional tires. Machine is not available with the walking tandem installed, kit to be installed by the dealer.</i>	1,852.00
SEVERE DUTY TIRES			
9027		Dual Wing Wheel Spindles, Hubs and 26" x 9" x 14.5" 24 PR Foam Filled "Fat Boy" Severe Duty Ag Tires	1,008.00
INDEPENDENT CONTROL VALVE			
9030		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	822.00
SHREDDING KIT			
9011		Shredding Attachment Kit	1,583.00
ATTACHMENTS FOR FIELD CONVERSION			
Drivelines			
BP18400		Constant Velocity with Lock-Slide Collar Driveline, Category 5, 1000 RPM - 34.925 mm (1 3/8 in.)	1,453.10
BP18401		Constant Velocity with Lock-Slide Collar Driveline, Category 5, 1000 RPM - 44.45 mm (1 3/4 in.)	1,514.70
Hitches			
BE24260		Safety chain for towed equipment, 4535.924 kg (10,000 lb) <i>Order from JD Ottumwa Works.</i>	44.00

**AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS**

**CX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades
- 6 Foam Filled wheels**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
ATTACHMENTS FOR FIELD CONVERSION ...Continued...			
		INDEPENDENT CONTROL VALVE	
BW15063		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	904.20
		LAMINATED TIRES	
BWA1246		Dual Wing Wheel Spindles, Hubs and 21.0" x 5.25" x 9.0" Puncture Proof Laminated Tires	849.20
		OPERATOR'S MANUAL, DECALS, AND LANGUAGE	
BW14560		French Operator's Manual and Decal Kit	No Charge
BW15680		Spanish Operator's Manual and Decal Kit	No Charge
		SEVERE DUTY TIRES	
BWA1247		Dual Wing Wheel Spindles, Hubs and 26" x 9" x 14.5" 24 PR "Fat Boy" Severe Duty Ag Tires	1,108.80
		Safety Shields	
BW15670		Front Safety Shield - Second Row Chain	509.30
BW15671		Rear Safety Shield - Second Row Chain	397.10
		WALKING TANDEM	
BP18539		Walking Tandem Kit <i>Kit just for center section. For full coverage order 1 additional kit and 2 additional tires. Machine is not available with the walking tandem installed, kit to be installed by the dealer.</i>	2,037.20
		Weight Box	
AW33895		Weight Box <i>To replace left wing for conversion from 15 Ft. to 10 Ft. flex wing. See parts catalog for other parts needed for conversion.</i>	3,842.74
		Wheels and Tires	
AW30747		21.0" x 5.25" x 9.0" Laminated Tire and Wheel	157.87
AW34779		26" x 9" x 14.5" 24 PR "Fat Boy" Severe Duty Ag Tire and Wheel	281.60

AGRICULTURAL PRODUCTS
JOHN DEERE ROTARY CUTTERS

**CX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades
- 6 Foam Filled wheels**

Continued

THIS PAGE INTENTIONALLY LEFT BLANK
