



July 2, 2018

PRODUCT AND PRICING BULLETIN

NEW HOLLAND BRAND PRODUCTS, U.S. NO. 18-20A

NEW HOLLAND DEALERS WITH MRT AGREEMENT

SUBJECT: **POWERSTAR™ SERIES: COMPLETE REVISION – EFFECTIVE** 10/1/2018

Attached please find price and data pages regarding the Model Year 2019 PowerStar™ Series tractor. These are in effect as of 10/1/2018.

The PowerStar 65 and 75 product offering is changing in conjunction with the launch of the new WORKMASTER 55, 65 and 75. Select packages and options have been removed to reflect this alignment. These adjustments allow the PowerStar Series to be better positioned as a premium tractor to meet the needs of customers who seek extreme comfort and performance in the utility tractor market.

- Utility and Klassic packages have been removed
- All Bias Ply R1 Ag bar tires have been removed

Now, the WORKMASTER Series is better positioned to meet the requirements of valuefocused customers who seek the best available price in a utility tractor and also request basic comfort and performance.

The PowerStar 90, 100, 110 and 120 product offering remains unchanged.

New Holland's 360-degree design approach and customer-focused strategy ensures we continuously deliver a robust line of products that meet the requirements of your customer and remain competitive in the marketplace.

This bulletin and the price pages may be accessed via the Dealer Portal if you have the MRT agreement with New Holland. Log on to the Dealer Portal. With the "Wholegoods" button displayed, click on "Pricing," click on "Tractors," and then click on "PowerStar Series." The latest published items will appear at the top of the list.

Please replace your current P&D pages with those attached to this bulletin.

Christine Chleboun Director, Commercial Marketing New Holland, North America Dan Valen Director, Product Marketing New Holland, North America

Attachment

CNH Industrial America LLC 500 Diller Avenue, P.O. Box 1895 New Holland, PA 17557-0903 Telephone: (717) 355-1121 www.newholland.com/na



PowerStar Series Tractor Index

EQUIPMENT DESCRIPTION	LATEST REVISION	PAGE NUMBER
Index	10/01/18	1
Models PowerStar 65, 75 - STANDARD CAB	10/01/18	2
PowerStar 65, 75 - A LA CARTE CAB	10/01/18	10
PowerStar 75 - A LA CARTE ROPS	10/01/18	19
Parts Divising Supplied Accessories - PowerStar 65, 75	10/01/18	27
Tire Chart - PowerStar 65, 75	10/01/18	28
PowerStar 90, 100, 110, 120 - Mechanical Shuttle - CAB	10/01/18	29
PowerStar 90, 100, 110, 120 - Mechanical Shuttle - ROPS	10/01/18	38
PowerStar 90, 100, 110, 120 - Power Shuttle - UTILITY CAB	10/01/18	47
PowerStar 90, 100, 110, 120 - Power Shuttle - STANDARD CAB	10/01/18	55
PowerStar 90, 100, 110, 120 - Power Shuttle - KLASSIC CAB	10/01/18	64
PowerStar 90, 100, 110, 120 - Power Shuttle - A LA CARTE CAB	10/01/18	73
PowerStar 90, 100, 110, 120 - Power Shuttle - A LA CARTE ROPS	10/01/18	83
Parts Divising Supplied Accessories - PowerStar 90, 100, 110, 120	10/01/18	93
Tire Chart - PowerStar 90, 100, 110, 120	10/01/18	94



Standard Equipment

KEY SELLING POINTS:

- -CommandArc™ ergonomically places most frequently used controls to operator's right
- -Ten repositionable vents for heating and air conditioning
- -12x12 Transmission
- -Hydraulic shuttle lever
- -Full-size instructor seat
- -Hi Visibility Panel
- -Lift-O-Matic Plus
- -Tier 4B EPA emissions compliant
- -Factory Installed Loader

DIESEL ENGINE

PowerStar 65

64 Gross Engine hp

50 PTO hp @ 2300 rpm

4 Cyl Turbocharged Engine

207 cu in (3.4 L) Displacement

PowerStar 75

74 Gross Engine hp

65 PTO hp @ 2300 rpm

4 Cyl Turbocharged Engine

207 cu in (3.4 L) Displacement

ALL MODELS

US EPA Tier 4B Emissions Compliant

Bosch Fuel Injection Pump

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Air Cleaner: Dry Type with Safety

Element

Under Hood Muffler

Vertical Exhaust

Fuel Sediment Filter with Water Sensor

23.8 gal Fuel Tank w/ Protection Shield

Parking brake

TRANSMISSION

Wet Clutch

LH side steering column mounted

shuttle

12 Forward and 12 Reverse Speeds

(4) Synchronized Gears

(3) Non-synchronized Ranges

Forward Reverse Power Shuttle

FWD - 19 mph (30 kph)

Speed varies with tire selection

AXLES

FWD FRONT AXLE

Electro-Hydraulic engagement standard

Adjustable Tread Width from 60.8 in.

to 76.6 in.

Limited Slip Differential Lock

Standard FAS Ready

REAR AXLE

Flange Type

Adjustable Tread Width 52.2 in.

to 76.0 in.

Rear Differential Lock - FWD

mechanically engaged.

HYDRAULIC SYSTEM

Open Center System

(2) Open Center Valves with detent

Dual Gear Pumps

Implement Pump: 12.5 gpm (47.5 L)

Steering Pump: 7.3 gpm (27.5 L)

Total Flow: 19.8 gpm (75 L)

PTO

540 rpm Hydraulic PTO

(1-3/8 in. 6 splines)

Fully Independent, wet clutch

Electro-Hydraulic engagement

Flip-up PTO Shaft Guard

Bid Term: 2/20/19 - 2/19/21

-T1LO 02

POWERSTAR 65-75 STANDARD CAB US PRICE LIST

Standard Equipment

HITCH

3-point Category II with flex lower links and telescoping stabilizers Lift-O-Matic Plus rear hitch control 3664 lbs. Lift Capacity (SAE) Swinging Drawbar Mechanical Draft Control Upper Link Draft Sensing

STEERING/BRAKES

Hydrostatic Power Steering Brakes-Wet disk brakes Hydraulically assited

INSTRUMENTATION

Analog Instrumentation with warning lights for air cleaner service, alternator, oil pressure, fuel sediment/water sensor, PTO engagement, head light high beam, low fuel and parking brake, digital speed readout, gauges for fuel level, engine temperature, tachometer and hour meter

ELECTRICAL

(1) 800 cca Heavy-duty Battery Alternator: 120 amp 7-pin Outlet for trailer/implement lighting and signals 4-pin Power Outlet (30 amp) 8 amp single pole 2 Auxiliary power sockets (cigarette lighter)

LIGHTING

Front: (2) Halogen Headlights and (2) cab mounted worklights Rear: (2) cab mounted worklights Turn Signals/Flashers/Rear Lights

OPERATOR PROTECTIVE STRUCTURE ROPS protected, flat deck platform with heat and air conditioning, tinted windshield, retractable sun screen, front and rear wiper and washer, two doors with locks, two external mirrors, openable side windows, hinged rear window (fully opens) High Visibility Panel Steering Wheel - adjustable tilt Seat - Cloth covered with air suspension and 10 degrees of swivel, operator's presence sensor, retractable seat belt and arm rests Instructor Seat Suspended pedals Radio, speakers, and antenna

MISCELLANEOUS

Pivoting Engine Hood SMV Emblem Toolbox

WARRANTY

New Holland Standard Warranty Applies



Standard Equipment

LOADER:

655TL/710LU NON SELF-LEVELING Maximum Lift Height @ pivot pin: 127.2" Dump Clearance: 94.4" Digging Depth: 6.4" Lift Capacity Max Height @ 800mm: 2,478 LBS 59" high @ 800mm: 3,080 LBS Breakout Force @ 800mm: 3,739 LBS Reach @ Max Lift Height: 39.5" Reach @ Ground Level: 90.7" Bucket Rollback Angle: 45 degrees Bucket Dump Angle: 60 degrees Skid Steer or Euro style bucket attach 655TL/715LU SELF-LEVELING Maximum Lift Height @ pivot pin: 127.2" Dump Clearance: 94.4" Digging Depth: 6.4" Lift Capacity Max Height @ 800mm: 3,179 LBS 59" high @ 800mm: 4,665 LBS Breakout Force @ 800mm: 3,860 LBS Reach @ Max Lift Height: 39.5" Reach @ Ground Level: 90.7" Bucket Rollback Angle: 40 degrees Bucket Dump Angle: 60 degrees Skid Steer or Euro style bucket attach

Models

COMMERCIAL MODEL	VERSION	ENGINE POWER	Weight	Factory Data	List Price	
POWERSTAR 65	Cab	65 HP	6,239 LB	9039775P32	\$50,994.00	
Includes the following Equipment 11.2R24 R1W (8232404) \$1,127.00 16.9R30 R1W (8355404) \$2,456.00						
POWERSTAR 75	Cab	75 HP	7,996 LB	9042243P24	\$54,158.00	
Includes the following Equipment 11.2R24 R1W (8232404) \$1,127.00 16.9R30 R1W (8355404) \$2,456.00						

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

PACKAGE SELECTION

SD_T9980 PACKAGING

X99803X	STANDARD PACKAGING	9006826P56	\$8,752.00
	Standard Package and Pricing Includes:		
	12x12 Power shuttle transmission (330276)		
	Deluxe cab with instructor seat and hi-vis panel (334183)		
	Lift-O-Matic Plus (743595)		
	Requires one selection for each of the following:		
	Mid mount valve and joystick:		
	2 Function mid mount valve and joystick or		
	2 Function mid mount valve and joystick + 3rd fucntion diverter		
	Loader:		
	665TL loader (select one)		
	Bucket:		
	72" or 84" bucket (select one)		
	Tires:		
	Radial ply Ag or Industrial bar tires (select front and rear)		



POV	WER TRAIN			
TD	ANIONALOGIONI			
IR	ANSMISSION			
	CD TOOOO CE			
	SD_T2800 SF		9000201P24	\$258.00
	743552	40 KPH Max Ground Speed	9000201P24	\$258.00
		25 MPH (40 KPH) Transmission for 4WD.		
		Requires a 12x12 transmission (743546, 330276 or 334176).		
	SD_T2810 TR	MOLOSIMSIAN		
	Power Shutt			
	330276	12x12 Power Shuttle		No Charge
	330270	Hydraulic PTO		No Onlarge
		Trydraulic 1 TO		
	SD_T2820 PA	ARK LOCK		
	759176	Hand Brake		No Charge
	100170	Hand operated parking brake lever		110 Onlargo
	743551	Parking Lock	9000039P78	\$51.00
	7 10001	Transmission parking lock	000000170	φο1.00
		Engaged using the range shift lever		
			<u> </u>	
TIRI	EG			
HIIN	L3			
FD	ONT			
110	ONI			
	SD T4940 FR	RONT WHEELS AND TIRES		
	4WD Radial			
		11.2R24 R1W	9000879P06	\$1,127.00
	4WD Specia		0000070100	ψ1,121.00
	8290904		9001258P92	\$1,614.00
			1 333,233,321	¥ 1,0 1 1100
RE	AR			
	SD T4950 RE	EAR WHEELS AND TIRES		
	Radial Tires			
	8355404	16.9R30 R1W	9001915P68	\$2,456.00
		4WD Front Tire - 11.2R24 (8232404)		
		2WD Front Tire - 9.5L15 4 Rib (8126601) or		
		7.5-16 (8125801)		
- '	Specialty Tir		- '	
	T ' '	19.5L-24 10 PR R4	9001948P44	\$2,498.00

4WD Front Tire - 12.5/80-18 (8290904)

HYDRAULICS			
MID MOUNT			
MID-MOUNT			
SD T8280 I	MID-MOUNT VALVES		
338125			No Charge
000120	2 function mid-mount valve and joystick.		140 Onargo
336780		9000567P84	\$728.00
	2 function mid-mount valve and joystick with 3rd function diverter.		ψ. 20.00
	Requires a 655TL Loader.		
	Bucket with Grapple NOT AVAILABLE as Factory Installed.		
		1	
LOADER			
LOADLIN			
LOADER			
LONDLIN			
SD T8110 I	OADER BRACKETS		
	Duty Loader		
336914	i		No Charge
	655TL/710LU		
	Non Self Leveling with Skid Steer Attachment		
336732			No Charge
	655TL/710LU		3.
	Non Self Leveling with Euro Style Attachment		
336734		9000847P08	\$1,086.00
	655TL/715LU		• •
	Mechanical Self Leveling with Skid Steer Style Attachment		
336736		9000847P08	\$1,086.00
	655TL/715LU		. ,
	Mechanical Self Leveling with Euro Style Attachment		
	,	•	
SD_T8140 I	BUCKET		
336748	if PACKAGING is STANDARD PACKAGING	9000428P22	\$549.00
336750	84" Bucket	9000292P50	\$375.00
•		•	
PTO			
REAR PTO			
SD_T8010 I	PTO		
743566		9000472P68	\$606.00
	540/540 Economy PTO		
	· · · · · · · · · · · · · · · · · · ·		

Н	IITC	:H					
	REA	AR 3 POINT HI	rch				
		2D T0120 2 F	DOINT HITCH CONTROL				
Г	T	332035	POINT HITCH CONTROL Mech 3 Pt Hitch Ground Control		9000198P90	\$255.00	
		332033	External mechanical rear ground control for 3pt hitch		3000130130	Ψ233.00	
_							
С	AB	OR ROPS PI	_ATFORM				
	OTH	HER					
		CD TOZOO DI	N CONNECTOR				
	Т	334992	STD+30Ah+HORN+ACS			No Charge	
		334332	30Ah socket & 2-12V power outlets			140 Onlarge	
		334994	STD+30+HRN+ACS+MON		9000060P06	\$77.00	
			Monitor mounting bracket, 30Ah socket & 2-12V power outlets			,	
٧	VEIC	SHTS					
_							
	REA	AR					
	,	SD T4004 DE	AD DALLACT				
	T^{S}	SD_T4961 RE 330470	AR BALLAST 4 x 110 lb Rear Wheel Weights		9000488P28	\$626.00	
<u> </u>	<u> </u>	330470	4 X 110 lb Neal Wileel Weights		9000488F28	φ020.00	
N	/IISC	ELLANEOUS					
		PELEANEOU					
	FEN	NDERS FRONT					
_		D_T8740 FR	ONT FENDERS				
		744674	Dynamic Fenders		9000546P78	\$701.00	
			Dynamic front fenders				
		IDEDC DEAD				1	
	FEN	IDERS REAR					
	5	SD_T8700 FE	NDERS				
	T	744599	Rear Fenders w/Extensions		9000119P34	\$153.00	
			Rear fenders with flat extensions				
С	PE	RATOR'S MA	NUALS				
	T .		DUNTRY CONFIGURATION	<u> </u>		1	
1	1	334256	Canada (FR) Config ROPS	1	1	No Charge	

The Educational Services Commission of New Jersey
NJ State Approved Co-op #65MCESCCPS
NEW HOLLAND
AGRICULTURE

Grounds Equipment Bid #ESCNJ 18/19-25
-T1LO 02

POWERSTAR 65-75 STANDARD CAB US PRICE LIST

334257 USA Spanish Configuration No Charge
--

-T1LO 04

POWERSTAR 65-75 A LA CARTE CAB US PRICE LIST

Standard Equipment

KEY SELLING POINTS:

- -CommandArc™ ergonomically places most frequently used controls to operator's right
- -Ten repositionable vents for heating and air conditioning
- -12x12 Transmission
- -Mechanical or hydraulic shuttle lever
- -Full-size instructor seat option
- -Hi Visibility Panel Option
- -Tier 4B EPA emissions compliant
- -Factory Installed Loader

DIESEL ENGINE

PowerStar 65

64 Gross Engine hp

50 PTO hp @ 2300 rpm

4 Cyl Turbocharged Engine

207 cu in (3.4 L) Displacement

PowerStar 75

74 Gross Engine hp

65 PTO hp @ 2300 rpm

4 Cyl Turbocharged Engine

207 cu in (3.4 L) Displacemen

ALL MODELS

US EPA Tier 4B Emissions Compliant

Bosch Fuel Injection Pump

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Air Cleaner: Dry Type with Safety

Element

Under Hood Muffler

Vertical Exhaust

Fuel Sediment Filter with Water Sensor

23.8 gal Fuel Tank w/ Protection Shield

Parking brake

TRANSMISSION

Wet Clutch

LH side steering column mounted

shuttle

12 Forward and 12 Reverse Speeds

(4) Synchronized Gears

(3) Non-synchronized Ranges

Forward Reverse Power Shuttle

FWD - 19 mph (30 kph)

Speed varies with tire selection

AXLES

2WD HD FRONT AXLE - PowerStar 75

Inverted U-section type

Adjustable Tread Width from 57.0 in.

to 79.7 in.

FWD FRONT AXLE

 ${\tt Electro-Hydraulic\ engagement\ standard}$

Adjustable Tread Width from 60.8 in.

to 76.6 in.

Limited Slip Differential Lock

REAR AXLE

Flange Type

Adjustable Tread Width 52.2 in.

to 76.0 in.

Rear Differential Lock - 2WD and FWD

mechanically engaged.

HYDRAULIC SYSTEM

Open Center System

(2) Open Center Valves with detent

Dual Gear Pumps

Implement Pump: 12.5 gpm (47.5 L)

Steering Pump: 7.3 gpm (27.5 L)

Total Flow: 19.8 gpm (75 L)

PTO

540 rpm Mechanical PTO

(1-3/8 in. 6 splines)

Fully Independent, dry clutch

Mechanical Engagement

Flip-up PTO Shaft Guard

-T1LO 04

POWERSTAR 65-75 A LA CARTE CAB US PRICE LIST

Standard Equipment

HITCH

3-point Category II with flex lower links
 and telescoping stabilizers
3664 lbs. Lift Capacity (SAE)
Swinging Drawbar
Mechanical Draft Control
Upper Link Draft Sensing

STEERING/BRAKES

Hydrostatic Power Steering Brakes-

Wet disk brakes Hydraulically assited

INSTRUMENTATION

Analog Instrumentation with warning lights for air cleaner service, alternator, oil pressure, fuel sediment/water sensor, PTO engagement, head light high beam, low fuel and parking brake, digital speed readout

Gauges for fuel level, engine temperature, tachometer and hour meter

ELECTRICAL

(1) 800 cca Heavy-duty Battery

Alternator: 120 amp
7-pin Outlet for trailer/implement lighting
and signals
4-pin Power Outlet (30 amp)
8 amp single pole
Auxiliary power socket (cigarette lighter)

LIGHTING

OPERATOR PROTECTIVE STRUCTURE ROPS protected, flat deck platform with heat and air conditioning, tinted windshield, retractable sun screen, front wiper and washer, two doors with locks, two external mirrors, openable side windows, hinged rear window (fully opens) Steering Wheel - adjustable tilt Seat - Cloth covered with air suspension and 10 degrees of swivel, operator's presence sensor, retractable seat belt and arm rests Instructor Seat Suspended pedals Radio, speakers, and antenna

MISCELLANEOUS
Pivoting Engine Hood
SMV Emblem
Toolbox
Toolbox on ROPS unit located in fenders

WARRANTY

New Holland Standard Warranty Applies



Standard Equipment

LOADER:

655TL/710LU NON SELF-LEVELING Maximum Lift Height @ pivot pin: 127.2" Dump Clearance: 94.4" Digging Depth: 6.4" Lift Capacity Max Height @ 800mm: 2,478 LBS 59" high @ 800mm: 3,080 LBS Breakout Force @ 800mm: 3,739 LBS Reach @ Max Lift Height: 39.5" Reach @ Ground Level: 90.7" Bucket Rollback Angle: 45 degrees Bucket Dump Angle: 60 degrees Skid Steer or Euro style bucket attach 655TL/715LU SELF-LEVELING Maximum Lift Height @ pivot pin: 127.2" Dump Clearance: 94.4" Digging Depth: 6.4" Lift Capacity Max Height @ 800mm: 3,179 LBS 59" high @ 800mm: 4,665 LBS Breakout Force @ 800mm: 3,860 LBS Reach @ Max Lift Height: 39.5" Reach @ Ground Level: 90.7" Bucket Rollback Angle: 40 degrees Bucket Dump Angle: 60 degrees Skid Steer or Euro style bucket attach

Order Code

POWERSTAR 65-75 A LA CARTE CAB US PRICE LIST

Models

COMMERCIAL MODEL	VERSION	ENGINE POWER	Weight	Factory Data	List Price	
POWERSTAR 65	Cab	65 HP	6,239 LB	9039775P32	\$50,994.00	
Includes the following Equipment 11.2R24 R1W (8232404) \$1,127.00 16.9R30 R1W (8355404) \$2,456.00						
POWERSTAR 75	Cab	75 HP	7,996 LB	9042243P24	\$54,158.00	
Includes the following E 11.2R24 R1W (823240 16.9R30 R1W (835540						

Factory Supplied Options

Weight

Factory Data

List Price

Description

PACKAGE SELECTION	
SD_T9980 PACKAGING	
X99801X LESS PACKAGING	No Charge
OPERATOR PLATFORM	
SD_T9200 OPERATOR STRUCTURE #1	
334183 Deluxe Cab w/HiVis Panel	9000425P88 \$546.00
Deluxe cab with radio, rear wiper and washer, instr	usten and
	uctor seat, and
internal mirror.	uctor seat, and
	uctor seat, and
internal mirror. Includes high visibility panel 744588 Deluxe Cab	No Charge
Includes high visibility panel	No Charge

on of New Jersey Grounds Equipment Bid #ESCNJ 18/19-25
ICESCCPS -T1LO 04



POWERSTAR 65-75 A LA CARTE CAB US PRICE LIST

TRANSMISSION			
SD T2800 SI	PEED		
743552	40 KPH Max Ground Speed	9000201P24	\$258.0
	25 MPH (40 KPH) Transmission for 4WD.		Ψ=00.0
	Requires a 12x12 transmission (743546, 330276 or 334176).		
SD_T2810 TF			
Mechanical			(0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.0.
743546	12x12 Mechanical Shuttle	(901284P66)	(\$1,647.0
	Mechanical PTO		
	PowerStar 75 ONLY		
Power Shut	tle		
330276	12x12 Power Shuttle		No Charç
	Hydraulic PTO		
Power Shut	tle with Creeper		
334176	12x12 Power Shuttle w/Creeper	9000624P00	\$800.0
	20x20 Power Shuttle with Creeper		
	(12x12 + 8x8 creeper)		
	Hydraulic PTO		
	PowerStar 75 ONLY		
! !	1	'	
SD_T2820 PA	ARK LOCK		
759176	Hand Brake		No Charg
	Hand operated parking brake lever		
743551	Parking Lock	9000039P78	\$51.0
	Transmission parking lock		
	Engaged using the range shift lever		
AXLES			
AKLLO			
SD_T4010 FF	RONT AXLE		
336858	2WD Standard Axle Heavy Duty	(901215P24)	(\$1,558.0
	Requires 20 MPH (30 KPH)		
	Compatible with 655TL		
	Requires rear wheel weights (330470) ONLY when		
	ordered with 655TL		
	PowerStar 75 ONLY		
744580	4WD Electro Hyd Limited Slip		No Char
1 1 7 7 7 5 5 6	= =.os.o rija Eminoa Onp		. to Char

9000232P44

\$298.00



POWERSTAR 65-75 A LA CARTE CAB US PRICE LIST

C	HTC	ER				
	SD_T1510 ENGINE EXHAUST					
		743544	Horizontal Exhaust w/Guard			
			Horizontal exhaust			

TIRES

FRONT

SD T4940 FRONT WHEELS AND TIRES

if BRAND is New Holland Ag

SD_14940	FRONT WHEELS AND TIKES		
2WD Fr	ront Tires		
8125	801 7.50-16 8 PLY HD	9000358P02	\$459.00
8126	601 9.5L15 4 RIB 8 PLY	9000468P78	\$601.00
4WD Ra	adial Tires		
82234	404 11.2R20 R1W	9000921P18	\$1,181.00
82694	405 12.4R20 (320/85R20) 8269405	9001006P20	\$1,290.00
82324	404 11.2R24 R1W	9000879P06	\$1,127.00
4WD Sp	pecialty Tires		
8284	604 13.6-16.1 8PR R3	9000771P42	\$989.00
82909	904 12.5/80-18 10PR R4	9001258P92	\$1,614.00
4WD Fr	ront Shipping Wheels		
82998	801 Non-Return Ship Wheels - 4WD	9000071P76	\$92.00

REAR

SD_T4950 REAR WHEELS AND TIRES

Radial Tires	AN WHELEO AND TINES		
8351404	14.9R28 R1W 4WD Front Tire - 11.2R20 (8223404) 2WD Front Tire - 7.5-16 (8125801) Not compatible with front loader	9001569P36	\$2,012.00
8352404	PowerStar 75 ONLY 16.9R28 R1W 4WD Front Tire - 12.4R20 (8269405) 2WD Front Tire - 9.5L15 4 Rib (8126601) or 7.5-16 (8125801) PowerStar 75 ONLY	9001829P88	\$2,346.00
8355404	16.9R30 R1W 4WD Front Tire - 11.2R24 (8232404) 2WD Front Tire - 9.5L15 4 Rib (8126601) or 7.5-16 (8125801)	9001915P68	\$2,456.00

Specialty Tir	es		
8320704	16.9-24 6PR R3_Turf	9001725	5P36 \$2,212.00
	4WD Front Tire - 13.6-16.1 AW (8284604)		
	PowerStar 75 ONLY		
8320604	16.9-24 8PR R4	900177	P38 \$2,271.00
	4WD Front Tire - 12.5/80-18 (8290904)		
	PowerStar 75 ONLY		
8391904	19.5L-24 10 PR R4	9001948	\$2,498.00
	4WD Front Tire - 12.5/80-18 (8290904)		
Rear Shippir	ng Wheels		
8399801	Non-Returnable Shipping Wheel	9000429	P78 \$551.00

HYDRAULICS

REAR REMOTES

SD_T8270 REAR REMOTES

	743568	1 Remote 2 Couplers	(900566P28)	(\$726.00)
		1 rear remote valve with detent		
		PowerStar 75 ONLY		

MID-MOUNT

SD_T8280 MID-MOUNT VALVES

	338125	2Mid-Mount w/Mec Joystick	9001134P90	\$1,455.00
L		2 function mid-mount valve and joystick.		
Г	336780	2Mid-Mount w/Mec Joystick +Div	9001702P74	\$2,183.00
		2 function mid-mount valve and joystick with 3rd function diverter.		
		Requires a 655TL Loader.		
		Bucket with Grapple NOT AVAILABLE as Factory Installed.		

LOADER

LOADER

SD_T8110 LOADER BRACKETS

Standard Duty Loader					
	336914	Non Self Leveling Ldr +SSQA		9004634P76	\$5,942.00
		655TL/710LU			
		Non Self Leveling with Skid Steer Attachment			
	336732	Non Self Leveling Ldr +Euro		9004634P76	\$5,942.00
		655TL/710LU			
		Non Self Leveling with Euro Style Attachment			



336734	Mech Self Leveling Ldr +SSQA	9005481P84	\$7,028.00
	655TL/715LU		
	Mechanical Self Leveling with Skid Steer Style Attachment		
336736	Mech Self Leveling Ldr +Euro	9005481P84	\$7,028.00
	655TL/715LU		
	Mechanical Self Leveling with Euro Style Attachment		
SD_T8140 BU	ICKET		
336748	72" Bucket	9000428P22	\$549.00
336750	84" Bucket	9000720P72	\$924.00
	Of Bucket	3000720172	ψ324.00
РТО			
2512.250			
REAR PTO			
SD_T8010 PT	0		
743566	540/540E PTO	9000472P68	\$606.00
	540/540 Economy PTO		
НІТСН			
REAR 3 POINT HI	ГСН		
SD T0120 2 I	DOINT HITCH CONTROL		
332035	POINT HITCH CONTROL Mech 3 Pt Hitch Ground Control	9000198P90	\$255.00
332033	External mechanical rear ground control for 3pt hitch	90001981 90	Ψ203.00
	External mechanical real ground control for Spt mich		
SD_T8200 HI	тсн		
743595	Lift-O-Matic Plus	9000202P02	\$259.00
	Lift-O-Matic Plus		
CAB OR ROPS P	LATFORM		
OTHER			
OTHER			
SD_T6730 PII	N CONNECTOR		
334992	STD+30Ah+HORN+ACS		No Charge
	30Ah socket & 2-12V power outlets		
334994	STD+30+HRN+ACS+MON	9000060P06	\$77.00
	Monitor mounting bracket, 30Ah socket & 2-12V power outlets		

WEIGHTS			
FRONT			
05 70.70			
	RONT BALLAST		***
332215	Front Carrier +4 88 lb Weights	9000468P78	\$601.00
	Total weight - 485 lbs (220 kg)		
333215	Front Carrier +6 88 lb Weights	9000638P82	\$819.00
	Total weight - 661 lbs (300 kg)		
REAR			
SD_T4961 RE	EAR BALLAST		
330470	4 x 110 lb Rear Wheel Weights	9000488P28	\$626.00
MISCELLANEOU	S		
FENDERS FRONT			
SD_T8740 FF	RONT FENDERS		
744674	Dynamic Fenders	9000546P78	\$701.00
	Dynamic front fenders		
FENDERS REAR			
SD_T8700 FE	NDERS		
744599	Rear Fenders w/Extensions	9000119P34	\$153.00
	Rear fenders with flat extensions		
OPERATOR'S MA	ANUALS		
	DUNTRY CONFIGURATION		
334256	Canada (FR) Config ROPS		No Charge
334257	USA Spanish Configuration		No Charge

-T1LO 05

POWERSTAR 75 A LA CARTE ROPS US PRICE LIST

Standard Equipment

KEY SELLING POINTS:

- -CommandArc™ ergonomically places most frequently used controls to operator's right
- -12x12 Transmission
- -Mechanical or hydraulic shuttle lever
- -Tier 4B EPA emissions compliant
- -Factory Installed Loader

DIESEL ENGINE

Powerstar 75

74 Gross Engine hp

65 PTO hp @ 2300 rpm

4 Cyl Turbocharged Engine

207 cu in (3.4 L) Displacement

ALL MODELS

US EPA Tier 4B Emissions Compliant

Bosch Fuel Injection Pump

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Air Cleaner: Dry Type with Safety

Element

Under Hood Muffler

Vertical Exhaust

Fuel Sediment Filter with Water Sensor

23.8 gal Fuel Tank w/ Protection Shield

Parking brake

TRANSMISSION

Wet Clutch

LH side steering column mounted

shuttle

12 Forward and 12 Reverse Speeds

(4) Synchronized Gears

(3) Non-synchronized Ranges

Forward Reverse Power Shuttle

FWD - 19 mph (30 kph)

Speed varies with tire selection

AXLES

2WD HD FRONT AXLE

Inverted U-section type

Adjustable Tread Width from 57.0 in.

to 79.7 in.

FWD FRONT AXLE

 ${\tt Electro-Hydraulic\ engagement\ standard}$

Adjustable Tread Width from 60.8 in.

to 76.6 in.

Limited Slip Differential Lock

REAR AXLE

Flange Type

Adjustable Tread Width 52.2 in.

to 76.0 in.

Rear Differential Lock - 2WD and FWD

mechanically engaged.

HYDRAULIC SYSTEM

Open Center System

(2) Open Center Valves with detent

Dual Gear Pumps

Implement Pump: 12.5 gpm (47.5 L)

Steering Pump: 7.3 gpm (27.5 L)

Total Flow: 19.8 gpm (75 L)

PTO

540 rpm Mechanical PTO

(1-3/8 in. 6 splines)

Fully Independent, dry clutch

Mechanical Engagement

Flip-up PTO Shaft Guard

HITCH

3-point Category II with flex lower links

and telescoping stabilizers

3664 lbs. Lift Capacity (SAE)

Swinging Drawbar

Mechanical Draft Control

Upper Link Draft Sensing

-T1LO 05

POWERSTAR 75 A LA CARTE ROPS US PRICE LIST

Standard Equipment

STEERING/BRAKES

Hydrostatic Power Steering

Brakes-

Wet disk brakes

Hydraulically assited

INSTRUMENTATION

Analog Instrumentation with warning

lights for air cleaner service,

alternator, oil pressure, fuel

sediment/water sensor, PTO

engagement, head light high beam,

low fuel and parking brake, digital

speed readout

Gauges for fuel level, engine

temperature, tachometer and hour

meter

ELECTRICAL

(1) 730 cca Heavy-duty Battery

Alternator: 120 amp

7-pin Outlet for trailer/implement lighting

and signals

4-pin Power Outlet (30 amp)

8 amp single pole

Auxiliary power socket (cigarette lighter)

LIGHTING

Front: (2) Halogen Headlights and

(2) cab mounted worklights

Rear: (2) cab mounted worklights

Turn Signals/Flashers/Rear Lights

OPERATOR PROTECTIVE STRUCTURE

2-Post Foldable ROPS with ISO-

mounted flat deck platform

Steering Wheel - adjustable tilt

Seat - Vinyl covered with mechanical

suspension, operator's presence

sensor, retractable seat belts and

arm rests

Suspended pedals

Locking brake pedals

MISCELLANEOUS

Pivoting Engine Hood

SMV Emblem

Toolbox

Toolbox on ROPS unit located in fenders

WARRANTY

New Holland Standard Warranty Applies

LOADER:

655TL/710LU NON SELF-LEVELING

Maximum Lift Height @ pivot pin: 127.2"

Dump Clearance: 94.4"

Digging Depth: 6.4"

Lift Capacity

Max Height @ 800mm: 2,478 LBS

59" high @ 800mm: 3,080 LBS

Breakout Force @ 800mm: 3,739 LBS

Reach @ Max Lift Height: 39.5"

Reach @ Ground Level: 90.7"

Bucket Rollback Angle: 45 degrees

Bucket Dump Angle: 60 degrees

Skid Steer or Euro style bucket attach

655TL/715LU SELF-LEVELING

Maximum Lift Height @ pivot pin: 127.2"

Dump Clearance: 94.4"

Digging Depth: 6.4"

Lift Capacity

Max Height @ 800mm: 3,179 LBS

59" high @ 800mm: 4,665 LBS

Breakout Force @ 800mm: 3,860 LBS

Reach @ Max Lift Height: 39.5"

Reach @ Ground Level: 90.7"

Bucket Rollback Angle: 40 degrees

Bucket Dump Angle: 60 degrees

Skid Steer or Euro style bucket attach

POWERSTAR 75 A LA CARTE ROPS US PRICE LIST

Models

COMMERCIAL MODEL	VERSION	ENGINE POWER	Weight	Factory Data	List Price
POWERSTAR 75	Rops	75 HP	6,239 LB	9035979P84	\$46,128.00
Includes the following Equipment 11.2R24 R1W (8232404) \$1,127.00 16.9R30 R1W (8355404) \$2,456.00					

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
PACKAGE SELEC	CTION			
CD T0000 DA	CKAGING			
	LESS PACKAGING			No Charge
POWER TRAIN				
TRANSMISSION				
SD_T2800 SP	PEED			
743552	40 KPH Max Ground Speed		9000201P24	\$258.00
	25 MPH (40 KPH) Transmission for 4WD.			·
	Requires a 12x12 transmission (743546, 330276 or 334176).			
SD_T2810 TR				
Mechanical 743546	Shuttle 12x12 Mechanical Shuttle	1	(901284P66)	(\$1,647.00)
743340	Mechanical PTO		(901204F00)	(\$1,647.00)
	incondition 170			
	PowerStar 75 ONLY			
Power Shutt	le			
330276	12x12 Power Shuttle			No Charge
	Hydraulic PTO			



POWERSTAR 75 A LA CARTE ROPS US PRICE LIST

Power Shut	ttle with Creeper		
334176	12x12 Power Shuttle w/Creeper	9000624P00	\$800.00
	20x20 Power Shuttle with Creeper		
	(12x12 + 8x8 creeper)		
	Hydraulic PTO		
	PowerStar 75 ONLY		
CD T2020 D	ARK LOCK		
SD_T2820 Pa	Hand Brake		No Charge
755176	Hand operated parking brake lever		140 Onarge
743551	Parking Lock	9000039P78	\$51.00
143331		9000039F78	φ51.00
	Transmission parking lock		
	Engaged using the range shift lever		
AXLES			
CD T4040 FI	DON'T AVI F		
SD_T4010 FI 336858	RONT AXLE	(901215P24)	(\$1 EE0 00\
330858	2WD Standard Axle Heavy Duty	(901215P24)	(\$1,558.00)
	Requires 20 MPH (30 KPH)		
	Compatible with 655TL		
	Requires rear wheel weights (330470) ONLY when		
	ordered with 655TL		
	PowerStar 75 ONLY		
744580	4WD Electro Hyd Limited Slip		No Charge
	Electro-hydraulic 4WD engagement		
OTHER			
	NGINE EXHAUST		
743544	Horizontal Exhaust w/Guard		
	Horizontal exhaust		
	if BRAND is New Holland Ag	9000232P44	\$298.00
TIRES	if BRAND is New Holland Ag	9000232P44	\$298.00
TIRES	if BRAND is New Holland Ag	9000232P44	\$298.00
TIRES FRONT	if BRAND is New Holland Ag	9000232P44	\$298.00
-	if BRAND is New Holland Ag	9000232P44	\$298.00
FRONT	if BRAND is New Holland Ag RONT WHEELS AND TIRES	9000232P44	\$298.00
FRONT	RONT WHEELS AND TIRES	9000232P44	\$298.00
FRONT SD_T4940 FI	RONT WHEELS AND TIRES Tires	9000232P44 9000358P02	
FRONT SD_T4940 FI 2WD Front	RONT WHEELS AND TIRES Tires		\$459.00
FRONT SD_T4940 FI 2WD Front 8125801	RONT WHEELS AND TIRES Tires 7.50-16 8 PLY HD 9.5L15 4 RIB 8 PLY	9000358P02	\$459.00
SD_T4940 FI 2WD Front 8125801 8126601 4WD Radia	RONT WHEELS AND TIRES Tires 7.50-16 8 PLY HD 9.5L15 4 RIB 8 PLY	9000358P02 9000468P78	\$459.00 \$601.00
SD_T4940 FI 2WD Front 8125801 8126601	RONT WHEELS AND TIRES Tires 7.50-16 8 PLY HD 9.5L15 4 RIB 8 PLY Il Tires 11.2R20 R1W	9000358P02	\$298.00 \$459.00 \$601.00 \$1,181.00 \$1,290.00

POWERSTAR 75 A LA CARTE ROPS US PRICE LIST

4WD Specialty Tires						
	8284604	13.6-16.1 8PR R3		9000771P42	\$989.00	
	8290904	12.5/80-18 10PR R4		9001258P92	\$1,614.00	
4WD Front Shipping Wheels						
	8299801	Non-Return Ship Wheels - 4WD		9000071P76	\$92.00	

REAR

SD_T4950 REAR WHEELS AND TIRES

Radial Tires			
8351404	14.9R28 R1W	9001569P36	\$2,012.00
	4WD Front Tire - 11.2R20 (8223404)		
	2WD Front Tire - 7.5-16 (8125801)		
	Not compatible with front loader		
	PowerStar 75 ONLY		
8352404	16.9R28 R1W	9001829P88	\$2,346.00
	4WD Front Tire - 12.4R20 (8269405)		
	2WD Front Tire - 9.5L15 4 Rib (8126601) or		
	7.5-16 (8125801)		
	PowerStar 75 ONLY		
8355404	16.9R30 R1W	9001915P68	\$2,456.00
	4WD Front Tire - 11.2R24 (8232404)		
	2WD Front Tire - 9.5L15 4 Rib (8126601) or		
	7.5-16 (8125801)		
Specialty Tir	res		
8320704	16.9-24 6PR R3_Turf	9001725P36	\$2,212.00
	4WD Front Tire - 13.6-16.1 AW (8284604)		
	PowerStar 75 ONLY		
8320604	16.9-24 8PR R4	9001771P38	\$2,271.00
	4WD Front Tire - 12.5/80-18 (8290904)		
	PowerStar 75 ONLY		
8391904	19.5L-24 10 PR R4	9001948P44	\$2,498.00
	4WD Front Tire - 12.5/80-18 (8290904)		
Rear Shippir			
8399801	Non-Returnable Shipping Wheel	9000429P78	\$551.00

336750

84" Bucket

POWERSTAR 75 A LA CARTE ROPS US PRICE LIST

HYDRAULICS			
DEAD DEMOTEO			
REAR REMOTES			
SD T9270 P	EAR REMOTES		
743568	1 Remote 2 Couplers	(900566P28)	(\$726.00)
743300	1 rear remote valve with detent	(9003001 28)	(ψ120.00)
	Treat remote valve with detent		
	PowerStar 75 ONLY		
	1 OWCIOLAL 13 ONE I		
MID-MOUNT			
SD T8280 M	ID-MOUNT VALVES		
338125	2Mid-Mount w/Mec Joystick	9001134P90	\$1,455.00
	2 function mid-mount valve and joystick.		
336780	2Mid-Mount w/Mec Joystick +Div	9001702P74	\$2,183.00
	2 function mid-mount valve and joystick with 3rd function diverter.		
	Requires a 655TL Loader.		
	Bucket with Grapple NOT AVAILABLE as Factory Installed.		
•		•	
LOADER			
LONDEN			
LOADER			
LOTIBLIT			
SD T8110 L0	DADER BRACKETS		
Standard D			
336914	Non Self Leveling Ldr +SSQA	9004634P76	\$5,942.00
	655TL/710LU		
	Non Self Leveling with Skid Steer Attachment		
336732	Non Self Leveling Ldr +Euro	9004634P76	\$5,942.00
	655TL/710LU		
	Non Self Leveling with Euro Style Attachment		
336734	Mech Self Leveling Ldr +SSQA	9005481P84	\$7,028.00
	655TL/715LU		
	Mechanical Self Leveling with Skid Steer Style Attachment		
336736	Mech Self Leveling Ldr +Euro	9005481P84	\$7,028.00
	655TL/715LU		•
	Mechanical Self Leveling with Euro Style Attachment		
	, , , , , , , , , , , , , , , , , , , ,	•	
SD_T8140 B	UCKET		
336748	72" Bucket	9000428P22	\$549.00

\$924.00

9000720P72

Dynamic front fenders



POWERSTAR 75 A LA CARTE ROPS US PRICE LIST

PΊ	ГО				
F	REA	R PTO			
	S	D_T8010 PT		1	
		743566	540/540E PTO	9000472P68	\$606.00
			540/540 Economy PTO		
HI	TCI	1			
F	REA	R 3 POINT HIT	TCH		
	_				
\Box	<u>S</u>	_	POINT HITCH CONTROL	0000400000	#055.00
		332035	Mech 3 Pt Hitch Ground Control	9000198P90	\$255.00
			External mechanical rear ground control for 3pt hitch		
	0	D_T8200 HIT	TCU		
		743595	Lift-O-Matic Plus	9000202P02	\$259.00
		743393	Lift-O-Matic Plus	90002021 02	Ψ239.00
ш			Ent-o-matic rius		
۱۸/	EIG	HTS			
VV	EIG	піз			
	RO	NT			
<u>'</u>	110	IVI			
	s	D T2150 FR	ONT BALLAST		
	Ť	332215	Front Carrier +4 88 lb Weights	9000468P78	\$601.00
			Total weight - 485 lbs (220 kg)		
		333215	Front Carrier +6 88 lb Weights	9000638P82	\$819.00
			Total weight - 661 lbs (300 kg)		
F	REA	R			
_	S	D_T4961 RE			
		330470	4 x 110 lb Rear Wheel Weights	9000488P28	\$626.00
M	SC	ELLANEOUS			
F	EN	DERS FRONT			
	S	_	ONT FENDERS		
ıl		744674	Dynamic Fenders	9000546P78	\$701.00

The Educational Services Commission of New Jersey Grounds Equipment Bid #ESCNJ 18/19-25 ate Approved Co-op #65MCESCCPS



POWERSTAR 75 A LA CARTE ROPS US PRICE LIST

FENDERS REAR					
S	SD_T8700 FE	NDERS			
	744599	Rear Fenders w/Extensions	9000119P34	\$153.00	
		Rear fenders with flat extensions			
OPEI	RATOR'S MA	NUALS			
SD_T9840 COUNTRY CONFIGURATION					
	334256	Canada (FR) Config ROPS		No Charge	
	334257	USA Spanish Configuration		No Charge	

-T1LO 05

Part Number	Description	PowerStar 75	PowerStar 65, 75	Notes
	HYDRAULICS	ROPS	CAB	
19108250	Second rear remote valve with lever control	Х	Х	
19195250	Third rear remote valve with lever control	Х	Х	Tractor must have 2nd rear remote valve installed.
19405250	First rear remote valve flow control	х	Х	Tractor must have 2nd rear remote valve installed. No compatible with 3 rear remote valves.
19124250	Two mid mount valves with joystick control	Х	Х	Includes trim kit
SML362492	Fitting for low pressure direct sump return line when using hydraulic powered implements such as post drivers or hydraulic motors.	Х	Х	3/4 inch - 14BSPP to 5/8 JIC 37 degree flare male fitting
6593621	Fitting for low pressure direct sump return line when using hydraulic powered implements such as post drivers or hydraulic motors.	Х	Х	3/4 inch - 14BSPP to 3/4 JIC 37 degree flare male fitting
	WEIGHTS			
710225250	Front End weight bracket	Х	Х	
10226250	6 Front Weights 88 lbs each (528 lbs total)	X	Х	Requires front end weight bracket #710225250
10471250	4 Rear Wheel Weights 110 lbs each (440 lbs total)	X	Х	For 28" and 30" rear wheels
10465250	6 Rear Wheel Weights 70 lbs each (420 lbs total)	X	Х	For 24" wheels
	ELECTRICAL			
10762251	Rotary Beacon Kit	X		Connects to 12V power socket
10762252	Rotary Beacon Kit		Х	Connects to 12V power socket
19216250	Engine Block Heater Kit			
1864735	4 Pin Outlet (25 amp) Electrical Plug			
6508819	Single Pin Male (8 amp) Electrical Plug			
18122950	Back Up Alarm		X	
	PLATFORM			
18130050	Monitor Mounting Bracket			Requires Cab
18462250	White Canopy	X		FOPS Compliant
18463250	Blue Canopy	X		FOPS Compliant
	LOADER			
	DIA	Х	Х	See 600TL Series Loader Price and Data Pages
	3rd Function Diverter Valve	Х	Х	NOT AVAILABLE AS DIA
15824136	Grill Guard Insert			Order from 600TL Series Loader Price and Data Pages
	MISCELLANEOUS			
10167250	Front Fenders 310mm	х	Х	Requires 4WD - 11.2R20 or 11.2 - 24 or 11.2R24 or 12LLx16 or 12.5/80-18 or 300/70R20 or 320/70R20 or 320/70R24
19429250	Bolt-on Cutting Edge for 72" Bucket	Х	Х	
19430250	Bolt-on Cutting Edge for 84" Bucket	Х	Х	

PowerStar 65 Tire Chart					
Tire Tyre	Application	Rear Tires		Matching 4WD Front Tires	
Tire Type	Application	Tire	Order Code	Tire	Order Code
Radial	Agricultural - R1W	16.9R30	8355404	11.2R24	8232404
Specialty	Industrial - R4	19.5L24	8391904	12.5/80-18	8290904

PowerStar 75 Tire Chart								
Time Tomas	Annlingtion	Rear Tires		Matching 4WD Front Tires		Matching 2	Matching 2WD Front Tires	
Tire Type	Application	Tire	Order Code	Tire	Order Code	Tire	Order Code	
		14.9R28	8351404	11.2R20	8223404	7.5-16	8125801	
		16.9R28	8352404	12.4R20	8269404	9.5L 15	8126601	
Radial	Agricultural - R1W					7.5-16	8125801	
		16.9R30	8355404 11.2R24	44 2024	8232404	9.5L 15	8126601	
		10.9130		0232404	7.5-16	8125801		
	Turf	16.9-24 R3	8320704	13.6-16.1 R3	8284604	N/A		
Specialty	Industrial - R4	16.9-24	8320604	12.5/80-18	8290904	N/A		
		19.5L24	8391904	12.5/80-18	8290904		N/A	

Bid Term: 2/20/19 - 2/19/21



POWERSTAR 90-120 MECHANICAL SHUTTLE CAB US PRICE LIST

Standard Equipment

KEY SELLING POINTS:

- -CommandArc™ ergonomically places most frequently used controls to operator's right
- -High visibility panel option for better view of loader when at full height
- -Ten repositionable vents for heating and air conditioning
- -Full-size instructor seat
- -3.4L, 4-cylinder, 16 valve F5G engines with common rail fuel injection system
- -Tier 4B EPA emissions compliant with Selective Catalytic Reduction (SCR) & Cooled Exhaust Gas Recirculation (CEGR)
- -Factory Installed Loader available

PowerStar 90 86 Gross Engine hp 73 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207 cu in (3.4 L) Displacement

PowerStar 100 98 Gross Engine hp 85 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207 cu in (3.4 L) Displacement

PowerStar 110 107 Gross Engine hp 93 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207 cu in (3.4 L) Displacement

PowerStar 120 117 Gross Engine hp 100 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207 cu in (3.4 L) Displacement

ALL MODELS:

Tier 4B Emissions Compliant: (SCR + CEGR) Electronic Injection Bosch High-pressure Common Rail System Electric Engine Shutoff Hand and Foot Throttle Controls Grid Heater Starting Aid Dual Element Air Filter Constant Engine RPM Vertical Exhaust 30.3 gal Fuel Tank with Guard 2.8 gal AdBlue DEF Tank Parking brake

TRANSMISSION:

Mechanical Shuttle 12 Forward and 12 Reverse Speeds (4) Synchronized Gears (3) Non-synchronized Ranges Forward Reverse Shuttle 19 mph (30 kph) Speed varies with tire selection

LH side steering column mounted

HYDRAULIC SYSTEM:

Open Center System Dual Gear Pumps Implement Pump: 16.9 gpm (63.9 L) Steering Pump: 9.7 gpm (37.0 L) Total Flow: 26.6 gpm (100.8 L) (2) Open Center Remote Valves with detent

3-POINT LIFT SYSTEM: Right hand console mounted lever control Mechanical Draft Control 5,620 Pounds Lift Capacity Category II Ends Telescopic Stabilizers Flexible Lower Link Ends

-T1LI 01

-T1LI 01

POWERSTAR 90-120 MECHANICAL SHUTTLE CAB US PRICE LIST

Standard Equipment

STEERING/BRAKES:
Hydrostatic Power Steering
BrakesWet disk brakes
Hydraulically assited

AXLES:
FRONT - 2WD (19 mph, 30 kph)
Inverted U-section type
Adjustable Tread Width from 57.0 in.

to 79.7 in.
FRONT - 4WD
Limited Slip

- PowerStar 90, 100 & 110: Electrohydraulic FWD Engagement Adjustable Tread Width from

56.6 in. to 76.6 in.

- PowerStar 120:

Heavy Duty Electrohydraulic FWD Engagement Adjustable Tread Width from 56.6 in. to 76.6 in.

REAR

- PowerStar 90, 100 & 110:

Flange Type
Adjustable Tread Width 55.5 in.
to 76.2 in.

- PowerStar 120:

Heavy Duty Flange Type Adjustable Tread Width 55.5 in. to 76.2 in.

REAR DIFFERENTIAL LOCK: Mechanically Engaged

PTO:

Fully Independent Flip-up PTO Shaft Guard - PowerStar 90, 100 & 110:

540 rpm -PowerStar 120:

540/1000 rpm

-Mechanical engagement

-Dry clutch

1-3/8 in. 6 splines

ELECTRICAL:

(1) 800 cca Heavy-Duty Battery - Cab
120 amp Alternator
7-pin Outlet for trailer/implement lighting
 and signals
3-pin Power Outlet (30 amp)
Single Pin (8 amp) Accessory Power
outlet
12V power socket

INSTRUMENTATION:

Analog Instrumentation with warning lights for air cleaner service, alternator, oil pressure, fuel sediment/water sensor, PTO engagement, head light high beam, low fuel and parking brake, digital speed readout

Gauges for fuel level, engine temperature, tachometer and hour meter

LIGHTING:

CAB

OPERATOR PROTECTIVE STRUCTURE:
ROPS protected, flat deck platform
with heat and air conditioning, tinted
windshield, retractable sun screen,
front and rear wiper and washer, two
doors with locks, two external mirrors,
openable side windows, hinged rear
window (opens completely)
Steering Wheel - adjustable tilt
Seat - Cloth covered with air
suspension and 10 degrees of swivel,
operator's presence sensor, retractable
seat belt and arm rests

Instructor Seat
Suspended pedals
Radio, speakers, and antenna

POWERSTAR 90-120 MECHANICAL SHUTTLE CAB US PRICE LIST

Standard Equipment

MISCELLANEOUS:
Pivoting Engine Hood
SMV Emblem
Toolbox

WARRANTY:

New Holland Standard Warranty Applies

LOADER:

655TL/710LU NON SELF-LEVELING

Maximum Lift Height @ pivot pin: 126"

Dump Clearance: 93.6"
Digging Depth: 8.2"

Lift Capacity

Max Height @ 800mm: 2,478 LBS
59" high @ 800mm: 3,080 LBS
Breakout Force @ 800mm: 3,739 LBS
Reach @ Max Lift Height: 39.5"
Reach @ Ground Level: 90.7"
Bucket Rollback Angle: 45 degrees

Bucket Dump Angle: 60 degrees Skid Steer or Euro Style Loader

bucket attach

655TL/715LU SELF-LEVELING

Maximum Lift Height @ pivot pin: 125"

Dump Clearance: 93"
Digging Depth: 8"
Lift Capacity

Max Height @ 800mm: 3,179 LBS
59" high @ 800mm: 4,665 LBS
Breakout Force @ 800mm: 3,860 LBS
Reach @ Max Lift Height: 39.4"
Reach @ Ground Level: 90.5"
Bucket Rollback Angle: 40 degrees
Bucket Dump Angle: 60 degrees
Skid Steer or Euro sytle Loader

bucket attach

665TL/720LU NON SELF-LEVELING

Maximum Lift Height @ pivot pin: 134"

Dump Clearance: 101.4"
Digging Depth: 7"

Lift Capacity

Max Height @ 800mm: 2,632 LBS 59" high @ 800mm: 3,638 LBS

Breakout Force @ 800mm: 4,455 LBS

Reach @ Max Lift Height: 43"
Reach @ Ground Level: 91"

Bucket Rollback Angle: 44 degrees

Bucket Dump Angle: 60 degrees
Skid Steer or Euro style Loader

bucket attach

665TL/725LU SELF-LEVELING

Maximum Lift Height @ pivot pin: 135"

Dump Clearance: 102.2"
Digging Depth: 6.4"

Lift Capacity

Max Height @ 800mm: 3,428 LBS 59" high @ 800mm: 5,549 LBS

Breakout Force @ 800mm: 5,661 LBS

Reach @ Max Lift Height: 43"

Reach @ Ground Level: 93

Bucket Rollback Angle: 40 degrees

Bucket Dump Angle: 60 degrees

Skid Steer or Euro style Loader

bucket attach



POWERSTAR 90-120 MECHANICAL SHUTTLE CAB US PRICE LIST

Models

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price		
POWERSTAR 90 MS	Cab	8,157 LB	9051869P22	\$66,499.00		
Includes the following Equipment 12.4-24 8PR (8235601) \$1,044.00 18.4-30 12PR R1 FLAN (8363801) \$2,533.00						
POWERSTAR 100 MS	Cab	8,157 LB	9053731P86	\$68,887.00		
Includes the following Equipment 12.4-24 8PR (8235601) \$1,0 18.4-30 12PR R1 FLAN (8363801))44.00 \$2,533.00					
POWERSTAR 110 MS	Cab	8,157 LB	9055755P18	\$71,481.00		
Includes the following Equipment 12.4-24 8PR (8235601) \$1,0 18.4-30 12PR R1 FLAN (8363801)	044.00 \$2,533.00					
POWERSTAR 120 MS	Cab	8,157 LB	9058755P06	\$75,327.00		
Includes the following Equipment 4WD+EH Engage+Limited Slip (744581) \$269.00 Heavy Duty Rear Axle (333411) \$646.00 12.4-24 8PR (8235601) \$1,044.00 18.4-30 12PR R1 FLAN (8363801) \$2,533.00 540/1000 RPM PTO (743594) \$544.00						

Factory Supplied Options

Order Code Desc	cription Wei	eight Factory Da	ata List Price
-----------------	--------------	------------------	----------------

OPERATOR PLATFORM

SD_T9200 OPERATOR STRUCTURE #1

	Cab			
	744588	Deluxe Cab		No Charge
		Includes instructor seat, rear wiper and washer,		
		radio & internal mirror		
	334183	Deluxe Cab w/HiVis Panel	9000421P98	\$541.00
		Includes high visibility panel, instructor seat,		
		rear wiper and washer, radio & internal mirror		

8125801 7.50-16 8 PLY HD

POWERSTAR 90-120 MECHANICAL SHUTTLE CAB US PRICE LIST

POWER TRAIN			
TRANSMISSION			
SD_T2810 TF	RANSMISSION		
743546	12x12 Mechanical Shuttle		No Charge
SD_T2820 P	ARK LOCK		
759176	Hand Brake		No Charge
	Hand operated parking brake lever		
743551	Parking Lock	9000039P78	\$51.00
	Transmission parking lock		
	Engaged using the range shift lever		
AXLES			
OD T4040 F	DON'T AVI F		
SD_T4010 FI		(004000DE4)	(\$4.540.00)
336858	2WD Standard Axle Heavy Duty	(901203P54)	(\$1,543.00
	Requires 20 MPH (30 KPH)		
	Compatible with 655TL		
	Requires rear wheel weights (330470) ONLY when		
	ordered with 655TL		
744504	NOT compatible with 665TL	000000000000000000000000000000000000000	Ф000 00
744581	4WD+EH Engage+Limited Slip+HD	9000209P82	\$269.00
	Heavy-Duty Limited Slip		
	Base equipment on PowerStar 120		
	Requires Heavy-Duty rear axle (333411)		
SD_T4810 R	EAR AYLE		
333411	Heavy Duty Rear Axle	9000503P88	\$646.00
	Heavy-Duty Rear Axle		φο 10.00
	Base Equipment on PowerStar 120		
	Required for 34 & 38 inch rear tires		
	NOT compatible with Standard-Duty 4WD		
	front axles (743559 or 744580)		
	NOT compatible with 30 inch or smaller rear tires		
	on PowerStar 90, 100 or 110		
	on overestal ed, 100 or 110		
TRES			
IIICLO			
FRONT			
-	RONT WHEELS AND TIRES		
2WD Front		2000/055/6	***
8126601	9.5L15 4 RIB 8 PLY	9000485P16	\$622.00

9000370P50

\$475.00

POWERSTAR 90-120 MECHANICAL SHUTTLE CAB US PRICE LIST

8125901	10.00-16 8 PLY HD	9000691P86	\$887.00			
4WD Bias Front Tires						
8232304	11.2 x 24 6PR R1	9000755P04	\$968.00			
8235601	12.4-24 8PR	9000814P32	\$1,044.00			
8236501	13.6-24 8PR R1 FLANG	9000997P62	\$1,279.00			
8240604	14.9-24 8PR R1	9001228P50	\$1,575.00			
4WD Radial	Front Tires					
8232404	11.2R24 R1W	9000911P04	\$1,168.00			
8235404	12.4R24 R1W	9001087P32	\$1,394.00			
8236404	13.6R24 R1W	9001330P68	\$1,706.00			
8239404	14.9R24 R1W	9001637P22	\$2,099.00			
4WD Specialty Front Tires						
8290904	12.5/80-18 10PR R4	9001300P26	\$1,667.00			
8247404	11.2R28 R1W	9001123P98	\$1,441.00			

REAR

SD_T4950 REAR WHEELS AND TIRES

Bias Rear Ti	res		
8355304	16.9-30 6PR R1	9001720P68	\$2,206.00
	4WD Front Tire - 11.2-24 (8232304)		
	2WD Front Tire - 9.5L-15 4 rib (8126601)		
8363801	18.4-30 12PR R1 FLAN	9001975P74	\$2,533.00
	4WD Front Tire - 12.4-24 (8235601)		
	2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)		
8364604	16.9-34 8PR R1	9001421P94	\$1,823.00
	4WD Front Tire - 13.6-24 (8236501)		
	2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)		
8365501	18.4-34 10PR	9002176P98	\$2,791.00
	4WD Front Tire - 14.9-24 (8240604)		
	2WD Front Tire - 10.00-16 (8125901)		
Radial Rear	Tires		
8355404	16.9R30 R1W	9001975P74	\$2,533.00
	4WD Front Tire - 11.2R24 (8232404)		
	2WD Front Tire - 7.50-16 (8125801) or 9.5L-15 4 rib (8122601)		
8357404	18.4R30 R1W	9002635P62	\$3,379.00
	4WD Front Tire - 12.4R24 (8235404)		
	2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)		
8302804	16.9R34 R1W	9001896P96	\$2,432.00
	4WD Front Tire - 13.6R24 (8236404)		
	2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)		
8365404	18.4R34 R1W	9002853P24	\$3,658.00
	4WD Front Tire - 14.9R24 (8239404)		
	2WD Front Tire - 10.00-16 (8125901)		
Specialty Re	ar Tires		
8391904	19.5L-24 10 PR R4	9002013P18	\$2,581.00
	4WD Front Tire - 12.5/80-18 (8290904)		



POWERSTAR 90-120 MECHANICAL SHUTTLE CAB US PRICE LIST

	8372404	13.6R38 R1W 8372404	9001770P60	\$2,270.00
		4WD Front Tire - 11.2R28 (8247404)		
L		2WD Front Tire - 7.50-16 (8125801)		

HYDRAULICS

MID-MOUNT

SD T8280 MID-MOUNT VALVES

 3D_10200 WID-WOONT VALVES					
	338125	2Mid-Mount w/Mec Joystick		9001123P98	\$1,441.00
		2 function mid-mount valve and joystick			
	336780	2Mid-Mount w/Mec Joystick +Div		9001686P36	\$2,162.00
		2 function mid-mount valve and joystick with 3rd function diverter			
		Requires a Loader			
		Bucket with Grapple NOT AVAILABLE as Factory Installed			

LOADER

LOADER

SD_T8110 LOADER BRACKETS

Standard Du	uty Loader		
336914	Non Self Leveling Ldr +SSQA	9004590P30	\$5,885.00
	655TL/710LU		
	Non Self Leveling with Skid Steer Attachment		
	NOT compatible with 38" rear tires		
336732	Non Self Leveling Ldr +Euro	9004590P30	\$5,885.00
	655TL/710LU		
	Non Self Leveling with Euro Style Attachment		
	NOT compatible with 38" rear tires		
336734	Mech Self Leveling Ldr +SSQA	9005429P58	\$6,961.00
	655TL/715LU		
	Mechanical Self Leveling with Skid Steer Style Attachment		
	NOT compatible with 38" rear tires		
336736	Mech Self Leveling Ldr +Euro	9005429P58	\$6,961.00
	655TL/715LU		
	Mechanical Self Leveling with Euro Style Attachment		
	NOT compatible with 38" rear tires		
Heavy Duty	Loader		
336740	HD Non Self Leveling Ldr +SSQA	9005319P60	\$6,820.00
	665TL/720LU		
	Non Self Leveling with Skid Steer Style Attachment		
336742	HD Non Self Leveling Ldr +Euro	9005319P60	\$6,820.00
	665TL/720LU		
	Non Self Leveling with Euro Style Attachment		

Bid Term: 2/20/19 - 2/19/21

336744	HD Self Leveling Ldr +SSQA	9006162P78	\$7,901.00
	665TL/725LU		
	Mechanical Self Leveling with Skid Steer Style Attachment		
336746	HD Self Leveling Ldr +Euro	9006162P78	\$7,901.0
	665TL/725LU		
	Mechanical Self Leveling with Euro Style Attachment		
SD_T8140 B		0000404P20	ФЕ 4.4. О
336748	72" Bucket	9000424P32	\$544.0
336750	84" Bucket	9000713P70	\$915.00
РТО			
REAR PTO			
	TO.		
SD_T8010 P 743594	540/1000 RPM PTO	9000424P32	\$544.00
743394	340/1000 KFWIFTO	9000424F32	φ544.00
НІТСН			
REAR 3 POINT H	ITCH		
SD T8130 3	POINT HITCH CONTROL		
332035	Mech 3 Pt Hitch Ground Control	9000197P34	\$253.00
SD_T8200 H	•	,	
759058	MDC - REAR HPL - 2 A	9000811P20	\$1,040.00
	2 auxiliary lift rams	00000111 20	ψ1,010.0
	8,000 lbs lift capacity		
	o,see in suprairy		
	Requires Heavy Duty front and rear axles		
•		•	
WEIGHTS			
FRONT			
SD_T2150 F	RONT BALLAST		
333215	Front Carrier +6 88 lb Weights	9000620P10	\$795.0
	Total weight - 661 lbs (300 kg)		
335215	8 WEIGHTS 40 KG - CA	9000784P68	\$1,006.0
1 1			+ /

Total weight - 837 lbs (380 kg)

REAR	}			
SD	_T4961 RE	AR BALLAST		
	330470	4 x 110 lb Rear Wheel Weights	9000483P60	\$620.00
		Total weight - 440 lbs (200 kg)		
		NOT compatible with 24" rear tires option		
		Required with 2WD HD front axle		

OPERATOR'S MANUALS

SD_T9840 COUNTRY CONFIGURATION

	334255	USA English Configuration		No Charge
	334256	Canada (FR) Config ROPS		No Charge
		French operator manual		
	334257	USA Spanish Configuration		No Charge
		Spanish operator manual		



Standard Equipment

KEY SELLING POINTS:

- -CommandArc™ ergonomically places most frequently used controls to operator's right
- -3.4L, 4-cylinder, 16 valve F5G engines with common rail fuel injection system
- -Tier 4B EPA emissions compliant with Selective Catalytic Reduction (SCR) & Cooled Exhaust Gas Recirculation (CEGR)
- -Factory Installed Loader available

PowerStar 90 86 Gross Engine hp 73 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207 cu in (3.4 L) Displacement

PowerStar 100 98 Gross Engine hp 85 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207 cu in (3.4 L) Displacement

PowerStar 110 107 Gross Engine hp 93 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207 cu in (3.4 L) Displacement

PowerStar 120 117 Gross Engine hp 100 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207 cu in (3.4 L) Displacement ALL MODELS:

Tier 4B Emissions Compliant: (SCR + CEGR) Electronic Injection Bosch High-pressure Common Rail System Electric Engine Shutoff Hand and Foot Throttle Controls Grid Heater Starting Aid Dual Element Air Filter Constant Engine RPM Vertical Exhaust 30.3 gal Fuel Tank with Guard 2.8 gal AdBlue DEF Tank Parking brake

TRANSMISSION:

Mechanical Shuttle 12 Forward and 12 Reverse Speeds (4) Synchronized Gears (3) Non-synchronized Ranges Forward Reverse Shuttle 19 mph (30 kph) Speed varies with tire selection

LH side steering column mounted

HYDRAULIC SYSTEM:

Open Center System Dual Gear Pumps Implement Pump: 16.9 gpm (63.9 L) Steering Pump: 9.7 gpm (37.0 L) Total Flow: 26.6 gpm (100.8 L) (2) Open Center Remote Valves with detent

3-POINT LIFT SYSTEM: Right hand console mounted lever control Mechanical Draft Control 5,620 Pounds Lift Capacity Category II Ends Telescopic Stabilizers Flexible Lower Link Ends

-T1LI 02

-T1LI 02

POWERSTAR 90-120 MECHANICAL SHUTTLE ROPS US PRICE LIST

Standard Equipment

STEERING/BRAKES: Hydrostatic Power Steering Brakes-Wet disk brakes Hydraulically assited AXLES:

FRONT - 2WD (19 mph, 30 kph) Inverted U-section type Adjustable Tread Width from 57.0 in. to 79.7 in. FRONT - 4WD Limited Slip - PowerStar 90, 100 & 110: Electrohydraulic FWD Engagement Adjustable Tread Width from

- PowerStar 120: Heavy Duty Electrohydraulic FWD Engagement Adjustable Tread Width from 56.6 in. to 76.6 in.

56.6 in. to 76.6 in.

REAR

- PowerStar 90, 100 & 110: Flange Type Adjustable Tread Width 55.5 in. to 76.2 in.

- PowerStar 120:

Heavy Duty Flange Type Adjustable Tread Width 55.5 in. to 76.2 in.

REAR DIFFERENTIAL LOCK: Mechanically Engaged

PTO:

Fully Independent Flip-up PTO Shaft Guard PowerStar 90, 100 & 110: 540 rpm PowerStar 120: 540/1000 rpm -Mechanical Engagment -Dry clutch 1-3/8 in. 6 splines

ELECTRICAL:

(1) 800 cca Heavy-Duty Battery - ROPS 120 amp Alternator 7-pin Outlet for trailer/implement lighting and signals 3-pin Power Outlet (30 amp) Single Pin (8 amp) Accessory Power outlet 12V power socket

INSTRUMENTATION:

Analog Instrumentation with warning lights for air cleaner service, alternator, oil pressure, fuel sediment/water sensor, PTO engagement, head light high beam, low fuel and parking brake, digital speed readout Gauges for fuel level, engine temp, tachometer and hour meter

LIGHTING:

ROPS

Front: (2) Halogen Headlights Rear: (1) ROPS mounted worklight Turn Signals/Flashers/Rear Lights

OPERATOR PROTECTIVE STRUCTURE: ROPS MODELS 2-Post Foldable ROPS with ISOmounted flat deck platform Steering Wheel - adjustable tilt Seat - Vinyl covered with mechanical suspension, operator's presence sensor, retractable seat belts and arm rests Suspended pedals

MISCELLANEOUS: Pivoting Engine Hood SMV Emblem Toolbox

Locking brake pedals



Standard Equipment

WARRANTY:

New Holland Standard Warranty Applies

LOADER:

655TL/710LU NON SELF-LEVELING

Maximum Lift Height @ pivot pin: 126"

Dump Clearance: 93.6"

Digging Depth: 8.2"

Lift Capacity

Max Height @ 800mm: 2,478 LBS

59" high @ 800mm: 3,080 LBS

Breakout Force @ 800mm: 3,739 LBS

Reach @ Max Lift Height: 39.5"

Reach @ Ground Level: 90.7"

Bucket Rollback Angle: 45 degrees

Bucket Dump Angle: 60 degrees

Skid Steer or Euro Style Loader

bucket attach

655TL/715LU SELF-LEVELING

Maximum Lift Height @ pivot pin: 125"

Dump Clearance: 93"

Digging Depth: 8"

Lift Capacity

Max Height @ 800mm: 3,179 LBS

59" high @ 800mm: 4,665 LBS

Breakout Force @ 800mm: 3,860 LBS

Reach @ Max Lift Height: 39.4"

Reach @ Ground Level: 90.5"

Bucket Rollback Angle: 40 degrees

Bucket Dump Angle: 60 degrees

Skid Steer or Euro sytle Loader

bucket attach

665TL/720LU NON SELF-LEVELING

Maximum Lift Height @ pivot pin: 134"

Dump Clearance: 101.4"

Digging Depth: 7"

Lift Capacity

Max Height @ 800mm: 2,632 LBS

59" high @ 800mm: 3,638 LBS

Breakout Force @ 800mm: 4,455 LBS

Reach @ Max Lift Height: 43"

Reach @ Ground Level: 91"

Bucket Rollback Angle: 44 degrees

Bucket Dump Angle: 60 degrees

Skid Steer or Euro style Loader

bucket attach

665TL/725LU SELF-LEVELING

Maximum Lift Height @ pivot pin: 135"

Dump Clearance: 102.2"

Digging Depth: 6.4"

Lift Capacity

Max Height @ 800mm: 3,428 LBS

59" high @ 800mm: 5,549 LBS

Breakout Force @ 800mm: 5,661 LBS

Reach @ Max Lift Height: 43"

Reach @ Ground Level: 93

Bucket Rollback Angle: 40 degrees

Bucket Dump Angle: 60 degrees

Skid Steer or Euro style Loader

bucket attach

41

Models

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price		
POWERSTAR 90 MS	Rops	8,157 LB	9043612P14	\$55,913.00		
Includes the following Equipment 12.4-24 8PR (8235601) \$1,0 18.4-30 12PR R1 FLAN (8363801)	12.4-24 8PR (8235601) \$1,044.00					
10.4-30 12FK KT FLAN (0303001)	\$2,533.00					
POWERSTAR 100 MS	Rops	8,157 LB	9045474P78	\$58,301.00		
, , , ,	Includes the following Equipment					
POWERSTAR 110 MS	Rops	8,157 LB	9047498P10	\$60,895.00		
Includes the following Equipment 12.4-24 8PR (8235601) \$1,0 18.4-30 12PR R1 FLAN (8363801))44.00) \$2,533.00					
POWERSTAR 120 MS	Rops	8,157 LB	9050497P98	\$64,741.00		
Includes the following Equipment 4WD+EH Engage+Limited Slip (744581) \$269.00 Heavy Duty Rear Axle (333411) \$646.00 12.4-24 8PR (8235601) \$1,044.00 18.4-30 12PR R1 FLAN (8363801) \$2,533.00 540/1000 RPM PTO (743594) \$544.00						

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

OPERATOR PLATFORM

SD_T9200 OPERATOR STRUCTURE #1

ROPS					
	392315	Platform w/Foldable ROPS			No Charge
		Includes tilt column			
	334190	Deluxe Platform w/FOPS		9001258P14	\$1,613.00
		Includes tilt column, FOPS canopy, noise reduction kit			
		and 12V power outlet			



POWER TRAIN			
TDANICMICCION			
TRANSMISSION			
SD T2810 TR	PANSMISSION		
743546	12x12 Mechanical Shuttle		No Charge
7 100 10	TEXTE Modification of the title		Tto Onargo
SD_T2820 PA	ARK LOCK		
759176	Hand Brake		No Charge
	Hand operated parking brake lever		
743551	Parking Lock	9000039P78	\$51.00
	Transmission parking lock		
	Engaged using the range shift lever		
AXLES			
SD_T4010 FF			
336858	2WD Standard Axle Heavy Duty	(901203P54)	(\$1,543.00)
	Requires 20 MPH (30 KPH)		
	Compatible with 655TL		
	Requires rear wheel weights (330470) ONLY when		
	ordered with 655TL		
	NOT compatible with 665TL		
744581	4WD+EH Engage+Limited Slip+HD	9000209P82	\$269.00
	Heavy-Duty Limited Slip		
	Base equipment on PowerStar 120		
	Requires Heavy-Duty rear axle (333411)		
CD T4040 DE	CAD AVI E		
SD_T4810 RE	Heavy Duty Rear Axle	9000503P88	\$646.00
333411	Heavy-Duty Rear Axle	9000303F88	φ040.00
	Base Equipment on PowerStar 120		
	Required for 34 & 38 inch rear tires		
	NOT compatible with Standard-Duty 4WD		
	front axles (743559 or 744580)		
	NOT compatible with 30 inch or smaller rear tires		
	on PowerStar 90, 100 or 110		
	On rowerstar 30, 100 or 110		
TIRES			
TIKES			
FRONT			
SD_T4940 FF	RONT WHEELS AND TIRES		
2WD Front	Tires		
8126601	9.5L15 4 RIB 8 PLY	9000485P16	\$622.00
8125801	7.50-16 8 PLY HD	9000370P50	\$475.00

8125901	10.00-16 8 PLY HD	9000691P86	\$887.00				
4WD Bias F	4WD Bias Front Tires						
8232304	11.2 x 24 6PR R1	9000755P04	\$968.00				
8235601	12.4-24 8PR	9000814P32	\$1,044.00				
8236501	13.6-24 8PR R1 FLANG	9000997P62	\$1,279.00				
8240604	14.9-24 8PR R1	9001228P50	\$1,575.00				
4WD Radia	Front Tires						
8232404	11.2R24 R1W	9000911P04	\$1,168.00				
8235404	12.4R24 R1W	9001087P32	\$1,394.00				
8236404	13.6R24 R1W	9001330P68	\$1,706.00				
8239404	14.9R24 R1W	9001637P22	\$2,099.00				
4WD Specialty Front Tires							
8290904	12.5/80-18 10PR R4	9001300P26	\$1,667.00				
8247404	11.2R28 R1W	9001123P98	\$1,441.00				

REAR

SD_T4950 REAR WHEELS AND TIRES

Bias Rear Ti	res		
8355304	16.9-30 6PR R1	9001720P68	\$2,206.00
	4WD Front Tire - 11.2-24 (8232304)		
	2WD Front Tire - 9.5L-15 4 rib (8126601)		
8363801	18.4-30 12PR R1 FLAN	9001975P74	\$2,533.00
	4WD Front Tire - 12.4-24 (8235601)		
	2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)		
8364604	16.9-34 8PR R1	9001421P94	\$1,823.00
	4WD Front Tire - 13.6-24 (8236501)		
	2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)		
8365501	18.4-34 10PR	9002176P98	\$2,791.00
	4WD Front Tire - 14.9-24 (8240604)		
	2WD Front Tire - 10.00-16 (8125901)		
Radial Rear	Tires		
8355404	16.9R30 R1W	9001975P74	\$2,533.00
	4WD Front Tire - 11.2R24 (8232404)		
	2WD Front Tire - 7.50-16 (8125801) or 9.5L-15 4 rib (8122601)		
8357404	18.4R30 R1W	9002635P62	\$3,379.00
	4WD Front Tire - 12.4R24 (8235404)		
	2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)		
8302804	16.9R34 R1W	9001896P96	\$2,432.00
	4WD Front Tire - 13.6R24 (8236404)		
	2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)		
8365404	18.4R34 R1W	9002853P24	\$3,658.00
	4WD Front Tire - 14.9R24 (8239404)		
	2WD Front Tire - 10.00-16 (8125901)		
Specialty Re	ar Tires		
8391904	19.5L-24 10 PR R4	9002013P18	\$2,581.00
	4WD Front Tire - 12.5/80-18 (8290904)		

The Educational Services Commission of New Jersey
NJ State Approved Co-op #65MCESCCPS
NEW HOLLAND

Grounds Equipment Bid #ESCNJ 18/19-25
-T1LI 02

POWERSTAR 90-120 MECHANICAL SHUTTLE ROPS US PRICE LIST

AGRICULTURE

Г	8372404	13.6R38 R1W 8372404	9001770P60	\$2,270.00
		4WD Front Tire - 11.2R28 (8247404)		
		2WD Front Tire - 7.50-16 (8125801)		

HYDRAULICS

MID-MOUNT

SD T8280 MID-MOUNT VALVES

 CB_10200 WIID WOONT VALVEO					
	338125	2Mid-Mount w/Mec Joystick		9001123P98	\$1,441.00
		2 function mid-mount valve and joystick			
	336780	2Mid-Mount w/Mec Joystick +Div		9001686P36	\$2,162.00
		2 function mid-mount valve and joystick with 3rd function diverter			
		Requires a Loader			
		Bucket with Grapple NOT AVAILABLE as Factory Installed			

LOADER

LOADER

SD_T8110 LOADER BRACKETS

Standard Du	ıty Loader		
336914	Non Self Leveling Ldr +SSQA	9004590P30	\$5,885.00
	655TL/710LU		
	Non Self Leveling with Skid Steer Attachment		
	NOT compatible with 38" rear tires		
336732	Non Self Leveling Ldr +Euro	9004590P30	\$5,885.00
	655TL/710LU		
	Non Self Leveling with Euro Style Attachment		
	NOT compatible with 38" rear tires		
336734	Mech Self Leveling Ldr +SSQA	9005429P58	\$6,961.00
	655TL/715LU		
	Mechanical Self Leveling with Skid Steer Style Attachment		
	NOT compatible with 38" rear tires		
336736	Mech Self Leveling Ldr +Euro	9005429P58	\$6,961.00
	655TL/715LU		
	Mechanical Self Leveling with Euro Style Attachment		
	NOT compatible with 38" rear tires		
Heavy Duty	Loader		
336740	HD Non Self Leveling Ldr +SSQA	9005319P60	\$6,820.00
	665TL/720LU		
	Non Self Leveling with Skid Steer Style Attachment		
336742	HD Non Self Leveling Ldr +Euro	9005319P60	\$6,820.00
	665TL/720LU		
	Non Self Leveling with Euro Style Attachment		

Grounds Equipment Bid #ESCNJ 18/19-25
-T1LI 02

POWERSTAR 90-120 MECHANICAL SHUTTLE ROPS US PRICE LIST

	336744	HD Self Leveling Ldr +SSQA	9006162P78	\$7,901.00
		665TL/725LU		
		Mechanical Self Leveling with Skid Steer Style Attachment		
	336746	HD Self Leveling Ldr +Euro	9006162P78	\$7,901.00
		665TL/725LU		
		Mechanical Self Leveling with Euro Style Attachment		
		· · · · · · · · · · · · · · · · · · ·	•	
	SD_T8140 BU	JCKET		
	336748	72" Bucket	9000424P32	\$544.00
	336750	84" Bucket	9000713P70	\$915.00
PT	0			
R	EAR PTO			
	SD_T8010 P1	70		
	743594	540/1000 RPM PTO	9000424P32	\$544.00
	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	3-0/1000 KI WIT TO	30004241 32	ψ344.00]
НІТ	.cn			
ПП	СП			
RI	EAR 3 POINT HI	TCH		
		· • · · · · · · · · · · · · · · · · · ·		
	SD_T8130 3	POINT HITCH CONTROL		
	332035	Mech 3 Pt Hitch Ground Control	9000197P34	\$253.00
	SD_T8200 HI	TCH		
	759058	MDC - REAR HPL - 2 A	9000811P20	\$1,040.00
		2 auxiliary lift rams		
		8,000 lbs lift capacity		
Ш		Requires Heavy Duty front and rear axles		
WE	IGHTS			
FF	RONT			
	OD T0450 F	OONT DALLACT		
		RONT BALLAST	0000630040	\$70E 00
	333215	Front Carrier +6 88 lb Weights	9000620P10	\$795.00
\vdash	335215	Total weight - 661 lbs (300 kg) 8 WEIGHTS 40 KG - CA	9000784P68	\$1,006.00
	333215	Total weight - 837 lbs (380 kg)	9000704F08	φ1,000.00
Щ.		Total weight - 03/ ibs (300 kg)		

334256

334257

Canada (FR) Config ROPS

French operator manual

USA Spanish Configuration

Spanish operator manual

POWERSTAR 90-120 MECHANICAL SHUTTLE ROPS US PRICE LIST

RI	REAR						
	SD_T4961 RE	EAR BALLAST					
	330470	4 x 110 lb Rear Wheel Weights		9000483P60	\$620.00		
		Total weight - 440 lbs (200 kg)					
		NOT compatible with 24" rear tires option					
		Required with 2WD HD front axle					
OP	ERATOR'S MA	NUALS					
	SD_T9840 COUNTRY CONFIGURATION						
	334255	USA English Configuration			No Charge		

No Charge

No Charge

-T1LJ 01

POWERSTAR 90-120 PS UTILITY CAB US PRICE LIST

Standard Equipment

KEY SELLING POINTS:

- -CommandArc™ ergonomically places most frequently used controls to operator's right
- -Ten repositionable vents for heating and air conditioning
- -Full-size instructor seat
- -Hydraulic shuttle lever
- -3.4L, 4-cylinder, 16 valve F5G engines with common rail fuel injection system
- -Tier 4B EPA emissions compliant with Selective Catalytic Reduction (SCR) & Cooled Exhaust Gas Recirculation (CEGR)
- -Factory Installed Loader available

PowerStar 90 86 Gross Engine hp 73 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207 cu in (3.4 L) Displacement

PowerStar 100 99 Gross Engine hp 85 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207 cu in (3.4 L) Displacement

PowerStar 110 107 Gross Engine hp 93 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207 cu in (3.4 L) Displacement

PowerStar 120 117 Gross Engine hp 100 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207 cu in (3.4 L) Displacement Tier 4B Emissions Compliant:
 (SCR + CEGR)

Electronic Injection Bosch
 High-pressure Common Rail System

Electric Engine Shutoff
Hand and Foot Throttle Controls
Grid Heater Starting Aid
Dual Element Air Filter
Constant Engine RPM
Vertical Exhaust
30.3 gal Fuel Tank with Guard
2.8 gal AdBlue DEF Tank
Parking brake

TRANSMISSION:

ALL MODELS:

LH side steering column mounted Power Shuttle

- 12 Forward and 12 Reverse Speeds
- (4) Synchronized Gears
- (3) Non-synchronized Ranges
 Forward Reverse Synchronized Shuttle
 19 mph (30 kph)

Speed varies with tire selection

STEERING/BRAKES:

Hydrostatic Power Steering Brakes-

Wet disk brakes Hydraulically assited

AXLES:

FRONT - 4WD Limited Slip

- PowerStar 90, 100 & 110:

Electrohydraulic FWD Engagement Adjustable Tread Width from 56.6 in. to 76.6 in.

- PowerStar 120:

Heavy Duty Electrohydraulic FWD Engagement
Adjustable Tread Width from 56.6 in. to 76.6 in.

-T1LJ 01

POWERSTAR 90-120 PS UTILITY CAB US PRICE LIST

Standard Equipment

AXLES Continued:

REAR

- PowerStar 90, 100 & 110:

Flange Type

Adjustable Tread Width 55.5 in.

to 76.2 in.

- PowerStar 120:

Heavy Duty Flange Type

Adjustable Tread Width 55.5 in.

to 76.2 in.

HYDRAULIC SYSTEM:

Open Center System

Dual Gear Pumps

Implement Pump: 16.9 gpm (63.9 L)

Steering Pump: 9.7 gpm (37.0 L)

Total Flow: 26.6 gpm (100.8 L)

(2) Open Center Remote Valves with

detent

2 Function Mid Mount Valve and Joystick

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent

Flip-up PTO Shaft Guard

PowerStar 90, 100 & 110:

540 rpm Hydraulic

PowerStar 120:

540/1000 rpm Hydraulic

-Electronic engagement

-Wet clutch

1-3/8 in. 6 splines

3-POINT LIFT SYSTEM:

Right hand console mounted

lever control

Mechanical Draft Control

5,620 Pounds Lift Capacity

Category II Ends

Telescopic Stabilizers

Flexible Lower Link Ends

ELECTRICAL:

(1) 800 cca Heavy-Duty Battery - Cab

120 amp Alternator

7-pin Outlet for trailer/implement lighting

and signals

3-pin Power Outlet (30 amp)

Single Pin (8 amp) Accessory Power

outlet

12V power socket

INSTRUMENTATION:

Analog Instrumentation with warning

lights for air cleaner service,

alternator, oil pressure, fuel

sediment/water sensor, PTO

engagement, head light high beam,

low fuel and parking brake,

digital speed readout

Gauges for fuel level, engine

temperature, tachometer and hour

meter

LIGHTING:

Front: (2) Halogen Headlights and

(2) cab mounted worklights

Rear: (2) cab mounted worklights

Turn Signals/Flashers/Rear Lights

OPERATOR PROTECTIVE STRUCTURE:

CAB MODELS

ROPS protected, flat deck platform

with heat and air conditioning, tinted

windshield, retractable sun screen,

front and rear wiper and washer, two

doors with locks, two external mirrors,

openable side windows, hinged rear

window (opens completely)

Steering Wheel - adjustable tilt

Seat - Cloth covered with air

suspension and 10 degrees of swivel,

operator's presence sensor, retractable

seat belt and arm rests

Instructor Seat

Suspended pedals

Radio, speakers, and antenna



Grounds Equipment Bid #ESCNJ 18/19-25
-T1LJ 01

POWERSTAR 90-120 PS UTILITY CAB US PRICE LIST

Standard Equipment

MISCELLANEOUS:
Pivoting Engine Hood
SMV Emblem
Toolbox

WARRANTY:

New Holland Standard Warranty Applies

LOADER:

Maximum Lift Height @ pivot pin: 126"

Dump Clearance: 93.6"

Digging Depth: 8.2"

Lift Capacity

Max Height @ 800mm: 2,478 LBS

59" high @ 800mm: 3,080 LBS

Breakout Force @ 800mm: 3,739 LBS

Reach @ Max Lift Height: 39.5"

Reach @ Ground Level: 90.7"

Bucket Rollback Angle: 45 degrees

Bucket Dump Angle: 60 degrees

Skid Steer or Euro Style Loader

bucket attach

655TL/710LU NON SELF-LEVELING

655TL/715LU SELF-LEVELING

Maximum Lift Height @ pivot pin: 125"

Dump Clearance: 93"

Digging Depth: 8"

Lift Capacity

Max Height @ 800mm: 3,179 LBS

59" high @ 800mm: 4,665 LBS

Breakout Force @ 800mm: 3,860 LBS

Reach @ Max Lift Height: 39.4"

Bucket Rollback Angle: 40 degrees Bucket Dump Angle: 60 degrees Skid Steer or Euro sytle Loader

Reach @ Ground Level: 90.5"



Models

VERSION	Weight	Factory Data	List Price					
Cab	8,157 LB	9053816P10	\$68,995.00					
Includes the following Equipment 12.4-24 8PR (8235601) \$1,044.00 18.4-30 12PR R1 FLAN (8363801) \$2,533.00								
Cab	10,031 LB	9055678P74	\$71,383.00					
Includes the following Equipment 12.4-24 8PR (8235601) \$1,044.00 18.4-30 12PR R1 FLAN (8363801) \$2,533.00								
Cab	8,157 LB	9057702P06	\$73,977.00					
)44.00) \$2,533.00								
	1							
Cab	8,157 LB	9060701P94	\$77,823.00					
ncludes the following Equipment 4WD+EH Engage+Limited Slip (744581) \$269.00 Heavy Duty Rear Axle (333411) \$646.00 12.4-24 8PR (8235601) \$1,044.00 18.4-30 12PR R1 FLAN (8363801) \$2,533.00 540/1000 RPM PTO (743594) \$544.00								
	044.00 \$2,533.00 Cab 044.00 \$2,533.00 Cab 044.00 \$2,533.00 Cab 044.00 \$2,533.00	044.00 \$2,533.00 Cab 10,031 LB 044.00 \$2,533.00 Cab 8,157 LB 044.00 \$2,533.00 Cab 8,157 LB 044.00 \$2,533.00	044.00 \$2,533.00 Cab 10,031 LB 9055678P74 044.00 \$2,533.00 Cab 8,157 LB 9057702P06 044.00 \$2,533.00 Cab 8,157 LB 9060701P94 14581) \$269.00 \$646.00 044.00 \$2,533.00					



Factory Supplied Options

Ord	ler Code	Description	Weight	Factory Data	List Price
PACK	AGE SELEC	CTION			
SI	D_T9980 PA	CKAGING			
ΠĬ	759310	UTILITY PACKAGE		9005728P32	\$7,344.00
		UTILITY Package and Pricing Includes:			
		UTILITY package discount			
		12x12 Power shuttle transmission (330276)			
		Deluxe cab with instructor seat (744588)			
		2 Function mid mount valve and joystick (338125)			
		Requires one selection for each of the following:			
		Loader:			
		655TL loader (select one)			
		Bucket:			
		72" or 84" bucket (select one)			
		Tires:			
		Bias ply Ag or Industrial bar tires (select front and rear)			
POWE	ER TRAIN				
TRAI	NSMISSION				
SI	D_T2800 SP		1	1	
	759059	40KPH - REAL ALL TYR		9000199P68	\$256.00
ШШ		25 MPH (40 KPH) Transmission for 4WD			
01	D T0040 TD	ANOMIOGION			
		ANSMISSION 12x12 Power Shuttle w/Creeper	1	9000478P92	\$614.00
	334176	•		9000476F92	\$614.00
		20x20 Power Shuttle with Creeper (12x12 + 8x8 creeper)			
		Hydraulic PTO			
шШ		Tryuraulic 1 TO			
SI	D T2820 PA	RK LOCK			
ΠĬ	743551	Parking Lock		9000039P78	\$51.00
1 1 1		I 2		1	Ψ000

Transmission parking lock

Engaged using the range shift lever

Α	XLI	ES			
	0	D_T4010 FR	ONT AVIE		
	ૉ	744581	4WD+EH Engage+Limited Slip+HD	9000209P82	\$269.00
		7 1 100 1	Heavy-Duty Limited Slip		Ψ200.00
			Base equipment on PowerStar 120		
			Requires Heavy-Duty rear axle (333411)		
			reduires fleavy buty fear date (600-11)		
	S	D_T4810 RE	AR AXLE		
		333411	Heavy Duty Rear Axle	9000503P88	\$646.00
			Heavy-Duty Rear Axle		
			Base Equipment on PowerStar 120		
			Required for 34 & 38 inch rear tires		
			NOT compatible with Standard-Duty 4WD		
			front axles (743559 or 744580)		
			NOT compatible with 30 inch or smaller rear tires		
			on PowerStar 90, 100 or 110		
TII	RES	S			
		-			
F	RO	NT			
	S	D_T4940 FR	ONT WHEELS AND TIRES		
		4WD Bias Fr	ont Tires		
		8232304	11.2 x 24 6PR R1	9000755P04	\$968.00
		8235601	12.4-24 8PR	9000814P32	\$1,044.00
		8236501	13.6-24 8PR R1 FLANG	9000997P62	\$1,279.00
		8240604	14.9-24 8PR R1	9001228P50	\$1,575.00
		4WD Specia	ty Front Tires		
		8290904	12.5/80-18 10PR R4	9001300P26	\$1,667.00
F	REA	R			
	S	D_T4950 RE	AR WHEELS AND TIRES		
		Bias Rear Ti			
		8355304	16.9-30 6PR R1	9001720P68	\$2,206.00
			4WD Front Tire - 11.2-24 (8232304)		
_			2WD Front Tire - 9.5L-15 4 rib (8126601)		
		8363801	18.4-30 12PR R1 FLAN	9001975P74	\$2,533.00
			4WD Front Tire - 12.4-24 (8235601)		
	_		2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)		
		8364604	16.9-34 8PR R1	9001421P94	\$1,823.00
			4WD Front Tire - 13.6-24 (8236501)		
			2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)		

	8365501	18.4-34 10PR	9002176P98	\$2,791.00
		4WD Front Tire - 14.9-24 (8240604)		
		2WD Front Tire - 10.00-16 (8125901)		
	Specialty Re	ar Tires		
	8391904	19.5L-24 10 PR R4	9002013P18	\$2,581.00
		4WD Front Tire - 12.5/80-18 (8290904)		

LOADER

LOADER

SD_T8110 LOADER BRACKETS

Standard D	uty Loader		
336914	Non Self Leveling Ldr +SSQA		No Charge
	655TL/710LU		
	Non Self Leveling with Skid Steer Attachment		
	NOT compatible with 38" rear tires		
336732	Non Self Leveling Ldr +Euro		No Charge
	655TL/710LU		
	Non Self Leveling with Euro Style Attachment		
	NOT compatible with 38" rear tires		
336734	Mech Self Leveling Ldr +SSQA	9000838P50	\$1,075.00
	655TL/715LU		
	Mechanical Self Leveling with Skid Steer Style Attachment		
	NOT compatible with 38" rear tires		
336736	Mech Self Leveling Ldr +Euro	9000838P50	\$1,075.00
	655TL/715LU		
	Mechanical Self Leveling with Euro Style Attachment		
	NOT compatible with 38" rear tires		

SD_T8140 BUCKET

	336748	72" Bucket		No Charge
	336750	84" Bucket	9000289P38	\$371.00

PTO

REAR PTO

SD_T8010 PTO

 OB_10010 1 10					
Ι	743594	540/1000 RPM PTO		9000424P32	\$544.00

НІТСН

REAR 3 POINT HITCH

SD_T8130 3 POINT HITCH CONTROL

332035 Mech 3 Pt Hitch Ground Control		9000197P34	\$253.00
---------------------------------------	--	------------	----------

Spanish operator manual

POWERSTAR 90-120 PS UTILITY CAB US PRICE LIST

	S	D_T8200 HI	ГСН		
		743595	Lift-O-Matic Plus	9000200P46	\$257.00
			Lift-O-Matic Plus		
CA	۱В	OR ROPS PL	ATFORM		
	ЭТН	IER			
	S	D_T6730 PI	CONNECTOR	 	
		334994	STD+30+HRN+ACS+MON	9000059P28	\$76.00
			Monitor mounting bracket, 30Ah socket & 2-12V power outlets		
W	EIG	HTS			
F	REA	.R			
	S	D_T4961 RE	AR BALLAST		
		330470	4 x 110 lb Rear Wheel Weights	9000483P60	\$620.00
			Total weight - 440 lbs (200 kg)		
			NOT compatible with 24" rear tires option		
			Required with 2WD HD front axle		
OF	PEF	RATOR'S MA	NUALS		
					_
	S	D_T9840 CC	OUNTRY CONFIGURATION		
		334256	Canada (FR) Config ROPS		No Charge
			French operator manual		
		334257	USA Spanish Configuration		No Charge

-T1LJ 02



POWERSTAR 90-120 PS STANDARD CAB US PRICE LIST

Standard Equipment

KEY SELLING POINTS:

- -CommandArc™ ergonomically places most frequently used controls to operator's right
- -Ten repositionable vents for heating and air conditioning
- -High visibility panel for better view of loader when at full height
- -Full-size instructor seat
- -Hydraulic shuttle lever
- -3.4L, 4-cylinder, 16 valve F5G engines with common rail fuel injection system
- -Tier 4B EPA emissions compliant with Selective Catalytic Reduction (SCR) & Cooled Exhaust Gas Recirculation (CEGR)
- -Factory Installed Loader available

PowerStar 90 86 Gross Engine hp 73 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207 cu in (3.4 L) Displacement

PowerStar 100 98 Gross Engine hp 85 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207 cu in (3.4 L) Displacement

PowerStar 110 107 Gross Engine hp 93 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207 cu in (3.4 L) Displacement

PowerStar 120 117 Gross Engine hp 100 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207 cu in (3.4 L) Displacement ALL MODELS:

Tier 4B Emissions Compliant:
 (SCR + CEGR)

Electronic Injection Bosch
 High-pressure Common Rail System

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Dual Element Air Filter

Constant Engine RPM

Vertical Exhaust

30.3 gal Fuel Tank with Guard

2.8 gal AdBlue DEF Tank

TRANSMISSION:

Parking brake

LH side steering column mounted
Power Shuttle
12 Forward and 12 Reverse Speeds
(4) Synchronized Gears
(3) Non-synchronized Ranges
Forward Reverse Synchronized Shuttle
19 mph (30 kph)
Speed varies with tire selection

STEERING/BRAKES:

Hydrostatic Power Steering Brakes-

Wet disk brakes Hydraulically assited

AXLES:

FRONT - 4WD

- PowerStar 120:

Heavy Duty Electrohydraulic FWD Engagement Adjustable Tread Width from 56.6 in. to 76.6 in.

-T1LJ 02

POWERSTAR 90-120 PS STANDARD CAB US PRICE LIST

AGRICULTURE

Standard Equipment

AXLES Continued:

REAR

- PowerStar 90, 100 & 110:

Flange Type

Adjustable Tread Width 55.5 in.

to 76.2 in.

- PowerStar 120:

Heavy Duty Flange Type

Adjustable Tread Width 55.5 in.

to 76.2 in.

HYDRAULIC SYSTEM:

Open Center System

Dual Gear Pumps

Implement Pump: 16.9 gpm (63.9 L)

Steering Pump: 9.7 gpm (37.0 L)

Total Flow: 26.6 gpm (100.8 L)

(2) Open Center Remote Valves with

detent

2 Function Mid Mount Valve and Joystick

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent

Flip-up PTO Shaft Guard

PowerStar 90, 100 & 110:

540 rpm Hydrauilc

PowerStar 120:

540/1000 rpm Hydraulic

-Electronic engagement

-Wet clutch

1-3/8 in. 6 splines

3-POINT LIFT SYSTEM:

Right hand console mounted

lever control

Lift-O-Matic Plus single lever control

Mechanical Draft Control

5,620 Pounds Lift Capacity

Category II Ends

Telescopic Stabilizers

Flexible Lower Link Ends

ELECTRICAL:

(1) 800 cca Heavy-Duty Battery - Cab

120 amp Alternator

7-pin Outlet for trailer/implement lighting

and signals

3-pin Power Outlet (30 amp)

Single Pin (8 amp) Accessory Power

outlet

(2) - 12V power sockets

INSTRUMENTATION:

Analog Instrumentation with warning

lights for air cleaner service,

alternator, oil pressure, fuel

sediment/water sensor, PTO

engagement, head light high beam,

low fuel and parking brake,

digital speed readout

Gauges for fuel level, engine

temperature, tachometer and hour meter

CAB LIGHTING:

Front: (2) Halogen Headlights and

(2) cab mounted worklights

Rear: (2) cab mounted worklights

Turn Signals/Flashers/Rear Lights

OPERATOR PROTECTIVE STRUCTURE:

CAB MODELS

ROPS protected, flat deck platform

with heat and air conditioning, tinted

windshield, retractable sun screen,

front and rear wiper and washer, two

doors with locks, two external mirrors,

openable side windows, hinged rear

window, high visibility panel

Steering Wheel - adjustable tilt

Seat - Cloth covered with air

suspension and 10 degrees of swivel,

operator's presence sensor, retractable

seat belt and arm rests

Instructor Seat

Suspended pedals

Radio, speakers, and antenna

POWERSTAR 90-120 PS STANDARD CAB US PRICE LIST

Standard Equipment

MISCELLANEOUS:
Pivoting Engine Hood
SMV Emblem
Toolbox

WARRANTY:

New Holland Standard Warranty Applies

LOADER:

665TL/720LU NON SELF-LEVELING

Maximum Lift Height @ pivot pin: 134"

Dump Clearance: 101.4"

Digging Depth: 7"

Lift Capacity

Max Height @ 800mm: 2,632 LBS 59" high @ 800mm: 3,638 LBS

Breakout Force @ 800mm: 4,455 LBS

Reach @ Max Lift Height: 43"

Reach @ Ground Level: 91"

Bucket Rollback Angle: 44 degrees Bucket Dump Angle: 60 degrees

Skid Steer or Euro style Loader

la la description de la company

bucket attach

665TL/725LU SELF-LEVELING

Maximum Lift Height @ pivot pin: 135"

Dump Clearance: 102.2"

Digging Depth: 6.4"

Lift Capacity

Max Height @ 800mm: 3,428 LBS 59" high @ 800mm: 5,549 LBS

Breakout Force @ 800mm: 5,661 LBS

Reach @ Max Lift Height: 43"

Reach @ Ground Level: 93

Bucket Rollback Angle: 40 degrees

Bucket Dump Angle: 60 degrees

Skid Steer or Euro style Loader

bucket attach

Page 57 of 94

-T1LJ 02 0032 000 01-OCT-18

58

POWERSTAR 90-120 PS STANDARD CAB US PRICE LIST

Models

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price				
POWERSTAR 90	Cab	8,157 LB	9053816P10	\$68,995.00				
Includes the following Equipment 12.4-24 8PR (8235601) \$1,044.00 18.4-30 12PR R1 FLAN (8363801) \$2,533.00								
POWERSTAR 100	Cab	10,031 LB	9055678P74	\$71,383.00				
POWERSTAR 110	Cab	8,157 LB	9057702P06	\$73,977.00				
- (/								
POWERSTAR 120	Cab	8,157 LB	9060701P94	\$77,823.00				
ncludes the following Equipment 4WD+EH Engage+Limited Slip (744581) \$269.00 Heavy Duty Rear Axle (333411) \$646.00 12.4-24 8PR (8235601) \$1,044.00 18.4-30 12PR R1 FLAN (8363801) \$2,533.00 540/1000 RPM PTO (743594) \$544.00								

-T1LJ 02



POWERSTAR 90-120 PS STANDARD CAB US PRICE LIST

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price	
	•				
PACKAGE SELEC	CTION				
OD T0000 D4	OVA ONIO				
SD_T9980 PA			9007780P50	\$9,975.00	
\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	Standard Package and Pricing Includes:		9007780F30	φ9,973.00	
	12x12 Power shuttle transmission (330276)				
	Deluxe cab with instructor seat and hi-vis panel (334183)				
	84" Bucket (336750)				
	04 Bucket (000/00)				
	Requires one selection for each of the following:				
	Mid mount valve and joystick:				
	2 Function mid mount valve and joystick or				
	2 Function mid mount valve and joystick + 3rd fucntion diverter				
	Loader:				
	665TL loader (select one)				
	Hitch:				
	Lift-O-Matic Plus or				
	Lift-O-Matic Plus with 2 auxiliary lift rams (select one)				
	Tires:				
	Radial ply Ag or Industrial bar tires (select front and rear)				
	,	•			
POWER TRAIN					
TRANSMISSION					
SD_T2800 SF		1		***	
759059	40KPH - REAL ALL TYR		9000199P68	\$256.00	
	25 MPH (40 KPH) Transmission for 4WD				
SD_T2810 TF	ANCMICCION				
334176	12x12 Power Shuttle w/Creeper	T	9000478P92	\$614.00	
354170	20x20 Power Shuttle with Creeper		30004701 32	ψ014.00	
	(12x12 + 8x8 creeper)				
	Hydraulic PTO				
	_ injunuanio i TO	-1	1		
SD_T2820 PA	ARK LOCK				
743551	Parking Lock		9000039P78	\$51.00	
	Transmission parking lock				
1 1 1	1		1		

Engaged using the range shift lever

AXLES



POWERSTAR 90-120 PS STANDARD CAB US PRICE LIST

	SD_T4010 FF	RONT AXLE		
	744581	4WD+EH Engage+Limited Slip+HD	9000209P82	\$269.00
		Heavy-Duty Limited Slip		
		Base equipment on PowerStar 120		
		Requires Heavy-Duty rear axle (333411)		
	SD T4810 RE	EAR AXLE		
Τ	333411	Heavy Duty Rear Axle	9000503P88	\$646.00
		Heavy-Duty Rear Axle		·
		Base Equipment on PowerStar 120		
		Required for 34 & 38 inch rear tires		
		NOT compatible with Standard-Duty 4WD		
		front axles (743559 or 744580)		
		NOT compatible with 30 inch or smaller rear tires		
		on PowerStar 90, 100 or 110		
TIRI	ES			
	ONT			
	SD_T4940 FF	RONT WHEELS AND TIRES		
	4WD Radia	Tires		
	8232404	11.2R24 R1W	9000911P04	\$1,168.00
	8235404	12.4R24 R1W	9001087P32	\$1,394.00
	4WD Radia	Front Tires		
	8236404	13.6R24 R1W	9001330P68	\$1,706.00
	8239404	14.9R24 R1W	9001637P22	\$2,099.00
		alty Front Tires		
4		12.5/80-18 10PR R4	9001300P26	\$1,667.00
	8247404	11.2R28 R1W	9001123P98	\$1,441.00
	· A D			
KE	AR			
	SD_T4950 RE	EAR WHEELS AND TIRES		
	Radial Rear	Tires		
	8355404	16.9R30 R1W	9001975P74	\$2,533.00
		4WD Front Tire - 11.2R24 (8232404)		
		2WD Front Tire - 7.50-16 (8125801) or 9.5L-15 4 rib (8122601)		
	8357404	18.4R30 R1W	9002635P62	\$3,379.00
		4WD Front Tire - 12.4R24 (8235404)		
	<u> </u>	2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)		
	8302804	16.9R34 R1W	9001896P96	\$2,432.00
		4WD Front Tire - 13.6R24 (8236404)		
		2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)		

Grounds Equipment Bid #ESCNJ 18/19-25
-T1LJ 02

POWERSTAR 90-120 PS STANDARD CAB US PRICE LIST

		8365404	18.4R34 R1W		9002853P24	\$3,658.00
			4WD Front Tire - 14.9R24 (8239404)			
			2WD Front Tire - 10.00-16 (8125901)			
Specialty Rear Tires						
		8391904	19.5L-24 10 PR R4		9002013P18	\$2,581.00
			4WD Front Tire - 12.5/80-18 (8290904)			
		8372404	13.6R38 R1W 8372404		9001770P60	\$2,270.00
			4WD Front Tire - 11.2R28 (8247404)			
			2WD Front Tire - 7.50-16 (8125801)			

HYDRAULICS

MID-MOUNT

SD_T8280 MID-MOUNT VALVES

	338125	2Mid-Mount w/Mec Joystick		No Charge
		2 function mid-mount valve and joystick		
	336780	2Mid-Mount w/Mec Joystick +Div	9000579P54	\$743.00
		2 function mid-mount valve and joystick with 3rd function diverter		
		Requires a Loader		
		Bucket with Grapple NOT AVAILABLE as Factory Installed		

LOADER

LOADER

SD_T8110 LOADER BRACKETS

_	ADER BIORETO		
 Heavy Duty	Loader		
336740	HD Non Self Leveling Ldr +SSQA		No Charge
	665TL/720LU		
	Non Self Leveling with Skid Steer Style Attachment		
336742	HD Non Self Leveling Ldr +Euro		No Charge
	665TL/720LU		
	Non Self Leveling with Euro Style Attachment		
336744	HD Self Leveling Ldr +SSQA	9000868P92	\$1,114.00
	665TL/725LU		
	Mechanical Self Leveling with Skid Steer Style Attachment		
336746	HD Self Leveling Ldr +Euro	9000868P92	\$1,114.00
	665TL/725LU		
	Mechanical Self Leveling with Euro Style Attachment		

SD_T8140 BUCKET

336750 84" Bucket	No Charge



POWERSTAR 90-120 PS STANDARD CAB US PRICE LIST

PTO		
REAR PTO		
SD_T8010 PTO		
743594 540/1000 RPM PTO	9000424P32	\$544.00
143334 340/1000 IX INIT TO	90004241 32	ψ344.00]
HITCH		
REAR 3 POINT HITCH		
SD_T8130 3 POINT HITCH CONTROL		
332035 Mech 3 Pt Hitch Ground Control	9000197P34	\$253.00
SD_T8200 HITCH	0000004500	\$4.000.00
758931 MDC HPL+LOM+2AUX	9000804P96	\$1,032.00
Lift-O-Matic Plus with 2 auxiliary lift rams 8,000 lbs lift capacity		
6,000 IDS IIII Capacity		
Requires Heavy Duty front and rear axles		
Transport of the state of the s		
CAB OR ROPS PLATFORM		
OTHER		
SD_T6730 PIN CONNECTOR		
334994 STD+30+HRN+ACS+MON	9000060P84	\$78.00
Monitor mounting bracket, 30Ah socket & 2-12V power outlets		
WEIGHTS		
DEAD		1
REAR		
SD_T4961 REAR BALLAST		
330470 4 x 110 lb Rear Wheel Weights	9000483P60	\$620.00
Total weight - 440 lbs (200 kg)		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
NOT compatible with 24" rear tires option		
Required with 2WD HD front axle		
MISCELLANEOUS		
FENDERS FRONT		
OD TOTAL FRONT FENDERO		
SD_T8740 FRONT FENDERS 744674 Dvnamic Fenders	9000542P10	\$695.00

Spanish operator manual

The Educational Services Commission of New Jersey ate Approved Co-op #65MCESCCPS

Grounds Equipment Bid #ESCNJ 18/19-25 -T1LJ 02



POWERSTAR 90-120 PS STANDARD CAB US PRICE LIST

FEN	IDERS REAR			
	<u>SD_T8700 FE</u>	NDERS		
	744599	Rear Fenders w/Extensions	9000125P58	\$161.00
OPE	RATOR'S MA	NUALS		
	SD_T9840 CO	UNTRY CONFIGURATION		
	334256	Canada (FR) Config ROPS		No Charge
		French operator manual		
	334257	USA Spanish Configuration		No Charge



Standard Equipment

KEY SELLING POINTS:

- -CommandArc™ ergonomically places most frequently used controls to operator's right
- -Ten repositionable vents for heating and air conditioning
- -High visibility panel for better view of loader when at full height
- -Full-size instructor seat
- -Hydraulic shuttle lever
- -3.4L, 4-cylinder, 16 valve F5G engines with common rail fuel injection system
- -Tier 4B EPA emissions compliant with Selective Catalytic Reduction (SCR) & Cooled Exhaust Gas Recirculation (CEGR)
- -Factory Installed Loader available

PowerStar 90 86 Gross Engine hp 73 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207 cu in (3.4 L) Displacement

PowerStar 100 98 Gross Engine hp 85 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207 cu in (3.4 L) Displacement

PowerStar 110 107 Gross Engine hp 93 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207 cu in (3.4 L) Displacement

PowerStar 120 117 Gross Engine hp 100 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207 cu in (3.4 L) Displacement ALL MODELS:

Tier 4B Emissions Compliant:
 (SCR + CEGR)

Electronic Injection Bosch
 High-pressure Common Rail System

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Dual Element Air Filter

Constant Engine RPM

Vertical Exhaust

30.3 gal Fuel Tank with Guard

2.8 gal AdBlue DEF Tank

TRANSMISSION:

Parking brake

LH side steering column mounted Power Shuttle 12 Forward and 12 Reverse Speeds (4) Synchronized Gears (3) Non-synchronized Ranges Forward Reverse Synchronized Shuttle 25 ph (40 kph) Speed varies with tire selection

STEERING/BRAKES:

Hydrostatic Power Steering Brakes-Wet disk brakes

Wet disk brakes Hydraulically assited

AXLES:

FRONT - 4WD

- PowerStar 120:

Heavy Duty Electrohydraulic FWD Engagement Adjustable Tread Width from 56.6 in. to 76.6 in.

-T1LJ 03

POWERSTAR 90-120 PS KLASSIC CAB US PRICE LIST

Standard Equipment

AXLES Continued:

REAR

- PowerStar 90, 100 & 110:

Flange Type

Adjustable Tread Width 55.5 in.

to 76.2 in.

- PowerStar 120:

Heavy Duty Flange Type

Adjustable Tread Width 55.5 in.

to 76.2 in.

HYDRAULIC SYSTEM:

Open Center System

Dual Gear Pumps

Implement Pump: 16.9 gpm (63.9 L)

Steering Pump: 9.7 gpm (37.0 L)

Total Flow: 26.6 gpm (100.8 L)

(2) Open Center Remote Valves with

detent

2 Function Mid Mount Valve and Joystick

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent

Flip-up PTO Shaft Guard

PowerStar 90, 100 & 110:

540 rpm Hydrauilc

PowerStar 120:

540/1000 rpm Hydraulic

-Electronic engagement

-Wet clutch

1-3/8 in. 6 splines

3-POINT LIFT SYSTEM:

Right hand console mounted

lever control

Mechanical Draft Control

5,620 Pounds Lift Capacity

Category II Ends

Telescopic Stabilizers

Flexible Lower Link Ends

ELECTRICAL:

(1) 800 cca Heavy-Duty Battery - Cab

120 amp Alternator

7-pin Outlet for trailer/implement lighting

and signals

3-pin Power Outlet (30 amp)

Single Pin (8 amp) Accessory Power

outlet

(2) - 12V power sockets

INSTRUMENTATION:

Analog Instrumentation with warning

lights for air cleaner service,

alternator, oil pressure, fuel

sediment/water sensor, PTO

engagement, head light high beam,

low fuel and parking brake,
digital speed readout

Gauges for fuel level, engine

temperature, tachometer and hour

meter

CAB LIGHTING:

Front: (2) Halogen Headlights and

(2) cab mounted worklights

Rear: (2) cab mounted worklights

Turn Signals/Flashers/Rear Lights

OPERATOR PROTECTIVE STRUCTURE:

CAB MODELS

ROPS protected, flat deck platform

with heat and air conditioning, tinted

windshield, retractable sun screen,

front and rear wiper and washer, two

doors with locks, two external mirrors,

openable side windows, hinged rear

window, high visibility panel

Steering Wheel - adjustable tilt

Seat - Cloth covered with air

suspension and 10 degrees of swivel,

operator's presence sensor, retractable

seat belt and arm rests

Instructor Seat

Suspended pedals

Radio, speakers, and antenna

Standard Equipment

MISCELLANEOUS:
Pivoting Engine Hood
SMV Emblem
Toolbox

WARRANTY:

New Holland Standard Warranty Applies

LOADER:

655TL/710LU NON SELF-LEVELING

Maximum Lift Height @ pivot pin: 126"

Dump Clearance: 93.6"
Digging Depth: 8.2"

Lift Capacity

Max Height @ 800mm: 2,478 LBS
59" high @ 800mm: 3,080 LBS
Breakout Force @ 800mm: 3,739 LBS
Reach @ Max Lift Height: 39.5"
Reach @ Ground Level: 90.7"
Bucket Rollback Angle: 45 degrees
Bucket Dump Angle: 60 degrees
Skid Steer or Euro Style Loader

bucket attach

bucket attach

655TL/715LU SELF-LEVELING

Maximum Lift Height @ pivot pin: 125"

Dump Clearance: 93"
Digging Depth: 8"
Lift Capacity

Max Height @ 800mm: 3,179 LBS
59" high @ 800mm: 4,665 LBS
Breakout Force @ 800mm: 3,860 LBS
Reach @ Max Lift Height: 39.4"
Reach @ Ground Level: 90.5"
Bucket Rollback Angle: 40 degrees
Bucket Dump Angle: 60 degrees
Skid Steer or Euro sytle Loader

665TL/720LU NON SELF-LEVELING

Maximum Lift Height @ pivot pin: 134"

Dump Clearance: 101.4"
Digging Depth: 7"
Lift Capacity

Max Height @ 800mm: 2,632 LBS 59" high @ 800mm: 3,638 LBS Breakout Force @ 800mm: 4,455 LBS Reach @ Max Lift Height: 43" Reach @ Ground Level: 91"

Bucket Rollback Angle: 44 degrees Bucket Dump Angle: 60 degrees Skid Steer or Euro style Loader

bucket attach

665TL/725LU SELF-LEVELING

Maximum Lift Height @ pivot pin: 135"

Dump Clearance: 102.2" Digging Depth: 6.4" Lift Capacity

Max Height @ 800mm: 3,428 LBS 59" high @ 800mm: 5,549 LBS

Breakout Force @ 800mm: 5,661 LBS

Reach @ Max Lift Height: 43"

Reach @ Ground Level: 93

Bucket Rollback Angle: 40 degrees

Bucket Dump Angle: 60 degrees

Skid Steer or Euro style Loader

bucket attach



Models

VERSION	Weight	Factory Data	List Price					
Cab	8,157 LB	9053816P10	\$68,995.00					
Includes the following Equipment 12.4-24 8PR (8235601) \$1,044.00 18.4-30 12PR R1 FLAN (8363801) \$2,533.00								
Cab	10,031 LB	9055678P74	\$71,383.00					
044.00) \$2,533.00								
Cab	8,157 LB	9057702P06	\$73,977.00					
)44.00) \$2,533.00								
	1							
Cab	8,157 LB	9060701P94	\$77,823.00					
Includes the following Equipment 4WD+EH Engage+Limited Slip (744581) \$269.00 Heavy Duty Rear Axle (333411) \$646.00 12.4-24 8PR (8235601) \$1,044.00 18.4-30 12PR R1 FLAN (8363801) \$2,533.00 540/1000 RPM PTO (743594) \$544.00								
	044.00 \$2,533.00 Cab 044.00 \$2,533.00 Cab 044.00 \$2,533.00 Cab 044.00 \$2,533.00	044.00 \$2,533.00 Cab 10,031 LB 044.00 \$2,533.00 Cab 8,157 LB 044.00 \$2,533.00 Cab 8,157 LB 044.00 \$2,533.00	044.00 \$2,533.00 Cab 10,031 LB 9055678P74 044.00 \$2,533.00 Cab 8,157 LB 9057702P06 044.00 \$2,533.00 Cab 8,157 LB 9060701P94 14581) \$269.00 \$646.00 044.00 \$2,533.00					



Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
PACKAGE SELEC	CTION			
THORNOL OLLEG	5116N			
SD_T9980 PA				
X99804X	KLASSIC PACKAGING		9000621P66	\$797.00
	Klassic Package and Pricing Includes:			
	12x12 Power shuttle transmission (330276)			
	Deluxe cab with instructor seat and hi-vis panel (334183)			
	25 MPH (40 KPH) (759059)			
POWER TRAIN				
1 011211 110 1111				
TRANSMISSION				
SD_T2810 TR	ANSMISSION			
334176	12x12 Power Shuttle w/Creeper		9000478P92	\$614.00
	20x20 Power Shuttle with Creeper			
	(12x12 + 8x8 creeper)			
	Hydraulic PTO			
AXLES				
SD_T4010 FR	ONT AYLE			
744581	4WD+EH Engage+Limited Slip+HD		9000209P82	\$269.00
	Heavy-Duty Limited Slip			Ψ200.00
	Base equipment on PowerStar 120			
	Requires Heavy-Duty rear axle (333411)			
SD_T4810 RE	AR AXLE			
333411	Heavy Duty Rear Axle		9000503P88	\$646.00
	Heavy-Duty Rear Axle			
	Base Equipment on PowerStar 120			
	Required for 34 & 38 inch rear tires			
	NOT compatible with Standard-Duty 4WD			
	front axles (743559 or 744580)			
	NOT compatible with 30 inch or smaller rear tires			

on PowerStar 90, 100 or 110

2 function mid-mount valve and joystick

POWERSTAR 90-120 PS KLASSIC CAB US PRICE LIST

TIRES			
FRONT			
SD T4940 FI	RONT WHEELS AND TIRES		
4WD Bias F			
	12.4-24 8PR	9000814P32	\$1,044.00
8236501	13.6-24 8PR R1 FLANG	9000997P62	\$1,279.00
4WD Radia	l Tires	·	
8235404	12.4R24 R1W	9001087P32	\$1,394.00
4WD Radia	Front Tires	·	
8236404	13.6R24 R1W	9001330P68	\$1,706.00
4WD Speci	alty Front Tires		
8290904	12.5/80-18 10PR R4	9001300P26	\$1,667.00
REAR			
SD_T4950 R	EAR WHEELS AND TIRES		
Bias Rear 1	ïres		
8363801	18.4-30 12PR R1 FLAN	9001975P74	\$2,533.00
	4WD Front Tire - 12.4-24 (8235601)		
	2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)		
8364604	16.9-34 8PR R1	9001421P94	\$1,823.00
	4WD Front Tire - 13.6-24 (8236501)		, ,
	2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)		
Radial Rea		•	
8357404	18.4R30 R1W	9002635P62	\$3,379.00
	4WD Front Tire - 12.4R24 (8235404)		
	2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)		
8302804	16.9R34 R1W	9001896P96	\$2,432.00
	4WD Front Tire - 13.6R24 (8236404)		, ,
	2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)		
Specialty R			
8391904	19.5L-24 10 PR R4	9002013P18	\$2,581.00
	4WD Front Tire - 12.5/80-18 (8290904)		+ =,==:::
	1115 11611 1116 1216/66 16 (6226661)		
HYDRAULICS			
MID-MOUNT			
SD_T8280 M 338125	D-MOUNT VALVES 2Mid-Mount w/Mec Joystick	9001123P98	\$1,441.00

lucational Services Commission of New Jersey

J State Approved Co-op #65MCESCCPS

-T1LJ 03



POWERSTAR 90-120 PS KLASSIC CAB US PRICE LIST

	336780	2Mid-Mount w/Mec Joystick +Div	9001686P36	\$2,162.00
		2 function mid-mount valve and joystick with 3rd function diverter		
		Requires a Loader		
		Bucket with Grapple NOT AVAILABLE as Factory Installed		

LOADER

LOADER

SD_T8110 LOADER BRACKETS

Standard D	uty Loader		
336914	Non Self Leveling Ldr +SSQA	9004590P30	\$5,885.00
	655TL/710LU		
	Non Self Leveling with Skid Steer Attachment		
	NOT compatible with 38" rear tires		
336732	Non Self Leveling Ldr +Euro	9004590P30	\$5,885.00
	655TL/710LU		
	Non Self Leveling with Euro Style Attachment		
	NOT compatible with 38" rear tires		
336734	Mech Self Leveling Ldr +SSQA	9005429P58	\$6,961.00
	655TL/715LU		
	Mechanical Self Leveling with Skid Steer Style Attachment		
	NOT compatible with 38" rear tires		
336736	Mech Self Leveling Ldr +Euro	9005429P58	\$6,961.0
	655TL/715LU		
	Mechanical Self Leveling with Euro Style Attachment		
	NOT compatible with 38" rear tires		
Heavy Duty	Loader	_	
336740	HD Non Self Leveling Ldr +SSQA	9005319P60	\$6,820.0
	665TL/720LU		
	Non Self Leveling with Skid Steer Style Attachment		
336742	HD Non Self Leveling Ldr +Euro	9005319P60	\$6,820.0
	665TL/720LU		
	Non Self Leveling with Euro Style Attachment		
336744	HD Self Leveling Ldr +SSQA	9006162P78	\$7,901.0
	665TL/725LU		
	Mechanical Self Leveling with Skid Steer Style Attachment		
336746	HD Self Leveling Ldr +Euro	9006162P78	\$7,901.0
	665TL/725LU		
	Mechanical Self Leveling with Euro Style Attachment		

SD_T8140 BUCKET

 OD_TOTIO BOOKET					
	336750	84" Bucket		9000713P70	\$915.00

REAR PTO	РТО			
SD_T8010 PTO				
T43594 540/1000 RPM PTO 9000424P32 \$544.00 HITCH	REAR PIO			
T43594 540/1000 RPM PTO 9000424P32 \$544.00 HITCH	SD T8010 F	PTO		
HITCH			9000424P32	\$544.00
REAR 3 POINT HITCH SD_T8130 3 POINT HITCH CONTROL 332035 Mech 3 Pt Hitch Ground Control 9000197P34 \$253.00			·	
SD_T8130 3 POINT HITCH CONTROL 332035 Mech 3 Pt Hitch Ground Control 9000197P34 \$253.00 SD_T8200 HITCH 759058 MDC - REAR HPL - 2 A 2 auxiliary lift rams 8,000 lbs lift capacity 8,000 lbs lift capacity 9000200P46 \$257.00 Lift-O-Matic Plus 9000200P46 \$257.00 Lift-O-Matic Plus 9000200P46 \$257.00 Lift-O-Matic Plus 9001011P66 \$1,297.00 T58931 MDC HPL+LOM+2AUX 9001011P66 \$1,297.00 Lift-O-Matic Plus with 2 auxiliary lift rams 8,000 lbs lift capacity Requires Heavy Duty front and rear axles CAB OR ROPS PLATFORM OTHER SD_T6730 PIN CONNECTOR 334994 STD+30+HRN+ACS+MON Monitor mounting bracket, 30Ah socket & 2-12V power outlets 9000059P28 \$76.00 WEIGHTS SD_T2150 FRONT BALLAST 333215 Front Carrier + 6 88 lb Weights 9000620P10 \$795.00 Total weight - 661 lbs (300 kg) 335215 8 WEIGHTS 40 KG - CA 9000784P68 \$1,006.00	нітсн			
SD_T8130 3 POINT HITCH CONTROL 332035 Mech 3 Pt Hitch Ground Control 9000197P34 \$253.00 SD_T8200 HITCH 759058 MDC - REAR HPL - 2 A 2 auxiliary lift rams 8,000 lbs lift capacity 8,000 lbs lift capacity 9000200P46 \$257.00 Lift-O-Matic Plus 9000200P46 \$257.00 Lift-O-Matic Plus 9000200P46 \$257.00 Lift-O-Matic Plus 9001011P66 \$1,297.00 T58931 MDC HPL+LOM+2AUX 9001011P66 \$1,297.00 Lift-O-Matic Plus with 2 auxiliary lift rams 8,000 lbs lift capacity Requires Heavy Duty front and rear axles CAB OR ROPS PLATFORM OTHER SD_T6730 PIN CONNECTOR 334994 STD+30+HRN+ACS+MON Monitor mounting bracket, 30Ah socket & 2-12V power outlets 9000059P28 \$76.00 WEIGHTS SD_T2150 FRONT BALLAST 333215 Front Carrier + 6 88 lb Weights 9000620P10 \$795.00 Total weight - 661 lbs (300 kg) 335215 8 WEIGHTS 40 KG - CA 9000784P68 \$1,006.00				
332035 Mech 3 Pt Hitch Ground Control 9000197P34 \$253.00 SD_T8200 HITCH 759058 MDC - REAR HPL - 2 A 9000811P20 \$1,040.00 2 auxiliary lift rams 8,000 lbs lift capacity Requires Heavy Duty front and rear axles 9000200P46 \$257.00 Lift-O-Matic Plus 9000200P46 \$257.00 Lift-O-Matic Plus with 2 auxiliary lift rams 8,000 lbs lift capacity Requires Heavy Duty front and rear axles 9001011P66 \$1,297.00 Lift-O-Matic Plus with 2 auxiliary lift rams 8,000 lbs lift capacity Requires Heavy Duty front and rear axles CAB OR ROPS PLATFORM OTHER SD_T6730 PIN CONNECTOR 334994 STD-30+HRN-ACS+MON Monitor mounting bracket, 30Ah socket & 2-12V power outlets 9000059P28 \$76.00 WEIGHTS SD_T2150 FRONT BALLAST SD_T2150 FRONT BALLAST Front Carrier + 68 lb Weights 9000620P10 \$795.00 \$795.00 \$335215 SWEIGHTS 40 KG - CA 9000784P68 \$1,006.00	REAR 3 POINT H	IITCH		
332035 Mech 3 Pt Hitch Ground Control 9000197P34 \$253.00 SD_T8200 HITCH				
SD_T8200 HITCH				^
T59058 MDC - REAR HPL - 2 A 2 auxiliary lift rams 8,000 lbs lift capacity Requires Heavy Duty front and rear axles 9000200P46 \$257.00	332035	Mech 3 Pt Hitch Ground Control	9000197P34	\$253.00
T59058 MDC - REAR HPL - 2 A 2 auxiliary lift rams 8,000 lbs lift capacity Requires Heavy Duty front and rear axles 9000200P46 \$257.00	SD T8200 F	HTCH		
2 auxiliary lift rams			9000811P20	\$1,040,00
Requires Heavy Duty front and rear axles 9000200P46 \$257.00		-	33331.11.23	ψ.,σ.σ.σσ
Requires Heavy Duty front and rear axles		•		
743595 Lift-O-Matic Plus 9000200P46 \$257.00				
Lift-O-Matic Plus		Requires Heavy Duty front and rear axles		
758931 MDC HPL+LOM+2AUX	743595	Lift-O-Matic Plus	9000200P46	\$257.00
Lift-O-Matic Plus with 2 auxiliary lift rams 8,000 lbs lift capacity				
Requires Heavy Duty front and rear axles	758931		9001011P66	\$1,297.00
Requires Heavy Duty front and rear axles		-		
CAB OR ROPS PLATFORM		8,000 lbs lift capacity		
CAB OR ROPS PLATFORM		Demisires Heavy Duty front and year cyles		
SD_T6730 PIN CONNECTOR 334994 STD+30+HRN+ACS+MON 9000059P28 \$76.00 Monitor mounting bracket, 30Ah socket & 2-12V power outlets 9000059P28 \$76.00 WEIGHTS SD_T2150 FRONT BALLAST 333215 Front Carrier +6 88 lb Weights 9000620P10 \$795.00 Total weight - 661 lbs (300 kg) 9000784P68 \$1,006.00		Requires neavy Duty Iront and real axies	L	
SD_T6730 PIN CONNECTOR 334994 STD+30+HRN+ACS+MON 9000059P28 \$76.00 WEIGHTS WEIGHTS SD_T2150 FRONT BALLAST 333215 Front Carrier +6 88 lb Weights 9000620P10 \$795.00 Total weight - 661 lbs (300 kg) 335215 8 WEIGHTS 40 KG - CA 9000784P68 \$1,006.00	CAR OP POPS	DI ATEODM		
SD_T6730 PIN CONNECTOR 334994 STD+30+HRN+ACS+MON 9000059P28 \$76.00 Monitor mounting bracket, 30Ah socket & 2-12V power outlets 9000059P28 \$76.00 WEIGHTS SD_T2150 FRONT BALLAST 333215 Front Carrier +6 88 lb Weights 9000620P10 \$795.00 Total weight - 661 lbs (300 kg) 9000784P68 \$1,006.00	CAB OR ROPS	LATIONW		
SD_T6730 PIN CONNECTOR 334994 STD+30+HRN+ACS+MON 9000059P28 \$76.00 Monitor mounting bracket, 30Ah socket & 2-12V power outlets 9000059P28 \$76.00 WEIGHTS SD_T2150 FRONT BALLAST 333215 Front Carrier +6 88 lb Weights 9000620P10 \$795.00 Total weight - 661 lbs (300 kg) 9000784P68 \$1,006.00	OTHER			
334994 STD+30+HRN+ACS+MON 9000059P28 \$76.00 Monitor mounting bracket, 30Ah socket & 2-12V power outlets 9000059P28 \$76.00 WEIGHTS	-			
Monitor mounting bracket, 30Ah socket & 2-12V power outlets	SD_T6730 F	PIN CONNECTOR		
SD_T2150 FRONT BALLAST SD_T2150 FRONT BALLAST 333215 Front Carrier +6 88 lb Weights 9000620P10 \$795.00 Total weight - 661 lbs (300 kg) 335215 8 WEIGHTS 40 KG - CA 9000784P68 \$1,006.00	334994	STD+30+HRN+ACS+MON	9000059P28	\$76.00
SD_T2150 FRONT BALLAST 333215 Front Carrier +6 88 lb Weights 9000620P10 \$795.00 Total weight - 661 lbs (300 kg) 335215 8 WEIGHTS 40 KG - CA 9000784P68 \$1,006.00		Monitor mounting bracket, 30Ah socket & 2-12V power outlets		
SD_T2150 FRONT BALLAST 333215 Front Carrier +6 88 lb Weights 9000620P10 \$795.00 Total weight - 661 lbs (300 kg) 335215 8 WEIGHTS 40 KG - CA 9000784P68 \$1,006.00				
SD_T2150 FRONT BALLAST 333215 Front Carrier +6 88 lb Weights 9000620P10 \$795.00 Total weight - 661 lbs (300 kg) 335215 8 WEIGHTS 40 KG - CA 9000784P68 \$1,006.00	WEIGHTS			
SD_T2150 FRONT BALLAST 333215 Front Carrier +6 88 lb Weights 9000620P10 \$795.00 Total weight - 661 lbs (300 kg) 335215 8 WEIGHTS 40 KG - CA 9000784P68 \$1,006.00				
333215 Front Carrier +6 88 lb Weights 9000620P10 \$795.00 Total weight - 661 lbs (300 kg) 9000784P68 \$1,006.00	FRONT			
333215 Front Carrier +6 88 lb Weights 9000620P10 \$795.00	SD 13150 E	PONT RALLAST		
Total weight - 661 lbs (300 kg) 9000784P68 \$1,006.00			9000620P10	\$795.00
335215 8 WEIGHTS 40 KG - CA 9000784P68 \$1,006.00		_	300020110	Ψ135.00
	335215		9000784P68	\$1,006.00

Spanish operator manual

POWERSTAR 90-120 PS KLASSIC CAB US PRICE LIST

R	EΑ	R			
	S	D_T4961 RE	AR BALLAST		
		330470	4 x 110 lb Rear Wheel Weights	9000483P60	\$620.00
			Total weight - 440 lbs (200 kg)		
			NOT compatible with 24" rear tires option		
			Required with 2WD HD front axle		
				•	
MIS	SC	ELLANEOUS	S		
F	ΕN	DERS FRONT			
	S	D_T8740 FR	ONT FENDERS		
		744674	Dynamic Fenders	9000542P10	\$695.00
F	ΕN	DERS REAR			
	S	D_T8700 FE	NDERS		
		744599	Rear Fenders w/Extensions	9000125P58	\$161.00
				-	
OP	EF	RATOR'S MA	NUALS		
	S	D_T9840 CO	DUNTRY CONFIGURATION		
		334256	Canada (FR) Config ROPS		No Charge
			French operator manual		ŭ
		334257	USA Spanish Configuration		No Charge



Standard Equipment

KEY SELLING POINTS:

- -CommandArc™ ergonomically places most frequently used controls to operator's right
- -High visibility panel option for better view of loader when at full height
- -Ten repositionable vents for heating and air conditioning
- -Full-size instructor seat option
- -Hydraulic shuttle lever
- -Creeper transmission option
- -3.4L, 4-cylinder, 16 valve F5G engines with common rail fuel injection system
- -Tier 4B EPA emissions compliant with Selective Catalytic Reduction (SCR) & Cooled Exhaust Gas Recirculation (CEGR)
- -Factory Installed Loader available

PowerStar 90 86 Gross Engine hp 73 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207 cu in (3.4 L) Displacement

PowerStar 100 98 Gross Engine hp 85 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207 cu in (3.4 L) Displacement

PowerStar 110 107 Gross Engine hp 93 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207 cu in (3.4 L) Displacement

PowerStar 120 117 Gross Engine hp 100 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207 cu in (3.4 L) Displacement

ALL MODELS:

Tier 4B Emissions Compliant:
 (SCR + CEGR)

Electronic Injection Bosch
 High-pressure Common Rail System

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Dual Element Air Filter

Constant Engine RPM

Vertical Exhaust

30.3 gal Fuel Tank with Guard

2.8 gal AdBlue DEF Tank

Parking brake

TRANSMISSION:

Power Shuttle
12 Forward and 12 Reverse Speeds
(4) Synchronized Gears
(3) Non-synchronized Ranges
Forward Reverse Synchronized Shuttle
19 mph (30 kph)
Speed varies with tire selection

LH side steering column mounted

HYDRAULIC SYSTEM:

Open Center System

Dual Gear Pumps

Implement Pump: 16.9 gpm (63.9 L)

Steering Pump: 9.7 gpm (37.0 L)

Total Flow: 26.6 gpm (100.8 L)

(2) Open Center Remote Valves with detent

3-POINT LIFT SYSTEM:
Right hand console mounted
lever control
Mechanical Draft Control
5,620 Pounds Lift Capacity
Category II Ends
Telescopic Stabilizers

Flexible Lower Link Ends

-T1LJ 04

POWERSTAR 90-120 PS A LA CARTE CAB US PRICE LIST

Standard Equipment

STEERING/BRAKES:
Hydrostatic Power Steering
Brakes-

Wet disk brakes Hydraulically assited

AXLES:

FRONT - 2WD (19 mph, 30 kph)
Inverted U-section type
Adjustable Tread Width from 57.0 in.
to 79.7 in.

FRONT - 4WD Limited Slip

- PowerStar 90, 100 & 110:

Electrohydraulic FWD Engagement Adjustable Tread Width from 56.6 in. to 76.6 in.

- PowerStar 120:

Heavy Duty Electrohydraulic FWD Engagement Adjustable Tread Width from 56.6 in. to 76.6 in.

REAR

- PowerStar 90, 100 & 110:

Flange Type Adjustable Tread Width 55.5 in. to 76.2 in.

- PowerStar 120:

Heavy Duty Flange Type Adjustable Tread Width 55.5 in. to 76.2 in.

REAR DIFFERENTIAL LOCK: Mechanically Engaged

PTO:

Fully Independent
Flip-up PTO Shaft Guard
PowerStar 90, 100 & 110:
540 rpm Hydraulic
PowerStar 120:
540/1000 rpm Hydraulic

-Electronic engagement
-Wet clutch

1-3/8 in. 6 splines

ELECTRICAL:

(1) 800 cca Heavy-Duty Battery - Cab
120 amp Alternator
7-pin Outlet for trailer/implement lighting
 and signals
3-pin Power Outlet (30 amp)
Single Pin (8 amp) Accessory Power
outlet
12V power socket

INSTRUMENTATION:

Analog Instrumentation with warning lights for air cleaner service, alternator, oil pressure, fuel sediment/water sensor, PTO engagement, head light high beam, low fuel and parking brake, digital speed readout

Gauges for fuel level, engine temperature, tachometer and hour meter

LIGHTING:

OPERATOR PROTECTIVE STRUCTURE:

CAB MODELS

ROPS protected, flat deck platform
with heat and air conditioning, tinted
windshield, retractable sun screen,
front and rear wiper and washer, two
doors with locks, two external mirrors,
openable side windows, hinged rear
window (opens completely)
Steering Wheel - adjustable tilt
Seat - Cloth covered with air
suspension and 10 degrees of swivel,
operator's presence sensor, retractable
seat belt and arm rests
Instructor seat
Suspended pedals
Radio, speakers, and antenna

-T1LJ 04

POWERSTAR 90-120 PS A LA CARTE CAB US PRICE LIST

Standard Equipment

MISCELLANEOUS:
Pivoting Engine Hood
SMV Emblem
Toolbox

WARRANTY:

New Holland Standard Warranty Applies

LOADER:

655 TL/710 LU NON SELF-LEVELING

Maximum Lift Height @ pivot pin: 126"

Dump Clearance: 93.6"
Digging Depth: 8.2"

Lift Capacity

Max Height @ 800mm: 2,478 LBS
59" high @ 800mm: 3,080 LBS
Breakout Force @ 800mm: 3,739 LBS
Reach @ Max Lift Height: 39.5"
Reach @ Ground Level: 90.7"
Bucket Rollback Angle: 45 degrees
Bucket Dump Angle: 60 degrees

Skid Steer or Euro Style Loader

bucket attach

655TL/715LU SELF-LEVELING

Maximum Lift Height @ pivot pin: 125"

Dump Clearance: 93"
Digging Depth: 8"
Lift Capacity

Max Height @ 800mm: 3,179 LBS
59" high @ 800mm: 4,665 LBS
Breakout Force @ 800mm: 3,860 LBS
Reach @ Max Lift Height: 39.4"
Reach @ Ground Level: 90.5"
Bucket Rollback Angle: 40 degrees
Bucket Dump Angle: 60 degrees
Skid Steer or Euro sytle Loader

bucket attach

665TL/720LU NON SELF-LEVELING

Maximum Lift Height @ pivot pin: 134"

Dump Clearance: 101.4"
Digging Depth: 7"

Lift Capacity

Max Height @ 800mm: 2,632 LBS 59" high @ 800mm: 3,638 LBS Breakout Force @ 800mm: 4,455 LBS

Reach @ Max Lift Height: 43"

Reach @ Ground Level: 91"

Bucket Rollback Angle: 44 degrees

Bucket Dump Angle: 60 degrees Skid Steer or Euro style Loader

bucket attach

665TL/725LU SELF-LEVELING

Maximum Lift Height @ pivot pin: 135"

Dump Clearance: 102.2"
Digging Depth: 6.4"

Lift Capacity

Max Height @ 800mm: 3,428 LBS 59" high @ 800mm: 5,549 LBS

Breakout Force @ 800mm: 5,661 LBS

Reach @ Max Lift Height: 43"

Reach @ Ground Level: 93

Bucket Rollback Angle: 40 degrees

Bucket Dump Angle: 60 degrees

Skid Steer or Euro style Loader

bucket attach



Models

VERSION	Weight	Factory Data	List Price					
Cab	8,157 LB	9053816P10	\$68,995.00					
Includes the following Equipment 12.4-24 8PR (8235601) \$1,044.00 18.4-30 12PR R1 FLAN (8363801) \$2,533.00								
Cab	10,031 LB	9055678P74	\$71,383.00					
044.00) \$2,533.00								
Cab	8,157 LB	9057702P06	\$73,977.00					
)44.00) \$2,533.00								
	1							
Cab	8,157 LB	9060701P94	\$77,823.00					
Includes the following Equipment 4WD+EH Engage+Limited Slip (744581) \$269.00 Heavy Duty Rear Axle (333411) \$646.00 12.4-24 8PR (8235601) \$1,044.00 18.4-30 12PR R1 FLAN (8363801) \$2,533.00 540/1000 RPM PTO (743594) \$544.00								
	044.00 \$2,533.00 Cab 044.00 \$2,533.00 Cab 044.00 \$2,533.00 Cab 044.00 \$2,533.00	044.00 \$2,533.00 Cab 10,031 LB 044.00 \$2,533.00 Cab 8,157 LB 044.00 \$2,533.00 Cab 8,157 LB 044.00 \$2,533.00	044.00 \$2,533.00 Cab 10,031 LB 9055678P74 044.00 \$2,533.00 Cab 8,157 LB 9057702P06 044.00 \$2,533.00 Cab 8,157 LB 9060701P94 14581) \$269.00 \$646.00 044.00 \$2,533.00					

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
	•		· · · ·	
	2721			
PACKAGE SELEC	CHON			
SD_T9980 PA	ACKAGING			
X99801X	LESS PACKAGING			No Charge
OPERATOR PLAT	TFORM			
SD 10300 OI	PERATOR STRUCTURE #1			
Cab	PERATOR STRUCTURE #1			
744588	Deluxe Cab			No Charge
	Includes instructor seat, rear wiper and washer,			
	radio & internal mirror			
334183	Deluxe Cab w/HiVis Panel		9000421P98	\$541.00
	Includes high visibility panel, instructor seat,			
	rear wiper and washer, radio & internal mirror			
DOWED TRAIN				
POWER TRAIN				
TRANSMISSION				
SD_T2800 SF	PEED		.	
759059	40KPH - REAL ALL TYR		9000199P68	\$256.00
	25 MPH (40 KPH) Transmission for 4WD			
CD T0040 TF	ANICHICCION			
SD_T2810 TF	12x12 Power Shuttle w/Creeper		9000478P92	\$614.00
334170	20x20 Power Shuttle with Creeper		30004761 92	Ψ014.00
	(12x12 + 8x8 creeper)			
	Hydraulic PTO			
SD_T2820 PA		1	, ,	
743551	Parking Lock		9000039P78	\$51.00
	Transmission parking lock			
	Engaged using the range shift lever			

AXLES			
SD_T4010 FR	ONT AXLE		
336858	2WD Standard Axle Heavy Duty	(901203F	(\$1,543.00)
	Requires 20 MPH (30 KPH)		
	Compatible with 655TL		
	Requires rear wheel weights (330470) ONLY when		
	ordered with 655TL		
	NOT compatible with 665TL		
744581	4WD+EH Engage+Limited Slip+HD	9000209	P82 \$269.00
	Heavy-Duty Limited Slip		
	Base equipment on PowerStar 120		
	Requires Heavy-Duty rear axle (333411)		
SD T4810 RE	EAR AXLE		
333411	Heavy Duty Rear Axle	9000503	P88 \$646.00
	Heavy-Duty Rear Axle		
	Base Equipment on PowerStar 120		
	Required for 34 & 38 inch rear tires		
	NOT compatible with Standard-Duty 4WD		
	front axles (743559 or 744580)		
	NOT compatible with 30 inch or smaller rear tires		
	on PowerStar 90, 100 or 110		
TIDEO			

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

3D_14940 FRONT WHEELS AND TIRES		
2WD Front Tires		
8126601 9.5L15 4 RIB 8 PLY	9000485P16	\$622.00
8125801 7.50-16 8 PLY HD	9000370P50	\$475.00
8125901 10.00-16 8 PLY HD	9000691P86	\$887.00
4WD Bias Front Tires		
8232304 11.2 x 24 6PR R1	9000755P04	\$968.00
8235601 12.4-24 8PR	9000814P32	\$1,044.00
8236501 13.6-24 8PR R1 FLANG	9000997P62	\$1,279.00
8240604 14.9-24 8PR R1	9001228P50	\$1,575.00
4WD Radial Tires		
8232404 11.2R24 R1W	9000911P04	\$1,168.00
8235404 12.4R24 R1W	9001087P32	\$1,394.00
4WD Radial Front Tires		
8236404 13.6R24 R1W	9001330P68	\$1,706.00
8239404 14.9R24 R1W	9001637P22	\$2,099.00
4WD Specialty Front Tires		
8290904 12.5/80-18 10PR R4	9001300P26	\$1,667.00

		8247404	11.2R28 R1W	9001123P98	\$1,441.00
Γ	RFA	R			

SD T4950 REAR WHEELS AND TIRES

	AR WHEELS AND TIRES		
Bias Rear T			
8355304	16.9-30 6PR R1	9001720P68	\$2,206.00
	4WD Front Tire - 11.2-24 (8232304)		
	2WD Front Tire - 9.5L-15 4 rib (8126601)		
8363801	18.4-30 12PR R1 FLAN	9001975P74	\$2,533.00
	4WD Front Tire - 12.4-24 (8235601)		
	2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)		
8364604	16.9-34 8PR R1	9001421P94	\$1,823.00
	4WD Front Tire - 13.6-24 (8236501)		
	2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)		
8365501	18.4-34 10PR	9002176P98	\$2,791.00
	4WD Front Tire - 14.9-24 (8240604)		
	2WD Front Tire - 10.00-16 (8125901)		
Radial Rear	Tires		
8355404	16.9R30 R1W	9001975P74	\$2,533.00
	4WD Front Tire - 11.2R24 (8232404)		
	2WD Front Tire - 7.50-16 (8125801) or 9.5L-15 4 rib (8122601)		
8357404	18.4R30 R1W	9002635P62	\$3,379.00
	4WD Front Tire - 12.4R24 (8235404)		
	2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)		
8302804	16.9R34 R1W	9001896P96	\$2,432.00
	4WD Front Tire - 13.6R24 (8236404)		
	2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)		
8365404	18.4R34 R1W	9002853P24	\$3,658.00
	4WD Front Tire - 14.9R24 (8239404)		
	2WD Front Tire - 10.00-16 (8125901)		
Specialty Re	ear Tires	•	
8391904	19.5L-24 10 PR R4	9002013P18	\$2,581.00
	4WD Front Tire - 12.5/80-18 (8290904)		
8372404	13.6R38 R1W 8372404	9001770P60	\$2,270.00
	4WD Front Tire - 11.2R28 (8247404)		
	2WD Front Tire - 7.50-16 (8125801)		

HYDRAULICS

	MID-MOUNT
_	

SD_T8280 MID-MOUNT VALVES

	338125	2Mid-Mount w/Mec Joystick	9001123P98	\$1,441.00
		2 function mid-mount valve and joystick		

Bid Term: 2/20/19 - 2/19/21

	336780	2Mid-Mount w/Mec Joystick +Div	9001686P36	\$2,162.00
		2 function mid-mount valve and joystick with 3rd function diverter		
		Requires a Loader		
		Bucket with Grapple NOT AVAILABLE as Factory Installed		

LOADER

LOADER

SD_T8110 LOADER BRACKETS

Standard D	uty Loader		
336914	Non Self Leveling Ldr +SSQA	9004590P30	\$5,885.00
	655TL/710LU		
	Non Self Leveling with Skid Steer Attachment		
	NOT compatible with 38" rear tires		
336732	Non Self Leveling Ldr +Euro	9004590P30	\$5,885.00
	655TL/710LU		
	Non Self Leveling with Euro Style Attachment		
	NOT compatible with 38" rear tires		
336734	Mech Self Leveling Ldr +SSQA	9005429P58	\$6,961.00
	655TL/715LU		
	Mechanical Self Leveling with Skid Steer Style Attachment		
	NOT compatible with 38" rear tires		
336736	Mech Self Leveling Ldr +Euro	9005429P58	\$6,961.00
	655TL/715LU		
	Mechanical Self Leveling with Euro Style Attachment		
	NOT compatible with 38" rear tires		
Heavy Duty	Loader		
336740	HD Non Self Leveling Ldr +SSQA	9005319P60	\$6,820.00
	665TL/720LU		
	Non Self Leveling with Skid Steer Style Attachment		
336742	HD Non Self Leveling Ldr +Euro	9005319P60	\$6,820.00
	665TL/720LU		
	Non Self Leveling with Euro Style Attachment		
336744	HD Self Leveling Ldr +SSQA	9006162P78	\$7,901.00
	665TL/725LU		
	Mechanical Self Leveling with Skid Steer Style Attachment		
336746	HD Self Leveling Ldr +Euro	9006162P78	\$7,901.00
	665TL/725LU		
	Mechanical Self Leveling with Euro Style Attachment		

SD_T8140 BUCKET

	336748	72" Bucket	9000424P32	\$544.00
	336750	84" Bucket	9000713P70	\$915.00



REAR PTO	
REAR FTO	
SD_T8010 PTO	
743594 540/1000 RPM PTO 9000424P32	\$544.00
HITCH	
REAR 3 POINT HITCH	
SD_T8130 3 POINT HITCH CONTROL	
332035 Mech 3 Pt Hitch Ground Control 9000197P34	\$253.00
SD_T8200 HITCH	
759058 MDC - REAR HPL - 2 A 9000811P20	\$1,040.00
2 auxiliary lift rams	
8,000 lbs lift capacity	
Requires Heavy Duty front and rear axles 743595 Lift-O-Matic Plus 9000200P46	\$257.00
Lift-O-Matic Plus	\$257.00
758931 MDC HPL+LOM+2AUX 9001011P66	\$1,297.00
Lift-O-Matic Plus with 2 auxiliary lift rams	
8,000 lbs lift capacity	
Requires Heavy Duty front and rear axles	
CAB OR ROPS PLATFORM	
CAB OR ROF3 FLATFORM	
OTHER	
SD_T6730 PIN CONNECTOR	
334994 STD+30+HRN+ACS+MON 9000059P28	\$76.00
Monitor mounting bracket, 30Ah socket & 2-12V power outlets	
WEIGHTS	
FRONT	
SD_T2150 FRONT BALLAST 333215 Front Carrier +6 88 lb Weights 9000620P10	\$70E 00
333215 Front Carrier +6 88 lb Weights 9000620P10 Total weight - 661 lbs (300 kg)	\$795.00
335215 8 WEIGHTS 40 KG - CA 9000784P68	\$1,006.00
Total weight - 837 lbs (380 kg)	

Spanish operator manual

POWERSTAR 90-120 PS A LA CARTE CAB US PRICE LIST

-	REA	R			
	S	D_T4961 RE	AR BALLAST		
		330470	4 x 110 lb Rear Wheel Weights	9000483P60	\$620.00
			Total weight - 440 lbs (200 kg)		
			NOT compatible with 24" rear tires option		
			Required with 2WD HD front axle		
М	ISC	ELLANEOUS	3		
F	EN	DERS FRONT			
	S	D_T8740 FR	ONT FENDERS		
		744674	Dynamic Fenders	9000542P10	\$695.00
ı	EN	DERS REAR			
	S	D_T8700 FE	NDERS		
		744599	Rear Fenders w/Extensions	9000125P58	\$161.00
0	PEF	RATOR'S MA	NUALS		
	S	D T9840 CC	OUNTRY CONFIGURATION		
		334256	Canada (FR) Config ROPS		No Charge
			French operator manual		9
		334257	USA Spanish Configuration		No Charge



Standard Equipment

KEY SELLING POINTS:

- -CommandArc™ ergonomically places most frequently used controls to operator's right
- -Hydraulic shuttle lever
- -3.4L, 4-cylinder, 16 valve F5G engines with common rail fuel injection system
- -Tier 4B EPA emissions compliant with Selective Catalytic Reduction (SCR) & Cooled Exhaust Gas Recirculation (CEGR)
- -Factory Installed Loader available

PowerStar 90 86 Gross Engine hp 73 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207 cu in (3.4 L) Displacement

PowerStar 100 98 Gross Engine hp 85 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207 cu in (3.4 L) Displacement

PowerStar 110 107 Gross Engine hp 93 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207 cu in (3.4 L) Displacement

PowerStar 120 117 Gross Engine hp 100 PTO hp @ 2300 rpm 4 Cyl Turbocharged Engine 207 cu in (3.4 L) Displacement ALL MODELS:

Tier 4B Emissions Compliant:
 (SCR + CEGR)

Electronic Injection Bosch
 High-pressure Common Rail System

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Dual Element Air Filter

Constant Engine RPM

Vertical Exhaust

30.3 gal Fuel Tank with Guard

2.8 gal AdBlue DEF Tank

TRANSMISSION:

Parking brake

Power Shuttle
12 Forward and 12 Reverse Speeds
(4) Synchronized Gears
(3) Non-synchronized Ranges
Forward Reverse Synchronized Shuttle
19 mph (30 kph)
Speed varies with tire selection

LH side steering column mounted

HYDRAULIC SYSTEM:

Open Center System

Dual Gear Pumps

Implement Pump: 16.9 gpm (63.9 L)

Steering Pump: 9.7 gpm (37.0 L)

Total Flow: 26.6 gpm (100.8 L)

(2) Open Center Remote Valves with detent

3-POINT LIFT SYSTEM:
Right hand console mounted
lever control
Mechanical Draft Control
5,620 Pounds Lift Capacity
Category II Ends
Telescopic Stabilizers
Flexible Lower Link Ends

-T1LJ 05

POWERSTAR 90-120 PS A LA CARTE ROPS US PRICE LIST

Standard Equipment

STEERING/BRAKES:
Hydrostatic Powe

Hydrostatic Power Steering

Brakes-

Wet disk brakes

Hydraulically assited

AXLES:

FRONT - 2WD (19 mph, 30 kph)

Inverted U-section type

Adjustable Tread Width from 57.0 in.

to 79.7 in.

FRONT - 4WD

Limited Slip

- PowerStar 90, 100 & 110:

Electrohydraulic FWD Engagement Adjustable Tread Width from

56.6 in. to 76.6 in.

- PowerStar 120:

Heavy Duty Electrohydraulic FWD

Engagement

Adjustable Tread Width from

56.6 in. to 76.6 in.

REAR

- PowerStar 90, 100 & 110:

Flange Type

Adjustable Tread Width 55.5 in.

to 76.2 in.

- PowerStar 120:

Heavy Duty Flange Type

Adjustable Tread Width 55.5 in.

to 76.2 in.

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent

Flip-up PTO Shaft Guard

PowerStar 90, 100 & 110:

540 rpm Hydraulic

PowerStar 120:

540/1000 rpm Hydraulic

-Electronic engagement

-Wet clutch

1-3/8 in. 6 splines

ELECTRICAL:

(1) 800 cca Heavy-Duty Battery - ROPS

120 amp Alternator

7-pin Outlet for trailer/implement lighting

and signals

3-pin Power Outlet (30 amp)

Single Pin (8 amp) Accessory Power

outlet

12V power socket

INSTRUMENTATION:

Analog Instrumentation with warning

lights for air cleaner service,

alternator, oil pressure, fuel

sediment/water sensor, PTO
engagement, head light high beam,

low fuel and parking brake,

digital speed readout

Gauges for fuel level, engine temp,

tachometer and hour meter

LIGHTING:

ROPS

Front: (2) Halogen Headlights

Rear: (1) ROPS mounted worklight

Turn Signals/Flashers/Rear Lights

OPERATOR PROTECTIVE STRUCTURE:

ROPS MODELS

2-Post Foldable ROPS with ISO-

mounted flat deck platform

Steering Wheel - adjustable tilt

Seat - Vinyl covered with mechanical

suspension, operator's presence

sensor, retractable seat belts and

arm rests

Suspended pedals

Locking brake pedals

MISCELLANEOUS:

Pivoting Engine Hood

SMV Emblem

Toolbox

-T1LJ 05

POWERSTAR 90-120 PS A LA CARTE ROPS US PRICE LIST

Standard Equipment

WARRANTY:

New Holland Standard Warranty Applies

LOADER:

LOADER:

655TL/710LU NON SELF-LEVELING

Maximum Lift Height @ pivot pin: 126"

Dump Clearance: 93.6"

Digging Depth: 8.2"

Lift Capacity

Max Height @ 800mm: 2,478 LBS

59" high @ 800mm: 3,080 LBS

Breakout Force @ 800mm: 3,739 LBS

Reach @ Max Lift Height: 39.5"

Reach @ Ground Level: 90.7"

Bucket Rollback Angle: 45 degrees

Bucket Dump Angle: 60 degrees

Skid Steer or Euro Style Loader

bucket attach

655TL/715LU SELF-LEVELING

Maximum Lift Height @ pivot pin: 125"

Dump Clearance: 93"

Digging Depth: 8"

Lift Capacity

Max Height @ 800mm: 3,179 LBS 59" high @ 800mm: 4,665 LBS

Breakout Force @ 800mm: 3,860 LBS

Reach @ Max Lift Height: 39.4"

Reach @ Ground Level: 90.5"

Bucket Rollback Angle: 40 degrees

Bucket Dump Angle: 60 degrees

Skid Steer or Euro sytle Loader

bucket attach

665TL/720LU NON SELF-LEVELING

Maximum Lift Height @ pivot pin: 134"

Dump Clearance: 101.4"

Digging Depth: 7"

Lift Capacity

Max Height @ 800mm: 2,632 LBS

59" high @ 800mm: 3,638 LBS

Breakout Force @ 800mm: 4,455 LBS

Reach @ Max Lift Height: 43"

Reach @ Ground Level: 91"

Bucket Rollback Angle: 44 degrees

Bucket Dump Angle: 60 degrees

Skid Steer or Euro style Loader

bucket attach

665TL/725LU SELF-LEVELING

Maximum Lift Height @ pivot pin: 135"

Dump Clearance: 102.2"

Digging Depth: 6.4"

Lift Capacity

Max Height @ 800mm: 3,428 LBS

59" high @ 800mm: 5,549 LBS

Breakout Force @ 800mm: 5,661 LBS

Reach @ Max Lift Height: 43"

Reach @ Ground Level: 93

Bucket Rollback Angle: 40 degrees

Bucket Dump Angle: 60 degrees

Skid Steer or Euro style Loader

bucket attach

Models

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price		
POWERSTAR 90	Rops	8,157 LB	9045559P02	\$58,409.00		
Includes the following Equipment 12.4-24 8PR (8235601) \$1,044.00 18.4-30 12PR R1 FLAN (8363801) \$2,533.00						
POWERSTAR 100	Rops	8,157 LB	9047421P66	\$60,797.00		
POWERSTAR 110	Rops	10,031 LB	9049444P98	\$63,391.00		
Includes the following Equipment 12.4-24 8PR (8235601) \$1,0 18.4-30 12PR R1 FLAN (8363801	044.00) \$2,533.00					
POWERSTAR 120	Rops	8,157 LB	9052444P86	\$67,237.00		
Includes the following Equipment 4WD+EH Engage+Limited Slip (744581) \$269.00 Heavy Duty Rear Axle (333411) \$646.00 12.4-24 8PR (8235601) \$1,044.00 18.4-30 12PR R1 FLAN (8363801) \$2,533.00 540/1000 RPM PTO (743594) \$544.00						



Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
PACKAGE SELE	CTION			
SD T9980 PA	ACKACING			
	LESS PACKAGING			No Charge
OPERATOR PLA	TFORM			
SD T9200 O	PERATOR STRUCTURE #1			
ROPS	THE THREE TONE WIT			
392315	Platform w/Foldable ROPS			No Charge
	Includes tilt column			
334190	Deluxe Platform w/FOPS		9001258P14	\$1,613.00
	Includes tilt column, FOPS canopy, noise reduction kit			
	and 12V power outlet			
DOWED TO AIN				
POWER TRAIN				
TRANSMISSION				
SD_T2800 SF		_	0000400000	#050.00
759059	40KPH - REAL ALL TYR		9000199P68	\$256.00
	25 MPH (40 KPH) Transmission for 4WD			
SD_T2810 TF	RANSMISSION			
334176	12x12 Power Shuttle w/Creeper		9000478P92	\$614.00
	20x20 Power Shuttle with Creeper			•
	(12x12 + 8x8 creeper)			
	Hydraulic PTO			
SD_T2820 PA			, 	
743551	Parking Lock		9000039P78	\$51.00
	Transmission parking lock			
	Engaged using the range shift lever			

Grounds Equipment Bid #ESCNJ 18/19-25 ate Approved Co-op #65MCESCCPS -T1LJ 05



POWERSTAR 90-120 PS A LA CARTE ROPS US PRICE LIST

3D_14010 F	RONT AXLE		
336858	2WD Standard Axle Heavy Duty	(901203P54)	(\$1,543.00)
	Requires 20 MPH (30 KPH)		
	Compatible with 655TL		
	Requires rear wheel weights (330470) ONLY when		
	ordered with 655TL		
	NOT compatible with 665TL		
744581	4WD+EH Engage+Limited Slip+HD	9000209P82	\$269.00
	Heavy-Duty Limited Slip		
	Base equipment on PowerStar 120		
	Requires Heavy-Duty rear axle (333411)		
SD_T4810 R	EAR AXLE		
333411	Heavy Duty Rear Axle	9000503P88	\$646.00
	Heavy-Duty Rear Axle		
	Base Equipment on PowerStar 120		
	Required for 34 & 38 inch rear tires		
	NOT compatible with Standard-Duty 4WD		
	front axles (743559 or 744580)		
	NOT compatible with 30 inch or smaller rear tires		
	on PowerStar 90, 100 or 110		

TIRES

FRONT

SD T4940 FRONT WHEELS AND TIRES

SD_14940 FR	ONT WHEELS AND TIRES		
2WD Front	ries		
8126601	9.5L15 4 RIB 8 PLY	9000485P16	\$622.00
8125801	7.50-16 8 PLY HD	9000370P50	\$475.00
8125901	10.00-16 8 PLY HD	9000691P86	\$887.00
4WD Bias F	ront Tires		
8232304	11.2 x 24 6PR R1	9000755P04	\$968.00
8235601	12.4-24 8PR	9000814P32	\$1,044.00
8236501	13.6-24 8PR R1 FLANG	9000997P62	\$1,279.00
8240604	14.9-24 8PR R1	9001228P50	\$1,575.00
4WD Radial	Tires		
8232404	11.2R24 R1W	9000911P04	\$1,168.00
8235404	12.4R24 R1W	9001087P32	\$1,394.00
4WD Radial	Front Tires		
8236404	13.6R24 R1W	9001330P68	\$1,706.00
8239404	14.9R24 R1W	9001637P22	\$2,099.00
4WD Specia	Ity Front Tires		
8290904	12.5/80-18 10PR R4	9001300P26	\$1,667.00

		8247404	11.2R28 R1W	9001123P98	\$1,441.00
Γ	RFA	·R			

SD_T4950 RE	AR WHEELS AND TIRES		
Bias Rear Ti	res		
8355304	16.9-30 6PR R1	9001720P68	\$2,206.00
	4WD Front Tire - 11.2-24 (8232304)		
	2WD Front Tire - 9.5L-15 4 rib (8126601)		
8363801	18.4-30 12PR R1 FLAN	9001975P74	\$2,533.00
	4WD Front Tire - 12.4-24 (8235601)		
	2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)		
8364604	16.9-34 8PR R1	9001421P94	\$1,823.00
	4WD Front Tire - 13.6-24 (8236501)		
	2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)		
8365501	18.4-34 10PR	9002176P98	\$2,791.00
	4WD Front Tire - 14.9-24 (8240604)		
	2WD Front Tire - 10.00-16 (8125901)		
Radial Rear	Tires		
8355404	16.9R30 R1W	9001975P74	\$2,533.00
	4WD Front Tire - 11.2R24 (8232404)		
	2WD Front Tire - 7.50-16 (8125801) or 9.5L-15 4 rib (8122601)		
8357404	18.4R30 R1W	9002635P62	\$3,379.00
	4WD Front Tire - 12.4R24 (8235404)		
	2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)		
8302804	16.9R34 R1W	9001896P96	\$2,432.00
	4WD Front Tire - 13.6R24 (8236404)		
	2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)		
8365404	18.4R34 R1W	9002853P24	\$3,658.00
	4WD Front Tire - 14.9R24 (8239404)		
	2WD Front Tire - 10.00-16 (8125901)		
Specialty Re	ear Tires		
8391904	19.5L-24 10 PR R4	9002013P18	\$2,581.00
	4WD Front Tire - 12.5/80-18 (8290904)		
8372404	13.6R38 R1W 8372404	9001770P60	\$2,270.00
	4WD Front Tire - 11.2R28 (8247404)		
	2WD Front Tire - 7.50-16 (8125801)		

HYDRAULICS

MID-MOUNT		

SD_T8280 MID-MOUNT VALVES

	338125	2Mid-Mount w/Mec Joystick	9001123P98	\$1,441.00
		2 function mid-mount valve and joystick		

The Educational Services Commission of New Jersey Grounds Equipment Bid #ESCNJ 18/19-25 ate Approved Co-op #65MCESCCPS NEW HOLLAND

POWERSTAR 90-120 PS A LA CARTE ROPS US PRICE LIST

AGRICULTURE

	336780	2Mid-Mount w/Mec Joystick +Div	9001686P36	\$2,162.00
		2 function mid-mount valve and joystick with 3rd function diverter		
		Requires a Loader		
		Bucket with Grapple NOT AVAILABLE as Factory Installed		

LOADER

LOADER

SD_T8110 LOADER BRACKETS

Standard D	uty Loader		
336914	Non Self Leveling Ldr +SSQA	9004590P30	\$5,885.00
	655TL/710LU		
	Non Self Leveling with Skid Steer Attachment		
	NOT compatible with 38" rear tires		
336732	Non Self Leveling Ldr +Euro	9004590P30	\$5,885.00
	655TL/710LU		
	Non Self Leveling with Euro Style Attachment		
	NOT compatible with 38" rear tires		
336734	Mech Self Leveling Ldr +SSQA	9005429P58	\$6,961.00
	655TL/715LU		
	Mechanical Self Leveling with Skid Steer Style Attachment		
	NOT compatible with 38" rear tires		
336736	Mech Self Leveling Ldr +Euro	9005429P58	\$6,961.00
	655TL/715LU		
	Mechanical Self Leveling with Euro Style Attachment		
	NOT compatible with 38" rear tires		
Heavy Duty	Loader		
336740	HD Non Self Leveling Ldr +SSQA	9005319P60	\$6,820.00
	665TL/720LU		
	Non Self Leveling with Skid Steer Style Attachment		
336742	HD Non Self Leveling Ldr +Euro	9005319P60	\$6,820.00
	665TL/720LU		
	Non Self Leveling with Euro Style Attachment		
336744	HD Self Leveling Ldr +SSQA	9006162P78	\$7,901.00
	665TL/725LU		
	Mechanical Self Leveling with Skid Steer Style Attachment		
336746	HD Self Leveling Ldr +Euro	9006162P78	\$7,901.00
	665TL/725LU		
	Mechanical Self Leveling with Euro Style Attachment		

SD_T8140 BUCKET

		336748	72" Bucket		9000424P32	\$544.00		
Γ		336750	84" Bucket		9000713P70	\$915.00		

The Educational Services Commission of New Jersey Grounds Equipment Bid #ESCNJ 18/19-25 ate Approved Co-op #65MCESCCPS

-T1LJ 05



POWERSTAR 90-120 PS A LA CARTE ROPS US PRICE LIST

PTO			
REAR PTO			
SD_T8010 PT	TO		
743594	540/1000 RPM PTO	9000424P32	\$544.00
		, , , , , , , , , , , , , , , , , , , ,	***************************************
нітсн			
REAR 3 POINT HI	TCH		
OD T0400 01	POINT LITTOU CONTROL		
SD_18130 31 332035	POINT HITCH CONTROL Mech 3 Pt Hitch Ground Control	9000197P34	\$253.00
332033	Medi 3 Ft Hitari Ground Control	9000197F34	\$255.00
SD_T8200 HI	TCH		
759058	MDC - REAR HPL - 2 A	9000811P20	\$1,040.00
	2 auxiliary lift rams		
	8,000 lbs lift capacity		
	Requires Heavy Duty front and rear axles		*
743595	Lift-O-Matic Plus	9000200P46	\$257.00
758931	Lift-O-Matic Plus MDC HPL+LOM+2AUX	9001011P66	\$1,297.00
730931	Lift-O-Matic Plus with 2 auxiliary lift rams	90010111100	φ1,297.00
	8,000 lbs lift capacity		
	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		
	Requires Heavy Duty front and rear axles		
WEIGHTS			
FRONT			
CD T0450 FF	OONT DALLACT		
333215	RONT BALLAST Front Carrier +6 88 lb Weights	9000620P10	\$795.00
333213	Total weight - 661 lbs (300 kg)	30000201 10	Ψ195.00
335215	8 WEIGHTS 40 KG - CA	9000784P68	\$1,006.00
	Total weight - 837 lbs (380 kg)		, ,
REAR			
OD 74004	CAD DALLACT		
SD_T4961 RE 330470	Ax 110 lb Rear Wheel Weights	9000483P60	\$620.00
330470	Total weight - 440 lbs (200 kg)	9000463760	\$620.00
	NOT compatible with 24" rear tires option		
	Required with 2WD HD front axle		
	• •		

MISCELLANEOUS									
FENDERS FRONT	FENDERS FRONT								
SD_T8740 FR	ONT FENDERS								
744674	Dynamic Fenders		9000542P10	\$695.00					
FENDERS REAR									
SD_T8700 FEI	NDERS								
744599	Rear Fenders w/Extensions		9000125P58	\$161.00					
OPERATOR'S MA	NUALS								
SD_T9840 COUNTRY CONFIGURATION									
334256	Canada (FR) Config ROPS			No Charge					
	French operator manual			_					
334257	USA Spanish Configuration			No Charge					
	Spanish operator manual								

Part Number	Description	PowerStar 90	, 100, 110, 120	Notes		
	HYDRAULICS	ROPS	САВ			
719195700	Third rear remote valve with lever control	Х	Х	Tractor must have 2nd rear remote valve installed.		
719195701	Third rear remote valve with lever control			Tractor must have 2nd rear remote valve installed.		
719405700	First rear remote valve flow control	Х	Х	Tractor must have 2nd rear remote valve installed. Not		
				compatible with 3 rear remote valves.		
719405701	First rear remote valve flow control			Tractor must have 2nd rear remote valve installed. Not compatible with 3 rear remote valves.		
719124720	Two mid mount valves with joystick control	Х	Х	Includes trim kit (NOT COMPATIBLE WITH TIER 4A)		
	WEIGHTS					
710225250	Front End weight bracket					
710226250	6 Front Weights 88 lbs each (528 lbs total)	Х	Х	Requires front end weight bracket #710225250		
710249250	8 Front Weights 88 lbs each (704 lbs total)	Х	Х	Requires front end weight bracket #710225250		
710471250	4 Rear Wheel Weights 110 lbs each (440 lbs total)	Х	Х	For 28" and 30" rear wheels		
710465250	6 Rear Wheel Weights 70 lbs each (420 lbs total)	X	Х	For 24" wheels		
	ELECTRICAL			_		
710762251	Rotary Beacon Kit	Х		Connects to 12V power socket		
710762252	Rotary Beacon Kit		Х	Connects to 12V power socket		
719216250	Engine Block Heater Kit	Х	Х	p =		
81864735	4 Pin Outlet (25 amp) Electrical Plug					
86508819	Single Pin Male (8 amp) Electrical Plug					
718122950	Back Up Alarm		Х			
	PLATFORM					
718130050	Monitor Mounting Bracket		Х			
718462250	White Canopy	Х		FOPS Compliant		
718463250	Blue Canopy	Х		FOPS Compliant		
	LOADER	+				
	DIA	Х	Х	See 600TL Series Loader Price and Data Pages		
	3rd Function Diverter Valve	Х	Х	NOT AVAILABLE AS DIA		
715824136	Grill Guard Insert	Х	Х	Order from 600TL Series Loader Price and Data Pages		
	MISCELLANEOUS					
718057720	Dynamic Front Fenders	х	х	Requires 4WD - 14.9-24, 14.9R24, 11.2-28, 11.2R28, 13.6-24, 13.6R24, 12.4-24 or 12.4R24 (NOT COMPATIBLE WITH 655TL Loader)		
719429250	Bolt-on Cutting Edge for 72" Bucket	Х	Х			
719430250	Bolt-on Cutting Edge for 84" Bucket	Х	X			

Bid Term: 2/20/19 - 2/19/21

PowerStar 90, 100, 110, 120 TIRE CHART							
Tire Tyre	Application	Rear Tires		Matching 4WD Front Tires		Matching 2WD Front Tires	
Tire Type		Tire	Order Code	Tire	Order Code	Tire	Order Code
	Agricultural - R1	16.9-30	8352404	11.2-24	8232304	9.5L-15 4 rib	8126601
		18.4-30	8363801	12.4-24	8235601	7.50-16	8125801
Bias		10.4-30	0303001	12.4-24	0233001	e Tire Order C 9.5L-15 4 rib 81266 7.50-16 81258 10.00-16 81258 10.00-16 81258 10.00-16 81259 9.5L-15 4 rib 81258 7.50-16 81258 10.00-16 81258 7.50-16 81258 10.00-16 81258 10.00-16 81258 10.00-16 81258 10.00-16 81259 10.00-16 81259	8125901
DidS		16.9-34	8364604	13.6-24	8236501	7.50-16 10.00-16	8125801
		10.9-34	0304004	13.0-24	13.6-24 8236501 10.00-16	8125901	
		18.4-34	8365501	14.9-24	8240604	10.00-16 8125	8125901
		16.9R30	8355404	11.2R24	8232404	9.5L-15 4 rib	8126601
		10.9130	0000404	11.21124	0232404	7.50-16	8125801
		18.4R30	8357404	12.4R24	8235404	7.50-16	8125801
Radial	Agricultural - R1W	10.4130	0007404	12.41124	0233404	10.00-16	8125901
		16.9R34	8302804	2804 13.6R24 8236404	8236404	7.50-16	8125801
		10.910-4	0302004		10.00-16	8125901	
		18.4R34	8365404	14.9R24	8239404	10.00-16	8125901
Specialty	Narrow	13.6R38	8372404	11.2R28	8247404	7.5-16	8125801
Specialty	Industrial - R4	19.5L24	8391904	12.5/80-18	8290904	N/A	