



July 2, 2018

PRODUCT AND PRICING BULLETIN

NEW HOLLAND BRAND PRODUCTS, U.S. NO. 18-31A

NEW HOLLAND AG DEALERS WITH CPT AGREEMENT

SUBJECT: COMPACT LOADERS: COMPLETE REVISION EFFECTIVE 10/1/2018

Attached please find a complete revision of the Compact Loaders Price and Data pages which reflect a general economic price increase for units invoiced 10/1/2018 and beyond.



Please take advantage of Fast Pick configurations of select Compact Tractor Loaders. These Fast Pick loaders are the perfect match for Fast Pick tractor configurations. Available Fast Pick Configurations:

- 235TL for Boomer™ 24 Fast Pick
- 140TLA2 for WORKMASTER™ 35 and 40 T4B Fast Picks
- 250TLA2 for Boomer™ 40 Cab T4B Fast Pick
- 260TLA2 for Boomer[™] 50 ROPS and Cab T4B Fast Picks

Select implement Fast Pick packages are also available.

This bulletin and the price pages may be accessed via the Dealer Portal if you have the CPT agreement with New Holland. Log on to the Dealer Portal. With the "Wholegoods" button displayed, click on "Pricing," click on "Loaders and Tractor Implements," and then click on "Compact Loaders." The latest published items will appear at the top of the list.

Please replace your current P&D pages with those attached to this bulletin.

Christine Chleboun
Director, Commercial Marketing
New Holland North America

Dan Valen
Director, Product Marketing
New Holland, North America

Attachment



IMPLEMENTS - "COMPACT LOADERS" INDEX

EQUIPMENT DESCRIPTION	LATEST REVISION	PAGE <u>NUMBER</u>
Index	10/01/18	1
Loaders 100LC for WORKMASTER 25S Sub Compact	10/01/18	2
200LC for WORKMASTER 25 (Tier 4B)	10/01/18	4
140TLA2 for WORKMASTER 35/40 (Tier 4B) 140TL for WORKMASTER 33/37 (Tier 4B)	10/01/18	6
235TLA for Boomer 24	10/01/18	14
250TLA2 for Boomer 35/40 Rops & 40 Cab (Tier 4B) 250TLA1 for Boomer 33/37 (Tier 4B) 250TLA1 for Boomer 37 Cab (Tier 4B)	10/01/18	18
260TLA2 for Boomer 45/50/55 Rops & Cab (Tier 4B) 260TLA1 for Boomer 41/47 (Tier 4B) 260TLA1 for Boomer 41/47 Cab (Tier 4B)	10/01/18	26
250TLA for Boomer 3000 Series (Tier 3) 250TLA for Boomer 45D/50D (Tier 3) 250TLA for Boomer 46D/54D (Tier 4B)	10/01/18	34

2

100LC LOADER FOR WM25S SUBCOMPACT (ONLY) US PRICE LIST

AGRICULTURE

Standard Equipment

TRACTOR APPLICATIONS:

Current New Holland Compact Models:
- WORKMASTER™ 25S (ONLY)

NOTE:

Important Compatibility Information

- A configured model 100LC is ONLY compatible with the WORKMASTER
 25S Subcompact tractor
- To assure proper performance, see
 Operator's Manual for recommended counterweighting

Loader Specifications:

Lift Capacity to Maximum Height

- @ Bucket Pivot Pins (lbs.): 1005
- @ 500mm forward (lbs.): 693

Lift Capacity to 1500 mm Height

- @ Bucket Pivot Pins (lbs.): 1142
- @ 500mm forward (lbs.): 823

Breakout Force

- @ Bucket Pivot Pins (lbs.): 2078
- @ 500mm forward (lbs.): 1426

Max Lift Height @ Pivot Pin (in.): 72
Clearance w/Bucket Dumped (in.): 51
Reach at Maximum Height (in.): 23.4
Maximum Dump Angle (deg.): 46
Maximum Rollback Angle (deg.): 28
Digging Depth (in.): 4.6
Height in Carry Position (in.): 41.5

Bucket Size and Capacity

- Width: 50 Inch
- Capacity (cu. ft.) Struck: 5.3 Heaped: 7.4

Cycle Times (sec)

- Raise: 3.6
- Lower: 2.1
- Bucket Dump: 2.3
- Bucket Rollback: 1.5

Approx. Weight w/ Bucket (lbs.): 363

Loader specifications may vary based on tractor model, hydraulic system, tire size, etc.

*NOTE: The 100LC DOES NOT come with mid mount valve, couplers or joystick as these items are standard on the WORKMASTER™ 25S

WARRANTY

New Holland Standard Warranty Applies

3



100LC LOADER FOR WM25S SUBCOMPACT (ONLY) US PRICE LIST

Models

COMMERCIAL MODEL	MODEL	Weight	Factory Data	List Price
LC100	100LC	511 LB	9002317P32	\$2,826.00

200LC LOADER FOR WM25 (ONLY) US PRICE LIST

Standard Equipment

TRACTOR APPLICATIONS:

Current New Holland Compact Models:

- WORKMASTER™ 25 (ONLY)

NOTE:

Important Compatibility Information

- A configured model 200LC is ONLY compatible with the WORKMASTER
 25 compact tractor. It is NOT compatible with WORKMASTER 33/37 (T4B) or WORKMASTER 35/40 (T4B) compact tractors
- To assure proper performance, see
 Operator's Manual for recommended counterweighting

Loader Specifications:

Lift Capacity to Maximum Height

- @ Bucket Pivot Pins (lbs.): 1600
- @ 500mm forward (lbs.): 1214

Lift Capacity to 1500 mm Height

- @ Bucket Pivot Pins (lbs.): 1955
- @ 500mm forward (lbs.): 1508

Breakout Force

- @ Bucket Pivot Pins (lbs.): 2637
- @ 500mm forward (lbs.): 1926

```
Max Lift Height @ Pivot Pin (in.): 94.3
Clearance w/Bucket Dumped (in.): 64.3
Reach at Maximum Height (in.): 18.2
Maximum Dump Angle (deg.): 52
Maximum Rollback Angle (deg.): 41
Digging Depth (in.): 4.3
Height in Carry Position (in.): 51.3
```

Bucket, Type Size and Capacity

- Quick Attach Design
- Width: 66 Inch
- Capacity (cu. ft.) Struck: 9.5 Heaped: 14.5

Cycle Times (sec)

- Raise: 3.1
- Lower: 2.0
- Bucket Dump: 1.7
- Bucket Rollback: 2.7

Approx. Weight w/ Bucket (lbs.): 1819

Loader specifications may vary based on tractor model, hydraulic system, tire size, etc.

*NOTE: The 200LC comes with a mid mount valve and couplers.

WARRANTY

New Holland Standard Warranty Applies



200LC LOADER FOR WM25 (ONLY) US PRICE LIST

AGRICULTURE

Models

COMMERCIAL MODEL	MODEL	Weight	Factory Data	List Price
LC200	200LC	1,124 LB	9003389P06	\$4,133.00



140TLA2 FARM LOADER WM35/40 (T4B ONLY) US PRICE LIST

Standard Equipment

TRACTOR APPLICATIONS: Current New Holland Compact Models: - WORKMASTER™ 35 (T4B ONLY) - WORKMASTER™ 40 (T4B ONLY) NOTE: Important Compatibility Information - A configured model 140TLA2 is NOT compatible with the WORKMASTER 35/40 T3 or WM33/37 T4B Tractors - To assure proper performance, see Operator's Manual for recommended counterweighting Loader Specifications: (PRELIMINARY) Max lift height (under level bucket): - 91.5 in / 2324 mm Clearance with bucket dumped: - 64 in / 1626 mm Max dump angle: 48 ° Reach with bucket on ground: - 74.0 in / 1879.6 mm Bucket roll back angle: 30.4 ° Lift capacity: @ bucket pivot pin, max height: - 1250 (lbs.) / 567 (kg) @ 500 mm forward, max height: - 1100 (lbs.) / 499 (kg) @ bucket pivot pin, 1500 mm height:

- 1500 (lbs.) / 680 (kg)

- 2700 (lbs.) / 1225 (kg)

- 1900 (lbs.) / 862 (kg)

Breakout force:

@ bucket pivot pin:

@ 500 mm forward:

```
Cycle times:
 Raising: 3.8 sec
 Lowering: 1.7 sec
 Lowering (float): 2.2 sec
 Bucket dumping: 2.2 sec
 Bucket roll back: 1.7 sec
Bucket Dimensions:
Width: 68.4 in / 1736.7 mm
Depth: 22.0 in / 558.8 mm
Height: 21.4 in / 542.9 mm
Length: 31.0 in / 787.4 mm
 Weight: 260 (lbs.) / 118 (kg)
Bucket Capacities:
 Struck:
    68" Bucket = .43 cu yd.
 Heaped:
    68" Bucket = .53 cu yd.
Loader specifications may vary based
  on tractor model, hydraulic system, tire
 size, etc.
*NOTE: The 140TLA2 DOES NOT come
 with mid mount valve, couplers or
  joystick as these items are now
 standard on the WORKMASTER™
  35/40 T4B tractors. If a mid mount
 valve, coupler or joystick is needed,
 these items must be ordered from
 parts.
```

New Holland Standard Warranty Applies



140TLA2 FARM LOADER WM35/40 (T4B ONLY) US PRICE LIST

AGRICULTURE

Models

COMMERCIAL MODEL	Weight	Factory Data	List Price
140TLA2 T4B 35/40	800 LB	9004318P12	\$5,266.00

140TLA2 FARM LOADER WM35/40 (T4B ONLY) US PRICE LIST

Factory Supplied Options

Order Code Description	Weight	Factory Data	List Price
------------------------	--------	--------------	------------

FAST PICK CONFIGURATION

SD_T9981 CONFIGURATION

XT9981X	Less Fast Pick Config		No Charge
X0341XX	WM 35 Gear R1 Fast Pick	(900086	SP92) (\$106.00)
	Fast Pick 140TLA2 Loader for WORKMASTER 35 ROPS (T4B)		
	Package Contains:		
	- Base 140TLA2 Loader		
	- Mounting Frame		
	- SSL Quick Attach Face plate		
	- 68" Quick Attach bucket		
X0337XX	WM 35 Gear R4 Fast Pick	(900086	6P92) (\$106.00)
	Fast Pick 140TL2 Loader for WORKMASTER 35 ROPS (T4B)		
	Package Contains:		
	- Base 140TLA2 Loader		
	- Mounting Frame		
	- SSL Quick Attach Face plate		
	- 68" Quick Attach bucket		
X0338XX	WM 40 HST R4 Fast Pick	(900086	SP92) (\$106.00)
	Fast Pick 140TLA2 Loader for WORKMASTER 40 ROPS (T4B)		
	Package Contains:		
	- Base 140TLA2 Loader		
	- Mounting Frame		
	- SSL Quick Attach Face plate		
	- 68" Quick Attach bucket		

140TLA2 FARM LOADER WM35/40 (T4B ONLY) US PRICE LIST

Factory Supplied Attachments

O	rder Code	Description	Weight	Factory Data	List Price
	713762006	Cls 2 Hydraulic Line & Fitting Kit CONVERSION KIT. This kit allows a 140TL loader (713740016) for WORKMASTER 33/37 tractors to be used on WORKMASTER 35/40 T4B tractors.	300 LB	9000615P00	\$750.00
		The kit contains new loader mounting brackets, hardware and hydraulic coupler kit.			

10

140TLA FARM LOADER WM33/37 (T4B ONLY) US PRICE LIST

AGRICULTURE

Standard Equipment

TRACTOR APPLICATIONS:

Current New Holland Compact Models:

- WORKMASTER™ 33 (T4B)
- WORKMASTER™ 37 (T4B)

NOTE:

Important Compatibility Information

- A configured model 140TLA is NOT compatible with the WORKMASTER 35/40 T3 or T4B Tractors
- To assure proper performance, see Operator's Manual for recommended counterweighting

Loader Specifications:

Max lift height (under level bucket):

- 91.5 in / 2324 mm

Clearance with bucket dumped:

- 64 in / 1626 mm

Max dump angle: 48 °

Reach with bucket on ground:

- 74.0 in / 1879.6 mm

Bucket roll back angle: 30.4 °

Lift capacity:

- @ bucket pivot pin, max height:
 - 1250 (lbs.) / 567 (kg)
- @ 500 mm forward, max height:
 - 1100 (lbs.) / 499 (kg)
- @ bucket pivot pin, 1500 mm height:
 - 1500 (lbs.) / 680 (kg)

Breakout force:

- @ bucket pivot pin:
 - 2700 (lbs.) / 1225 (kg)
- @ 500 mm forward:
 - 1900 (lbs.) / 862 (kg)

Cycle times:

Raising: 3.8 sec Lowering: 1.7 sec

Lowering (float): 2.2 sec Bucket dumping: 2.2 sec Bucket roll back: 1.7 sec

Bucket Dimensions:

Width: 68.4 in / 1736.7 mm
Depth: 22.0 in / 558.8 mm
Height: 21.4 in / 542.9 mm
Length: 31.0 in / 787.4 mm
Weight: 260 (lbs.) / 118 (kg)

Bucket Capacities:

Struck:

68" Bucket = .43 cu yd.

Heaped:

68" Bucket = .53 cu yd.

Loader specifications may vary based on tractor model, hydraulic system, tire size, etc.

*NOTE: The 140TLA DOES NOT come with mid mount valve, couplers or joystick as these items are now standard on the WORKMASTER™ 33/37 tractors. If a mid mount valve, coupler or joystick is needed, these items must be ordered from parts.

WARRANTY

New Holland Standard Warranty Applies



140TLA FARM LOADER WM33/37 (T4B ONLY) US PRICE LIST

Models

COMMERCIAL MODEL	Weight	Factory Data	List Price	
140TL	800 LB	9004318P12	\$5,266.00	

12

140TLA FARM LOADER WM33/37 (T4B ONLY) US PRICE LIST

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

FAST PICK CONFIGURATION

SD_T9981 CONFIGURATION

XT9981X	Less Fast Pick Config		No Charge
X0279XX	WRKMSTR 33 Fast Pick	(900086P10)	(\$105.00)
	FAST PICK PKG PRICE = 2% SAVINGS OVER ALA-CART ORDER		
	Fast Pick 140TL Loader for WORKMASTER 33 ROPS		
	Package Contains:		
	- Base 140TL Loader		
	- Mounting Frame		
	- SSL Quick Attach Face plate		
	- 68" Quick Attach bucket		
X0280XX	WRKMSTR 37 Fast Pick	(900086P10)	(\$105.00)
	FAST PICK PKG PRICE = 2% SAVINGS OVER ALA-CART ORDER		
	Fast Pick 140TL Loader for WORKMASTER 33 ROPS		
	Package Contains:		
	- Base 140TL Loader		
	- Mounting Frame		
	- SSL Quick Attach Face plate		
	- 68" Quick Attach bucket		



140TLA FARM LOADER WM33/37 (T4B ONLY) US PRICE LIST

Factory Supplied Attachments

Order Code	Description	Weight	Factory Data	List Price
713762006	Cls 2 Hydraulic Line & Fitting Kit CONVERSION KIT. This kit allows a 140TL loader (713740016) for WORKMASTER 33/37 tractors to be used on WORKMASTER 35/40 T4B tractors.	300 LB	9000615P00	\$750.00
	The kit contains new loader mounting brackets, hardware and hydraulic coupler kit.			

TRACTOR APPLICATIONS:

235TL FARM LOADER BOOMER 24 US PRICE LIST

Standard Equipment

Breakout force

```
Current New Holland Compact Models:
                                                       @ bucket pivot pin:
  - Boomer™ 24
                                                         - 1672 (lbs.) / 760 (kg)
                                                        @ 500 mm forward:
NOTE:
                                                         - 1166 (lbs.) / 530 (kg)
Important Compatibility Information
                                                    Bucket roll back force:
- 235TL is only compatible with Boomer
                                                        @ ground level (500 mm forward):
                                                         - 1298 (lbs.) / 590 (kg)
  24 compact tractors
 - To assure proper performance, see
  Operator's Manual for recommended
                                                   Cycle times:
  counterweighting
                                                    Raising: 2.4 sec
                                                    Lowering: 1.2 sec
Loader Specifications:
                                                    Bucket dumping: 2.4 sec
Max lift height (to bucket pivot pin):
                                                    Bucket roll back: 1.2 sec
   - 80.7 in / 2050 mm
Max lift height (under level bucket):
                                                   Bucket width:
   - 75.6 in / 1920 mm
                                                        54.0 in / 1371 mm
Reach at max lift height:
   - 25.2 in / 640 mm
                                                   Bucket Capacities:
Max dump angle: 51.0°
                                                     Struck:
Bucket roll back angle: 29.0°
                                                       54" Bucket = .20 cu yd.
Digging depth:
                                                      Heaped:
   - 3.9 in / 100.0 mm
                                                       54" Bucket = .24 cu yd.
Lift capacity:
                                                    Loader includes Grill Guard
    @ bucket pivot pin, max height:
     - 1034 (lbs.) / 470 (kg)
                                                    Loader specifications may vary based
   @ 500 mm forward, max height:
                                                    on tractor model, engine speed,
     - 704 (lbs.) / 320 (kg)
                                                    hydraulic system, tire type/ size, etc.
   @ bucket pivot pin, 1500 mm height:
    - 1298 (lbs.) / 590 (kg)
    @ 500 mm forward, 1500 mm height
                                                   WARRANTY
     - 968 (lbs.) / 440 (kg)
                                                    New Holland Standard Warranty Applies
```



235TL FARM LOADER BOOMER 24 US PRICE LIST

AGRICULTURE

Models

COMMERCIAL MODEL	TECHNICAL TYPE	Weight	Factory Data	List Price
235TL	550941102	680 LB	9003441P54	\$4,197.00



235TL FARM LOADER BOOMER 24 US PRICE LIST

Factory Supplied Options

Order Code Description Weight	Factory Data	List Price
-------------------------------	--------------	------------

FAST PICK CONFIGURATION

SD_T9981 CONFIGURATION

	XT9981X	Less Fast Pick Config		No Charge
	X0283XX	BMR 24 Fast Pick	(900068P88)	(\$84.00)
		FAST PICK PKG PRICE = 2% SAVINGS OVER ALA-CART ORDER		
		Fast Pick 235TL Loader for Boomer 24		
		Package Contains:		
		- Base 235TL Loader		
		- Mounting Frame		
		- Valve and Joystick		
		- 54" Pin on bucket		
		- Grill Guard		



235TL FARM LOADER BOOMER 24 US PRICE LIST

Factory Supplied Attachments

Order Code		order Code	Description	Weight	Factory Data	List Price
		710440186	MID MNT REM VLV AND JSTIC	45 LB	9000515P78	\$629.00

250TLA2 FARM LOADER BOOMER 35/40 (T4B) US PRICE LIST

Standard Equipment

TRACTOR APPLICATIONS:

Current New Holland Compact Models:

- Boomer™ 35/40 ROPS (T4B ONLY)
- Boomer™ 40 Cab (T4B ONLY)

NOTE:

Important Compatibility Information

- A configured model 250TLA2 is NOT compatible with other model tractors:
 Boomer™ 3040/3045/3050, 30/40
 Tier 3 or 33/37 Tier 4B
- To assure proper performance, see Operator's Manual for recommended counterweighting.

Loader Specifications: (PRELIMINARY)

Max lift height (to bucket pivot pin):

- 104 in / 2642 mm

Max lift height (under level bucket):

- 98 in / 2489 mm

Clearance with bucket dumped:

- 77 in / 1956 mm

Reach at max lift height:

- 48 in/ 1219 mm

Max dump angle: 48 °

Reach with bucket on ground:

- 78 in / 1981 mm

Bucket roll back angle: 30 °

Digging depth:

- 6.8 in / 173 mm

Lift capacity:

- @ bucket pivot pin, max height:
 - 1822 (lbs.) / 826 (kg)
- @ 500 mm forward, max height:
 - 1354 (lbs.) / 614 (kg)
- @ bucket pivot pin, 1500 mm height:
 - 2176 (lbs.) / 987 (kg)
- @ 500 mm forward, 1500 mm height
 - 1686 (lbs.) / 765 (kg)

Breakout force:

- @ bucket pivot pin:
 - 3257 (lbs.) / 1477 (kg)
- @ 500 mm forward:
 - 2444 (lbs.) / 1109 (kg)

Cycle times:

Raising: 3.8 sec

Lowering: 2.0 sec

Bucket dumping: 3.5 sec

Bucket roll back: 2.2 sec

Bucket width:

- 68 in / 1727 mm

Bucket Capacities:

Struck:

68" Bucket = .43 cu yd.

Heaped:

68" Bucket = .53 cu yd.

Loader specifications may vary based on tractor model, hydraulic system, tire size, etc.

*NOTE: The 250TLA2 do not come configured come with a mid mount valve and joystick as these items are now standard on the Boomer™ 35/40 T4B tractors. If a mid mount valve, joystick is needed, these items must be ordered from parts.

*Couplers are included with loader

WARRANTY

New Holland Standard Warranty Applies



250TLA2 FARM LOADER BOOMER 35/40 (T4B) US PRICE LIST

Models

COMMERCIAL MODEL	TECHNICAL TYPE	Weight	Factory Data	List Price
250TLA2 T4B 35/40	550941121	800 LB	9005109P42	\$6,231.00

20



250TLA2 FARM LOADER BOOMER 35/40 (T4B) US PRICE LIST

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

FAST PICK CONFIGURATION

SD_T9981 CONFIGURATION

	XT9981X	Less Fast Pick Config		No Charge
	X0331XX	BMR 40 Cab Fast Pick	(900102P50)	(\$125.00)
		Fast Pick 250TLA2 Loader for Boomer 40 Cab (T4B)		
		Package Contains:		
		- Base 250TLA2 Loader		
		- Mounting Frame		
		- SSL Quick Attach Face plate		
		- 68" Quick Attach bucket		



250TLA2 FARM LOADER BOOMER 35/40 (T4B) US PRICE LIST

Factory Supplied Attachments

Order Code		Description	Weight	Factory Data	List Price
	713762016	Cls 2 Mounting & Hardware Kit CONVERSION KIT. This kit allows a 250TLA1 loader (727099016 Rops / 727099026 Cab) for BOOMER 33/37 tractors to be used on BOOMER 35/40 T4B Rops and Cab tractors. The kit contains new loader mounting brackets, hardware and	265 LB	9000615P00	\$750.00
		hydraulic coupler kit.			

22

250TLA1 FARM LOADER BOOMER 33/37 (T4B) US PRICE LIST

AGRICULTURE

Standard Equipment

TRACTOR APPLICATIONS:

Current New Holland Compact Models:

- Boomer™ 33/37 ROPS (T4B)
- Boomer™ 37 Cab (T4B)

NOTE:

Important Compatibility Information

- A configured model 250TLA1 is NOT compatible with other model tractors: Boomer™ 3040/3045/3050,30/40 T3
- To assure proper performance, see Operator's Manual for recommended counterweighting.

Loader Specifications:

Max lift height (to bucket pivot pin):

- 104 in / 2642 mm

Max lift height (under level bucket):

- 98 in / 2489 mm

Clearance with bucket dumped:

- 77 in / 1956 mm

Reach at max lift height:

- 48 in/ 1219 mm

Max dump angle: 48 °

Reach with bucket on ground:

- 78 in / 1981 mm

Bucket roll back angle: 30 °

Digging depth:

-6.8 in / 173 mm

Lift capacity:

- @ bucket pivot pin, max height:
 - 1822 (lbs.) / 826 (kg)
- @ 500 mm forward, max height:
 - 1354 (lbs.) / 614 (kg)
- @ bucket pivot pin, 1500 mm height:
 - 2176 (lbs.) / 987 (kg)
- @ 500 mm forward, 1500 mm height
 - 1686 (lbs.) / 765 (kg)

Breakout force:

- @ bucket pivot pin:
 - 3257 (lbs.) / 1477 (kg)
- @ 500 mm forward:
 - 2444 (lbs.) / 1109 (kg)

Cycle times:

Raising: 3.8 sec

Lowering: 2.0 sec

Bucket dumping: 3.5 sec

Bucket roll back: 2.2 sec

Bucket width:

- 68 in / 1727 mm

Bucket Capacities:

Struck:

68" Bucket = .43 cu yd.

Heaped:

68" Bucket = .53 cu yd.

Loader specifications may vary based on tractor model, hydraulic system, tire size, etc.

*NOTE: The 250TLA1 do not come configured come with a mid mount valve and joystick as these items are now standard on the Boomer™ 33/37 T4B tractors. If a mid mount valve, joystick is needed, these items must be ordered from parts.

*Couplers are included with loader

WARRANTY

New Holland Standard Warranty Applies



AGRICULTURE

Models

COMMERCIAL MODEL	Weight	Factory Data	List Price
250TLA1	800 LB	9005109P42	\$6,231.00
250TLA1	800 LB	9005309P50	\$6,475.00
250TLA1 CAB NON-CVT	800 LB	9005109P42	\$6,231.00



250TLA1 FARM LOADER BOOMER 33/37 (T4B) US PRICE LIST

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

FAST PICK CONFIGURATION

SD_T9981 CONFIGURATION

	XT9981X	Less Fast Pick Config		No Charge
	X0275XX	BMR 37 Cab Fast Pick	(900101P68)	(\$124.00)
		FAST PICK PKG PRICE = 2% SAVINGS OVER ALA-CART ORDER		
		Fast Pick 250TLA1 Loader for Boomer 37 Cab		
		Package Contains:		
		- Base 250TLA1 Loader		
		- Mounting Frame		
		- SSL Quick Attach Face plate		
		- 68" Quick Attach bucket		



250TLA1 FARM LOADER BOOMER 33/37 (T4B) US PRICE LIST

Factory Supplied Attachments

Order Code		Code	Description	Weight	Factory Data	List Price
	71376		Cls 2 Mounting & Hardware Kit CONVERSION KIT. This kit allows a 250TLA1 loader (727099016 Rops / 727099026 Cab) for BOOMER 33/37 tractors to be used on BOOMER 35/40 T4B Rops and Cab tractors.	265 LB	9000615P00	\$750.00
			The kit contains new loader mounting brackets, hardware and hydraulic coupler kit.			

AGRICULTURE

Standard Equipment

TRACTOR APPLICATIONS:

Current New Holland Compact Models:

- Boomer™ 45/50/55 ROPS(T4B ONLY)
- Boomer™ 45/50/55 Cab (T4B ONLY)

NOTE:

Important Compatibility Information

- A configured model 260TLA2 is NOT compatible with other model tractors:

 Boomer™ 40/50 Tier 3 or 41/47 T4B
- To assure proper performance, see Operator's Manual for recommended counterweighting.

Loader Specifications: (PRELIMINARY)

Max lift height (to bucket pivot pin):

- 109 in / 2769 mm

Max lift height (under level bucket):

- 103 in / 2616 mm

Clearance with bucket dumped:

- 80 in / 2032 mm

Reach at max lift height:

- 58 in/ 1473 mm

Max dump angle: 56 °

Reach with bucket on ground:

- 86 in / 2184 mm

Bucket roll back angle: 28 °

Digging depth:

-6.3 in / 160 mm

Lift capacity:

- @ bucket pivot pin, max height:
 - 2371 (lbs.) / 1076 (kg)
- @ 500 mm forward, max height:
 - 1849 (lbs.) / 839 (kg)
- @ bucket pivot pin, 1500 mm height:
 - 2828 (lbs.) / 1283 (kg)
- @ 500 mm forward, 1500 mm height
 - 2256 (lbs.) / 1023 (kg)

Breakout force:

- @ bucket pivot pin:
 - 4081 (lbs.) / 1851 (kg)
- @ 500 mm forward:
 - 3191 (lbs.) / 1447 (kg)

Cylce times:

Raising: 3.8 sec

Lowering: 2.0 sec

Bucket dumping: 3.5 sec

Bucket roll back: 2.2 sec

Bucket width:

- 72 in / 1829 mm

Loader specifications may vary based on tractor model, hydraulic system, tire size, etc.

*NOTE: The 260TLA2 do not come configured come with a mid mount valve and joystick as these items are now standard on the Boomer™ 45/50/55 tractors. If a mid mount valve, joystick is needed, these items must be ordered from parts.

*Couplers are included with loader

WARRANTY

New Holland Standard Warranty Applies

AGRICULTURE

Models

COMMERCIAL MODEL	Weight	Factory Data	List Price
260TLA2 T4B 45/50/55	800 LB	9005309P50	\$6,475.00

Factory Supplied Options

Order Code Description Weight	Factory Data	List Price
-------------------------------	--------------	------------

FAST PICK CONFIGURATION

SD_T9981 CONFIGURATION

XT9981X	Less Fast Pick Config		No Charge
X0333XX	BMR 50 Cab Fast Pick	(900105P78)	(\$129.00)
	Fast Pick 260TLA2 Loader for Boomer 50 Cab (T4B)		
	Package Contains:		
	- Base 260TLA2 Loader		
	- Mounting Frame		
	- SSL Quick Attach Face plate		
	- 72" Quick Attach bucket		
X0332XX	BMR 50 ROPS Fast Pick	(900105P78)	(\$129.00)
	Fast Pick 260TLA2 Loader for Boomer 50 ROPS (T4B)		
	Package Contains:		
	- Base 260TLA2 Loader		
	- Mounting Frame		
	- SSL Quick Attach Face plate		
	- 72" Quick Attach bucket		



Factory Supplied Attachments

Order Code		Description	Weight	Factory Data	List Price
	713762026	Cls 3 Mounting & Hardware Kit CONVERSION KIT. This kit allows a 260TLA1 loader (727100006 Rops/ 727100026 Cab) for BOOMER 41/47 tractors to be used on BOOMER 45/50/55 T4B Rops and Cab tractors.	231 LB	9000615P00	\$750.00
		The kit contains new loader mounting brackets, hardware and hydraulic coupler kit.			

-CP9J 04

260TLA1 FARM LOADER BOOMER 41/47 (T4B) US PRICE LIST

AGRICULTURE

Standard Equipment

TRACTOR APPLICATIONS:

Current New Holland Compact Models:

- Boomer™ 41/47 ROPS (T4B)
- Boomer™ 41/47 Cab (T4B)

NOTE:

Important Compatibility Information

- A configured model 260TLA1 is NOT compatible with other model tractors:

 Boomer™ 40/50 T3 or 45/50/55 T4B
- To assure proper performance, see Operator's Manual for recommended counterweighting.

Loader Specifications:

Max lift height (to bucket pivot pin):

- 109 in / 2769 mm

Max lift height (under level bucket):

- 103 in / 2616 mm

Clearance with bucket dumped:

- 80 in / 2032 mm

Reach at max lift height:

- 58 in/ 1473 mm

Max dump angle: 56 °

Reach with bucket on ground:

- 86 in / 2184 mm

Bucket roll back angle: 28 °

Digging depth:

-6.3 in / 160 mm

Lift capacity:

- @ bucket pivot pin, max height:
 - 2371 (lbs.) / 1076 (kg)
- @ 500 mm forward, max height:
 - 1849 (lbs.) / 839 (kg)
- @ bucket pivot pin, 1500 mm height:
 - 2828 (lbs.) / 1283 (kg)
- @ 500 mm forward, 1500 mm height
 - 2256 (lbs.) / 1023 (kg)

Breakout force:

- @ bucket pivot pin:
 - 4081 (lbs.) / 1851 (kg)
- @ 500 mm forward:
 - 3191 (lbs.) / 1447 (kg)

Cylce times:

Raising: 3.8 sec

Lowering: 2.0 sec

Bucket dumping: 3.5 sec

Bucket roll back: 2.2 sec

Bucket width:

- 72 in / 1829 mm

Loader specifications may vary based on tractor model, hydraulic system, tire size, etc.

*NOTE: The 260TLA1 do not come configured come with a mid mount valve and joystick as these items are now standard on the Boomer™ 41/47 tractors. If a mid mount valve, joystick is needed, these items must be ordered from parts.

*Couplers are included with loader

WARRANTY

New Holland Standard Warranty Applies



260TLA1 FARM LOADER BOOMER 41/47 (T4B) US PRICE LIST

Models

COMMERCIAL MODEL	Weight	Factory Data	List Price
260TLA1	800 LB	9005309P50	\$6,475.00
260TLA1 CAB NON-CVT	800 LB	9005309P50	\$6,475.00

260TLA1 FARM LOADER BOOMER 41/47 (T4B) US PRICE LIST

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

FAST PICK CONFIGURATION

SD_T9981 CONFIGURATION

X ⁻	T9981X	Less Fast Pick Config		No Charge
X	0282XX	BMR 47 Rops Fast Pick	(900105P78)	(\$129.00)
		FAST PICK PKG PRICE = 2% SAVINGS OVER ALA-CART ORDER		
		Fast Pick 260TLA1 Loader for Boomer 47 ROPS		
		Package Contains:		
		- Base 260TLA1 Loader		
		- Mounting Frame		
		- SSL Quick Attach Face plate		
		- 72" Quick Attach bucket		
X	0276XX	BMR 47 Cab Fast Pick	(900105P78)	(\$129.00)
		FAST PICK PKG PRICE = 2% SAVINGS OVER ALA-CART ORDER		
		Fast Pick 260TLA1 Loader for Boomer 47 Cab		
		Package Contains:		
		- Base 260TLA1 Loader		
		- Mounting Frame		
		- SSL Quick Attach Face plate		
		- 72" Quick Attach bucket		



260TLA1 FARM LOADER BOOMER 41/47 (T4B) US PRICE LIST

Factory Supplied Attachments

Or	der Code	Description	Weight	Factory Data	List Price
	713762026	Cls 3 Mounting & Hardware Kit CONVERSION KIT. This kit allows a 260TLA1 loader (727100006 Rops/ 727100026 Cab) for BOOMER 41/47 tractors to be used on BOOMER 45/50/55 T4B Rops and Cab tractors. The kit contains new loader mounting brackets, hardware and	231 LB	9000615P00	\$750.00
		hydraulic coupler kit.			

TRACTOR APPLICATIONS:

- 6.8 in / 173 mm

250TLA FARM LOADER BOOMER 45/50D 46/54D US PRICE LIST

Standard Equipment

Current New Holland Compact Models: - Boomer™ CVT 45/50D - Boomer™ CVT 46/54D Prior New Holland Compact Models: - Boomer™ CVT 3040/3045/3050 Serial # ZDMB11925 & newer ONLY NOTE: Important Compatibility Information - A configured model 250TLA IV is NOT compatible with other model tractors - To assure proper performance, see Operator's Manual for recommended counterweighting. Loader Specifications: Max lift height (to bucket pivot pin): - 104 in / 2642 mm Max lift height (under level bucket): - 98 in / 2489 mm Clearance with bucket dumped: - 77 in / 1956 mm Reach at max lift height: - 48 in/ 1219 mm Max dump angle: 48 ° Reach with bucket on ground: - 78 in / 1981 mm Bucket roll back angle: 30 ° Digging depth:

```
Lift capacity:
    @ bucket pivot pin, max height:
       - 1822 (lbs.) / 826 (kg)
    @ 500 mm forward, max height:
       - 1354 (lbs.) / 614 (kg)
    @ bucket pivot pin, 1500 mm height:
       - 2176 (lbs.) / 987 (kg)
    @ 500 mm forward, 1500 mm height
       - 1686 (lbs.) / 765 (kg)
 Breakout force:
    @ bucket pivot pin:
       - 3257 (lbs.) / 1477 (kg)
    @ 500 mm forward:
       - 2444 (lbs.) / 1109 (kg)
Cycle times:
 Raising: 3.8 sec
Lowering: 2.0 sec
Bucket dumping: 3.5 sec
Bucket roll back: 2.2 sec
Bucket width:
   - 68 in / 1727 mm
Bucket Capacities:
 Struck:
    68" Bucket = .43 cu yd.
 Heaped:
    68" Bucket = .53 cu yd.
Loader specifications may vary based
  on tractor model, hydraulic system, tire
  size, etc.
```

WARRANTY

New Holland Standard Warranty Applies



250TLA FARM LOADER BOOMER 45/50D 46/54D US PRICE LIST

Models

COMMERCIAL MODEL	Weight	Factory Data	List Price	
250TLA	800 LB	9004496P88	\$5,484.00	



250TLA FARM LOADER BOOMER 45/50D 46/54D US PRICE LIST

Factory Supplied Options

Order Code	Description	Weigh	t Factory	v Data	List Price
Oldol Oddo	Description	vvo.g	it i dottor	, Data	E10t 1 1100

FAST PICK CONFIGURATION

SD_T9981 CONFIGURATION

	XT9981X	Less Fast Pick Config		No Charge
	X0281XX	BMR 54D Fast Pick	(900090P20)	(\$110.00)
		FAST PICK PKG PRICE = 2% SAVINGS OVER ALA-CART ORDER		
		Fast Pick 250TLA1 Loader for Boomer 54D Cab		
		Package Contains:		
		- Base 250TLA1 Loader for Loader Ready Tractor		
		- SSL Quick Attach Face plate		
		- 72" Quick Attach bucket		