Power and Data Solutions



98

113

139

W x D x H (in) **ELECTRICAL AND COMMUNICATION MODULES**

Code Includes two electrical outlets. Can accommodate the listed couplers.

LGC-PC2P

communication module

Electrical /

72" (1829 mm) cord included. Silver anodized aluminum. Field installed. UL and CUL certified. Adaptors included.

Nouble-sided electrical / communication module

Includes two electrical outlets on each side. Can accommodate the listed couplers. 72" (1829 mm) cord included. Silver anodized aluminum, Field installed, UL and CUL certified. Adaptors included.

 $8^{1}/_{4} \times 8 \times 3$ 206 x 200 x 75

W x D x H (mm)

212 x 110 x 75

LGC-DPC4P



Flush-mount rectangular electrical / communication module

Includes two electrical outlets and two 2.1A USB ports. 120VAC power outlet. Spill resistant. 108" (2743 mm) cord included. Mounting screw included. Silver. Field installed. ETL certified.



6 1/4 x 2 1/2 x 3 1/8 159 x 64 x 79 LGC-PC01IISR2P 417

Grommet-mounted flush rectangular electrical/ communication module Includes one electrical outlet and two 2.1A USB ports. Fits in the rectangular Lacasse grommet hole. 120VAC power outlet. Spill resistant. 108" (2743 mm) cord included. Mounting screw included. Silver. Field installed. ETL certified.

3³/₄ x 2¹/₄ x 3¹/₈ 95 x 57 x 79 LGC-PCQ1USB1P



371

Flush-mount round electrical / communication module

Includes two electrical outlets and two 2.1A USB ports. 120VAC power outlet. Spill resistant. 108" (2743 mm) cord included. Mounting screw included. Silver. Field installed. ETL certified.

6 x 6 x 3 ½

152 x 152 x 79

LGC-PCV1USB2P



Grommet-mounted flush round electrical / communication module

Includes one electrical outlet and two 2.1A USB ports. Fits in the rectangular Lacasse grommet hole. 120VAC power outlet. Spill resistant. 108" (2746 mm) cord included. Mounting screw included. Silver. Field installed. ETL certified.

5 1/4 x 5 1/4 x 3 1/8 133 x 133 x 79



Wireless charger

Compatible with any Qi rated devices and smartphones, refer to the wireless compatibility chart on next page. 78" (1981 mm) cord included. Silver anodized aluminum. Field installed. The transformer is UL and CUL certified.

3 1/4 x 3 1/4 x 3/4

84 x 84 x 17

LGC-CHARGE

494

417

Price W x D x H (in) W x D x H (mm) Code (\$)

COUPLERS

Voice coupler

Price

(\$)

382

678



RJ11 coupler, category 3. Modular coupler to connect a standard phone. Compatible with electrical / communication modules LGC-PC2P or LGC-DPC4P. Black. Must be used with the adaptors provided with selected accessories plates

or modules. Field installed.

9/₁₆ x 5/₈ x 1 3/₁₆ 14 x 16 x 30 LGC-RJ11 57

Data jack

RJ-45 coupler, category 5. 110 connect jack used for internet and multi-line/VOIP phone systems. Compatible with electrical / communication modules LGC-PC2P or LGC-DPC4P. Black. Must be used with the adaptors provided with selected accessories plates or modules. Field installed.

 $5/_{8} \times 5/_{8} \times 1^{3}/_{16}$ 16 x 16 x 30

LGC-RI45

HDMI connector

To connect to HD displays that accept HDMI feed. Female / female connection. 18" (457 mm) cord. Compatible with electrical / communication modules LGC-PC2P or LGC-DPC4P. Black. Must be used with the adaptors provided with selected accessories plates or modules. Field installed.

5/8 x 9/16 x 1 3/16 16 x 14 x 30 I GC-HDMI 113

VGA coupler



Female-to-male connector cable. Device cable not included. 120" (3048 mm) cord included. Compatible with electrical / communication modules LGC-PC2P or LGC-DPC4P. Black. Must be used with the adaptors provided with selected accessories plates or modules. Field installed.

1 1/4 x 1/4 x 1 1/2 33 x 12 x 37 LGC-VGA

USB 3.0 coupler



Simultaneous read and write capability. Transfer speed of 5 gbs/sec. Does not charge. 72" (1829 mm) cord. Compatible with electrical / communication modules LGC-PC2P or LGC-DPC4P. Black. Must be used with the adaptors provided with selected accessories plates or modules. Field installed.

5/8 x 9/16 x 1 3/16 16 x 14 x 30

LGC-USBDATA 93

USB charging coupler



USB-A connections for USB-powered device and charging mobile electronics. 2,000 mA of charging power. 72" (1829 mm) cord. Compatible with electrical / communication modules LGC-PC2P or LGC-DPC4P. Black. Must be used with the adaptors provided with selected accessories plates or modules. Field installed. The transformer is UL and CUL certified.

1 x 1 x 1 3/16 26 x 26 x 30

LGC-USB

POWER AND DATA SOLUTIONS USA PRICE LIST - JANUARY 2017

LGC-CHARGE WIRELESS COMPATIBILITY CHART

Casio - G'zone Commando	LG G3**	Nexus 6
Blackberry Z30*	LG Optimus LTE 2	Nexus 7
Dell Venue 8	Motorola Moto Maxx*	Philips X723
Droid Maxx	NEC Medias PP N-01D	Samsung Galaxy S6
Droid Mini	NEC Medias X N-04E	Samsung Galaxy S6 Edge
Droid Turbo	Nokia Lumina 735	Saygus V2
Fujitsu Arrows Kiss F-03D	Nokia Lumina 830	Sharp Q-Pot SH-04D
Fujitsu Arrows X F-10D	Nokia Lumina 920	Sharp SH-05D
Fujitsu Arrows F-09D Anteprima	Nokia Lumina 928	Sharp Aquos SH-13C
Fujitsu Arrows Kiss F-03E	Nokia Lumina 930	Sharp Aquos SH-07D
HTC Droid DNA	Nokia Lumina 1520	Sharp Aquos Zeta SH-09D
HTC Windows Phone 8X*	Nokia Lumina Icon	Sharp Aquos Ex SH-04E
LG Spectrum 2*	Nexus 4	Sharp Aquos Xeta SH-06E
LG G2*	Nexus 5	Sharp Aquos Slider SH-02D

^{*} Only through Verizon in US ** European Model

DEVICES THAT MUST BE USED WITH OFFICIAL OEM QI COVER

HTC Thunderbolt	Motorola Droid 3	Samsung Galaxy Note II
HTC Incredible 2	Motorola Droid 4	Samsung Galaxy Note III
HTC Rezound	Motorola Droid X	Samsung Galaxy Note IV
LG Revolution	Nokia Lumina 720	Samsung Galaxy Alpha
LG Spectrum	Nokia Lumina 810	Samsung Galaxy S3
LG Lucid	Nokia Lumina 820	Samsung Galaxy S4
LG Lucid 2	Nokia Lumina 822	Samsung Galaxy S5
LG Optimus G Pro	Nokia Lumina 925	Samsung Droid Charge
LG Optimus Pro	Nokia Lumina 1020	Sony- Xperia Z3
LG Optimus IT L-05E	Nokia Lumina Icon	
Motorola Droid Bionic	Pantech Breakout	



1-888-522-2773 www.groupelacasse.com

